
angr

The angr Project

Apr 02, 2024

CONTENTS

1	Introduction	3
1.1	Getting Support	3
1.2	Citing angr	4
1.3	Going further:	4
2	Getting Started	5
2.1	Installing angr	5
2.2	Reporting Bugs	6
2.3	Developing angr	7
2.4	Help Wanted	9
3	Core Concepts	15
3.1	Core Concepts	15
3.2	Loading a Binary	20
3.3	Symbolic Expressions and Constraint Solving	26
3.4	Machine State - memory, registers, and so on	32
3.5	Simulation Managers	38
3.6	Simulation and Instrumentation	42
3.7	Analyses	48
3.8	Symbolic Execution	49
3.9	A final word of advice	49
4	Build-in Analyses	51
4.1	Control-flow Graph Recovery (CFG)	51
4.2	Backward Slicing	56
4.3	Identifier	58
4.4	angr Decompiler	61
5	Advanced Topics	63
5.1	Gotchas when using angr	63
5.2	Understanding the Execution Pipeline	64
5.3	What's Up With Mixins, Anyway?	69
5.4	Optimization considerations	72
5.5	Working with File System, Sockets, and Pipes	74
5.6	Intermediate Representation	79
5.7	Working with Data and Conventions	83
5.8	Solver Engine	86
5.9	Symbolic memory addressing	91
5.10	Java Support	92
5.11	Symbion: Interleaving symbolic and concrete execution	93

5.12	Debug variable resolution	95
5.13	Variable visibility	96
6	Extending angr	99
6.1	Hooks and SimProcedures	99
6.2	State Plugins	103
6.3	Extending the Environment Model	107
6.4	Writing Analyses	110
6.5	Scripting angr management	112
7	angr examples	115
7.1	Introduction	115
7.2	Reversing	115
7.3	Vulnerability Discovery	118
7.4	Exploitation	119
8	Frequently Asked Questions	121
8.1	Why is it named angr?	121
8.2	How should “angr” be stylized?	121
8.3	Why isn’t symbolic execution doing the thing I want?	121
8.4	How can I get diagnostic information about what angr is doing?	122
8.5	Why is angr so slow?	122
8.6	How do I find bugs using angr?	122
8.7	Why did you choose VEX instead of another IR (such as LLVM, REIL, BAP, etc)?	122
8.8	Why are some ARM addresses off-by-one?	123
8.9	How do I serialize angr objects?	123
8.10	What does <code>UnsupportedIROpError("floating point support disabled")</code> mean?	123
8.11	Why is angr’s CFG different from IDA’s?	124
8.12	Why do I get incorrect register values when reading from a state during a <code>SimInspect</code> breakpoint?	124
9	Appendix	125
9.1	Cheatsheet	125
9.2	List of Claripy Operations	130
9.3	List of State Options	131
9.4	CTF Challenge Examples	134
9.5	Changelog	138
9.6	Migrating to angr 9.1	150
9.7	Migrating to angr 8	150
9.8	Migrating to angr 7	153
10	API Reference	157
10.1	Project	212
10.2	Plugin Ecosystem	222
10.3	Program State	224
10.4	Storage	309
10.5	Memory Mixins	336
10.6	Concretization Strategies	379
10.7	Simulation Manager	382
10.8	Exploration Techniques	390
10.9	Simulation Engines	427
10.10	Simulation Logging	467
10.11	Procedures	469
10.12	Calling Conventions and Types	484
10.13	Knowledge Base	523
10.14	Serialization	620

10.15 Analysis	623
10.16 SimOS	884
10.17 Function Signature Matching	892
10.18 Utils	893
10.19 Errors	903
10.20 Distributed analysis	909
11 Indices and tables	911
Python Module Index	913
Index	919

Welcome to angr's documentation! This documentation is intended to be a guide for learning angr, as well as a reference for the API. If you're new to angr,

The angr team maintains a number of libraries that are used as part of angr. These libraries are:

- [archinfo](#) - Information about CPU architectures
- [pyvex](#) - Python bindings to the VEX IR
- [pypcode](#) - Python bindings to the Pcode IR
- [ailment](#) - angr's high-level intermediate language
- [cle](#) - Many-platform binary loader
- [claripy](#) - Solver abstraction layer

INTRODUCTION

angr is a multi-architecture binary analysis toolkit, with the capability to perform dynamic symbolic execution (like Mayhem, KLEE, etc.) and various static analyses on binaries. If you'd like to learn how to use it, you're in the right place!

We've tried to make using angr as pain-free as possible - our goal is to create a user-friendly binary analysis suite, allowing a user to simply start up iPython and easily perform intensive binary analyses with a couple of commands. That being said, binary analysis is complex, which makes angr complex. This documentation is an attempt to help out with that, providing narrative explanation and exploration of angr and its design.

Several challenges must be overcome to programmatically analyze a binary. They are, roughly:

- Loading a binary into the analysis program.
- Translating a binary into an intermediate representation (IR).
- Performing the actual analysis. This could be:
 - A partial or full-program static analysis (i.e., dependency analysis, program slicing).
 - A symbolic exploration of the program's state space (i.e., "Can we execute it until we find an overflow?").
 - Some combination of the above (i.e., "Let's execute only program slices that lead to a memory write, to find an overflow.")

angr has components that meet all of these challenges. This documentation will explain how each component works, and how they can all be used to accomplish your goals.

1.1 Getting Support

To get help with angr, you can ask via:

- the slack channel: angr.slack.com, for which you can get an account [here](#).
- opening an issue on the appropriate github repository

1.2 Citing Angr

If you use Angr in an academic work, please cite the papers for which it was developed:

```
@article{shoshitaishvili2016state,
  title={SoK: (State of) The Art of War: Offensive Techniques in Binary Analysis},
  author={Shoshitaishvili, Yan and Wang, Ruoyu and Salls, Christopher and Stephens, Nick
↪and Polino, Mario and Dutcher, Audrey and Grosen, Jessie and Feng, Siji and Hauser,
↪Christophe and Kruegel, Christopher and Vigna, Giovanni},
  booktitle={IEEE Symposium on Security and Privacy},
  year={2016}
}

@article{stephens2016driller,
  title={Driller: Augmenting Fuzzing Through Selective Symbolic Execution},
  author={Stephens, Nick and Grosen, Jessie and Salls, Christopher and Dutcher, Audrey
↪and Wang, Ruoyu and Corbetta, Jacopo and Shoshitaishvili, Yan and Kruegel, Christopher
↪and Vigna, Giovanni},
  booktitle={NDSS},
  year={2016}
}

@article{shoshitaishvili2015fomalice,
  title={Fomalice - Automatic Detection of Authentication Bypass Vulnerabilities in
↪Binary Firmware},
  author={Shoshitaishvili, Yan and Wang, Ruoyu and Hauser, Christophe and Kruegel,
↪Christopher and Vigna, Giovanni},
  booktitle={NDSS},
  year={2015}
}
```

1.3 Going further:

You can read this [paper](#), explaining some of the internals, algorithms, and used techniques to get a better understanding on what's going on under the hood.

If you enjoy playing CTFs and would like to learn Angr in a similar fashion, [Angr-CTF](#) will be a fun way for you to get familiar with much of the symbolic execution capability of Angr. The [Angr-CTF repo](#) is maintained by [@jakespringer](#).

GETTING STARTED

2.1 Installing angr

angr is a library for Python 3.8+, and must be installed into a Python environment before it can be used.

Tip: It is recommended to use an isolated python environment rather than installing angr globally. Doing so reduces dependency conflicts and aids in reproducibility while debugging. Some popular tools that accomplish this include:

- `venv`
 - `pipenv`
 - `virtualenv`
 - `virtualenvwrapper`
 - `conda`
-

2.1.1 Installing from PyPI

angr is published on [PyPI](#), and using this is the easiest and recommended way to install angr. It can be installed angr with pip:

```
pip install angr
```

Note: The PyPI distribution includes binary packages for most popular system configurations. If you are using a system that is not supported by the binary packages, you will need to build the C dependencies from source. See the *Installing from Source* section for more information.

2.1.2 Installing from Source

angr is a collection of Python packages, each of which is published on GitHub. The easiest way to install angr from source is to use `angr-dev`.

To set up a development environment manually, first ensure that build dependencies are installed. These consist of python development headers, `make`, and a C compiler. On Ubuntu, these can be installed with:

```
sudo apt-get install python3-dev build-essential
```

Then, checkout and install the following packages, in order:

- `archinfo`
- `pyvex` (clone with `--recursive`)
- `cle`
- `claripy`
- `ailment`
- `angr` (pip install with `--no-build-isolation`)

2.1.3 Troubleshooting

angr has no attribute Project, or similar

If angr can be imported but the `Project` class is missing, it is likely one of two problems:

1. There is a script named `angr.py` in the working directory. Rename it to something else.
2. There is a folder called `angr` in your working directory, possibly the cloned repository. Change the working directory to somewhere else.

AttributeError: 'module' object has no attribute 'KS_ARCH_X86'

The `keystone` package is installed, which conflicts with the `keystone-engine` package, an optional dependency of angr. Uninstall `keystone` and install `keystone-engine`.

2.2 Reporting Bugs

If you've found something that angr isn't able to solve and appears to be a bug, please let us know!

1. Create a fork off of `angr/binaries` and `angr/angr`
2. Give us a pull request with `angr/binaries`, with the binaries in question
3. Give us a pull request for `angr/angr`, with testcases that trigger the binaries in `angr/tests/broken_x.py`, `angr/tests/broken_y.py`, etc

Please try to follow the testcase format that we have (so the code is in a `test_blah` function), that way we can very easily merge that and make the scripts run.

An example is:

```
def test_some_broken_feature():
    p = angr.Project("some_binary")
    result = p.analyses.SomethingThatDoesNotWork()
    assert result == "what it should *actually* be if it worked"

if __name__ == '__main__':
    test_some_broken_feature()
```

This will *greatly* help us recreate your bug and fix it faster.

The ideal situation is that, when the bug is fixed, your testcases passes (i.e., the assert at the end does not raise an `AssertionError`).

Then, we can just fix the bug and rename `broken_x.py` to `test_x.py` and the testcase will run in our internal CI at every push, ensuring that we do not break this feature again.

2.3 Developing angr

These are some guidelines so that we can keep the codebase in good shape!

2.3.1 pre-commit

Many angr repos contain pre-commit hooks provided by `pre-commit`. Installing this is as easy as `pip install pre-commit`. After git cloning an angr repository, if the repo contains a `.pre-commit-config.yaml`, run `pre-commit install`. Future git commits will now invoke these hooks automatically.

2.3.2 Coding style

We format our code with `black` and otherwise try to get as close as the [PEP8 code convention](#) as is reasonable without being dumb. If you use Vim, the `python-mode` plugin does all you need. You can also [manually configure](#) vim to adopt this behavior.

Most importantly, please consider the following when writing code as part of angr:

- Try to use attribute access (see the `@property` decorator) instead of getters and setters wherever you can. This isn't Java, and attributes enable tab completion in iPython. That being said, be reasonable: attributes should be fast. A rule of thumb is that if something could require a constraint solve, it should not be an attribute.
- Use [our pylintrc from the angr-dev repo](#). It's fairly permissive, but our CI server will fail your builds if pylint complains under those settings.
- DO NOT, under ANY circumstances, `raise Exception` or `assert False`. **Use the right exception type.** If there isn't a correct exception type, subclass the core exception of the module that you're working in (i.e., `AngrError` in angr, `SimError` in SimuVEX, etc) and raise that. We catch, and properly handle, the right types of errors in the right places, but `AssertionError` and `Exception` are not handled anywhere and force-terminate analyses.
- Avoid tabs; use space indentation instead. Even though it's wrong, the de facto standard is 4 spaces. It is a good idea to adopt this from the beginning, as merging code that mixes both tab and space indentation is awful.
- Avoid super long lines. It's okay to have longer lines, but keep in mind that long lines are harder to read and should be avoided. Let's try to stick to **120 characters**.
- Avoid extremely long functions, it is often better to break them up into smaller functions.
- Always use `_` instead of `__` for private members (so that we can access them when debugging). *You* might not think that anyone has a need to call a given function, but trust us, you're wrong.
- Format your code with `black`; config is already defined within `pyproject.toml`.

2.3.3 Documentation

Document your code. Every *class definition* and *public function definition* should have some description of:

- What it does.
- What are the type and the meaning of the parameters.
- What it returns.

Class docstrings will be enforced by our linter. Do *not* under any circumstances write a docstring which doesn't provide more information than the name of the class. What you should try to write is a description of the environment that the class should be used in. If the class should not be instantiated by end-users, write a description of where it will be generated and how instances can be acquired. If the class should be instantiated by end-users, explain what kind of object it represents at its core, what behavior is expected of its parameters, and how to safely manage objects of its type.

We use [Sphinx](#) to generate the API documentation. Sphinx supports docstrings written in [ReStructured Text](#) with special [keywords](#) to document function and class parameters, return values, return types, members, etc.

Here is an example of function documentation. Ideally the parameter descriptions should be aligned vertically to make the docstrings as readable as possible.

```
def prune(self, filter_func=None, from_stash=None, to_stash=None):
    """
    Prune unsatisfiable paths from a stash.

    :param filter_func: Only prune paths that match this filter.
    :param from_stash: Prune paths from this stash. (default: 'active')
    :param to_stash: Put pruned paths in this stash. (default: 'pruned')
    :returns: The resulting PathGroup.
    :rtype: PathGroup
    """
```

This format has the advantage that the function parameters are clearly identified in the generated documentation. However, it can make the documentation repetitive, in some cases a textual description can be more readable. Pick the format you feel is more appropriate for the functions or classes you are documenting.

```
def read_bytes(self, addr, n):
    """
    Read `n` bytes at address `addr` in memory and return an array of bytes.
    """
```

2.3.4 Unit tests

If you're pushing a new feature and it is not accompanied by a test case it **will be broken** in very short order. Please write test cases for your stuff.

We have an internal CI server to run tests to check functionality and regression on each commit. In order to have our server run your tests, write your tests in a format acceptable to [nosetests](#) in a file matching `test_*.py` in the `tests` folder of the appropriate repository. A test file can contain any number of functions of the form `def test_*():` or classes of the form `class Test*(unittest.TestCase):`. Each of them will be run as a test, and if they raise any exceptions or assertions, the test fails. Do not use the `nose.tools.assert_*` functions, as we are presently trying to migrate to `nose2`. Use `assert` statements with descriptive messages or the `unittest.TestCase` assert methods.

Look at the existing tests for examples. Many of them use an alternate format where the `test_*` function is actually a generator that yields tuples of functions to call and their arguments, for easy parametrization of tests.

Finally, do not add docstrings to your test functions.

2.4 Help Wanted

Todo: This page is woefully out of date. We need to update it.

angr is a huge project, and it's hard to keep up. Here, we list some big TODO items that we would love community contributions for in the hope that it can direct community involvement. They (will) have a wide range of complexity, and there should be something for all skill levels!

We tag issues on our github repositories that would be good for community involvement as “Help wanted”. To see the exhaustive list of these, use [this github search!](#)

2.4.1 Documentation

There are many parts of angr that suffer from little or no documentation. We desperately need community help in this area.

API

We are always behind on documentation. We've created several tracking issues on github to understand what's still missing:

1. [angr](#)
2. [claripy](#)
3. [cle](#)
4. [pyvex](#)

GitBook

This book is missing some core areas. Specifically, the following could be improved:

1. Finish some of the TODOs floating around the book.
2. Organize the Examples page in some way that makes sense. Right now, most of the examples are very redundant. It might be cool to have a simple table of most of them so that the page is not so overwhelming.

angr course

Developing a “course” of sorts to get people started with angr would be really beneficial. Steps have already been made in this direction [here](#), but more expansion would be beneficial.

Ideally, the course would have a hands-on component, of increasing difficulty, that would require people to use more and more of angr's capabilities.

2.4.2 Research re-implementation

Unfortunately, not everyone bases their research on `angr` ;-). Until that's remedied, we'll need to periodically implement related work, on top of `angr`, to make it reusable within the scope of the framework. This section lists some of this related work that's ripe for reimplementation in `angr`.

Redundant State Detection for Dynamic Symbolic Execution

Bugrara, et al. describe a method to identify and trim redundant states, increasing the speed of symbolic execution by up to 50 times and coverage by 4%. This would be great to have in `angr`, as an `ExplorationTechnique`. The paper is here: <http://nsl.cs.columbia.edu/projects/minestrone/papers/atc13-bugrara.pdf>

In-Vivo Multi-Path Analysis of Software Systems

Rather than developing symbolic summaries for every system call, we can use a technique proposed by `S2E` for concretizing necessary data and dispatching them to the OS itself. This would make `angr` applicable to a *much* larger set of binaries than it can currently analyze.

While this would be most useful for system calls, once it is implemented, it could be trivially applied to any location of code (i.e., library functions). By carefully choosing which library functions are handled like this, we can greatly increase `angr`'s scalability.

2.4.3 Development

We have several projects in mind that primarily require development effort.

`angr-management`

The `angr` GUI, `angr-management` needs a *lot* of work. Here is a non-exhaustive list of what is currently missing in `angr-management`:

- A navigator toolbar showing content in a program's memory space, just like IDA Pro's navigator toolbar.
- A text-based disassembly view of the program.
- Better view showing details in program states during path exploration, including modifiable register view, memory view, file descriptor view, etc.
- A GUI for cross referencing.

Exposing `angr`'s capabilities in a usable way, graphically, would be really useful!

IDA Plugins

Much of `angr`'s functionality could be exposed via IDA. For example, `angr`'s data dependence graph could be exposed in IDA through annotations, or obfuscated values can be resolved using symbolic execution.

Additional architectures

More architecture support would make angr all the more useful. Supporting a new architecture with angr would involve:

1. Adding the architecture information to [archinfo](#)
2. Adding an IR translation. This may be either an extension to PyVEX, producing IRSBs, or another IR entirely.
3. If your IR is not VEX, add a `SimEngine` to support it.
4. Adding a calling convention (`angr.SimCC`) to support `SimProcedures` (including system calls)
5. Adding or modifying an `angr.SimOS` to support initialization activities.
6. Creating a CLE backend to load binaries, or extending the CLE ELF backend to know about the new architecture if the binary format is ELF.

ideas for new architectures:

- PIC, AVR, other embedded architectures
- SPARC (there is some preliminary libVEX support for SPARC [here](#))

ideas for new IRs:

- LLVM IR (with this, we can extend angr from just a Binary Analysis Framework to a Program Analysis Framework and expand its capabilities in other ways!)
- SOOT (there is no reason that angr can't analyze Java code, although doing so would require some extensions to our memory model)

Environment support

We use the concept of “function summaries” in angr to model the environment of operating systems (i.e., the effects of their system calls) and library functions. Extending this would be greatly helpful in increasing angr's utility. These function summaries can be found [here](#).

A specific subset of this is system calls. Even more than library function `SimProcedures` (without which angr can always execute the actual function), we have very few workarounds for missing system calls. Every implemented system call extends the set of binaries that angr can handle.

2.4.4 Design Problems

There are some outstanding design challenges regarding the integration of additional functionalities into angr.

Type annotation and type information usage

angr has fledgling support for types, in the sense that it can parse them out of header files. However, those types are not well exposed to do anything useful with. Improving this support would make it possible to, for example, annotate certain memory regions with certain type information and interact with them intelligently. Consider, for example, interacting with a linked list like this: `print state.mem[state.regs.rax].l1list.next.next.value`.

(editor's note: you can actually already do this)

2.4.5 Research Challenges

Historically, angr has progressed in the course of research into novel areas of program analysis. Here, we list several self-contained research projects that can be tackled.

Semantic function identification/diffing

Current function diffing techniques (TODO: some examples) have drawbacks. For the CGC, we created a semantic-based binary identification engine (<https://github.com/angr/identifier>) that can identify functions based on testcases. There are two areas of improvement, each of which is its own research project:

1. Currently, the testcases used by this component are human-generated. However, symbolic execution can be used to automatically generate testcases that can be used to recognize instances of a given function in other binaries.
2. By creating testcases that achieve a “high-enough” code coverage of a given function, we can detect changes in functionality by applying the set of testcases to another implementation of the same function and analyzing changes in code coverage. This can then be used as a semantic function diff.

Applying AFL’s path selection criteria to symbolic execution

AFL does an excellent job in identifying “unique” paths during fuzzing by tracking the control flow transitions taken by every path. This same metric can be applied to symbolic exploration, and would probably do a depressingly good job, considering how simple it is.

2.4.6 Overarching Research Directions

There are areas of program analysis that are not well explored. We list general directions of research here, but readers should keep in mind that these directions likely describe potential undertakings of entire PhD dissertations.

Process interactions

Almost all work in the field of binary analysis deals with single binaries, but this is often unrealistic in the real world. For example, the type of input that can be passed to a CGI program depend on pre-processing by a web server. Currently, there is no way to support the analysis of multiple concurrent processes in angr, and many open questions in the field (i.e., how to model concurrent actions).

Intra-process concurrency

Similar to the modeling of interactions between processes, little work has been done in understanding the interaction of concurrent threads in the same process. Currently, angr has no way to reason about this, and it is unclear from the theoretical perspective how to approach this.

A subset of this problem is the analysis of signal handlers (or hardware interrupts). Each signal handler can be modeled as a thread that can be executed at any time that a signal can be triggered. Understanding when it is meaningful to analyze these handlers is an open problem. One system that does reason about the effect of interrupts is [FIE](#).

Path explosion

Many approaches (such as [Veriteesting](#)) attempt to mitigate the path explosion problem in symbolic execution. However, despite these efforts, path explosion is still *the* main problem preventing symbolic execution from being mainstream.

angr provides an excellent base to implement new techniques to control path explosion. Most approaches can be easily implemented as [ExplorationTechnique](#)s and quickly evaluated (for example, on the [CGC dataset](#)).

CORE CONCEPTS

3.1 Core Concepts

To get started with angr, you'll need to have a basic overview of some fundamental angr concepts and how to construct some basic angr objects. We'll go over this by examining what's directly available to you after you've loaded a binary!

Your first action with angr will always be to load a binary into a *project*. We'll use `/bin/true` for these examples.

```
>>> import angr
>>> proj = angr.Project('/bin/true')
```

A project is your control base in angr. With it, you will be able to dispatch analyses and simulations on the executable you just loaded. Almost every single object you work with in angr will depend on the existence of a project in some form.

Tip: Using and exploring angr in IPython (or other Python command line interpreters) is a main use case that we design angr for. When you are not sure what interfaces are available, tab completion is your friend!

Sometimes tab completion in IPython can be slow. We find the following workaround helpful without degrading the validity of completion results:

```
# Drop this file in IPython profile's startup directory to avoid running it every time.
import IPython
py = IPython.get_ipython()
py.Completer.use_jedi = False
```

3.1.1 Basic properties

First, we have some basic properties about the project: its CPU architecture, its filename, and the address of its entry point.

```
>>> import monkeyhex # this will format numerical results in hexadecimal
>>> proj.arch
<Arch AMD64 (LE)>
>>> proj.entry
0x401670
>>> proj.filename
'/bin/true'
```

- *arch* is an instance of an `archinfo.Arch` object for whichever architecture the program is compiled, in this case little-endian amd64. It contains a ton of clerical data about the CPU it runs on, which you can peruse [at your leisure](#). The common ones you care about are `arch.bits`, `arch.bytes` (that one is a `@property` declaration on the [main Arch class](#)), `arch.name`, and `arch.memory_endness`.
- *entry* is the entry point of the binary!
- *filename* is the absolute filename of the binary. Riveting stuff!

3.1.2 Loading

Getting from a binary file to its representation in a virtual address space is pretty complicated! We have a module called CLE to handle that. CLE's result, called the loader, is available in the `.loader` property. We'll get into detail on how to use this [soon](#), but for now just know that you can use it to see the shared libraries that angr loaded alongside your program and perform basic queries about the loaded address space.

```
>>> proj.loader
<Loaded true, maps [0x400000:0x5004000]>

>>> proj.loader.shared_objects # may look a little different for you!
{'ld-linux-x86-64.so.2': <ELF Object ld-2.24.so, maps [0x2000000:0x2227167]>,
 'libc.so.6': <ELF Object libc-2.24.so, maps [0x1000000:0x13c699f]>}}

>>> proj.loader.min_addr
0x400000
>>> proj.loader.max_addr
0x5004000

>>> proj.loader.main_object # we've loaded several binaries into this project. Here's_
↳ the main one!
<ELF Object true, maps [0x400000:0x60721f]>

>>> proj.loader.main_object.execstack # sample query: does this binary have an_
↳ executable stack?
False
>>> proj.loader.main_object.pic # sample query: is this binary position-independent?
True
```

3.1.3 The factory

There are a lot of classes in angr, and most of them require a project to be instantiated. Instead of making you pass around the project everywhere, we provide `project.factory`, which has several convenient constructors for common objects you'll want to use frequently.

This section will also serve as an introduction to several basic angr concepts. Strap in!

Blocks

First, we have `proj.factory.block()`, which is used to extract a **basic block** of code from a given address. This is an important fact - *angr analyzes code in units of basic blocks*. You will get back a Block object, which can tell you lots of fun things about the block of code:

```
>>> block = proj.factory.block(proj.entry) # lift a block of code from the program's
↳entry point
<Block for 0x401670, 42 bytes>

>>> block.pp() # pretty-print a disassembly to stdout
0x401670: xor    ebp, ebp
0x401672: mov    r9, rdx
0x401675: pop    rsi
0x401676: mov    rdx, rsp
0x401679: and    rsp, 0xfffffffffffffff0
0x40167d: push   rax
0x40167e: push   rsp
0x40167f: lea    r8, [rip + 0x2e2a]
0x401686: lea    rcx, [rip + 0x2db3]
0x40168d: lea    rdi, [rip - 0xd4]
0x401694: call   qword ptr [rip + 0x205866]

>>> block.instructions # how many instructions are there?
0xb
>>> block.instruction_addrs # what are the addresses of the instructions?
[0x401670, 0x401672, 0x401675, 0x401676, 0x401679, 0x40167d, 0x40167e, 0x40167f,
↳0x401686, 0x40168d, 0x401694]
```

Additionally, you can use a Block object to get other representations of the block of code:

```
>>> block.capstone # capstone disassembly
<CapstoneBlock for 0x401670>
>>> block.vex # VEX IRSB (that's a Python internal address,
↳not a program address)
<pyvex.block.IRSB at 0x7706330>
```

States

Here's another fact about angr - the Project object only represents an “initialization image” for the program. When you're performing execution with angr, you are working with a specific object representing a *simulated program state* - a SimState. Let's grab one right now!

```
>>> state = proj.factory.entry_state()
<SimState @ 0x401670>
```

A SimState contains a program's memory, registers, filesystem data... any “live data” that can be changed by execution has a home in the state. We'll cover how to interact with states in depth later, but for now, let's use `state.regs` and `state.mem` to access the registers and memory of this state:

```
>>> state.regs.rip # get the current instruction pointer
<BV64 0x401670>
>>> state.regs.rax
```

(continues on next page)

(continued from previous page)

```
<BV64 0x1c>
>>> state.mem[proj.entry].int.resolved # interpret the memory at the entry point as a C
↳ int
<BV32 0x8949ed31>
```

Those aren't Python ints! Those are *bitvectors*. Python integers don't have the same semantics as words on a CPU, e.g. wrapping on overflow, so we work with bitvectors, which you can think of as an integer as represented by a series of bits, to represent CPU data in angr. Note that each bitvector has a `.length` property describing how wide it is in bits.

We'll learn all about how to work with them soon, but for now, here's how to convert from Python ints to bitvectors and back again:

```
>>> bv = state.solver.BVV(0x1234, 32) # create a 32-bit-wide bitvector with value
↳ 0x1234
<BV32 0x1234> # BVV stands for bitvector value
>>> state.solver.eval(bv) # convert to Python int
0x1234
```

You can store these bitvectors back to registers and memory, or you can directly store a Python integer and it'll be converted to a bitvector of the appropriate size:

```
>>> state.regs.rsi = state.solver.BVV(3, 64)
>>> state.regs.rsi
<BV64 0x3>

>>> state.mem[0x1000].long = 4
>>> state.mem[0x1000].long.resolved
<BV64 0x4>
```

The `mem` interface is a little confusing at first, since it's using some pretty hefty Python magic. The short version of how to use it is:

- Use `array[index]` notation to specify an address
- Use `.<type>` to specify that the memory should be interpreted as `type` (common values: `char`, `short`, `int`, `long`, `size_t`, `uint8_t`, `uint16_t`...)
- From there, you can either:
 - Store a value to it, either a bitvector or a Python int
 - Use `.resolved` to get the value as a bitvector
 - Use `.concrete` to get the value as a Python int

There are more advanced usages that will be covered later!

Finally, if you try reading some more registers you may encounter a very strange looking value:

```
>>> state.regs.rdi
<BV64 reg_48_11_64{UNINITIALIZED}>
```

This is still a 64-bit bitvector, but it doesn't contain a numerical value. Instead, it has a name! This is called a *symbolic variable* and it is the underpinning of symbolic execution. Don't panic! We will discuss all of this in detail exactly two chapters from now.

Simulation Managers

If a state lets us represent a program at a given point in time, there must be a way to get it to the *next* point in time. A simulation manager is the primary interface in angr for performing execution, simulation, whatever you want to call it, with states. As a brief introduction, let's show how to tick that state we created earlier forward a few basic blocks.

First, we create the simulation manager we're going to be using. The constructor can take a state or a list of states.

```
>>> simgr = proj.factory.simulation_manager(state)
<SimulationManager with 1 active>
>>> simgr.active
[<SimState @ 0x401670>]
```

A simulation manager can contain several *stashes* of states. The default stash, `active`, is initialized with the state we passed in. We could look at `simgr.active[0]` to look at our state some more, if we haven't had enough!

Now... get ready, we're going to do some execution.

```
>>> simgr.step()
```

We've just performed a basic block's worth of symbolic execution! We can look at the active stash again, noticing that it's been updated, and furthermore, that it has **not** modified our original state. `SimState` objects are treated as immutable by execution - you can safely use a single state as a "base" for multiple rounds of execution.

```
>>> simgr.active
[<SimState @ 0x1020300>]
>>> simgr.active[0].regs.rip           # new and exciting!
<BV64 0x1020300>
>>> state.regs.rip                     # still the same!
<BV64 0x401670>
```

`/bin/true` isn't a very good example for describing how to do interesting things with symbolic execution, so we'll stop here for now.

3.1.4 Analyses

angr comes pre-packaged with several built-in analyses that you can use to extract some fun kinds of information from a program. Here they are:

```
>>> proj.analyses.           # Press TAB here in ipython to get an autocomplete-listing.
↳ of everything:
proj.analyses.BackwardSlice      proj.analyses.CongruencyCheck      proj.analyses.
↳ reload_analyses
proj.analyses.BinaryOptimizer    proj.analyses.DDG                  proj.analyses.
↳ StaticHooker
proj.analyses.BinDiff            proj.analyses.DFG                  proj.analyses.
↳ VariableRecovery
proj.analyses.BoyScout           proj.analyses.Disassembly          proj.analyses.
↳ VariableRecoveryFast
proj.analyses.CDG                proj.analyses.GirlScout            proj.analyses.
↳ Veritesting
proj.analyses.CFG                proj.analyses.Identifier            proj.analyses.VFG
proj.analyses.CFGEmulated        proj.analyses.LoopFinder            proj.analyses.VSA_
↳ DDG
proj.analyses.CFGFast            proj.analyses.Reassembler
```

A couple of these are documented later in this book, but in general, if you want to find how to use a given analysis, you should look in the api documentation for [angr.analyses](#). As an extremely brief example: here's how you construct and use a quick control-flow graph:

```
# Originally, when we loaded this binary it also loaded all its dependencies into the
↳ same virtual address space
# This is undesirable for most analysis.
>>> proj = angr.Project('/bin/true', auto_load_libs=False)
>>> cfg = proj.analyses.CFGFast()
<CFGFast Analysis Result at 0x2d85130>

# cfg.graph is a networkx DiGraph full of CFGNode instances
# You should go look up the networkx APIs to learn how to use this!
>>> cfg.graph
<networkx.classes.digraph.DiGraph at 0x2da43a0>
>>> len(cfg.graph.nodes())
951

# To get the CFGNode for a given address, use cfg.get_any_node
>>> entry_node = cfg.get_any_node(proj.entry)
>>> len(list(cfg.graph.successors(entry_node)))
2
```

3.1.5 Now what?

Having read this page, you should now be acquainted with several important angr concepts: basic blocks, states, bitvectors, simulation managers, and analyses. You can't really do anything interesting besides just use angr as a glorified debugger, though! Keep reading, and you will unlock deeper powers...

3.2 Loading a Binary

Previously, you saw just the barest taste of angr's loading facilities - you loaded `/bin/true`, and then loaded it again without its shared libraries. You also saw `proj.loader` and a few things it could do. Now, we'll dive into the nuances of these interfaces and the things they can tell you.

We briefly mentioned angr's binary loading component, CLE. CLE stands for "CLE Loads Everything", and is responsible for taking a binary (and any libraries that it depends on) and presenting it to the rest of angr in a way that is easy to work with.

3.2.1 The Loader

Let's load `examples/fauxware/fauxware` and take a deeper look at how to interact with the loader.

```
>>> import angr, monkeyhex
>>> proj = angr.Project('examples/fauxware/fauxware')
>>> proj.loader
<Loaded fauxware, maps [0x400000:0x5008000]>
```

Loaded Objects

The CLE loader (`cle.Loader`) represents an entire conglomerate of loaded *binary objects*, loaded and mapped into a single memory space. Each binary object is loaded by a loader backend that can handle its filetype (a subclass of `cle.Backend`). For example, `cle.ELF` is used to load ELF binaries.

There will also be objects in memory that don't correspond to any loaded binary. For example, an object used to provide thread-local storage support, and an externs object used to provide unresolved symbols.

You can get the full list of objects that CLE has loaded with `loader.all_objects`, as well as several more targeted classifications:

```
# All loaded objects
>>> proj.loader.all_objects
[<ELF Object fauxware, maps [0x400000:0x60105f]>,
 <ELF Object libc-2.23.so, maps [0x1000000:0x13c999f]>,
 <ELF Object ld-2.23.so, maps [0x2000000:0x2227167]>,
 <ELFTLSObject Object cle##tls, maps [0x3000000:0x3015010]>,
 <ExternObject Object cle##externs, maps [0x4000000:0x4008000]>,
 <KernelObject Object cle##kernel, maps [0x5000000:0x5008000]>]

# This is the "main" object, the one that you directly specified when loading the project
>>> proj.loader.main_object
<ELF Object fauxware, maps [0x400000:0x60105f]>

# This is a dictionary mapping from shared object name to object
>>> proj.loader.shared_objects
{'fauxware': <ELF Object fauxware, maps [0x400000:0x60105f]>,
 'libc.so.6': <ELF Object libc-2.23.so, maps [0x1000000:0x13c999f]>,
 'ld-linux-x86-64.so.2': <ELF Object ld-2.23.so, maps [0x2000000:0x2227167]> }

# Here's all the objects that were loaded from ELF files
# If this were a windows program we'd use all_pe_objects!
>>> proj.loader.all_elf_objects
[<ELF Object fauxware, maps [0x400000:0x60105f]>,
 <ELF Object libc-2.23.so, maps [0x1000000:0x13c999f]>,
 <ELF Object ld-2.23.so, maps [0x2000000:0x2227167]>]

# Here's the "externs object", which we use to provide addresses for unresolved imports,
↳ and angr internals
>>> proj.loader.extern_object
<ExternObject Object cle##externs, maps [0x4000000:0x4008000]>

# This object is used to provide addresses for emulated syscalls
>>> proj.loader.kernel_object
<KernelObject Object cle##kernel, maps [0x5000000:0x5008000]>

# Finally, you can to get a reference to an object given an address in it
>>> proj.loader.find_object_containing(0x400000)
<ELF Object fauxware, maps [0x400000:0x60105f]>
```

You can interact directly with these objects to extract metadata from them:

```
>>> obj = proj.loader.main_object
```

(continues on next page)

(continued from previous page)

```

# The entry point of the object
>>> obj.entry
0x400580

>>> obj.min_addr, obj.max_addr
(0x400000, 0x60105f)

# Retrieve this ELF's segments and sections
>>> obj.segments
<Regions: [<ELFSegment memsize=0xa74, filesize=0xa74, vaddr=0x400000, flags=0x5, ↵
↵offset=0x0>,
          <ELFSegment memsize=0x238, filesize=0x228, vaddr=0x600e28, flags=0x6, ↵
↵offset=0xe28>]>
>>> obj.sections
<Regions: [<Unnamed | offset 0x0, vaddr 0x0, size 0x0>,
          <.interp | offset 0x238, vaddr 0x400238, size 0x1c>,
          <.note.ABI-tag | offset 0x254, vaddr 0x400254, size 0x20>,
          ...etc

# You can get an individual segment or section by an address it contains:
>>> obj.find_segment_containing(obj.entry)
<ELFSegment memsize=0xa74, filesize=0xa74, vaddr=0x400000, flags=0x5, offset=0x0>
>>> obj.find_section_containing(obj.entry)
<.text | offset 0x580, vaddr 0x400580, size 0x338>

# Get the address of the PLT stub for a symbol
>>> addr = obj.plt['strcmp']
>>> addr
0x400550
>>> obj.reverse_plt[addr]
'strcmp'

# Show the prelinked base of the object and the location it was actually mapped into. ↵
↵memory by CLE
>>> obj.linked_base
0x400000
>>> obj.mapped_base
0x400000

```

Symbols and Relocations

You can also work with symbols while using CLE. A symbol is a fundamental concept in the world of executable formats, effectively mapping a name to an address.

The easiest way to get a symbol from CLE is to use `loader.find_symbol`, which takes either a name or an address and returns a `Symbol` object.

```

>>> strcmp = proj.loader.find_symbol('strcmp')
>>> strcmp
<Symbol "strcmp" in libc.so.6 at 0x1089cd0>

```

The most useful attributes on a symbol are its name, its owner, and its address, but the “address” of a symbol can be

ambiguous. The Symbol object has three ways of reporting its address:

- `.rebased_addr` is its address in the global address space. This is what is shown in the print output.
- `.linked_addr` is its address relative to the prelinked base of the binary. This is the address reported in, for example, `readelf(1)`.
- `.relative_addr` is its address relative to the object base. This is known in the literature (particularly the Windows literature) as an RVA (relative virtual address).

```
>>> strcmp.name
'strcmp'

>>> strcmp.owner
<ELF Object libc-2.23.so, maps [0x10000000:0x13c999f]>

>>> strcmp.rebased_addr
0x1089cd0
>>> strcmp.linked_addr
0x89cd0
>>> strcmp.relative_addr
0x89cd0
```

In addition to providing debug information, symbols also support the notion of dynamic linking. `libc` provides the `strcmp` symbol as an export, and the main binary depends on it. If we ask CLE to give us a `strcmp` symbol from the main object directly, it'll tell us that this is an *import symbol*. Import symbols do not have meaningful addresses associated with them, but they do provide a reference to the symbol that was used to resolve them, as `.resolvedby`.

```
>>> strcmp.is_export
True
>>> strcmp.is_import
False

# On Loader, the method is find_symbol because it performs a search operation to find
↳ the symbol.
# On an individual object, the method is get_symbol because there can only be one symbol
↳ with a given name.
>>> main_strcmp = proj.loader.main_object.get_symbol('strcmp')
>>> main_strcmp
<Symbol "strcmp" in fauxware (import)>
>>> main_strcmp.is_export
False
>>> main_strcmp.is_import
True
>>> main_strcmp.resolvedby
<Symbol "strcmp" in libc.so.6 at 0x1089cd0>
```

The specific ways that the links between imports and exports should be registered in memory are handled by another notion called *relocations*. A relocation says, “when you match *[import]* up with an export symbol, please write the export’s address to *[location]*, formatted as *[format]*.” We can see the full list of relocations for an object (as `Relocation` instances) as `obj.relocs`, or just a mapping from symbol name to `Relocation` as `obj.imports`. There is no corresponding list of export symbols.

A relocation’s corresponding import symbol can be accessed as `.symbol`. The address the relocation will write to is accessible through any of the address identifiers you can use for `Symbol`, and you can get a reference to the object requesting the relocation with `.owner` as well.

```
# Relocations don't have a good pretty-printing, so those addresses are Python-internal,
↳ unrelated to our program
>>> proj.loader.shared_objects['libc.so.6'].imports
{'__libc_enable_secure': <cle.backends.elf.relocation.amd64.R_X86_64_GLOB_DAT at
↳ 0x7ff5c5fce780>,
  '__tls_get_addr': <cle.backends.elf.relocation.amd64.R_X86_64_JUMP_SLOT at
↳ 0x7ff5c6018358>,
  '_dl_argv': <cle.backends.elf.relocation.amd64.R_X86_64_GLOB_DAT at 0x7ff5c5fd2e48>,
  '_dl_find_dso_for_object': <cle.backends.elf.relocation.amd64.R_X86_64_JUMP_SLOT at
↳ 0x7ff5c6018588>,
  '_dl_starting_up': <cle.backends.elf.relocation.amd64.R_X86_64_GLOB_DAT at
↳ 0x7ff5c5fd2550>,
  '_rtld_global': <cle.backends.elf.relocation.amd64.R_X86_64_GLOB_DAT at 0x7ff5c5fce4e0>,
  '_rtld_global_ro': <cle.backends.elf.relocation.amd64.R_X86_64_GLOB_DAT at
↳ 0x7ff5c5fcea20>}
```

If an import cannot be resolved to any export, for example, because a shared library could not be found, CLE will automatically update the externs object (`loader.extern_obj`) to claim it provides the symbol as an export.

3.2.2 Loading Options

If you are loading something with `angr.Project` and you want to pass an option to the `cle.Loader` instance that `Project` implicitly creates, you can just pass the keyword argument directly to the `Project` constructor, and it will be passed on to CLE. You should look at the [CLE API docs](#), if you want to know everything that could possibly be passed in as an option, but we will go over some important and frequently used options here.

We've discussed `auto_load_libs` already - it enables or disables CLE's attempt to automatically resolve shared library dependencies, and is on by default. Additionally, there is the opposite, `except_missing_libs`, which, if set to true, will cause an exception to be thrown whenever a binary has a shared library dependency that cannot be resolved.

You can pass a list of strings to `force_load_libs` and anything listed will be treated as an unresolved shared library dependency right out of the gate, or you can pass a list of strings to `skip_libs` to prevent any library of that name from being resolved as a dependency. Additionally, you can pass a list of strings (or a single string) to `ld_path`, which will be used as an additional search path for shared libraries, before any of the defaults: the same directory as the loaded program, the current working directory, and your system libraries.

If you want to specify some options that only apply to a specific binary object, CLE will let you do that too. The parameters `main_opts` and `lib_opts` do this by taking dictionaries of options. `main_opts` is a mapping from option names to option values, while `lib_opts` is a mapping from library name to dictionaries mapping option names to option values.

The options that you can use vary from backend to backend, but some common ones are:

- `backend` - which backend to use, as either a class or a name
- `base_addr` - a base address to use
- `entry_point` - an entry point to use
- `arch` - the name of an architecture to use

Example:

```
>>> angr.Project('examples/fauxware/fauxware', main_opts={'backend': 'blob', 'arch':
↳ 'i386'}, lib_opts={'libc.so.6': {'backend': 'elf'}})
<Project examples/fauxware/fauxware>
```

Backends

CLE currently has backends for statically loading ELF, PE, CGC, Mach-O and ELF core dump files, as well as loading files into a flat address space. CLE will automatically detect the correct backend to use in most cases, so you shouldn't need to specify which backend you're using unless you're doing some pretty weird stuff.

You can force CLE to use a specific backend for an object by including a key in its options dictionary, as described above. Some backends cannot autodetect which architecture to use and *must* have a `arch` specified. The key doesn't need to match any list of architectures; `angr` will identify which architecture you mean given almost any common identifier for any supported arch.

To refer to a backend, use the name from this table:

backend name	description	requires arch?
elf	Static loader for ELF files based on PyELFTools	no
pe	Static loader for PE files based on PEFile	no
mach-o	Static loader for Mach-O files. Does not support dynamic linking or rebasing.	no
cgc	Static loader for Cyber Grand Challenge binaries	no
backedcgc	Static loader for CGC binaries that allows specifying memory and register backers	no
elfcore	Static loader for ELF core dumps	no
blob	Loads the file into memory as a flat image	yes

3.2.3 Symbolic Function Summaries

By default, Project tries to replace external calls to library functions by using symbolic summaries termed *SimProcedures* - effectively just Python functions that imitate the library function's effect on the state. We've implemented [a whole bunch of functions](#) as SimProcedures. These builtin procedures are available in the `angr.SIM_PROCEDURES` dictionary, which is two-leveled, keyed first on the package name (`libc`, `posix`, `win32`, `stubs`) and then on the name of the library function. Executing a SimProcedure instead of the actual library function that gets loaded from your system makes analysis a LOT more tractable, at the cost of *some potential inaccuracies* <Gotchas when using `angr`>.

When no such summary is available for a given function:

- if `auto_load_libs` is `True` (this is the default), then the *real* library function is executed instead. This may or may not be what you want, depending on the actual function. For example, some of `libc`'s functions are extremely complex to analyze and will most likely cause an explosion of the number of states for the path trying to execute them.
- if `auto_load_libs` is `False`, then external functions are unresolved, and Project will resolve them to a generic "stub" SimProcedure called `ReturnUnconstrained`. It does what its name says: it returns a unique unconstrained symbolic value each time it is called.
- if `use_sim_procedures` (this is a parameter to `angr.Project`, not `cle.Loader`) is `False` (it is `True` by default), then only symbols provided by the extern object will be replaced with SimProcedures, and they will be replaced by a stub `ReturnUnconstrained`, which does nothing but return a symbolic value.
- you may specify specific symbols to exclude from being replaced with SimProcedures with the parameters to `angr.Project`: `exclude_sim_procedures_list` and `exclude_sim_procedures_func`.
- Look at the code for `angr.Project._register_object` for the exact algorithm.

The mechanism by which `angr` replaces library code with a Python summary is called hooking, and you can do it too! When performing simulation, at every step `angr` checks if the current address has been hooked, and if so, runs the hook instead of the binary code at that address. The API to let you do this is `proj.hook(addr, hook)`, where `hook` is a

SimProcedure instance. You can manage your project's hooks with `.is_hooked`, `.unhook`, and `.hooked_by`, which should hopefully not require explanation.

There is an alternate API for hooking an address that lets you specify your own off-the-cuff function to use as a hook, by using `proj.hook(addr)` as a function decorator. If you do this, you can also optionally specify a `length` keyword argument to make execution jump some number of bytes forward after your hook finishes.

```
>>> stub_func = angr.SIM_PROCEDURES['stubs']['ReturnUnconstrained'] # this is a CLASS
>>> proj.hook(0x10000, stub_func()) # hook with an instance of the class

>>> proj.is_hooked(0x10000) # these functions should be pretty self-
↪ explanatory
True
>>> proj.hooked_by(0x10000)
<ReturnUnconstrained>
>>> proj.unhook(0x10000)

>>> @proj.hook(0x20000, length=5)
... def my_hook(state):
...     state.regs.rax = 1

>>> proj.is_hooked(0x20000)
True
```

Furthermore, you can use `proj.hook_symbol(name, hook)`, providing the name of a symbol as the first argument, to hook the address where the symbol lives. One very important usage of this is to extend the behavior of angr's built-in library SimProcedures. Since these library functions are just classes, you can subclass them, overriding pieces of their behavior, and then use your subclass in a hook.

3.2.4 So far so good!

By now, you should have a reasonable understanding of how to control the environment in which your analysis happens, on the level of the CLE loader and the angr Project. You should also understand that angr makes a reasonable attempt to simplify its analysis by hooking complex library functions with SimProcedures that summarize the effects of the functions.

In order to see all the things you can do with the CLE loader and its backends, look at the [CLE API docs](#).

3.3 Symbolic Expressions and Constraint Solving

angr's power comes not from it being an emulator, but from being able to execute with what we call *symbolic variables*. Instead of saying that a variable has a *concrete* numerical value, we can say that it holds a *symbol*, effectively just a name. Then, performing arithmetic operations with that variable will yield a tree of operations (termed an *abstract syntax tree* or *AST*, from compiler theory). ASTs can be translated into constraints for an *SMT solver*, like z3, in order to ask questions like “*given the output of this sequence of operations, what must the input have been?*” Here, you'll learn how to use angr to answer this.

3.3.1 Working with Bitvectors

Let's get a dummy project and state so we can start playing with numbers.

```
>>> import angr, monkeyhex
>>> proj = angr.Project('/bin/true')
>>> state = proj.factory.entry_state()
```

A bitvector is just a sequence of bits, interpreted with the semantics of a bounded integer for arithmetic. Let's make a few.

```
# 64-bit bitvectors with concrete values 1 and 100
>>> one = state.solver.BVV(1, 64)
>>> one
<BV64 0x1>
>>> one_hundred = state.solver.BVV(100, 64)
>>> one_hundred
<BV64 0x64>

# create a 27-bit bitvector with concrete value 9
>>> weird_nine = state.solver.BVV(9, 27)
>>> weird_nine
<BV27 0x9>
```

As you can see, you can have any sequence of bits and call them a bitvector. You can do math with them too:

```
>>> one + one_hundred
<BV64 0x65>

# You can provide normal Python integers and they will be coerced to the
appropriate type: >>> one_hundred + 0x100 <BV64 0x164>

# The semantics of normal wrapping arithmetic apply
>>> one_hundred - one*200
<BV64 0xffffffffffffff9c>
```

You *cannot* say `one + weird_nine`, though. It is a type error to perform an operation on bitvectors of differing lengths. You can, however, extend `weird_nine` so it has an appropriate number of bits:

```
>>> weird_nine.zero_extend(64 - 27)
<BV64 0x9>
>>> one + weird_nine.zero_extend(64 - 27)
<BV64 0xa>
```

`zero_extend` will pad the bitvector on the left with the given number of zero bits. You can also use `sign_extend` to pad with a duplicate of the highest bit, preserving the value of the bitvector under two's complement signed integer semantics.

Now, let's introduce some symbols into the mix.

```
# Create a bitvector symbol named "x" of length 64 bits
>>> x = state.solver.BVS("x", 64)
>>> x
<BV64 x_9_64>
>>> y = state.solver.BVS("y", 64)
```

(continues on next page)

(continued from previous page)

```
>>> y
<BV64 y_10_64>
```

x and y are now *symbolic variables*, which are kind of like the variables you learned to work with in 7th grade algebra. Notice that the name you provided has been mangled by appending an incrementing counter and You can do as much arithmetic as you want with them, but you won't get a number back, you'll get an AST instead.

```
>>> x + one
<BV64 x_9_64 + 0x1>

>>> (x + one) / 2
<BV64 (x_9_64 + 0x1) / 0x2>

>>> x - y
<BV64 x_9_64 - y_10_64>
```

Technically x and y and even `one` are also ASTs - any bitvector is a tree of operations, even if that tree is only one layer deep. To understand this, let's learn how to process ASTs.

Each AST has a `.op` and a `.args`. The `op` is a string naming the operation being performed, and the `args` are the values the operation takes as input. Unless the `op` is BVV or BVS (or a few others...), the `args` are all other ASTs, the tree eventually terminating with BVVs or BVSs.

```
>>> tree = (x + 1) / (y + 2)
>>> tree
<BV64 (x_9_64 + 0x1) / (y_10_64 + 0x2)>
>>> tree.op
'__floordiv__'
>>> tree.args
(<BV64 x_9_64 + 0x1>, <BV64 y_10_64 + 0x2>)
>>> tree.args[0].op
'__add__'
>>> tree.args[0].args
(<BV64 x_9_64>, <BV64 0x1>)
>>> tree.args[0].args[1].op
'BVV'
>>> tree.args[0].args[1].args
(1, 64)
```

From here on out, we will use the word “bitvector” to refer to any AST whose topmost operation produces a bitvector. There can be other data types represented through ASTs, including floating point numbers and, as we're about to see, booleans.

3.3.2 Symbolic Constraints

Performing comparison operations between any two similarly-typed ASTs will yield another AST - not a bitvector, but now a symbolic boolean.

```
>>> x == 1
<Bool x_9_64 == 0x1>
>>> x == one
<Bool x_9_64 == 0x1>
```

(continues on next page)

(continued from previous page)

```
>>> x > 2
<Bool x_9_64 > 0x2>
>>> x + y == one_hundred + 5
<Bool (x_9_64 + y_10_64) == 0x69>
>>> one_hundred > 5
<Bool True>
>>> one_hundred > -5
<Bool False>
```

One tidbit you can see from this is that the comparisons are unsigned by default. The -5 in the last example is coerced to <BV64 0xfffffffffffffffb>, which is definitely not less than one hundred. If you want the comparison to be signed, you can say `one_hundred.SGT(-5)` (that's "signed greater-than"). A full list of operations can be found at the end of this chapter.

This snippet also illustrates an important point about working with angr - you should never directly use a comparison between variables in the condition for an if- or while-statement, since the answer might not have a concrete truth value. Even if there is a concrete truth value, if `one > one_hundred` will raise an exception. Instead, you should use `solver.is_true` and `solver.is_false`, which test for concrete truthiness/falsiness without performing a constraint solve.

```
>>> yes = one == 1
>>> no = one == 2
>>> maybe = x == y
>>> state.solver.is_true(yes)
True
>>> state.solver.is_false(yes)
False
>>> state.solver.is_true(no)
False
>>> state.solver.is_false(no)
True
>>> state.solver.is_true(maybe)
False
>>> state.solver.is_false(maybe)
False
```

3.3.3 Constraint Solving

You can treat any symbolic boolean as an assertion about the valid values of a symbolic variable by adding it as a *constraint* to the state. You can then query for a valid value of a symbolic variable by asking for an evaluation of a symbolic expression.

An example will probably be more clear than an explanation here:

```
>>> state.solver.add(x > y)
>>> state.solver.add(y > 2)
>>> state.solver.add(10 > x)
>>> state.solver.eval(x)
4
```

By adding these constraints to the state, we've forced the constraint solver to consider them as assertions that must be satisfied about any values it returns. If you run this code, you might get a different value for x, but that value will definitely be greater than 3 (since y must be greater than 2 and x must be greater than y) and less than 10. Furthermore,

if you then say `state.solver.eval(y)`, you'll get a value of `y` which is consistent with the value of `x` that you got. If you don't add any constraints between two queries, the results will be consistent with each other.

From here, it's easy to see how to do the task we proposed at the beginning of the chapter - finding the input that produced a given output.

```
# get a fresh state without constraints
>>> state = proj.factory.entry_state()
>>> input = state.solver.BVS('input', 64)
>>> operation = (((input + 4) * 3) >> 1) + input
>>> output = 200
>>> state.solver.add(operation == output)
>>> state.solver.eval(input)
0x3333333333333381
```

Note that, again, this solution only works because of the bitvector semantics. If we were operating over the domain of integers, there would be no solutions!

If we add conflicting or contradictory constraints, such that there are no values that can be assigned to the variables such that the constraints are satisfied, the state becomes *unsatisfiable*, or *unsat*, and queries against it will raise an exception. You can check the satisfiability of a state with `state.satisfiable()`.

```
>>> state.solver.add(input < 2**32)
>>> state.satisfiable()
False
```

You can also evaluate more complex expressions, not just single variables.

```
# fresh state
>>> state = proj.factory.entry_state()
>>> state.solver.add(x - y >= 4)
>>> state.solver.add(y > 0)
>>> state.solver.eval(x)
5
>>> state.solver.eval(y)
1
>>> state.solver.eval(x + y)
6
```

From this we can see that `eval` is a general purpose method to convert any bitvector into a Python primitive while respecting the integrity of the state. This is why we use `eval` to convert from concrete bitvectors to Python ints, too!

Also note that the `x` and `y` variables can be used in this new state despite having been created using an old state. Variables are not tied to any one state, and can exist freely.

3.3.4 Floating point numbers

`z3` has support for the theory of IEEE754 floating point numbers, and so `angr` can use them as well. The main difference is that instead of a width, a floating point number has a *sort*. You can create floating point symbols and values with `FPV` and `FPS`.

```
# fresh state
>>> state = proj.factory.entry_state()
>>> a = state.solver.FPV(3.2, state.solver.fp.FSORT_DOUBLE)
>>> a
```

(continues on next page)

(continued from previous page)

```
<FP64 FPV(3.2, DOUBLE)>

>>> b = state.solver.FPS('b', state.solver.fp.FSORT_DOUBLE)
>>> b
<FP64 FPS('FP_b_0_64', DOUBLE)>

>>> a + b
<FP64 fpAdd('RNE', FPV(3.2, DOUBLE), FPS('FP_b_0_64', DOUBLE))>

>>> a + 4.4
<FP64 FPV(7.6000000000000005, DOUBLE)>

>>> b + 2 < 0
<Bool fpLT(fpAdd('RNE', FPS('FP_b_0_64', DOUBLE), FPV(2.0, DOUBLE)), FPV(0.0, DOUBLE))>
```

So there's a bit to unpack here - for starters the pretty-printing isn't as smart about floating point numbers. But past that, most operations actually have a third parameter, implicitly added when you use the binary operators - the rounding mode. The IEEE754 spec supports multiple rounding modes (round-to-nearest, round-to-zero, round-to-positive, etc), so z3 has to support them. If you want to specify the rounding mode for an operation, use the fp operation explicitly (solver.fpAdd for example) with a rounding mode (one of solver.fp.RM_*) as the first argument.

Constraints and solving work in the same way, but with eval returning a floating point number:

```
>>> state.solver.add(b + 2 < 0)
>>> state.solver.add(b + 2 > -1)
>>> state.solver.eval(b)
-2.4999999999999996
```

This is nice, but sometimes we need to be able to work directly with the representation of the float as a bitvector. You can interpret bitvectors as floats and vice versa, with the methods raw_to_bv and raw_to_fp:

```
>>> a.raw_to_bv()
<BV64 0x4009999999999999a>
>>> b.raw_to_bv()
<BV64 fpToIEEEBV(FPS('FP_b_0_64', DOUBLE))>

>>> state.solver.BVV(0, 64).raw_to_fp()
<FP64 FPV(0.0, DOUBLE)>
>>> state.solver.BVS('x', 64).raw_to_fp()
<FP64 fpToFP(x_1_64, DOUBLE)>
```

These conversions preserve the bit-pattern, as if you casted a float pointer to an int pointer or vice versa. However, if you want to preserve the value as closely as possible, as if you casted a float to an int (or vice versa), you can use a different set of methods, val_to_fp and val_to_bv. These methods must take the size or sort of the target value as a parameter, due to the floating-point nature of floats.

```
>>> a
<FP64 FPV(3.2, DOUBLE)>
>>> a.val_to_bv(12)
<BV12 0x3>
>>> a.val_to_bv(12).val_to_fp(state.solver.fp.FSORT_FLOAT)
<FP32 FPV(3.0, FLOAT)>
```

These methods can also take a signed parameter, designating the signedness of the source or target bitvector.

3.3.5 More Solving Methods

`eval` will give you one possible solution to an expression, but what if you want several? What if you want to ensure that the solution is unique? The solver provides you with several methods for common solving patterns:

- `solver.eval(expression)` will give you one possible solution to the given expression.
- `solver.eval_one(expression)` will give you the solution to the given expression, or throw an error if more than one solution is possible.
- `solver.eval_upto(expression, n)` will give you up to `n` solutions to the given expression, returning fewer than `n` if fewer than `n` are possible.
- `solver.eval_atleast(expression, n)` will give you `n` solutions to the given expression, throwing an error if fewer than `n` are possible.
- `solver.eval_exact(expression, n)` will give you `n` solutions to the given expression, throwing an error if fewer or more than are possible.
- `solver.min(expression)` will give you the minimum possible solution to the given expression.
- `solver.max(expression)` will give you the maximum possible solution to the given expression.

Additionally, all of these methods can take the following keyword arguments:

- `extra_constraints` can be passed as a tuple of constraints. These constraints will be taken into account for this evaluation, but will not be added to the state.
- `cast_to` can be passed a data type to cast the result to. Currently, this can only be `int` and `bytes`, which will cause the method to return the corresponding representation of the underlying data. For example, `state.solver.eval(state.solver.BVV(0x41424344, 32), cast_to=bytes)` will return `b'ABCD'`.

3.3.6 Summary

That was a lot!! After reading this, you should be able to create and manipulate bitvectors, booleans, and floating point values to form trees of operations, and then query the constraint solver attached to a state for possible solutions under a set of constraints. Hopefully by this point you understand the power of using ASTs to represent computations, and the power of a constraint solver.

In the [appendix](#), you can find a reference for all the additional operations you can apply to ASTs, in case you ever need a quick table to look at.

3.4 Machine State - memory, registers, and so on

So far, we've only used angr's simulated program states (`SimState` objects) in the barest possible way in order to demonstrate basic concepts about angr's operation. Here, you'll learn about the structure of a state object and how to interact with it in a variety of useful ways.

3.4.1 Review: Reading and writing memory and registers

If you’ve been reading this book in order (and you should be, at least for this first section), you already saw the basics of how to access memory and registers. `state.regs` provides read and write access to the registers through attributes with the names of each register, and `state.mem` provides typed read and write access to memory with index-access notation to specify the address followed by an attribute access to specify the type you would like to interpret the memory as.

Additionally, you should now know how to work with ASTs, so you can now understand that any bitvector-typed AST can be stored in registers or memory.

Here are some quick examples for copying and performing operations on data from the state:

```
>>> import angr, claripy
>>> proj = angr.Project('/bin/true')
>>> state = proj.factory.entry_state()

# copy rsp to rbp
>>> state.regs.rbp = state.regs.rsp

# store rdx to memory at 0x1000
>>> state.mem[0x1000].uint64_t = state.regs.rdx

# dereference rbp
>>> state.regs.rbp = state.mem[state.regs.rbp].uint64_t.resolved

# add rax, qword ptr [rsp + 8]
>>> state.regs.rax += state.mem[state.regs.rsp + 8].uint64_t.resolved
```

3.4.2 Basic Execution

Earlier, we showed how to use a Simulation Manager to do some basic execution. We’ll show off the full capabilities of the simulation manager in the next chapter, but for now we can use a much simpler interface to demonstrate how symbolic execution works: `state.step()`. This method will perform one step of symbolic execution and return an object called `angr.engines.successors.SimSuccessors`. Unlike normal emulation, symbolic execution can produce several successor states that can be classified in a number of ways. For now, what we care about is the `.successors` property of this object, which is a list containing all the “normal” successors of a given step.

Why a list, instead of just a single successor state? Well, angr’s process of symbolic execution is just the taking the operations of the individual instructions compiled into the program and performing them to mutate a `SimState`. When a line of code like `if (x > 4)` is reached, what happens if `x` is a symbolic bitvector? Somewhere in the depths of angr, the comparison `x > 4` is going to get performed, and the result is going to be `<Bool x_32_1 > 4>`.

That’s fine, but the next question is, do we take the “true” branch or the “false” one? The answer is, we take both! We generate two entirely separate successor states - one simulating the case where the condition was true and simulating the case where the condition was false. In the first state, we add `x > 4` as a constraint, and in the second state, we add `!(x > 4)` as a constraint. That way, whenever we perform a constraint solve using either of these successor states, *the conditions on the state ensure that any solutions we get are valid inputs that will cause execution to follow the same path that the given state has followed.*

To demonstrate this, let’s use a *fake firmware image* `<../examples/fauxware/fauxware>` as an example. If you look at the *source code* `<../examples/fauxware/fauxware.c>` for this binary, you’ll see that the authentication mechanism for the firmware is backdoored; any username can be authenticated as an administrator with the password “SOSNEAKY”. Furthermore, the first comparison against user input that happens is the comparison against the backdoor, so if we step

until we get more than one successor state, one of those states will contain conditions constraining the user input to be the backdoor password. The following snippet implements this:

```
>>> proj = angr.Project('examples/fauxware/fauxware')
>>> state = proj.factory.entry_state(stdin=angr.SimFile) # ignore that argument for now.
↳- we're disabling a more complicated default setup for the sake of education
>>> while True:
...     succ = state.step()
...     if len(succ.successors) == 2:
...         break
...     state = succ.successors[0]

>>> state1, state2 = succ.successors
>>> state1
<SimState @ 0x400629>
>>> state2
<SimState @ 0x400699>
```

Don't look at the constraints on these states directly - the branch we just went through involves the result of `strcmp`, which is a tricky function to emulate symbolically, and the resulting constraints are *very* complicated.

The program we emulated took data from standard input, which angr treats as an infinite stream of symbolic data by default. To perform a constraint solve and get a possible value that input could have taken in order to satisfy the constraints, we'll need to get a reference to the actual contents of `stdin`. We'll go over how our file and input subsystems work later on this very page, but for now, just use `state.posix.stdin.load(0, state.posix.stdin.size)` to retrieve a bitvector representing all the content read from `stdin` so far.

```
>>> input_data = state1.posix.stdin.load(0, state1.posix.stdin.size)

>>> state1.solver.eval(input_data, cast_to=bytes)
b'\x00\x00\x00\x00\x00\x00\x00\x00\x00SOSNEAKY\x00\x00\x00'

>>> state2.solver.eval(input_data, cast_to=bytes)
b'\x00\x00\x00\x00\x00\x00\x00\x00\x00S\x00x80N\x00\x00 \x00\x00\x00\x00'
```

As you can see, in order to go down the `state1` path, you must have given as a password the backdoor string “SOSNEAKY”. In order to go down the `state2` path, you must have given something *besides* “SOSNEAKY”. z3 has helpfully provided one of the billions of strings fitting this criteria.

Fauxware was the first program angr's symbolic execution ever successfully worked on, back in 2013. By finding its backdoor using angr you are participating in a grand tradition of having a bare-bones understanding of how to use symbolic execution to extract meaning from binaries!

3.4.3 State Presets

So far, whenever we've been working with a state, we've created it with `project.factory.entry_state()`. This is just one of several *state constructors* available on the project factory:

- `.blank_state()` constructs a “blank slate” blank state, with most of its data left uninitialized. When accessing uninitialized data, an unconstrained symbolic value will be returned.
- `.entry_state()` constructs a state ready to execute at the main binary's entry point.
- `.full_init_state()` constructs a state that is ready to execute through any initializers that need to be run before the main binary's entry point, for example, shared library constructors or preinitializers. When it is finished with these it will jump to the entry point.

- `.call_state()` constructs a state ready to execute a given function.

You can customize the state through several arguments to these constructors:

- All of these constructors can take an `addr` argument to specify the exact address to start.
- If you're executing in an environment that can take command line arguments or an environment, you can pass a list of arguments through `args` and a dictionary of environment variables through `env` into `entry_state` and `full_init_state`. The values in these structures can be strings or bitvectors, and will be serialized into the state as the arguments and environment to the simulated execution. The default `args` is an empty list, so if the program you're analyzing expects to find at least an `argv[0]`, you should always provide that!
- If you'd like to have `argc` be symbolic, you can pass a symbolic bitvector as `argc` to the `entry_state` and `full_init_state` constructors. Be careful, though: if you do this, you should also add a constraint to the resulting state that your value for `argc` cannot be larger than the number of `args` you passed into `args`.
- To use the call state, you should call it with `.call_state(addr, arg1, arg2, ...)`, where `addr` is the address of the function you want to call and `argN` is the Nth argument to that function, either as a Python integer, string, or array, or a bitvector. If you want to have memory allocated and actually pass in a pointer to an object, you should wrap it in an `PointerWrapper`, i.e. `angr.PointerWrapper("point to me!")`. The results of this API can be a little unpredictable, but we're working on it.
- To specify the calling convention used for a function with `call_state`, you can pass a `SimCC` instance as the `cc` argument. We try to pick a sane default, but for special cases you will need to help angr out.

There are several more options that can be used in any of these constructors! See the docs on the `project.factory` object (an `angr.factory.AngrObjectFactory`) for more details.

3.4.4 Low level interface for memory

The `state.mem` interface is convenient for loading typed data from memory, but when you want to do raw loads and stores to and from ranges of memory, it's very cumbersome. It turns out that `state.mem` is actually just a bunch of logic to correctly access the underlying memory storage, which is just a flat address space filled with bitvector data: `state.memory`. You can use `state.memory` directly with the `.load(addr, size)` and `.store(addr, val)` methods:

```
>>> s = proj.factory.blank_state()
>>> s.memory.store(0x4000, s.solver.BVV(0x0123456789abcdef0123456789abcdef, 128))
>>> s.memory.load(0x4004, 6) # load-size is in bytes
<BV48 0x89abcdef0123>
```

As you can see, the data is loaded and stored in a “big-endian” fashion, since the primary purpose of `state.memory` is to load and store swaths of data with no attached semantics. However, if you want to perform a byteswap on the loaded or stored data, you can pass a keyword argument `endness` - if you specify little-endian, byteswap will happen. The `endness` should be one of the members of the `Endness` enum in the `archinfo` package used to hold declarative data about CPU architectures for angr. Additionally, the `endness` of the program being analyzed can be found as `arch.memory_endness` - for instance `state.arch.memory_endness`.

```
>>> import archinfo
>>> s.memory.load(0x4000, 4, endness=archinfo.Endness.LE)
<BV32 0x67452301>
```

There is also a low-level interface for register access, `state.registers`, that uses the exact same API as `state.memory`, but explaining its behavior involves a *dive* into the abstractions that angr uses to seamlessly work with multiple architectures. The short version is that it is simply a register file, with the mapping between registers and offsets defined in `archinfo`.

3.4.5 State Options

There are a lot of little tweaks that can be made to the internals of angr that will optimize behavior in some situations and be a detriment in others. These tweaks are controlled through state options.

On each SimState object, there is a set (`state.options`) of all its enabled options. Each option (really just a string) controls the behavior of angr's execution engine in some minute way. A listing of the full domain of options, along with the defaults for different state types, can be found in *the appendix*. You can access an individual option for adding to a state through `angr.options`. The individual options are named with CAPITAL_LETTERS, but there are also common groupings of objects that you might want to use bundled together, named with lowercase_letters.

When creating a SimState through any constructor, you may pass the keyword arguments `add_options` and `remove_options`, which should be sets of options that modify the initial options set from the default.

```
# Example: enable lazy solves, an option that causes state satisfiability to be checked
↳ as infrequently as possible.
# This change to the settings will be propagated to all successor states created from
↳ this state after this line.
>>> s.options.add(angr.options.LAZY_SOLVES)

# Create a new state with lazy solves enabled
>>> s = proj.factory.entry_state(add_options={angr.options.LAZY_SOLVES})

# Create a new state without simplification options enabled
>>> s = proj.factory.entry_state(remove_options=angr.options.simplification)
```

3.4.6 State Plugins

With the exception of the set of options just discussed, everything stored in a SimState is actually stored in a *plugin* attached to the state. Almost every property on the state we've discussed so far is a plugin - `memory`, `registers`, `mem`, `regs`, `solver`, etc. This design allows for code modularity as well as the ability to easily *implement new kinds of data storage* for other aspects of an emulated state, or the ability to provide alternate implementations of plugins.

For example, the normal memory plugin simulates a flat memory space, but analyses can choose to enable the “abstract memory” plugin, which uses alternate data types for addresses to simulate free-floating memory mappings independent of address, to provide `state.memory`. Conversely, plugins can reduce code complexity: `state.memory` and `state.registers` are actually two different instances of the same plugin, since the registers are emulated with an address space as well.

The globals plugin

`state.globals` is an extremely simple plugin: it implements the interface of a standard Python dict, allowing you to store arbitrary data on a state.

The history plugin

`state.history` is a very important plugin storing historical data about the path a state has taken during execution. It is actually a linked list of several history nodes, each one representing a single round of execution—you can traverse this list with `state.history.parent.parent` etc.

To make it more convenient to work with this structure, the history also provides several efficient iterators over the history of certain values. In general, these values are stored as `history.recent_NAME` and the iterator over them is just `history.NAME`. For example, for `addr in state.history.bbl_addrs: print hex(addr)` will print out a basic block address trace for the binary, while `state.history.recent_bbl_addrs` is the list of basic blocks executed in the most recent step, `state.history.parent.recent_bbl_addrs` is the list of basic blocks executed in the previous step, etc. If you ever need to quickly obtain a flat list of these values, you can access `.hardcopy`, e.g. `state.history.bbl_addrs.hardcopy`. Keep in mind though, index-based accessing is implemented on the iterators.

Here is a brief listing of some of the values stored in the history:

- `history.descriptions` is a listing of string descriptions of each of the rounds of execution performed on the state.
- `history.bbl_addrs` is a listing of the basic block addresses executed by the state. There may be more than one per round of execution, and not all addresses may correspond to binary code - some may be addresses at which `SimProcedures` are hooked.
- `history.jumpkinds` is a listing of the disposition of each of the control flow transitions in the state's history, as VEX enum strings.
- `history.jump_guards` is a listing of the conditions guarding each of the branches that the state has encountered.
- `history.events` is a semantic listing of “interesting events” which happened during execution, such as the presence of a symbolic jump condition, the program popping up a message box, or execution terminating with an exit code.
- `history.actions` is usually empty, but if you add the `angr.options.refs` options to the state, it will be populated with a log of all the memory, register, and temporary value accesses performed by the program.

The callstack plugin

angr will track the call stack for the emulated program. On every call instruction, a frame will be added to the top of the tracked callstack, and whenever the stack pointer drops below the point where the topmost frame was called, a frame is popped. This allows angr to robustly store data local to the current emulated function.

Similar to the history, the callstack is also a linked list of nodes, but there are no provided iterators over the contents of the nodes - instead you can directly iterate over `state.callstack` to get the callstack frames for each of the active frames, in order from most recent to oldest. If you just want the topmost frame, this is `state.callstack`.

- `callstack.func_addr` is the address of the function currently being executed
- `callstack.call_site_addr` is the address of the basic block which called the current function
- `callstack.stack_ptr` is the value of the stack pointer from the beginning of the current function
- `callstack.ret_addr` is the location that the current function will return to if it returns

3.4.7 More about I/O: Files, file systems, and network sockets

Please refer to *Working with File System, Sockets, and Pipes* for a more complete and detailed documentation of how I/O is modeled in angr.

3.4.8 Copying and Merging

A state supports very fast copies, so that you can explore different possibilities:

```
>>> proj = angr.Project('/bin/true')
>>> s = proj.factory.blank_state()
>>> s1 = s.copy()
>>> s2 = s.copy()

>>> s1.mem[0x1000].uint32_t = 0x41414141
>>> s2.mem[0x1000].uint32_t = 0x42424242
```

States can also be merged together.

```
# merge will return a tuple. the first element is the merged state
# the second element is a symbolic variable describing a state flag
# the third element is a boolean describing whether any merging was done
>>> (s_merged, m, anything_merged) = s1.merge(s2)

# this is now an expression that can resolve to "AAAA" *or* "BBBB"
>>> aaaa_or_bbbb = s_merged.mem[0x1000].uint32_t
```

Todo: describe limitations of merging

3.5 Simulation Managers

The most important control interface in angr is the `SimulationManager`, which allows you to control symbolic execution over groups of states simultaneously, applying search strategies to explore a program's state space. Here, you'll learn how to use it.

Simulation managers let you wrangle multiple states in a slick way. States are organized into “stashes”, which you can step forward, filter, merge, and move around as you wish. This allows you to, for example, step two different stashes of states at different rates, then merge them together. The default stash for most operations is the `active` stash, which is where your states get put when you initialize a new simulation manager.

3.5.1 Stepping

The most basic capability of a simulation manager is to step forward all states in a given stash by one basic block. You do this with `.step()`.

```
>>> import angr
>>> proj = angr.Project('examples/fauxware/fauxware', auto_load_libs=False)
>>> state = proj.factory.entry_state()
>>> simgr = proj.factory.simgr(state)
>>> simgr.active
[<SimState @ 0x400580>]

>>> simgr.step()
>>> simgr.active
[<SimState @ 0x400540>]
```

Of course, the real power of the stash model is that when a state encounters a symbolic branch condition, both of the successor states appear in the stash, and you can step both of them in sync. When you don't really care about controlling analysis very carefully and you just want to step until there's nothing left to step, you can just use the `.run()` method.

```
# Step until the first symbolic branch
>>> while len(simgr.active) == 1:
...     simgr.step()

>>> simgr
<SimulationManager with 2 active>
>>> simgr.active
[<SimState @ 0x400692>, <SimState @ 0x400699>]

# Step until everything terminates
>>> simgr.run()
>>> simgr
<SimulationManager with 3 deadended>
```

We now have 3 deadended states! When a state fails to produce any successors during execution, for example, because it reached an `exit` syscall, it is removed from the active stash and placed in the deadended stash.

3.5.2 Stash Management

Let's see how to work with other stashes.

To move states between stashes, use `.move()`, which takes `from_stash`, `to_stash`, and `filter_func` (optional, default is to move everything). For example, let's move everything that has a certain string in its output:

```
>>> simgr.move(from_stash='deadended', to_stash='authenticated', filter_func=lambda s: b
↳ 'Welcome' in s.posix.dumps(1))
>>> simgr
<SimulationManager with 2 authenticated, 1 deadended>
```

We were able to just create a new stash named “authenticated” just by asking for states to be moved to it. All the states in this stash have “Welcome” in their stdout, which is a fine metric for now.

Each stash is just a list, and you can index into or iterate over the list to access each of the individual states, but there are some alternate methods to access the states too. If you prepend the name of a stash with `one_`, you will be given

the first state in the stash. If you prepend the name of a stash with `mp_`, you will be given a `multiplexed` version of the stash.

```
>>> for s in simgr.deadended + simgr.authenticated:
...     print(hex(s.addr))
0x10000030
0x10000078
0x10000078

>>> simgr.one_deadended
<SimState @ 0x10000030>
>>> simgr.mp_authenticated
MP([<SimState @ 0x10000078>, <SimState @ 0x10000078>])
>>> simgr.mp_authenticated.posix.dumps(0)
MP(['\x00\x00\x00\x00\x00\x00\x00\x00SOSNEAKY\x00',
    '\x00\x00\x00\x00\x00\x00\x00\x00S\x80\x80\x80\x80@\x80@\x00'])
```

Of course, `step`, `run`, and any other method that operates on a single stash of paths can take a `stash` argument, specifying which stash to operate on.

There are lots of fun tools that the simulation manager provides you for managing your stashes. We won't go into the rest of them for now, but you should check out the API documentation. TODO: link

Stash types

You can use stashes for whatever you like, but there are a few stashes that will be used to categorize some special kinds of states. These are:

Stash	Description
active	This stash contains the states that will be stepped by default, unless an alternate stash is specified.
deadended	A state goes to the deadended stash when it cannot continue the execution for some reason, including no more valid instructions, unsat state of all of its successors, or an invalid instruction pointer.
pruned	When using <code>LAZY_SOLVES</code> , states are not checked for satisfiability unless absolutely necessary. When a state is found to be unsat in the presence of <code>LAZY_SOLVES</code> , the state hierarchy is traversed to identify when, in its history, it initially became unsat. All states that are descendants of that point (which will also be unsat, since a state cannot become un-unsat) are pruned and put in this stash.
unconstrained	If the <code>save_unconstrained</code> option is provided to the <code>SimulationManager</code> constructor, states that are determined to be unconstrained (i.e., with the instruction pointer controlled by user data or some other source of symbolic data) are placed here.
unsat	If the <code>save_unsat</code> option is provided to the <code>SimulationManager</code> constructor, states that are determined to be unsatisfiable (i.e., they have constraints that are contradictory, like the input having to be both "AAAA" and "BBBB" at the same time) are placed here.

There is another list of states that is not a stash: `errored`. If, during execution, an error is raised, then the state will be wrapped in an `ErrorRecord` object, which contains the state and the error it raised, and then the record will be inserted into `errored`. You can get at the state as it was at the beginning of the execution tick that caused the error with `record.state`, you can see the error that was raised with `record.error`, and you can launch a debug shell at the site of the error with `record.debug()`. This is an invaluable debugging tool!

3.5.3 Simple Exploration

An extremely common operation in symbolic execution is to find a state that reaches a certain address, while discarding all states that go through another address. Simulation manager has a shortcut for this pattern, the `.explore()` method.

When launching `.explore()` with a `find` argument, execution will run until a state is found that matches the `find` condition, which can be the address of an instruction to stop at, a list of addresses to stop at, or a function which takes a state and returns whether it meets some criteria. When any of the states in the active stash match the `find` condition, they are placed in the `found` stash, and execution terminates. You can then explore the found state, or decide to discard it and continue with the other ones. You can also specify an `avoid` condition in the same format as `find`. When a state matches the `avoid` condition, it is put in the `avoided` stash, and execution continues. Finally, the `num_find` argument controls the number of states that should be found before returning, with a default of 1. Of course, if you run out of states in the active stash before finding this many solutions, execution will stop anyway.

Let's look at a simple crackme *example* [example <./examples.md#reverseme-modern-binary-exploitation—csci-4968>](https://github.com/angr/examples/blob/master/reverseme-modern-binary-exploitation-csci-4968.py):

First, we load the binary.

```
>>> proj = angr.Project('examples/CSCI-4968-MBE/challenges/crackme0x00a/crackme0x00a')
```

Next, we create a `SimulationManager`.

```
>>> simgr = proj.factory.simgr()
```

Now, we symbolically execute until we find a state that matches our condition (i.e., the “win” condition).

```
>>> simgr.explore(find=lambda s: b"Congrats" in s.posix.dumps(1))
<SimulationManager with 1 active, 1 found>
```

Now, we can get the flag out of that state!

```
>>> s = simgr.found[0]
>>> print(s.posix.dumps(1))
Enter password: Congrats!

>>> flag = s.posix.dumps(0)
>>> print(flag)
g00dJ0B!
```

Pretty simple, isn't it?

Other examples can be found by browsing the *examples*.

Exploration Techniques

angr ships with several pieces of canned functionality that let you customize the behavior of a simulation manager, called *exploration techniques*. The archetypical example of why you would want an exploration technique is to modify the pattern in which the state space of the program is explored - the default “step everything at once” strategy is effectively breadth-first search, but with an exploration technique you could implement, for example, depth-first search. However, the instrumentation power of these techniques is much more flexible than that - you can totally alter the behavior of angr's stepping process. Writing your own exploration techniques will be covered in a later chapter.

To use an exploration technique, call `simgr.use_technique(tech)`, where `tech` is an instance of an `ExplorationTechnique` subclass. angr's built-in exploration techniques can be found under `angr.exploration_techniques`.

Here's a quick overview of some of the built-in ones:

- *DFS*: Depth first search, as mentioned earlier. Keeps only one state active at once, putting the rest in the deferred stash until it deadends or errors.
- *Explorer*: This technique implements the `.explore()` functionality, allowing you to search for and avoid addresses.
- *LengthLimiter*: Puts a cap on the maximum length of the path a state goes through.
- *LoopSeer*: Uses a reasonable approximation of loop counting to discard states that appear to be going through a loop too many times, putting them in a `spinning` stash and pulling them out again if we run out of otherwise viable states.
- *ManualMergepoint*: Marks an address in the program as a merge point, so states that reach that address will be briefly held, and any other states that reach that same point within a timeout will be merged together.
- *MemoryWatcher*: Monitors how much memory is free/available on the system between simgr steps and stops exploration if it gets too low.
- *Oppologist*: The “operation apologist” is an especially fun gadget - if this technique is enabled and angr encounters an unsupported instruction, for example a bizarre and foreign floating point SIMD op, it will concretize all the inputs to that instruction and emulate the single instruction using the unicorn engine, allowing execution to continue.
- *Spiller*: When there are too many states active, this technique can dump some of them to disk in order to keep memory consumption low.
- *Threading*: Adds thread-level parallelism to the stepping process. This doesn’t help much because of Python’s global interpreter locks, but if you have a program whose analysis spends a lot of time in angr’s native-code dependencies (unicorn, z3, libvex) you can seem some gains.
- *Tracer*: An exploration technique that causes execution to follow a dynamic trace recorded from some other source. The [dynamic tracer repository](#) has some tools to generate those traces.
- *Veritesting*: An implementation of a [CMU paper](#) on automatically identifying useful merge points. This is so useful, you can enable it automatically with `veritesting=True` in the `SimulationManager` constructor! Note that it frequently doesn’t play nice with other techniques due to the invasive way it implements static symbolic execution.

Look at the API documentation for the [SimulationManager](#) and [ExplorationTechnique](#) classes for more information.

3.6 Simulation and Instrumentation

When you ask for a step of execution to happen in angr, something has to actually perform the step. angr uses a series of engines (subclasses of the `SimEngine` class) to emulate the effects that of a given section of code has on an input state. The execution core of angr simply tries all the available engines in sequence, taking the first one that is able to handle the step. The following is the default list of engines, in order:

- The failure engine kicks in when the previous step took us to some uncontinuable state
- The syscall engine kicks in when the previous step ended in a syscall
- The hook engine kicks in when the current address is hooked
- The unicorn engine kicks in when the UNICORN state option is enabled and there is no symbolic data in the state
- The VEX engine kicks in as the final fallback.

3.6.1 SimSuccessors

The code that actually tries all the engines in turn is `project.factory.successors(state, **kwargs)`, which passes its arguments onto each of the engines. This function is at the heart of `state.step()` and `simulation_manager.step()`. It returns a `SimSuccessors` object, which we discussed briefly before. The purpose of `SimSuccessors` is to perform a simple categorization of the successor states, stored in various list attributes. They are:

Attribution	Guard Condition	Instruction Pointer	Description
succ	True (can be symbolic, but constrained to True)	Can be symbolic (but 256 solutions or less; see <code>unconst</code>)	A normal, satisfiable successor state to the state processed by the engine. The instruction pointer of this state may be symbolic (i.e., a computed jump based on user input), so the state might actually represent <i>several</i> potential continuations of execution going forward.
unsa	False (can be symbolic, but constrained to False)	Can be symbolic.	Unsatisfiable successors. These are successors whose guard conditions can only be false (i.e., jumps that cannot be taken, or the default branch of jumps that <i>must</i> be taken).
flat	True (can be symbolic, but constrained to True).	Concrete value.	As noted above, states in the <code>successors</code> list can have symbolic instruction pointers. This is rather confusing, as elsewhere in the code (i.e., in <code>SimEngineVEX.process</code> , when it's time to step that state forward), we make assumptions that a single program state only represents the execution of a single spot in the code. To alleviate this, when we encounter states in <code>successors</code> with symbolic instruction pointers, we compute all possible concrete solutions (up to an arbitrary threshold of 256) for them, and make a copy of the state for each such solution. We call this process "flattening". These <code>flat_successors</code> are states, each of which has a different, concrete instruction pointer. For example, if the instruction pointer of a state in <code>successors</code> was <code>X+5</code> , where <code>X</code> had constraints of <code>X > 0x800000</code> and <code>X <= 0x800010</code> , we would flatten it into 16 different <code>flat_successors</code> states, one with an instruction pointer of <code>0x800006</code> , one with <code>0x800007</code> , and so on until <code>0x800015</code> .
unco	True (can be symbolic, but constrained to True).	Symbolic (with more than 256 solutions).	During the flattening procedure described above, if it turns out that there are more than 256 possible solutions for the instruction pointer, we assume that the instruction pointer has been overwritten with unconstrained data (i.e., a stack overflow with user data). <i>This assumption is not sound in general.</i> Such states are placed in <code>unconstrained_successors</code> and not in <code>successors</code> .
all_	Anything	Can be symbolic.	This is <code>successors</code> + <code>unsa_successors</code> + <code>unconstrained_successors</code> .

3.6.2 Breakpoints

Todo: rewrite this to fix the narrative

Like any decent execution engine, angr supports breakpoints. This is pretty cool! A point is set as follows:

```
>>> import angr
>>> b = angr.Project('examples/fauxware/fauxware')

# get our state
>>> s = b.factory.entry_state()

# add a breakpoint. This breakpoint will drop into ipdb right before a memory write_
↳ happens.
>>> s.inspect.b('mem_write')

# on the other hand, we can have a breakpoint trigger right *after* a memory write_
↳ happens.
# we can also have a callback function run instead of opening ipdb.
>>> def debug_func(state):
...     print("State %s is about to do a memory write!")

>>> s.inspect.b('mem_write', when=angr.BP_AFTER, action=debug_func)

# or, you can have it drop you in an embedded IPython!
>>> s.inspect.b('mem_write', when=angr.BP_AFTER, action=angr.BP_IPYTHON)
```

There are many other places to break than a memory write. Here is the list. You can break at BP_BEFORE or BP_AFTER for each of these events.

Event type	Event meaning
mem_read	Memory is being read.
mem_write	Memory is being written.
address_concretization	A symbolic memory access is being resolved.
reg_read	A register is being read.
reg_write	A register is being written.
tmp_read	A temp is being read.
tmp_write	A temp is being written.
expr	An expression is being created (i.e., a result of an arithmetic operation or a constant in the IR).
statement	An IR statement is being translated.
instruction	A new (native) instruction is being translated.
irsb	A new basic block is being translated.
constraints	New constraints are being added to the state.
exit	A successor is being generated from execution.
fork	A symbolic execution state has forked into multiple states.
symbolic_variable	A new symbolic variable is being created.
call	A call instruction is hit.
return	A ret instruction is hit.
simprocedure	A simprocedure (or syscall) is executed.
dirty	A dirty IR callback is executed.
syscall	A syscall is executed (called in addition to the simprocedure event).
engine_process	A SimEngine is about to process some code.

These events expose different attributes:

Event type	Attribute name	Attribute availability	Attribute meaning
mem_read	mem_read_address	BP_BEFORE or BP_AFTER	The address at which memory is read.
mem_read	mem_read_expr	BP_AFTER	The expression at that address.
mem_read	mem_read_length	BP_BEFORE or BP_AFTER	The length of the memory read.
mem_read	mem_read_condition	BP_BEFORE or BP_AFTER	The condition of the memory read.
mem_write	mem_write_address	BP_BEFORE or BP_AFTER	The address at which memory is written.
mem_write	mem_write_length	BP_BEFORE or BP_AFTER	The length of the memory write.
mem_write	mem_write_expr	BP_BEFORE or BP_AFTER	The expression that is being written.
mem_write	mem_write_condition	BP_BEFORE or BP_AFTER	The condition of the memory write.
reg_read	reg_read_offset	BP_BEFORE or BP_AFTER	The offset of the register being read.
reg_read	reg_read_length	BP_BEFORE or BP_AFTER	The length of the register read.
reg_read	reg_read_expr	BP_AFTER	The expression in the register.
reg_read	reg_read_condition	BP_BEFORE or BP_AFTER	The condition of the register read.
reg_write	reg_write_offset	BP_BEFORE or BP_AFTER	The offset of the register being written.
reg_write	reg_write_length	BP_BEFORE or BP_AFTER	The length of the register write.
reg_write	reg_write_expr	BP_BEFORE or BP_AFTER	The expression that is being written.
reg_write	reg_write_condition	BP_BEFORE or BP_AFTER	The condition of the register write.
tmp_read	tmp_read_num	BP_BEFORE or BP_AFTER	The number of the temp being read.
tmp_read	tmp_read_expr	BP_AFTER	The expression of the temp.
tmp_write	tmp_write_num	BP_BEFORE or BP_AFTER	The number of the temp written.
tmp_write	tmp_write_expr	BP_AFTER	The expression written to the temp.
expr	expr	BP_BEFORE or BP_AFTER	The IR expression.
expr	expr_result	BP_AFTER	The value (e.g. AST) which the expression evaluates to.

Event type	Attribute name	Attribute availability	Attribute meaning
statement	statement	BP_BEFORE or BP_AFTER	The index of the IR statement (in
instruction	instruction	BP_BEFORE or BP_AFTER	The address of the native instruct
irsb	address	BP_BEFORE or BP_AFTER	The address of the basic block.
constraints	added_constraints	BP_BEFORE or BP_AFTER	The list of constraint expressions
call	function_address	BP_BEFORE or BP_AFTER	The name of the function being c
exit	exit_target	BP_BEFORE or BP_AFTER	The expression representing the t
exit	exit_guard	BP_BEFORE or BP_AFTER	The expression representing the g
exit	exit_jumpkind	BP_BEFORE or BP_AFTER	The expression representing the l
symbolic_variable	symbolic_name	BP_AFTER	The name of the symbolic variab
symbolic_variable	symbolic_size	BP_AFTER	The size of the symbolic variable
symbolic_variable	symbolic_expr	BP_AFTER	The expression representing the m
address_concretization	address_concretization_strategy	BP_BEFORE or BP_AFTER	The SimConcretizationStrategy b
address_concretization	address_concretization_action	BP_BEFORE or BP_AFTER	The SimAction object being used
address_concretization	address_concretization_memory	BP_BEFORE or BP_AFTER	The SimMemory object on which
address_concretization	address_concretization_expr	BP_BEFORE or BP_AFTER	The AST representing the memo
address_concretization	address_concretization_add_constraints	BP_BEFORE or BP_AFTER	Whether or not constraints shoul
address_concretization	address_concretization_result	BP_AFTER	The list of resolved memory add
syscall	syscall_name	BP_BEFORE or BP_AFTER	The name of the system call.
simprocedure	simprocedure_name	BP_BEFORE or BP_AFTER	The name of the simprocedure.
simprocedure	simprocedure_addr	BP_BEFORE or BP_AFTER	The address of the simprocedure.
simprocedure	simprocedure_result	BP_AFTER	The return value of the simproce
simprocedure	simprocedure	BP_BEFORE or BP_AFTER	The actual SimProcedure object.
dirty	dirty_name	BP_BEFORE or BP_AFTER	The name of the dirty call.
dirty	dirty_handler	BP_BEFORE	The function that will be run to h
dirty	dirty_args	BP_BEFORE or BP_AFTER	The address of the dirty.
dirty	dirty_result	BP_AFTER	The return value of the dirty call.
engine_process	sim_engine	BP_BEFORE or BP_AFTER	The SimEngine that is processing
engine_process	successors	BP_BEFORE or BP_AFTER	The SimSuccessors object defini

These attributes can be accessed as members of `state.inspect` during the appropriate breakpoint callback to access the appropriate values. You can even modify these value to modify further uses of the values!

```
>>> def track_reads(state):
...     print('Read', state.inspect.mem_read_expr, 'from', state.inspect.mem_read_
↳ address)
...
>>> s.inspect.b('mem_read', when=angr.BP_AFTER, action=track_reads)
```

Additionally, each of these properties can be used as a keyword argument to `inspect.b` to make the breakpoint conditional:

```
# This will break before a memory write if 0x1000 is a possible value of its target.
↳ expression
>>> s.inspect.b('mem_write', mem_write_address=0x1000)

# This will break before a memory write if 0x1000 is the *only* value of its target.
↳ expression
>>> s.inspect.b('mem_write', mem_write_address=0x1000, mem_write_address_unique=True)

# This will break after instruction 0x8000, but only 0x1000 is a possible value of the.
↳ last expression that was read from memory
```

(continues on next page)

(continued from previous page)

```
>>> s.inspect.b('instruction', when=angr.BP_AFTER, instruction=0x8000, mem_read_  
↳expr=0x1000)
```

Cool stuff! In fact, we can even specify a function as a condition:

```
# this is a complex condition that could do anything! In this case, it makes sure that_  
↳RAX is 0x41414141 and  
# that the basic block starting at 0x8004 was executed sometime in this path's history  
>>> def cond(state):  
...     return state.eval(state.regs.rax, cast_to=str) == 'AAAA' and 0x8004 in state.  
↳inspect.backtrace  
  
>>> s.inspect.b('mem_write', condition=cond)
```

That is some cool stuff!

Caution about `mem_read` breakpoint

The `mem_read` breakpoint gets triggered anytime there are memory reads by either the executing program or the binary analysis. If you are using breakpoint on `mem_read` and also using `state.mem` to load data from memory addresses, then know that the breakpoint will be fired as you are technically reading memory.

So if you want to load data from memory and not trigger any `mem_read` breakpoint you have had set up, then use `state.memory.load` with the keyword arguments `disable_actions=True` and `inspect=False`.

This is also true for `state.find` and you can use the same keyword arguments to prevent `mem_read` breakpoints from firing.

3.7 Analyses

angr's goal is to make it easy to carry out useful analyses on binary programs. To this end, angr allows you to package analysis code in a common format that can be easily applied to any project. We will cover writing your own analyses *Writing Analyses*, but the idea is that all the analyses appear under `project.analyses` (for example, `project.analyses.CFGFast()`) and can be called as functions, returning analysis result instances.

3.7.1 Built-in Analyses

Name	Description
CFGFast	Constructs a fast <i>Control Flow Graph</i> of the program
CFGEmulated	Constructs an accurate <i>Control Flow Graph</i> of the program
VFG	Performs VSA on every function of the program, creating a <i>Value Flow Graph</i> and detecting stack variables
DDG	Calculates a <i>Data Dependency Graph</i> , allowing one to determine what statements a given value depends on
Backward-Slice	Computes a <i>Backward Slice</i> of a program with respect to a certain target
Identifier	Identifies common library functions in CGC binaries
More!	angr has quite a few analyses, most of which work! If you'd like to know how to use one, please submit an issue requesting documentation.

3.7.2 Resilience

Analyses can be written to be resilient, and catch and log basically any error. These errors, depending on how they're caught, are logged to the `errors` or `named_errors` attribute of the analysis. However, you might want to run an analysis in "fail fast" mode, so that errors are not handled. To do this, the argument `fail_fast=True` can be passed into the analysis constructor.

3.8 Symbolic Execution

Symbolic execution allows at a time in emulation to determine for a branch all conditions necessary to take a branch or not. Every variable is represented as a symbolic value, and each branch as a constraint. Thus, symbolic execution allows us to see which conditions allows the program to go from a point A to a point B, by resolving the constraints.

If you've read this far, you can see how the components of angr work together to make this possible. Read on to learn about how to make the leap from tools to results.

Todo: A real introduction to the concept of symbolic execution.

3.9 A final word of advice

Congratulations! If you've read this far through the book (editor's note: this comment only really applies when we've actually finished writing all the TODOs so far) then you've been introduced to all the fundamental components of angr necessary to get started with binary analysis.

Ultimately, angr is just an emulator. It is a highly instrumentable and very unique emulator with lots of considerations for environment, true, but at its core, the work you do with angr is about extracting knowledge about how a bunch of bytecode behaves on a CPU. In designing angr, we've tried to provide you with the tools and abstractions on top of this emulator to make certain common tasks more useful, but there's no problem you can't solve just by working with a `SimState` and observing the affects of `.step()`.

As you read further into this book, we'll describe more technical subjects and how to tune angr's behavior for complicated scenarios. This knowledge should inform your use of angr so you can take the quickest path to a solution to any

given problem, but ultimately, you will want to solve problems by exercising creativity with the tools at your disposal. If you can take a problem and wrangle it into a form where it has defined and tractable inputs and outputs, you can absolutely use angr to achieve your goals, given that these goals involve analyzing binaries. None of the abstractions or instrumentations we provide are the end-all of how to use angr for a given task - angr is designed so it can be used in as integrated or as ad-hoc of a manner as you desire. If you see a path from problem to solution, take it.

Of course, it's very difficult to become well-acquainted with such a huge piece of technology as angr. To this end you can absolutely lean on the community (through the [angr slack](#) is the best option) to discuss angr and solving problems with it.

Good luck!

BUILD-IN ANALYSES

4.1 Control-flow Graph Recovery (CFG)

angr includes analyses to recover the control-flow graph of a binary program. This also includes recovery of function boundaries, as well as reasoning about indirect jumps and other useful metadata.

4.1.1 General ideas

A basic analysis that one might carry out on a binary is a Control Flow Graph. A CFG is a graph with (conceptually) basic blocks as nodes and jumps/calls/rets/etc as edges.

In angr, there are two types of CFG that can be generated: a static CFG (CFGFast) and a dynamic CFG (CFGEmulated).

CFGFast uses static analysis to generate a CFG. It is significantly faster, but is theoretically bounded by the fact that some control-flow transitions can only be resolved at execution-time. This is the same sort of CFG analysis performed by other popular reverse-engineering tools, and its results are comparable with their output.

CFGEmulated uses symbolic execution to capture the CFG. While it is theoretically more accurate, it is dramatically slower. It is also typically less complete, due to issues with the accuracy of emulation (system calls, missing hardware features, and so on)

If you are unsure which CFG to use, or are having problems with CFGEmulated, try CFGFast first.

A CFG can be constructed by doing:

```
>>> import angr
# load your project
>>> p = angr.Project('/bin/true', load_options={'auto_load_libs': False})

# Generate a static CFG
>>> cfg = p.analyses.CFGFast()

# generate a dynamic CFG
>>> cfg = p.analyses.CFGEmulated(keep_state=True)
```

4.1.2 Using the CFG

The CFG, at its core, is a [NetworkX](#) di-graph. This means that all of the normal NetworkX APIs are available:

```
>>> print("This is the graph:", cfg.graph)
>>> print("It has %d nodes and %d edges" % (len(cfg.graph.nodes()), len(cfg.graph.
↳ edges())))
```

The nodes of the CFG graph are instances of class `CFGNode`. Due to context sensitivity, a given basic block can have multiple nodes in the graph (for multiple contexts).

```
# this grabs *any* node at a given location:
>>> entry_node = cfg.get_any_node(p.entry)

# on the other hand, this grabs all of the nodes
>>> print("There were %d contexts for the entry block" % len(cfg.get_all_nodes(p.entry)))

# we can also look up predecessors and successors
>>> print("Predecessors of the entry point:", entry_node.predecessors)
>>> print("Successors of the entry point:", entry_node.successors)
>>> print("Successors (and type of jump) of the entry point:", [ jumpkind + " to " +
↳ str(node.addr) for node, jumpkind in cfg.get_successors_and_jumpkind(entry_node) ])
```

Viewing the CFG

Control-flow graph rendering is a hard problem. angr does not provide any built-in mechanism for rendering the output of a CFG analysis, and attempting to use a traditional graph rendering library, like matplotlib, will result in an unusable image.

One solution for viewing angr CFGs is found in [axt's angr-utils repository](#).

4.1.3 Shared Libraries

The CFG analysis does not distinguish between code from different binary objects. This means that by default, it will try to analyze control flow through loaded shared libraries. This is almost never intended behavior, since this will extend the analysis time to several days, probably. To load a binary without shared libraries, add the following keyword argument to the `Project` constructor: `load_options={'auto_load_libs': False}`

4.1.4 Function Manager

The CFG result produces an object called the *Function Manager*, accessible through `cfg.kb.functions`. The most common use case for this object is to access it like a dictionary. It maps addresses to `Function` objects, which can tell you properties about a function.

```
>>> entry_func = cfg.kb.functions[p.entry]
```

Functions have several important properties!

- `entry_func.block_addrs` is a set of addresses at which basic blocks belonging to the function begin.
- `entry_func.blocks` is the set of basic blocks belonging to the function, that you can explore and disassemble using capstone.

- `entry_func.string_references()` returns a list of all the constant strings that were referred to at any point in the function. They are formatted as `(addr, string)` tuples, where `addr` is the address in the binary's data section the string lives, and `string` is a Python string that contains the value of the string.
- `entry_func.returns` is a boolean value signifying whether or not the function can return. `False` indicates that all paths do not return.
- `entry_func.callable` is an `angr Callable` object referring to this function. You can call it like a Python function with Python arguments and get back an actual result (may be symbolic) as if you ran the function with those arguments!
- `entry_func.transition_graph` is a `NetworkX DiGraph` describing control flow within the function itself. It resembles the control-flow graphs IDA displays on a per-function level.
- `entry_func.name` is the name of the function.
- `entry_func.has_unresolved_calls` and `entry.has_unresolved_jumps` have to do with detecting imprecision within the CFG. Sometimes, the analysis cannot detect what the possible target of an indirect call or jump could be. If this occurs within a function, that function will have the appropriate `has_unresolved_*` value set to `True`.
- `entry_func.get_call_sites()` returns a list of all the addresses of basic blocks which end in calls out to other functions.
- `entry_func.get_call_target(callsite_addr)` will, given `callsite_addr` from the list of call site addresses, return where that callsite will call out to.
- `entry_func.get_call_return(callsite_addr)` will, given `callsite_addr` from the list of call site addresses, return where that callsite should return to.

and many more !

4.1.5 CFGFast details

CFGFast performs a static control-flow and function recovery. Starting with the entry point (or any user-defined points) roughly the following procedure is performed:

- 1) The basic block is lifted to VEX IR, and all its exits (jumps, calls, returns, or continuation to the next block) are collected
- 2) For each exit, if this exit is a constant address, we add an edge to the CFG of the correct type, and add the destination block to the set of blocks to be analyzed.
- 3) In the event of a function call, the destination block is also considered the start of a new function. If the target function is known to return, the block after the call is also analyzed.
- 4) In the event of a return, the current function is marked as returning, and the appropriate edges in the callgraph and CFG are updated.
- 5) For all indirect jumps (block exits with a non-constant destination) Indirect Jump Resolution is performed.

Finding function starts

CFGFast supports multiple ways of deciding where a function starts and ends.

First the binary’s main entry point will be analyzed. For binaries with symbols (e.g., non-stripped ELF and PE binaries) all function symbols will be used as possible starting points. For binaries without symbols, such as stripped binaries, or binaries loaded using the blob loader backend, CFG will scan the binary for a set of function prologues defined for the binary’s architecture. Finally, by default, the binary’s entire code section will be scanned for executable contents, regardless of prologues or symbols.

In addition to these, as with CFGEmlated, function starts will also be considered when they are the target of a “call” instruction on the given architecture.

All of these options can be disabled

FakeRets and function returns

When a function call is observed, we first assume that the callee function eventually returns, and treat the block after it as part of the caller function. This inferred control-flow edge is known as a “FakeRet”. If, in analyzing the callee, we find this not to be true, we update the CFG, removing this “FakeRet”, and updating the callgraph and function blocks accordingly. As such, the CFG is recovered *twice*. In doing this, the set of blocks in each function, and whether the function returns, can be recovered and propagated directly.

Indirect Jump Resolution

Options

These are the most useful options when working with CFGFast:

Option	Description
<code>force_complete_</code>	(Default: True) Treat the entire binary as code for the purposes of function detection. If you have a blob (e.g., mixed code and data) <i>you want to turn this off</i> .
<code>func- tion_starts</code>	A list of addresses, to use as entry points into the analysis.
<code>normalize</code>	(Default: False) Normalize the resulting functions (e.g., each basic block belongs to at most one function, back-edges point to the start of basic blocks)
<code>re- solve_indirect_j more!</code>	(Default: True) Perform additional analysis to attempt to find targets for every indirect jump found during CFG creation. Examine the docstring on <code>p.analyses.CFGFast</code> for more up-to-date options

4.1.6 CFGEmlated details

Options

The most common options for CFGEmlated include:

Option	Description
con- text_sensitivity_level	This sets the context sensitivity level of the analysis. See the context sensitivity level section below for more information. This is 1 by default.
starts	A list of addresses, to use as entry points into the analysis.
avoid_runs	A list of addresses to ignore in the analysis.
call_depth	Limit the depth of the analysis to some number calls. This is useful for checking which functions a specific function can directly jump to (by setting <code>call_depth</code> to 1).
initial_state	An initial state can be provided to the CFG, which it will use throughout its analysis.
keep_state	To save memory, the state at each basic block is discarded by default. If <code>keep_state</code> is True, the state is saved in the CFGNode.
en- able_symbolic_back_	Whether to enable an intensive technique for resolving indirect jumps
en- able_advanced_back	Whether to enable another intensive technique for resolving direct jumps
more!	Examine the docstring on <code>p.analyses.CFGEmlated</code> for more up-to-date options

Context Sensitivity Level

angr constructs a CFG by executing every basic block and seeing where it goes. This introduces some challenges: a basic block can act differently in different *contexts*. For example, if a block ends in a function return, the target of that return will be different, depending on different callers of the function containing that basic block.

The context sensitivity level is, conceptually, the number of such callers to keep on the callstack. To explain this concept, let's look at the following code:

```
void error(char *error)
{
    puts(error);
}

void alpha()
{
    puts("alpha");
    error("alpha!");
}

void beta()
{
    puts("beta");
    error("beta!");
}

void main()
{
    alpha();
    beta();
}
```

The above sample has four call chains: `main>alpha>puts`, `main>alpha>error>puts` and `main>beta>puts`, and `main>beta>error>puts`. While, in this case, angr can probably execute both call chains, this becomes unfeasible for larger binaries. Thus, angr executes the blocks with states limited by the context sensitivity level. That is, each function is re-analyzed for each unique context that it is called in.

For example, the `puts()` function above will be analyzed with the following contexts, given different context sensitivity levels:

Level	Meaning	Contexts
0	Callee-only	<code>puts</code>
1	One caller, plus callee	<code>alpha>puts beta>puts error>puts</code>
2	Two callers, plus callee	<code>alpha>error>puts main>alpha>puts beta>error>puts main>beta>puts</code>
3	Three callers, plus callee	<code>main>alpha>error>puts main>alpha>puts main>beta>error>puts</code> <code>main>beta>puts</code>

The upside of increasing the context sensitivity level is that more information can be gleaned from the CFG. For example, with context sensitivity of 1, the CFG will show that, when called from `alpha`, `puts` returns to `alpha`, when called from `error`, `puts` returns to `error`, and so forth. With context sensitivity of 0, the CFG simply shows that `puts` returns to `alpha`, `beta`, and `error`. This, specifically, is the context sensitivity level used in IDA. The downside of increasing the context sensitivity level is that it exponentially increases the analysis time.

4.2 Backward Slicing

A *program slice* is a subset of statements that is obtained from the original program, usually by removing zero or more statements. Slicing is often helpful in debugging and program understanding. For instance, it's usually easier to locate the source of a variable on a program slice.

A backward slice is constructed from a *target* in the program, and all data flows in this slice end at the *target*.

angr has a built-in analysis, called `BackwardSlice`, to construct a backward program slice. This section will act as a how-to for angr's `BackwardSlice` analysis, and followed by some in-depth discussion over the implementation choices and limitations.

4.2.1 First Step First

To build a `BackwardSlice`, you will need the following information as input.

- **Required** CFG. A control flow graph (CFG) of the program. This CFG must be an accurate CFG (CFGEmulated).
- **Required** Target, which is the final destination that your backward slice terminates at.
- **Optional** CDG. A control dependence graph (CDG) derived from the CFG. angr has a built-in analysis CDG for that purpose.
- **Optional** DDG. A data dependence graph (DDG) built on top of the CFG. angr has a built-in analysis DDG for that purpose.

A `BackwardSlice` can be constructed with the following code:

```
>>> import angr
# Load the project
>>> b = angr.Project("examples/fauxware/fauxware", load_options={"auto_load_libs": False})
↪

# Generate a CFG first. In order to generate data dependence graph afterwards, you'll
↪have to:
```

(continues on next page)

(continued from previous page)

```
# - keep all input states by specifying keep_state=True.
# - store memory, register and temporary values accesses by adding the angr.options.refs_
  ↳ option set.
# Feel free to provide more parameters (for example, context_sensitivity_level) for CFG
# recovery based on your needs.
>>> cfg = b.analyses.CFGEmlated(keep_state=True,
...                               state_add_options=angr.sim_options.refs,
...                               context_sensitivity_level=2)

# Generate the control dependence graph
>>> cdg = b.analyses.CDG(cfg)

# Build the data dependence graph. It might take a while. Be patient!
>>> ddg = b.analyses.DDG(cfg)

# See where we wanna go... let's go to the exit() call, which is modeled as a
# SimProcedure.
>>> target_func = cfg.kb.functions.function(name="exit")
# We need the CFGNode instance
>>> target_node = cfg.get_any_node(target_func.addr)

# Let's get a BackwardSlice out of them!
# ``targets`` is a list of objects, where each one is either a CodeLocation
# object, or a tuple of CFGNode instance and a statement ID. Setting statement
# ID to -1 means the very beginning of that CFGNode. A SimProcedure does not
# have any statement, so you should always specify -1 for it.
>>> bs = b.analyses.BackwardSlice(cfg, cdg=cdg, ddg=ddg, targets=[ (target_node, -1) ])

# Here is our awesome program slice!
>>> print(bs)
```

Sometimes it's difficult to get a data dependence graph, or you may simply want build a program slice on top of a CFG. That's basically why DDG is an optional parameter. You can build a BackwardSlice solely based on CFG by doing:

```
>>> bs = b.analyses.BackwardSlice(cfg, control_flow_slice=True)
BackwardSlice (to [(<CFGNode exit (0x10000a0) [0]>, -1)])
```

4.2.2 Using The BackwardSlice Object

Before you go ahead and use BackwardSlice object, you should notice that the design of this class is fairly arbitrary right now, and it is still subject to change in the near future. We'll try our best to keep this documentation up-to-date.

Members

After construction, a `BackwardSlice` has the following members which describe a program slice:

Member	Mode	Meaning
<code>runs_in_slice</code>	CFG-only	A <code>networkx.DiGraph</code> instance showing addresses of blocks and <code>SimProcedures</code> in the program slice, as well as transitions between them
<code>cfg_nodes_in</code>	CFG-only	A <code>networkx.DiGraph</code> instance showing <code>CFGNodes</code> in the program slice and transitions in between
<code>chosen_statement</code>	With DDG	A dict mapping basic block addresses to lists of statement IDs that are part of the program slice
<code>chosen_exits</code>	With DDG	A dict mapping basic block addresses to a list of “exits”. Each exit in the list is a valid transition in the program slice

Each “exit” in `chosen_exit` is a tuple including a statement ID and a list of target addresses. For example, an “exit” might look like the following:

```
(35, [ 0x400020 ])
```

If the “exit” is the default exit of a basic block, it’ll look like the following:

```
("default", [ 0x400085 ])
```

Export an Annotated Control Flow Graph

User-friendly Representation

Take a look at `BackwardSlice.dbg_repr()`!

4.2.3 Implementation Choices

4.2.4 Limitations

Completeness

Soundness

4.3 Identifier

The identifier uses test cases to identify common library functions in CGC binaries. It prefilters by finding some basic information about stack variables/arguments. The information of about stack variables can be generally useful in other projects.

```
>>> import angr

# get all the matches
>>> p = angr.Project("../binaries/tests/i386/identifiable")
# note analysis is executed via the Identifier call
>>> idfer = p.analyses.Identifier()
```

(continues on next page)

(continued from previous page)

```
>>> for funcInfo in idfer.func_info:
...     print(hex(funcInfo.addr), funcInfo.name)

0x8048e60 memcmp
0x8048ef0 memcpy
0x8048f60 memmove
0x8049030 memset
0x8049320 fdprintf
0x8049a70 sprintf
0x8049f40 strcasecmp
0x804a0f0 strcmp
0x804a190 strcpy
0x804a260 strlen
0x804a3d0 strncmp
0x804a620 strtol
0x804aa00 strtol
0x80485b0 free
0x804aab0 free
0x804aad0 free
0x8048660 malloc
0x80485b0 free
```


4.4 angr Decompiler

4.4.1 Analysis Passes

Name	Description	Sub-analysis
CFG recovery	Recover the control flow graph.	Indirect branch resolving
Indirect branch resolving	Resolve the targets of indirect branches.	Jump table resolving
Removing alignment blocks		
Calling convention recovery		
Stack pointer analysis	Determine values of stack pointer at each instruction.	
IR Lifting	Lift the original representation to AIL, block by block.	
AIL graph building		
Rewriting single-target indirect branches	Replace single-target indirect branches with direct branches.	
Making return statements	Convert Ijk_Ret jump kinds into AIL Return statements.	
Simplifying AIL blocks	Simplify each AIL block.	Constant folding, copy propagation, dead assignment elimination, peephole optimizations
Reaching definition analysis		
Constant folding		
Copy propagation		
Dead assignment elimination		
Peephole optimizations		
Simplifying AIL function	Simplify the entire AIL function.	Assignment expression folding, unifying local variables, call expression folding, reaching definition analysis
Assignment expression folding	Eliminate variables that are assigned to once and used once.	Copy propagation
Unifying local variables	Find local variables that are always equivalent and eliminate redundant copies.	Copy propagation
Call expression folding	Fold call expressions into the variable where its return value is stored.	Copy propagation
Call site building	Apply calling conventions to each call site and rewrite call statements to ones with arguments	Reaching definition analysis
Variable recovery	Identify local and global variables.	
Variable type inference	Collect type constraints and infer variable types.	
Simplification passes		
Region identification	Identify single-entry, single-exit regions.	
Structure analysis	Structure each identified region to create high-level control flow structures.	

ADVANCED TOPICS

5.1 Gotchas when using angr

This section contains a list of gotchas that users/victims of angr frequently run into.

5.1.1 SimProcedure inaccuracy

To make symbolic execution more tractable, angr replaces common library functions with summaries written in Python. We call these summaries SimProcedures. SimProcedures allow us to mitigate path explosion that would otherwise be introduced by, for example, `strlen` running on a symbolic string.

Unfortunately, our SimProcedures are far from perfect. If angr is displaying unexpected behavior, it might be caused by a buggy/incomplete SimProcedure. There are several things that you can do:

1. Disable the SimProcedure (you can exclude specific SimProcedures by passing options to the [*angr.Project*](#) class. This has the drawback of likely leading to a path explosion, unless you are very careful about constraining the input to the function in question. The path explosion can be partially mitigated with other angr capabilities (such as Veritesting).
2. Replace the SimProcedure with something written directly to the situation in question. For example, our `scanf` implementation is not complete, but if you just need to support a single, known format string, you can write a hook to do exactly that.
3. Fix the SimProcedure.

5.1.2 Unsupported syscalls

System calls are also implemented as SimProcedures. Unfortunately, there are system calls that we have not yet implemented in angr. There are several workarounds for an unsupported system call:

1. Implement the system call.

Todo: document this process

2. Hook the callsite of the system call (using `project.hook`) to make the required modifications to the state in an ad-hoc way.
3. Use the `state.posix.queued_syscall_returns` list to queue syscall return values. If a return value is queued, the system call will not be executed, and the value will be used instead. Furthermore, a function can be queued instead as the “return value”, which will result in that function being applied to the state when the system call is triggered.

5.1.3 Symbolic memory model

The default memory model used by angr is inspired by [Mayhem](#). This memory model supports limited symbolic reads and writes. If the memory index of a read is symbolic and the range of possible values of this index is too wide, the index is concretized to a single value. If the memory index of a write is symbolic at all, the index is concretized to a single value. This is configurable by changing the memory concretization strategies of `state.memory`.

5.1.4 Symbolic lengths

SimProcedures, and especially system calls such as `read()` and `write()` might run into a situation where the *length* of a buffer is symbolic. In general, this is handled very poorly: in many cases, this length will end up being concretized outright or retroactively concretized in later steps of execution. Even in cases when it is not, the source or destination file might end up looking a bit “weird”.

5.1.5 Division by Zero

Z3 has some issues with divisions by zero. For example:

```
>>> z = z3.Solver()
>>> a = z3.BitVec('a', 32)
>>> b = z3.BitVec('b', 32)
>>> c = z3.BitVec('c', 32)
>>> z.add(a/b == c)
>>> z.add(b == 0)
>>> z.check()
>>> print(z.model().eval(b), z.model().eval(a/b))
0 4294967295
```

This makes it very difficult to handle certain situations in Claripy. We post-process the VEX IR itself to explicitly check for zero-divisions and create IRSB side-exits corresponding to the exceptional case, but SimProcedures and custom analysis code may let occurrences of zero divisions split through, which will then cause weird issues in your analysis. Be safe — when dividing, add a constraint against the denominator being zero.

5.2 Understanding the Execution Pipeline

If you’ve made it this far you know that at its core, angr is a highly flexible and intensely instrumentable emulator. In order to get the most mileage out of it, you’ll want to know what happens at every step of the way when you say `simgr.run()`.

This is intended to be a more advanced document; you’ll need to understand the function and intent of `SimulationManager`, `ExplorationTechnique`, `SimState`, and `SimEngine` in order to understand what we’re talking about at times! You may want to have the angr source open to follow along with this.

At every step along the way, each function will take `**kwargs` and pass them along to the next function in the hierarchy, so you can pass parameters to any point in the hierarchy and they will trickle down to everything below.

5.2.1 Simulation Managers

So you’ve set your analysis in motion. Time to begin our journey.

`run()`

`SimulationManager.run()` takes several optional parameters, all of which control when to break out of the stepping loop. Notably, `n`, and `until`. `n` is used immediately - the run function loops, calling the `step()` function and passing on all its parameters until either `n` steps have happened or some other termination condition has occurred. If `n` is not provided, it defaults to 1, unless an `until` function is provided, in which case there will be no numerical cap on the loop. Additionally, the stash that is being used is taken into consideration, as if it becomes empty execution must terminate.

So, in summary, when you call `run()`, `step()` will be called in a loop until any of the following:

1. The `n` number of steps have elapsed
2. The `until` function returns true
3. The exploration techniques `complete()` hooks (combined via the `SimulationManager.completion_mode` parameter/attribute - it is by default the any builtin function but can be changed to `all` for example) indicate that the analysis is complete
4. The stash being executed becomes empty

An aside: `explore()`

`SimulationManager.explore()` is a very thin wrapper around `run()` which adds the `Explorer` exploration technique, since performing one-off explorations is a very common action. Its code in its entirety is below:

```
num_find += len(self._stashes[find_stash]) if find_stash in self._stashes else 0
tech = self.use_technique(Explorer(find, avoid, find_stash, avoid_stash, cfg, num_find))

try:
    self.run(stash=stash, n=n, **kwargs)
finally:
    self.remove_technique(tech)

return self
```

Exploration technique hooking

From here down, every function in the simulation manager can be instrumented by an exploration technique. The exact mechanism through which this works is that when you call `SimulationManager.use_technique()`, `angr` monkeypatches the simulation manager to replace any function implemented in the exploration technique’s body with a function which will first call the exploration technique’s function, and then on the second call will call the original function. This is somewhat messy to implement and certainly not thread safe by any means, but does produce a clean and powerful interface for exploration techniques to instrument stepping behavior, either before or after the original function is called, even choosing whether or not to call the original function whatsoever. Additionally, it allows multiple exploration techniques to hook the same function, as the monkeypatched function simply becomes the “original” function for the next-applied hook.

step()

There is a lot of complicated logic in `step()` to handle degenerate cases - mostly implementing the population of the deadended stash, the `save_unsat` option, and calling the `filter()` exploration technique hooks. Beyond this, though, most of the logic is looping through the stash specified by the `stash` argument and calling `step_state()` on each state, then applying the dict result of `step_state()` to the stash list. Finally, if the `step_func` parameter is provided, it is called with the simulation manager as a parameter before the step ends.

step_state()

The default `step_state()`, which can be overridden or instrumented by exploration techniques, is also simple - it calls `successors()`, which returns a `SimSuccessors` object, and then translates it into a dict mapping stash names to new states which should be added to that stash. It also implements error handling - if `successors()` throws an error, it will be caught and an `ErrorRecord` will be inserted into `SimulationManager.errorred`.

successors()

We've almost made it out of `SimulationManager`. `successors()`, which can also be instrumented by exploration techniques, is supposed to take a state and step it forward, returning a `SimSuccessors` object categorizing its successors independently of any stash logic. If the `successor_func` parameter was provided, it is used and its return value is returned directly. If this parameter was not provided, we use the `project.factory.successors` method to tick the state forward and get our `SimSuccessors`.

5.2.2 The Engine

When we get to the actual successors generation, we need to figure out how to actually perform the execution. Hopefully, the `angr` documentation has been organized in a way such that by the time you reach this page, you know that a `SimEngine` is a device that knows how to take a state and produce its successors. There is only one "default engine" per project, but you can provide the `engine` parameter to specify which engine will be used to perform the step.

Keep in mind that this parameter can be provided way at the top, to `.step()`, `.explore()`, `.run()` or anything else that starts execution, and they will be filtered down to this level. Any additional parameters will continue being passed down, until they reach the part of the engine they are intended for. The engine will discard any parameters it doesn't understand.

Generally, the main entry point of an engine is `SimEngine.process()`, which can return whatever result it likes, but for simulation managers, engines are required to use `SuccessorsMixin`, which provides a `process()` method, which creates a `SimSuccessors` object and then calls `process_successors()` so that other mixins can fill it out.

`angr`'s default engine, the `UberEngine`, contains several mixins which provide the `process_successors()` method:

- `SimEngineFailure` - handles stepping states with degenerate jumpkinds
- `SimEngineSyscall` - handles stepping states which have performed a syscall and need it executed
- `HooksMixin` - handles stepping states which have reached a hooked address and need the hook executed
- `SimEngineUnicorn` - executes machine code via the unicorn engine
- `SootMixin` - executes java bytecode via the SOOT IR
- `HeavyVEXMixin` - executes machine code via the VEX IR

Each of these mixins is implemented to fill out the `SimSuccessors` object if they can handle the current state, otherwise they call `super()` to pass the job on to the next class in the stack.

5.2.3 Engine mixins

`SimEngineFailure` handles error cases. It is only used when the previous jumpkind is one of `Ijk_EmFail`, `Ijk_MapFail`, `Ijk_Sig*`, `Ijk_NoDecode` (but only if the address is not hooked), or `Ijk_Exit`. In the first four cases, its action is to raise an exception. In the last case, its action is to simply produce no successors.

`SimEngineSyscall` services syscalls. It is used when the previous jumpkind is anything of the form `Ijk_Sys*`. It works by making a call into `SimOS` to retrieve the `SimProcedure` that should be run to respond to this syscall, and then running it! Pretty simple.

`HooksMixin` provides the hooking functionality in `angr`. It is used when a state is at an address that is hooked, and the previous jumpkind is *not* `Ijk_NoHook`. It simply looks up the associated `SimProcedure` and runs it on the state! It also takes the parameter `procedure`, which will cause the given procedure to be run for the current step even if the address is not hooked.

`SimEngineUnicorn` performs concrete execution with the Unicorn Engine. It is used when the state option `o.UNICORN` is enabled, and a myriad of other conditions designed for maximum efficiency (described below) are met.

`SootMixin` performs execution over the SOOT IR. Not very important unless you are analyzing java bytecode, in which case it is very important.

`SimEngineVEX` is the big fellow. It is used whenever any of the previous can't be used. It attempts to lift bytes from the current address into an `IRSB`, and then executes that `IRSB` symbolically. There are a huge number of parameters that can control this process, so it is best to reference the API doc for `angr.engines.vex.engine.SimEngineVEX.process()` describing them.

The exact process by which `SimEngineVEX` digs into an `IRSB` is a little complicated, but essentially it runs all the block's statements in order. This code is worth reading if you want to see the true inner core of `angr`'s symbolic execution.

5.2.4 When using Unicorn Engine

If you add the `o.UNICORN` state option, at every step `SimEngineUnicorn` will be invoked, and try to see if it is allowed to use Unicorn to execute concretely.

What you REALLY want to do is to add the predefined set `o.unicorn` (lowercase) of options to your state:

```
unicorn = { UNICORN, UNICORN_SYM_REGS_SUPPORT, INITIALIZE_ZERO_REGISTERS, UNICORN_HANDLE_
↳ TRANSMIT_SYSCALL }
```

These will enable some additional functionalities and defaults which will greatly enhance your experience. Additionally, there are a lot of options you can tune on the `state.unicorn` plugin.

A good way to understand how unicorn works is by examining the logging output (`logging.getLogger('angr.engines.unicorn_engine').setLevel('DEBUG');` `logging.getLogger('angr.state_plugins.unicorn_engine').setLevel('DEBUG')` from a sample run of unicorn.

```
INFO | 2017-02-25 08:19:48,012 | angr.state_plugins.unicorn | started emulation at_
↳ 0x4012f9 (1000000 steps)
```

Here, `angr` diverts to unicorn engine, beginning with the basic block at `0x4012f9`. The maximum step count is set to `1000000`, so if execution stays in Unicorn for `1000000` blocks, it'll automatically pop out. This is to avoid hanging in an infinite loop. The block count is configurable via the `state.unicorn.max_steps` variable.

```
INFO | 2017-02-25 08:19:48,014 | angr.state_plugins.unicorn | mmap [0x401000,
↳ 0x401fff], 5 (symbolic)
INFO | 2017-02-25 08:19:48,016 | angr.state_plugins.unicorn | mmap [0x7fffffffef0000,
```

(continues on next page)

(continued from previous page)

```

↪ 0x7ffffffffffffffe], 3 (symbolic)
INFO      | 2017-02-25 08:19:48,019 | angr.state_plugins.unicorn | mmap [0x6010000,↪
↪0x601ffff], 3
INFO      | 2017-02-25 08:19:48,022 | angr.state_plugins.unicorn | mmap [0x602000,↪
↪0x602fff], 3 (symbolic)
INFO      | 2017-02-25 08:19:48,023 | angr.state_plugins.unicorn | mmap [0x400000,↪
↪0x400fff], 5
INFO      | 2017-02-25 08:19:48,025 | angr.state_plugins.unicorn | mmap [0x7000000,↪
↪0x7000fff], 5

```

angr performs lazy mapping of data that is accessed by unicorn engine, as it is accessed. 0x401000 is the page of instructions that it is executing, 0x7ffffffffe0000 is the stack, and so on. Some of these pages are symbolic, meaning that they contain at least some data that, when accessed, will cause execution to abort out of Unicorn.

```

INFO      | 2017-02-25 08:19:48,037 | angr.state_plugins.unicorn | finished emulation at↪
↪0x7000080 after 3 steps: STOP_STOPPOINT

```

Execution stays in Unicorn for 3 basic blocks (a computational waste, considering the required setup), after which it reaches a simprocedure location and jumps out to execute the simproc in angr.

```

INFO      | 2017-02-25 08:19:48,076 | angr.state_plugins.unicorn | started emulation at↪
↪0x40175d (1000000 steps)
INFO      | 2017-02-25 08:19:48,077 | angr.state_plugins.unicorn | mmap [0x401000,↪
↪0x401fff], 5 (symbolic)
INFO      | 2017-02-25 08:19:48,079 | angr.state_plugins.unicorn | mmap [0x7ffffffffffffffe0000,↪
↪ 0x7ffffffffffffffe], 3 (symbolic)
INFO      | 2017-02-25 08:19:48,081 | angr.state_plugins.unicorn | mmap [0x6010000,↪
↪0x601ffff], 3

```

After the simprocedure, execution jumps back into Unicorn.

```

WARNING   | 2017-02-25 08:19:48,082 | angr.state_plugins.unicorn | fetching empty page↪
↪[0x0, 0xffff]
INFO      | 2017-02-25 08:19:48,103 | angr.state_plugins.unicorn | finished emulation at↪
↪0x401777 after 1 steps: STOP_EXECNONE

```

Execution bounces out of Unicorn almost right away because the binary accessed the zero-page.

```

INFO      | 2017-02-25 08:19:48,120 | angr.engines.unicorn_engine | not enough runs since↪
↪last unicorn (100)
INFO      | 2017-02-25 08:19:48,125 | angr.engines.unicorn_engine | not enough runs since↪
↪last unicorn (99)

```

To avoid thrashing in and out of Unicorn (which is expensive), we have cooldowns (attributes of the `state.unicorn` plugin) that wait for certain conditions to hold (i.e., no symbolic memory accesses for X blocks) before jumping back into unicorn when a unicorn run is aborted due to anything but a simprocedure or syscall. Here, the condition it's waiting for is for 100 blocks to be executed before jumping back in.

5.3 What's Up With Mixins, Anyway?

If you are trying to work more intently with the deeper parts of angr, you will need to understand one of the design patterns we use frequently: the mixin pattern.

In brief, the mixin pattern is where Python's subclassing features is used not to implement IS-A relationships (a Child is a kind of Person) but instead to implement pieces of functionality for a type in different classes to make more modular and maintainable code. Here's an example of the mixin pattern in action:

```
class Base:
    def add_one(self, v):
        return v + 1

class StringsMixin(Base):
    def add_one(self, v):
        coerce = type(v) is str
        if coerce:
            v = int(v)
        result = super().add_one(v)
        if coerce:
            result = str(result)
        return result

class ArraysMixin(Base):
    def add_one(self, v):
        if type(v) is list:
            return [super().add_one(v_x) for v_x in v]
        else:
            return super().add_one(v)

class FinalClass(ArraysMixin, StringsMixin, Base):
    pass
```

With this construction, we are able to define a very simple interface in the Base class, and by “mixing in” two mixins, we can create the FinalClass which has the same interface but with additional features. This is accomplished through Python's powerful multiple inheritance model, which handles method dispatch by creating a *method resolution order*, or MRO, which is unsurprisingly a list which determines the order in which methods are called as execution proceeds through `super()` calls. You can view a class' MRO as such:

```
FinalClass.__mro__

(FinalClass, ArraysMixin, StringsMixin, Base, object)
```

This means that when we take an instance of FinalClass and call `add_one()`, Python first checks to see if FinalClass defines an `add_one`, and then ArraysMixin, and so on and so forth. Furthermore, when ArraysMixin calls `super().add_one()`, Python will skip past ArraysMixin in the MRO, first checking if StringsMixin defines an `add_one`, and so forth.

Because multiple inheritance can create strange dependency graphs in the subclass relationship, there are rules for generating the MRO and for determining if a given mix of mixins is even allowed. This is important to understand when building complex classes with many mixins which have dependencies on each other. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A. If

there is any case in which the MRO would be ambiguous, the class construction is illegal and will throw an exception at import time.

This is complicated! If you find yourself confused, the canonical document explaining the rationale, history, and mechanics of Python's multiple inheritance can be found [here](#).

5.3.1 Mixins in Claripy Solvers

Todo: Write this section

5.3.2 Mixins in angr Engines

The main entry point to a SimEngine is `process()`, but how do we determine what that does?

The mixin model is used in SimEngine and friends in order to allow pieces of functionality to be reused between static and symbolic analyses. The default engine, `UberEngine`, is defined as follows:

```
class UberEngine(SimEngineFailure,
    SimEngineSyscall,
    HooksMixin,
    SimEngineUunicorn,
    SuperFastpathMixin,
    TrackActionsMixin,
    SimInspectMixin,
    HeavyResilienceMixin,
    SootMixin,
    HeavyVEXMixin
):
    pass
```

Each of these mixins provides either execution through a different medium or some additional instrumentation feature. Though they are not listed here explicitly, there are some base classes implicit to this hierarchy which set up the way this class is traversed. Most of these mixins inherit from `SuccessorsMixin`, which is what provides the basic `process()` implementation. This function sets up the `SimSuccessors` for the rest of the mixins to fill in, and then calls `process_successors()`, which each of the mixins which provide some mode of execution implement. If the mixin can handle the step, it does so and returns, otherwise it calls `super().process_successors()`. In this way, the MRO for the engine class determines what the order of precedence for the engine's pieces is.

HeavyVEXMixin and friends

Let's take a closer look at the last mixin, `HeavyVEXMixin`. If you look at the module hierarchy of the `angr engines` submodule, you will see that the `vex` submodule has a lot of pieces in it which are organized by how tightly tied to particular state types or data types they are. The heavy VEX mixin is one version of the culmination of all of these. Let's look at its definition:

```
class HeavyVEXMixin(SuccessorsMixin, ClaripyDataMixin, SimStateStorageMixin, VEXMixin,
    ↪ VEXLifter):
    ...
    # a WHOLE lot of implementation
```

So, the heavy VEX mixin is meant to provide fully instrumented symbolic execution on a `SimState`. What does this entail? The mixins tell the tale.

First, the plain `VEXMixin`. This mixin is designed to provide the barest-bones framework for processing a VEX block. Take a look at its [source code](#). Its main purpose is to perform the preliminary digestion of the VEX IRSB and dispatch processing of it to methods which are provided by mixins - look at the methods which are either `pass` or `return NotImplemented`. Notice that absolutely none of its code makes any assumption whatsoever of what the type of state is or even what the type of the data words inside state are. This job is delegated to other mixins, making the `VEXMixin` an appropriate base class for literally any analysis on VEX blocks.

The next-most interesting mixin is the `ClaripyDataMixin`, whose source code is [here](#). This mixin actually integrates the fact that we are executing over the domain of Claripy ASTs. It does this by implementing some of the methods which are unimplemented in the `VEXMixin`, most importantly the ITE expression, all the operations, and the clean helpers.

In terms of what it looks like to actually touch the `SimState`, the `SimStateStorageMixin` provides the glue between the `VEXMixin`'s interface for memory writes et al and `SimState`'s interface for memory writes and such. It is unremarkable, except for a small interaction between it and the `ClaripyDataMixin`. The `Claripy` mixin also overrides the memory/register read/write functions, for the purpose of converting between the bitvector and floating-point types, since the vex interface expects to be able to load and store floats, but the `SimState` interface wants to load and store only bitvectors. Because of this, *the claripy mixin must come before the storage mixin in the MRO*. This is very much an interaction like the one in the `add_one` example at the start of this page - one mixin serves as a data filtering layer for another mixin.

Instrumenting the data layer

Let's turn our attention to a mixin which is not included in the `HeavyVEXMixin` but rather mixed into the `UberEngine` formula explicitly: the `TrackActionsMixin`. This mixin implements "SimActions", which is angr parlance for dataflow tracking. Again, look at the [source code](#). The way it does this is that it *wraps and unwraps the data layer* to pass around additional information about data flows. Look at how it instruments `RdTmp`, for instance. It immediately `super()`-calls to the next method in the MRO, but instead of returning that data it returns a tuple of the data and its dependencies, which depending on whether you want temporary variables to be atoms in the dataflow model, will either be just the tmp which was read or the dependencies of the value written to that tmp.

This pattern continues for every single method that this mixin touches - any expression it receives must be unpacked into the expression and its dependencies, and any result must be packaged with its dependencies before it is returned. This works because the mixin above it makes no assumptions about what data it is passing around, and the mixin below it never gets to see any dependencies whatsoever. In fact, there could be multiple mixins performing this kind of wrap-unwrap trick and they could all coexist peacefully!

Note that a mixin which instruments the data layer in this way is *obligated* to override *every single method which takes or returns an expression value*, even if it doesn't perform any operation on the expression other than doing the wrapping and unwrapping. To understand why, imagine that the mixin does not override the `handle_vex_const` expression, so immediate value loads are not annotated with dependencies. The expression value which will be returned from the mixin which does provide `handle_vex_const` will not be a tuple of (expression, deps), it will just be the expression. Imagine this execution is taking place in the context of a `WrTmp(t0, Const(0))`. The const expression will be passed down to the `WrTmp` handler along with the identifier of the tmp to write to. However, since `handle_vex_stmt_WrTmp` will be overridden by our mixin which touches the data layer, it expects to be passed the tuple including the deps, and so it will crash when trying to unpack the not-a-tuple value.

In this way, you can sort of imagine that a mixin which instruments the data layer in this way is actually creating a contract within Python's nonexistent typesystem - you are guaranteed to receive back any types you return, but you must pass down any types you receive as return values from below.

5.3.3 Mixins in the memory model

Todo: write this section

5.4 Optimization considerations

The performance of angr as an analysis tool or emulator is greatly handicapped by the fact that lots of it is written in Python. Regardless, there are a lot of optimizations and tweaks you can use to make angr faster and lighter.

5.4.1 General speed tips

- *Use pypy.* [Pypy](#) is an alternate Python interpreter that performs optimized jitting of Python code. In our tests, it's a 10x speedup out of the box.
- *Only use the SimEngine mixins that you need.* SimEngine uses a mixin model which allows you to add and remove features by constructing new classes. The default engine mixes in every possible features, and the consequence of that is that it is slower than it needs to be. Look at the definition for `UberEngine` (the default SimEngine), copy its declaration, and remove all the base classes which provide features you don't need.
- *Don't load shared libraries unless you need them.* The default setting in angr is to try at all costs to find shared libraries that are compatible with the binary you've loaded, including loading them straight out of your OS libraries. This can complicate things in a lot of scenarios. If you're performing an analysis that's anything more abstract than bare-bones symbolic execution, ESPECIALLY control-flow graph construction, you might want to make the tradeoff of sacrificing accuracy for tractability. angr does a reasonable job of making sane things happen when library calls to functions that don't exist try to happen.
- *Use hooking and SimProcedures.* If you're enabling shared libraries, then you definitely want to have SimProcedures written for any complicated library function you're jumping into. If there's no autonomy requirement for this project, you can often isolate individual problem spots where analysis hangs up and summarize them with a hook.
- *Use SimInspect.* [SimInspect](#) is the most underused and one of the most powerful features of angr. You can hook and modify almost any behavior of angr, including memory index resolution (which is often the slowest part of any angr analysis).
- *Write a concretization strategy.* A more powerful solution to the problem of memory index resolution is a [concretization strategy](#).
- *Use the Replacement Solver.* You can enable it with the `angr.options.REPLACEMENT_SOLVER` state option. The replacement solver allows you to specify AST replacements that are applied at solve-time. If you add replacements so that all symbolic data is replaced with concrete data when it comes time to do the solve, the runtime is greatly reduced. The API for adding a replacement is `state.se._solver.add_replacement(old, new)`. The replacement solver is a bit finicky, so there are some gotchas, but it'll definitely help.

5.4.2 If you're performing lots of concrete or partially-concrete execution

- *Use the unicorn engine.* If you have `unicorn engine` installed, angr can be built to take advantage of it for concrete emulation. To enable it, add the options in the set `angr.options.unicorn` to your state. Keep in mind that while most items under `angr.options` are individual options, `angr.options.unicorn` is a bundle of options, and is thus a set. *NOTE:* At time of writing the official version of unicorn engine will not work with angr - we have a lot of patches to it to make it work well with angr. They're all pending pull requests at this time, so sit tight. If you're really impatient, ping us about uploading our fork!
- *Enable fast memory and fast registers.* The state options `angr.options.FAST_MEMORY` and `angr.options.FAST_REGISTERS` will do this. These will switch the memory/registers over to a less intensive memory model that sacrifices accuracy for speed. *TODO:* document the specific sacrifices. Should be safe for mostly concrete access though. *NOTE:* not compatible with concretization strategies.
- *Concretize your input ahead of time.* This is the approach taken by `driller`. When creating a state with `entry_state` or the like, you can create a `SimFile` filled with symbolic data, pass it to the initialization function as an argument `entry_state(..., stdin=my_simfile)`, and then constrain the symbolic data in the `SimFile` to what you want the input to be. If you don't require any tracking of the data coming from `stdin`, you can forego the symbolic part and just fill it with concrete data. If there are other sources of input besides standard input, do the same for those.
- *Use the afterburner.* While using unicorn, if you add the `UNICORN_THRESHOLD_CONCRETIZATION` state option, angr will accept thresholds after which it causes symbolic values to be concretized so that execution can spend more time in Unicorn. Specifically, the following thresholds exist:
 - `state.unicorn.concretization_threshold_memory` - this is the number of times a symbolic variable, stored in memory, is allowed to kick execution out of Unicorn before it is forcefully concretized and forced into Unicorn anyways.
 - `state.unicorn.concretization_threshold_registers` - this is the number of times a symbolic variable, stored in a register, is allowed to kick execution out of Unicorn before it is forcefully concretized and forced into Unicorn anyways.
 - `state.unicorn.concretization_threshold_instruction` - this is the number of times that any given instruction can force execution out of Unicorn (by running into symbolic data) before any symbolic data encountered at that instruction is concretized to force execution into Unicorn.

You can get further control of what is and isn't concretized with the following sets:

- `state.unicorn.always_concretize` - a set of variable names that will always be concretized to force execution into unicorn (in fact, the memory and register thresholds just end up causing variables to be added to this list).
- `state.unicorn.never_concretize` - a set of variable names that will never be concretized and forced into Unicorn under any condition.
- `state.unicorn.concretize_at` - a set of instruction addresses at which data should be concretized and forced into Unicorn. The instruction threshold causes addresses to be added to this set.

Once something is concretized with the afterburner, you will lose track of that variable. The state will still be consistent, but you'll lose dependencies, as the stuff that comes out of Unicorn is just concrete bits with no memory of what variables they came from. Still, this might be worth it for the speed in some cases, if you know what you want to (or do not want to) concretize.

5.4.3 Memory optimization

The golden rule for memory optimization is to make sure you're not keeping any references to data you don't care about anymore, especially related to states which have been left behind. If you find yourself running out of memory during analysis, the first thing you want to do is make sure you haven't caused a state explosion, meaning that the analysis is accumulating program states too quickly. If the state count is in control, then you can start looking for reference leaks. A good tool to do this with is <https://github.com/rhelmot/dumpsterdiver>, which gives you an interactive prompt for exploring the reference graph of a Python process.

One specific consideration that should be made when analyzing programs with very long paths is that the state history is designed to accumulate data infinitely. This is less of a problem than it could be because the data is stored in a smart tree structure and never copied, but it will accumulate infinitely. To downsize a state's history and free all data related to old steps, call `state.history.trim()`.

One *particularly* problematic member of the history dataset is the basic block trace and the stack pointer trace. When using unicorn engine, these lists of ints can become huge very very quickly. To disable unicorn's capture of ip and sp data, remove the state options `UNICORN_TRACK_BBL_ADDRS` and `UNICORN_TRACK_STACK_POINTERS`.

5.5 Working with File System, Sockets, and Pipes

It's very important to be able to control the environment that emulated programs see, including how symbolic data is introduced from the environment! angr has a robust series of abstractions to help you set up the environment you want.

The root of any interaction with the filesystem, sockets, pipes, or terminals is a `SimFile` object. A `SimFile` is a *storage* abstraction that defines a sequence of bytes, symbolic or otherwise. There are several kinds of `SimFiles` which store their data very differently - the two easiest examples are `SimFile` (the base class is actually called `SimFileBase`), which stores files as a flat address-space of data, and `SimPackets`, which stores a sequence of variable-sized reads. The former is best for modeling programs that need to perform seeks on their files, and is the default storage for opened files, while the latter is best for modeling programs that depend on short-reads or use `scanf`, and is the default storage for `stdin/stdout/stderr`.

Because `SimFiles` can have such diverse storage mechanisms, the interface for interacting with them is *very* abstracted. You can read from the file from some position, you can write to the file at some position, you can ask how many bytes are currently stored in the file, and you can concretize the file, generating a testcase for it. If you know specifically which `SimFile` class you're working with, you can take much more powerful control over it, and as a result you're encouraged to manually create any files you want to work with when you create your initial state.

Specifically, each `SimFile` class creates its own abstraction of a "position" within the file - each read and write takes a position and returns a new position that you should use to continue from where you left off. If you're working with `SimFiles` of unknown type you have to treat this position as a totally opaque object with no semantics other than the contract with the read/write functions.

However! This is a very poor match to how programs generally interact with files, so angr also has a `SimFileDescriptor` abstraction, which provides the familiar read/write/seek/tell interfaces but will also return error conditions when the underlying storage don't support the appropriate operations - just like normal file descriptors!

You may access the mapping from file descriptor number to file descriptor object in `state.posix.fd`. See the API document for [angr.storage.file.SimFileDescriptorBase](#) for more details.

5.5.1 Just tell me how to do what I want to do!

Okay okay!!

To create a SimFile, you should just create an instance of the class you want to use. Refer to [angr.storage.file](#) for the full instructions.

Let's go through a few illustrative examples, which cover how you can work with a concrete file, a symbolic file, a file with mixed concrete and symbolic content, or streams.

Example 1: Create a file with concrete content

```
>>> import angr
>>> simfile = angr.SimFile('myconcretefile', content='hello world!\n')
```

Here's a nuance - you can't use SimFiles without a state attached, because reasons. You'll **never** have to do this in a real scenario (this operation happens automatically when you pass a SimFile into a constructor or the filesystem) but let's mock it up:

```
>>> proj = angr.Project('/bin/true')
>>> state = proj.factory.blank_state()
>>> simfile.set_state(state)
```

To demonstrate the behavior of these files we're going to use the fact that the default SimFile position is just the number of bytes from the start of the file. SimFile.read returns a tuple (bitvector data, actual size, new pos):

```
>>> data, actual_size, new_pos = simfile.read(0, 5)
>>> import claripy
>>> assert claripy.is_true(data == 'hello')
>>> assert claripy.is_true(actual_size == 5)
>>> assert claripy.is_true(new_pos == 5)
```

Continue the read, trying to read way too much:

```
>>> data, actual_size, new_pos = simfile.read(new_pos, 1000)
```

angr doesn't try to sanitize the data returned, only the size - we returned 1000 bytes! The intent is that you're only allowed to use up to actual_size of them.

```
>>> assert len(data) == 1000*8 # bitvector sizes are in bits
>>> assert claripy.is_true(actual_size == 8)
>>> assert claripy.is_true(data.get_bytes(0, 8) == ' world!\n')
>>> assert claripy.is_true(new_pos == 13)
```

Example 2: Create a file with symbolic content and a defined size

```
>>> simfile = angr.SimFile('mysymbolicfile', size=0x20)
>>> simfile.set_state(state)

>>> data, actual_size, new_pos = simfile.read(0, 0x30)
>>> assert data.symbolic
>>> assert claripy.is_true(actual_size == 0x20)
```

The basic SimFile provides the same interface as `state.memory`, so you can load data directly:

```
>>> assert simfile.load(0, actual_size) is data.get_bytes(0, 0x20)
```

Example 3: Create a file with constrained symbolic content

```
>>> bytes_list = [claripy.BVS('byte_%d' % i, 8) for i in range(32)]
>>> bytes_ast = claripy.Concat(*bytes_list)
>>> mystate = proj.factory.entry_state(stdin=angr.SimFile('/dev/stdin', content=bytes_
↳ ast))
>>> for byte in bytes_list:
...     mystate.solver.add(byte >= 0x20)
...     mystate.solver.add(byte <= 0x7e)
```

Example 4: Create a file with some mixed concrete and symbolic content, but no EOF

```
>>> variable = claripy.BVS('myvar', 10*8)
>>> simfile = angr.SimFile('mymixedfile', content=variable.concat(claripy.BVV('\n')),
↳ has_end=False)
>>> simfile.set_state(state)
```

We can always query the number of bytes stored in the file:

```
>>> assert claripy.is_true(simfile.size == 11)
```

Reads will generate additional symbolic data past the current frontier:

```
>>> data, actual_size, new_pos = simfile.read(0, 15)
>>> assert claripy.is_true(actual_size == 15)
>>> assert claripy.is_true(new_pos == 15)

>>> assert claripy.is_true(data.get_bytes(0, 10) == variable)
>>> assert claripy.is_true(data.get_bytes(10, 1) == '\n')
>>> assert data.get_bytes(11, 4).symbolic
```

Example 5: Create a file with a symbolic size (`has_end` is implicitly true here)

```
>>> symsize = claripy.BVS('mysize', 64)
>>> state.solver.add(symsize >= 10)
>>> state.solver.add(symsize < 20)
>>> simfile = angr.SimFile('mysymsizefile', size=symsize)
>>> simfile.set_state(state)
```

Reads will encode all possibilities:

```
>>> data, actual_size, new_pos = simfile.read(0, 30)
>>> assert set(state.solver.eval_upto(actual_size, 30)) == set(range(10, 20))
```

The maximum size can't be easily resolved, so the data returned is 30 bytes long, and we're supposed to use it conjunction with `actual_size`.

```
>>> assert len(data) == 30*8
```

Symbolic read sizes work too!

```
>>> symreadsize = claripy.BVS('myreadsize', 64)
>>> state.solver.add(symreadsize >= 5)
>>> state.solver.add(symreadsize < 30)
>>> data, actual_size, new_pos = simfile.read(0, symreadsize)
```

All sizes between 5 and 20 should be possible:

```
>>> assert set(state.solver.eval_upto(actual_size, 30)) == set(range(5, 20))
```

Example 6: Working with streams (SimPackets)

So far, we’ve only used the SimFile class, which models a random-accessible file object. However, in real life, files are not everything. Streams (standard I/O, TCP, etc.) are a great example: While they hold data like a normal file does, they do not support random accesses, e.g., you cannot read out the second byte of stdin if you have already read passed that position, and you cannot modify any byte that has been previously sent out to a network endpoint. This allows us to design a simpler abstraction for streams in angr.

Believe it or not, this simpler abstraction for streams will benefit symbolic execution. Consider an example program that calls `scanf` `N` times to read in `N` strings. With a traditional SimFile, as we do not know the length of each input string, there does not exist any clear boundary in the file between these symbolic input strings. In this case, angr will perform `N` symbolic reads where each read will generate a gigantic tree of claripy ASTs, with string lengths being symbolic. This is a nightmare for constraint solving. Nevertheless, the fact that `scanf` is used on a stream (stdin) dictates that there will be zero overlap between individual reads, regardless of the sizes of each symbolic input string. We may as well model stdin as a stream that comprises of *consecutive packets*, instead of a file containing a sequence of bytes. Each of the packet can be of a fixed length or a symbolic length. Since there will be absolutely no byte overlap between packets, the constraints that angr will produce after executing this example program will be a lot simpler.

The key concept involved is “short reads”, i.e. when you ask for `n` bytes but actually get back fewer bytes than that. We use a different class implementing SimFileBase, SimPackets, to automatically enable support for short reads. By default, stdin, stdout, and stderr are all SimPackets objects.

```
>>> simfile = angr.SimPackets('mypackets')
>>> simfile.set_state(state)
```

This’ll just generate a single packet. For SimPackets, the position is just a packet number! If left unspecified, `short_reads` is determined from a state option.

```
>>> data, actual_size, new_pos = simfile.read(0, 20, short_reads=True)
>>> assert len(data) == 20*8
>>> assert set(state.solver.eval_upto(actual_size, 30)) == set(range(21))
```

Data in a SimPackets is stored as tuples of (packet data, packet size) in `.content`.

```
>>> print(simfile.content)
[(<BV160 packet_0_mypackets>, <BV64 packet_size_0_mypackets>)]

>>> simfile.read(0, 1, short_reads=False)
>>> print(simfile.content)
[(<BV160 packet_0_mypackets>, <BV64 packet_size_0_mypackets>), (<BV8 packet_1_mypackets>,
↳ <BV64 0x1>)]
```

So hopefully you understand sort of the kind of data that a SimFile can store and what'll happen when a program tries to interact with it with various combinations of symbolic and concrete data. Those examples only covered reads, but writes are pretty similar.

5.5.2 The filesystem, for real now

If you want to make a SimFile available to the program, we need to either stick it in the filesystem or serve stdin/stdout from it.

The simulated filesystem is the `state.fs` plugin. You can store, load, and delete files from the filesystem, with the `insert`, `get`, and `delete` methods. Refer to [angr.state_plugins.filesystem](#) for details.

So to make our file available as `/tmp/myfile`:

```
>>> state.fs.insert('/tmp/myfile', simfile)
>>> assert state.fs.get('/tmp/myfile') is simfile
```

Then, after execution, we would extract the file from the result state and use `simfile.concretize()` to generate a testcase to reach that state. Keep in mind that `concretize()` returns different types depending on the file type - for a SimFile it's a bytestring and for SimPackets it's a list of bytestrings.

The simulated filesystem supports a fun concept of “mounts”, where you can designate a subtree as instrumented by a particular provider. The most common mount is to expose a part of the host filesystem to the guest, lazily importing file data when the program asks for it:

```
>>> state.fs.mount('/', angr.SimHostFilesystem('./guest_chroot'))
```

You can write whatever kind of mount you want to instrument filesystem access by subclassing `angr.SimMount`!

5.5.3 Stdio streams

For stdin and friends, it's a little more complicated. The relevant plugin is `state.posix`, which stores all abstractions relevant to a POSIX-compliant environment. You can always get a state's stdin SimFile with `state.posix.stdin`, but you can't just replace it - as soon as the state is created, references to this file are created in the file descriptors. Because of this you need to specify it at the time the POSIX plugin is created:

```
>>> state.register_plugin('posix', angr.state_plugins.posix.SimSystemPosix(stdin=simfile,
↳ stdout=simfile, stderr=simfile))
>>> assert state.posix.stdin is simfile
>>> assert state.posix.stdout is simfile
>>> assert state.posix.stderr is simfile
```

Or, there's a nice shortcut while creating the state if you only need to specify stdin:

```
>>> state = proj.factory.entry_state(stdin=simfile)
>>> assert state.posix.stdin is simfile
```

Any of those places you can specify a SimFileBase, you can also specify a string or a bitvector (a flat SimFile with fixed size will be created to hold it) or a SimFile type (it'll be instantiated for you).

5.6 Intermediate Representation

In order to be able to analyze and execute machine code from different CPU architectures, such as MIPS, ARM, and PowerPC in addition to the classic x86, angr performs most of its analysis on an *intermediate representation*, a structured description of the fundamental actions performed by each CPU instruction. By understanding angr’s IR, VEX (which we borrowed from Valgrind), you will be able to write very quick static analyses and have a better understanding of how angr works.

The VEX IR abstracts away several architecture differences when dealing with different architectures, allowing a single analysis to be run on all of them:

- **Register names.** The quantity and names of registers differ between architectures, but modern CPU designs hold to a common theme: each CPU contains several general purpose registers, a register to hold the stack pointer, a set of registers to store condition flags, and so forth. The IR provides a consistent, abstracted interface to registers on different platforms. Specifically, VEX models the registers as a separate memory space, with integer offsets (e.g., AMD64’s `rax` is stored starting at address 16 in this memory space).
- **Memory access.** Different architectures access memory in different ways. For example, ARM can access memory in both little-endian and big-endian modes. The IR abstracts away these differences.
- **Memory segmentation.** Some architectures, such as x86, support memory segmentation through the use of special segment registers. The IR understands such memory access mechanisms.
- **Instruction side-effects.** Most instructions have side-effects. For example, most operations in Thumb mode on ARM update the condition flags, and stack push/pop instructions update the stack pointer. Tracking these side-effects in an *ad hoc* manner in the analysis would be crazy, so the IR makes these effects explicit.

There are lots of choices for an IR. We use VEX, since the uplifting of binary code into VEX is quite well supported. VEX is an architecture-agnostic, side-effects-free representation of a number of target machine languages. It abstracts machine code into a representation designed to make program analysis easier. This representation has four main classes of objects:

- **Expressions.** IR Expressions represent a calculated or constant value. This includes memory loads, register reads, and results of arithmetic operations.
- **Operations.** IR Operations describe a *modification* of IR Expressions. This includes integer arithmetic, floating-point arithmetic, bit operations, and so forth. An IR Operation applied to IR Expressions yields an IR Expression as a result.
- **Temporary variables.** VEX uses temporary variables as internal registers: IR Expressions are stored in temporary variables between use. The content of a temporary variable can be retrieved using an IR Expression. These temporaries are numbered, starting at `t0`. These temporaries are strongly typed (e.g., “64-bit integer” or “32-bit float”).
- **Statements.** IR Statements model changes in the state of the target machine, such as the effect of memory stores and register writes. IR Statements use IR Expressions for values they may need. For example, a memory store *IR Statement* uses an *IR Expression* for the target address of the write, and another *IR Expression* for the content.
- **Blocks.** An IR Block is a collection of IR Statements, representing an extended basic block (termed “IR Super Block” or “IRSB”) in the target architecture. A block can have several exits. For conditional exits from the middle of a basic block, a special *Exit* IR Statement is used. An IR Expression is used to represent the target of the unconditional exit at the end of the block.

VEX IR is actually quite well documented in the `libvex_ir.h` file (https://github.com/angr/vex/blob/master/pub/libvex_ir.h) in the VEX repository. For the lazy, we’ll detail some parts of VEX that you’ll likely interact with fairly frequently. To begin with, here are some IR Expressions:

IR Expression	Evaluated Value	VEX Output Example
Constant	A constant value.	0x4:I32
Read Temp	The value stored in a VEX temporary variable.	RdTmp(t10)
Get Register	The value stored in a register.	GET:I32(16)
Load Memory	The value stored at a memory address, with the address specified by another IR Expression.	LDle:I32 / LDbe:I64
Operation	A result of a specified IR Operation, applied to specified IR Expression arguments.	Add32
If-Then-Else	If a given IR Expression evaluates to 0, return one IR Expression. Otherwise, return another.	ITE
Helper Function	VEX uses C helper functions for certain operations, such as computing the conditional flags registers of certain architectures. These functions return IR Expressions.	function_name()

These expressions are then, in turn, used in IR Statements. Here are some common ones:

IR Statement	Meaning	VEX Output Example
Write Temp	Set a VEX temporary variable to the value of the given IR Expression.	WrTmp(t1) = (IR Expression)
Put Register	Update a register with the value of the given IR Expression.	PUT(16) = (IR Expression)
Store Memory	Update a location in memory, given as an IR Expression, with a value, also given as an IR Expression.	STle(0x1000) = (IR Expression)
Exit	A conditional exit from a basic block, with the jump target specified by an IR Expression. The condition is specified by an IR Expression.	if (condition) goto (Boring) 0x4000A00:I32

An example of an IR translation, on ARM, is produced below. In the example, the subtraction operation is translated into a single IR block comprising 5 IR Statements, each of which contains at least one IR Expression (although, in real life, an IR block would typically consist of more than one instruction). Register names are translated into numerical indices given to the *GET* Expression and *PUT* Statement. The astute reader will observe that the actual subtraction is modeled by the first 4 IR Statements of the block, and the incrementing of the program counter to point to the next instruction (which, in this case, is located at `0x59FC8`) is modeled by the last statement.

The following ARM instruction:

```
subs R2, R2, #8
```

Becomes this VEX IR:

```
t0 = GET:I32(16)
t1 = 0x8:I32
```

(continues on next page)

(continued from previous page)

```
t3 = Sub32(t0,t1)
PUT(16) = t3
PUT(68) = 0x59FC8:I32
```

Now that you understand VEX, you can actually play with some VEX in angr: We use a library called **PyVEX** that exposes VEX into Python. In addition, PyVEX implements its own pretty-printing so that it can show register names instead of register offsets in PUT and GET instructions.

PyVEX is accessible through angr through the `Project.factory.block` interface. There are many different representations you could use to access syntactic properties of a block of code, but they all have in common the trait of analyzing a particular sequence of bytes. Through the `factory.block` constructor, you get a `Block` object that can be easily turned into several different representations. Try `.vex` for a PyVEX IRSB, or `.capstone` for a Capstone block.

Let's play with PyVEX:

```
>>> import angr

# load the program binary
>>> proj = angr.Project("/bin/true")

# translate the starting basic block
>>> irsb = proj.factory.block(proj.entry).vex
# and then pretty-print it
>>> irsb.pp()

# translate and pretty-print a basic block starting at an address
>>> irsb = proj.factory.block(0x401340).vex
>>> irsb.pp()

# this is the IR Expression of the jump target of the unconditional exit at the end of
↳ the basic block
>>> print(irsb.next)

# this is the type of the unconditional exit (e.g., a call, ret, syscall, etc)
>>> print(irsb.jumpkind)

# you can also pretty-print it
>>> irsb.next.pp()

# iterate through each statement and print all the statements
>>> for stmt in irsb.statements:
...     stmt.pp()

# pretty-print the IR expression representing the data, and the *type* of that IR
↳ expression written by every store statement
>>> import pyvex
>>> for stmt in irsb.statements:
...     if isinstance(stmt, pyvex.IRStmt.Store):
...         print("Data:",)
...         stmt.data.pp()
...         print("")
...         print("Type:",)
...         print(stmt.data.result_type)
```

(continues on next page)

(continued from previous page)

```

...     print("")

# pretty-print the condition and jump target of every conditional exit from the basic_
↳ block
>>> for stmt in irsb.statements:
...     if isinstance(stmt, pyvex.IRStmt.Exit):
...         print("Condition:",)
...         stmt.guard.pp()
...         print("")
...         print("Target:",)
...         stmt.dst.pp()
...         print("")

# these are the types of every temp in the IRSB
>>> print(irsb.tyenv.types)

# here is one way to get the type of temp 0
>>> print(irsb.tyenv.types[0])

```

5.6.1 Condition flags computation (for x86 and ARM)

One of the most common instruction side-effects on x86 and ARM CPUs is updating condition flags, such as the zero flag, the carry flag, or the overflow flag. Computer architects usually put the concatenation of these flags (yes, concatenation of the flags, since each condition flag is 1 bit wide) into a special register (i.e. EFLAGS/RFLAGS on x86, APSR/CPSR on ARM). This special register stores important information about the program state, and is critical for correct emulation of the CPU.

VEX uses 4 registers as its “Flag thunk descriptors” to record details of the latest flag-setting operation. VEX has a lazy strategy to compute the flags: when an operation that would update the flags happens, instead of computing the flags, VEX stores a code representing this operation to the `cc_op` pseudo-register, and the arguments to the operation in `cc_dep1` and `cc_dep2`. Then, whenever VEX needs to get the actual flag values, it can figure out what the one bit corresponding to the flag in question actually is, based on its flag thunk descriptors. This is an optimization in the flags computation, as VEX can now just directly perform the relevant operation in the IR without bothering to compute and update the flags’ value.

Amongst different operations that can be placed in `cc_op`, there is a special value 0 which corresponds to `OP_COPY` operation. This operation is supposed to copy the value in `cc_dep1` to the flags. It simply means that `cc_dep1` contains the flags’ value. angr uses this fact to let us efficiently retrieve the flags’ value: whenever we ask for the actual flags, angr computes their value, then dumps them back into `cc_dep1` and sets `cc_op = OP_COPY` in order to cache the computation. We can also use this operation to allow the user to write to the flags: we just set `cc_op = OP_COPY` to say that a new value being set to the flags, then set `cc_dep1` to that new value.

5.7 Working with Data and Conventions

Frequently, you'll want to access structured data from the program you're analyzing. angr has several features to make this less of a headache.

5.7.1 Working with types

angr has a system for representing types. These `SimTypes` are found in `angr.types` - an instance of any of these classes represents a type. Many of the types are incomplete unless they are supplemented with a `SimState` - their size depends on the architecture you're running under. You may do this with `ty.with_arch(arch)`, which returns a copy of itself, with the architecture specified.

angr also has a light wrapper around `pyparser`, which is a C parser. This helps with getting instances of type objects:

```
>>> import angr, monkeyhex

# note that SimType objects have their __repr__ defined to return their c type name,
# so this function actually returned a SimType instance.
>>> angr.types.parse_type('int')
int

>>> angr.types.parse_type('char **')
char**

>>> angr.types.parse_type('struct aa {int x; long y;}')
struct aa

>>> angr.types.parse_type('struct aa {int x; long y;}').fields
OrderedDict([('x', int), ('y', long)])
```

Additionally, you may parse C definitions and have them returned to you in a dict, either of variable/function declarations or of newly defined types:

```
>>> angr.types.parse_defns("int x; typedef struct llist { char* str; struct llist *next; } list_node; list_node *y;")
{'x': int, 'y': struct llist*}

>>> defs = angr.types.parse_types("int x; typedef struct llist { char* str; struct llist *next; } list_node; list_node *y;")
>>> defs
{'struct llist': struct llist, 'list_node': struct llist}

# if you want to get both of these dicts at once, use parse_file, which returns both in a tuple.
>>> angr.types.parse_file("int x; typedef struct llist { char* str; struct llist *next; } list_node; list_node *y;")
({'x': int, 'y': struct llist*}, {'struct llist': struct llist, 'list_node': struct llist})

>>> defs['list_node'].fields
OrderedDict([('str', char*), ('next', struct llist*)])

>>> defs['list_node'].fields['next'].pts_to.fields
```

(continues on next page)

(continued from previous page)

```
OrderedDict([('str', char*), ('next', struct llist*)])

# If you want to get a function type and you don't want to construct it manually,
# you can use parse_type
>>> angr.types.parse_type("int (int y, double z)")
(int, double) -> int
```

And finally, you can register struct definitions for future use:

```
>>> angr.types.register_types(angr.types.parse_type('struct abcd { int x; int y; }'))
>>> angr.types.register_types(angr.types.parse_type('typedef long time_t;'))
>>> angr.types.parse_defns('struct abcd a; time_t b;')
{'a': struct abcd, 'b': long}
```

These type objects aren't all that useful on their own, but they can be passed to other parts of angr to specify data types.

5.7.2 Accessing typed data from memory

Now that you know how angr's type system works, you can unlock the full power of the `state.mem` interface! Any type that's registered with the types module can be used to extract data from memory.

```
>>> p = angr.Project('examples/fauxware/fauxware')
>>> s = p.factory.entry_state()
>>> s.mem[0x601048]
<<untyped> <unresolvable> at 0x601048>

>>> s.mem[0x601048].long
<long (64 bits) <BV64 0x4008d0> at 0x601048>

>>> s.mem[0x601048].long.resolved
<BV64 0x4008d0>

>>> s.mem[0x601048].long.concrete
0x4008d0

>>> s.mem[0x601048].struct.abcd
<struct abcd {
  .x = <BV32 0x4008d0>,
  .y = <BV32 0x0>
} at 0x601048>

>>> s.mem[0x601048].struct.abcd.x
<int (32 bits) <BV32 0x4008d0> at 0x601048>

>>> s.mem[0x601048].struct.abcd.y
<int (32 bits) <BV32 0x0> at 0x60104c>

>>> s.mem[0x601048].deref
<<untyped> <unresolvable> at 0x4008d0>

>>> s.mem[0x601048].deref.string
<string_t <BV64 0x534f534e45414b59> at 0x4008d0>
```

(continues on next page)

(continued from previous page)

```
>>> s.mem[0x601048].deref.string.resolved
<BV64 0x534f534e45414b59>

>>> s.mem[0x601048].deref.string.concrete
b'SOSNEAKY'
```

The interface works like this:

- You first use [array index notation] to specify the address you'd like to load from
- If at that address is a pointer, you may access the `deref` property to return a `SimMemView` at the address present in memory.
- You then specify a type for the data by simply accessing a property of that name. For a list of supported types, look at `state.mem.types`.
- You can then *refine* the type. Any type may support any refinement it likes. Right now the only refinements supported are that you may access any member of a struct by its member name, and you may index into a string or array to access that element.
- If the address you specified initially points to an array of that type, you can say `.array(n)` to view the data as an array of `n` elements.
- Finally, extract the structured data with `.resolved` or `.concrete`. `.resolved` will return bitvector values, while `.concrete` will return integer, string, array, etc values, whatever best represents the data.
- Alternately, you may store a value to memory, by assigning to the chain of properties that you've constructed. Note that because of the way Python works, `x = s.mem[...].prop`; `x = val` will NOT work, you must say `s.mem[...].prop = val`.

If you define a struct using `register_types(parse_type(struct_expr))`, you can access it here as a type:

```
>>> s.mem[p.entry].struct.abcd
<struct abcd {
  .x = <BV32 0x8949ed31>,
  .y = <BV32 0x89485ed1>
} at 0x400580>
```

5.7.3 Working with Calling Conventions

A calling convention is the specific means by which code passes arguments and return values through function calls. `angr`'s abstraction of calling conventions is called `SimCC`. You can construct new `SimCC` instances through the `angr` object factory, with `p.factory.cc(...)`. This will give a calling convention which is guessed based your guest architecture and OS. If `angr` guesses wrong, you can explicitly pick one of the calling conventions in the `angr.calling_conventions` module.

If you have a very wacky calling convention, you can use `angr.calling_conventions.SimCCUsercall`. This will ask you to specify locations for the arguments and the return value. To do this, use instances of the `SimRegArg` or `SimStackArg` classes. You can find them in the factory - `p.factory.cc.Sim*Arg`.

Once you have a `SimCC` object, you can use it along with a `SimState` object and a function prototype (a `SimTypeFunction`) to extract or store function arguments more cleanly. Take a look at the `angr.calling_conventions.SimCC` for details. Alternately, you can pass it to an interface that can use it to modify its own behavior, like `p.factory.call_state`, or...

5.7.4 Callables

Callables are a Foreign Functions Interface (FFI) for symbolic execution. Basic callable usage is to create one with `myfunc = p.factory.callable(addr)`, and then call it! `result = myfunc(args, ...)` When you call the callable, angr will set up a `call_state` at the given address, dump the given arguments into memory, and run a `path_group` based on this state until all the paths have exited from the function. Then, it merges all the result states together, pulls the return value out of that state, and returns it.

All the interaction with the state happens with the aid of a `SimCC` and a `SimTypeFunction`, to tell where to put the arguments and where to get the return value. It will try to use a sane default for the architecture, but if you'd like to customize it, you can pass a `SimCC` object in the `cc` keyword argument when constructing the callable. The `SimTypeFunction` is required - you must pass the `prototype` parameter. If you pass a string to this parameter it will be parsed as a function declaration.

You can pass symbolic data as function arguments, and everything will work fine. You can even pass more complicated data, like strings, lists, and structures as native Python data (use tuples for structures), and it'll be serialized as cleanly as possible into the state. If you'd like to specify a pointer to a certain value, you can wrap it in a `PointerWrapper` object, available as `p.factory.callable.PointerWrapper`. The exact semantics of how pointer-wrapping work are a little confusing, but they can be boiled down to "unless you specify it with a `PointerWrapper` or a specific `SimArrayType`, nothing will be wrapped in a pointer automatically unless it gets to the end and it hasn't yet been wrapped in a pointer yet and the original type is a string, array, or tuple." The relevant code is actually in `SimCC` - it's the `setup_callsite` function.

If you don't care for the actual return value of the call, you can say `func.perform_call(arg, ...)`, and then the properties `func.result_state` and `func.result_path_group` will be populated. They will actually be populated even if you call the callable normally, but you probably care about them more in this case!

5.8 Solver Engine

angr's solver engine is called Claripy. Claripy exposes the following design:

- Claripy ASTs (the subclasses of `claripy.ast.Base`) provide a unified way to interact with concrete and symbolic expressions
- Frontends provide different paradigms for evaluating these expressions. For example, the `FullFrontend` solves expressions using something like an SMT solver backend, while `LightFrontend` handles them by using an abstract (and approximating) data domain backend.
- Each Frontend needs to, at some point, do actual operation and evaluations on an AST. ASTs don't support this on their own. Instead, Backends translate ASTs into backend objects (i.e., Python primitives for `BackendConcrete`, Z3 expressions for `BackendZ3`, strided intervals for `BackendVSA`, etc) and handle any appropriate state-tracking objects (such as tracking the solver state in the case of `BackendZ3`). Roughly speaking, frontends take ASTs as inputs and use backends to `backend.convert()` those ASTs into backend objects that can be evaluated and otherwise reasoned about.
- `FrontendMixins` customize the operation of Frontends. For example, `ModelCacheMixin` caches solutions from an SMT solver.
- The combination of a Frontend, a number of FrontendMixins, and a number of Backends comprise a Claripy Solver.

Internally, Claripy seamlessly mediates the co-operation of multiple disparate backends – concrete bitvectors, VSA constructs, and SAT solvers. It is pretty badass.

Most users of angr will not need to interact directly with Claripy (except for, maybe, Claripy AST objects, which represent symbolic expressions) – angr handles most interactions with Claripy internally. However, for dealing with expressions, an understanding of Claripy might be useful.

5.8.1 Claripy ASTs

Claripy ASTs abstract away the differences between mathematical constructs that Claripy supports. They define a tree of operations (i.e., $(a + b) / c$) on any type of underlying data. Claripy handles the application of these operations on the underlying objects themselves by dispatching requests to the backends.

Currently, Claripy supports the following types of ASTs:

Name	Description	Supported By (Claripy Backends)	Example Code
BV	This is a bitvector, whether symbolic (with a name) or concrete (with a value). It has a size (in bits).	BackendConcrete, BackendVSA, BackendZ3	Create a 32-bit symbolic bitvector “x”: <code>claripy.BVS('x', 32)</code> Create a 32-bit bitvector with the value <code>0xc001b3475</code> : <code>claripy.BVV(0xc001b3475, 32)</code> Create a 32-bit “strided interval” (see VSA documentation) that can be any divisible-by-10 number between 1000 and 2000: <code>claripy.SI(name='x', bits=32, lower_bound=1000, upper_bound=2000, stride=10)</code>
FP	This is a floating-point number, whether symbolic (with a name) or concrete (with a value).	BackendConcrete, BackendZ3	Create a <code>claripy.fp.FSORT_DOUBLE</code> symbolic floating point “b”: <code>claripy.FPS('b', claripy.fp.FSORT_DOUBLE)</code> Create a <code>claripy.fp.FSORT_FLOAT</code> floating point with value 3.2: <code>claripy.FPV(3.2, claripy.fp.FSORT_FLOAT)</code>
Bool	This is a boolean operation (True or False).	BackendConcrete, BackendVSA, BackendZ3	<code>claripy.BoolV(True)</code> , or <code>claripy.true</code> or <code>claripy.false</code> , or by comparing two ASTs (i.e., <code>claripy.BVS('x', 32) < claripy.BVS('y', 32)</code>)

All of the above creation code returns `claripy.AST` objects, on which operations can then be carried out.

ASTs provide several useful operations.

```
>>> import claripy
```

(continues on next page)

(continued from previous page)

```
>>> bv = claripy.BVV(0x41424344, 32)

# Size - you can get the size of an AST with .size()
>>> assert bv.size() == 32

# Reversing - .reversed is the reversed version of the BVV
>>> assert bv.reversed is claripy.BVV(0x44434241, 32)
>>> assert bv.reversed.reversed is bv

# Depth - you can get the depth of the AST
>>> print(bv.depth)
>>> assert bv.depth == 1
>>> x = claripy.BVS('x', 32)
>>> assert (x+bv).depth == 2
>>> assert ((x+bv)/10).depth == 3
```

Applying a condition (`==`, `!=`, etc) on ASTs will return an AST that represents the condition being carried out. For example:

```
>>> r = bv == x
>>> assert isinstance(r, claripy.ast.Bool)

>>> p = bv == bv
>>> assert isinstance(p, claripy.ast.Bool)
>>> assert p.is_true()
```

You can combine these conditions in different ways.

```
>>> q = claripy.And(claripy.Or(bv == x, bv * 2 == x, bv * 3 == x), x == 0)
>>> assert isinstance(q, claripy.ast.Bool)
```

The usefulness of this will become apparent when we discuss Claripy solvers.

In general, Claripy supports all of the normal Python operations (`+`, `-`, `!`, `==`, etc), and provides additional ones via the Claripy instance object. Here's a list of available operations from the latter.

Name	Description	Example
LShR	Logically shifts a bit expression (BVV, BV, SI) to the right.	<code>claripy.LShR(x, 10)</code>
SignExt	Sign-extends a bit expression.	<code>claripy.SignExt(32, x)</code> or <code>x.sign_extend(32)</code>
ZeroExt	Zero-extends a bit expression.	<code>claripy.ZeroExt(32, x)</code> or <code>x.zero_extend(32)</code>
Extract	Extracts the given bits (zero-indexed from the <i>right</i> , inclusive) from a bit expression.	Extract the rightmost byte of x: <code>claripy.Extract(7, 0, x)</code> or <code>x[7:0]</code>
Concat	Concatenates several bit expressions together into a new bit expression.	<code>claripy.Concat(x, y, z)</code>
RotateLeft	Rotates a bit expression left.	<code>claripy.RotateLeft(x, 8)</code>
RotateRight	Rotates a bit expression right.	<code>claripy.RotateRight(x, 8)</code>
Reverse	Endian-reverses a bit expression.	<code>claripy.Reverse(x)</code> or <code>x.reversed</code>
And	Logical And (on boolean expressions)	<code>claripy.And(x == y, x > 0)</code>
Or	Logical Or (on boolean expressions)	<code>claripy.Or(x == y, y < 10)</code>
Not	Logical Not (on a boolean expression)	<code>claripy.Not(x == y)</code> is the same as <code>x != y</code>
If	An If-then-else	Choose the maximum of two expressions: <code>claripy.If(x > y, x, y)</code>
ULE	Unsigned less than or equal to.	Check if x is less than or equal to y: <code>claripy.ULE(x, y)</code>
ULT	Unsigned less than.	Check if x is less than y: <code>claripy.ULT(x, y)</code>
UGE	Unsigned greater than or equal to.	Check if x is greater than or equal to y: <code>claripy.UGE(x, y)</code>
UGT	Unsigned greater than.	Check if x is greater than y: <code>claripy.UGT(x, y)</code>
SLE	Signed less than or equal to.	Check if x is less than or equal to y: <code>claripy.SLE(x, y)</code>
SLT	Signed less than.	Check if x is less than y: <code>claripy.SLT(x, y)</code>
SGE	Signed greater than or equal to.	Check if x is greater than or equal to y: <code>claripy.SGE(x, y)</code>
SGT	Signed greater than.	Check if x is greater than y: <code>claripy.SGT(x, y)</code>

Note: The default Python `>`, `<`, `>=`, and `<=` are unsigned in Claripy. This is different than their behavior in Z3, because it seems more natural in binary analysis.

5.8.2 Solvers

The main point of interaction with Claripy are the Claripy Solvers. Solvers expose an API to interpret ASTs in different ways and return usable values. There are several different solvers.

Name	Description
Solver	This is analogous to a <code>z3.Solver()</code> . It is a solver that tracks constraints on symbolic variables and uses a constraint solver (currently, Z3) to evaluate symbolic expressions.
SolverVSA	This solver uses VSA to reason about values. It is an <i>approximating</i> solver, but produces values without performing actual constraint solves.
Solver-Replace-ment	This solver acts as a pass-through to a child solver, allowing the replacement of expressions on-the-fly. It is used as a helper by other solvers and can be used directly to implement exotic analyses.
Solver-Hybrid	This solver combines the SolverReplacement and the Solver (VSA and Z3) to allow for <i>approximating</i> values. You can specify whether or not you want an exact result from your evaluations, and this solver does the rest.
Solver-Com-posite	This solver implements optimizations that solve smaller sets of constraints to speed up constraint solving.

Some examples of solver usage:

```
# create the solver and an expression
>>> s = claripy.Solver()
>>> x = claripy.BVS('x', 8)

# now let's add a constraint on x
>>> s.add(claripy.ULT(x, 5))

>>> assert sorted(s.eval(x, 10)) == [0, 1, 2, 3, 4]
>>> assert s.max(x) == 4
>>> assert s.min(x) == 0

# we can also get the values of complex expressions
>>> y = claripy.BVV(65, 8)
>>> z = claripy.If(x == 1, x, y)
>>> assert sorted(s.eval(z, 10)) == [1, 65]

# and, of course, we can add constraints on complex expressions
>>> s.add(z % 5 != 0)
>>> assert s.eval(z, 10) == (1,)
>>> assert s.eval(x, 10) == (1,) # interestingly enough, since z can't be y, x can only
↳ be 1!
```

Custom solvers can be built by combining a Claripy Frontend (the class that handles the actual interaction with SMT solver or the underlying data domain) and some combination of frontend mixins (that handle things like caching, filtering out duplicate constraints, doing opportunistic simplification, and so on).

5.8.3 Claripy Backends

Backends are Claripy’s workhorses. Claripy exposes ASTs to the world, but when actual computation has to be done, it pushes those ASTs into objects that can be handled by the backends themselves. This provides a unified interface to the outside world while allowing Claripy to support different types of computation. For example, BackendConcrete provides computation support for concrete bitvectors and booleans, BackendVSA introduces VSA constructs such as StridedIntervals (and details what happens when operations are performed on them, and BackendZ3 provides support for symbolic variables and constraint solving.

There are a set of functions that a backend is expected to implement. For all of these functions, the “public” version is expected to be able to deal with claripy’s AST objects, while the “private” version should only deal with objects specific to the backend itself. This is distinguished with Python idioms: a public function will be named `func()` while a private function will be `_func()`. All functions should return objects that are usable by the backend in its private methods. If this can’t be done (i.e., some functionality is being attempted that the backend can’t handle), the backend should raise a `BackendError`. In this case, Claripy will move on to the next backend in its list.

All backends must implement a `convert()` function. This function receives a claripy AST and should return an object that the backend can handle in its private methods. Backends should also implement a `convert()` method, which will receive anything that is *not* a claripy AST object (i.e., an integer or an object from a different backend). If `convert()` or `convert()` receives something that the backend can’t translate to a format that is usable internally, the backend should raise `BackendError`, and thus won’t be used for that object. All backends must also implement any functions of the base `Backend` abstract class that currently raise `NotImplementedError()`.

Claripy’s contract with its backends is as follows: backends should be able to handle, in their private functions, any object that they return from their private *or* public functions. Claripy will never pass an object to any backend private function that did not originate as a return value from a private or public function of that backend. One exception to this is `convert()` and `convert()`, as Claripy can try to stuff anything it feels like into `_convert()` to see if the backend can handle that type of object.

Backend Objects

To perform actual, useful computation on ASTs, Claripy uses backend objects. A `BackendObject` is a result of the operation represented by the AST. Claripy expects these objects to be returned from their respective backends, and will pass such objects into that backend’s other functions.

5.9 Symbolic memory addressing

angr supports *symbolic memory addressing*, meaning that offsets into memory may be symbolic. Our implementation of this is inspired by “Mayhem”. Specifically, this means that angr concretizes symbolic addresses when they are used as the target of a write. This causes some surprises, as users tend to expect symbolic writes to be treated purely symbolically, or “as symbolically” as we treat symbolic reads, but that is not the default behavior. However, like most things in angr, this is configurable.

The address resolution behavior is governed by *concretization strategies*, which are subclasses of `angr.concretization_strategies.SimConcretizationStrategy`. Concretization strategies for reads are set in `state.memory.read_strategies` and for writes in `state.memory.write_strategies`. These strategies are called, in order, until one of them is able to resolve addresses for the symbolic index. By setting your own concretization strategies (or through the use of `SimInspect` address_concretization breakpoints, described above), you can change the way angr resolves symbolic addresses.

For example, angr’s default concretization strategies for writes are:

1. A conditional concretization strategy that allows symbolic writes (with a maximum range of 128 possible solutions) for any indices that are annotated with `angr.plugins.symbolic_memory.MultiwriteAnnotation`.

2. A concretization strategy that simply selects the maximum possible solution of the symbolic index.

To enable symbolic writes for all indices, you can either add the `SYMBOLIC_WRITE_ADDRESSES` state option at state creation time or manually insert a `angr.concretization_strategies.SimConcretizationStrategyRange` object into `state.memory.write_strategies`. The strategy object takes a single argument, which is the maximum range of possible solutions that it allows before giving up and moving on to the next (presumably non-symbolic) strategy.

5.9.1 Writing concretization strategies

Todo: Write this section

5.10 Java Support

angr also supports symbolically executing Java code and Android apps! This also includes Android apps using a combination of compiled Java and native (C/C++) code.

Warning: Java support is experimental! Contribution from the community is highly encouraged! Pull requests are very welcomed!

We implemented Java support by lifting the compiled Java code, both Java and DEX bytecode, leveraging our Soot Python wrapper: `pysoot`. `pysoot` extracts a fully serializable interface from Android apps and Java code (unfortunately, as of now, it only works on Linux). For every class of the generated IR (for instance, `SootMethod`), you can nicely print its instructions (in a format similar to Soot `shimple`) using `print()` or `str()`.

We then leverage the generated IR in a new angr engine able to run code in Soot IR: `angr/engines/soot/engine.py`. This engine is also able to automatically switch to executing native code if the Java code calls any native method using the JNI interface.

Together with the symbolic execution, we also implemented some basic static analysis, specifically a basic CFG reconstruction analysis. Moreover, we added support for string constraint solving, modifying `claripy` and using the CVC4 solver.

5.10.1 How to install

Enabling Java support requires few more steps than typical angr installation. Assuming you installed `angr-dev`, activate the `virtualenv` and run:

```
pip install -e ./claripy[cvc4-solver]
./setup.sh pysoot
```

Analyzing Android apps.

Analyzing Android apps (.APK files, containing Java code compiled to the DEX format) requires the Android SDK. Typically, it is installed in `<HOME>/Android/SDK/platforms/platform-XX/android.jar`, where `XX` is the Android SDK version used by the app you want to analyze (you may want to install all the platforms required by the Android apps you want to analyze).

5.10.2 Examples

There are multiple examples available:

- Easy Java crackmes: `java_crackme1`, `java_simple3`, `java_simple4`
- A more complex example (solving a CTF challenge): `ictf2017_javaisnotfun`, `blogpost`
- Symbolically executing an Android app (using a mix of Java and native code): `java_androidnative1`
- Many other low-level tests: `test_java`

5.11 Symbion: Interleaving symbolic and concrete execution

Let's suppose you want to symbolically analyze a specific function of a program, but there is a huge initialization step that you want to skip because it is not necessary for your analysis, or cannot properly be emulated by angr. For example, maybe your program is running on an embedded system and you have access to a debug interface, but you can't easily replicate the hardware in a simulated environment.

This is the perfect scenario for Symbion, our interleaved execution technique!

We implemented a built-in system that let users define a `ConcreteTarget` that is used to “import” a concrete state of the target program from an external source into angr. Once the state is imported you can make parts of the state symbolic, use symbolic execution on this state, run your analyses, and finally concretize the symbolic parts and resume concrete execution in the external environment. By iterating this process it is possible to implement run-time and interactive advanced symbolic analyses that are backed up by the real program's execution!

Isn't that cool?

5.11.1 How to install

To use this technique you'll need an implementation of a `ConcreteTarget` (effectively, an object that is going to be the “glue” between angr and the external process.) We ship a default one (the `AvatarGDBConcreteTarget`, which control an instance of a program being debugged under GDB) in the following repo <https://github.com/angr/angr-targets>.

Assuming you installed angr-dev, activate the virtualenv and run:

```
git clone https://github.com/angr/angr-targets.git
cd angr-targets
pip install .
```

Now you're ready to go!

5.11.2 Gists

Once you have created an entry state, instantiated a `SimulationManager`, and specified a list of *stop_points* using the Symbion interface we are going to resume the concrete process execution.

```
# Instantiating the ConcreteTarget
avatar_gdb = AvatarGDBConcreteTarget(avatar2.archs.x86.X86_64,
                                     GDB_SERVER_IP, GDB_SERVER_PORT)

# Creating the Project
p = angr.Project(binary_x64, concrete_target=avatar_gdb,
                  use_sim_procedures=True)

# Getting an entry_state
entry_state = p.factory.entry_state()

# Forget about these options as for now, will explain later.
entry_state.options.add(angr.options.SYMBION_SYNC_CLE)
entry_state.options.add(angr.options.SYMBION_KEEP_STUBS_ON_SYNC)

# Use Symbion!
simgr.use_technique(angr.exploration_techniques.Symbion(find=[0x85b853]))
```

When one of your *stop_points* (effectively a breakpoint) is hit, we give control to `angr`. A new plugin called *concrete* is in charge of synchronizing the concrete state of the program inside a new `SimState`.

Roughly, synchronization does the following:

- All the registers' values (NOT marked with `concrete=False` in the respective arch file in `archinfo`) are copied inside the new `SimState`.
- The underlying memory backend is hooked in a way that all the further memory accesses triggered during symbolic execution are redirected to the concrete process.
- If the project is initialized with `SimProcedure` (`use_sim_procedures=True`) we are going to re-hook the external functions' addresses with a `SimProcedure` if we happen to have it, otherwise with a `SimProcedure` stub (you can control this decision by using the Options `SYMBION_KEEP_STUBS_ON_SYNC`). Conversely, the real code of the function is executed inside `angr` (Warning: do that at your own risk!)

Once this process is completed, you can play with your new `SimState` backed by the concrete process stopped at that particular *stop_point*.

5.11.3 Options

The way we synchronize the concrete process inside `angr` is customizable by 2 state options:

- **SYMBION_SYNC_CLE**: this option controls the synchronization of the memory mapping of the program inside `angr`. When the project is created, the memory mapping inside `angr` is different from the one inside the concrete process (this will change as soon as Symbion will be fully compatible with `archr`). If you want the process mapping to be fully synchronized with the one of the concrete process, set this option to the `SimState` before initializing the `SimulationManager` (Note that this is going to happen at the first synchronization of the concrete process inside `angr`, NOT before)

```
entry_state.options.add(angr.options.SYMBION_SYNC_CLE)
simgr = project.factory.simgr(state)
```

- **SYMBION_KEEP_STUBS_ON_SYNC**: this option controls how we re-hook external functions with SimProcedures. If the project has been initialized to use SimProcedures (`use_sim_procedures=True`), we are going to re-hook external functions with SimProcedures (if we have that particular implementation) or with a generic stub. If you want to execute SimProcedures for functions for which we have an available implementation and a generic stub SimProcedure for the ones we have not, set this option to the SimState before initializing the SimulationManager. In the other case, we are going to execute the real code for the external functions that miss a SimProcedure (no generic stub is going to be used).

```
entry_state.options.add(angr.options.SYMBION_KEEP_STUBS_ON_SYNC)
simgr = project.factory.simgr(state)
```

5.11.4 Example

You can find more information about this technique and a complete example in our blog post: https://angr.io/blog/angr_symbion/. For more technical details a public paper will be available soon, or, ping @degrigis on our **angr** Slack channel.

5.12 Debug variable resolution

angr now support resolve source level variable (debug variable) in binary with debug information. This article will introduce you how to use it.

5.12.1 Setting up

To use it you need binary that is compiled with dwarf debugging information (ex: `gcc -g`) and load in angr with the option `load_debug_info`. After that you need to run `project.kb.dvars.load_from_dwarf()` to set up the feature and we're set.

Overall it looks like this:

```
# compile your binary with debug information
gcc -g -o debug_var debug_var.c
```

```
>>> import angr
>>> project = angr.Project('./examples/debug_var/simple_var', load_debug_info = True)
>>> project.kb.dvars.load_from_dwarf()
```

5.12.2 Core feature

With things now set up you can view the value in the angr memory view of the debug variable within a state with: `state.dvars['variable_name'].mem` or the value that it point to if it is a pointer with: `state.dvars['pointer_name'].deref.mem`. Here are some example:

Given the source code in `examples/debug_var/simple_var.c`

```
#include<stdio.h>

int global_var = 100;
int main(void){
```

(continues on next page)

(continued from previous page)

```

int a = 10;
int* b = &a;
printf("%d\n", *b);
{
    int a = 24;
    *b = *b + a;
    int c[] = {5, 6, 7, 8};
    printf("%d\n", a);
}
return 0;
}

```

```

# Get a state before executing printf(%d\n", *b) (line 7)
# the addr to line 7 is 0x401193 you can search for it with
>>> project.loader.main_object.addr_to_line
{...}
>>> addr = 0x401193
# Create an simulation manager and run to that addr
>>> simgr = project.factory.simgr()
>>> simgr.explore(find = addr)
<SimulationManager with 1 found>
>>> state = simgr.found[0]
# Resolve 'a' in state
>>> state.dvars['a'].mem
<int (32 bits) <BV32 0xa> at 0x7fffffffffeff30>
# Dereference pointer b
>>> state.dvars['b'].deref.mem
<int (32 bits) <BV32 0xa> at 0x7fffffffffeff30>
# It works as expected when resolving the value of b gives the address of a
>>> state.dvars['b'].mem
<reg64_t <BV64 0x7fffffffffeff30> at 0x7fffffffffeff38>

```

Side-note: For string type you can use `.string` instead of `.mem` to resolve it. For struct type you can resolve its member by `.member("member_name").mem`. For array type you can use `.array(index).mem` to access the element in array.

5.13 Variable visibility

If you have many variable with the same name but in different scope, calling `state.dvars['var_name']` would resolve the variable with the nearest scope.

Example:

```

# Find the addr before executing printf("%d\n", a) (line 12)
# with the same method to find addr
>>> addr = 0x4011e0
# Explore until find state
>>> simgr.move(from_stash='found', to_stash='active')
<SimulationManager with 1 active>
>>> simgr.explore(find = addr)
<SimulationManager with 1 found>
>>> state = simgr.found[0]

```

(continues on next page)

(continued from previous page)

```
# Resolve 'a' in state before execute line 10
>>> state.dvars['a'].mem
<int (32 bits) <BV32 0x18> at 0x7fffffffffeff34>
```

Congratulation, you've now know how to resolve debug variable using angr, for more info check out the [api-doc](#).

EXTENDING ANGR

6.1 Hooks and SimProcedures

Hooks in angr are very powerful! You can use them to modify a program's behavior in any way you could imagine. However, the exact way you might want to program a specific hook may be non-obvious. This chapter should serve as a guide when programming SimProcedures.

6.1.1 Quick Start

Here's an example that will remove all bugs from any program:

```
>>> from angr import Project, SimProcedure
>>> project = Project('examples/fauxware/fauxware')

>>> class BugFree(SimProcedure):
...     def run(self, argc, argv):
...         print('Program running with argc=%s and argv=%s' % (argc, argv))
...         return 0

# this assumes we have symbols for the binary
>>> project.hook_symbol('main', BugFree())

# Run a quick execution!
>>> simgr = project.factory.simulation_manager()
>>> simgr.run() # step until no more active states
Program running with argc=<SA0 <BV64 0x0>> and argv=<SA0 <BV64 0x7fffffffffeffa0>>
<SimulationManager with 1 deadended>
```

Now, whenever program execution reaches the main function, instead of executing the actual main function, it will execute this procedure! It just prints out a message, and returns.

Now, let's talk about what happens on the edge of this function! When entering the function, where do the values that go into the arguments come from? You can define your `run()` function with however many arguments you like, and the SimProcedure runtime will automatically extract from the program state those arguments for you, via a *calling convention*, and call your run function with them. Similarly, when you return a value from the run function, it is placed into the state (again, according to the calling convention), and the actual control-flow action of returning from a function is performed, which depending on the architecture may involve jumping to the link register or jumping to the result of a stack pop.

It should be clear at this point that the SimProcedure we just wrote is meant to totally replace whatever function it is hooked over top of. In fact, the original use case for SimProcedures was replacing library functions. More on that later.

6.1.2 Implementation Context

On a `Project` class, the dict `project._sim_procedures` is a mapping from address to `SimProcedure` instances. When the *execution pipeline* reaches an address that is present in that dict, that is, an address that is hooked, it will execute `project._sim_procedures[address].execute(state)`. This will consult the calling convention to extract the arguments, make a copy of itself in order to preserve thread safety, and run the `run()` method. It is important to produce a new instance of the `SimProcedure` for each time it is run, since the process of running a `SimProcedure` necessarily involves mutating state on the `SimProcedure` instance, so we need separate ones for each step, lest we run into race conditions in multithreaded environments.

kwargs

This hierarchy implies that you might want to reuse a single `SimProcedure` in multiple hooks. What if you want to hook the same `SimProcedure` in several places, but tweaked slightly each time? `angr`'s support for this is that any additional keyword arguments you pass to the constructor of your `SimProcedure` will end up getting passed as keyword args to your `SimProcedure`'s `run()` method. Pretty cool!

6.1.3 Data Types

If you were paying attention to the example earlier, you noticed that when we printed out the arguments to the `run()` function, they came out as a weird `<SAO <BV64 0xSTUFF>> class`. This is a `SimActionObject`. Basically, you don't need to worry about it too much, it's just a thin wrapper over a normal bitvector. It does a bit of tracking of what exactly you do with it inside the `SimProcedure`—this is helpful for static analysis.

You may also have noticed that we directly returned the Python int `0` from the procedure. This will automatically be promoted to a word-sized bitvector! You can return a native number, a bitvector, or a `SimActionObject`.

When you want to write a procedure that deals with floating point numbers, you will need to specify the calling convention manually. It's not too hard, just provide a `cc` to the hook: ``cc = project.factory.cc_from_arg_kinds((True, True), ret_fp=True)` and `project.hook(address, ProcedureClass(cc=mycc))` This method for passing in a calling convention works for all calling conventions, so if `angr`'s autodetected one isn't right, you can fix that.

6.1.4 Control Flow

How can you exit a `SimProcedure`? We've already gone over the simplest way to do this, returning a value from `run()`. This is actually shorthand for calling `self.ret(value)`. `self.ret()` is the function which knows how to perform the specific action of returning from a function.

`SimProcedures` can use lots of different functions like this!

- `ret(expr)`: Return from a function
- `jump(addr)`: Jump to an address in the binary
- `exit(code)`: Terminate the program
- `call(addr, args, continue_at)`: Call a function in the binary
- `inline_call(procedure, *args)`: Call another `SimProcedure` in-line and return the results

That second-last one deserves some looking-at. We'll get there after a quick detour...

Conditional Exits

What if we want to add a conditional branch out of a `SimProcedure`? In order to do that, you'll need to work directly with the `SimSuccessors` object for the current execution step.

The interface for this is `self.successors.add_successor(state, addr, guard, jumpkind)`. All of these parameters should have an obvious meaning if you've followed along so far. Keep in mind that the state you pass in will NOT be copied and WILL be mutated, so be sure to make a copy beforehand if there will be more work to do!

SimProcedure Continuations

How can we call a function in the binary and have execution resume within our `SimProcedure`? There is a whole bunch of infrastructure called the "SimProcedure Continuation" that will let you do this. When you use `self.call(addr, args, continue_at)`, `addr` is expected to be the address you'd like to call, `args` is the tuple of arguments you'd like to call it with, and `continue_at` is the name of another method in your `SimProcedure` class that you'd like execution to continue at when it returns. This method must have the same signature as the `run()` method. Furthermore, you can pass the keyword argument `cc` as the calling convention that ought to be used to communicate with the callee.

When you do this, you finish your current step, and execution will start again at the next step at the function you've specified. When that function returns, it has to return to some concrete address! That address is specified by the `SimProcedure` runtime: an address is allocated in `angr`'s externs segment to be used as the return site for returning to the given method call. It is then hooked with a copy of the procedure instance tweaked to run the specified `continue_at` function instead of `run()`, with the same args and kwargs as the first time.

There are two pieces of metadata you need to attach to your `SimProcedure` class in order to use the continuation subsystem correctly:

- Set the class variable `IS_FUNCTION = True`
- Set the class variable `local_vars` to a tuple of strings, where each string is the name of an instance variable on your `SimProcedure` whose value you would like to persist to when you return. Local variables can be any type so long as you don't mutate their instances.

You may have guessed by now that there exists some sort of auxiliary storage in order to hold on to all this data. You would be right! The state plugin `state.callstack` has an entry called `.procedure_data` which is used by the `SimProcedure` runtime to store information local to the current call frame. `angr` tracks the stack pointer in order to make the current top of the `state.callstack` a meaningful local data store. It's stuff that ought to be stored in memory in a stack frame, but the data can't be serialized and/or memory allocation is hard.

As an example, let's look at the `SimProcedure` that `angr` uses internally to run all the shared library initializers for a `full_init_state` for a linux program:

```
class LinuxLoader(angr.SimProcedure):
    NO_RET = True
    IS_FUNCTION = True
    local_vars = ('initializers',)

    def run(self):
        self.initializers = self.project.loader.initializers
        self.run_initializer()

    def run_initializer(self):
        if len(self.initializers) == 0:
            self.project._simos.set_entry_register_values(self.state)
            self.jump(self.project.entry)
        else:
```

(continues on next page)

(continued from previous page)

```

        addr = self.initializers[0]
        self.initializers = self.initializers[1:]
        self.call(addr, (self.state.posix.argc, self.state.posix.argv, self.state.
↪posix.environ), 'run_initializer')

```

This is a particularly clever usage of the SimProcedure continuations. First, notice that the current project is available for use on the procedure instance. This is some powerful stuff you can get yourself into; for safety you generally only want to use the project as a read-only or append-only data structure. Here we're just getting the list of dynamic initializers from the loader. Then, for as long as the list isn't empty, we pop a single function pointer out of the list, being careful not to mutate the list, since the list object is shared across states, and then call it, returning to the `run_initializer` function again. When we run out of initializers, we set up the entry state and jump to the program entry point.

Very cool!

6.1.5 Global Variables

As a brief aside, you can store global variables in `state.globals`. This is a dictionary that just gets shallow-copied from state to successor state. Because it's only a shallow copy, its members are the same instances, so the same rules as local variables in SimProcedure continuations apply. You need to be careful not to mutate any item that is used as a global variable unless you know exactly what you're doing.

6.1.6 Helping out static analysis

We've already looked at the class variable `IS_FUNCTION`, which allows you to use the SimProcedure continuation. There are a few more class variables you can set, though these ones have no direct benefit to you - they merely mark attributes of your function so that static analysis knows what it's doing.

- `NO_RET`: Set this to true if control flow will never return from this function
- `ADDS_EXITS`: Set this to true if you do any control flow other than returning
- `IS_SYSCALL`: Self-explanatory

Furthermore, if you set `ADDS_EXITS = True`, you'll need to define the method `static_exits()`. This function takes a single parameter, a list of IRSBs that would be executed in the run-up to your function, and asks you to return a list of all the exits that you know would be produced by your function in that case. The return value is expected to be a list of tuples of (address (int), jumpkind (str)). This is meant to be a quick, best-effort analysis, and you shouldn't try to do anything crazy or intensive to get your answer.

6.1.7 User Hooks

The process of writing and using a SimProcedure makes a lot of assumptions that you want to hook over a whole function. What if you don't? There's an alternate interface for hooking, a *user hook*, that lets you streamline the process of hooking sections of code.

```

>>> @project.hook(0x1234, length=5)
... def set_rax(state):
...     state.regs.rax = 1

```

This is a lot simpler! The idea is to use a single function instead of an entire SimProcedure subclass. No extraction of arguments is performed, no complex control flow happens.

Control flow is controlled by the `length` argument. After the function finishes executing in this example, the next step will start at 5 bytes after the hooked address. If the `length` argument is omitted or set to zero, execution will resume executing the binary code at exactly the hooked address, without re-triggering the hook. The `Ijk_NoHook` jumpkind allows this to happen.

If you want more control over control flow coming out of a user hook, you can return a list of successor states. Each successor will be expected to have `state.regs.ip`, `state.scratch.guard`, and `state.scratch.jumpkind` set. The IP is the target instruction pointer, the guard is a symbolic boolean representing a constraint to add to the state related to it being taken as opposed to the others, and the jumpkind is a VEX enum string, like `Ijk_Boring`, representing the nature of the branch.

The general rule is, if you want your `SimProcedure` to either be able to extract function arguments or cause a program return, write a full `SimProcedure` class. Otherwise, use a user hook.

6.1.8 Hooking Symbols

As you should recall from the [section on loading a binary](#), dynamically linked programs have a list of symbols that they must import from the libraries they have listed as dependencies, and angr will make sure, rain or shine, that every import symbol gets resolved by *some* address, whether it's a real implementation of the function or just a dummy address hooked with a do-nothing stub. As a result, you can just use the `Project.hook_symbol` API to hook the address referred to by a symbol!

This means that you can replace library functions with your own code. For instance, to replace `rand()` with a function that always returns a consistent sequence of values:

```
>>> class NotVeryRand(SimProcedure):
...     def run(self, return_values=None):
...         rand_idx = self.state.globals.get('rand_idx', 0) % len(return_values)
...         out = return_values[rand_idx]
...         self.state.globals['rand_idx'] = rand_idx + 1
...         return out
>>> project.hook_symbol('rand', NotVeryRand(return_values=[413, 612, 1025, 1111]))
```

Now, whenever the program tries to call `rand()`, it'll return the integers from the `return_values` array in a loop.

6.2 State Plugins

If you want to store some data on a state and have that information propagated from successor to successor, the easiest way to do this is with `state.globals`. However, this can become obnoxious with large amounts of interesting data, doesn't work at all for merging states, and isn't very object-oriented.

The solution to these problems is to write a *State Plugin* - an appendix to the state that holds data and implements an interface for dealing with the lifecycle of a state.

6.2.1 My First Plugin

Let's get started! All state plugins are implemented as subclasses of `SimStatePlugin`. Once you've read this document, you can use the API reference for this class [angr.state_plugins.plugin.SimStatePlugin](#) to quickly review the semantics of all the interfaces you should implement.

The most important method you need to implement is `copy`: it should be annotated with the `memo` staticmethod and take a dict called the “memo”—these'll be important later—and returns a copy of the plugin. Short of that, you can do whatever you want. Just make sure to call the superclass initializer!

```
>>> import angr
>>> class MyFirstPlugin(angr.SimStatePlugin):
...     def __init__(self, foo):
...         super(MyFirstPlugin, self).__init__()
...         self.foo = foo
...
...     @angr.SimStatePlugin.memo
...     def copy(self, memo):
...         return MyFirstPlugin(self.foo)

>>> state = angr.SimState(arch='AMD64')
>>> state.register_plugin('my_plugin', MyFirstPlugin('bar'))
>>> assert state.my_plugin.foo == 'bar'

>>> state2 = state.copy()
>>> state.my_plugin.foo = 'baz'
>>> state3 = state.copy()
>>> assert state2.my_plugin.foo == 'bar'
>>> assert state3.my_plugin.foo == 'baz'
```

It works! Note that plugins automatically become available as attributes on the state. `state.get_plugin(name)` is also available as a more programmatic interface.

6.2.2 Where's the state?

State plugins have access to the state, right? So why isn't it part of the initializer? It turns out, there are a plethora of issues related to initialization order and dependency issues, so to simplify things as much as possible, the state is not part of the initializer but is rather set onto the state in a separate phase, by using the `set_state` method. You can override this state if you need to do things like propagate the state to subcomponents or extract architectural information.

```
>>> def set_state(self, state):
...     super(SimStatePlugin, self).set_state(state)
...     self.symbolic_word = claripy.BVS('my_variable', self.state.arch.bits)
```

Note the `self.state`! That's what the super `set_state` sets up.

However, there's no guarantee on what order the states will be set onto the plugins in, so if you need to interact with *other plugins* for initialization, you need to override the `init_state` method.

Once again, there's no guarantee on what order these will be called in, so the rule is to make sure you set yourself up good enough during `set_state` so that if someone else tries to interact with you, no type errors will happen. Here's an example of a good use of `init_state`, to map a memory region in the state. The use of an instance variable (presumably copied as part of `copy()`) ensures this only happens the first time the plugin is added to a state.

```
>>> def init_state(self):
...     if self.region is None:
...         self.region = self.state.memory.map_region(SOMEWHERE, 0x1000, 7)
```

Note: weak references

`self.state` is not the state itself, but rather a [weak proxy](#) to the state. You can still use this object as a normal state, but attempts to store it persistently will not work.

6.2.3 Merging

The other element besides copying in the state lifecycle is merging. As input you get the plugins to merge and a list of “merge conditions” - symbolic booleans that are the “guard conditions” describing when the values from each state should actually apply.

The important properties of the merge conditions are:

- They are mutually exclusive and span an entire domain - exactly one may be satisfied at once, and there will be additional constraints to ensure that at least one must be satisfied.
- `len(merge_conditions) == len(others) + 1`, since `self` counts too.
- `zip(merge_conditions, [self] + others)` will correctly pair merge conditions with plugins.

During the merge function, you should *mutate* `self` to become the merged version of itself and all the others, with respect to the merge conditions. This involves using the if-then-else structure that `claripy` provides. Here is an example of constructing this merged structure by merging a bitvector instance variable called `myvar`, producing a binary tree of if-then-else expressions searching for the correct condition:

```
for other_plugin, condition in zip(others, merge_conditions[1:]): # chop off self's
    ↪ condition
    self.myvar = claripy.If(condition, other_plugin.myvar, self.myvar)
```

This is such a common construction that we provide a utility to perform it automatically: `claripy.ite_cases`. The following code snippet is identical to the previous one:

```
self.myvar = claripy.ite_cases(zip(merge_conditions[1:], [o.myvar for o in others]),
    ↪ self.myvar)
```

Keep in mind that like the rest of the top-level `claripy` functions, `ite_cases` and `If` are also available from `state.solver`, and these versions will perform `SimActionObject` unwrapping if applicable.

Common Ancestor

The full prototype of the merge interface is `def merge(self, others, merge_conditions, common_ancestor=None)`. `others` and `merge_conditions` have been discussed in depth already.

The common ancestor is the instance of the plugin from the most recent common ancestor of the states being merged. It may not be available for all merges, in which case it will be `None`. There are no rules for how exactly you should use this to improve the quality of your merges, but you may find it useful in more complex setups.

6.2.4 Widening

There is another kind of merging called *widening* which takes several states and produces a more general state. It is used during static analysis.

Todo: Explain what this means

6.2.5 Serialization

In order to support serialization of states which contain your plugin, you should implement the `__getstate__`/`__setstate__` magic method pair. Keep in mind the following guidelines:

- Your serialization result should *not* include the state.
- After deserialization, `set_state()` will be called again.

This means that plugins are “detached” from the state and serialized in an isolated environment, and then reattached to the state on deserialization.

6.2.6 Plugins all the way down

You may have components within your state plugins which are large and complicated and start breaking object-orientation in order to make copy/merge work well with the state lifecycle. You’re in luck! Things can be state plugins even if they aren’t directly attached to a state. A great example of this is `SimFile`, which is a state plugin but is stored in the filesystem plugin, and is never used with `SimState.register_plugin`. When you’re doing this, there are a handful of rules to remember which will keep your plugins safe and happy:

- Annotate your copy function with `@SimStatePlugin.memo`.
- In order to prevent *divergence* while copying multiple references to the same plugin, make sure you’re passing the memo (the argument to copy) to the `.copy` of any subplugins. This with the previous point will preserve object identity.
- In order to prevent *duplicate merging* while merging multiple references to the same plugin, there should be a concept of the “owner” of each instance, and only the owner should run the merge routine.
- While passing arguments down into sub-plugins `merge()` routines, make sure you unwrap `others` and `common_ancestor` into the appropriate types. For example, if `PluginA` contains a `PluginB`, the former should do the following:

```
>>> def merge(self, others, merge_conditions, common_ancestor=None):
...     # ... merge self
...     self.plugin_b.merge([o.plugin_b for o in others], merge_conditions,
...         common_ancestor=None if common_ancestor is None else common_ancestor.plugin_b)
...     return b)
```


6.2.7 Setting Defaults

To make it so that a plugin will automatically become available on a state when requested, without having to register it with the state first, you can register it as a *default*. The following code example will make it so that whenever you access `state.my_plugin`, a new instance of `MyPlugin` will be instantiated and registered with the state.

```
MyPlugin.register_default('my_plugin')
```

6.3 Extending the Environment Model

One of the biggest issues you may encounter while using `angr` to analyze programs is an incomplete model of the environment, or the APIs, surrounding your program. This usually takes the form of syscalls or dynamic library calls, or in rare cases, loader artifacts. `angr` provides a convenient interface to do most of these things!

Everything discussed here involves writing `SimProcedures`, so *make sure you know how to do that!*.

Note that this page should be treated as a narrative document, not a reference document, so you should read it at least once start to end.

6.3.1 Setup

You *probably* want to have a development install of `angr`, i.e. set up with the script in the [angr-dev repository](#). It is remarkably easy to add new API models by just implementing them in certain folders of the `angr` repository. This is also desirable because any work you do in this field will almost always be useful to other people, and this makes it extremely easy to submit a pull request.

However, if you want to do your development out-of-tree, you want to work against a production version of `angr`, or you want to make customized versions of already-implemented API functions, there are ways to incorporate your extensions programmatically. Both these techniques, in-tree and out-of-tree, will be documented at each step.

6.3.2 Dynamic library functions - import dependencies

This is the easiest case, and the case that `SimProcedures` were originally designed for.

First, you need to write a `SimProcedure` representing the function. Then you need to let `angr` know about it.

Case 1, in-tree development: `SimLibraries` and catalogues

`angr` has a magical folder in its repository, [angr/procedures](#). Within it are all the `SimProcedure` implementations that come bundled with `angr` as well as information about what libraries implement what functions.

Each folder in the `procedures` directory corresponds to some sort of *standard*, or a body that specifies the interface part of an API and its semantics. We call each folder a *catalog* of procedures. For example, we have `libc` which contains the functions defined by the C standard library, and a separate folder `posix` which contains the functions defined by the `posix` standard. There is some magic which automatically scrapes these folders in the `procedures` directory and organizes them into the `angr.SIM_PROCEDURES` dict. For example, `angr/procedures/libc/printf.py` contains both `class printf` and `class __printf_chk`, so there exists both `angr.SIM_PROCEDURES['libc']['printf']` and `angr.SIM_PROCEDURES['libc']['__printf_chk']`.

The purpose of this categorization is to enable easy sharing of procedures among different libraries. For example, `libc.so.6` contains all the C standard library functions, but so does `msvcrt.dll`! These relationships are represented with objects called `SimLibraries` which represent an actual shared library file, its functions, and their metadata. Take a look at the API reference for [SimLibrary](#) along with [the code for setting up glibc](#) to learn how to use it.

SimLibraries are defined in a special folder in the procedures directory, `procedures/definitions`. Files in here should contain an *instance*, not a subclass, of `SimLibrary`. The same magic that scrapes up `SimProcedures` will also scrape up `SimLibraries` and put them in `angr.SIM_LIBRARIES`, keyed on each of their common names. For example, `angr/procedures/definitions/linux_loader.py` contains `lib = SimLibrary(); lib.set_library_names('ld.so', 'ld-linux.so', 'ld.so.2', 'ld-linux.so.2', 'ld-linux-x86_64.so.2')`, so you can access it via `angr.SIM_LIBRARIES['ld.so']` or `angr.SIM_LIBRARIES['ld-linux.so']` or any of the other names.

At load time, all the dynamic library dependencies are looked up in `SIM_LIBRARIES` and their procedures (or stubs!) are hooked into the project's address space to summarize any functions it can. The code for this process is found [here](#).

SO, the bottom line is that you can just write your own `SimProcedure` and `SimLibrary` definitions, drop them into the directory structure, and they'll automatically be applied. If you're adding a procedure to an existing library, you can just drop it into the appropriate catalog and it'll be picked up by all the libraries using that catalog, since most libraries construct their list of function implementation by batch-adding entire catalogs.

Case 2, out-of-tree development, tight integration

If you'd like to implement your procedures outside the `angr` repository, you can do that. You effectively do this by just manually adding your procedures to the appropriate `SimLibrary`. Just call `angr.SIM_LIBRARIES[libname].add(name, proc_cls)` to do the registration.

Note that this will only work if you do this before the project is loaded with `angr.Project`. Note also that adding the procedure to `angr.SIM_PROCEDURES`, i.e. adding it directly to a catalog, will *not* work, since these catalogs are used to construct the `SimLibraries` only at import and are used by value, not by reference.

Case 3, out-of-tree development, loose integration

Finally, if you don't want to mess with `SimLibraries` at all, you can do things purely on the project level with `hook_symbol()`.

6.3.3 Syscalls

Unlike dynamic library methods, syscall procedures aren't incorporated into the project via hooks. Instead, whenever a syscall instruction is encountered, the basic block should end with a jumpkind of `Ijk_Sys`. This will cause the next step to be handled by the `SimOS` associated with the project, which will extract the syscall number from the state and query a specialized `SimLibrary` with that.

This deserves some explanation.

There is a subclass of `SimLibrary` called `SimSyscallLibrary` which is used for collecting all the functions that are part of an operating system's syscall interface. `SimSyscallLibrary` uses the same system for managing implementations and metadata as `SimLibrary`, but adds on top of it a system for managing syscall numbers for multiple ABIs (application binary interfaces, like an API but lower level). The best example for an implementation of a `SimSyscallLibrary` is the [linux syscalls](#). It keeps its procedures in a normal `SimProcedure` catalog called `linux_kernel` and adds them to the library, then adds several syscall number mappings, including separate mappings for `mips-o32`, `mips-n32`, and `mips-n64`.

In order for syscalls to be supported in the first place, the project's `SimOS` must inherit from [SimUserland](#), itself a `SimOS` subclass. This requires the class to call `SimUserland`'s constructor with a `super()` call that includes the `syscall_library` keyword argument, specifying the specific `SimSyscallLibrary` that contains the appropriate procedures and mappings for the operating system. Additionally, the class's `configure_project` must perform a `super()` call including the `abi_list` keyword argument, which contains the list of ABIs that are valid for the current architecture. If the ABI for the syscall can't be determined by just the syscall number, for example, that `amd64` linux programs can use either `int 0x80` or `syscall` to invoke a syscall and these two ABIs use overlapping numbers, the `SimOS` call

override `syscall_abi()`, which takes a `SimState` and returns the name of the current syscall ABI. This is determined for `int80/syscall` by examining the most recent jumpkind, since `libVEX` will produce different syscall jumpkinds for the different instructions.

Calling conventions for syscalls are a little weird right now and they ought to be refactored. The current situation requires that `angr.SYSCALL_CC` be a map of maps `{arch_name: {os_name: cc_cls}}`, where `os_name` is the value of `project.simos.name`, and each of the calling convention classes must include an extra method called `syscall_number` which takes a state and return the current syscall number. Look at the bottom of [calling_conventions.py](#) to learn more about it. Not very object-oriented at all...

As a side note, each syscall is given a unique address in a special object in CLE called the “kernel object”. Upon a syscall, the address for the specific syscall is set into the state’s instruction pointer, so it will show up in the logs. These addresses are not hooked, they are just used to identify syscalls during analysis given only an address trace. The test for determining if an address corresponds to a syscall is `project.simos.is_syscall_addr(addr)` and the syscall corresponding to the address can be retrieved with `project.simos.syscall_from_addr(addr)`.

Case 1, in-tree development

`SimSyscallLibraries` are stored in the same place as the normal `SimLibraries`, `angr/procedures/definitions`. These libraries don’t have to specify any common name, but they can if they’d like to show up in `SIM_LIBRARIES` for easy access.

The same thing about adding procedures to existing catalogs of dynamic library functions also applies to syscalls - implementing a linux syscall is as easy as writing the `SimProcedure` and dropping the implementation into `angr/procedures/linux_kernel`. As long as the class name matches one of the names in the number-to-name mapping of the `SimLibrary` (all the linux syscall numbers are included with recent releases of `angr`), it will be used.

To add a new operating system entirely, you need to implement the `SimOS` as well, as a subclass of `SimUserland`. To integrate it into the tree, you should add it to the `simos` directory, but this is not a magic directory like `procedures`. Instead, you should add a line to `angr/simos/__init__.py` calling `register_simos()` with the OS name as it appears in `project.loader.main_object.os` and the `SimOS` class. Your class should do everything described above.

Case 2, out-of-tree development, tight integration

You can add syscalls to a `SimSyscallLibrary` the same way you can add functions to a normal `SimLibrary`, by tweaking the entries in `angr.SIM_LIBRARIES`. If you’re this for linux you want `angr.SIM_LIBRARIES['linux'].add(name, proc_cls)`.

You can register a `SimOS` with `angr` from out-of-tree as well - the same `register_simos` method is just sitting there waiting for you as `angr.simos.register_simos(name, simos_cls)`.

Case 3, out-of-tree development, loose integration

The `SimSyscallLibrary` the `SimOS` uses is copied from the original during setup, so it is safe to mutate. You can directly fiddle with `project.simos.syscall_library` to manipulate an individual project’s syscalls.

You can provide a `SimOS` class (not an instance) directly to the `Project` constructor via the `simos` keyword argument, so you can specify the `SimOS` for a project explicitly if you like.

6.3.4 SimData

What about when there is an import dependency on a data object? This is easily resolved when the given library is actually loaded into memory - the relocation can just be resolved as normal. However, when the library is not loaded (for example, `auto_load_libs=False`, or perhaps some dependency is simply missing), things get tricky. It is not possible to guess in most cases what the value should be, or even what its size should be, so if the guest program ever dereferences a pointer to such a symbol, emulation will go off the rails.

CLE will warn you when this might happen:

```
[22:26:58] [cle.backends.externs] | WARNING: Symbol was allocated without a known size;␣
↪emulation will fail if it is used non-opaquely: _rtld_global
[22:26:58] [cle.backends.externs] | WARNING: Symbol was allocated without a known size;␣
↪emulation will fail if it is used non-opaquely: __libc_enable_secure
[22:26:58] [cle.backends.externs] | WARNING: Symbol was allocated without a known size;␣
↪emulation will fail if it is used non-opaquely: _rtld_global_ro
[22:26:58] [cle.backends.externs] | WARNING: Symbol was allocated without a known size;␣
↪emulation will fail if it is used non-opaquely: _dl_argv
```

If you see this message and suspect it is causing issues (i.e. the program is actually introspecting the value of these symbols), you can resolve it by implementing and registering a `SimData` class, which is like a `SimProcedure` but for data. Simulated data. Very cool.

A `SimData` can effectively specify some data that must be used to provide an unresolved import symbol. It has a number of mechanisms to make this more useful, including the ability to specify relocations and subdependencies.

Look at the `SimData` `cle.backends.externs.simdata.SimData` class reference and the existing `SimData` subclasses for guidelines on how to do this.

6.4 Writing Analyses

An analysis can be created by subclassing the `angr.Analysis` class. In this section, we'll create a mock analysis to show off the various features. Let's start with something simple:

```
>>> import angr

>>> class MockAnalysis(angr.Analysis):
...     def __init__(self, option):
...         self.option = option

>>> angr.AnalysesHub.register_default('MockAnalysis', MockAnalysis) # register the class␣
↪with angr's global analysis list
```

This is a very simple analysis – it takes an option, and stores it. Of course, it's not useful, but this is just a demonstration.

Let's see how to run our new analysis:

```
>>> proj = angr.Project("/bin/true")
>>> mock = proj.analyses.MockAnalysis('this is my option')
>>> assert mock.option == 'this is my option'
```

6.4.1 Working with projects

Via some Python magic, your analysis will automatically have the project upon which you are running it under the `self.project` property. Use this to interact with your project and analyze it!

```
>>> class ProjectSummary(angr.Analysis):
...     def __init__(self):
...         self.result = 'This project is a %s binary with an entry point at %#x.' %_
↪(self.project.arch.name, self.project.entry)

>>> angr.AnalysesHub.register_default('ProjectSummary', ProjectSummary)
>>> proj = angr.Project("/bin/true")

>>> summary = proj.analyses.ProjectSummary()
>>> print(summary.result)
This project is a AMD64 binary with an entry point at 0x401410.
```

6.4.2 Analysis Resilience

Sometimes, your (or our) code might suck and analyses might throw exceptions. We understand, and we also understand that oftentimes a partial result is better than nothing. This is specifically true when, for example, running an analysis on all of the functions in a program. Even if some of the functions fails, we still want to know the results of the functions that do not.

To facilitate this, the `Analysis` base class provides a resilience context manager under `self._resilience`. Here's an example:

```
>>> class ComplexFunctionAnalysis(angr.Analysis):
...     def __init__(self):
...         self._cfg = self.project.analyses.CFG()
...         self.results = { }
...         for addr, func in self._cfg.function_manager.functions.items():
...             with self._resilience():
...                 if addr % 2 == 0:
...                     raise ValueError("can't handle functions at even addresses")
...                 else:
...                     self.results[addr] = "GOOD"
```

The context manager catches any exceptions thrown and logs them (as a tuple of the exception type, message, and traceback) to `self.errors`. These are also saved and loaded when the analysis is saved and loaded (although the traceback is discarded, as it is not picklable).

You can tune the effects of the resilience with two optional keyword parameters to `self._resilience()`.

The first is `name`, which affects where the error is logged. By default, errors are placed in `self.errors`, but if `name` is provided, then instead the error is logged to `self.named_errors`, which is a dict mapping `name` to a list of all the errors that were caught under that name. This allows you to easily tell where thrown without examining its traceback.

The second argument is `exception`, which should be the type of the exception that `resilience` should catch. This defaults to `Exception`, which handles (and logs) almost anything that could go wrong. You can also pass a tuple of exception types to this option, in which case all of them will be caught.

Using `resilience` has a few advantages:

1. Your exceptions are gracefully logged and easily accessible afterwards. This is really nice for writing testcases.

2. When creating your analysis, the user can pass `fail_fast=True`, which transparently disable the resilience, which is really nice for manual testing.
3. It's prettier than having `try except` everywhere.

Have fun with analyses! Once you master the rest of angr, you can use analyses to understand anything computable!

6.5 Scripting angr management

Warning: Please note that the documentation and the API for angr management are highly in-flux. You will need to spend time reading the source code. Grep is your friend. If you have questions, please ask in the angr slack.

If you build something which uses an API and you want to make sure it doesn't break, you can contribute a testcase for the API!

This codebase is absolutely filled to the brim with one-off hacks. If you see some code and think, "hm, that doesn't seem like an extensible or best-practices way to code that", you're probably right. Cleaning up angr management's code is a top priority for us, so if you have some ideas to fix these sorts of issues, please let us know, either in an issue or a pull request!

6.5.1 The console, and the basic objects

angr management opens with an IPython console ready for input. This console has in its namespace several objects which are important for manipulating angr management and its data.

- First, the `main_window`. This is the `QMainWindow` instance for the application. It contains basic functions that correspond to top-level buttons, such as loading a binary.
- Next, the `workspace`. This is a light object which coordinates the UI elements and manages the tabbed environment. You can use it to access any analysis-related GUI element, such as the disassembly view.
- Finally, the `instance`. This is angr management's data model. It contains mechanisms for synchronizing components on shared data sources, as well as logic for creating long-running jobs.

`workspace` is also available as an attribute on `main_window` and `instance` is available as an attribute on `workspace`. If you are programming in a namespace where none of these objects are available, you can import the `angrmanagement`. `logic.GlobalInfo` object, which contains a reference to `main_window`.

6.5.2 The ObjectContainer

angr management uses a class called `ObjectContainer` to implement a pub-sub model and synchronize changing object references. Let's use `instance.project` as an example. This is an `ObjectContainer` that contains the current project. You can use it in every way that you would normally use a project - you can access `project.factory`, `project.kb`, etc. However, it also has two very important features that are helpful for building UIs.

First, the pub-sub model. You can subscribe to changes to this object by calling `instance.project.am_subscribe(callback)`. Then, you can notify listeners of changes by calling `instance.project.am_event()`. Note that events are NEVER automatically triggered - you must call `am_event` in order to trigger the callbacks. One useful feature of this model is that you can provide arbitrary keyword arguments to `am_event`, and they will be passed on to each callback. This means that you should always have your callbacks take `**kwargs` in order to account for unknown parameters. This feature is particularly useful to prevent feedback loops - if you ever find yourself in a situation where you need to broadcast an event from your callback, you can add an argument that you can use as a flag not to recurse any further.

Next, object reference mutability. Let's say you have a widget that displays information about the project. Following the principle of least access, you should only provide as much information as is necessary to do the job - in this case, just the project object. If you provide the basic project object, this will cause issues when a new project is loaded. Notably, there will be a dangling reference held to the original project, preventing it from being garbage collected, and the widget will not update, continuing to show the old project's information. Now, if you provide the project's `ObjectContainer`, a new project can be created and inserted into the container and the reference will instantly be available to your widget. If you ever wanted to load a new project yourself, all you have to do is assign to `instance.project.am_obj` and then send off an event. Combined with the event publication model, this provides an efficient way to build responsive UIs that follow the principle of least access.

One important way that you can't use the object container the same way that you would a normal object is that `is None` will obviously not work. To resolve this, you can use `instance.project.am_none` - this will be `True` when no project is loaded.

One interesting feature of the `ObjectContainer` is that they can nest. If you have a container which contains a container which contains an object, any events sent to the inner container will also be sent to subscribers to the outer container. This allows patterns such as the list of `SimStates` actually containing a list of `ObjectContainers` which contain states, and the "current state" container actually contains one of these containers. The result of this is that UI elements can either subscribe to the current state, no matter

A full list of standard `ObjectContainers` that can be found in the `instance.__init__` method. There are more containers floating around for synchronizing on non-global elements - for example, the current state of the disassembly view is synchronized through its `InfoDock` object. Given a disassembly view instance, you can subscribe to, for example, its current selected instructions through `view.infodock.selected_insns`.

6.5.3 Manipulating UI elements

The `workspace` contains methods to manipulate UI elements. Notably, you can manipulate all open tabs with the `workspace.view_manager` reference. Additionally, you can pass any sort of object you like to `workspace.viz()` and it will attempt to visualize the object in the current window.

6.5.4 Writing plugins

angr management has a very flexible plugin framework. A plugin is a Python file containing a subclass of `angrmanagement.plugins.BasePlugin`. Plugin files will be automatically loaded from the `plugins` module of angr management, and also from `~/.local/share/angr-management/plugins`. These paths are configurable through the program configuration, but at the time of writing, this is not exposed in the UI.

The best way to see the tools you can use while building a plugin is to read the `plugin base class source code`. Any method or attribute can be overridden from a base class and will be automatically called on relevant events.

6.5.5 Writing tests

Look at the `existing tests` for examples. Generally, you can test UI components by creating the component and driving input to it via `QTest`. You can create a headless `MainWindow` instance by passing `show=False` to its constructor - this will also get you access to a `workspace` and an `instance`.

ANGR EXAMPLES

To help you get started with [angr](#), we’ve created several examples. We’ve tried to organize them into major categories, and briefly summarize that each example will expose you to. Enjoy!

If you want a high-level cheatsheet of the “techniques” used in the examples, see [the angr strategies cheatsheet](#) by Florent Bordinon.

To jump to a specific category:

- *Introduction* - examples showing off the very basics of angr’s functionality
- *Reversing* - examples showing angr being used in reverse engineering tasks
- *Vulnerability Discovery* - examples of angr being used to search for vulnerabilities
- *Exploitation* - examples of angr being used as an exploitation assistance tool

7.1 Introduction

These are some introductory examples to give an idea of how to use angr’s API.

7.1.1 Fauxware

This is a basic script that explains how to use angr to symbolically execute a program and produce concrete input satisfying certain conditions.

Binary, source, and script are found [here](#).

7.2 Reversing

These are examples that use angr to solve reverse engineering challenges. There are a lot of these. We’ve chosen the most unique ones, and relegated the rest to the CTF Challenges section below.

7.2.1 Beginner reversing example: little_engine

Script author: Michael Reeves (github: @mastermjr)
 Script runtime: 3 min 26 seconds (206 seconds)
 Concepts presented:
 stdin constraining, concrete optimization with Unicorn

This challenge is similar to the csaw challenge below, however the reversing is much more simple. The original code, solution, and writeup for the challenge can be found at the b0llers github [here](#).

The angr solution script is [here](#) and the binary is [here](#).

7.2.2 Whitehat CTF 2015 - Crypto 400

Script author: Yan Shoshitaishvili (github: @Zardus)
 Script runtime: 30 seconds
 Concepts presented: statically linked binary (manually hooking with function summaries),
 ↪commandline argument, partial solutions

We solved this crackme with angr's help. The resulting script will help you understand how angr can be used for crackme *assistance*, not a full-out solve. Since angr cannot solve the actual crypto part of the challenge, we use it just to reduce the keyspace, and brute-force the rest.

You can find this script [here](#) and the binary [here](#).

7.2.3 CSAW CTF 2015 Quals - Reversing 500, "wyvern"

Script author: Audrey Dutcher (github: @rhemot)
 Script runtime: 15 mins
 Concepts presented: stdin constraining, concrete optimization with Unicorn

angr can outright solve this challenge with very little assistance from the user. The script to do so is [here](#) <https://github.com/angr/angr-examples/tree/master/examples/csaw_wyvern/solve.py>_ and the binary is [here](#).

7.2.4 TUMCTF 2016 - zwiebel

Script author: Fish
 Script runtime: 2 hours 31 minutes with pypy and Unicorn - expect much longer with
 ↪CPython only
 Concepts presented: self-modifying code support, concrete optimization with Unicorn

This example is of a self-unpacking reversing challenge. This example shows how to enable Unicorn support and self-modification support in angr. Unicorn support is essential to solve this challenge within a reasonable amount of time - simulating the unpacking code symbolically is *very* slow. Thus, we execute it concretely in unicorn/qemu and only switch into symbolic execution when needed.

You may refer to other writeup about the internals of this binary. I didn't reverse too much since I was pretty confident that angr is able to solve it :-)

The long-term goal of optimizing angr is to execute this script within 10 minutes. Pretty ambitious :P

Here is the [binary](#) and the [script](#).

7.2.5 FlareOn 2015 - Challenge 5

Script author: Adrian Tang (github: @tangabc)
Script runtime: 2 mins 10 secs
Concepts presented: Windows support

This is another [reversing challenge](#) from the FlareOn challenges.

“The challenge is designed to teach you about PCAP file parsing and traffic decryption by reverse engineering an executable used to generate it. This is a typical scenario in our malware analysis practice where we need to figure out precisely what the malware was doing on the network”

For this challenge, the author used `angr` to represent the desired encoded output as a series of constraints for the SAT solver to solve for the input.

For a detailed write-up please visit the author’s post [here](#) and you can also find the solution from the FireEye [here](#)

7.2.6 Ocf qual's 2016 - trace

Script author: WGH (wgh@bushwhackers.ru)
Script runtime: 1 min 50 secs (CPython 2.7.10), 1 min 12 secs (PyPy 4.0.1)
Concepts presented: guided symbolic tracing

In this challenge we’re given a text file with trace of a program execution. The file has two columns, address and instruction executed. So we know all the instructions being executed, and which branches were taken. But the initial data is not known.

Reversing reveals that a buffer on the stack is initialized with known constant string first, then an unknown string is appended to it (the flag), and finally it’s sorted with some variant of quicksort. And we need to find the flag somehow.

`angr` easily solves this problem. We only have to direct it to the right direction at every branch, and the solver finds the flag at a glance.

Files are [here](#).

7.2.7 ASIS CTF Finals 2015 - license

Script author: Fish Wang (github: @ltfish)
Script runtime: 3.6 sec
Concepts presented: using the filesystem, manual symbolic summary execution

This is a crackme challenge that reads a license file. Rather than hooking the read operations of the flag file, we actually pass in a filesystem with the correct file created.

Here is the [binary](#) and the [script](#).

7.2.8 DEFCON Quals 2017 - Crackme2000

Script author: Shellphish
Script runtime: varies, but on the order of seconds
Concepts presented: automated reverse engineering

DEFCON Quals had a whole category for automatic reversing in 2017. Our scripts are [here](#).

7.3 Vulnerability Discovery

These are examples of angr being used to identify vulnerabilities in binaries.

7.3.1 Beginner vulnerability discovery example: strcpy_find

Script author: Kyle Ossinger (github: [@k0ss](#))
Concepts presented: exploration to vulnerability, programmatic find condition

This is the first in a series of “tutorial scripts” I’ll be making which use angr to find exploitable conditions in binaries. The first example is a very simple program. The script finds a path from the main entry point to `strcpy`, but **only** when we control the source buffer of the `strcpy` operation. To hit the right path, angr has to solve for a password argument, but angr solved this in less than 2 seconds on my machine using the standard Python interpreter. The script might look large, but that’s only because I’ve heavily commented it to be more helpful to beginners. The challenge binary is [here](#) and the script is [here](#).

7.3.2 CGC crash identification

Script author: Antonio Bianchi, Jacopo Corbetta
Concepts presented: exploration to vulnerability

This is a very easy binary containing a stack buffer overflow and an easter egg. CADET_00001 is one of the challenge released by DARPA for the Cyber Grand Challenge: [link](#) The binary can run in the DECREE VM: [link](#) A copy of the original challenge and the angr solution is provided [here](#) CADET_00001.adapted (by Jacopo Corbetta) is the same program, modified to be runnable in an Intel x86 Linux machine.

7.3.3 Grub “back to 28” bug

Script author: Audrey Dutcher (github: [@rhelmot](#))
Concepts presented: unusual target (custom function hooking required), use of exploration, [↪ techniques to categorize and prune the program's state space](#)

This is the demonstration presented at 32c3. The script uses angr to discover the input to crash grub’s password entry prompt.

[script](#) - [vulnerable module](#)

7.4 Exploitation

These are examples of angr's use as an exploitation assistance engine.

7.4.1 Insomnihack Simple AEG

Script author: Nick Stephens (github: [@NickStephens](#))
 Concepts presented: automatic exploit generation, [global](#) symbolic data tracking

Demonstration for Insomni'hack 2016. The script is a very simple implementation of AEG.

[script](#)

7.4.2 SecuInside 2016 Quals - mbrainfuzz - symbolic exploration for exploitability conditions

Script author: nsr (nsr@tasteless.eu)
 Script runtime: [~15](#) seconds per binary
 Concepts presented: symbolic exploration guided by static analysis, using the CFG

Originally, a binary was given to the ctf-player by the challenge-service, and an exploit had to be crafted automatically. Four sample binaries, obtained during the ctf, are included in the example. All binaries follow the same format; the command-line argument is validated in a bunch of functions, and when every check succeeds, a `memcpy()` resulting into a stack-based buffer overflow is executed. angr is used to find the way through the binary to the `memcpy()` and to generate valid inputs to every checking function individually.

The sample binaries and the script are located [here](#) and additional information be found at the author's [Write-Up](#).

7.4.3 SECCON 2016 Quals - ropsynth

Script author: Yan Shoshitaishvili (github [@zardus](#)) [and](#) Nilo Redini
 Script runtime: [2](#) minutes
 Concepts presented: automatic ROP chain generation, binary modification, reasoning over [L](#)
[↔](#)constraints, reasoning over action history

This challenge required the automatic generation of ropchains, with the twist that every ropchain was succeeded by an input check that, if not passed, would terminate the application. We used symbolic execution to recover those checks, removed the checks from the binary, used angr to build the ropchains, and instrumented them with the inputs to pass the checks.

The various challenge files are located [here](#), with the actual solve script [here](#).

FREQUENTLY ASKED QUESTIONS

This is a collection of commonly-asked “how do I do X?” questions and other general questions about angr, for those too lazy to read this whole document.

If your question is of the form “how do I fix X issue after installing”, see also the Troubleshooting section of the [:ref:install instructions <Installing angr>`_](#).

8.1 Why is it named angr?

The core of angr’s analysis is on VEX IR, and when something is vexing, it makes you angry.

8.2 How should “angr” be stylized?

All lowercase, even at the beginning of sentences. It’s an anti-proper noun.

8.3 Why isn’t symbolic execution doing the thing I want?

The universal debugging technique for symbolic execution is as follows:

- Check your simulation manager for errored states. `print(simgr)` is a good place to start, and if you see anything to do with “errored”, go for `print(simgr.errored)`.
- If you have any errored states and it’s not immediately obvious what you did wrong, you can get a `pdb` shell at the crash site by going `simgr.errored[n].debug()`.
- If no state has reached an address you care about, you should check the path each state has gone down: `import pprint; pprint.pprint(state.history.descriptions.hardcopy)`. This will show you a high-level summary of what the symbolic execution engine did at each step along the state’s history. You will be able to see from this a basic block trace and also a list of executed simprocedures. If you’re using unicorn engine, you can check `state.history.bbl_addrs.hardcopy` to see what blocks were executed in each invocation of unicorn.
- If a state is going down the wrong path, you can check what constraints caused it to go that way: `print(state.solver.constraints)`. If a state has just gone past a branch, you can check the most recent branch condition with `state.history.events[-1]`.

8.4 How can I get diagnostic information about what angr is doing?

angr uses the standard logging module for logging, with every package and submodule creating a new logger.

The simplest way to get debug output is the following:

```
import logging
logging.getLogger('angr').setLevel('DEBUG')
```

You may want to use INFO or whatever else instead. By default, angr will enable logging at the WARNING level.

Each angr module has its own logger string, usually all the Python modules above it in the hierarchy, plus itself, joined with dots. For example, `angr.analyses.cfg`. Because of the way the Python logging module works, you can set the verbosity for all submodules in a module by setting a verbosity level for the parent module. For example, `logging.getLogger('angr.analyses').setLevel('INFO')` will make the CFG, as well as all other analyses, log at the INFO level.

8.5 Why is angr so slow?

It's complicated! *Optimization considerations*

8.6 How do I find bugs using angr?

It's complicated! The easiest way to do this is to define a “bug condition”, for example, “the instruction pointer has become a symbolic variable”, and run symbolic exploration until you find a state matching that condition, then dump the input as a testcase. However, you will quickly run into the state explosion problem. How you address this is up to you. Your solution may be as simple as adding an avoid condition or as complicated as implementing CMU's MAYHEM system as an Exploration Technique.

8.7 Why did you choose VEX instead of another IR (such as LLVM, REIL, BAP, etc)?

We had two design goals in angr that influenced this choice:

1. angr needed to be able to analyze binaries from multiple architectures. This mandated the use of an IR to preserve our sanity, and required the IR to support many architectures.
2. We wanted to implement a binary analysis engine, not a binary lifter. Many projects start and end with the implementation of a lifter, which is a time consuming process. We needed to take something that existed and already supported the lifting of multiple architectures.

Searching around the internet, the major choices were:

- LLVM is an obvious first candidate, but lifting binary code to LLVM cleanly is a pain. The two solutions are either lifting to LLVM through QEMU, which is hackish (and the only implementation of it seems very tightly integrated into S2E), or McSema, which only supported x86 at the time but has since gone through a rewrite and gotten support for x86-64 and aarch64.
- TCG is QEMU's IR, but extracting it seems very daunting as well and documentation is very scarce.

- REIL seems promising, but there is no standard reference implementation that supports all the architectures that we wanted. It seems like a nice academic work, but to use it, we would have to implement our own lifters, which we wanted to avoid.
- BAP was another possibility. When we started work on angr, BAP only supported lifting x86 code, and up-to-date versions of BAP were only available to academic collaborators of the BAP authors. These were two deal-breakers. BAP has since become open, but it still only supports x86_64, x86, and ARM.
- VEX was the only choice that offered an open library and support for many architectures. As a bonus, it is very well documented and designed specifically for program analysis, making it very easy to use in angr.

While angr uses VEX now, there's no fundamental reason that multiple IRs cannot be used. There are two parts of angr, outside of the `angr.engines.vex` package, that are VEX-specific:

- the jump labels (i.e., the `Ijk_Ret` for returns, `Ijk_Call` for calls, and so forth) are VEX enums.
- VEX treats registers as a memory space, and so does angr. While we provide accesses to `state.regs.rax` and friends, on the backend, this does `state.registers.load(8, 8)`, where the first 8 is a VEX-defined offset for `rax` to the register file.

To support multiple IRs, we'll either want to abstract these things or translate their labels to VEX analogues.

8.8 Why are some ARM addresses off-by-one?

In order to encode THUMB-ness of an ARM code address, we set the lowest bit to one. This convention comes from LibVEX, and is not entirely our choice! If you see an odd ARM address, that just means the code at `address - 1` is in THUMB mode.

8.9 How do I serialize angr objects?

`Pickle` will work. However, Python will default to using an extremely old pickle protocol that does not support more complex Python data structures, so you must specify a [more advanced data stream format](#). The easiest way to do this is `pickle.dumps(obj, -1)`.

8.10 What does `UnsupportedIR0pError("floating point support disabled")` mean?

This might crop up if you're using a CGC analysis such as driller or rex. Floating point support in angr has been disabled in the CGC analyses for a tight-knit nebula of reasons:

- Libvex's representation of floating point numbers is imprecise - it converts the 80-bit extended precision format used by the x87 for computation to 64-bit doubles, making it impossible to get precise results
- There is very limited implementation support in angr for the actual primitive operations themselves as reported by libvex, so you will often get a less friendly "unsupported operation" error if you go too much further
- For what operations are implemented, the basic optimizations that allow tractability during symbolic computation (AST deduplication, operation collapsing) are not implemented for floating point ops, leading to gigantic ASTs
- There are memory corruption bugs in z3 that get triggered frighteningly easily when you're using huge workloads of mixed floating point and bitvector ops. We haven't been able to get a testcase that doesn't involve "just run angr" for the z3 guys to investigate.

Instead of trying to cope with all of these, we have simply disabled floating point support in the symbolic execution engine. To allow for execution in the presence of floating point ops, we have enabled an exploration technique called the https://github.com/angr/angr/blob/master/angr/exploration_techniques/oppologist.py <oppologist> that is supposed to catch these issues, concretize their inputs, and run the problematic instructions through qemu via unicorn engine, allowing execution to continue. The intuition is that the specific values of floating point operations don't typically affect the exploitation process.

If you're seeing this error and it's terminating the analysis, it's probably because you don't have unicorn installed or configured correctly. If you're seeing this issue just in a log somewhere, it's just the oppologist kicking in and you have nothing to worry about.

8.11 Why is angr's CFG different from IDA's?

Two main reasons:

- IDA does not split basic blocks at function calls. angr will, because they are a form of control flow and basic blocks end at control flow instructions. You generally do not need the supergraph for performing automated analyses.
- IDA will split basic blocks if another block jumps into the middle of it. This is called basic block normalization, and angr does not do it by default since it is unnecessary for most static analyses. You may enable it by passing `normalize=True` to the CFG analysis.

8.12 Why do I get incorrect register values when reading from a state during a SimInspect breakpoint?

libVEX will eliminate duplicate register writes within a single basic block when optimizations are enabled. Turn off IR optimization to make everything look right at all times.

In the case of the instruction pointer, libVEX will frequently omit mid-block writes even when optimizations are disabled. In this case, you should use `state.scratch.ins_addr` to get the current instruction pointer.

9.1 Cheatsheet

The following cheatsheet aims to give an overview of various things you can do with angr and act as a quick reference to check the syntax for something without having to dig through the deeper docs.

9.1.1 General getting started

Some useful imports

```
import angr #the main framework
import claripy #the solver engine
```

Loading the binary

```
proj = angr.Project("/path/to/binary", auto_load_libs=False) # auto_load_libs False for
↳ improved performance
```

9.1.2 States

Create a SimState object

```
state = proj.factory.entry_state()
```

9.1.3 Simulation Managers

Generate a simulation manager object

```
simgr = proj.factory.simulation_manager(state)
```

9.1.4 Exploring and analysing states

Choosing a different Exploring strategy

```
simgr.use_technique(angr.exploration_techniques.DFS())
```

Symbolically execute until we find a state satisfying our find= and avoid= parameters

```
avoid_addr = [0x400c06, 0x400bc7]
find_addr = 0x400c10d
simgr.explore(find=find_addr, avoid=avoid_addr)
```

```
found = simgr.found[0] # A state that reached the find condition from explore
found.solver.eval(sym_arg, cast_to=bytes) # Return a concrete string value for the sym_
↳ arg to reach this state
```

Symbolically execute until lambda expression is True

```
simgr.step(until=lambda sm: sm.active[0].addr >= first_jump)
```

This is especially useful with the ability to access the current STDOUT or STDERR (1 here is the File Descriptor for STDOUT)

```
simgr.explore(find=lambda s: "correct" in s.posix.dumps(1))
```

Memory Managment on big searches (Auto Drop Stashes):

```
simgr.explore(find=find_addr, avoid=avoid_addr, step_func=lambda lsm: lsm.drop(stash=
↳ 'avoid'))
```

Manually Exploring

```
simgr.step(step_func=step_func, until=lambda lsm: len(sm.found) > 0)

def step_func(lsm):
    lsm.stash(filter_func=lambda state: state.addr == 0x400c06, from_stash='active', to_
↳ stash='avoid')
    lsm.stash(filter_func=lambda state: state.addr == 0x400bc7, from_stash='active', to_
↳ stash='avoid')
    lsm.stash(filter_func=lambda state: state.addr == 0x400c10, from_stash='active', to_
↳ stash='found')
    return lsm
```

Enable Logging output from Simulation Manager:

```
import logging
logging.getLogger('angr.sim_manager').setLevel(logging.DEBUG)
```

Stashes

Move Stash:

```
simgr.stash(from_stash="found", to_stash="active")
```

Drop Stashes:

```
simgr.drop(stash="avoid")
```

9.1.5 Constraint Solver (claripy)

Create symbolic object

```
sym_arg_size = 15 #Length in Bytes because we will multiply with 8 later
sym_arg = claripy.BVS('sym_arg', 8*sym_arg_size)
```

Restrict sym_arg to typical char range

```
for byte in sym_arg.chop(8):
    initial_state.add_constraints(byte >= '\x20') # ' '
    initial_state.add_constraints(byte <= '\x7e') # '~'
```

Create a state with a symbolic argument

```
argv = [proj.filename]
argv.append(sym_arg)
state = proj.factory.entry_state(args=argv)
```

Use argument for solving:

```
sym_arg = angr.claripy.BVS("sym_arg", flag_size * 8)
argv = [proj.filename]
argv.append(sym_arg)
initial_state = proj.factory.full_init_state(args=argv, add_options=angr.options.unicorn,
→ remove_options={angr.options.LAZY_SOLVES})
```

9.1.6 FFI and Hooking

Calling a function from ipython

```
f = proj.factory.callable(address)
f(10)
x=claripy.BVS('x', 64)
f(x) #TODO: Find out how to make that result readable
```

If what you are interested in is not directly returned because for example the function returns the pointer to a buffer you can access the state after the function returns with

```
>>> f.result_state
<SimState @ 0x1000550>
```

Hooking

There are already predefined hooks for libc functions (useful for statically compiled libraries)

```
proj = angr.Project('/path/to/binary', use_sim_procedures=True)
proj.hook(addr, angr.SIM_PROCEDURES['libc']['atoi']())
```

Hooking with Simprocedure:

```
class fixpid(angr.SimProcedure):
    def run(self):
        return 0x30

proj.hook(0x4008cd, fixpid())
```

9.1.7 Other useful tricks

Drop into an ipython if a ctrl+c is received (useful for debugging scripts that are running forever)

```
import signal
def killmyself():
    os.system('kill %d' % os.getpid())
def sigint_handler(signum, frame):
    print 'Stopping Execution for Debug. If you want to kill the program issue: ^C'
    killmyself()
    if not "IPython" in sys.modules:
        import IPython
        IPython.embed()

signal.signal(signal.SIGINT, sigint_handler)
```

Get the calltrace of a state to find out where we got stuck

```
state = simgr.active[0]
print state.callstack
```

Get a basic block

```
block = proj.factory.block(address)
block.capstone.pp() # Capstone object has pretty print and other data about the block
↳ disassembly
block.vex.pp()      # Print vex representation
```

9.1.8 State manipulation

Write to state:

```
aaaa = claripy.BVV(0x41414141, 32) # 32 = Bits
state.memory.store(0x6021f2, aaaa)
```

Read Pointer to Pointer from Frame:

```
poi1 = new_state.solver.eval(new_state.regs.rbp)-0x10
poi1 = new_state.mem[poi1].long.concrete
poi1 += 0x8
ptr1 = new_state.mem[poi1].long.concrete
```

Read from State:

```
key = []
for i in range(38):
    key.append(extractkey.mem[0x602140 + i*4].int.concrete)
```

Alternatively, the below expression is equivalent

```
key = extractkey.mem[0x602140].int.array(38).concrete
```

9.1.9 Debugging angr

Set Breakpoint at every Memory read/write:

```
new_state.inspect.b('mem_read', when=angr.BP_AFTER, action=debug_funcRead)
def debug_funcRead(state):
    print 'Read', state.inspect.mem_read_expr, 'from', state.inspect.mem_read_address
```

Set Breakpoint at specific Memory location:

```
new_state.inspect.b('mem_write', mem_write_address=0x6021f1, when=angr.BP_AFTER,
↳ action=debug_funcWrite)
```

9.2 List of Claripy Operations

9.2.1 Arithmetic and Logic

Name	Description	Example
LShR	Logically shifts an expression to the right. (the default shifts are arithmetic)	<code>x.LShR(10)</code>
RotateLeft	Rotates an expression left	<code>x.RotateLeft(8)</code>
RotateRight	Rotates an expression right	<code>x.RotateRight(8)</code>
And	Logical And (on boolean expressions)	<code>solver.And(x == y, x > 0)</code>
Or	Logical Or (on boolean expressions)	<code>solver.Or(x == y, y < 10)</code>
Not	Logical Not (on a boolean expression)	<code>solver.Not(x == y)</code> is the same as <code>x != y</code>
If	An If-then-else	Choose the maximum of two expressions: <code>solver.If(x > y, x, y)</code>
ULE	Unsigned less than or equal to	Check if x is less than or equal to y: <code>x.ULE(y)</code>
ULT	Unsigned less than	Check if x is less than y: <code>x.ULT(y)</code>
UGE	Unsigned greater than or equal to	Check if x is greater than or equal to y: <code>x.UGE(y)</code>
UGT	Unsigned greater than	Check if x is greater than y: <code>x.UGT(y)</code>
SLE	Signed less than or equal to	Check if x is less than or equal to y: <code>x.SLE(y)</code>
SLT	Signed less than	Check if x is less than y: <code>x.SLT(y)</code>
SGE	Signed greater than or equal to	Check if x is greater than or equal to y: <code>x.SGE(y)</code>
SGT	Signed greater than	Check if x is greater than y: <code>x.SGT(y)</code>

Todo: Add the floating point ops

9.2.2 Bitvector Manipulation

Name	Description	Example
SignExt	Pad a bitvector on the left with n sign bits	<code>x.sign_extend(n)</code>
ZeroExt	Pad a bitvector on the left with n zero bits	<code>x.zero_extend(n)</code>
Extract	Extracts the given bits (zero-indexed from the <i>right</i> , inclusive) from an expression.	Extract the least significant byte of x: <code>x[7:0]</code>
Concat	Concatenates any number of expressions together into a new expression.	<code>x.concat(y, ...)</code>

9.2.3 Extra Functionality

There's a bunch of prepackaged behavior that you *could* implement by analyzing the ASTs and composing sets of operations, but here's an easier way to do it:

- You can chop a bitvector into a list of chunks of `n` bits with `val.chop(n)`
- You can endian-reverse a bitvector with `x.reversed`
- You can get the width of a bitvector in bits with `val.length`
- You can test if an AST has any symbolic components with `val.symbolic`
- You can get a set of the names of all the symbolic variables implicated in the construction of an AST with `val.variables`

9.3 List of State Options

9.3.1 State Modes

These may be enabled by passing `mode=xxx` to a state constructor.

Mode name	Description
<code>symbolic</code>	The default mode. Useful for most emulation and analysis tasks.
<code>symbolic_appx</code>	Symbolic mode, but enables approximations for constraint solving.
<code>static</code>	A preset useful for static analysis. The memory model becomes an abstract region-mapping system, “fake return” successors skipping calls are added, and more.
<code>fastpath</code>	A preset for extremely lightweight static analysis. Executing will skip all intensive processing to give a quick view of the behavior of code.
<code>tracing</code>	A preset for attempting to execute concretely through a program with a given input. Enables unicorn, enables resilience options, and will attempt to emulate access violations correctly.

9.3.2 Option Sets

These are sets of options, found as `angr.options.xxx`.

Set name	Description
<code>common_o</code>	Options necessary for basic execution
<code>symbolic</code>	Options necessary for basic symbolic execution
<code>resilien</code>	Options that harden angr's emulation against unsupported operations, attempting to carry on by treating the result as an unconstrained symbolic value and logging the occasion to <code>state.history.events</code> .
<code>refs</code>	Options that cause angr to keep a log of all the memory, register, and temporary references complete with dependency information in <code>history.actions</code> . This option consumes a lot of memory, so be careful!
<code>approxim</code>	Options that enable approximations of constraint solves via value-set analysis instead of calling into z3
<code>simplifi</code>	Options that cause data to be run through z3's simplifiers before it reaches memory or register storage
<code>unicorn</code>	Options that enable the unicorn engine for executing on concrete data

9.3.3 Options

These are individual option objects, found as `angr.options.XXX`.

Option name	Description
ABSTRACT_MEMORY	Use <code>SimAbstractMemory</code> to model memory as discrete regions
ABSTRACT_SOLVER	Allow splitting constraint sets during simplification
ACTION_DEPS	Track dependencies in <code>SimActions</code>
APPROXIMATE_GUARDS	Use VSA when evaluating guard conditions
APPROXIMATE_MEMORY_INDICES	Use VSA when evaluating memory indices
APPROXIMATE_MEMORY_SIZES	Use VSA when evaluating memory load/store sizes
APPROXIMATE_SATISFIABILITY	Use VSA when evaluating state satisfiability
AST_DEPS	Enables dependency tracking for all claripy ASTs
AUTO_REFS	An internal option used to track dependencies in <code>SimProcedures</code>
AVOID_MULTIVALUED_READS	Return a symbolic value without touching memory for any read that has a symbolic address
AVOID_MULTIVALUED_WRITES	Do not perform any write that has a symbolic address
BEST_EFFORT_MEMORY_STORING	Handle huge writes of symbolic size by pretending they are actually smaller
BREAK_SIRSB_END	Debug: trigger a breakpoint at the end of each block
BREAK_SIRSB_START	Debug: trigger a breakpoint at the start of each block
BREAK_SIRSTMT_END	Debug: trigger a breakpoint at the end of each IR statement
BREAK_SIRSTMT_START	Debug: trigger a breakpoint at the start of each IR statement
BYPASS_ERRORED_IRCCALL	Treat clean helpers that fail with errors as returning unconstrained symbolic values
BYPASS_ERRORED_IROP	Treat operations that fail with errors as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_IRCCALL	Treat unsupported clean helpers as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_IRDIRTY	Treat unsupported dirty helpers as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_IREXPR	Treat unsupported IR expressions as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_IROP	Treat unsupported operations as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_IRSTMT	Treat unsupported IR statements as returning unconstrained symbolic values
BYPASS_UNSUPPORTED_SYSCALL	Treat unsupported syscalls as returning unconstrained symbolic values
BYPASS_VERITESTING_EXCEPTIONS	Discard emulation errors during veritesting
CACHELESS_SOLVER	enable <code>SolverCacheless</code>
CALLESS	Emulate call instructions as an unconstraining of the return value register
CGC_ENFORCE_FD	CGC: make sure all reads and writes go to <code>stdin</code> and <code>stdout</code> , respectively
CGC_NON_BLOCKING_FDS	CGC: always report “data available” in <code>fdwait</code>
CGC_NO_SYMBOLIC_RECEIVE_LENGTH	CGC: always read the maximum amount of data requested in the receive syscall
COMPOSITE_SOLVER	Enable <code>SolverComposite</code> for independent constraint set optimization
CONCRETIZE	Concretize all symbolic expressions encountered during emulation
CONCRETIZE_SYMBOLIC_FILE_READ_SIZES	Concretize the sizes of file reads
CONCRETIZE_SYMBOLIC_WRITE_SIZES	Concretize the sizes of symbolic writes to memory
CONSERVATIVE_READ_STRATEGY	Do not use <code>SimConcretizationStrategyAny</code> for reads; in case of read address concretization
CONSERVATIVE_WRITE_STRATEGY	Do not use <code>SimConcretizationStrategyAny</code> for writes; in case of write address concretization
CONSTRAINT_TRACKING_IN_SOLVER	Set <code>track=True</code> for making claripy Solvers; enable use of <code>unsat_core</code>
COW_STATES	Copy states instead of mutating the initial state directly
DOWNSIZE_Z3	Downsize the claripy solver whenever possible to save memory
DO_CCALLS	Perform IR clean calls
DO_GETS	Perform IR register reads
DO_LOADS	Perform IR memory loads
DO_OPS	Perform IR computation operations
DO_PUTS	Perform IR register writes
DO_RET_EMULATION	For each <code>Ijk_Call</code> successor, add a corresponding <code>Ijk_FakeRet</code> successor
DO_STORES	Perform IR memory stores
EFFICIENT_STATE_MERGING	Keep in memory any state that might be a common ancestor in a merge

Option name	Description
ENABLE_NX	When in conjunction with STRICT_PAGE_ACCESS, raise a SimSegfaultException on
EXCEPTION_HANDLING	Ask all SimExceptions raised during execution to be handled by the SimOS
FAST_MEMORY	Use SimFastMemory for memory storage
FAST_REGISTERS	Use SimFastMemory for register storage
INITIALIZE_ZERO_REGISTERS	Treat the initial value of registers as zero instead of unconstrained symbolic
KEEP_IP_SYMBOLIC	Don't try to concretize successor states with symbolic instruction pointers
KEEP_MEMORY_READS_DISCRETE	In abstract memory, handle failed loads by returning a DCIS?
LAZY_SOLVES	Don't check satisfiability until absolutely necessary
MEMORY_SYMBOLIC_BYTES_MAP	Maintain a mapping of symbolic variable to which memory address it "really" corres
NO_SYMBOLIC_JUMP_RESOLUTION	Do not attempt to flatten symbolic-ip successors into discrete targets
NO_SYMBOLIC_SYSCALL_RESOLUTION	Do not attempt to flatten symbolic-syscall-number successors into discrete targets
OPTIMIZE_IR	Use LibVEX's optimization
REGION_MAPPING	Maintain a mapping of symbolic variable to which memory region it corresponds to,
REPLACEMENT_SOLVER	Enable SolverReplacement
REVERSE_MEMORY_HASH_MAP	Maintain a mapping from AST hash to which addresses it is present in
REVERSE_MEMORY_NAME_MAP	Maintain a mapping from symbolic variable name to which addresses it is present in,
SIMPLIFY_CONSTRAINTS	Run added constraints through z3's simplification
SIMPLIFY_EXIT_GUARD	Run branch guards through z3's simplification
SIMPLIFY_EXIT_STATE	Perform simplification on all successor states generated
SIMPLIFY_EXIT_TARGET	Run jump/call/branch targets through z3's simplification
SIMPLIFY_EXPRS	Run the results of IR expressions through z3's simplification
SIMPLIFY_MEMORY_READS	Run the results of memory reads through z3's simplification
SIMPLIFY_MEMORY_WRITES	Run values stored to memory through z3's simplification
SIMPLIFY_REGISTER_READS	Run values read from registers through z3's simplification
SIMPLIFY_REGISTER_WRITES	Run values written to registers through z3's simplification
SIMPLIFY_RETs	Run values returned from SimProcedures through z3's simplification
STRICT_PAGE_ACCESS	Raise a SimSegfaultException when attempting to interact with memory in a way not
SUPER_FASTPATH	Only execute the last four instructions of each block
SUPPORT_FLOATING_POINT	When disabled, throw an UnsupportedIROPError when encountering floating point o
SYMBOLIC	Enable constraint solving?
SYMBOLIC_INITIAL_VALUES	make state.solver.Unconstrained return a symbolic value instead of zero
SYMBOLIC_TEMPS	Treat each IR temporary as a symbolic variable; treat stores to them as constraint add
SYMBOLIC_WRITE_ADDRESSES	Allow writes with symbolic addresses to be processed by concretization strategies; w
TRACK_CONSTRAINTS	When disabled, don't keep any constraints added to the state
TRACK_CONSTRAINT_ACTIONS	Keep a SimAction for each constraint added
TRACK_JMP_ACTIONS	Keep a SimAction for each jump or branch
TRACK_MEMORY_ACTIONS	Keep a SimAction for each memory read and write
TRACK_MEMORY_MAPPING	Keep track of which pages are mapped into memory and which are not
TRACK_OP_ACTIONS	Keep a SimAction for each IR operation
TRACK_REGISTER_ACTIONS	Keep a SimAction for each register read and write
TRACK_SOLVER_VARIABLES	Maintain a listing of all the variables in all the constraints in the solver
TRACK_TMP_ACTIONS	Keep a SimAction for each temporary variable read and write
TRUE_RET_EMULATION_GUARD	With DO_RET_EMULATION, add fake returns with guard condition true instead of false
UNDER_CONSTRAINED_SYMEC	Enable under-constrained symbolic execution
UNICORN	Use unicorn engine to execute symbolically when data is concrete
UNICORN_AGGRESSIVE_CONCRETIZATION	Concretize any register variable unicorn tries to access
UNICORN_HANDLE_TRANSMIT_SYSCALL	CGC: handle the transmit syscall without leaving unicorn
UNICORN_SYM_REGS_SUPPORT	Attempt to stay in unicorn even in the presence of symbolic registers by checking tha
UNICORN_THRESHOLD_CONCRETIZATION	Concretize variables if they prevent unicorn from executing too often
UNICORN_TRACK_BBL_ADDRS	Keep state.history.bbl_addrs up to date when using unicorn

Option name	Description
UNICORN_TRACK_STACK_POINTERS	Track a list of the stack pointer's value at each block in <code>state.scratch.stack_pointer</code>
UNICORN_ZEROPAGE_GUARD	Prevent unicorn from mapping the zero page into memory
UNINITIALIZED_ACCESS_AWARENESS	Broken/unused?
UNSUPPORTED_BYPASS_ZERO_DEFAULT	When using the resilience options, return zero instead of an unconstrained symbol
USE_SIMPLIFIED_CCALLS	Use a "simplified" set of ccalls optimized for specific cases
USE_SYSTEM_TIMES	In library functions and syscalls and hardware instructions accessing clock data, retrieve system times
VALIDATE_APPROXIMATIONS	Debug: When performing approximations, ensure that the approximation is sound by validating against the original expression
ZERO_FILL_UNCONSTRAINED_MEMORY	Make the value of memory read from an uninitialized address zero instead of an unconstrained value

9.4 CTF Challenge Examples

angr is very often used in CTFs. These are example scripts resulting from that use, mostly from Shellphish but also from many others.

9.4.1 ReverseMe example: HackCon 2016 - angry-reverser

Script author: Stanislas Lejay (github: [@P1kachu](#))

Script runtime: ~31 minutes

Here is the [binary](#) and the [script](#)

9.4.2 ReverseMe example: SecurityFest 2016 - fairlight

Script author: chuckleberryfinn (github: [@chuckleberryfinn](#))

Script runtime: ~20 seconds

A simple reverse me that takes a key as a command line argument and checks it against 14 checks. Possible to solve the challenge using angr without reversing any of the checks.

Here is the [binary](#) and the [script](#)

9.4.3 ReverseMe example: DEFCON Quals 2016 - baby-re

Authors David Manouchehri (github: [@Manouchehri](#)), Stanislas Lejay (github: [@P1kachu](#)) and Audrey Dutcher (github: [@rhelmot](#)).

Script runtime: 10 sec

Here is the [binary](#) and the [script](#)

9.4.4 ReverseMe example: Google CTF - Unbreakable Enterprise Product Activation (150 points)

Script 0 author: David Manouchehri (github: [@Manouchehri](#))

Script runtime: 4.5 sec

Script 1 author: Adam Van Prooyen (github: [@docileninja](#))

Script runtime: 6.7 sec

A Linux binary that takes a key as a command line argument and checks it against a series of constraints.

Challenge Description:

We need help activating this product – we’ve lost our license key :(

You’re our only hope!

Here are the binary and scripts: [script 0](#), [script_1](#)

9.4.5 ReverseMe example: EKOPARTY CTF - Fuckzing reverse (250 points)

Author: Adam Van Prooyen (github: [@docileninja](#))

Script runtime: 29 sec

A Linux binary that takes a team name as input and checks it against a series of constraints.

Challenge Description:

Hundreds of conditions to be meet, will you be able to surpass them?

Both sample binaries and the script are located [here](#) and additional information be found at the author’s [write-up](#).

9.4.6 ReverseMe example: WhiteHat Grant Prix Global Challenge 2015 - Re400

Author: Fish Wang (github: [@ltfish](#))

Script runtime: 5.5 sec

A Windows binary that takes a flag as argument, and tells you if the flag is correct or not.

“I have to patch out some checks that are difficult for angr to solve (e.g., it uses some bytes of the flag to decrypt some data, and see if those data are legit Windows APIs). Other than that, angr works really well for solving this challenge.”

The [binary](#) and the [script](#).

9.4.7 ReverseMe example: EKOPARTY CTF 2015 - rev 100

Author: Fish Wang (github: [@ltfish](#))

Script runtime: 5.5 sec

This is a painful challenge to solve with angr. I should have done things in a smarter way.

Here is the [binary](#) and the [script](#).

9.4.8 ReverseMe example: ASIS CTF Finals 2015 - fake

Author: Fish Wang (github: @ltfish)

Script runtime: 1 min 57 sec

The solution is pretty straight-forward.

The [binary](#) and the [script](#).

9.4.9 ReverseMe example: Defcamp CTF Qualification 2015 - Reversing 100

Author: Fish Wang (github: @ltfish)

angr solves this challenge with almost zero user-interference.

See the [script](#) and the [binary](#).

9.4.10 ReverseMe example: Defcamp CTF Qualification 2015 - Reversing 200

Author: Fish Wang (github: @ltfish)

angr solves this challenge with almost zero user-interference. Veritesting is required to retrieve the flag promptly.

The [script](#) and the [binary](#). It takes a few minutes to run on my laptop.

9.4.11 ReverseMe example: MMA CTF 2015 - HowToUse

Author: Audrey Dutcher (github: @rhelmot)

We solved this simple reversing challenge with angr, since we were too lazy to reverse it or run it in Windows. The resulting [script](#) shows how we grabbed the flag out of the [DLL](#).

9.4.12 CrackMe example: MMA CTF 2015 - SimpleHash

Author: Chris Salls (github: @salls)

This crackme is 95% solvable with angr, but we did have to overcome some difficulties. The [script](#) describes the difficulties that were encountered and how we worked around them. The binary can be found [here](#).

9.4.13 ReverseMe example: FlareOn 2015 - Challenge 10

Author: Fish Wang (github: @ltfish)

angr acts as a binary loader and an emulator in solving this challenge. I didn't have to load the driver onto my Windows box.

The [script](#) demonstrates how to hook at arbitrary program points without affecting the intended bytes to be executed (a zero-length hook). It also shows how to read bytes out of memory and decode as a string.

By the way, here is the [link](#) to the intended solution from FireEye.

9.4.14 ReverseMe example: FlareOn 2015 - Challenge 2

Author: Chris Salls (github: @salls)

This [reversing challenge](#) is simple to solve almost entirely with angr, and a lot faster than trying to reverse the password checking function. The script is [here](#)

9.4.15 ReverseMe example: Octf 2016 - momo

Author: Fish Wang (github: @ltfish), ocean (github: @ocean1)

This challenge is a [movfuscated](#) binary. To find the correct password after exploring the binary with Qira it is possible to understand how to find the places in the binary where every character is checked using capstone and using angr to load the [binary](#) and brute-force the single characters of the flag. Be aware that the [script](#) is really slow. Runtime: > 1 hour.

9.4.16 CrackMe example: 9447 CTF 2015 - Reversing 330, “nobranch”

Author: Audrey Dutcher (github: @rhelmot)

angr cannot currently solve this problem natively, as the problem is too complex for z3 to solve. Formatting the constraints to z3 a little differently allows z3 to come up with an answer relatively quickly. (I was asleep while it was solving, so I don't know exactly how long!) The script for this is [here](#) and the binary is [here](#).

9.4.17 CrackMe example: ais3_crackme

Author: Antonio Bianchi, Tyler Nighswander

ais3_crackme has been developed by Tyler Nighswander (tylerni7) for ais3 summer school. It is an easy crackme challenge, checking its command line argument.

9.4.18 ReverseMe: Modern Binary Exploitation - CSCI 4968

Author: David Manouchehri (GitHub [@Manouchehri](#))

This [folder](#) contains scripts used to solve some of the challenges with angr. At the moment it only contains the examples from the IOLI crackme suite, but eventually other solutions will be added.

9.4.19 CrackMe example: Android License Check

Author: Bernhard Mueller (GitHub [@b-mueller](#))

A [native binary for Android/ARM](#) that validates a license key passed as a command line argument. It was created for the symbolic execution tutorial in the [OWASP Mobile Testing Guide](#).

9.5 Changelog

This lists the *major* changes in angr. Tracking minor changes are left as an exercise for the reader :-)

9.5.1 angr 9.1

- (#2961) Refactored SimCC to support passing and returning structs and arrays by value
- (#2964) Functions from the knowledge base may now be pretty-printed, showing colors and reference arrows
- Improved `import angr` speed substantially
- (#2948) RDA's `dep_graph` can now be used to track dependencies between temporaries, constants, guard conditions, and function calls - if you want it!
- (#2929) Basic support for structs with bitfields in `SimType`
- There's a decompiler now

9.5.2 angr 9.0

- Switched to a new versioning scheme: `major.minor.build_id`

9.5.3 angr 8.19.7.25

- (#1503) Implement necessary helpers and information storage for call pretty printing
- (#1546) Add a new state option `MEMORY_FIND_STRICT_SIZE_LIMIT`
- (#1548) `SimProcedure.static_exits`: Allow providing name hints
- (cle#177) Use Enums for Symbol Types
- (cle#193) Add support for "named regions"
- (claripy#151) Implement operator precedence in claripy op rendering
- Added support for interaction recording in angr-management
- Several new `simprocedure` implementations
- Substantial improvements to our CFG

9.5.4 angr 8.19.4.5

- (#1234) Massive improvements to CFG recovery for ARM and ARM cortex-m binaries.
- (#1416) Added support for analyzing Java programs via the Soot IR, including the ability to analyze interplay between Java code and JNI libraries. This branch was two years old!
- (#1427) Added a `MemoryWatcher` exploration technique to take action when the system is running out of RAM. Thanks @bannsec.
- (#1432) Added a `state.heap` plugin which manages the heap (with pluggable heap schemes!) and provides `malloc` functionality. Thanks @tgduckworth.
- Speed improvements for using the VEX engine and working with concrete data.

- Added SimLightRegisters, an alternate registers plugin that eliminates the abstraction of the register file for performance improvements at the cost of removing all instrumentability.
- `version__` variable has been added to all modules.
- The `stack_base` kwarg for `call_state` is not broken for the first time ever
- <https://github.com/python/cpython/pull/11384>

9.5.5 angr 8.19.2.4

- (#1279) Support C++ function name demangling via itanium-demangler. Thanks @fmagin.
- (#1283) `security_cookie` is initialized for SimWindows. Thanks @zeroSteiner.
- (#1298) Introduce `SimData`. It's a cleaner interface to deal with data imports in CLE – especially for those data entries that are not imported because of missing or unloaded libraries. This commit fixes long-standing issues #151 and #693.
- (#1299, #1300, #1301, #1313, #1314, #1315, #1336, #1337, #1343, ...) Multiple CFGFast-related improvements and bug fixes.
- (#1332) `UnresolvableTarget` is now split into two classes: `UnresolvableJumpTarget` and `UnresolvableCallTarget`. Thanks @Kyle-Kyle.
- (#1382) Add a preliminary implementation of angr decompiler. Give it a try! `p = angr.Project("cfg_loop_unrolling", auto_load_libs=False); p.analyses.CFG(); print(p.analyses.Decompiler(p.kb.functions['test_func']).codegen.text).`
- (#1421) `SimActions` now have incrementing IDs. Thanks @bannsec.
- (#1408) ANA, angr's old identity-aware serialization backend, has been removed. Instead of non-obvious serialization behavior, all angr objects should now be pickleable. If one is not, please file an issue. For use-cases that require identity-awareness (i.e., deduplicating ASTs across states serialized at different times), an `angr.vaults` module has been introduced.
- Added a [facility to synchronize state between angr and a running target a la avatar2](#)
- Changed unconstrained registers/memory warning to be less obnoxious and contain useful information. Also added `SYMBOL_FILL_UNCONSTRAINED_REGISTERS` and `SYMBOL_FILL_UNCONSTRAINED_MEMORY` state options to silence them.

9.5.6 angr 8.18.10.25

- The IDA backend for CLE has been removed. It has been broken for quite some time, but now it has been disabled for your own safety.
- Surveyors have been removed! Finally! This is thanks to @danse-macabre who contributed an Exploration Technique for the SliceCutor. Backwards slicing has now been brought out of the angr dark ages.
- SimCC can now be initialized with a string containing C function prototype in its `func_ty` argument
- Similarly, Callable can now be run with its arguments instantiated from a string containing C expressions
- Tracer has been substantially refactored - it will now handle more kinds of desyncs, ASLR slides, and is much more friendly for hacking. We will be continuing to improve it!
- The Oppologist and Driller have been refactored to play nice with other exploration techniques

- SimProcedure continuations now have symbols in the externs object, so `describe_addr` will work on them. Additionally, the representation for SimProcedure (appearing in `history.descriptions` and `project._sim_procedures` among other places) has been improved to show this information.

9.5.7 angr 8.18.10.5

Largely a bugfix release, but with a few bonus treats:

- API documentation has been rewritten for Exploration Technique. It should be much easier to use now.
- Simulation Manager will throw an error if you pass incorrect keyword arguments (??? why was it like this)
- The `save_unconstrained` flag of Simulation Manager is now on by default
- If a step produces only unsatisfiable states, they will appear in the 'unsat' stash regardless of the `save_unsat` setting, since this usually indicates a bug. Add `unsat` to the `auto_drop` parameter to restore the old behavior.

9.5.8 angr 8.18.10.1

Welcome to angr 8! The biggest change for this major version bump is the transition to Python 3. You can read about this, as well as a few other breaking changes, in the [Migrating to angr 8](#).

- Switch to Python 3
- Refactor to Clemory to clean up the API and speed things up drastically
- Remove `object.symbols_by_addr` (dict) and add `object.symbols` (sorted list); add `fuzzy` parameter to `loader.find_symbol`
- CFGFast is much, much faster now. CFGAccurate has been renamed to CFGEmlated.
- Support for `avx2` unpack instructions, courtesy of D. J. Bernstein
- Removed support for immutable simulation managers
- angr will now show you a warning when using uninitialized memory or registers
- angr will now NOT show you a warning if you have a capstone 3.x install unless you're actually interacting with the relevant missing parts
- Many, many, many bug fixes

9.5.9 angr 7.8.7.1

- Remove `LoopLimiter` and `DFG`.
- (#1063) `CFGAccurate` can now leverage indirect jump resolvers to resolve indirect jumps.

9.5.10 angr 7.8.6.23

- (PyVEX!#134) We now recognize LDMDb r11, {xxx, pc} as a ret instruction for ARM.
- (#1053) CFGFast spends less time running next_pos_with_sort_not_in(), thus it runs faster on large binaries.
- (#1080) Jump table resolvers now support resolving ARM jump tables.
- (#1081, together with the PyVEX commit 61efbdcf6303a936aa3de35011d2d1e3fe5fdea5) The memory footprint of CFGFast is noticeably smaller, especially on large binaries (over 10 MB in size).
- (#1034) Concretizing a SimFile with unconstrained size can no longer run you out of memory.
- Other minor changes and bug fixes.

9.5.11 angr 7.8.6.16

- The modeling of file system is refactored.
- (#808) Add a new class Control flow blanket (CFBlanket) to support generating a linear view of a control flow graph.
- (#863) Add support to AIL, the new angr intermediate language (still pretty WIP though). Merged in several static analyses (reaching definition analysis, VEX-to-AIL translation, redundant assignment elimination, code region identification, control flow structuring, etc.) that support the development of decompilation in the near future.
- (#888) SimulationManager is extensively refactored and cleaned up.
- (#892) Keystone is integrated. You can assemble instructions inside angr now.
- (#897) A new class PluginHub is added. Plugins (analyses, engines) are refactored to be based on PluginHub.
- (#899) Support of bidirectional mapping between syscall numbers and syscalls.
- (#925, #941, #942) A bunch of library function prototypes (including glibc) are added to angr.
- (#953) Fix the issue where evaluating the jump target of a jump table that contains many entries (e.g., > 512) is extremely slow.
- (#964) State options are now stored in instances of SimStateOptions. state.options is no longer a set of strings.
- (#973) Add two new exploration techniques: Stochastic and unique.
- (#996) SimType structs are now much easier to use.
- (#998) Add a new state option PRODUCE_ZERODIV_SUCCESORS to generate divide-by-zero successors.
- Speed improvements and bug fixes in CFG generation (CFGFast and CFGAccurate).

9.5.12 angr 7.8.2.21

- Refactor of how syscall handling and SimSyscallLibrary work - it is now possible to handle syscalls using multiple ABIs in the same process
- Added syscall name-number mappings from all linux ABIs, parsed from gdb
- Add ManualMergepoint exploration technique for when veritesting is too mysterious for your tastes
- Add LoopSeer exploration technique for managing loops during symbolic exploration (credit @tyb0807)
- Add ProxyTechnique exploration technique for easily composing simple lambda-based instrumentations (credit @danse-macabre)

9.5.13 angr 7.7.12.16

- You can now tell where the variables implicitly created by angr come from! `state.solver.BVS` now can take a key parameter, which describes its meaning in relation to the emulated environment. You can then use `state.solver.get_variables(...)` and `state.solver.describe_variables(...)` to map tags and ASTs to and from each other. Check out the [API docs](#)!
- The SimOS for a project is now a public property - `project.simos` instead of `project._simos`. Additionally, the SimOS code structure has been shuffled around a bit - it's now a subpackage instead of a submodule.
- The core components of Tracer and Driller have been refactored into Exploration Techniques and integrated into angr proper, so you can now follow instruction traces without installing another repository! (credit @tyb0807)
- Archinfo now contains a `byte_width` parameter and angr supports emulation of platforms with non-octet bytes, lord help us
- Upgraded to networkx 2 (credit @tyb0807)
- Hopefully installation issues with capstone should be fixed FOREVER
- Minor fixes to gender

9.5.14 angr 7.7.9.8

Welcome to angr 7! We worked long and hard all summer to make this release the best ever. It introduces several breaking changes, so for a quick guide on the most common ways you'll need to update your scripts, take a look at the [Migrating to angr 7](#).

- SimuVEX has been removed and its components have been integrated into angr
- Path has been removed and its components have been integrated into SimState, notably the new `history` state plugin
- PathGroup has been renamed to `SimulationManager`
- SimState and SimProcedure now have a reference to their parent Project, though it is verboten to use it in anything other than an append-only fashion
- A new class `SimLibrary` is used to track SimProcedure and metadata corresponding to an individual shared library
- Several CLE interfaces have been refactored up for consistency
- Hook has been removed. Hooking is now done with individual SimProcedure instances, which are shallow-copied at execution time for thread-safety.
- The `state.solver` interface has been cleaned up drastically

These are the major refactor-y points. As for the improvements:

- Greatly improved support for analyzing 32 bit windows binaries (partial credit @schieb)
- Unicorn will now stop for stop points and breakpoints in the middle of blocks (credit @bennofs)
- The processor flags for a state can now be accessed through `state.regs.eflags` on x86 and `state.regs.flags` on ARM (partial credit @tyb0807)
- Fledgling support for emulating exception handling. Currently the only implementation of this is support for Structured Exception Handling on Windows, see `angr.SimOS.handle_exception` for details
- Fledgling support for runtime library loading by treating the CLE loader as an append-only interface, though only implemented for windows. See `cle.Loader.dynamic_load` and `angr.procedures.win32.dynamic_loading` for details.

- The knowledge base has been refactored into a series of plugins similar to SimState (credit @danse-macabre)
- The testcase-based function identifier we wrote for CGC has been integrated into angr as the Identifier analysis
- Improved support for writing custom VEX lifters

9.5.15 angr 6.7.6.9

- angr: A static data-flow analysis framework has been introduced, and implemented as part of the `ForwardAnalysis` class. Additionally, a few exemplary data-flow analyses, like `VariableRecovery` and `VariableRecoveryFast`, have been implemented in angr.
- angr: We introduced the notion of *variable* to the angr world. Now a `VariableManager` is available in the knowledge base. Variable information can be recovered by running a variable recovery analysis. Currently the variable information recovered for each function is still pretty coarse. More updates to it will arrive soon.
- angr: Fix a bug in the topological sorting in `CFGUtils`, which resulted in suboptimal graph node ordering after sorting.
- SimuVEX: `LAZY_SOLVES` is no longer enabled by default during symbolic execution. It's still there if it's wanted, but it just caused confusion when on by default.
- SimuVEX: Thanks to @ekilmer, a few new libc SimProcedures are added.
- SimuVEX: The default memory model has been refactored for expandability. Custom pages can now be created (derive the `simuvex.storage.ListPage` class) and used instead of the default page classes to implement custom memory behavior for specific pages. The user-friendly API for this is pending the next release.
- angr-management: Implemented our own graph layout and edge routing algorithm. We do not rely on `grandalf` anymore.
- angr-management: Added support for displaying variable information for operands.
- angr-management: Added support for highlighting dependent operands when an operand is highlighted.

9.5.16 angr 6.7.3.26

Building off of the engine changes from the last release, we have begun to extend angr to other architectures. AVR and MSP430 are in progress. In the meantime, subwire has created a reference implementation of BrainFuck support in angr, done two different ways! Check out [angr-platforms](#) for more info!

- We have rebased our fork of VEX on the latest master branch from Valgrind (as of 2 months ago, at least...). We have also submitted our patches to VEX to upstream, so we should be able to stop maintaining a fork pretty soon.
- The way we interact with VEX has changed substantially, and should speed things up a bit.
- Loading sets of binaries with many import symbols has been sped up
- Many, many improvements to angr-management, including the switch away from `enaml` to using `pyside` directly.

9.5.17 angr 6.7.1.13

For the last month, we have been working on a major refactor of the angr to change the way that angr reasons about the code that it analyzes. Until now, angr has been bound to the VEX intermediate representation to lift native code, supporting a wide range of architectures but not being very expandable past them. This release represents the ground work for what we call translation and execution engines. These engines are independent backends, pluggable into the angr framework, that will allow angr to reason about a wide range of targets. For now, we have restructured the existing VEX and Unicorn Engine support into this engine paradigm, but as we discuss in [our blog post](#), the plan is to create engines to enable angr’s reasoning of Java bytecode and source code, and to augment angr’s environment support through the use of external dynamic sandboxes.

For now, these changes are mostly internal. We have attempted to maintain compatibility for end-users, but those building systems atop angr will have to adapt to the modern codebase. The following are the major changes:

- **simuvex:** we have introduced `SimEngine`. `SimEngine` is a base class for abstractions over native code. For example, angr’s VEX-specific functionality is now concentrated in `SimEngineVEX`, and new engines (such as `SimEngineLLVM`) can be implemented (even outside of `simuvex` itself) to support the analysis of new types of code.
- **simuvex:** as part of the engines refactor, the `SimRun` class has been eliminated. Instead of different subclasses of `SimRun` that would be instantiated from an input state, engines each have a `process` function that, from an input state, produces a `SimSuccessors` instance containing lists of different successor states (normal, unsat, unconstrained, etc) and any engine-specific artifacts (such as the VEX statements. Take a look at `successors.artifacts`).
- **simuvex:** `state.mem[x:] = y` now *requires* a type for storage (for example `state.mem[x:].dword = y`).
- **simuvex:** the way of calling inline `SimProcedures` has been changed. Now you have to create a `SimProcedure`, and then call `execute()` on it and pass in a program state as well as the arguments.
- **simuvex:** accessing registers through `SimRegNameView` (like `state.regs.eax`) always triggers `SimInspect` breakpoints and creates new actions. Now you can access a register by prefixing its name with an underscore (e.g. `state.regs._eax` or `state._ip`) to avoid triggering breakpoints or creating actions.
- **angr:** the way hooks work has slightly changed, though is backwards-compatible. The new `angr.Hook` class acts as a wrapper for hooks (`SimProcedures` and functions), keeping things cleaner in the `project._sim_procedures` dict.
- **angr:** we have deprecated the keyword argument `max_size` and changed it to `size` in the `angr.Block` constructor (i.e., the argument to `project.factory.block` and more upstream methods (`path.step`, `path_group.step`, etc)).
- **angr:** we have deprecated `project.factory.sim_run` and changed it to `project.factory.successors`, and it now generates a `SimSuccessors` object.
- **angr:** `project.factory.sim_block` has been deprecated and replaced with `project.factory.successors(default_engine=True)`.
- **angr:** angr syscalls are no longer hooks. Instead, the syscall table is now in `project._simos.syscall_table`. This will be made “public” after a usability refactor. If you were using `project.is_hooked(addr)` to see if an address has a related `SimProcedure`, now you probably want to check if there is a related syscall as well (using `project._simos.syscall_table.get_by_addr(addr)` is not `None`).
- **pyvex:** to support custom lifters to VEX, `pyvex` has introduced the concept of backend lifters. Lifters can be written in pure Python to produce VEX IR, allowing for extendability of angr’s VEX-based analyses to other hardware architectures.

As usual, there are many other improvements and minor bugfixes.

- claripy: support `unsat_core()` to get the core of unsatness of constraints. It is in fact a thin wrapper of the `unsat_core()` function provided by Z3. Also a new state option `CONSTRAINT_TRACKING_IN_SOLVER` is added to SimuVEX. That state option must be enabled if you want to use `unsat_core()` on any state.
- simuvex: `SimMemory.load()` and `SimMemory.store()` now takes a new parameter `disable_actions`. Setting it to `True` will prevent any `SimAction` creation.
- angr: CFGFast has a better support for ARM binaries, especially for code in THUMB mode.
- angr: thanks to an improvement in SimuVEX, CFGAccurate now uses slightly less memory than before.
- angr: `len()` on `path trace` or `addr_trace` is made much faster.
- angr: Fix a crash during CFG generation or symbolic execution on platforms/architectures with no syscall defined.
- angr: as part of the refactor, `BackwardSlicing` is temporarily disabled. It will be re-enabled once all DDG-related refactor are merged to master.

Additionally, packaging and build-system improvements coordinated between the angr and Unicorn Engine projects have allowed angr's Unicorn support to be built on Windows. Because of this, `unicorn` is now a dependency for `simuvex`.

Looking forward, angr is poised to become a program analysis engine for binaries *and more*!

9.5.18 angr 5.6.12.3

It has been over a month since the last release 5.6.10.12. Again, we've made some significant changes and improvements on the code base.

- angr: Labels are now stored in KnowledgeBase.
- angr: Add a new analysis: `Disassembly`. The new `Disassembly` analysis provides an easy-to-use interface to render assembly of functions.
- angr: Fix the issue that `ForwardAnalysis` may prematurely terminate while there are still un-processed jobs.
- angr: Many small improvements and bug fixes on CFGFast.
- angr: Many small improvements and bug fixes on VFG. Bring back widening support. Fix the issue that VFG may not terminate under certain cases. Implement a new graph traversal algorithm to have an optimal traversal order. Allow state merging at non-merge-points, which allows faster convergence.
- angr-management: Display a progress during initial CFG recovery.
- angr-management: Display a "Load binary" window upon binary loading. Some analysis options can be adjusted there.
- angr-management: Disassembly view: Edge routing on the graph is improved.
- angr-management: Disassembly view: Support starting a new symbolic execution task from an arbitrary address in the program.
- angr-management: Disassembly view: Support renaming of function names and labels.
- angr-management: Disassembly view: Support "Jump to address".
- angr-management: Disassembly view: Display resolved and unresolved jump targets. All jump targets are double-clickable.
- SimuVEX: Move region mapping from `SimAbstractMemory` to `SimMemory`. This will allow an easier conversion between `SimAbstractMemory` and `SimSymbolicMemory`, which is to say, conversion between symbolic states and static states is now possible.

- SimuVEX & claripy: Provide support for `unsat_core` in Z3. It returns a set of constraints that led to unsatness of the constraint set on the current state.
- archinfo: Add a new Boolean variable `branch_delay_slot` for each architecture. It is set to True on MIPS32.

9.5.19 angr 5.6.8.22

Major point release! An incredible number of things have changed in the month run-up to the Cyber Grand Challenge.

- Integration with [Unicorn Engine](#) supported for concrete execution. A new SimRun type, SimUnicorn, may step through many basic blocks at once, so long as there is no operation on symbolic data. Please use [our fork of unicorn engine](#), which has many patches applied. All these patches are pending merge into upstream.
- Lots of improvements and bug fixes to CFGFast. Rumors are angr's CFG was only "optimized" for x86-64 binaries (which is really because most of our test cases are compiled as 64-bit ELF's). Now it is also "optimized" for x86 binaries :) (editor's note: angr is built with cross-architecture analysis in mind. CFG construction is pretty much the only component which has architecture-specific behavior.)
- Lots of improvements to the VFG analysis, including speed and accuracy. However, there is still a lot to be done.
- Lots of speed optimizations in general - CFGFast should be 3-6x faster under CPython with much less memory usage.
- Now data dependence graph gives you a real dependence graph between variable definitions. Try `data_graph` and `simplified_data_graph` on a DDG object!
- New state option `simuvex.o.STRICT_PAGE_ACCESS` will cause a `SimSegfaultError` to be raised whenever the guest reads/writes/executes memory that is either unmapped or doesn't have the appropriate permissions.
- Merging of paths (as opposed to states) is performed in a much smarter way.
- The behavior of the `support_selfmodifying_code` project option is changed: Before, this would allow the state to be used as a fallback source of instruction bytes when no backer from CLE is available. Now, this option makes instruction lifting use the state as the source of bytes always. When the option is disabled and execution jumps outside the normal binary, the state will be used automatically.
- *Actually* support self-modifying code - if a basic block of code modifies itself, the block will be re-lifted before the next instruction starts.
- Syscalls are handled differently now - Before you would see a SimRun for a syscall helper, now you'll just see a SimProcedure for the given syscall. Additionally, each syscall has its own address in a "syscalls segment", and syscalls are treated as jumps to this segment. This simplifies a lot of things analysis-wise.
- CFGAccurate accepts a `base_graph` keyword to its constructor, e.g. `CFGFast().graph`, or even `.graph` of a function, to use as a base for analysis.
- New fast memory model for cases where symbolic-addressed reads and writes are unlikely.
- Conflicts between the `find` and `avoid` parameters to the Explorer `otiegnqwk` are resolved correctly. (credit `clsgrnc`)
- New analysis `StaticHooker` which hooks library functions in unstripped statically linked binaries.
- `Lifter` can be used without creating an angr Project. You must manually specify the architecture and bytestring in calls to `.lift()` and `.fresh_block()`. If you like, you can also specify the architecture as a parameter to the constructor and omit it from the lifting calls.
- Add two new analyses developed for the CGC (mostly as examples of doing static analysis with angr): `Reassembler` and `BinaryOptimizer`.

9.5.20 angr 4.6.6.28

In general, there have been enormous amounts of speed improvements in this release. Depending on the workload, angr should run about twice as fast. Aside from this, there have also been many submodule-specific changes:

angr

Quite a few changes and improvements are made to CFGFast and CFGAccurate in order to have better and faster CFG recovery. The two biggest changes in CFGFast are jump table resolution and data references collection, respectively. Now CFGFast resolves indirect jumps by default. You may get a list of indirect jumps recovered in CFGFast by accessing the `indirect_jumps` attribute. For many cases, it resolves the jump table accurately. Data references collection is still in alpha mode. To test data references collection, just pass `collect_data_references=True` when creating a fast CFG, and access the `memory_data` attribute after the CFG is constructed.

CFG recovery on ARM binaries is also improved.

A new paradigm called an “otiegnqwk”, or an “exploration technique”, allows the packaging of special logic related to path group stepping.

SimuVEX

Reads/writes to the x87 fpu registers now work correctly - there is special logic that rotates a pointer into part of the register file to simulate the x87 stack.

With the recent changes to Claripy, we have configured SimuVEX to use the composite solver by default. This should be transparent, but should be considered if strange issues (or differences in behavior) arise during symbolic execution.

Claripy

Fixed a bug in claripy where `div__` was not always doing unsigned division, and added new methods `SDiv` and `SMod` for signed division and signed remainder, respectively.

Claripy frontends have been completely rewritten into a mixin-centric solver design. Basic frontend functionality (i.e., calling into the solver or dealing with backends) is handled by frontends (in `claripy.frontends`), and additional functionality (such as caching, deciding when to simplify, etc) is handled by frontend mixins (in `claripy.frontend_mixins`). This makes it considerably easier to customize solvers to your specific needE. For examples, look at `claripy/solver.py`.

Alongside the solver rewrite, the composite solver (which splits constraints into independent constraint sets for faster solving) has been immensely improved and is now functional and fast.

9.5.21 angr 4.6.6.4

Syscalls are no longer handled by `simuvex.procedures.syscalls.handler`. Instead, syscalls are now handled by `angr.SimOS.handle_syscall()`. Previously, the address of a syscall `SimProcedure` is the address right after the syscall instruction (e.g. `int 80h`), which collides with the real basic block starting at that address, and is very confusing. Now each syscall `SimProcedure` has its own address, just as a normal `SimProcedure`. To support this, there is another region mapped for the syscall addresses, `Project._syscall_obj`.

Some refactoring and bug fixes in CFGFast.

Claripy has been given the ability to handle *annotations* on ASTs. An annotation can be used to customize the behavior of some backends without impacting others. For more information, check the docstrings of `claripy.Annotation` and `claripy.Backend.apply_annotation`.

9.5.22 angr 4.6.5.25

New state constructor - `call_state`. Comes with a refactor to `SimCC`, a refactor to `callable`, and the removal of `PathGroup.call`. All these changes are thoroughly documented, in `angr/docs/advanced-topics/structured_data.md`

Refactor of `SimType` to make it easier to use types - they can be instantiated without a `SimState` and one can be added later. Comes with some usability improvements to `SimMemView`. Also, there's a better wrapper around `PyCParser` for generating `SimType` instances from `c` declarations and definitions. Again, thoroughly documented, still in the `structured_data` doc.

`CFG` is now an alias to `CFGFast` instead of `CFGAccurate`. In general, `CFGFast` should work under most cases, and it's way faster than `CFGAccurate`. We believe such a change is necessary, and will make `angr` more approachable to new users. You will have to change your code from `CFG` to `CFGAccurate` if you are relying on specific functionalities that only exist in `CFGAccurate`, for example, context-sensitivity and state-preserving. An exception will be raised by `angr` if any parameter passed to `CFG` is only supported by `CFGAccurate`. For more detailed explanation, please take a look at the documentation of `angr.analyses.CFG`.

9.5.23 angr 4.6.3.28

`PyVEX` has a structural overhaul. The `IRExpr`, `IRStmt`, and `IRConst` modules no longer exist as submodules, and those module names are deprecated. Use `pyvex.expr`, `pyvex.stmt`, and `pyvex.const` if you need to access the members of those modules.

The names of the first three parameters to `pyvex.IRSB` (the required ones) have been changed. If you were passing the positional args to `IRSB` as keyword args, consider switching to positional args. The order is `data`, `mem_addr`, `arch`.

The optional parameter `sargc` to the `entry_state` and `full_init_state` constructors has been removed and replaced with an `argc` parameter. `sargc` predates being able to have claripy ASTs independent from a solver. The new system is to pass in the exact value, `ast` or `integer`, that you'd like to have as the guest program's arg count.

CLE and `angr` can now accept file-like streams, that is, objects that support `stream.read()` and `stream.seek()` can be passed in wherever a filepath is expected.

Documentation is much more complete, especially for `PyVEX` and `angr`'s symbolic execution control components.

9.5.24 angr 4.6.3.15

There have been several improvements to `claripy` that should be transparent to users:

- There's been a refactoring of the `VSA StridedInterval` classes to fix cases where operations were not sound. Precision might suffer as a result, however.
- Some general speed improvements.
- We've introduced a new backend into `claripy`: the `ReplacementBackend`. This frontend generates replacement sets from constraints added to it, and uses these replacement sets to increase the precision of `VSA`. Additionally, we have introduced the `HybridBackend`, which combines this functionality with a constraint solver, allowing for memory index resolution using `VSA`.

`angr` itself has undergone some improvements, with API changes as a result:

- We are moving toward a new way to store information that `angr` has recovered about a program: the knowledge base. When an analysis recovers some truth about a program (i.e., "there's a basic block at `0x400400`", or "the block at `0x400400` has a jump to `0x400500`"), it gets stored in a knowledge-base. Analysis that used to store data (currently, the `CFG`) now store them in a knowledge base and can *share* the global knowledge base of the project, now accessible via `project.kb`. Over time, this knowledge base will be expanded in the course of any analysis or symbolic execution, so `angr` is constantly learning more information about the program it is analyzing.

- A forward data-flow analysis framework (called ForwardAnalysis) has been introduced, and the CFG was rewritten on top of it. The framework is still in alpha stage - expect more changes to be made. Documentation and more details will arrive shortly. The goal is to refactor other data-flow analysis, like CFGFast, VFG, DDG, etc. to use ForwardAnalysis.
- We refactored the CFG to a) improve code readability, and b) eliminate some bad designs that linger due to historical reasons.

9.5.25 angr 4.5.12.?

Claripy has a new manager for backends, allowing external backends (i.e., those implemented by other modules) to be used. The result is that `claripy.backend_concrete` is now `claripy.backends.concrete`, `claripy.backend_vsa` is now `claripy.backends.vsa`, and so on.

9.5.26 angr 4.5.12.12

Improved the ability to recover from failures in instruction decoding. You can now hook specific addresses at which VEX fails to decode with `project.hook`, even if those addresses are not the beginning of a basic block.

9.5.27 angr 4.5.11.23

This is a pretty beefy release, with over half of claripy having been rewritten and major changes to other analyses. Internally, Claripy has been unified – the VSA mode and symbolic mode now work on the same structures instead of requiring structures to be created differently. This opens the door for awesome capabilities in the future, but could also result in unexpected behavior if we failed to account for something.

Claripy has had some major interface changes:

- `claripy.BV` has been renamed to `claripy.BVS` (bit-vector symbol). It can now create bitvectors out of strings (i.e., `claripy.BVS(0x41, 8)` and `claripy.BVS("A")` are identical).
- `state.BV` and `state.BVV` are deprecated. Please use `state.se.BVS` and `state.se.BVV`.
- `BV.model` is deprecated. If you're using it, you're doing something wrong, anyways. If you really need a specific model, convert it with the appropriate backend (i.e., `claripy.backend_concrete.convert(bv)`).

There have also been some changes to analyses:

- Interface: CFG argument `keep_input_state` has been renamed to `keep_state`. With this option enabled, both input and final states are kept.
- Interface: Two arguments `cfg_node` and `stmt_id` of `BackwardSlicing` have been deprecated. Instead, `BackwardSlicing` takes a single argument, `targets`. This means that we now support slicing from multiple sources.
- Performance: The speed of CFG recovery has been slightly improved. There is a noticeable speed improvement on MIPS binaries.
- Several bugs have been fixed in DDG, and some sanity checks were added to make it more usable.

And some general changes to angr itself:

- `StringSpec` is deprecated! You can now pass claripy bitvectors directly as arguments.

9.6 Migrating to angr 9.1

angr 9.1 is here!

9.6.1 Calling Conventions and Prototypes

The main change motivating angr 9.1 is [this large refactor of SimCC](#). Here are the breaking changes:

SimCCs can no longer be customized

If you were using the `sp_delta`, `args`, or `ret_val` parameters to `SimCC`, you should use the new class `SimCCUsercall`, which lets (requires) you to be explicit about the locations of each argument.

Passing SimTypes is now mandatory

Every method call on `SimCC` which interacts with typed data now requires a `SimType` to be passed in. Previously, the use of `is_fp` and `size` was optional, but now these parameters will no longer be accepted and a `SimType` will be required.

This has some fairly non-intuitive consequences - in order to accommodate more esoteric calling conventions (think: passing large structs by value via an “invisible reference”) you have to specify a function’s return type before you can extract any of its arguments.

Additionally, some non-cc interfaces, such as `call_state` and `callable` and `SimProcedure.call()`, now *require* a prototype to be passed to them. You’d be surprised how many bugs we found in our own code from enforcing this requirement!

PointerWrapper has a new parameter

Imagine you’re passing something into a function which has a parameter of type `char*`. Is this a pointer to a single char or a pointer to an array of chars? The answer changes how we typecheck the values you pass in. If you’re passing a `PointerWrapper` wrapping a large value which should be treated as an array of chars, you should construct your pointerwrapper as `PointerWrapper(foo, buffer=True)`. The `buffer` argument to `PointerWrapper` now instructs `SimCC` to treat the data to be serialized as an array of the child type instead of as a scalar.

func_ty -> prototype

Every usage of the name `func_ty` has been replaced with the name `prototype`. This was done for consistency between the static analysis code and the dynamic FFI.

9.7 Migrating to angr 8

angr has moved from Python 2 to Python 3! We took this opportunity of a major version bump to make a few breaking API changes that improve quality-of-life.

9.7.1 What do I need to know for migrating my scripts to Python 3?

To begin, just the standard py3k changes, the relevant parts of which we'll rehash here as a reference guide:

- Strings and bytestrings
 - Strings are now unicode by default, a new `bytes` type holds bytestrings
 - Bytestring literals can be constructed with the `b` prefix, like `b'ABCD'`
 - Conversion between strings and bytestrings happens with `.encode()` and `.decode()`, which use utf-8 as a default. The `latin-1` codec will map byte values to their equivalent unicode codepoints
 - The `ord()` and `chr()` functions operate on strings, not bytestrings
 - Enumerating over or indexing into bytestrings produces an unsigned 8 bit integer, not a 1-byte bytestring
 - Bytestrings have all the string manipulation functions present on strings, including `join`, `upper/lower`, `translate`, etc
 - `hex` and `base64` are no longer string encoding codecs. For hex, use `bytes.fromhex()` and `bytes.hex()`. For base64 use the `base64` module.
- Builtin functions
 - `print` and `exec` are now builtin functions instead of statements
 - Many builtin functions previously returning lists now return iterators, such as `map`, `filter`, and `zip`. `reduce` is no longer a builtin; you have to import it from `functools`.
- Numbers
 - The `/` operator is explicitly floating-point division, the `//` operator is explicitly integer division. The magic functions for overriding these ops are `truediv__` and `floordiv__`
 - The `int` and `long` types have been merged, there is only `int` now
- Dictionary objects have had their `.iterkeys`, `.itervalues`, and `.iteritems` methods removed, and then non-iter versions have been made to return efficient iterators
- Comparisons between objects of very different types (such as between strings and ints) will raise an exception

In terms of how this has affected angr, any string that represents data from the emulated program will be a bytestring. This means that where you previously said `state.solver.eval(x, cast_to=str)` you should now say `cast_to=bytes`. When creating concrete bitvectors from strings (including implicitly by just making a comparison against a string) these should be bytestrings. If they are not they will be utf-8 converted and a warning will be printed. Symbol names should be unicode strings.

For division, however, ASTs are strongly typed so they will treat both division operators as the kind of division that makes sense for their type.

9.7.2 Clefory API changes

The memory object in CLE (`project.loader.memory`, not `state.memory`) has had a few breaking API changes since the `bytes` type is much nicer to work with than the py2 string for this specific case, and the old API was an inconsistent mess.

Before	After
<code>memory.read_bytes(addr, n) -> list[str]</code>	<code>memory.load(addr, n) -> bytes</code>
<code>memory.write_bytes(addr, list[str])</code>	<code>memory.store(addr, bytes)</code>
<code>memory.get_byte(addr) -> str</code>	<code>memory[addr] -> int</code>
<code>memory.read_addr_at(addr) -> int</code>	<code>memory.unpack_word(addr) -> int</code>
<code>memory.write_addr_at(addr, value) -> int</code>	<code>memory.pack_word(addr, value)</code>
<code>memory.stride_repr -> list[(start, end, str)]</code>	<code>memory.backers() -> iter[(start, bytearray)]</code>

Additionally, `pack_word` and `unpack_word` now take optional `size`, `endness`, and `signed` parameters. We have also added `memory.pack(addr, fmt, *data)` and `memory.unpack(addr, fmt)`, which take format strings for use with the `struct` module.

If you were using the `cbackers` or `read_bytes_c` functions, the conversion is a little more complicated - we were able to remove the split notion of “backers” and “updates” and replaced all backers with bytearrays that we mutate, so we can work directly with the backer objects. The `backers()` function iterates through all bottom-level backer objects and their start addresses. You can provide an optional address to the function, and it will skip over all backers that end before that address.

Here is some sample code for producing a C-pointer to a given address:

```
import cffi, cle
ffi = cffi.FFI()
ld = cle.Loader('/bin/true')

addr = ld.main_object.entry
try:
    backer_start, backer = next(ld.memory.backers(addr))
except StopIteration:
    raise Exception("not mapped")

if backer_start > addr:
    raise Exception("not mapped")

cbacker = ffi.from_buffer(backer)
addr_pointer = cbacker + (addr - backer_start)
```

You should not have to use this if you aren’t passing the data to a native library - the normal load methods should now be more than fast enough for intensive use.

9.7.3 CLE symbols changes

Previously, your mechanisms for looking up symbols by their address were `loader.find_symbol()` and `object.symbols_by_addr`, where there was clearly some overlap. However, `symbols_by_addr` stayed because it was the only way to enumerate symbols in an object. This has changed! `symbols_by_addr` is deprecated and here is now `object.symbols`, a sorted list of `Symbol` objects, to enumerate symbols in a binary.

Additionally, you can now enumerate all symbols in the entire project with `loader.symbols`. This change has also enabled us to add a fuzzy parameter to `find_symbol` (returns the first symbol before the given address) and make the output of `loader.describe_addr` much nicer (shows offset from closest symbol).

9.7.4 Deprecations and name changes

- All parameters in `cle` that started with `custom_` - so, `custom_base_addr`, `custom_entry_point`, `custom_offset`, `custom_arch`, and `custom_ld_path` - have had the `custom_` removed from the beginning of their names.
- All the functions that were deprecated more than a year ago (at or before the angr 7 release) have been removed.
- `state.se` has been deprecated. You should have been using `state.solver` for the past few years.
- Support for immutable simulation managers has been removed. So far as we're aware, nobody was actually using this, and it was making debugging a pain.

9.8 Migrating to angr 7

The release of angr 7 introduces several departures from long-standing angr-isms. While the community has created a compatibility layer to give external code written for angr 6 a good chance of working on angr 7, the best thing to do is to port it to the new version. This document serves as a guide for this.

9.8.1 SimuVEX is gone

angr versions up through angr 6 split the program analysis into two modules: `simuvex`, which was responsible for analyzing the effects of a single piece of code (whether a basic block or a `SimProcedure`) on a program state, and `angr`, which aggregated analyses of these basic blocks into program-level analysis such as control-flow recovery, symbolic execution, and so forth. In theory, this would encourage for the encapsulation of block-level analyses, and allow other program analysis frameworks to build upon `simuvex` for their needs. In practice, no one (to our knowledge) used `simuvex` without `angr`, and the separation introduced frustrating limitations (such as not being able to reference the history of a state from a `SimInspect` breakpoint) and duplication of code (such as the need to synchronize data from `state.scratch` into `path.history`).

Realizing that SimuVEX wasn't a usable independent package, we brainstormed about merging it into angr and further noticed that this would allow us to address the frustrations resulting from their separation.

All of the SimuVEX concepts (`SimStates`, `SimProcedures`, calling conventions, types, etc) have been migrated into angr. The migration guide for common classes is below:

Before	After
<code>simuvex.SimState</code>	<code>angr.SimState</code>
<code>simuvex.SimProcedure</code>	<code>angr.SimProcedure</code>
<code>simuvex.SimEngine</code>	<code>angr.SimEngine</code>
<code>simuvex.SimCC</code>	<code>angr.SimCC</code>

And for common modules:

Before	After
<code>simuvex.s_cc</code>	<code>angr.calling_conventions</code>
<code>simuvex.s_state</code>	<code>angr.sim_state</code>
<code>simuvex.s_procedure</code>	<code>angr.sim_procedure</code>
<code>simuvex.plugins</code>	<code>angr.state_plugins</code>
<code>simuvex.engines</code>	<code>angr.engines</code>
<code>simuvex.concretization_strategies</code>	<code>angr.concretization_strategies</code>

Additionally, `simuvex.SimProcedures` has been renamed to `angr.SIM_PROCEDURES`, since it is a global variable and not a class. There have been some other changes to its semantics, see the section on `SimProcedures` for details.

9.8.2 Removal of `angr.Path`

In `angr`, a `Path` object maintained references to a `SimState` and its history. The fact that the history was separated from the state caused a lot of headaches when trying to analyze states inside a breakpoint, and caused overhead in synchronizing data from the state to its history.

In the new model, a state's history is maintained in a `SimState` plugin: `state.history`. Since the path would now simply point to the state, we got rid of it. The mapping of concepts is roughly as follows:

Before	After
<code>path</code>	<code>state</code>
<code>path.state</code>	<code>state</code>
<code>path.history</code>	<code>state.history</code>
<code>path.callstack</code>	<code>state.callstack</code>
<code>path.trace</code>	<code>state.history.descriptions</code>
<code>path.addr_trace</code>	<code>state.history.bbl_addrs</code>
<code>path.jumpkinds</code>	<code>state.history.jumpkinds</code>
<code>path.guards</code>	<code>state.history.jump_guards</code>
<code>path.targets</code>	<code>state.history.jump_targets</code>
<code>path.actions</code>	<code>state.history.actions</code>
<code>path.events</code>	<code>state.history.events</code>
<code>path.recent_actions</code>	<code>state.history.recent_actions</code>
<code>path.reachable</code>	<code>state.history.reachable()</code>

An important behavior change about `path.actions` and `path.recent_actions` - actions are no longer tracked by default. If you would like them to be tracked again, please add `angr.options.refs` to your state.

Path Group -> Simulation Manager

Since there are no paths, there cannot be a path group. Instead, we have a Simulation Manager now (we recommend using the abbreviation “`simgr`” in places you were previously using “`pg`”), which is exactly the same as a path group except it holds states instead of paths. You can make one with `project.factory.simulation_manager(...)`.

Errored Paths

Before, error resilience was handled at the path level, where stepping a path that caused an error would return a subclass of `Path` called `ErroredPath`, and these paths would be put in the `errored` stash of a path group. Now, error resilience is handled at the simulation manager level, and any state that throws an error during stepping will be wrapped in an `ErrorRecord` object, which is *not* a subclass of `SimState`, and put into the `errored` list attribute of the simulation manager, which is *not* a stash.

An `ErrorRecord` object has attributes for `.state` (the initial state that caused the error), `.error` (the error that was thrown), and `.traceback` (the traceback from the error). To debug these errors you can call `.debug()`.

These changes are because we were uncomfortable making a subclass of `SimState`, and the `ErrorRecord` class then has sufficiently different semantics from a normal state that it cannot be placed in a stash.

9.8.3 Changes to SimProcedures

The most noticeable difference from the old version to the new version is that the catalog of built-in simprocedures are no longer organized strictly according to which library they live in. Now, they are organized according to which *standards* they conform to, which helps with re-using procedures between different libraries. For instance, the old `SimProcedures['libc.so.6']` has been split up between `SIM_PROCEDURES['libc']`, `SIM_PROCEDURES['posix']`, and `SIM_PROCEDURES['glibc']`, depending on what specifications each function conforms to. This allows us to reuse the `libc` catalog in `msvcrt.dll` and the `MUSL libc`, for example.

In order to group `SimProcedures` together by libraries, we have introduced a new abstraction called the `SimLibrary`, the definitions for which are stored in `angr.procedures.definitions`. Each `SimLibrary` object stores information about a single shared library, and can contain `SimProcedure` implementations, calling convention information, and type information. `SimLibraries` are scraped from the filesystem at import time, just like `SimProcedures`, and placed into `angr.SIM_LIBRARIES`.

Syscalls are now categorized through a subclass of `SimLibrary` called `SimSyscallLibrary`. The API for managing syscalls through `SimOS` has been changed - check the API docs for the `SimUserspace` class.

One important implication of this change is that if you previously used a trick where you changed one of the `SimProcedures` present in the `SimProcedures` dict in order to change which `SimProcedures` would be used to hook over library functions by default, this will no longer work. Instead of `SimProcedures[lib][func_name] = proc`, you now need to say `SIM_LIBRARIES[lib].add(func_name, proc)`. But really you should just be using `hook_symbol` anyway.

9.8.4 Changes to hooking

The `Hook` class is gone. Instead, we now can hook with individual instances of `SimProcedure` objects, as opposed to just the classes. A shallow copy of the `SimProcedure` will be made at runtime to preserve thread safety.

So, previously, where you would have done `project.hook(addr, Hook(proc, ...))` or `project.hook(addr, proc)`, you can now do `project.hook(addr, proc(...))`. In order to use simple functions as hooks, you can either say `project.hook(addr, func)` or decorate the declaration of your function with `@project.hook(addr)`.

Having simprocedures as instances and letting them have access to the project cleans up a lot of other hacks that were present in the codebase, mostly related to the `self.call(...)` `SimProcedure` continuation system. It is no longer required to set `IS_FUNCTION = True` if you intend to use `self.call()` while writing a `SimProcedure`, and each call-return target you use will have a unique address associated with it. These addresses will be allocated lazily, which does have the side effect of making address allocation nondeterministic, sometimes based on dictionary-iteration order.

9.8.5 Changes to loading

The `hook_symbol` method will no longer attempt to redo relocations for the given symbol, instead just hooking directly over the address of the symbol in whatever library it comes from. This speeds up loading substantially and ensures more consistent behavior for when mixing and matching native library code and `SimProcedure` summaries.

The `angr externs` object has been moved into `CLE`, which will ALWAYS make sure that every dependency is resolved to something, never left unrelocated. Similarly, `CLE` provides the “kernel object” used to provide addresses for syscalls now.

Before	After
<code>project._extern_obj</code>	<code>loader.extern_object</code>
<code>project._syscall_obj</code>	<code>loader.kernel_object</code>

Several properties and methods have been renamed in CLE in order to maintain a more consistent and explicit API. The most common changes are listed below:

Before	After
<code>loader.whats_at()</code>	<code>loader.describe_addr</code>
<code>loader.addr_belongs_to_object()</code>	<code>loader.find_object_containing()</code>
<code>loader.find_symbol_name()</code>	<code>loader.find_symbol().name</code>
whatever the hell you were doing before to look up a symbol	<code>loader.find_symbol(name or addr)</code>
<code>loader.find_module_name()</code>	<code>loader.find_object_containing().provides</code>
<code>loader.find_symbol_got_entry()</code>	<code>loader.find_relevant_relocations()</code>
<code>loader.main_bin</code>	<code>loader.main_object</code>
<code>anything.get_min_addr()</code>	<code>anything.min_addr</code>
<code>symbol.addr</code>	<code>symbol.linked_addr</code>

9.8.6 Changes to the solver interface

We cleaned up the menagerie of functions present on `state.solver` (if you're still referring to it as `state.se` you should stop) and simplified it into a cleaner interface:

- `solver.eval(expression)` will give you one possible solution to the given expression.
- `solver.eval_one(expression)` will give you the solution to the given expression, or throw an error if more than one solution is possible.
- `solver.eval_upto(expression, n)` will give you up to `n` solutions to the given expression, returning fewer than `n` if fewer than `n` are possible.
- `solver.eval_atleast(expression, n)` will give you `n` solutions to the given expression, throwing an error if fewer than `n` are possible.
- `solver.eval_exact(expression, n)` will give you `n` solutions to the given expression, throwing an error if fewer or more than are possible.
- `solver.min(expression)` will give you the minimum possible solution to the given expression.
- `solver.max(expression)` will give you the maximum possible solution to the given expression.

Additionally, all of these methods can take the following keyword arguments:

- `extra_constraints` can be passed as a tuple of constraints. These constraints will be taken into account for this evaluation, but will not be added to the state.
- `cast_to` can be passed a data type to cast the result to. Currently, this can only be `str`, which will cause the method to return the byte representation of the underlying data. For example, `state.solver.eval(state.solver.BVV(0x41424344, 32, cast_to=str))` will return "ABCD".

API REFERENCE

```
class angr.SimProcedure(project=None, cc=None, prototype=None, symbolic_return=None, returns=None,  
                      is_syscall=False, is_stub=False, num_args=None, display_name=None,  
                      library_name=None, is_function=None, **kwargs)
```

Bases: `object`

A SimProcedure is a wonderful object which describes a procedure to run on a state.

You may subclass SimProcedure and override `run()`, replacing it with mutating `self.state` however you like, and then either returning a value or jumping away somehow.

A detailed discussion of programming SimProcedures may be found at <https://docs.angr.io/extending-angr/simprocedures>

Parameters

arch – The architecture to use for this procedure

The following parameters are optional:

Parameters

- **symbolic_return** – Whether the procedure’s return value should be stubbed into a single symbolic variable constrained to the real return value
- **returns** – Whether the procedure should return to its caller afterwards
- **is_syscall** – Whether this procedure is a syscall
- **num_args** – The number of arguments this procedure should extract
- **display_name** – The name to use when displaying this procedure
- **library_name** – The name of the library from which the function we’re emulating comes
- **cc** – The SimCC to use for this procedure
- **sim_kwargs** – Additional keyword arguments to be passed to `run()`
- **is_function** – Whether this procedure emulates a function

The following class variables should be set if necessary when implementing a new SimProcedure:

Variables

- **NO_RET** – Set this to true if control flow will never return from this function
- **DYNAMIC_RET** – Set this to true if whether the control flow returns from this function or not depends on the context (e.g., libc’s `error()` call). Must implement `dynamic_returns()` method.
- **ADDS_EXITS** – Set this to true if you do any control flow other than returning
- **IS_FUNCTION** – Does this procedure simulate a function? True by default

- **ARGS_MISMATCH** – Does this procedure have a different list of arguments than what is provided in the function specification? This may happen when we manually extract arguments in the `run()` method of a `SimProcedure`. False by default.
- **local_vars** – If you use `self.call()`, set this to a list of all the local variable names in your class. They will be restored on return.

The following instance variables are available when working with simprocedures from the inside or the outside:

Variables

- **project** – The associated angr project
- **arch** – The associated architecture
- **addr** – The linear address at which the procedure is executing
- **cc** – The calling convention in use for engaging with the ABI
- **canonical** – The canonical version of this `SimProcedure`. Procedures are deepcopied for many reasons, including to be able to store state related to a specific run and to be able to hook continuations.
- **kwargs** – Any extra keyword arguments used to construct the procedure; will be passed to `run`
- **display_name** – See the eponymous parameter
- **library_name** – See the eponymous parameter
- **abi** – If this is a syscall simprocedure, which ABI are we using to map the syscall numbers?
- **symbolic_return** – See the eponymous parameter
- **syscall_number** – If this procedure is a syscall, the number will be populated here.
- **returns** – See eponymous parameter and `NO_RET` cvar
- **is_syscall** – See eponymous parameter
- **is_function** – See eponymous parameter and cvar
- **is_stub** – See eponymous parameter
- **is_continuation** – Whether this procedure is the original or a continuation resulting from `self.call()`
- **continuations** – A mapping from name to each known continuation
- **run_func** – The name of the function implementing the procedure. “run” by default, but different in continuations.
- **num_args** – The number of arguments to the procedure. If not provided in the parameter, extracted from the definition of `self.run`

The following instance variables are only used in a copy of the procedure that is actually executing on a state:

Variables

- **state** – The `SimState` we should be mutating to perform the procedure
- **successors** – The `SimSuccessors` associated with the current step
- **arguments** – The function arguments, deserialized from the state
- **arg_session** – The `ArgSession` that was used to parse arguments out of the state, in case you need it for varargs

- **use_state_arguments** – Whether we’re using arguments extracted from the state or manually provided
- **ret_to** – The current return address
- **ret_expr** – The computed return value
- **call_ret_expr** – The return value from having used `self.call()`
- **inhibit_autoret** – Whether we should avoid automatically adding an exit for returning once the run function ends
- **arg_session** – The ArgSession object that was used to extract the runtime argument values. Useful for if you want to extract variadic args.

```
__init__(project=None, cc=None, prototype=None, symbolic_return=None, returns=None,
         is_syscall=False, is_stub=False, num_args=None, display_name=None, library_name=None,
         is_function=None, **kwargs)
```

state: *SimState*

```
execute(state, successors=None, arguments=None, ret_to=None)
```

Call this method with a SimState and a SimSuccessors to execute the procedure.

Alternately, successors may be none if this is an inline call. In that case, you should provide arguments to the function.

```
make_continuation(name)
```

```
NO_RET = False
```

```
DYNAMIC_RET = False
```

```
ADDS_EXITS = False
```

```
IS_FUNCTION = True
```

```
ARGS_MISMATCH = False
```

```
ALT_NAMES = None
```

```
local_vars: Tuple[str, ...] = ()
```

```
run(*args, **kwargs)
```

Implement the actual procedure here!

```
static_exits(blocks, **kwargs)
```

Get new exits by performing static analysis and heuristics. This is a fast and best-effort approach to get new exits for scenarios where states are not available (e.g. when building a fast CFG).

Parameters

blocks (*list*) – Blocks that are executed before reaching this SimProcedure.

Returns

A list of dicts. Each dict should contain the following entries: ‘address’, ‘jumpkind’, and ‘namehint’.

Return type

list

dynamic_returns(*blocks*, ***kwargs*)

Determines if a call to this function returns or not by performing static analysis and heuristics.

Parameters

blocks – Blocks that are executed before reaching this SimProcedure.

Return type

`bool`

Returns

True if the call returns, False otherwise.

property should_add_successors

set_args(*args*)

va_arg(*ty*, *index=None*)

inline_call(*procedure*, **arguments*, ***kwargs*)

Call another SimProcedure in-line to retrieve its return value. Returns an instance of the procedure with the `ret_expr` property set.

Parameters

- **procedure** – The class of the procedure to execute
- **arguments** – Any additional positional args will be used as arguments to the procedure call
- **sim_kwargs** – Any additional keyword args will be passed as `sim_kwargs` to the procedure constructor

fix_prototype_returnty(*ret_size*)

ret(*expr=None*)

Add an exit representing a return from this function. If this is not an inline call, grab a return address from the state and jump to it. If this is not an inline call, set a return expression with the calling convention.

call(*addr*, *args*, *continue_at*, *cc=None*, *prototype=None*, *jumpkind='Ijk_Call'*)

Add an exit representing calling another function via pointer.

Parameters

- **addr** – The address of the function to call
- **args** – The list of arguments to call the function with
- **continue_at** – Later, when the called function returns, execution of the current procedure will continue in the named method.
- **cc** – Optional: use this calling convention for calling the new function. Default is to use the current convention.
- **prototype** – Optional: The prototype to use for the call. Will default to all-ints.

jump(*addr*, *jumpkind='Ijk_Boring'*)

Add an exit representing jumping to an address.

exit(*exit_code*)

Add an exit representing terminating the program.

ty_ptr(*ty*)

property `is_java`

property `argument_types`

property `return_type`

class `angr.BP`(*when*='before', *enabled*=None, *condition*=None, *action*=None, ***kwargs*)

Bases: `object`

A breakpoint.

__init__(*when*='before', *enabled*=None, *condition*=None, *action*=None, ***kwargs*)

check(*state*, *when*)

Checks state *state* to see if the breakpoint should fire.

Parameters

- **state** – The state.
- **when** – Whether the check is happening before or after the event.

Returns

A boolean representing whether the checkpoint should fire.

fire(*state*)

Trigger the breakpoint.

Parameters

state – The state.

class `angr.SimStatePlugin`

Bases: `object`

This is a base class for SimState plugins. A SimState plugin will be copied along with the state when the state is branched. They are intended to be used for things such as tracking open files, tracking heap details, and providing storage and persistence for SimProcedures.

STRONGREF_STATE = `False`

__init__()

set_state(*state*)

Sets a new state (for example, if the state has been branched)

set_strongref_state(*state*)

copy(*_memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

static memo(f)

A decorator function you should apply to copy

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you "deepen" both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(others)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`


```
classmethod register_default(name, xtr=None)
```

```
init_state()
```

Use this function to perform any initialization on the state at plugin-add time

```
class angr.Project(thing, default_analysis_mode=None, ignore_functions=None, use_sim_procedures=True,
                  exclude_sim_procedures_func=None, exclude_sim_procedures_list=(), arch=None,
                  simos=None, engine=None, load_options=None, translation_cache=True,
                  selfmodifying_code=False, support_selfmodifying_code=None, store_function=None,
                  load_function=None, analyses_preset=None, concrete_target=None,
                  eager_ifunc_resolution=None, **kwargs)
```

Bases: `object`

This is the main class of the angr module. It is meant to contain a set of binaries and the relationships between them, and perform analyses on them.

Parameters

- **thing** – The path to the main executable object to analyze, or a CLE Loader object.
- **arch** (`Arch`) –
- **load_options** (`Dict[str, Any] | None`) –
- **selfmodifying_code** (`bool`) –
- **support_selfmodifying_code** (`bool | None`) –

The following parameters are optional.

Parameters

- **default_analysis_mode** – The mode of analysis to use by default. Defaults to ‘symbolic’.
- **ignore_functions** – A list of function names that, when imported from shared libraries, should never be stepped into in analysis (calls will return an unconstrained value).
- **use_sim_procedures** – Whether to replace resolved dependencies for which simprocedures are available with said simprocedures.
- **exclude_sim_procedures_func** – A function that, when passed a function name, returns whether or not to wrap it with a simprocedure.
- **exclude_sim_procedures_list** – A list of functions to *not* wrap with simprocedures.
- **arch** – The target architecture (auto-detected otherwise).
- **simos** – a SimOS class to use for this project.
- **engine** – The SimEngine class to use for this project.
- **translation_cache** (`bool`) – If True, cache translated basic blocks rather than re-translating them.
- **selfmodifying_code** (`bool`) – Whether we aggressively support self-modifying code. When enabled, emulation will try to read code from the current state instead of the original memory, regardless of the current memory protections.
- **store_function** – A function that defines how the Project should be stored. Default to pickling.
- **load_function** – A function that defines how the Project should be loaded. Default to unpickling.

- **analyses_preset** (*angr.misc.PluginPreset*) – The plugin preset for the analyses provider (i.e. Analyses instance).
- **load_options** (*Dict[str, Any]* | *None*) –
- **support_selfmodifying_code** (*bool* | *None*) –

Any additional keyword arguments passed will be passed onto `cle.Loader`.

Variables

- **analyses** – The available analyses.
- **entry** – The program entrypoint.
- **factory** – Provides access to important analysis elements such as path groups and symbolic execution results.
- **filename** – The filename of the executable.
- **loader** – The program loader.
- **storage** – Dictionary of things that should be loaded/stored with the Project.

Parameters

- **arch** (*Arch*) –
- **load_options** (*Dict[str, Any]* | *None*) –
- **selfmodifying_code** (*bool*) –
- **support_selfmodifying_code** (*bool* | *None*) –

__init__ (*thing*, *default_analysis_mode=None*, *ignore_functions=None*, *use_sim_procedures=True*, *exclude_sim_procedures_func=None*, *exclude_sim_procedures_list=()*, *arch=None*, *simos=None*, *engine=None*, *load_options=None*, *translation_cache=True*, *selfmodifying_code=False*, *support_selfmodifying_code=None*, *store_function=None*, *load_function=None*, *analyses_preset=None*, *concrete_target=None*, *eager_ifunc_resolution=None*, ***kwargs*)

Parameters

- **load_options** (*Dict[str, Any]* | *None*) –
- **selfmodifying_code** (*bool*) –
- **support_selfmodifying_code** (*bool* | *None*) –

arch: *Arch*

property analyses: *AnalysesHubWithDefault*

hook (*addr*, *hook=None*, *length=0*, *kwargs=None*, *replace=False*)

Hook a section of code with a custom function. This is used internally to provide symbolic summaries of library functions, and can be used to instrument execution or to modify control flow.

When hook is not specified, it returns a function decorator that allows easy hooking. Usage:

```
# Assuming proj is an instance of angr.Project, we will add a custom hook at
↳ the entry
# point of the project.
@proj.hook(proj.entry)
def my_hook(state):
    print("Welcome to execution!")
```

Parameters

- **addr** – The address to hook.
- **hook** – A `angr.project.Hook` describing a procedure to run at the given address. You may also pass in a `SimProcedure` class or a function directly and it will be wrapped in a `Hook` object for you.
- **length** – If you provide a function for the hook, this is the number of bytes that will be skipped by executing the hook by default.
- **kwargs** – If you provide a `SimProcedure` for the hook, these are the keyword arguments that will be passed to the procedure’s `run` method eventually.
- **replace** (`Optional[bool]`) – Control the behavior on finding that the address is already hooked. If true, silently replace the hook. If false (default), warn and do not replace the hook. If none, warn and replace the hook.

`is_hooked(addr)`

Returns True if `addr` is hooked.

Parameters

addr – An address.

Return type

`bool`

Returns

True if `addr` is hooked, False otherwise.

`hooked_by(addr)`

Returns the current hook for `addr`.

Parameters

addr – An address.

Return type

`Optional[SimProcedure]`

Returns

None if the address is not hooked.

`unhook(addr)`

Remove a hook.

Parameters

addr – The address of the hook.

`hook_symbol(symbol_name, simproc, kwargs=None, replace=None)`

Resolve a dependency in a binary. Looks up the address of the given symbol, and then hooks that address. If the symbol was not available in the loaded libraries, this address may be provided by the CLE externs object.

Additionally, if instead of a symbol name you provide an address, some secret functionality will kick in and you will probably just hook that address, UNLESS you’re on powerpc64 ABIv1 or some yet-unknown scary ABI that has its function pointers point to something other than the actual functions, in which case it’ll do the right thing.

Parameters

- **symbol_name** – The name of the dependency to resolve.

- **simproc** – The SimProcedure instance (or function) with which to hook the symbol
- **kwargs** – If you provide a SimProcedure for the hook, these are the keyword arguments that will be passed to the procedure’s *run* method eventually.
- **replace** (*Optional[bool]*) – Control the behavior on finding that the address is already hooked. If true, silently replace the hook. If false, warn and do not replace the hook. If none (default), warn and replace the hook.

Returns

The address of the new symbol.

Return type

int

symbol_hooked_by(*symbol_name*)

Return the SimProcedure, if it exists, for the given symbol name.

Parameters

symbol_name (*str*) – Name of the symbol.

Return type

Optional[SimProcedure]

Returns

None if the address is not hooked.

is_symbol_hooked(*symbol_name*)

Check if a symbol is already hooked.

Parameters

symbol_name (*str*) – Name of the symbol.

Returns

True if the symbol can be resolved and is hooked, False otherwise.

Return type

bool

unhook_symbol(*symbol_name*)

Remove the hook on a symbol. This function will fail if the symbol is provided by the extern object, as that would result in a state where analysis would be unable to cope with a call to this symbol.

rehook_symbol(*new_address, symbol_name, stubs_on_sync*)

Move the hook for a symbol to a specific address :type new_address: :param new_address: the new address that will trigger the SimProc execution :type symbol_name: :param symbol_name: the name of the symbol (f.i. strcmp) :return: None

execute(**args, **kwargs*)

This function is a symbolic execution helper in the simple style supported by triton and manticore. It designed to be run after setting up hooks (see Project.hook), in which the symbolic state can be checked.

This function can be run in three different ways:

- When run with no parameters, this function begins symbolic execution from the entrypoint.
- It can also be run with a “state” parameter specifying a SimState to begin symbolic execution from.
- Finally, it can accept any arbitrary keyword arguments, which are all passed to project.factory.full_init_state.

If symbolic execution finishes, this function returns the resulting simulation manager.

`terminate_execution()`

Terminates a symbolic execution that was started with `Project.execute()`.

`angr.load_shellcode(shellcode, arch, start_offset=0, load_address=0, thumb=False, **kwargs)`

Load a new project based on a snippet of assembly or bytecode.

Parameters

- **shellcode** (`Union[bytes, str]`) – The data to load, as either a bytestring of instructions or a string of assembly text
- **arch** – The name of the arch to use, or an `archinfo` class
- **start_offset** – The offset into the data to start analysis (default 0)
- **load_address** – The address to place the data in memory (default 0)
- **thumb** – Whether this is ARM Thumb shellcode

```
class angr.Blade(graph, dst_run, dst_stmt_idx, direction='backward', project=None, cfg=None,
                 ignore_sp=False, ignore_bp=False, ignored_regs=None, max_level=3, base_state=None,
                 stop_at_calls=False, cross_insn_opt=False, max_predecessors=10, include_emarks=True)
```

Bases: `object`

Blade is a light-weight program slicer that works with networkx `DiGraph` containing `CFGNodes`. It is meant to be used in `angr` for small or on-the-fly analyses.

Parameters

- **graph** (`DiGraph`) –
- **dst_run** (`int`) –
- **dst_stmt_idx** (`int`) –
- **direction** (`str`) –
- **ignore_sp** (`bool`) –
- **ignore_bp** (`bool`) –
- **max_level** (`int`) –
- **stop_at_calls** (`bool`) –
- **max_predecessors** (`int`) –
- **include_emarks** (`bool`) –

```
__init__(graph, dst_run, dst_stmt_idx, direction='backward', project=None, cfg=None, ignore_sp=False,
         ignore_bp=False, ignored_regs=None, max_level=3, base_state=None, stop_at_calls=False,
         cross_insn_opt=False, max_predecessors=10, include_emarks=True)
```

Parameters

- **graph** (`DiGraph`) – A graph representing the control flow graph. Note that it does not take `angr.analyses.CFGEEmulated` or `angr.analyses.CFGFast`.
- **dst_run** (`int`) – An address specifying the target `SimRun`.
- **dst_stmt_idx** (`int`) – The target statement index. -1 means executing until the last statement.
- **direction** (`str`) – ‘backward’ or ‘forward’ slicing. Forward slicing is not yet supported.
- **project** (`angr.Project`) – The project instance.

- **cfg** (*angr.analyses.CFGBase*) – the CFG instance. It will be made mandatory later.
- **ignore_sp** (*bool*) – Whether the stack pointer should be ignored in dependency tracking. Any dependency from/to stack pointers will be ignored if this options is True.
- **ignore_bp** (*bool*) – Whether the base pointer should be ignored or not.
- **max_level** (*int*) – The maximum number of blocks that we trace back for.
- **stop_at_calls** (*bool*) – Limit slicing within a single function. Do not proceed when encounters a call edge.
- **include_emarks** (*bool*) – Should IMarks (instruction boundaries) be included in the slice.
- **max_predecessors** (*int*) –

Returns

None

property slice

dbg_repr(*arch=None*)

class *angr.SimOS*(*project, name=None*)

Bases: *object*

A class describing OS/arch-level configuration.

Parameters

project (*angr.Project*) –

__init__(*project, name=None*)

Parameters

project (*Project*) –

configure_project()

Configure the project to set up global settings (like SimProcedures).

state_blank(*addr=None, initial_prefix=None, brk=None, stack_end=None, stack_size=8388608, stdin=None, thread_idx=None, permissions_backer=None, **kwargs*)

Initialize a blank state.

All parameters are optional.

Parameters

- **addr** – The execution start address.
- **initial_prefix** –
- **stack_end** – The end of the stack (i.e., the byte after the last valid stack address).
- **stack_size** – The number of bytes to allocate for stack space
- **brk** – The address of the process' break.

Returns

The initialized SimState.

Any additional arguments will be passed to the SimState constructor

state_entry(***kwargs*)

state_full_init(**kwargs)

state_call(addr, *args, **kwargs)

prepare_call_state(calling_state, initial_state=None, preserve_registers=(), preserve_memory=())

This function prepares a state that is executing a call instruction. If given an initial_state, it copies over all of the critical registers to it from the calling_state. Otherwise, it prepares the calling_state for action.

This is mostly used to create minimalistic for CFG generation. Some ABIs, such as MIPS PIE and x86 PIE, require certain information to be maintained in certain registers. For example, for PIE MIPS, this function transfer t9, gp, and ra to the new state.

prepare_function_symbol(symbol_name, basic_addr=None)

Prepare the address space with the data necessary to perform relocations pointing to the given symbol

Returns a 2-tuple. The first item is the address of the function code, the second is the address of the relocation target.

handle_exception(successors, engine, exception)

Perform exception handling. This method will be called when, during execution, a SimException is thrown. Currently, this can only indicate a segfault, but in the future it could indicate any unexpected exceptional behavior that can't be handled by ordinary control flow.

The method may mutate the provided SimSuccessors object in any way it likes, or re-raise the exception.

Parameters

- **successors** – The SimSuccessors object currently being executed on
- **engine** – The engine that was processing this step
- **exception** – The actual exception object

syscall(state, allow_unsupported=True)

syscall_abi(state)

Return type

str

syscall_cc(state)

Return type

Optional[SimCCSyscall]

is_syscall_addr(addr)

syscall_from_addr(addr, allow_unsupported=True)

syscall_from_number(number, allow_unsupported=True, abi=None)

setup_gdt(state, gdt)

Write the GlobalDescriptorTable object in the current state memory

Parameters

- **state** – state in which to write the GDT
- **gdt** – GlobalDescriptorTable object

Returns

generate_gdt(fs, gs, fs_size=4294967295, gs_size=4294967295)

Generate a GlobalDescriptorTable object and populate it using the value of the gs and fs register

Parameters

- **fs** – value of the fs segment register
- **gs** – value of the gs segment register
- **fs_size** – size of the fs segment register
- **gs_size** – size of the gs segment register

Returns

gdt a GlobalDescriptorTable object

```
class angr.Block(addr, project=None, arch=None, size=None, byte_string=None, vex=None, thumb=False,
                  backup_state=None, extra_stop_points=None, opt_level=None, num_inst=None, traceflags=0,
                  strict_block_end=None, collect_data_refs=False, cross_insn_opt=True,
                  load_from_ro_regions=False, initial_regs=None)
```

Bases: [Serializable](#)

Represents a basic block in a binary or a program.

BLOCK_MAX_SIZE = 4096

```
__init__(addr, project=None, arch=None, size=None, byte_string=None, vex=None, thumb=False,
          backup_state=None, extra_stop_points=None, opt_level=None, num_inst=None, traceflags=0,
          strict_block_end=None, collect_data_refs=False, cross_insn_opt=True,
          load_from_ro_regions=False, initial_regs=None)
```

arch

thumb

addr

size

pp(**kwargs)

set_initial_regs()

static reset_initial_regs()

property vex: [IRSB](#)

property vex_nostmt

property disassembly: [DisassemblerBlock](#)

Provide a disassembly object using whatever disassembler is available

property capstone

property codenode

property bytes

property instructions

property instruction_addrs

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(cmsg)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

```
class angr.SimulationManager(project, active_states=None, stashes=None, hierarchy=None,
                             resilience=None, save_unsat=False, auto_drop=None, errored=None,
                             completion_mode=<built-in function any>, techniques=None,
                             suggestions=True, **kwargs)
```

Bases: [object](#)

The Simulation Manager is the future future.

Simulation managers allow you to wrangle multiple states in a slick way. States are organized into “stashes”, which you can step forward, filter, merge, and move around as you wish. This allows you to, for example, step two different stashes of states at different rates, then merge them together.

Stashes can be accessed as attributes (i.e. `.active`). A multiplexed stash can be retrieved by prepending the name with `mp_`, e.g. `.mp_active`. A single state from the stash can be retrieved by prepending the name with `one_`, e.g. `.one_active`.

Note that you shouldn’t usually be constructing SimulationManagers directly - there is a convenient shortcut for creating them in `Project.factory`: see [`AngrObjectFactory`](#) .

The most important methods you should look at are `step`, `explore`, and `use_technique`.

Parameters

- **project** ([`Angr.project.Project`](#)) – A Project instance.
- **stashes** – A dictionary to use as the stash store.
- **active_states** – Active states to seed the “active” stash with.
- **hierarchy** – A StateHierarchy object to use to track the relationships between states.
- **resilience** – A set of errors to catch during stepping to put a state in the `errored` list. You may also provide the values `False`, `None` (default), or `True` to catch, respectively, no errors, all angr-specific errors, and a set of many common errors.
- **save_unsat** – Set to `True` in order to introduce unsatisfiable states into the `unsat` stash instead of discarding them immediately.
- **auto_drop** – A set of stash names which should be treated as garbage chutes.
- **completion_mode** – A function describing how multiple exploration techniques with the `complete` hook set will interact. By default, the builtin function `any`.

- **techniques** – A list of techniques that should be pre-set to use with this manager.
- **suggestions** – Whether to automatically install the Suggestions exploration technique. Default True.

Variables

- **errored** – Not a stash, but a list of ErrorRecords. Whenever a step raises an exception that we catch, the state and some information about the error are placed in this list. You can adjust the list of caught exceptions with the *resilience* parameter.
- **stashes** – All the stashes on this instance, as a dictionary.
- **completion_mode** – A function describing how multiple exploration techniques with the complete hook set will interact. By default, the builtin function any.

`ALL = '_ALL'`

`DROP = '_DROP'`

`__init__(project, active_states=None, stashes=None, hierarchy=None, resilience=None, save_unsat=False, auto_drop=None, errored=None, completion_mode=<built-in function any>, techniques=None, suggestions=True, **kwargs)`

`active: List[SimState]`

`stashed: List[SimState]`

`pruned: List[SimState]`

`unsat: List[SimState]`

`deadended: List[SimState]`

`unconstrained: List[SimState]`

`found: List[SimState]`

`one_active: SimState`

`one_stashed: SimState`

`one_pruned: SimState`

`one_unsat: SimState`

`one_deadended: SimState`

`one_unconstrained: SimState`

`one_found: SimState`

`property errored`

`property stashes: DefaultDict[str, List[SimState]]`

`multiplex(*stashes)`

Multiplex across several stashes.

Parameters

stashes – the stashes to multiplex

Returns

a multiplexed list of states from the stashes in question, in the specified order

`copy(deep=False)`

Make a copy of this simulation manager. Pass `deep=True` to copy all the states in it as well.

If the current callstack includes hooked methods, the already-called methods will not be included in the copy.

`use_technique(tech)`

Use an exploration technique with this SimulationManager.

Techniques can be found in [`angr.exploration_techniques`](#).

Parameters

tech ([ExplorationTechnique](#)) – An ExplorationTechnique object that contains code to modify this SimulationManager’s behavior.

Returns

The technique that was added, for convenience

`remove_technique(tech)`

Remove an exploration technique from a list of active techniques.

Parameters

tech ([ExplorationTechnique](#)) – An ExplorationTechnique object.

`explore(stash='active', n=None, find=None, avoid=None, find_stash='found', avoid_stash='avoid', cfg=None, num_find=1, avoid_priority=False, **kwargs)`

Tick stash “stash” forward (up to “n” times or until “num_find” states are found), looking for condition “find”, avoiding condition “avoid”. Stores found states into “find_stash” and avoided states into “avoid_stash”.

The “find” and “avoid” parameters may be any of:

- An address to find
- A set or list of addresses to find
- A function that takes a state and returns whether or not it matches.

If an angr CFG is passed in as the “cfg” parameter and “find” is either a number or a list or a set, then any states which cannot possibly reach a success state without going through a failure state will be preemptively avoided.

`run(stash='active', n=None, until=None, **kwargs)`

Run until the SimulationManager has reached a completed state, according to the current exploration techniques. If no exploration techniques that define a completion state are being used, run until there is nothing left to run.

Parameters

- **stash** – Operate on this stash
- **n** – Step at most this many times
- **until** – If provided, should be a function that takes a SimulationManager and returns True or False. Stepping will terminate when it is True.

Returns

The simulation manager, for chaining.

Return type

SimulationManager

complete()

Returns whether or not this manager has reached a “completed” state.

step(*stash='active', target_stash=None, n=None, selector_func=None, step_func=None, error_list=None, successor_func=None, until=None, filter_func=None, **run_args*)

Step a stash of states forward and categorize the successors appropriately.

The parameters to this function allow you to control everything about the stepping and categorization process.

Parameters

- **stash** – The name of the stash to step (default: ‘active’)
- **target_stash** – The name of the stash to put the results in (default: same as stash)
- **error_list** – The list to put ErroredState objects in (default: `self.errorred`)
- **selector_func** – If provided, should be a function that takes a state and returns a boolean. If True, the state will be stepped. Otherwise, it will be kept as-is.
- **step_func** – If provided, should be a function that takes a SimulationManager and returns a SimulationManager. Will be called with the SimulationManager at every step. Note that this function should not actually perform any stepping - it is meant to be a maintenance function called after each step.
- **successor_func** – If provided, should be a function that takes a state and return its successors. Otherwise, `project.factory.successors` will be used.
- **filter_func** – If provided, should be a function that takes a state and return the name of the stash, to which the state should be moved.
- **until** – (DEPRECATED) If provided, should be a function that takes a SimulationManager and returns True or False. Stepping will terminate when it is True.
- **n** – (DEPRECATED) The number of times to step (default: 1 if “until” is not provided)

Additionally, you can pass in any of the following keyword args for `project.factory.successors`:

Parameters

- **jumpkind** – The jumpkind of the previous exit
- **addr** – An address to execute at instead of the state’s ip.
- **stmt_whitelist** – A list of stmt indexes to which to confine execution.
- **last_stmt** – A statement index at which to stop execution.
- **thumb** – Whether the block should be lifted in ARM’s THUMB mode.
- **backup_state** – A state to read bytes from instead of using project memory.
- **opt_level** – The VEX optimization level to use.
- **insn_bytes** – A string of bytes to use for the block instead of the project.
- **size** – The maximum size of the block, in bytes.
- **num_inst** – The maximum number of instructions.
- **traceflags** – traceflags to be passed to VEX. Default: 0

Returns

The simulation manager, for chaining.

Return type

SimulationManager

step_state(state, successor_func=None, error_list=None, **run_args)

Don't use this function manually - it is meant to interface with exploration techniques.

filter(state, filter_func=None)

Don't use this function manually - it is meant to interface with exploration techniques.

selector(state, selector_func=None)

Don't use this function manually - it is meant to interface with exploration techniques.

successors(state, successor_func=None, **run_args)

Don't use this function manually - it is meant to interface with exploration techniques.

prune(filter_func=None, from_stash='active', to_stash='pruned')

Prune unsatisfiable states from a stash.

This function will move all unsatisfiable states in the given stash into a different stash.

Parameters

- **filter_func** – Only prune states that match this filter.
- **from_stash** – Prune states from this stash. (default: 'active')
- **to_stash** – Put pruned states in this stash. (default: 'pruned')

Returns

The simulation manager, for chaining.

Return type

SimulationManager

populate(stash, states)

Populate a stash with a collection of states.

Parameters

- **stash** – A stash to populate.
- **states** – A list of states with which to populate the stash.

absorb(simgr)

Collect all the states from simgr and put them in their corresponding stashes in this manager. This will not modify simgr.

move(from_stash, to_stash, filter_func=None)

Move states from one stash to another.

Parameters

- **from_stash** – Take matching states from this stash.
- **to_stash** – Put matching states into this stash.
- **filter_func** – Stash states that match this filter. Should be a function that takes a state and returns True or False. (default: stash all states)

Returns

The simulation manager, for chaining.

Return type*SimulationManager***stash**(*filter_func=None, from_stash='active', to_stash='stashed'*)

Stash some states. This is an alias for `move()`, with defaults for the stashes.

Parameters

- **filter_func** – Stash states that match this filter. Should be a function that takes a state and returns True or False. (default: stash all states)
- **from_stash** – Take matching states from this stash. (default: 'active')
- **to_stash** – Put matching states into this stash. (default: 'stashed')

Returns

The simulation manager, for chaining.

Return type*SimulationManager***unstash**(*filter_func=None, to_stash='active', from_stash='stashed'*)

Unstash some states. This is an alias for `move()`, with defaults for the stashes.

Parameters

- **filter_func** – Unstash states that match this filter. Should be a function that takes a state and returns True or False. (default: unstash all states)
- **from_stash** – take matching states from this stash. (default: 'stashed')
- **to_stash** – put matching states into this stash. (default: 'active')

Returns

The simulation manager, for chaining.

Return type*SimulationManager***drop**(*filter_func=None, stash='active'*)

Drops states from a stash. This is an alias for `move()`, with defaults for the stashes.

Parameters

- **filter_func** – Drop states that match this filter. Should be a function that takes a state and returns True or False. (default: drop all states)
- **stash** – Drop matching states from this stash. (default: 'active')

Returns

The simulation manager, for chaining.

Return type*SimulationManager***apply**(*state_func=None, stash_func=None, stash='active', to_stash=None*)

Applies a given function to a given stash.

Parameters

- **state_func** – A function to apply to every state. Should take a state and return a state. The returned state will take the place of the old state. If the function *doesn't* return a state, the old state will be used. If the function returns a list of states, they will replace the original states.

- **stash_func** – A function to apply to the whole stash. Should take a list of states and return a list of states. The resulting list will replace the stash. If both state_func and stash_func are provided state_func is applied first, then stash_func is applied on the results.
- **stash** – A stash to work with.
- **to_stash** – If specified, this stash will be used to store the resulting states instead.

Returns

The simulation manager, for chaining.

Return type

SimulationManager

split(stash_splitter=None, stash_ranker=None, state_ranker=None, limit=8, from_stash='active', to_stash='stashed')

Split a stash of states into two stashes depending on the specified options.

The stash from_stash will be split into two stashes depending on the other options passed in. If to_stash is provided, the second stash will be written there.

stash_splitter overrides stash_ranker, which in turn overrides state_ranker. If no functions are provided, the states are simply split according to the limit.

The sort done with state_ranker is ascending.

Parameters

- **stash_splitter** – A function that should take a list of states and return a tuple of two lists (the two resulting stashes).
- **stash_ranker** – A function that should take a list of states and return a sorted list of states. This list will then be split according to “limit”.
- **state_ranker** – An alternative to stash_splitter. States will be sorted with outputs of this function, which are to be used as a key. The first “limit” of them will be kept, the rest split off.
- **limit** – For use with state_ranker. The number of states to keep. Default: 8
- **from_stash** – The stash to split (default: ‘active’)
- **to_stash** – The stash to write to (default: ‘stashed’)

Returns

The simulation manager, for chaining.

Return type

SimulationManager

merge(merge_func=None, merge_key=None, stash='active', prune=True)

Merge the states in a given stash.

Parameters

- **stash** – The stash (default: ‘active’)
- **merge_func** – If provided, instead of using state.merge, call this function with the states as the argument. Should return the merged state.
- **merge_key** – If provided, should be a function that takes a state and returns a key that will compare equal for all states that are allowed to be merged together, as a first approximation. By default: uses PC, callstack, and open file descriptors.
- **prune** – Whether to prune the stash prior to merging it

Returns

The simulation manager, for chaining.

Return type

SimulationManager

class `angr.Analysis`

Bases: `object`

This class represents an analysis on the program.

Variables

- **project** – The project for this analysis.
- **kb** (`KnowledgeBase`) – The knowledgebase object.
- **_progress_callback** – A callback function for receiving the progress of this analysis. It only takes one argument, which is a float number from 0.0 to 100.0 indicating the current progress.
- **_show_progressbar** (`bool`) – If a progressbar should be shown during the analysis. It's independent from `_progress_callback`.
- **_progressbar** (`progress.Progress`) – The progress bar object.

project: `Project`

kb: `KnowledgeBase`

errors = []

named_errors = {}

`angr.register_analysis(cls, name)`

class `angr.ExplorationTechnique`

Bases: `object`

An *otiegnqvwk* is a set of hooks for a simulation manager that assists in the implementation of new techniques in symbolic exploration.

TODO: choose actual name for the functionality (techniques? strategies?)

Any number of these methods may be overridden by a subclass. To use an exploration technique, call `simgr.use_technique` with an *instance* of the technique.

__init__()

setup(simgr)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(simgr, stash='active', **kwargs)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –

- **stash**(*str*) –

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

selector(*simgr*, *state*, ***kwargs*)

Determine if a state should participate in the current round of stepping. Return True if the state should be stepped, and False if the state should not be stepped. To defer to the original selection procedure, return the result of `simgr.selector(state, **kwargs)`.

If the user provided a `selector_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

step_state(*simgr*, *state*, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a *SimSuccessors* object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

simgr (`angr.SimulationManager`) –

class `angr.StateHierarchy`

Bases: `object`

The state hierarchy holds weak references to `SimStateHistory` objects in a directed acyclic graph. It is useful for queries about a state’s ancestry, notably “what is the best ancestor state for a merge among these states” and “what is the most recent unsatisfiable state while using LAZY_SOLVES”

__init__()

get_ref(*obj*)

dead_ref(*ref*)

defer_cleanup()

add_state(*s*)

add_history(*h*)

simplify()

full_simplify()

lineage(*h*)

Returns the lineage of histories leading up to *h*.

all_successors(*h*)

history_successors(*h*)

history_predecessors(*h*)

history_contains(*h*)

unreachable_state(*state*)

unreachable_history(*h*)

most_mergeable(*states*)

Find the “most mergeable” set of states from those provided.

Parameters

states – a list of states

Returns

a tuple of: (list of states to merge, those states’ common history, list of states to not merge yet)

```
class angr.SimState(project=None, arch=None, plugins=None, mode=None, options=None,
                  add_options=None, remove_options=None, special_memory_filler=None, os_name=None,
                  plugin_preset='default', cle_memory_backer=None, dict_memory_backer=None,
                  permissions_map=None, default_permissions=3, stack_perms=None, stack_end=None,
                  stack_size=None, regioned_memory_cls=None, **kwargs)
```

Bases: [PluginHub](#)

The SimState represents the state of a program, including its memory, registers, and so forth.

Parameters

- **project** ([angr.Project](#)) – The project instance.
- **arch** ([archinfo.Arch](#) / *str*) – The architecture of the state.

Variables

- **regs** – A convenient view of the state’s registers, where each register is a property
- **mem** – A convenient view of the state’s memory, a [angr.state_plugins.view.SimMemView](#)
- **registers** – The state’s register file as a flat memory region
- **memory** – The state’s memory as a flat memory region
- **solver** – The symbolic solver and variable manager for this state
- **inspect** – The breakpoint manager, a [angr.state_plugins.inspect.SimInspector](#)
- **log** – Information about the state’s history
- **scratch** – Information about the current execution step
- **posix** – MISNOMER: information about the operating system or environment model
- **fs** – The current state of the simulated filesystem
- **libc** – Information about the standard library we are emulating
- **cgc** – Information about the cgc environment
- **uc_manager** – Control of under-constrained symbolic execution
- **unicorn** – Control of the Unicorn Engine

solver: [SimSolver](#)

posix: [SimSystemPosix](#)

registers: [DefaultMemory](#)

regs: [SimRegNameView](#)

memory: [DefaultMemory](#)

callstack: [CallStack](#)

mem: [SimMemView](#)

history: [SimStateHistory](#)

inspect: [SimInspector](#)

jni_references: [SimStateJNIReferences](#)

scratch: `SimStateScratch`

__init__(*project=None, arch=None, plugins=None, mode=None, options=None, add_options=None, remove_options=None, special_memory_filler=None, os_name=None, plugin_preset='default', cle_memory_backer=None, dict_memory_backer=None, permissions_map=None, default_permissions=3, stack_perms=None, stack_end=None, stack_size=None, regioned_memory_cls=None, **kwargs*)

property plugins

property se

Deprecated alias for *solver*

property ip

Get the instruction pointer expression, trigger `SimInspect` breakpoints, and generate `SimActions`. Use `_ip` to not trigger breakpoints or generate actions.

Returns

an expression

property addr

Get the concrete address of the instruction pointer, without triggering `SimInspect` breakpoints or generating `SimActions`. An integer is returned, or an exception is raised if the instruction pointer is symbolic.

Returns

an int

property arch: `Arch`

T = ~T

get_plugin(*name*)

Get the plugin named *name*. If no such plugin is currently active, try to activate a new one using the current preset.

has_plugin(*name*)

Return whether or not a plugin with the name *name* is currently active.

register_plugin(*name, plugin, inhibit_init=False*)

Add a new plugin *plugin* with name *name* to the active plugins.

property javavm_memory

In case of an `JavaVM` with `JNI` support, a state can store the memory plugin twice; one for the native and one for the java view of the state.

Returns

The `JavaVM` view of the memory plugin.

property javavm_registers

In case of an `JavaVM` with `JNI` support, a state can store the registers plugin twice; one for the native and one for the java view of the state.

Returns

The `JavaVM` view of the registers plugin.

simplify(**args*)

Simplify this state's constraints.

add_constraints(*args, **kwargs)

Add some constraints to the state.

You may pass in any number of symbolic booleans as variadic positional arguments.

satisfiable(**kwargs)

Whether the state's constraints are satisfiable

downsize()

Clean up after the solver engine. Calling this when a state no longer needs to be solved on will reduce memory usage.

step(**kwargs)

Perform a step of symbolic execution using this state. Any arguments to *AngrObjectFactory.successors* can be passed to this.

Returns

A SimSuccessors object categorizing the results of the step.

block(*args, **kwargs)

Represent the basic block at this state's instruction pointer. Any arguments to *AngrObjectFactory.block* can be passed to this.

Returns

A Block object describing the basic block of code at this point.

copy()

Returns a copy of the state.

merge(*others, **kwargs)

Merges this state with the other states. Returns the merging result, merged state, and the merge flag.

Parameters

- **states** – the states to merge
- **merge_conditions** – a tuple of the conditions under which each state holds
- **common_ancestor** – a state that represents the common history between the states being merged. Usually it is only available when `EFFICIENT_STATE_MERGING` is enabled, otherwise weak-refed states might be dropped from state history instances.
- **plugin_whitelist** – a list of plugin names that will be merged. If this option is given and is not None, any plugin that is not inside this list will not be merged, and will be created as a fresh instance in the new state.
- **common_ancestor_history** – a SimStateHistory instance that represents the common history between the states being merged. This is to allow optimal state merging when `EFFICIENT_STATE_MERGING` is disabled.

Returns

(merged state, merge flag, a bool indicating if any merging occurred)

widen(*others)

Perform a widening between self and other states :type others: :param others: :return:

reg_concrete(*args, **kwargs)

Returns the contents of a register but, if that register is symbolic, raises a SimValueError.

mem_concrete(*args, **kwargs)

Returns the contents of a memory but, if the contents are symbolic, raises a SimValueError.

stack_push(*thing*)

Push ‘thing’ to the stack, writing the thing to memory and adjusting the stack pointer.

stack_pop()

Pops from the stack and returns the popped thing. The length will be the architecture word size.

stack_read(*offset*, *length*, *bp=False*)

Reads length bytes, at an offset into the stack.

Parameters

- **offset** – The offset from the stack pointer.
- **length** – The number of bytes to read.
- **bp** – If True, offset from the BP instead of the SP. Default: False.

make_concrete_int(*expr*)

prepare_callsite(*retval*, *args*, *cc='wtf'*)

dbg_print_stack(*depth=None*, *sp=None*)

Only used for debugging purposes. Return the current stack info in formatted string. If depth is None, the current stack frame (from sp to bp) will be printed out.

set_mode(*mode*)

property thumb

property with_condition

angr.default_cc(*arch*, *platform='Linux'*, *language=None*, *syscall=False*, ***kwargs*)

Return the default calling convention for a given architecture, platform, and language combination.

Parameters

- **arch** (*str*) – The architecture name.
- **platform** (*Optional[str]*) – The platform name (e.g., “Linux” or “Win32”).
- **language** (*Optional[str]*) – The programming language name (e.g., “go”).
- **syscall** (*bool*) – Return syscall convention (True), or normal calling convention (False, default).

Return type

Optional[*Type*[*SimCC*]]

Returns

A default calling convention class if we can find one for the architecture, platform, and language combination, or None if nothing fits.

class **angr.PointerWrapper**(*value*, *buffer=False*)

Bases: *object*

__init__(*value*, *buffer=False*)

class **angr.SimCC**(*arch*)

Bases: *object*

A calling convention allows you to extract from a state the data passed from function to function by calls and returns. Most of the methods provided by SimCC that operate on a state assume that the program is just after a

call but just before stack frame allocation, though this may be overridden with the *stack_base* parameter to each individual method.

This is the base class for all calling conventions.

```

Parameters
  arch (Arch) –

__init__(arch)

Parameters
  arch (Arch) – The Archinfo arch for this CC

ARG_REGS: List[str] = []
FP_ARG_REGS: List[str] = []
STACKARG_SP_BUFF = 0
STACKARG_SP_DIFF = 0
CALLER_SAVED_REGS: List[str] = []
RETURN_ADDR: SimFunctionArgument = None
RETURN_VAL: SimFunctionArgument = None
OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = None
FP_RETURN_VAL: Optional[SimFunctionArgument] = None
ARCH = None
CALLEE_CLEANUP = False
STACK_ALIGNMENT = 1

property int_args
  Iterate through all the possible arg positions that can only be used to store integer or pointer values.
  Returns an iterator of SimFunctionArguments

property memory_args
  Iterate through all the possible arg positions that can be used to store any kind of argument.
  Returns an iterator of SimFunctionArguments

property fp_args
  Iterate through all the possible arg positions that can only be used to store floating point values.
  Returns an iterator of SimFunctionArguments

is_fp_arg(arg)
  This should take a SimFunctionArgument instance and return whether or not that argument is a floating-
  point argument.

Returns True for MUST be a floating point arg,
  False for MUST NOT be a floating point arg, None for when it can be either.

class ArgSession(cc)
  Bases: object
  A class to keep track of the state accumulated in laying parameters out into memory

```

```

cc
fp_iter
int_iter
both_iter
__init__(cc)
getstate()
setstate(state)

```

arg_session(*ret_ty*)

Return an arg session.

A session provides the control interface necessary to describe how integral and floating-point arguments are laid out into memory. The default behavior is that there are a finite list of int-only and fp-only argument slots, and an infinite number of generic slots, and when an argument of a given type is requested, the most slot available is used. If you need different behavior, subclass `ArgSession`.

You need to provide the return type of the function in order to kick off an arg layout session.

Parameters

ret_ty (`SimType` / `None`) –

return_in_implicit_outparam(*ty*)

stack_space(*args*)

Parameters

args – A list of `SimFunctionArguments`

Returns

The number of bytes that should be allocated on the stack to store all these args, NOT INCLUDING the return address.

return_val(*ty*, *perspective_returned=False*)

The location the return value is stored, based on its type.

property return_addr

The location the return address is stored.

next_arg(*session*, *arg_type*)

Parameters

- **session** (`ArgSession`) –
- **arg_type** (`SimType`) –

static is_fp_value(*val*)

static guess_prototype(*args*, *prototype=None*)

Come up with a plausible `SimTypeFunction` for the given args (as would be passed to e.g. `setup_callsite`).

You can pass a variadic function prototype in the *base_type* parameter and all its arguments will be used, only guessing types for the variadic arguments.

arg_locs(*prototype*)

Return type

`List[SimFunctionArgument]`

get_args(*state*, *prototype*, *stack_base*=None)

set_return_val(*state*, *val*, *ty*, *stack_base*=None, *perspective_returned*=False)

setup_callsite(*state*, *ret_addr*, *args*, *prototype*, *stack_base*=None, *alloc_base*=None, *grow_like_stack*=True)

This function performs the actions of the caller getting ready to jump into a function.

Parameters

- **state** – The SimState to operate on
- **ret_addr** – The address to return to when the called function finishes
- **args** – The list of arguments that that the called function will see
- **prototype** – The signature of the call you’re making. Should include variadic args concretely.
- **stack_base** – An optional pointer to use as the top of the stack, circa the function entry point
- **alloc_base** – An optional pointer to use as the place to put excess argument data
- **grow_like_stack** – When allocating data at *alloc_base*, whether to allocate at decreasing addresses

The idea here is that you can provide almost any kind of python type in *args* and it’ll be translated to a binary format to be placed into simulated memory. Lists (representing arrays) must be entirely elements of the same type and size, while tuples (representing structs) can be elements of any type and size. If you’d like there to be a pointer to a given value, wrap the value in a *PointerWrapper*.

If *stack_base* is not provided, the current stack pointer will be used, and it will be updated. If *alloc_base* is not provided, the stack base will be used and *grow_like_stack* will implicitly be True.

grow_like_stack controls the behavior of allocating data at *alloc_base*. When data from *args* needs to be wrapped in a pointer, the pointer needs to point somewhere, so that data is dumped into memory at *alloc_base*. If you set *alloc_base* to point to somewhere other than the stack, set *grow_like_stack* to False so that sequential allocations happen at increasing addresses.

teardown_callsite(*state*, *return_val*=None, *prototype*=None, *force_callee_cleanup*=False)

This function performs the actions of the callee as it’s getting ready to return. It returns the address to return to.

Parameters

- **state** – The state to mutate
- **return_val** – The value to return
- **prototype** – The prototype of the given function
- **force_callee_cleanup** – If we should clean up the stack allocation for the arguments even if it’s not the callee’s job to do so

TODO: support the *stack_base* parameter from *setup_callsite*...? Does that make sense in this context? Maybe it could make sense by saying that you pass it in as something like the “saved base pointer” value?

static find_cc(*arch*, *args*, *sp_delta*, *platform*='Linux')

Pinpoint the best-fit calling convention and return the corresponding SimCC instance, or None if no fit is found.

Parameters

- **arch** ([Arch](#)) – An ArchX instance. Can be obtained from archinfo.
- **args** ([List\[SimFunctionArgument\]](#)) – A list of arguments. It may be updated by the first matched calling convention to remove non-argument arguments.
- **sp_delta** ([int](#)) – The change of stack pointer before and after the call is made.
- **platform** ([str](#)) –

Return type

[Optional\[SimCC\]](#)

Returns

A calling convention instance, or None if none of the SimCC subclasses seems to fit the arguments provided.

get_arg_info(*state*, *prototype*)

This is just a simple wrapper that collects the information from various locations prototype is as passed to self.arg_locs and self.get_args :param [angr.SimState](#) state: The state to evaluate and extract the values from :return: A list of tuples, where the nth tuple is (type, name, location, value) of the nth argument

class [angr.SimFileBase](#)(*name*=None, *writable*=True, *ident*=None, *concrete*=False, *file_exists*=True, ***kwargs*)

Bases: [SimStatePlugin](#)

SimFiles are the storage mechanisms used by SimFileDescriptors.

Different types of SimFiles can have drastically different interfaces, and as a result there's not much that can be specified on this base class. All the read and write methods take a pos argument, which may have different semantics per-class. 0 will always be a valid position to use, though, and the next position you should use is part of the return tuple.

Some simfiles are “streams”, meaning that the position that reads come from is determined not by the position you pass in (it will in fact be ignored), but by an internal variable. This is stored as .pos if you care to read it. Don't write to it. The same lack-of-semantics applies to this field as well.

Variables

- **name** – The name of the file. Purely for cosmetic purposes
- **ident** – The identifier of the file, typically autogenerated from the name and a nonce. Purely for cosmetic purposes, but does appear in symbolic values autogenerated in the file.
- **seekable** – Bool indicating whether seek operations on this file should succeed. If this is True, then pos must be a number of bytes from the start of the file.
- **writable** – Bool indicating whether writing to this file is allowed.
- **pos** – If the file is a stream, this will be the current position. Otherwise, None.
- **concrete** – Whether or not this file contains mostly concrete data. Will be used by some SimProcedures to choose how to handle variable-length operations like fgets.
- **file_exists** – Set to False, if file does not exists, set to a claripy Bool if unknown, default True.

seekable = False

pos = None

__init__(*name=None, writable=True, ident=None, concrete=False, file_exists=True, **kwargs*)

static make_ident(*name*)

concretize(***kwargs*)

Return a concretization of the contents of the file. The type of the return value of this method will vary depending on which kind of SimFile you're using.

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(*pos, data, size=None, **kwargs*)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

property size

The number of data bytes stored by the file at present. May be a symbolic value.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.SimFile`(*name=None, content=None, size=None, has_end=None, seekable=True, writable=True, ident=None, concrete=None, **kwargs*)

Bases: `SimFileBase`, `DefaultMemory`

The normal SimFile is meant to model files on disk. It subclasses `SimSymbolicMemory` so loads and stores to/from it are very simple.

Parameters

- **name** – The name of the file
- **content** – Optional initial content for the file as a string or bitvector
- **size** – Optional size of the file. If content is not specified, it defaults to zero
- **has_end** – Whether the size boundary is treated as the end of the file or a frontier at which new content will be generated. If unspecified, will pick its value based on options.FILES_HAVE_EOF. Another caveat is that if the size is also unspecified this value will default to False.
- **seekable** – Optional bool indicating whether seek operations on this file should succeed, default True.
- **writable** – Whether writing to this file is allowed
- **concrete** – Whether or not this file contains mostly concrete data. Will be used by some SimProcedures to choose how to handle variable-length operations like fgets.

Variables

has_end – Whether this file has an EOF

__init__(*name=None, content=None, size=None, has_end=None, seekable=True, writable=True, ident=None, concrete=None, **kwargs*)

property category

reg, mem, or file.

Type

Return the category of this SimMemory instance. It can be one of the three following categories

set_state(*state*)

Sets a new state (for example, if the state has been branched)

property size

The number of data bytes stored by the file at present. May be a symbolic value.

concretize(**kwargs)

Return a concretization of the contents of the file, as a flat bytestring.

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(*pos, data, size=None, events=True, **kwargs*)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector

- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen()

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.SimPackets`(*name*, *write_mode=None*, *content=None*, *writable=True*, *ident=None*, ***kwargs*)

Bases: `SimFileBase`

The `SimPackets` is meant to model inputs whose content is delivered a series of asynchronous chunks. The data is stored as a list of read or write results. For symbolic sizes, `state.libc.max_packet_size` will be respected. If the `SHORT_READS` option is enabled, reads will return a symbolic size constrained to be less than or equal to the requested size.

A `SimPackets` cannot be used for both reading and writing - for socket objects that can be both read and written to you should use a file descriptor to multiplex the read and write operations into two separate file storage mechanisms.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **write_mode** – Whether this file is opened in read or write mode. If this is unspecified it will be autodetected.
- **content** – Some initial content to use for the file. Can be a list of bytestrings or a list of tuples of content ASTs and size ASTs.

Variables

- **write_mode** – See the eponymous parameter
- **content** – A list of packets, as tuples of content ASTs and size ASTs.

__init__(*name*, *write_mode=None*, *content=None*, *writable=True*, *ident=None*, ***kwargs*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

property size

The number of data bytes stored by the file at present. May be a symbolic value.

concretize(***kwargs*)

Returns a list of the packets read or written as bytestrings.

read(*pos*, *size*, ***kwargs*)

Read a packet from the stream.

Parameters

- **pos** (*int*) – The packet number to read from the sequence of the stream. May be `None` to append to the stream.

- **size** – The size to read. May be symbolic.
- **short_reads** – Whether to replace the size with a symbolic value constrained to less than or equal to the original size. If unspecified, will be chosen based on the state option.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read) and the actual size of the read.

write(*pos*, *data*, *size=None*, *events=True*, ***kwargs*)

Write a packet to the stream.

Parameters

- **pos** (*int*) – The packet number to write in the sequence of the stream. May be None to append to the stream.
- **data** – The data to write, as a string or bitvector.
- **size** – The optional size to write. May be symbolic; must be constrained to at most the size of data.

Returns

The next packet to use after this

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen()`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.SimFileStream`(*name=None, content=None, pos=0, **kwargs*)

Bases: `SimFile`

A specialized `SimFile` that uses a flat memory backing, but functions as a stream, tracking its position internally.

The `pos` argument to the `read` and `write` methods will be ignored, and will return `None`. Instead, there is an attribute `pos` on the file itself, which will give you what you want.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **pos** – The initial position of the file, default zero
- **kwargs** – Any other keyword arguments will go on to the `SimFile` constructor.

Variables

pos – The current position in the file.

__init__(*name=None, content=None, pos=0, **kwargs*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(_, data, size=None, **kwargs)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

state: `angr.SimState`

class `angr.SimPacketsStream(name, pos=0, **kwargs)`

Bases: `SimPackets`

A specialized `SimPackets` that tracks its position internally.

The `pos` argument to the read and write methods will be ignored, and will return `None`. Instead, there is an attribute `pos` on the file itself, which will give you what you want.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **pos** – The initial position of the file, default zero
- **kwargs** – Any other keyword arguments will go on to the `SimPackets` constructor.

Variables

pos – The current position in the file.

__init__(`name, pos=0, **kwargs`)

read(`pos, size, **kwargs`)

Read a packet from the stream.

Parameters

- **pos** (`int`) – The packet number to read from the sequence of the stream. May be `None` to append to the stream.
- **size** – The size to read. May be symbolic.
- **short_reads** – Whether to replace the size with a symbolic value constrained to less than or equal to the original size. If unspecified, will be chosen based on the state option.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read) and the actual size of the read.

write(`_, data, size=None, **kwargs`)

Write a packet to the stream.

Parameters

- **pos** (`int`) – The packet number to write in the sequence of the stream. May be `None` to append to the stream.

- **data** – The data to write, as a string or bitvector.
- **size** – The optional size to write. May be symbolic; must be constrained to at most the size of data.

Returns

The next packet to use after this

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

state: `angr.SimState`

class `angr.SimFileDescriptor`(*simfile*, *flags=0*)

Bases: `SimFileDescriptorBase`

A simple file descriptor forwarding reads and writes to a `SimFile`. Contains information about the current opened state of the file, such as the flags or (if relevant) the current position.

Variables

- **file** – The `SimFile` described to by this descriptor
- **flags** – The mode that the file descriptor was opened with, a bitfield of flags

__init__(*simfile*, *flags=0*)

read_data(*size*, ***kwargs*)

Reads some data from the file, returning the data.

Parameters

- size** – The requested length of the read

Returns

A tuple of the data read and the real length of the read

write_data(*data*, *size=None*, ***kwargs*)

Write some data, provided as an argument into the file.

Parameters

- **data** – A bitvector to write into the file
- **size** – The requested size of the write (may be symbolic)

Returns

The real length of the write

seek(*offset*, *whence='start'*)

Seek the file descriptor to a different position in the file.

Parameters

- **offset** – The offset to seek to, interpreted according to *whence*
- **whence** – What the offset is relative to; one of the strings “start”, “current”, or “end”

Returns

A symbolic boolean describing whether the seek succeeded or not

eof()

Return the EOF status. May be a symbolic boolean.

tell()

Return the current position, or `None` if the concept doesn’t make sense for the given file.

size()

Return the size of the data stored in the file in bytes, or `None` if the concept doesn’t make sense for the given file.

concretize(kwargs)**

Return a concretization of the underlying file. Returns whatever format is preferred by the file.

property file_exists

This should be True in most cases. Only if we opened an fd of unknown existence, ALL_FILES_EXIST is False and ANY_FILE_MIGHT_EXIST is True, this is a symbolic boolean.

property read_storage

Return the SimFile backing reads from this fd

property write_storage

Return the SimFile backing writes to this fd

property read_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

property write_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

set_state(state)

Sets a new state (for example, if the state has been branched)

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen()`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.SimFileDescriptorDuplex(read_file, write_file)`

Bases: `SimFileDescriptorBase`

A file descriptor that refers to two file storage mechanisms, one to read from and one to write to. As a result, operations like `seek`, `eof`, etc no longer make sense.

Parameters

- **read_file** – The `SimFile` to read from
- **write_file** – The `SimFile` to write to

__init__(`read_file, write_file`)

read_data(`size, **kwargs`)

Reads some data from the file, returning the data.

Parameters

- **size** – The requested length of the read

Returns

A tuple of the data read and the real length of the read

write_data(*data*, *size=None*, ***kwargs*)

Write some data, provided as an argument into the file.

Parameters

- **data** – A bitvector to write into the file
- **size** – The requested size of the write (may be symbolic)

Returns

The real length of the write

set_state(*state*)

Sets a new state (for example, if the state has been branched)

eof()

Return the EOF status. May be a symbolic boolean.

tell()

Return the current position, or None if the concept doesn't make sense for the given file.

seek(*offset*, *whence='start'*)

Seek the file descriptor to a different position in the file.

Parameters

- **offset** – The offset to seek to, interpreted according to whence
- **whence** – What the offset is relative to; one of the strings “start”, “current”, or “end”

Returns

A symbolic boolean describing whether the seek succeeded or not

size()

Return the size of the data stored in the file in bytes, or None if the concept doesn't make sense for the given file.

concretize(***kwargs*)

Return a concretization of the underlying files, as a tuple of (read file, write file).

property read_storage

Return the SimFile backing reads from this fd

property write_storage

Return the SimFile backing writes to this fd

property read_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

property write_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(`_`)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.SimMount`

Bases: `SimStatePlugin`

This is the base class for “mount points” in angr’s simulated filesystem. Subclass this class and give it to the filesystem to intercept all file creations and opens below the mountpoint. Since this a `SimStatePlugin` you may also want to implement `set_state`, `copy`, `merge`, etc.

get(*path_elements*)

Implement this function to instrument file lookups.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `SimFile`, or `None`

insert(*path_elements*, *simfile*)

Implement this function to instrument file creation.

Parameters

- **path_elements** – A list of path elements traversing from the mountpoint to the file
- **simfile** – The file to insert

Returns

A `bool` indicating whether the insert occurred

delete(*path_elements*)

Implement this function to instrument file deletion.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `bool` indicating whether the delete occurred

lookup(*sim_file*)

Look up the path of a `SimFile` in the mountpoint

Parameters

sim_file – A `SimFile` object needs to be looked up

Returns

A string representing the path of the file in the mountpoint Or `None` if the `SimFile` does not exist in the mountpoint

state: `angr.SimState`

class `angr.SimHostFilesystem`(*host_path=None, **kwargs*)

Bases: `SimConcreteFilesystem`

Simulated mount that makes some piece from the host filesystem available to the guest.

Parameters

- **host_path** (*str*) – The path on the host to mount
- **pathsep** (*str*) – The host path separator character, default `os.path.sep`

__init__(*host_path=None, **kwargs*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.SimHeapBrk`(*heap_base=None, heap_size=None*)

Bases: `SimHeapBase`

`SimHeapBrk` represents a trivial heap implementation based on the Unix *brk* system call. This type of heap stores virtually no metadata, so it is up to the user to determine when it is safe to release memory. This also means that it does not properly support standard heap operations like *realloc*.

This heap implementation is a holdover from before any more proper implementations were modelled. At the time, various libc (or win32) `SimProcedures` handled the heap in the same way that this plugin does now. To make future heap implementations plug-and-playable, they should implement the necessary logic themselves, and dependent `SimProcedures` should invoke a method by the same name as theirs (prefixed with an underscore) upon the heap plugin. Depending on the heap implementation, if the method is not supported, an error should be raised.

Out of consideration for the original way the heap was handled, this plugin implements functionality for all relevant `SimProcedures` (even those that would not normally be supported together in a single heap implementation).

Variables

heap_location – the address of the top of the heap, bounding the allocations made starting from *heap_base*

__init__(*heap_base=None, heap_size=None*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

`allocate(sim_size)`

The actual allocation primitive for this heap implementation. Increases the position of the break to allocate space. Has no guards against the heap growing too large.

Parameters

sim_size – a size specifying how much to increase the break pointer by

Returns

a pointer to the previous break position, above which there is now allocated space

`release(sim_size)`

The memory release primitive for this heap implementation. Decreases the position of the break to deallocate space. Guards against releasing beyond the initial heap base.

Parameters

sim_size – a size specifying how much to decrease the break pointer by (may be symbolic or not)

`merge(others, merge_conditions, common_ancestor=None)`

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.SimHeapPTMalloc(heap_base=None, heap_size=None)`

Bases: `SimHeapFreelist`

A freelist-style heap implementation inspired by `ptmalloc`. The chunks used by this heap contain heap metadata in addition to user data. While the real-world `ptmalloc` is implemented using multiple lists of free chunks (corresponding to their different sizes), this more basic model uses a single list of chunks and searches for free chunks using a first-fit algorithm.

NOTE: The plugin must be registered using `register_plugin` with name `heap` in order to function properly.

Variables

- **`heap_base`** – the address of the base of the heap in memory
- **`heap_size`** – the total size of the main memory region managed by the heap in memory
- **`mmap_base`** – the address of the region from which large `mmap` allocations will be made
- **`free_head_chunk`** – the head of the linked list of free chunks in the heap

`__init__`(*heap_base=None, heap_size=None*)

`copy`(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the `memo` first, and add itself to `memo` if it ends up making a new copy.

In order to simplify using the `memo`, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your `copy` method!

Parameters

`memo` – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

`chunks()`

Returns an iterator over all the chunks in the heap.

`allocated_chunks()`

Returns an iterator over all the allocated chunks in the heap.

free_chunks()

Returns an iterator over all the free chunks in the heap.

chunk_from_mem(ptr)

Given a pointer to a user payload, return the base of the chunk associated with that payload (i.e. the chunk pointer). Returns None if ptr is null.

Parameters

ptr – a pointer to the base of a user payload in the heap

Returns

a pointer to the base of the associated heap chunk, or None if ptr is null

malloc(sim_size)

A somewhat faithful implementation of libc *malloc*.

Parameters

sim_size – the amount of memory (in bytes) to be allocated

Returns

the address of the allocation, or a NULL pointer if the allocation failed

free(ptr)

A somewhat faithful implementation of libc *free*.

Parameters

ptr – the location in memory to be freed

calloc(sim_nmemb, sim_size)

A somewhat faithful implementation of libc *calloc*.

Parameters

- **sim_nmemb** – the number of elements to allocated
- **sim_size** – the size of each element (in bytes)

Returns

the address of the allocation, or a NULL pointer if the allocation failed

realloc(ptr, size)

A somewhat faithful implementation of libc *realloc*.

Parameters

- **ptr** – the location in memory to be reallocated
- **size** – the new size desired for the allocation

Returns

the address of the allocation, or a NULL pointer if the allocation was freed or if no new allocation was made

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be n `others` and $n+1$ merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`init_state()`

Use this function to perform any initialization on the state at plugin-add time

state: `angr.SimState`

class `angr.PTChunk`(*base, sim_state, heap=None*)

Bases: `Chunk`

A chunk, inspired by the implementation of chunks in `ptmalloc`. Provides a representation of a chunk via a view into the memory plugin. For the chunk definitions and docs that this was loosely based off of, see `glibc malloc/malloc.c`, line 1033, as of commit `5a580643111ef6081be7b4c7bd1997a5447c903f`. Alternatively, take the following link. <https://sourceware.org/git/?p=glibc.git;a=blob;f=malloc/malloc.c;h=67cdfd0ad2f003964cd0f7dfe3bcd85ca98528a7;hb=5a580643111ef6081be7b4c7bd1997a5447c903f#l1033>

Variables

- **base** – the location of the base of the chunk in memory
- **state** – the program state that the chunk is resident in
- **heap** – the heap plugin that the chunk is managed by

__init__(*base, sim_state, heap=None*)

get_size()

Returns the actual size of a chunk (as opposed to the entire size field, which may include some flags).

get_data_size()

Returns the size of the data portion of a chunk.

set_size(*size, is_free=None*)

Use this to set the size on a chunk. When the chunk is new (such as when a free chunk is shrunk to form an allocated chunk and a remainder free chunk) it is recommended that the `is_free` hint be used since setting the size depends on the chunk's freeness, and vice versa.

Parameters

- **size** – size of the chunk
- **is_free** – boolean indicating the chunk's freeness

set_prev_freeness(*is_free*)

Sets (or unsets) the flag controlling whether the previous chunk is free.

Parameters

- **is_free** – if True, sets the previous chunk to be free; if False, sets it to be allocated

is_prev_free()

Returns a concrete state of the flag indicating whether the previous chunk is free or not. Issues a warning if that flag is symbolic and has multiple solutions, and then assumes that the previous chunk is free.

Returns

True if the previous chunk is free; False otherwise

prev_size()

Returns the size of the previous chunk, masking off what would be the flag bits if it were in the actual size field. Performs NO CHECKING to determine whether the previous chunk size is valid (for example, when the previous chunk is not free, its size cannot be determined).

is_free()

Returns a concrete determination as to whether the chunk is free.

data_ptr()

Returns the address of the payload of the chunk.

next_chunk()

Returns the chunk immediately following (and adjacent to) this one, if it exists.

Returns

The following chunk, or None if applicable

prev_chunk()

Returns the chunk immediately prior (and adjacent) to this one, if that chunk is free. If the prior chunk is not free, then its base cannot be located and this method raises an error.

Returns

If possible, the previous chunk; otherwise, raises an error

fwd_chunk()

Returns the chunk following this chunk in the list of free chunks. If this chunk is not free, then it resides in no such list and this method raises an error.

Returns

If possible, the forward chunk; otherwise, raises an error

set_fwd_chunk(*fwd*)

Sets the chunk following this chunk in the list of free chunks.

Parameters

fwd – the chunk to follow this chunk in the list of free chunks

bck_chunk()

Returns the chunk backward from this chunk in the list of free chunks. If this chunk is not free, then it resides in no such list and this method raises an error.

Returns

If possible, the backward chunk; otherwise, raises an error

set_bck_chunk(*bck*)

Sets the chunk backward from this chunk in the list of free chunks.

Parameters

bck – the chunk to precede this chunk in the list of free chunks

```
class angr.Server(project, spill_yard=None, db=None, max_workers=None, max_states=10, staging_max=10,
                  bucketizer=True, recursion_limit=1000, worker_exit_callback=None, techniques=None,
                  add_options=None, remove_options=None)
```

Bases: `object`

Server implements the analysis server with a series of control interfaces exposed.

Variables

- **project** – An instance of `angr.Project`.
- **spill_yard** (*str*) – A directory to store spilled states.
- **db** (*str*) – Path of the database that stores information about spilled states.
- **max_workers** (*int*) – Maximum number of workers. Each worker starts a new process.
- **max_states** (*int*) – Maximum number of active states for each worker.
- **staging_max** (*int*) – Maximum number of inactive states that are kept into memory before spilled onto the disk and potentially be picked up by another worker.
- **bucketizer** (*bool*) – Use the Bucketizer exploration strategy.
- **_worker_exit_callback** – A method that will be called upon the exit of each worker.

```
__init__(project, spill_yard=None, db=None, max_workers=None, max_states=10, staging_max=10,
         bucketizer=True, recursion_limit=1000, worker_exit_callback=None, techniques=None,
         add_options=None, remove_options=None)
```

inc_active_workers()

dec_active_workers()

stop()


```

property active_workers
property stopped
on_worker_exit(worker_id, stashes)

run()

```

```
class angr.KnowledgeBase(project, obj=None, name=None)
```

Bases: `object`

Represents a “model” of knowledge about an artifact.

Contains things like a CFG, data references, etc.

functions: `FunctionManager`

variables: `VariableManager`

structured_code: `StructuredCodeManager`

defs: `KeyDefinitionManager`

cfgs: `CFGManager`

types: `TypesStore`

propagations: `PropagationManager`

xrefs: `XRefManager`

`__init__`(project, obj=None, name=None)

property callgraph

property unresolved_indirect_jumps

property resolved_indirect_jumps

has_plugin(name)

get_plugin(name)

register_plugin(name, plugin)

release_plugin(name)

`K = ~K`

`get_knowledge(requested_plugin_cls)`

Type inference safe method to request a knowledge base plugin Explicitly passing the type of the requested plugin achieves two things: 1. Every location using this plugin can be easily found with an IDE by searching explicit references to the type 2. Basic type inference can deduce the result type and properly type check usages of it

If there isn’t already an instance of this class None will be returned to make it clear to the caller that there is no existing knowledge of this type yet. The code that initially creates this knowledge should use the `register_plugin` method to register the initial knowledge state :type requested_plugin_cls: `Type[TypeVar(K, bound= KnowledgeBasePlugin)]` :param requested_plugin_cls: :rtype: `Optional[TypeVar(K, bound= KnowledgeBasePlugin)]` :return: Instance of the requested plugin class or null if it is not a known plugin

Parameters

requested_plugin_cls (*Type*[*K*]) –

Return type

K | None

request_knowledge(*requested_plugin_cls*)

Return type

TypeVar(*K*, bound= *KnowledgeBasePlugin*)

Parameters

requested_plugin_cls (*Type*[*K*]) –

10.1 Project

angr.project.load_shellcode(*shellcode*, *arch*, *start_offset*=0, *load_address*=0, *thumb*=False, ***kwargs*)

Load a new project based on a snippet of assembly or bytecode.

Parameters

- **shellcode** (*Union*[*bytes*, *str*]) – The data to load, as either a bytestring of instructions or a string of assembly text
- **arch** – The name of the arch to use, or an archinfo class
- **start_offset** – The offset into the data to start analysis (default 0)
- **load_address** – The address to place the data in memory (default 0)
- **thumb** – Whether this is ARM Thumb shellcode

class **angr.project.Project**(*thing*, *default_analysis_mode*=None, *ignore_functions*=None, *use_sim_procedures*=True, *exclude_sim_procedures_func*=None, *exclude_sim_procedures_list*=(), *arch*=None, *simos*=None, *engine*=None, *load_options*=None, *translation_cache*=True, *selfmodifying_code*=False, *support_selfmodifying_code*=None, *store_function*=None, *load_function*=None, *analyses_preset*=None, *concrete_target*=None, *eager_ifunc_resolution*=None, ***kwargs*)

Bases: *object*

This is the main class of the angr module. It is meant to contain a set of binaries and the relationships between them, and perform analyses on them.

Parameters

- **thing** – The path to the main executable object to analyze, or a CLE Loader object.
- **arch** (*Arch*) –
- **load_options** (*Dict*[*str*, *Any*] | None) –
- **selfmodifying_code** (*bool*) –
- **support_selfmodifying_code** (*bool* | None) –

The following parameters are optional.

Parameters

- **default_analysis_mode** – The mode of analysis to use by default. Defaults to ‘symbolic’.

- **ignore_functions** – A list of function names that, when imported from shared libraries, should never be stepped into in analysis (calls will return an unconstrained value).
- **use_sim_procedures** – Whether to replace resolved dependencies for which simprocedures are available with said simprocedures.
- **exclude_sim_procedures_func** – A function that, when passed a function name, returns whether or not to wrap it with a simprocedure.
- **exclude_sim_procedures_list** – A list of functions to *not* wrap with simprocedures.
- **arch** – The target architecture (auto-detected otherwise).
- **simos** – a SimOS class to use for this project.
- **engine** – The SimEngine class to use for this project.
- **translation_cache** (*bool*) – If True, cache translated basic blocks rather than re-translating them.
- **selfmodifying_code** (*bool*) – Whether we aggressively support self-modifying code. When enabled, emulation will try to read code from the current state instead of the original memory, regardless of the current memory protections.
- **store_function** – A function that defines how the Project should be stored. Default to pickling.
- **load_function** – A function that defines how the Project should be loaded. Default to unpickling.
- **analyses_preset** (*angr.misc.PluginPreset*) – The plugin preset for the analyses provider (i.e. Analyses instance).
- **load_options** (*Dict[str, Any] | None*) –
- **support_selfmodifying_code** (*bool | None*) –

Any additional keyword arguments passed will be passed onto `Cle.Loader`.

Variables

- **analyses** – The available analyses.
- **entry** – The program entrypoint.
- **factory** – Provides access to important analysis elements such as path groups and symbolic execution results.
- **filename** – The filename of the executable.
- **loader** – The program loader.
- **storage** – Dictionary of things that should be loaded/stored with the Project.

Parameters

- **arch** (*Arch*) –
- **load_options** (*Dict[str, Any] | None*) –
- **selfmodifying_code** (*bool*) –
- **support_selfmodifying_code** (*bool | None*) –

```
__init__(thing, default_analysis_mode=None, ignore_functions=None, use_sim_procedures=True,
         exclude_sim_procedures_func=None, exclude_sim_procedures_list=(), arch=None, simos=None,
         engine=None, load_options=None, translation_cache=True, selfmodifying_code=False,
         support_selfmodifying_code=None, store_function=None, load_function=None,
         analyses_preset=None, concrete_target=None, eager_ifunc_resolution=None, **kwargs)
```

Parameters

- **load_options** (*Dict[str, Any] | None*) –
- **selfmodifying_code** (*bool*) –
- **support_selfmodifying_code** (*bool | None*) –

arch: [Arch](#)

property analyses: [AnalysesHubWithDefault](#)

hook(*addr, hook=None, length=0, kwargs=None, replace=False*)

Hook a section of code with a custom function. This is used internally to provide symbolic summaries of library functions, and can be used to instrument execution or to modify control flow.

When hook is not specified, it returns a function decorator that allows easy hooking. Usage:

```
# Assuming proj is an instance of angr.Project, we will add a custom hook at
↳ the entry
# point of the project.
@proj.hook(proj.entry)
def my_hook(state):
    print("Welcome to execution!")
```

Parameters

- **addr** – The address to hook.
- **hook** – A `angr.project.Hook` describing a procedure to run at the given address. You may also pass in a `SimProcedure` class or a function directly and it will be wrapped in a `Hook` object for you.
- **length** – If you provide a function for the hook, this is the number of bytes that will be skipped by executing the hook by default.
- **kwargs** – If you provide a `SimProcedure` for the hook, these are the keyword arguments that will be passed to the procedure's `run` method eventually.
- **replace** (*Optional[bool]*) – Control the behavior on finding that the address is already hooked. If true, silently replace the hook. If false (default), warn and do not replace the hook. If none, warn and replace the hook.

is_hooked(*addr*)

Returns True if *addr* is hooked.

Parameters

addr – An address.

Return type

bool

Returns

True if *addr* is hooked, False otherwise.

hooked_by(addr)

Returns the current hook for *addr*.

Parameters

addr – An address.

Return type

`Optional[SimProcedure]`

Returns

None if the address is not hooked.

unhook(addr)

Remove a hook.

Parameters

addr – The address of the hook.

hook_symbol(symbol_name, simproc, kwargs=None, replace=None)

Resolve a dependency in a binary. Looks up the address of the given symbol, and then hooks that address. If the symbol was not available in the loaded libraries, this address may be provided by the CLE externs object.

Additionally, if instead of a symbol name you provide an address, some secret functionality will kick in and you will probably just hook that address, UNLESS you're on powerpc64 ABIv1 or some yet-unknown scary ABI that has its function pointers point to something other than the actual functions, in which case it'll do the right thing.

Parameters

- **symbol_name** – The name of the dependency to resolve.
- **simproc** – The SimProcedure instance (or function) with which to hook the symbol
- **kwargs** – If you provide a SimProcedure for the hook, these are the keyword arguments that will be passed to the procedure's *run* method eventually.
- **replace** (`Optional[bool]`) – Control the behavior on finding that the address is already hooked. If true, silently replace the hook. If false, warn and do not replace the hook. If none (default), warn and replace the hook.

Returns

The address of the new symbol.

Return type

`int`

symbol_hooked_by(symbol_name)

Return the SimProcedure, if it exists, for the given symbol name.

Parameters

symbol_name (*str*) – Name of the symbol.

Return type

`Optional[SimProcedure]`

Returns

None if the address is not hooked.

is_symbol_hooked(symbol_name)

Check if a symbol is already hooked.

Parameters

symbol_name (*str*) – Name of the symbol.

Returns

True if the symbol can be resolved and is hooked, False otherwise.

Return type

bool

unhook_symbol(*symbol_name*)

Remove the hook on a symbol. This function will fail if the symbol is provided by the extern object, as that would result in a state where analysis would be unable to cope with a call to this symbol.

rehook_symbol(*new_address*, *symbol_name*, *stubs_on_sync*)

Move the hook for a symbol to a specific address :type new_address: :param new_address: the new address that will trigger the SimProc execution :type symbol_name: :param symbol_name: the name of the symbol (f.i. strcmp) :return: None

execute(*args, **kwargs)

This function is a symbolic execution helper in the simple style supported by triton and manticore. It designed to be run after setting up hooks (see Project.hook), in which the symbolic state can be checked.

This function can be run in three different ways:

- When run with no parameters, this function begins symbolic execution from the entrypoint.
- It can also be run with a “state” parameter specifying a SimState to begin symbolic execution from.
- Finally, it can accept any arbitrary keyword arguments, which are all passed to project.factory.full_init_state.

If symbolic execution finishes, this function returns the resulting simulation manager.

terminate_execution()

Terminates a symbolic execution that was started with Project.execute().

class `angr.factory.AngrObjectFactory`(*project*, *default_engine=None*)

Bases: *object*

This factory provides access to important analysis elements.

Parameters

default_engine (*Type[SimEngine]* | *None*) –

__init__(*project*, *default_engine=None*)

Parameters

default_engine (*Type[SimEngine]* | *None*) –

snippet(*addr*, *jumpkind=None*, ***block_opts*)

successors(*args, *engine=None*, **kwargs)

Perform execution using an engine. Generally, return a SimSuccessors object classifying the results of the run.

Parameters

- **state** – The state to analyze
- **engine** – The engine to use. If not provided, will use the project default.
- **addr** – optional, an address to execute at instead of the state’s ip
- **jumpkind** – optional, the jumpkind of the previous exit

- **inline** – This is an inline execution. Do not bother copying the state.

Additional keyword arguments will be passed directly into each engine's process method.

blank_state(**kwargs)

Returns a mostly-uninitialized state object. All parameters are optional.

Parameters

- **addr** – The address the state should start at instead of the entry point.
- **initial_prefix** – If this is provided, all symbolic registers will hold symbolic values with names prefixed by this string.
- **fs** – A dictionary of file names with associated preset SimFile objects.
- **concrete_fs** – bool describing whether the host filesystem should be consulted when opening files.
- **chroot** – A path to use as a fake root directory, Behaves similarly to a real chroot. Used only when concrete_fs is set to True.
- **kwargs** – Any additional keyword args will be passed to the SimState constructor.

Returns

The blank state.

Return type

SimState

entry_state(**kwargs)

Returns a state object representing the program at its entry point. All parameters are optional.

Parameters

- **addr** – The address the state should start at instead of the entry point.
- **initial_prefix** – If this is provided, all symbolic registers will hold symbolic values with names prefixed by this string.
- **fs** – a dictionary of file names with associated preset SimFile objects.
- **concrete_fs** – boolean describing whether the host filesystem should be consulted when opening files.
- **chroot** – a path to use as a fake root directory, behaves similar to a real chroot. used only when concrete_fs is set to True.
- **argc** – a custom value to use for the program's argc. May be either an int or a bitvector. If not provided, defaults to the length of args.
- **args** – a list of values to use as the program's argv. May be mixed strings and bitvectors.
- **env** – a dictionary to use as the environment for the program. Both keys and values may be mixed strings and bitvectors.

Returns

The entry state.

Return type

SimState

full_init_state(kwargs)**

Very much like `entry_state()`, except that instead of starting execution at the program entry point, execution begins at a special `SimProcedure` that plays the role of the dynamic loader, calling each of the initializer functions that should be called before execution reaches the entry point.

It can take any of the arguments that can be provided to `entry_state`, except for `addr`.

call_state(addr, *args, **kwargs)

Returns a state object initialized to the start of a given function, as if it were called with given parameters.

Parameters

- **addr** – The address the state should start at instead of the entry point.
- **args** – Any additional positional arguments will be used as arguments to the function call.

The following parameters are optional.

Parameters

- **base_state** – Use this `SimState` as the base for the new state instead of a blank state.
- **cc** – Optionally provide a `SimCC` object to use a specific calling convention.
- **ret_addr** – Use this address as the function’s return target.
- **stack_base** – An optional pointer to use as the top of the stack, circa the function entry point
- **alloc_base** – An optional pointer to use as the place to put excess argument data
- **grow_like_stack** – When allocating data at `alloc_base`, whether to allocate at decreasing addresses
- **toc** – The address of the table of contents for ppc64
- **initial_prefix** – If this is provided, all symbolic registers will hold symbolic values with names prefixed by this string.
- **fs** – A dictionary of file names with associated preset `SimFile` objects.
- **concrete_fs** – bool describing whether the host filesystem should be consulted when opening files.
- **chroot** – A path to use as a fake root directory, Behaves similarly to a real `chroot`. Used only when `concrete_fs` is set to `True`.
- **kwargs** – Any additional keyword args will be passed to the `SimState` constructor.

Returns

The state at the beginning of the function.

Return type

SimState

The idea here is that you can provide almost any kind of python type in `args` and it’ll be translated to a binary format to be placed into simulated memory. Lists (representing arrays) must be entirely elements of the same type and size, while tuples (representing structs) can be elements of any type and size. If you’d like there to be a pointer to a given value, wrap the value in a `SimCC.PointerWrapper`. Any value that can’t fit in a register will be automatically put in a `PointerWrapper`.

If `stack_base` is not provided, the current stack pointer will be used, and it will be updated. If `alloc_base` is not provided, the current stack pointer will be used, and it will be updated. You might not like the results if you provide `stack_base` but not `alloc_base`.

`grow_like_stack` controls the behavior of allocating data at `alloc_base`. When data from `args` needs to be wrapped in a pointer, the pointer needs to point somewhere, so that data is dumped into memory at `alloc_base`. If you set `alloc_base` to point to somewhere other than the stack, set `grow_like_stack` to `False` so that sequential allocations happen at increasing addresses.

`simulation_manager`(*thing=None, **kwargs*)

Constructs a new simulation manager.

Parameters

- **`thing`** (`Union[List[SimState], SimState, None]`) – What to put in the new SimulationManager’s active stash (either a `SimState` or a list of `SimStates`).
- **`kwargs`** – Any additional keyword arguments will be passed to the `SimulationManager` constructor

Returns

The new `SimulationManager`

Return type

angr.sim_manager.SimulationManager

Many different types can be passed to this method:

- If nothing is passed in, the `SimulationManager` is seeded with a state initialized for the program entry point, i.e. *entry_state()*.
- If a `SimState` is passed in, the `SimulationManager` is seeded with that state.
- If a list is passed in, the list must contain only `SimStates` and the whole list will be used to seed the `SimulationManager`.

`simgr`(**args, **kwargs*)

Alias for *simulation_manager* to save our poor fingers

`callable`(*addr, prototype=None, concrete_only=False, perform_merge=True, base_state=None, toc=None, cc=None, add_options=None, remove_options=None*)

A `Callable` is a representation of a function in the binary that can be interacted with like a native python function.

Parameters

- **`addr`** – The address of the function to use
- **`prototype`** – The prototype of the call to use, as a string or a `SimTypeFunction`
- **`concrete_only`** – Throw an exception if the execution splits into multiple states
- **`perform_merge`** – Merge all result states into one at the end (only relevant if `concrete_only=False`)
- **`base_state`** – The state from which to do these runs
- **`toc`** – The address of the table of contents for ppc64
- **`cc`** – The `SimCC` to use for a calling convention

Returns

A `Callable` object that can be used as a interface for executing guest code like a python function.

Return type

angr.callable.Callable

cc()

Return a SimCC (calling convention) parameterized for this project.

Relevant subclasses of SimFunctionArgument are SimRegArg and SimStackArg, and shortcuts to them can be found on this *cc* object.

For stack arguments, offsets are relative to the stack pointer on function entry.

function_prototype()

Return a default function prototype parameterized for this project and SimOS.

block(*addr*, *size=None*, *max_size=None*, *byte_string=None*, *vex=None*, *thumb=False*, *backup_state=None*, *extra_stop_points=None*, *opt_level=None*, *num_inst=None*, *traceflags=0*, *insn_bytes=None*, *insn_text=None*, *strict_block_end=None*, *collect_data_refs=False*, *cross_insn_opt=True*, *load_from_ro_regions=False*, *initial_regs=None*)

fresh_block(*addr*, *size*, *backup_state=None*)

class `angr.block.DisassemblerBlock`(*addr*, *insns*, *thumb*, *arch*)

Bases: `object`

Helper class to represent a block of disassembled target architecture instructions

__init__(*addr*, *insns*, *thumb*, *arch*)

addr

insns

thumb

arch

pp()

class `angr.block.DisassemblerInsn`

Bases: `object`

Helper class to represent a disassembled target architecture instruction

property size: `int`

property address: `int`

property mnemonic: `str`

property op_str: `str`

class `angr.block.CapstoneBlock`(*addr*, *insns*, *thumb*, *arch*)

Bases: `DisassemblerBlock`

Deep copy of the capstone blocks, which have serious issues with having extended lifespans outside of capstone itself

class `angr.block.CapstoneInsn`(*capstone_insn*)

Bases: `DisassemblerInsn`

Represents a capstone instruction.

__init__(*capstone_insn*)

`insn`

property `size`: `int`

property `address`: `int`

property `mnemonic`: `str`

property `op_str`: `str`

```
class angr.block.Block(addr, project=None, arch=None, size=None, byte_string=None, vex=None,
                       thumb=False, backup_state=None, extra_stop_points=None, opt_level=None,
                       num_inst=None, traceflags=0, strict_block_end=None, collect_data_refs=False,
                       cross_insn_opt=True, load_from_ro_regions=False, initial_regs=None)
```

Bases: `Serializable`

Represents a basic block in a binary or a program.

`BLOCK_MAX_SIZE = 4096`

```
__init__(addr, project=None, arch=None, size=None, byte_string=None, vex=None, thumb=False,
         backup_state=None, extra_stop_points=None, opt_level=None, num_inst=None, traceflags=0,
         strict_block_end=None, collect_data_refs=False, cross_insn_opt=True,
         load_from_ro_regions=False, initial_regs=None)
```

`arch`

`thumb`

`addr`

`size`

`pp(**kwargs)`

`set_initial_regs()`

`static reset_initial_regs()`

property `vex`: `IRSB`

property `vex_nostmt`

property `disassembly`: `DisassemblerBlock`

Provide a disassembly object using whatever disassembler is available

property `capstone`

property `codenode`

property `bytes`

property `instructions`

property `instruction_addrs`

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(cmsg)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

class `angr.block.SootBlock(addr, project=None, arch=None)`

Bases: `object`

Represents a Soot IR basic block.

__init__(addr, project=None, arch=None)

property `soot`

property `size`

property `codenode`

10.2 Plugin Ecosystem

class `angr.misc.plugins.PluginHub`

Bases: `Generic[P]`

A plugin hub is an object which contains many plugins, as well as the notion of a “preset”, or a backer that can provide default implementations of plugins which cater to a certain circumstance.

Objects in angr like the SimState, the Analyses hub, the SimEngine selector, etc all use this model to unify their mechanisms for automatically collecting and selecting components to use. If you’re familiar with design patterns this is a configurable Strategy Pattern.

Each PluginHub subclass should have a corresponding Plugin subclass, and perhaps a PluginPreset subclass if it wants its presets to be able to specify anything more interesting than a list of defaults.

__init__()

classmethod `register_default(name, plugin_cls, preset='default')`

classmethod `register_preset(name, preset)`

Register a preset instance with the class of the hub it corresponds to. This allows individual plugin objects to automatically register themselves with a preset by using a classmethod of their own with only the name of the preset to register with.

property plugin_preset

Get the current active plugin preset

property has_plugin_preset: bool

Check whether or not there is a plugin preset in use on this hub right now

use_plugin_preset(preset)

Apply a preset to the hub. If there was a previously active preset, discard it.

Preset can be either the string name of a preset or a PluginPreset instance.

discard_plugin_preset()

Discard the current active preset. Will release any active plugins that could have come from the old preset.

get_plugin(name)

Get the plugin named name. If no such plugin is currently active, try to activate a new one using the current preset.

Return type

`TypeVar(P)`

Parameters

name (*str*) –

has_plugin(name)

Return whether or not a plugin with the name name is currently active.

register_plugin(name, plugin)

Add a new plugin plugin with name name to the active plugins.

Parameters

name (*str*) –

release_plugin(name)

Deactivate and remove the plugin with name name.

class angr.misc.plugins.PluginPreset

Bases: `object`

A plugin preset object contains a mapping from name to a plugin class. A preset can be active on a hub, which will cause it to handle requests for plugins which are not already present on the hub.

Unlike Plugins and PluginHubs, instances of PluginPresets are defined on the module level for individual presets. You should register the preset instance with a hub to allow plugins to easily add themselves to the preset without an explicit reference to the preset itself.

__init__()
activate(hub)

This method is called when the preset becomes active on a hub.

deactivate(hub)

This method is called when the preset is discarded from the hub.

add_default_plugin(name, plugin_cls)

Add a plugin to the preset.

list_default_plugins()

Return a list of the names of available default plugins.

request_plugin(name)

Return the plugin class which is registered under the name `name`, or raise `NoPlugin` if the name isn't available.

Return type

`Type[TypeVar(P)]`

Parameters

name (*str*) –

copy()

Return a copy of self.

class `angr.misc.plugins.PluginVendor`

Bases: `Generic[P]`, `PluginHub[P]`

A specialized hub which serves only as a plugin vendor, never having any “active” plugins. It will directly return the plugins provided by the preset instead of instantiating them.

release_plugin(name)

Deactivate and remove the plugin with name `name`.

register_plugin(name, plugin)

Add a new plugin `plugin` with name `name` to the active plugins.

class `angr.misc.plugins.VendorPreset`

Bases: `PluginPreset`

A specialized preset class for use with the `PluginVendor`.

10.3 Program State

`angr.sim_state.arch_overrideable(f)`

class `angr.sim_state.SimState`(*project=None, arch=None, plugins=None, mode=None, options=None, add_options=None, remove_options=None, special_memory_filler=None, os_name=None, plugin_preset='default', cle_memory_backer=None, dict_memory_backer=None, permissions_map=None, default_permissions=3, stack_perms=None, stack_end=None, stack_size=None, regioned_memory_cls=None, **kwargs*)

Bases: `PluginHub`

The `SimState` represents the state of a program, including its memory, registers, and so forth.

Parameters

- **project** (`angr.Project`) – The project instance.
- **arch** (`archinfo.Arch` | *str*) – The architecture of the state.

Variables

- **regs** – A convenient view of the state's registers, where each register is a property
- **mem** – A convenient view of the state's memory, a `angr.state_plugins.view.SimMemView`
- **registers** – The state's register file as a flat memory region
- **memory** – The state's memory as a flat memory region

- **solver** – The symbolic solver and variable manager for this state
- **inspect** – The breakpoint manager, a [*angr.state_plugins.inspect.SimInspector*](#)
- **log** – Information about the state’s history
- **scratch** – Information about the current execution step
- **posix** – MISNOMER: information about the operating system or environment model
- **fs** – The current state of the simulated filesystem
- **libc** – Information about the standard library we are emulating
- **cgc** – Information about the cgc environment
- **uc_manager** – Control of under-constrained symbolic execution
- **unicorn** – Control of the Unicorn Engine

solver: `SimSolver`

posix: `SimSystemPosix`

registers: `DefaultMemory`

regs: `SimRegNameView`

memory: `DefaultMemory`

callstack: `CallStack`

mem: `SimMemView`

history: `SimStateHistory`

inspect: `SimInspector`

jni_references: `SimStateJNIReferences`

scratch: `SimStateScratch`

__init__(*project=None, arch=None, plugins=None, mode=None, options=None, add_options=None, remove_options=None, special_memory_filler=None, os_name=None, plugin_preset='default', cle_memory_backer=None, dict_memory_backer=None, permissions_map=None, default_permissions=3, stack_perms=None, stack_end=None, stack_size=None, regioned_memory_cls=None, **kwargs*)

property plugins

property se

Deprecated alias for *solver*

property ip

Get the instruction pointer expression, trigger `SimInspect` breakpoints, and generate `SimActions`. Use `_ip` to not trigger breakpoints or generate actions.

Returns

an expression

property addr

Get the concrete address of the instruction pointer, without triggering SimInspect breakpoints or generating SimActions. An integer is returned, or an exception is raised if the instruction pointer is symbolic.

Returns

an int

property arch: Arch

T = ~T

get_plugin(name)

Get the plugin named name. If no such plugin is currently active, try to activate a new one using the current preset.

has_plugin(name)

Return whether or not a plugin with the name name is currently active.

register_plugin(name, plugin, inhibit_init=False)

Add a new plugin plugin with name name to the active plugins.

property javavm_memory

In case of an JavaVM with JNI support, a state can store the memory plugin twice; one for the native and one for the java view of the state.

Returns

The JavaVM view of the memory plugin.

property javavm_registers

In case of an JavaVM with JNI support, a state can store the registers plugin twice; one for the native and one for the java view of the state.

Returns

The JavaVM view of the registers plugin.

simplify(*args)

Simplify this state's constraints.

add_constraints(*args, **kwargs)

Add some constraints to the state.

You may pass in any number of symbolic booleans as variadic positional arguments.

satisfiable(kwargs)**

Whether the state's constraints are satisfiable

downsize()

Clean up after the solver engine. Calling this when a state no longer needs to be solved on will reduce memory usage.

step(kwargs)**

Perform a step of symbolic execution using this state. Any arguments to *AngrObjectFactory.successors* can be passed to this.

Returns

A SimSuccessors object categorizing the results of the step.

block(*args, **kwargs)

Represent the basic block at this state's instruction pointer. Any arguments to *AngrObjectFactory.block* can be passed to this.

Returns

A Block object describing the basic block of code at this point.

copy()

Returns a copy of the state.

merge(*others, **kwargs)

Merges this state with the other states. Returns the merging result, merged state, and the merge flag.

Parameters

- **states** – the states to merge
- **merge_conditions** – a tuple of the conditions under which each state holds
- **common_ancestor** – a state that represents the common history between the states being merged. Usually it is only available when `EFFICIENT_STATE_MERGING` is enabled, otherwise weak-refed states might be dropped from state history instances.
- **plugin_whitelist** – a list of plugin names that will be merged. If this option is given and is not `None`, any plugin that is not inside this list will not be merged, and will be created as a fresh instance in the new state.
- **common_ancestor_history** – a `SimStateHistory` instance that represents the common history between the states being merged. This is to allow optimal state merging when `EFFICIENT_STATE_MERGING` is disabled.

Returns

(merged state, merge flag, a bool indicating if any merging occurred)

widen(*others)

Perform a widening between self and other states :type others: :param others: :return:

reg_concrete(*args, **kwargs)

Returns the contents of a register but, if that register is symbolic, raises a `SimValueError`.

mem_concrete(*args, **kwargs)

Returns the contents of a memory but, if the contents are symbolic, raises a `SimValueError`.

stack_push(thing)

Push 'thing' to the stack, writing the thing to memory and adjusting the stack pointer.

stack_pop()

Pops from the stack and returns the popped thing. The length will be the architecture word size.

stack_read(offset, length, bp=False)

Reads length bytes, at an offset into the stack.

Parameters

- **offset** – The offset from the stack pointer.
- **length** – The number of bytes to read.
- **bp** – If True, offset from the BP instead of the SP. Default: False.

make_concrete_int(expr)

prepare_callsite(*retval*, *args*, *cc*='wtf')

dbg_print_stack(*depth*=None, *sp*=None)

Only used for debugging purposes. Return the current stack info in formatted string. If depth is None, the current stack frame (from sp to bp) will be printed out.

set_mode(*mode*)

property thumb

property with_condition

class `angr.sim_state_options.StateOption`(*name*, *types*, *default*='_NO_DEFAULT_VALUE',
description=None)

Bases: `object`

Describes a state option.

__init__(*name*, *types*, *default*='_NO_DEFAULT_VALUE', *description*=None)

name

types

default

description

property has_default_value

one_type()

class `angr.sim_state_options.SimStateOptions`(*thing*)

Bases: `object`

A per-state manager of state options. An option can be either a key-valued entry or a Boolean switch (which can be seen as a key-valued entry whose value can only be either True or False).

```

OPTIONS = {'ABSTRACT_MEMORY': <0 ABSTRACT_MEMORY[bool]>, 'ABSTRACT_SOLVER': <0
ABSTRACT_SOLVER[bool]>, 'ACTION_DEPS': <0 ACTION_DEPS[bool]>, 'ADD_AUTO_REFS': <0
ADD_AUTO_REFS[bool]>, 'ALLOW_SEND_FAILURES': <0 ALLOW_SEND_FAILURES[bool]>,
'ALL_FILES_EXIST': <0 ALL_FILES_EXIST[bool]>, 'ANY_FILE_MIGHT_EXIST': <0
ANY_FILE_MIGHT_EXIST[bool]>, 'APPROXIMATE_FIRST': <0 APPROXIMATE_FIRST[bool]>,
'APPROXIMATE_GUARDS': <0 APPROXIMATE_GUARDS[bool]>, 'APPROXIMATE_MEMORY_INDICES': <0
APPROXIMATE_MEMORY_INDICES[bool]>, 'APPROXIMATE_MEMORY_SIZES': <0
APPROXIMATE_MEMORY_SIZES[bool]>, 'APPROXIMATE_SATISFIABILITY': <0
APPROXIMATE_SATISFIABILITY[bool]>, 'AST_DEPS': <0 AST_DEPS[bool]>, 'AUTO_REFS': <0
AUTO_REFS[bool]>, 'AVOID_MULTIVALUED_READS': <0 AVOID_MULTIVALUED_READS[bool]>,
'AVOID_MULTIVALUED_WRITES': <0 AVOID_MULTIVALUED_WRITES[bool]>,
'BEST_EFFORT_MEMORY_STORING': <0 BEST_EFFORT_MEMORY_STORING[bool]>,
'BYPASS_ERRORED_IRCCALL': <0 BYPASS_ERRORED_IRCCALL[bool]>, 'BYPASS_ERRORED_IROP':
<0 BYPASS_ERRORED_IROP[bool]>, 'BYPASS_ERRORED_IRSTMT': <0
BYPASS_ERRORED_IRSTMT[bool]>, 'BYPASS_UNSUPPORTED_IRCCALL': <0
BYPASS_UNSUPPORTED_IRCCALL[bool]>, 'BYPASS_UNSUPPORTED_IRDIRTY': <0
BYPASS_UNSUPPORTED_IRDIRTY[bool]>, 'BYPASS_UNSUPPORTED_IEXPR': <0
BYPASS_UNSUPPORTED_IEXPR[bool]>, 'BYPASS_UNSUPPORTED_IROP': <0
BYPASS_UNSUPPORTED_IROP[bool]>, 'BYPASS_UNSUPPORTED_IRSTMT': <0
BYPASS_UNSUPPORTED_IRSTMT[bool]>, 'BYPASS_UNSUPPORTED_SYSCALL': <0
BYPASS_UNSUPPORTED_SYSCALL[bool]>, 'BYPASS_VERITESTING_EXCEPTIONS': <0
BYPASS_VERITESTING_EXCEPTIONS[bool]>, 'CACHELESS_SOLVER': <0
CACHELESS_SOLVER[bool]>, 'CALLLESS': <0 CALLLESS[bool]>, 'CGC_ENFORCE_FD': <0
CGC_ENFORCE_FD[bool]>, 'CGC_NON_BLOCKING_FDS': <0 CGC_NON_BLOCKING_FDS[bool]>,
'CGC_NO_SYMBOLIC_RECEIVE_LENGTH': <0 CGC_NO_SYMBOLIC_RECEIVE_LENGTH[bool]>,
'COMPOSITE_SOLVER': <0 COMPOSITE_SOLVER[bool]>, 'CONCRETIZE': <0 CONCRETIZE[bool]>,
'CONCRETIZE_SYMBOLIC_FILE_READ_SIZES': <0
CONCRETIZE_SYMBOLIC_FILE_READ_SIZES[bool]>, 'CONCRETIZE_SYMBOLIC_WRITE_SIZES': <0
CONCRETIZE_SYMBOLIC_WRITE_SIZES[bool]>, 'CONSERVATIVE_READ_STRATEGY': <0
CONSERVATIVE_READ_STRATEGY[bool]>, 'CONSERVATIVE_WRITE_STRATEGY': <0
CONSERVATIVE_WRITE_STRATEGY[bool]>, 'CONSTRAINT_TRACKING_IN_SOLVER': <0
CONSTRAINT_TRACKING_IN_SOLVER[bool]>, 'COPY_STATES': <0 COPY_STATES[bool]>,
'CPUID_SYMBOLIC': <0 CPUID_SYMBOLIC[bool]>, 'DOWNSIZE_Z3': <0 DOWNSIZE_Z3[bool]>,
'DO_CCALLS': <0 DO_CCALLS[bool]>, 'DO_RET_EMULATION': <0 DO_RET_EMULATION[bool]>,
'EFFICIENT_STATE_MERGING': <0 EFFICIENT_STATE_MERGING[bool]>, 'ENABLE_NX': <0
ENABLE_NX[bool]>, 'EXCEPTION_HANDLING': <0 EXCEPTION_HANDLING[bool]>,
'EXTENDED_IROP_SUPPORT': <0 EXTENDED_IROP_SUPPORT[bool]>, 'FAST_MEMORY': <0
FAST_MEMORY[bool]>, 'FAST_REGISTERS': <0 FAST_REGISTERS[bool]>, 'FILES_HAVE_EOF': <0
FILES_HAVE_EOF[bool]>, 'HYBRID_SOLVER': <0 HYBRID_SOLVER[bool]>,
'JAVA_IDENTIFY_GETTER_SETTER': <0 JAVA_IDENTIFY_GETTER_SETTER[bool]>,
'JAVA_TRACK_ATTRIBUTES': <0 JAVA_TRACK_ATTRIBUTES[bool]>, 'KEEP_IP_SYMBOLIC': <0
KEEP_IP_SYMBOLIC[bool]>, 'KEEP_MEMORY_READS_DISCRETE': <0
KEEP_MEMORY_READS_DISCRETE[bool]>, 'LAZY_SOLVES': <0 LAZY_SOLVES[bool]>,
'MEMORY_CHUNK_INDIVIDUAL_READS': <0 MEMORY_CHUNK_INDIVIDUAL_READS[bool]>,
'MEMORY_FIND_STRICT_SIZE_LIMIT': <0 MEMORY_FIND_STRICT_SIZE_LIMIT[bool]>,
'MEMORY_SYMBOLIC_BYTES_MAP': <0 MEMORY_SYMBOLIC_BYTES_MAP[bool]>,
'NO_CROSS_INSN_OPT': <0 NO_CROSS_INSN_OPT[bool]>, 'NO_IP_CONCRETIZATION': <0
NO_IP_CONCRETIZATION[bool]>, 'NO_SYMBOLIC_JUMP_RESOLUTION': <0
NO_SYMBOLIC_JUMP_RESOLUTION[bool]>, 'NO_SYMBOLIC_SYSCALL_RESOLUTION': <0
NO_SYMBOLIC_SYSCALL_RESOLUTION[bool]>, 'OPTIMIZE_IR': <0 OPTIMIZE_IR[bool]>,
'PRODUCE_ZERODIV_SUCCESORS': <0 PRODUCE_ZERODIV_SUCCESORS[bool]>,
'REGION_MAPPING': <0 REGION_MAPPING[bool]>, 'REPLACEMENT_SOLVER': <0
REPLACEMENT_SOLVER[bool]>, 'REVERSE_MEMORY_HASH_MAP': <0
REVERSE_MEMORY_HASH_MAP[bool]>, 'REVERSE_MEMORY_NAME_MAP': <0
REVERSE_MEMORY_NAME_MAP[bool]>, 'SHORT_READS': <0 SHORT_READS[bool]>,
'SIMPLIFY_CONSTRAINTS': <0 SIMPLIFY_CONSTRAINTS[bool]>, 'SIMPLIFY_EXIT_GUARD': <0
SIMPLIFY_EXIT_GUARD[bool]>, 'SIMPLIFY_EXIT_STATE': <0 SIMPLIFY_EXIT_STATE[bool]>,
'SIMPLIFY_EXIT_TARGET': <0 SIMPLIFY_EXIT_TARGET[bool]>, 'SIMPLIFY_EXPRS': <0
SIMPLIFY_EXPRS[bool]>, 'SIMPLIFY_MEMORY_READS': <0 SIMPLIFY_MEMORY_READS[bool]>,
'SIMPLIFY_MEMORY_WRITES': <0 SIMPLIFY_MEMORY_WRITES[bool]>,

```

__init__(*thing*)

Parameters

thing – Either a set of Boolean switches to enable, or an existing SimStateOptions instance.

add(*boolean_switch*)

[COMPATIBILITY] Enable a Boolean switch.

Parameters

boolean_switch (*str*) – Name of the Boolean switch.

Returns

None

update(*boolean_switches*)

[COMPATIBILITY] In order to be compatible with the old interface, you can enable a collection of Boolean switches at the same time by doing the following:

```
>>> state.options.update({sim_options.SYMBOLIC, sim_options.ABSTRACT_MEMORY})
```

or

```
>>> state.options.update(sim_options.unicorn)
```

Parameters

boolean_switches (*set*) – A collection of Boolean switches to enable.

Returns

None

remove(*name*)

Drop a state option if it exists, or raise a KeyError if the state option is not set.

[COMPATIBILITY] Remove a Boolean switch.

Parameters

name (*str*) – Name of the state option.

Returns

NNone

discard(*name*)

Drop a state option if it exists, or silently return if the state option is not set.

[COMPATIBILITY] Disable a Boolean switch.

Parameters

name (*str*) – Name of the Boolean switch.

Returns

None

difference(*boolean_switches*)

[COMPATIBILITY] Make a copy of the current instance, and then discard all options that are in boolean_switches.

Parameters

boolean_switches (*set*) – A collection of Boolean switches to disable.

Returns

A new SimStateOptions instance.

copy()

Get a copy of the current SimStateOptions instance.

Returns

A new SimStateOptions instance.

Return type

SimStateOptions

tally(*exclude_false=True, description=False*)

Return a string representation of all state options.

Parameters

- **exclude_false** (*bool*) – Whether to exclude Boolean switches that are disabled.
- **description** (*bool*) – Whether to display the description of each option.

Returns

A string representation.

Return type

str

classmethod register_option(*name, types, default=None, description=None*)

Register a state option.

Parameters

- **name** (*str*) – Name of the state option.
- **types** – A collection of allowed types of this state option.
- **default** – The default value of this state option.
- **description** (*str*) – The description of this state option.

Returns

None

classmethod register_bool_option(*name, description=None*)

Register a Boolean switch as state option. This is equivalent to `cls.register_option(name, set([bool]), description=description)`

Parameters

- **name** (*str*) – Name of the state option.
- **description** (*str*) – The description of this state option.

Returns

None

class angr.state_plugins.plugin.SimStatePlugin

Bases: *object*

This is a base class for SimState plugins. A SimState plugin will be copied along with the state when the state is branched. They are intended to be used for things such as tracking open files, tracking heap details, and providing storage and persistence for SimProcedures.

STRONGREF_STATE = False

`__init__()`

state: *SimState*

set_state(*state*)

Sets a new state (for example, if the state has been branched)

set_strongref_state(*state*)

copy(*_memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

static memo(*f*)

A decorator function you should apply to `copy`

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins

- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

classmethod **register_default**(*name*, *xtr=None*)

init_state()

Use this function to perform any initialization on the state at plugin-add time

class `angr.state_plugins.inspect.BP`(*when='before'*, *enabled=None*, *condition=None*, *action=None*, ***kwargs*)

Bases: `object`

A breakpoint.

__init__(*when='before'*, *enabled=None*, *condition=None*, *action=None*, ***kwargs*)

check(*state*, *when*)

Checks state *state* to see if the breakpoint should fire.

Parameters

- **state** – The state.
- **when** – Whether the check is happening before or after the event.

Returns

A boolean representing whether the checkpoint should fire.

fire(*state*)

Trigger the breakpoint.

Parameters

state – The state.

class `angr.state_plugins.inspect.SimInspector`

Bases: `SimStatePlugin`

The breakpoint interface, used to instrument execution. For usage information, look here: <https://docs.angr.io/core-concepts/simulation#breakpoints>

BP_AFTER = 'after'

BP_BEFORE = 'before'

BP_BOTH = 'both'

__init__()

action(*event_type*, *when*, ***kwargs*)

Called from within the engine when events happens. This function checks all breakpoints registered for that event and fires the ones whose conditions match.

make_breakpoint(*event_type*, **args*, ***kwargs*)

Creates and adds a breakpoint which would trigger on *event_type*. Additional arguments are passed to the [BP](#) constructor.

Returns

The created breakpoint, so that it can be removed later.

b(*event_type*, **args*, ***kwargs*)

Creates and adds a breakpoint which would trigger on *event_type*. Additional arguments are passed to the [BP](#) constructor.

Returns

The created breakpoint, so that it can be removed later.

add_breakpoint(*event_type*, *bp*)

Adds a breakpoint which would trigger on *event_type*.

Parameters

- **event_type** – The event type to trigger on
- **bp** – The breakpoint

Returns

The created breakpoint.

remove_breakpoint(*event_type*, *bp=None*, *filter_func=None*)

Removes a breakpoint.

Parameters

- **bp** – The breakpoint to remove.
- **filter_func** – A filter function to specify whether each breakpoint should be removed or not.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

downsize()

Remove previously stored attributes from this plugin instance to save memory. This method is supposed to be called by breakpoint implementors. A typical workflow looks like the following :


```

>>> # Add `attr0` and `attr1` to `self.state.inspect`
>>> self.state.inspect(xxxxxx, attr0=yyyy, attr1=zzzz)
>>> # Get new attributes out of SimInspect in case they are modified by the user
>>> new_attr0 = self.state._inspect.attr0
>>> new_attr1 = self.state._inspect.attr1
>>> # Remove them from SimInspect
>>> self.state._inspect.downsize()

```

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements' merge methods, e.g.

```

self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)

```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from merge should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

set_state(*state*)

Sets a new state (for example, if the state has been branched)

state: `angr.SimState`

class `angr.state_plugins.libc.SimStateLibc`

Bases: `SimStatePlugin`

This state plugin keeps track of various libc stuff:

10.3. Program State

```

TOLOWER_LOC_ARRAY = [128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139,
140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156,
157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173,
174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190,
191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207,
208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224,
225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241,
242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 4294967295, 0, 1,
2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24,
25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45,
46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 97, 98,
99, 100, 101, 102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115,
116, 117, 118, 119, 120, 121, 122, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100, 101,
102, 103, 104, 105, 106, 107, 108, 109, 110, 111, 112, 113, 114, 115, 116, 117, 118,
119, 120, 121, 122, 123, 124, 125, 126, 127, 128, 129, 130, 131, 132, 133, 134, 135,
136, 137, 138, 139, 140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152,
153, 154, 155, 156, 157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169,
170, 171, 172, 173, 174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186,
187, 188, 189, 190, 191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203,
204, 205, 206, 207, 208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220,
221, 222, 223, 224, 225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237,
238, 239, 240, 241, 242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254,
255]

```

```

TOUPPER_LOC_ARRAY = [128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139,
140, 141, 142, 143, 144, 145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156,
157, 158, 159, 160, 161, 162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173,
174, 175, 176, 177, 178, 179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190,
191, 192, 193, 194, 195, 196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207,
208, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224,
225, 226, 227, 228, 229, 230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241,
242, 243, 244, 245, 246, 247, 248, 249, 250, 251, 252, 253, 254, 4294967295, 0, 1,
2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24,
25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45,
46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66,
67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87,
88, 89, 90, 91, 92, 93, 94, 95, 96, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76,
77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 123, 124, 125, 126, 127,
128, 129, 130, 131, 132, 133, 134, 135, 136, 137, 138, 139, 140, 141, 142, 143, 144,
145, 146, 147, 148, 149, 150, 151, 152, 153, 154, 155, 156, 157, 158, 159, 160, 161,
162, 163, 164, 165, 166, 167, 168, 169, 170, 171, 172, 173, 174, 175, 176, 177, 178,
179, 180, 181, 182, 183, 184, 185, 186, 187, 188, 189, 190, 191, 192, 193, 194, 195,
196, 197, 198, 199, 200, 201, 202, 203, 204, 205, 206, 207, 208, 209, 210, 211, 212,
213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 229,
230, 231, 232, 233, 234, 235, 236, 237, 238, 239, 240, 241, 242, 243, 244, 245, 246,
247, 248, 249, 250, 251, 252, 253, 254, 255]

```

```
__init__()
```

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=*None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be *None*, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from merge should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

property `errno`

ret_errno(*val*)

state: `angr.SimState`

class `angr.state_plugins.posix.PosixDevFS`

Bases: `SimMount`

get(*path*)

Implement this function to instrument file lookups.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `SimFile`, or `None`

insert(*path*, *simfile*)

Implement this function to instrument file creation.

Parameters

- **path_elements** – A list of path elements traversing from the mountpoint to the file
- **simfile** – The file to insert

Returns

A `bool` indicating whether the insert occurred

delete(*path*)

Implement this function to instrument file deletion.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `bool` indicating whether the delete occurred

lookup(*_*)

Look up the path of a `SimFile` in the mountpoint

Parameters

sim_file – A `SimFile` object needs to be looked up

Returns

A string representing the path of the file in the mountpoint Or `None` if the `SimFile` does not exist in the mountpoint

merge(*others*, *conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to

resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` `others` and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

copy(`_`)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (id(obj)) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.state_plugins.posix.PosixProcFS`

Bases: `SimMount`

The virtual file system mounted at /proc (as of now, on Linux).

get(*path*)

Implement this function to instrument file lookups.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `SimFile`, or `None`

insert(*path*, *simfile*)

Implement this function to instrument file creation.

Parameters

- **path_elements** – A list of path elements traversing from the mountpoint to the file
- **simfile** – The file to insert

Returns

A bool indicating whether the insert occurred

delete(*path*)

Implement this function to instrument file deletion.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A bool indicating whether the delete occurred

lookup(*_*)

Look up the path of a `SimFile` in the mountpoint

Parameters

sim_file – A `SimFile` object needs to be looked up

Returns

A string representing the path of the file in the mountpoint Or `None` if the `SimFile` does not exist in the mountpoint

merge(*others*, *conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be n `others` and $n+1$ merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`copy(_)`

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.state_plugins.posix.SimSystemPosix`(*stdin=None, stdout=None, stderr=None, fd=None, sockets=None, socket_queue=None, argv=None, argc=None, environ=None, auxv=None, tls_modules=None, sigmask=None, pid=None, ppid=None, uid=None, gid=None, brk=None*)

Bases: [*SimStatePlugin*](#)

Data storage and interaction mechanisms for states with an environment conforming to posix. Available as `state.posix`.

SIG_BLOCK = 0

SIG_UNBLOCK = 1

SIG_SETMASK = 2

EPERM = 1

ENOENT = 2

ESRCH = 3

EINTR = 4

EIO = 5

ENXIO = 6

E2BIG = 7

ENOEXEC = 8

EBADF = 9

ECHILD = 10

EAGAIN = 11

ENOMEM = 12

EACCES = 13

EFAULT = 14

ENOTBLK = 15

EBUSY = 16

EEXIST = 17

EXDEV = 18

ENODEV = 19

ENOTDIR = 20

EISDIR = 21

EINVAL = 22

ENFILE = 23

EMFILE = 24

ENOTTY = 25

ETXTBSY = 26

EFBIG = 27

ENOSPC = 28

ESPIPE = 29

EROFS = 30

EMLINK = 31

EPIPE = 32

EDOM = 33

ERANGE = 34

__init__(*stdin=None, stdout=None, stderr=None, fd=None, sockets=None, socket_queue=None, argv=None, argc=None, environ=None, auxv=None, tls_modules=None, sigmask=None, pid=None, ppid=None, uid=None, gid=None, brk=None*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

property closed_fds

init_state()

Use this function to perform any initialization on the state at plugin-add time

set_brk(*new_brk*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

open(*name, flags, preferred_fd=None*)

Open a symbolic file. Basically `open(2)`.

Parameters

- **name** (*string* or *bytes*) – Path of the symbolic file, as a string or bytes.
- **flags** – File operation flags, a bitfield of constants from `open(2)`, as an AST

- **preferred_fd** – Assign this fd if it’s not already claimed.

Returns

The file descriptor number allocated (maps through `posix.get_fd` to a `SimFileDescriptor`) or -1 if the open fails.

mode from `open(2)` is unsupported at present.

open_socket(*ident*)

get_fd(*fd*, *create_file=True*)

Looks up the `SimFileDescriptor` associated with the given number (an AST). If the number is concrete and does not map to anything, return `None`. If the number is symbolic, constrain it to an open fd and create a new file for it. Set *create_file* to `False` if no write-access is planned (i.e. fd is read-only).

get_concrete_fd(*fd*, *create_file=True*)

Same behavior as `get_fd(fd)`, only the result is a concrete integer fd (or -1) instead of a `SimFileDescriptor`.

close(*fd*)

Closes the given file descriptor (an AST). Returns whether the operation succeeded (a concrete boolean)

fstat(*fd*)

fstat_with_result(*sim_fd*)

sigmask(*sigsetsize=None*)

Gets the current sigmask. If it’s blank, a new one is created (of *sigsetsize*).

Parameters

sigsetsize – the size (in *bytes* of the sigmask set)

Returns

the sigmask

sigprocmask(*how*, *new_mask*, *sigsetsize*, *valid_ptr=True*)

Updates the signal mask.

Parameters

- **how** – the “how” argument of `sigprocmask` (see manpage)
- **new_mask** – the mask modification to apply
- **sigsetsize** – the size (in *bytes* of the sigmask set)
- **valid_ptr** – is set if the *new_mask* was not `NULL`

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and *common_ancestor* before calling sub-elements’ merge methods, e.g.

```

self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)

```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen()`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`dump_file_by_path(path, **kwargs)`

Returns the concrete content for a file by path.

Parameters

- **path** – file path as string
- **kwargs** – passed to `state.solver.eval`

Returns

file contents as string

`dumps(fd, **kwargs)`

Returns the concrete content for a file descriptor.

BACKWARD COMPATIBILITY: if you ask for file descriptors 0 1 or 2, it will return the data from stdin, stdout, or stderr as a flat string.

Parameters

- **fd** – A file descriptor.

Returns

The concrete content.

Return type

`str`

state: `angr.SimState`

```
class angr.state_plugins.filesystem.Stat(st_dev, st_ino, st_nlink, st_mode, st_uid, st_gid, st_rdev,
                                         st_size, st_blksize, st_blocks, st_atime, st_atimensec, st_mtime,
                                         st_mtimensec, st_ctime, st_ctimensec)
```

Bases: `tuple`

st_atime

Alias for field number 10

st_atimensec

Alias for field number 11

st_blksize

Alias for field number 8

st_blocks

Alias for field number 9

st_ctime

Alias for field number 14

st_ctimensec

Alias for field number 15

st_dev

Alias for field number 0

st_gid

Alias for field number 5

st_ino

Alias for field number 1

st_mode

Alias for field number 3

st_mtime

Alias for field number 12

st_mtimensec

Alias for field number 13

st_nlink

Alias for field number 2

st_rdev

Alias for field number 6

st_size

Alias for field number 7

st_uid

Alias for field number 4

class `angr.state_plugins.filesystem.SimFilesystem`(*files=None, pathsep=None, cwd=None, mountpoints=None*)

Bases: [*SimStatePlugin*](#)

angr’s emulated filesystem. Available as `state.fs`. When constructing, all parameters are optional.

Parameters

- **files** – A mapping from filepath to `SimFile`
- **pathsep** – The character used to separate path elements, default forward slash.
- **cwd** – The path of the current working directory to use
- **mountpoints** – A mapping from filepath to `SimMountpoint`

Variables

- **pathsep** – The current pathsep
- **cwd** – The current working directory
- **unlinks** – A list of unlink operations, tuples of filename and simfile. Be careful, this list is shallow-copied from successor to successor, so don’t mutate anything in it without copying.

__init__(*files=None, pathsep=None, cwd=None, mountpoints=None*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

property `unlinks`

set_state(*state*)

Sets a new state (for example, if the state has been branched)

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

chdir(*path*)

Changes the current directory to the given path

get(*path*)

Get a file from the filesystem. Returns a `SimFile` or `None`.

insert(*path*, *simfile*)

Insert a file into the filesystem. Returns whether the operation was successful.

delete(*path*)

Remove a file from the filesystem. Returns whether the operation was successful.

This will add a `fs_unlink` event with the path of the file and also the index into the `unlinks` list.

mount(*path*, *mount*)

Add a mountpoint to the filesystem.

unmount(*path*)

Remove a mountpoint from the filesystem.

get_mountpoint(*path*)

Look up the mountpoint servicing the given path.

Returns

A tuple of the mount and a list of path elements traversing from the mountpoint to the specified file.

state: `angr.SimState`

class `angr.state_plugins.filesystem.SimMount`

Bases: `SimStatePlugin`

This is the base class for “mount points” in angr’s simulated filesystem. Subclass this class and give it to the filesystem to intercept all file creations and opens below the mountpoint. Since this a `SimStatePlugin` you may also want to implement `set_state`, `copy`, `merge`, etc.

get(*path_elements*)

Implement this function to instrument file lookups.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `SimFile`, or `None`

insert(*path_elements*, *simfile*)

Implement this function to instrument file creation.

Parameters

- **path_elements** – A list of path elements traversing from the mountpoint to the file
- **simfile** – The file to insert

Returns

A bool indicating whether the insert occurred

delete(*path_elements*)

Implement this function to instrument file deletion.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A bool indicating whether the delete occurred

lookup(*sim_file*)

Look up the path of a `SimFile` in the mountpoint

Parameters

sim_file – A `SimFile` object needs to be looked up

Returns

A string representing the path of the file in the mountpoint Or `None` if the `SimFile` does not exist in the mountpoint

state: `angr.SimState`

class `angr.state_plugins.filesystem.SimConcreteFilesystem`(*pathsep*='/')

Bases: `SimMount`

Abstract `SimMount` allowing the user to import files from some external source into the guest

Parameters

pathsep (*str*) – The host path separator character, default `os.path.sep`

__init__(*pathsep*='/')

get(*path_elements*)

Implement this function to instrument file lookups.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A `SimFile`, or `None`

insert(*path_elements*, *simfile*)

Implement this function to instrument file creation.

Parameters

- **path_elements** – A list of path elements traversing from the mountpoint to the file
- **simfile** – The file to insert

Returns

A bool indicating whether the insert occurred

delete(*path_elements*)

Implement this function to instrument file deletion.

Parameters

path_elements – A list of path elements traversing from the mountpoint to the file

Returns

A bool indicating whether the delete occurred

lookup(*sim_file*)

Look up the path of a `SimFile` in the mountpoint

Parameters

sim_file – A `SimFile` object needs to be looked up

Returns

A string representing the path of the file in the mountpoint Or `None` if the `SimFile` does not exist in the mountpoint

copy(*memo*=`None`, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

set_state(*state*)

Sets a new state (for example, if the state has been branched)

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

bool

state: `angr.SimState`

class `angr.state_plugins.filesystem.SimHostFilesystem`(*host_path=None, **kwargs*)

Bases: [*SimConcreteFilesystem*](#)

Simulated mount that makes some piece from the host filesystem available to the guest.

Parameters

- **host_path** (*str*) – The path on the host to mount
- **pathsep** (*str*) – The host path separator character, default `os.path.sep`

__init__(*host_path=None, **kwargs*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

`angr.state_plugins.solver.timed_function(f)`

`angr.state_plugins.solver.enable_timing()`

`angr.state_plugins.solver.disable_timing()`

`angr.state_plugins.solver.error_converter(f)`

`angr.state_plugins.solver.concrete_path_bool(f)`

`angr.state_plugins.solver.concrete_path_not_bool(f)`

`angr.state_plugins.solver.concrete_path_scalar(f)`

`angr.state_plugins.solver.concrete_path_tuple(f)`

`angr.state_plugins.solver.concrete_path_list(f)`

class `angr.state_plugins.solver.SimSolver`(*solver=None, all_variables=None, temporal_tracked_variables=None, eternal_tracked_variables=None*)

Bases: [*SimStatePlugin*](#)

This is the plugin you'll use to interact with symbolic variables, creating them and evaluating them. It should be available on a state as `state.solver`.

Any top-level variable of the claripy module can be accessed as a property of this object.

__init__(*solver=None, all_variables=None, temporal_tracked_variables=None, eternal_tracked_variables=None*)

reload_solver(*constraints=None*)

Reloads the solver. Useful when changing solver options.

Parameters

constraints (*list*) – A new list of constraints to use in the reloaded solver instead of the current one

get_variables(**keys*)

Iterate over all variables for which their tracking key is a prefix of the values provided.

Elements are a tuple, the first element is the full tracking key, the second is the symbol.

```
>>> list(s.solver.get_variables('mem'))
[ (('mem', 0x1000), <BV64 mem_1000_4_64>), (('mem', 0x1008), <BV64 mem_1008_5_64>
↪ )]
```

```
>>> list(s.solver.get_variables('file'))
[ (('file', 1, 0), <BV8 file_1_0_6_8>), (('file', 1, 1), <BV8 file_1_1_7_8>), (('
↪ 'file', 2, 0), <BV8 file_2_0_8_8>)]
```

```
>>> list(s.solver.get_variables('file', 2))
[ (('file', 2, 0), <BV8 file_2_0_8_8>)]
```

```
>>> list(s.solver.get_variables())
[ (('mem', 0x1000), <BV64 mem_1000_4_64>), (('mem', 0x1008), <BV64 mem_1008_5_64>
↪ ), (('file', 1, 0), <BV8 file_1_0_6_8>), (('file', 1, 1), <BV8 file_1_1_7_8>),
↪ (('file', 2, 0), <BV8 file_2_0_8_8>)]
```

register_variable(*v, key, eternal=True*)

Register a value with the variable tracking system

Parameters

- **v** – The BVS to register
- **key** – A tuple to register the variable under

Parma eternal

Whether this is an eternal variable, default True. If False, an incrementing counter will be appended to the key.

describe_variables(*v*)

Given an AST, iterate over all the keys of all the BVS leaves in the tree which are registered.

Unconstrained(*name, bits, uninitialized=True, inspect=True, events=True, key=None, eternal=False, **kwargs*)

Creates an unconstrained symbol or a default concrete value (0), based on the state options.

Parameters

- **name** – The name of the symbol.
- **bits** – The size (in bits) of the symbol.
- **uninitialized** – Whether this value should be counted as an “uninitialized” value in the course of an analysis.
- **inspect** – Set to False to avoid firing SimInspect breakpoints
- **events** – Set to False to avoid generating a SimEvent for the occasion

- **key** – Set this to a tuple of increasingly specific identifiers (for example, ('mem', 0xffbeff00) or ('file', 4, 0x20) to cause it to be tracked, i.e. accessible through `solver.get_variables`.
- **eternal** – Set to True in conjunction with setting a key to cause all states with the same ancestry to retrieve the same symbol when trying to create the value. If False, a counter will be appended to the key.

Returns

an unconstrained symbol (or a concrete value of 0).

BVS(*name*, *size*, *min=None*, *max=None*, *stride=None*, *uninitialized=False*, *explicit_name=None*, *key=None*, *eternal=False*, *inspect=True*, *events=True*, ***kwargs*)

Creates a bit-vector symbol (i.e., a variable). Other keyword parameters are passed directly on to the constructor of `claripy.ast.BV`.

Parameters

- **name** – The name of the symbol.
- **size** – The size (in bits) of the bit-vector.
- **min** – The minimum value of the symbol. Note that this **only** work when using VSA.
- **max** – The maximum value of the symbol. Note that this **only** work when using VSA.
- **stride** – The stride of the symbol. Note that this **only** work when using VSA.
- **uninitialized** – Whether this value should be counted as an “uninitialized” value in the course of an analysis.
- **explicit_name** – Set to True to prevent an identifier from appended to the name to ensure uniqueness.
- **key** – Set this to a tuple of increasingly specific identifiers (for example, ('mem', 0xffbeff00) or ('file', 4, 0x20) to cause it to be tracked, i.e. accessible through `solver.get_variables`.
- **eternal** – Set to True in conjunction with setting a key to cause all states with the same ancestry to retrieve the same symbol when trying to create the value. If False, a counter will be appended to the key.
- **inspect** – Set to False to avoid firing `SimInspect` breakpoints
- **events** – Set to False to avoid generating a `SimEvent` for the occasion

Returns

A BV object representing this symbol.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

- **memo** – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

bool

downsize()

Frees memory associated with the constraint solver by clearing all of its internal caches.

property constraints

Returns the constraints of the state stored by the solver.

eval_to_ast(*e*, *n*, *extra_constraints*=(), *exact*=None)

Evaluate an expression, using the solver if necessary. Returns AST objects.

Parameters

- **e** – the expression
- **n** – the number of desired solutions
- **extra_constraints** – extra constraints to apply to the solver
- **exact** – if False, returns approximate solutions

Returns

a tuple of the solutions, in the form of claripy AST nodes

Return type

tuple

max(*e*, *extra_constraints*=(), *exact*=None, *signed*=False)

Return the maximum value of expression *e*.

:param *e* : expression (an AST) to evaluate :type *extra_constraints*: :param *extra_constraints*: extra constraints (as ASTs) to add to the solver for this solve :param *exact* : if False, return approximate solutions. :param *signed* : Whether the expression should be treated as a signed value. :return: the maximum possible value of *e* (backend object)

min(*e*, *extra_constraints*=(), *exact*=None, *signed*=False)

Return the minimum value of expression *e*.

:param *e* : expression (an AST) to evaluate :type *extra_constraints*: :param *extra_constraints*: extra constraints (as ASTs) to add to the solver for this solve :param *exact* : if False, return approximate solutions. :param *signed* : Whether the expression should be treated as a signed value. :return: the minimum possible value of *e* (backend object)

solution(*e*, *v*, *extra_constraints*=(), *exact*=None)

Return True if *v* is a solution of *expr* with the extra constraints, False otherwise.

Parameters

- **e** – An expression (an AST) to evaluate
- **v** – The proposed solution (an AST)
- **extra_constraints** – Extra constraints (as ASTs) to add to the solver for this solve.
- **exact** – If False, return approximate solutions.

Returns

True if *v* is a solution of *expr*, False otherwise

is_true(*e*, *extra_constraints*=(), *exact*=None)

If the expression provided is absolutely, definitely a true boolean, return True. Note that returning False doesn't necessarily mean that the expression can be false, just that we couldn't figure that out easily.

Parameters

- **e** – An expression (an AST) to evaluate
- **extra_constraints** – Extra constraints (as ASTs) to add to the solver for this solve.
- **exact** – If False, return approximate solutions.

Returns

True if v is definitely true, False otherwise

is_false(e , *extra_constraints*=(), *exact*=None)

If the expression provided is absolutely, definitely a false boolean, return True. Note that returning False doesn't necessarily mean that the expression can be true, just that we couldn't figure that out easily.

Parameters

- **e** – An expression (an AST) to evaluate
- **extra_constraints** – Extra constraints (as ASTs) to add to the solver for this solve.
- **exact** – If False, return approximate solutions.

Returns

True if v is definitely false, False otherwise

unsat_core(*extra_constraints*=())

This function returns the unsat core from the backend solver.

Parameters

extra_constraints – Extra constraints (as ASTs) to add to the solver for this solve.

Returns

The unsat core.

satisfiable(*extra_constraints*=(), *exact*=None)

This function does a constraint check and checks if the solver is in a sat state.

Parameters

- **extra_constraints** – Extra constraints (as ASTs) to add to s for this solve
- **exact** – If False, return approximate solutions.

Returns

True if sat, otherwise false

add(**constraints*)

Add some constraints to the solver.

Parameters

constraints – Pass any constraints that you want to add (ASTs) as varargs.

CastType = ~CastType

eval_upto(e , n , *cast_to*=None, ***kwargs*)

Evaluate an expression, using the solver if necessary. Returns primitives as specified by the *cast_to* parameter. Only certain primitives are supported, check the implementation of *_cast_to* to see which ones.

Parameters

- **e** – the expression
- **n** – the number of desired solutions
- **extra_constraints** – extra constraints to apply to the solver
- **exact** – if False, returns approximate solutions
- **cast_to** – desired type of resulting values

Returns

a tuple of the solutions, in the form of Python primitives

Return type

`tuple`

eval(*e*, *cast_to*=None, ****kwargs**)

Evaluate an expression to get any possible solution. The desired output types can be specified using the *cast_to* parameter. *extra_constraints* can be used to specify additional constraints the returned values must satisfy.

Parameters

- **e** – the expression to get a solution for
- **kwargs** – Any additional kwargs will be passed down to *eval_upto*
- **cast_to** – desired type of resulting values

Raises

SimUnsatError – if no solution could be found satisfying the given constraints

Returns

eval_one(*e*, *cast_to*=None, ****kwargs**)

Evaluate an expression to get the only possible solution. Errors if either no or more than one solution is returned. A kwarg parameter *default* can be specified to be returned instead of failure!

Parameters

- **e** – the expression to get a solution for
- **cast_to** – desired type of resulting values
- **default** – A value can be passed as a kwarg here. It will be returned in case of failure.
- **kwargs** – Any additional kwargs will be passed down to *eval_upto*

Raises

- *SimUnsatError* – if no solution could be found satisfying the given constraints
- *SimValueError* – if more than one solution was found to satisfy the given constraints

Returns

The value for *e*

state: `angr.SimState`

eval_atmost(*e*, *n*, *cast_to*=None, ****kwargs**)

Evaluate an expression to get at most *n* possible solutions. Errors if either none or more than *n* solutions are returned.

Parameters

- **e** – the expression to get a solution for
- **n** – the inclusive upper limit on the number of solutions
- **cast_to** – desired type of resulting values
- **kwargs** – Any additional kwargs will be passed down to *eval_upto*

Raises

- *SimUnsatError* – if no solution could be found satisfying the given constraints
- *SimValueError* – if more than *n* solutions were found to satisfy the given constraints

Returns

The solutions for e

eval_atleast($e, n, \text{cast_to}=\text{None}, **\text{kwards}$)

Evaluate an expression to get at least n possible solutions. Errors if less than n solutions were found.

Parameters

- **e** – the expression to get a solution for
- **n** – the inclusive lower limit on the number of solutions
- **cast_to** – desired type of resulting values
- **kwards** – Any additional kwards will be passed down to *eval_upto*

Raises

- **SimUnsatError** – if no solution could be found satisfying the given constraints
- **SimValueError** – if less than n solutions were found to satisfy the given constraints

Returns

The solutions for e

eval_exact($e, n, \text{cast_to}=\text{None}, **\text{kwards}$)

Evaluate an expression to get exactly the n possible solutions. Errors if any number of solutions other than n was found to exist.

Parameters

- **e** – the expression to get a solution for
- **n** – the inclusive lower limit on the number of solutions
- **cast_to** – desired type of resulting values
- **kwards** – Any additional kwards will be passed down to *eval_upto*

Raises

- **SimUnsatError** – if no solution could be found satisfying the given constraints
- **SimValueError** – if any number of solutions other than n were found to satisfy the given constraints

Returns

The solutions for e

min_int($e, \text{extra_constraints}=(), \text{exact}=\text{None}, \text{signed}=\text{False}$)

Return the minimum value of expression e .

:param e : expression (an AST) to evaluate :type extra_constraints : :param extra_constraints : extra constraints (as ASTs) to add to the solver for this solve :param exact : if False, return approximate solutions. :param signed : Whether the expression should be treated as a signed value. :return: the minimum possible value of e (backend object)

max_int($e, \text{extra_constraints}=(), \text{exact}=\text{None}, \text{signed}=\text{False}$)

Return the maximum value of expression e .

:param e : expression (an AST) to evaluate :type extra_constraints : :param extra_constraints : extra constraints (as ASTs) to add to the solver for this solve :param exact : if False, return approximate solutions. :param signed : Whether the expression should be treated as a signed value. :return: the maximum possible value of e (backend object)

unique(*e*, ***kwargs*)

Returns True if the expression *e* has only one solution by querying the constraint solver. It does also add that unique solution to the solver's constraints.

symbolic(*e*)

Returns True if the expression *e* is symbolic.

single_valued(*e*)

Returns True whether *e* is a concrete value or is a value set with only 1 possible value. This differs from *unique* in that this *does* not query the constraint solver.

simplify(*e=None*)

Simplifies *e*. If *e* is None, simplifies the constraints of this state.

variables(*e*)

Returns the symbolic variables present in the AST of *e*.

class `angr.state_plugins.log.SimStateLog`(*log=None*)

Bases: `SimStatePlugin`

__init__(*log=None*)

property actions

add_event(*event_type*, ***kwargs*)

add_action(*action*)

extend_actions(*new_actions*)

events_of_type(*event_type*)

actions_of_type(*action_type*)

property fresh_constraints

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` `others` and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`clear()`

state: `angr.SimState`

```
class angr.state_plugins.callstack.CallStack(call_site_addr=0, func_addr=0, stack_ptr=0,
                                             ret_addr=0, jumpkind='Ijk_Call', next_frame=None,
                                             invoke_return_variable=None)
```

Bases: `SimStatePlugin`

Stores the address of the function you’re in and the value of SP at the VERY BOTTOM of the stack, i.e. points to the return address.

Parameters

next_frame (`CallStack` / `None`) –

```
__init__(call_site_addr=0, func_addr=0, stack_ptr=0, ret_addr=0, jumpkind='Ijk_Call',
         next_frame=None, invoke_return_variable=None)
```

Parameters

next_frame (`CallStack` | `None`) –

state: `angr.SimState`

copy (`memo=None, **kwargs`)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

set_state (`state`)

Sets a new state (for example, if the state has been branched)

merge (`others, merge_conditions, common_ancestor=None`)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

property current_function_address

Address of the current function.

Returns

the address of the function

Return type

`int`

property current_stack_pointer

Get the value of the stack pointer.

Returns

Value of the stack pointer

Return type

`int`

property current_return_target

Get the return target.

Returns

The address of return target.

Return type

`int`

static stack_suffix_to_string(*stack_suffix*)

Convert a stack suffix to a human-readable string representation. :param tuple `stack_suffix`: The stack suffix. :return: A string representation :rtype: str

property top

Returns the element at the top of the callstack without removing it.

Returns

A CallStack.

push(*cf*)

Push the frame `cf` onto the stack. Return the new stack.

pop()

Pop the top frame from the stack. Return the new stack.

call(*callsite_addr*, *addr*, *retn_target=None*, *stack_pointer=None*)

Push a stack frame into the call stack. This method is called when calling a function in CFG recovery.

Parameters

- **callsite_addr** (*int*) – Address of the call site
- **addr** (*int*) – Address of the call target
- **retn_target** (*int* or *None*) – Address of the return target
- **stack_pointer** (*int*) – Value of the stack pointer

Returns

None

ret(*retn_target=None*)

Pop one or many call frames from the stack. This method is called when returning from a function in CFG recovery.

Parameters

- **retn_target** (*int*) – The target to return to.

Returns

None

dbg_repr()

Debugging representation of this CallStack object.

Returns

Details of this CallStack

Return type

str

stack_suffix(*context_sensitivity_level*)

Generate the stack suffix. A stack suffix can be used as the key to a SimRun in CFG recovery.

Parameters

- **context_sensitivity_level** (*int*) – Level of context sensitivity.

Returns

A tuple of stack suffix.

Return type

tuple

class `angr.state_plugins.callstack.CallStackAction`(*callstack_hash*, *callstack_depth*, *action*, *callframe=None*, *ret_site_addr=None*)

Bases: `object`

Used in callstack backtrace, which is a history of callstacks along a path, to record individual actions occurred each time the callstack is changed.

__init__(*callstack_hash*, *callstack_depth*, *action*, *callframe=None*, *ret_site_addr=None*)

class `angr.state_plugins.light_registers.SimLightRegisters`(*reg_map=None*, *registers=None*)

Bases: `SimStatePlugin`


```
__init__(reg_map=None, registers=None)
```

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
set_state(state)
```

Sets a new state (for example, if the state has been branched)

```
resolve_register(offset, size)
```

```
load(offset, size=None, **kwargs)
```

```
store(offset, value, size=None, endness=None, **kwargs)
```

```
state: angr.SimState
```

```
class angr.state_plugins.history.SimStateHistory(parent=None, clone=None)
```

Bases: [SimStatePlugin](#)

This class keeps track of historically-relevant information for paths.

```
STRONGREF_STATE = True
```

```
__init__(parent=None, clone=None)
```

```
init_state()
```

Use this function to perform any initialization on the state at plugin-add time

```
set_strongref_state(state)
```

```
property addr
```

```
merge(others, merge_conditions, common_ancestor=None)
```

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

- **memo** – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

trim()

Discard the ancestry of this state.

filter_actions(*start_block_addr=None, end_block_addr=None, block_stmt=None, insn_addr=None, read_from=None, write_to=None*)

Filter `self.actions` based on some common parameters.

[`start_block_addr`, `end_block_addr`]

Parameters

- **`start_block_addr`** – Only return actions generated in blocks starting at this address.
- **`end_block_addr`** – Only return actions generated in blocks ending at this address.
- **`block_stmt`** – Only return actions generated in the `nth` statement of each block.
- **`insn_addr`** – Only return actions generated in the assembly instruction at this address.
- **`read_from`** – Only return actions that perform a read from the specified location.
- **`write_to`** – Only return actions that perform a write to the specified location.

Notes: If IR optimization is turned on, reads and writes may not occur in the instruction they originally came from. Most commonly, If a register is read from twice in the same block, the second read will not happen, instead reusing the temp the value is already stored in.

Valid values for `read_from` and `write_to` are the string literals `'reg'` or `'mem'` (matching any read or write to registers or memory, respectively), any string (representing a read or write to the named register), and any integer (representing a read or write to the memory at this address).

`demote()`

Demotes this history node, causing it to drop the strong state reference.

`reachable()`

`add_event(event_type, **kwargs)`

`add_action(action)`

`extend_actions(new_actions)`

`subscribe_actions()`

property recent_constraints

property recent_actions

property block_count

property lineage

property parents

property events

property actions

property jumpkinds

property jump_guards

property jump_targets

property jump_sources

property descriptions

property `bbl_addrs`

property `ins_addrs`

property `stack_actions`

closest_common_ancestor(*other*)

Find the common ancestor between this history node and ‘other’.

Parameters

other – the PathHistory to find a common ancestor with.

Returns

the common ancestor SimStateHistory, or None if there isn’t one

constraints_since(*other*)

Returns the constraints that have been accumulated since *other*.

Parameters

other – a prior PathHistory object

Returns

a list of constraints

make_child()

state: `angr.SimState`

class `angr.state_plugins.history.TreeIter`(*start*, *end=None*)

Bases: `object`

__init__(*start*, *end=None*)

property `hardcopy`

count(*v*)

Count occurrences of value *v* in the entire history. Note that the subclass must implement the `__reversed__` method, otherwise an exception will be thrown. :param object *v*: The value to look for :return: The number of occurrences :rtype: int

class `angr.state_plugins.history.HistoryIter`(*start*, *end=None*)

Bases: `TreeIter`

class `angr.state_plugins.history.LambdaAttrIter`(*start*, *f*, ***kwargs*)

Bases: `TreeIter`

__init__(*start*, *f*, ***kwargs*)

class `angr.state_plugins.history.LambdaIterIter`(*start*, *f*, *reverse=True*, ***kwargs*)

Bases: `LambdaAttrIter`

__init__(*start*, *f*, *reverse=True*, ***kwargs*)

class `angr.state_plugins.gdb.GDB`(*omit_fp=False*, *adjust_stack=False*)

Bases: `SimStatePlugin`

Initialize or update a state from gdb dumps of the stack, heap, registers and data (or arbitrary) segments.

`__init__(omit_fp=False, adjust_stack=False)`

Parameters

- **omit_fp** – The frame pointer register is used for something else. (i.e. `-omit_frame_pointer`)
- **adjust_stack** – Use different stack addresses than the gdb session (not recommended).

`set_stack(stack_dump, stack_top)`

Stack dump is a dump of the stack from gdb, i.e. the result of the following gdb command :

`dump binary memory [stack_dump] [begin_addr] [end_addr]`

We set the stack to the same addresses as the gdb session to avoid pointers corruption.

Parameters

- **stack_dump** – The dump file.
- **stack_top** – The address of the top of the stack in the gdb session.

`set_heap(heap_dump, heap_base)`

Heap dump is a dump of the heap from gdb, i.e. the result of the following gdb command:

`dump binary memory [stack_dump] [begin] [end]`

Parameters

- **heap_dump** – The dump file.
- **heap_base** – The start address of the heap in the gdb session.

`set_data(addr, data_dump)`

Update any data range (most likely use is the data segments of loaded objects)

`set_regs(regs_dump)`

Initialize register values within the state

Parameters

regs_dump – The output of `info registers` in gdb.

`copy(memo=None, **kwargs)`

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

`class angr.state_plugins.cgc.SimStateCGC`

Bases: `SimStatePlugin`

This state plugin keeps track of CGC state.

EBADF = 1

EFAULT = 2

EINVAL = 3

ENOMEM = 4

ENOSYS = 5

EPIPE = 6

FD_SETSIZE = 1024

max_allocation = 268435456

__init__()

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

peek_input()

discard_input(num_bytes)

peek_output()

discard_output(num_bytes)

addr_invalid(a)

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

get_max_sinkhole(*length*)

Find a sinkhole which is large enough to support *length* bytes.

This uses first-fit. The first sinkhole (ordered in descending order by their address) which can hold *length* bytes is chosen. If there are more than *length* bytes in the sinkhole, a new sinkhole is created representing the remaining bytes while the old sinkhole is removed.

add_sinkhole(*address*, *length*)

Add a sinkhole.

Allow the possibility for the program to reuse the memory represented by the address length pair.

state: `angr.SimState`

This file contains objects to track additional information during a trace or modify symbolic variables during a trace.

The `ChallRespInfo` plugin tracks variables in `stdin` and `stdout` to enable handling of challenge response. It handles `atoi/int2str` in a special manner since path constraints will usually prevent their values from being modified.

The `Zen` plugin simplifies expressions created from variables in the flag page (losing some accuracy) to avoid situations where they become too complex for `z3`, but the actual equation doesn't matter much. This can happen in challenge response if all of the values in the flag page are multiplied together before being printed.

class `angr.state_plugins.trace_additions.FormatInfo`

Bases: `object`

`copy()`

compute(*state*)

get_type()

class angr.state_plugins.trace_additions.**FormatInfoStrToInt**(*addr, func_name, str_arg_num, base, base_arg, allows_negative*)

Bases: *FormatInfo*

__init__(*addr, func_name, str_arg_num, base, base_arg, allows_negative*)

copy()

compute(*state*)

get_type()

class angr.state_plugins.trace_additions.**FormatInfoIntToStr**(*addr, func_name, int_arg_num, str_dst_num, base, base_arg*)

Bases: *FormatInfo*

__init__(*addr, func_name, int_arg_num, str_dst_num, base, base_arg*)

copy()

compute(*state*)

get_type()

class angr.state_plugins.trace_additions.**FormatInfoDontConstrain**(*addr, func_name, check_symbolic_arg*)

Bases: *FormatInfo*

__init__(*addr, func_name, check_symbolic_arg*)

copy()

compute(*state*)

get_type()

angr.state_plugins.trace_additions.**int2base**(*x, base*)

angr.state_plugins.trace_additions.**generic_info_hook**(*state*)

angr.state_plugins.trace_additions.**end_info_hook**(*state*)

angr.state_plugins.trace_additions.**exit_hook**(*state*)

angr.state_plugins.trace_additions.**syscall_hook**(*state*)

angr.state_plugins.trace_additions.**constraint_hook**(*state*)

class angr.state_plugins.trace_additions.**ChallRespInfo**

Bases: *SimStatePlugin*

This state plugin keeps track of the reads and writes to symbolic addresses

__init__()

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`static get_byte(var_name)`

`lookup_original(replacement)`

`pop_from_backup()`

`get_stdin_indices(variable)`

`get_stdout_indices(variable)`

`get_real_len(input_val, base, result_bv, allows_negative)`

`get_possible_len(input_val, base, allows_negative)`

`get_same_length_constraints()`

`static atoi_dumps(state, require_same_length=True)`

`static prep_tracer(state, format_infos=None)`

`state: SimState`

`angr.state_plugins.trace_additions.zen_hook(state, expr)`

`angr.state_plugins.trace_additions.zen_memory_write(state)`

`angr.state_plugins.trace_additions.zen_register_write(state)`

`class angr.state_plugins.trace_additions.ZenPlugin(max_depth=13)`

Bases: `SimStatePlugin`

`__init__(max_depth=13)`

`static get_flag_rand_args(expr)`

`get_expr_depth(expr)`

`copy(memo=None, **kwargs)`

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

bool

get_flag_bytes(*ast*)

filter_constraints(*constraints*)

analyze_transmit(*state*, *buf*)

static prep_tracer(*state*)

state: *SimState*

class `angr.state_plugins.globals.SimStateGlobals`(*backer=None*)

Bases: *SimStatePlugin*

__init__(*backer=None*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* *others* and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you "deepen" both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be *None*, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

keys()

values()

items()

get(*k*, *alt=None*)

pop(*k*, *alt=None*)

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.state_plugins.uc_manager.SimUCManager`(*man=None*)

Bases: `SimStatePlugin`

__init__(*man=None*)

assign(*dst_addr_ast*)

Assign a new region for under-constrained symbolic execution.

Parameters

dst_addr_ast – the symbolic AST which address of the new allocated region will be assigned to.

Returns

as ast of memory address that points to a new region

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

get_alloc_depth(*addr*)

is_bounded(*ast*)

Test whether an AST is bounded by any existing constraint in the related solver.

Parameters

ast – an `claripy.AST` object

Returns

True if there is at least one related constraint, False otherwise

state: `angr.SimState`

set_state(*state*)

Sets a new state (for example, if the state has been branched)

class `angr.state_plugins.scratch.SimStateScratch`(*scratch=None*)

Bases: [*SimStatePlugin*](#)

Implements the scratch state plugin.

__init__(*scratch=None*)

state: `angr.SimState`

property `priv`

push_priv(*priv*)

pop_priv()

set_tyenv(*tyenv*)

tmp_expr(*tmp*)

Returns the Claripy expression of a VEX temp value.

Parameters

- **tmp** – the number of the tmp
- **simplify** – simplify the tmp before returning it

Returns

a Claripy expression of the tmp

store_tmp(*tmp, content, reg_deps=None, tmp_deps=None, deps=None, **kwargs*)

Stores a Claripy expression in a VEX temp value. If in symbolic mode, this involves adding a constraint for the tmp's symbolic variable.

Parameters

- **tmp** – the number of the tmp
- **content** – a Claripy expression of the content
- **reg_deps** – the register dependencies of the content
- **tmp_deps** – the temporary value dependencies of the content

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters**others** – the other state plugin**Returns**

True if the state plugin is actually widened.

Return type

bool

clear()**class** `angr.state_plugins.preconstrainer.SimStatePreconstrainer`(*constrained_addrs=None*)Bases: `SimStatePlugin`

This state plugin manages the concept of preconstraining - adding constraints which you would like to remove later.

Parameters**constrained_addrs** – SimActions for memory operations whose addresses should be constrained during crash analysis**__init__**(*constrained_addrs=None*)**merge**(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

bool

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

preconstrain(*value, variable*)

Add a precondition that `variable == value` to the state.

Parameters

- **value** – The concrete value. Can be a bitvector or a bytestring or an integer.
- **variable** – The BVS to precondition.

preconstrain_file(*content, simfile, set_length=False*)

Preconstrain the contents of a file.

Parameters

- **content** – The content to precondition the file to. Can be a bytestring or a list thereof.
- **simfile** – The actual simfile to precondition

preconstrain_flag_page(*magic_content*)

Preconstrain the data in the flag page.

Parameters

magic_content – The content of the magic page as a bytestring.

remove_preconstraints(*to_composite_solver=True, simplify=True*)

Remove the preconstraints from the state.

If you are using the zen plugin, this will also use that to filter the constraints.

Parameters

- **to_composite_solver** – Whether to convert the replacement solver to a composite solver. You probably want this if you're switching from tracing to symbolic analysis.

- **simplify** – Whether to simplify the resulting set of constraints.

reconstrain()

Split the solver. If any of the subsolvers time out after a short timeout (10 seconds), re-add the preconstraints associated with each of its variables. Hopefully these constraints still allow us to do meaningful things to the state.

state: `angr.SimState`

class `angr.state_plugins.unicorn_engine.MEM_PATCH`

Bases: `Structure`

`struct mem_update_t`

address

Structure/Union member

length

Structure/Union member

next

Structure/Union member

class `angr.state_plugins.unicorn_engine.TRANSMIT_RECORD`

Bases: `Structure`

`struct transmit_record_t`

count

Structure/Union member

data

Structure/Union member

fd

Structure/Union member

class `angr.state_plugins.unicorn_engine.TaintEntityEnum`

Bases: `object`

`taint_entity_enum_t`

TAINT_ENTITY_REG = 0

TAINT_ENTITY_TMP = 1

TAINT_ENTITY_MEM = 2

TAINT_ENTITY_NONE = 3

class `angr.state_plugins.unicorn_engine.MemoryValue`

Bases: `Structure`

`struct memory_value_t`

address

Structure/Union member

is_value_set

Structure/Union member

is_value_symbolic

Structure/Union member

value

Structure/Union member

class angr.state_plugins.unicorn_engine.**RegisterValue**

Bases: Structure

struct register_value_t

offset

Structure/Union member

size

Structure/Union member

value

Structure/Union member

class angr.state_plugins.unicorn_engine.**VEXStmtDetails**

Bases: Structure

struct sym_vex_stmt_details_t

has_memory_dep

Structure/Union member

memory_values

Structure/Union member

memory_values_count

Structure/Union member

stmt_idx

Structure/Union member

class angr.state_plugins.unicorn_engine.**BlockDetails**

Bases: Structure

struct sym_block_details_ret_t

block_addr

Structure/Union member

block_size

Structure/Union member

block_trace_ind

Structure/Union member

has_symbolic_exit

Structure/Union member

register_values

Structure/Union member

register_values_count

Structure/Union member

symbolic_vex_stmts

Structure/Union member

symbolic_vex_stmts_count

Structure/Union member

class `angr.state_plugins.unicorn_engine.STOP`

Bases: `object`

enum `stop_t`

`STOP_NORMAL = 0`

`STOP_STOPPOINT = 1`

`STOP_ERROR = 2`

`STOP_SYSCALL = 3`

`STOP_EXECPAGE = 4`

`STOP_ZEROPAGE = 5`

`STOP_NOSTART = 6`

`STOP_SEGFAULT = 7`

`STOP_ZERO_DIV = 8`

`STOP_NOEXCEPTION = 9`

`STOP_HLT = 10`

`STOP_VEX_LIFT_FAILED = 11`

`STOP_SYMBOLIC_PC = 12`

`STOP_SYMBOLIC_READ_ADDR = 13`

`STOP_SYMBOLIC_READ_SYMBOLIC_TRACKING_DISABLED = 14`

`STOP_SYMBOLIC_WRITE_ADDR = 15`

`STOP_SYMBOLIC_BLOCK_EXIT_CONDITION = 16`

`STOP_SYMBOLIC_BLOCK_EXIT_TARGET = 17`

`STOP_UNSUPPORTED_STMT_PUTI = 18`

`STOP_UNSUPPORTED_STMT_STOREG = 19`

`STOP_UNSUPPORTED_STMT_LOADG = 20`

`STOP_UNSUPPORTED_STMT_CAS = 21`

`STOP_UNSUPPORTED_STMT_LLSC = 22`

`STOP_UNSUPPORTED_STMT_DIRTY = 23`

`STOP_UNSUPPORTED_EXPR_GETI = 24`

```

STOP_UNSUPPORTED_STMT_UNKNOWN = 25

STOP_UNSUPPORTED_EXPR_UNKNOWN = 26

STOP_UNKNOWN_MEMORY_WRITE_SIZE = 27

STOP_SYSCALL_ARM = 28

STOP_X86_CPUID = 29

stop_message = {0: 'Reached maximum steps', 1: 'Hit a stop point', 2: 'Something
wrong', 3: 'Unable to handle syscall', 4: 'Fetching empty page', 5: 'Accessing
zero page', 6: 'Failed to start', 7: 'Permissions or mapping error', 8: 'Divide
by zero', 9: 'Instruction decoding error', 10: 'hlt instruction encountered', 11:
'Failed to lift block to VEX', 12: 'Instruction pointer became symbolic', 13:
'Attempted to read from symbolic address', 14: 'Attempted to read symbolic data
from memory but symbolic tracking is disabled', 15: 'Attempted to write to symbolic
address', 16: 'Guard condition of block's exit statement is symbolic', 17: 'Target
of default exit of block is symbolic', 18: 'Symbolic taint propagation for PutI
statement not yet supported', 19: 'Symbolic taint propagation for StoreG statement
not yet supported', 20: 'Symbolic taint propagation for LoadG statement not yet
supported', 21: 'Symbolic taint propagation for CAS statement not yet supported',
22: 'Symbolic taint propagation for LLSC statement not yet supported', 23:
'Symbolic taint propagation for Dirty statement not yet supported', 24: 'Symbolic
taint propagation for GetI expression not yet supported', 25: 'Canoo propagate
symbolic taint for unsupported VEX statement type', 26: 'Cannot propagate symbolic
taint for unsupported VEX expression', 27: 'Unicorn failed to determine size of
memory write', 28: 'ARM syscalls are currently not supported by SimEngineUnicorn',
29: 'Block executes cpuid which should be handled in VEX engine'}

symbolic_stop_reasons = {12, 13, 14, 15, 16, 17, 28, 29}

unsupported_reasons = {11, 18, 19, 20, 21, 22, 23, 25, 26}

static name_stop(num)

static get_stop_msg(stop_reason)

class angr.state_plugins.unicorn_engine.StopDetails
    Bases: Structure
    struct stop_details_t
    block_addr
        Structure/Union member
    block_size
        Structure/Union member
    stop_reason
        Structure/Union member

class angr.state_plugins.unicorn_engine.SimOSEnum
    Bases: object
    enum simos_t
    SIMOS_CGC = 0

```

```

SIMOS_LINUX = 1

SIMOS_OTHER = 2

exception angr.state_plugins.unicorn_engine.MemoryMappingError
    Bases: Exception

exception angr.state_plugins.unicorn_engine.AccessingZeroPageError
    Bases: MemoryMappingError

exception angr.state_plugins.unicorn_engine.FetchingZeroPageError
    Bases: MemoryMappingError

exception angr.state_plugins.unicorn_engine.SegfaultError
    Bases: MemoryMappingError

exception angr.state_plugins.unicorn_engine.MixedPermissionsError
    Bases: MemoryMappingError

class angr.state_plugins.unicorn_engine.AggressiveConcretizationAnnotation(addr)
    Bases: SimplificationAvoidanceAnnotation
    __init__(addr)

class angr.state_plugins.unicorn_engine.Uniwrapper(arch, cache_key, thumb=False)
    Bases: Uc
    __init__(arch, cache_key, thumb=False)

    hook_add(htype, callback, user_data=None, begin=1, end=0, arg1=0)

    hook_del(h)

    mem_map(addr, size, perms=7)

    mem_map_ptr(addr, size, perms, ptr)

    mem_unmap(addr, size)

    mem_reset()

    hook_reset()

    reset()

class angr.state_plugins.unicorn_engine.Unicorn(syscall_hooks=None, cache_key=None,
                                                unicount=None, symbolic_var_counts=None,
                                                symbolic_inst_counts=None, concretized_ast=None,
                                                always_concretize=None, never_concretize=None,
                                                concretize_at=None,
                                                concretization_threshold_memory=None,
                                                concretization_threshold_registers=None,
                                                concretization_threshold_instruction=None,
                                                cooldown_symbolic_stop=2,
                                                cooldown_unsupported_stop=2,
                                                cooldown_nonunicorn_blocks=100,
                                                cooldown_stop_point=1, max_steps=1000000)
    Bases: SimStatePlugin
    setup the unicorn engine for a state

```

```
UC_CONFIG = {}
```

```
__init__(syscall_hooks=None, cache_key=None, unicount=None, symbolic_var_counts=None,
         symbolic_inst_counts=None, concretized_ast=None, always_concretize=None,
         never_concretize=None, concretize_at=None, concretization_threshold_memory=None,
         concretization_threshold_registers=None, concretization_threshold_instruction=None,
         cooldown_symbolic_stop=2, cooldown_unsupported_stop=2, cooldown_nonunicorn_blocks=100,
         cooldown_stop_point=1, max_steps=1000000)
```

Initializes the Unicorn plugin for angr. This plugin handles communication with UnicornEngine.

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
merge(others, merge_conditions, common_ancestor=None)
```

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

set_state(*state*)

Sets a new state (for example, if the state has been branched)

property uc**static delete_uc**()**set_last_block_details**(*details*)**set_stops**(*stop_points*)**set_tracking**(*track_bbbs*, *track_stack*)**hook**()**uncache_region**(*addr*, *length*)**clear_page_cache**()**setup**(*syscall_data=None*, *fd_bytes=None*)**start**(*step=None*)**get_recent_bbl_addrs**()**get_stop_details**()**finish**(*succ_state*)**destroy**(*succ_state*)**set_regs**()

setting unicorn registers

setup_flags()**setup_gdt**(*fs*, *gs*)**read_msr**(*msr=3221225728*)**write_msr**(*val*, *msr=3221225728*)

get_regs(succ_state)

loading registers from unicorn. If succ_state is not None, update it instead of self.state. Needed when handling symbolic exits in native interface

state: `angr.SimState`

class `angr.state_plugins.loop_data.SimStateLoopData`(back_edge_trip_counts=None,
header_trip_counts=None, current_loop=None)

Bases: `SimStatePlugin`

This class keeps track of loop-related information for states. Note that we have 2 counters for loop iterations (trip counts): the first recording the number of times one of the back edges (or continue edges) of a loop is taken, whereas the second recording the number of times the loop header (or loop entry) is executed. These 2 counters may differ since compilers usually optimize loops hence completely change the loop structure at the binary level. This is supposed to be used with *LoopSeer* exploration technique, which monitors loop execution. For the moment, the only thing we want to analyze is loop trip counts, but nothing prevents us from extending this plugin for other loop analyses.

__init__(back_edge_trip_counts=None, header_trip_counts=None, current_loop=None)

Parameters

- **back_edge_trip_counts** – Dictionary that stores back edge based trip counts for each loop. Keys are address of loop headers.
- **header_trip_counts** – Dictionary that stores header based trip counts for each loop. Keys are address of loop headers.
- **current_loop** – List of currently running loops. Each element is a tuple (loop object, list of loop exits).

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, merge_conditions can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.state_plugins.concrete.Concrete(segment_registers_initialized=False,
                                           segment_registers_callback_initialized=False,
                                           whitelist=None, fs_register_bp=None,
                                           already_sync_objects_addresses=None)
```

Bases: `SimStatePlugin`

```
__init__(segment_registers_initialized=False, segment_registers_callback_initialized=False,
         whitelist=None, fs_register_bp=None, already_sync_objects_addresses=None)
```

copy(*_memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*_others*, *_merge_conditions*, *_common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` **others** and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both **others** and **common_ancestor** before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*_others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

set_state(*state*)

Sets a new state (for example, if the state has been branched)

sync()

Handle the switch between the concrete execution and angr. This method takes care of: 1- Synchronize registers. 2- Set a concrete target to the memory backer so the memory reads are redirected in the concrete process memory. 3- If possible restore the SimProcedures with the real addresses inside the concrete process. 4- Set an inspect point to sync the segments register as soon as they are read during the symbolic execution. 5- Flush all the pages loaded until now.

Returns

state: `angr.SimState`

class `angr.state_plugins.javavm_classloader.SimJavaVmClassLoader`(*initialized_classes=None*)

Bases: `SimStatePlugin`

JavaVM Classloader is used as an interface for resolving and initializing Java classes.

__init__(*initialized_classes=None*)

get_class(*class_name*, *init_class=False*, *step_func=None*)

Get a class descriptor for the class.

Parameters

- **class_name** (*str*) – Name of class.
- **init_class** (*bool*) – Whether the class initializer <clinit> should be executed.
- **step_func** (*func*) – Callback function executed at every step of the simulation manager during the execution of the main <clinit> method

get_superclass(*class_*)

Get the superclass of the class.

get_class_hierarchy(*base_class*)

Walks up the class hierarchy and returns a list of all classes between base class (inclusive) and `java.lang.Object` (exclusive).

is_class_initialized(*class_*)

Indicates whether the classes initializing method <clinit> was already executed on the state.

init_class(*class_*, *step_func=None*)

This method simulates the loading of a class by the JVM, during which parts of the class (e.g. static fields) are initialized. For this, we run the class initializer method <clinit> (if available) and update the state accordingly.

Note: Initialization is skipped, if the class has already been
initialized (or if it's not loaded in CLE).

property initialized_classes

List of all initialized classes.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (id(obj)) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from merge should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.state_plugins.jni_references.SimStateJNIReferences`(*local_refs=None*,
global_refs=None)

Bases: `SimStatePlugin`

Management of the mapping between opaque JNI references and the corresponding Java objects.

__init__(*local_refs=None*, *global_refs=None*)

lookup(*opaque_ref*)

Lookups the object that was used for creating the reference.

create_new_reference(*obj*, *global_ref=False*)

Create a new reference that maps to the given object.

Parameters

- **obj** – Object which gets referenced.
- **global_ref** (*bool*) – Whether a local or global reference is created.

clear_local_references()

Clear all local references.

delete_reference(*opaque_ref*, *global_ref=False*)

Delete the stored mapping of a reference.

Parameters

- **opaque_ref** – Reference which should be removed.
- **global_ref** (*bool*) – Whether *opaque_ref* is a local or global reference.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` `others` and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.state_plugins.heap.heap_base.SimHeapBase(heap_base=None, heap_size=None)`

Bases: `SimStatePlugin`

This is the base heap class that all heap implementations should subclass. It defines a few handlers for common heap functions (the libc memory management functions). Heap implementations are expected to override these functions regardless of whether they implement the `SimHeapLibc` interface. For an example, see the `SimHeapBrk` implementation, which is based on the original libc `SimProcedure` implementations.

Variables

- **heap_base** – the address of the base of the heap in memory
- **heap_size** – the total size of the main memory region managed by the heap in memory

- **mmap_base** – the address of the region from which large mmap allocations will be made

__init__(*heap_base=None, heap_size=None*)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

init_state()

Use this function to perform any initialization on the state at plugin-add time

state: `angr.SimState`

class `angr.state_plugins.heap.heap_brk.SimHeapBrk`(*heap_base=None, heap_size=None*)

Bases: `SimHeapBase`

`SimHeapBrk` represents a trivial heap implementation based on the Unix *brk* system call. This type of heap stores virtually no metadata, so it is up to the user to determine when it is safe to release memory. This also means that it does not properly support standard heap operations like *realloc*.

This heap implementation is a holdover from before any more proper implementations were modelled. At the time, various libc (or win32) `SimProcedures` handled the heap in the same way that this plugin does now. To make future heap implementations plug-and-playable, they should implement the necessary logic themselves, and dependent `SimProcedures` should invoke a method by the same name as theirs (prefixed with an underscore) upon the heap plugin. Depending on the heap implementation, if the method is not supported, an error should be raised.

Out of consideration for the original way the heap was handled, this plugin implements functionality for all relevant `SimProcedures` (even those that would not normally be supported together in a single heap implementation).

Variables

heap_location – the address of the top of the heap, bounding the allocations made starting from *heap_base*

__init__(*heap_base=None, heap_size=None*)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

allocate(*sim_size*)

The actual allocation primitive for this heap implementation. Increases the position of the break to allocate space. Has no guards against the heap growing too large.

Parameters

sim_size – a size specifying how much to increase the break pointer by

Returns

a pointer to the previous break position, above which there is now allocated space

release(*sim_size*)

The memory release primitive for this heap implementation. Decreases the position of the break to deallocate space. Guards against releasing beyond the initial heap base.

Parameters

sim_size – a size specifying how much to decrease the break pointer by (may be symbolic or not)

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` *others* and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.state_plugins.heap.heap_freelist.Chunk`(*base, sim_state*)

Bases: `object`

The sort of chunk as would typically be found in a freelist-style heap implementation. Provides a representation of a chunk via a view into the memory plugin. Chunks may be adjacent, in different senses, to as many as four other chunks. For any given chunk, two of these chunks are adjacent to it in memory, and are referred to as the “previous” and “next” chunks throughout this implementation. For any given free chunk, there may also be two significant chunks that are adjacent to it in some linked list of free chunks. These chunks are referred to the “backward” and “forward” chunks relative to the chunk in question.

Variables

- **base** – the location of the base of the chunk in memory
- **state** – the program state that the chunk is resident in

__init__(*base, sim_state*)

get_size()

Returns the actual size of a chunk (as opposed to the entire size field, which may include some flags).

get_data_size()

Returns the size of the data portion of a chunk.

set_size(*size*)

Sets the size of the chunk, preserving any flags.

data_ptr()

Returns the address of the payload of the chunk.

is_free()

Returns a concrete determination as to whether the chunk is free.

next_chunk()

Returns the chunk immediately following (and adjacent to) this one.

prev_chunk()

Returns the chunk immediately prior (and adjacent) to this one.

fwd_chunk()

Returns the chunk following this chunk in the list of free chunks.

set_fwd_chunk(*fwd*)

Sets the chunk following this chunk in the list of free chunks.

Parameters

fwd – the chunk to follow this chunk in the list of free chunks

bck_chunk()

Returns the chunk backward from this chunk in the list of free chunks.

set_bck_chunk(*bck*)

Sets the chunk backward from this chunk in the list of free chunks.

Parameters

bck – the chunk to precede this chunk in the list of free chunks

class `angr.state_plugins.heap.heap_freelist.SimHeapFreelist`(*heap_base=None, heap_size=None*)

Bases: [*SimHeapLibc*](#)

A freelist-style heap implementation. Distinguishing features of such heaps include chunks containing heap metadata in addition to user data and at least (but often more than) one linked list of free chunks.

chunks()

Returns an iterator over all the chunks in the heap.

allocated_chunks()

Returns an iterator over all the allocated chunks in the heap.

free_chunks()

Returns an iterator over all the free chunks in the heap.

chunk_from_mem(*ptr*)

Given a pointer to a user payload, return the chunk associated with that payload.

Parameters

ptr – a pointer to the base of a user payload in the heap

Returns

the associated heap chunk

print_heap_state()

print_all_chunks()

state: `angr.SimState`

class `angr.state_plugins.heap.heap_libc.SimHeapLibc`(*heap_base=None, heap_size=None*)

Bases: [*SimHeapBase*](#)

A class of heap that implements the major libc heap management functions.

malloc(*sim_size*)

A somewhat faithful implementation of libc *malloc*.

Parameters

sim_size – the amount of memory (in bytes) to be allocated

Returns

the address of the allocation, or a NULL pointer if the allocation failed

free(*ptr*)

A somewhat faithful implementation of libc *free*.

Parameters

ptr – the location in memory to be freed

calloc(*sim_nmemb*, *sim_size*)

A somewhat faithful implementation of libc *calloc*.

Parameters

- **sim_nmemb** – the number of elements to allocated
- **sim_size** – the size of each element (in bytes)

Returns

the address of the allocation, or a NULL pointer if the allocation failed

realloc(*ptr*, *size*)

A somewhat faithful implementation of libc *realloc*.

Parameters

- **ptr** – the location in memory to be reallocated
- **size** – the new size desired for the allocation

Returns

the address of the allocation, or a NULL pointer if the allocation was freed or if no new allocation was made

state: `angr.SimState`

`angr.state_plugins.heap.heap_ptmalloc.silence_logger()`

`angr.state_plugins.heap.heap_ptmalloc.unsilence_logger(level)`

class `angr.state_plugins.heap.heap_ptmalloc.PTChunk(base, sim_state, heap=None)`

Bases: `Chunk`

A chunk, inspired by the implementation of chunks in ptmalloc. Provides a representation of a chunk via a view into the memory plugin. For the chunk definitions and docs that this was loosely based off of, see glibc malloc/malloc.c, line 1033, as of commit 5a580643111ef6081be7b4c7bd1997a5447c903f. Alternatively, take the following link. <https://sourceware.org/git/?p=glibc.git;a=blob;f=malloc/malloc.c;h=67cdfd0ad2f003964cd0f7dfe3bcd85ca98528a7;hb=5a580643111ef6081be7b4c7bd1997a5447c903f#l1033>

Variables

- **base** – the location of the base of the chunk in memory
- **state** – the program state that the chunk is resident in
- **heap** – the heap plugin that the chunk is managed by

__init__(*base*, *sim_state*, *heap*=None)

get_size()

Returns the actual size of a chunk (as opposed to the entire size field, which may include some flags).

get_data_size()

Returns the size of the data portion of a chunk.

set_size(*size*, *is_free*=None)

Use this to set the size on a chunk. When the chunk is new (such as when a free chunk is shrunk to form an allocated chunk and a remainder free chunk) it is recommended that the *is_free* hint be used since setting the size depends on the chunk's freeness, and vice versa.

Parameters

- **size** – size of the chunk
- **is_free** – boolean indicating the chunk's freeness

set_prev_freeness(*is_free*)

Sets (or unsets) the flag controlling whether the previous chunk is free.

Parameters

- **is_free** – if True, sets the previous chunk to be free; if False, sets it to be allocated

is_prev_free()

Returns a concrete state of the flag indicating whether the previous chunk is free or not. Issues a warning if that flag is symbolic and has multiple solutions, and then assumes that the previous chunk is free.

Returns

True if the previous chunk is free; False otherwise

prev_size()

Returns the size of the previous chunk, masking off what would be the flag bits if it were in the actual size field. Performs NO CHECKING to determine whether the previous chunk size is valid (for example, when the previous chunk is not free, its size cannot be determined).

is_free()

Returns a concrete determination as to whether the chunk is free.

data_ptr()

Returns the address of the payload of the chunk.

next_chunk()

Returns the chunk immediately following (and adjacent to) this one, if it exists.

Returns

The following chunk, or None if applicable

prev_chunk()

Returns the chunk immediately prior (and adjacent) to this one, if that chunk is free. If the prior chunk is not free, then its base cannot be located and this method raises an error.

Returns

If possible, the previous chunk; otherwise, raises an error

fwd_chunk()

Returns the chunk following this chunk in the list of free chunks. If this chunk is not free, then it resides in no such list and this method raises an error.

Returns

If possible, the forward chunk; otherwise, raises an error

set_fwd_chunk(*fwd*)

Sets the chunk following this chunk in the list of free chunks.

Parameters

- **fwd** – the chunk to follow this chunk in the list of free chunks

bck_chunk()

Returns the chunk backward from this chunk in the list of free chunks. If this chunk is not free, then it resides in no such list and this method raises an error.

Returns

If possible, the backward chunk; otherwise, raises an error

set_bck_chunk(*bck*)

Sets the chunk backward from this chunk in the list of free chunks.

Parameters

bck – the chunk to precede this chunk in the list of free chunks

```
class angr.state_plugins.heap.heap_ptmalloc.PTChunkIterator(chunk, cond=<function
PTChunkIterator.<lambda>>>)
```

Bases: `object`

```
__init__(chunk, cond=<function PTChunkIterator.<lambda>>>)
```

```
class angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc(heap_base=None, heap_size=None)
```

Bases: `SimHeapFreelist`

A freelist-style heap implementation inspired by ptmalloc. The chunks used by this heap contain heap metadata in addition to user data. While the real-world ptmalloc is implemented using multiple lists of free chunks (corresponding to their different sizes), this more basic model uses a single list of chunks and searches for free chunks using a first-fit algorithm.

NOTE: The plugin must be registered using `register_plugin` with name `heap` in order to function properly.

Variables

- **heap_base** – the address of the base of the heap in memory
- **heap_size** – the total size of the main memory region managed by the heap in memory
- **mmap_base** – the address of the region from which large mmap allocations will be made
- **free_head_chunk** – the head of the linked list of free chunks in the heap

```
__init__(heap_base=None, heap_size=None)
```

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

chunks()

Returns an iterator over all the chunks in the heap.

allocated_chunks()

Returns an iterator over all the allocated chunks in the heap.

free_chunks()

Returns an iterator over all the free chunks in the heap.

chunk_from_mem(ptr)

Given a pointer to a user payload, return the base of the chunk associated with that payload (i.e. the chunk pointer). Returns None if ptr is null.

Parameters

ptr – a pointer to the base of a user payload in the heap

Returns

a pointer to the base of the associated heap chunk, or None if ptr is null

malloc(sim_size)

A somewhat faithful implementation of libc *malloc*.

Parameters

sim_size – the amount of memory (in bytes) to be allocated

Returns

the address of the allocation, or a NULL pointer if the allocation failed

free(ptr)

A somewhat faithful implementation of libc *free*.

Parameters

ptr – the location in memory to be freed

calloc(sim_nmemb, sim_size)

A somewhat faithful implementation of libc *calloc*.

Parameters

- **sim_nmemb** – the number of elements to allocated
- **sim_size** – the size of each element (in bytes)

Returns

the address of the allocation, or a NULL pointer if the allocation failed

realloc(ptr, size)

A somewhat faithful implementation of libc *realloc*.

Parameters

- **ptr** – the location in memory to be reallocated
- **size** – the new size desired for the allocation

Returns

the address of the allocation, or a NULL pointer if the allocation was freed or if no new allocation was made

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` `others` and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`init_state()`

Use this function to perform any initialization on the state at plugin-add time

state: `angr.SimState`

`angr.state_plugins.heap.utils.concretize(x, solver, sym_handler)`

For now a lot of naive concretization is done when handling heap metadata to keep things manageable. This idiom showed up a lot as a result, so to reduce code repetition this function uses a callback to handle the one or two operations that varied across invocations.

Parameters

- **x** – the item to be concretized
- **solver** – the solver to evaluate the item with

- **sym_handler** – the handler to be used when the item may take on more than one value

Returns

a concrete value for the item

class `angr.state_plugins.symbolizer.SimSymbolizer`

Bases: `SimStatePlugin`

The symbolizer state plugin ensures that pointers that are stored in memory are symbolic. This allows for the tracking of and reasoning over these pointers (for example, to reason about memory disclosure).

__init__()

init_state()

Use this function to perform any initialization on the state at plugin-add time

set_symbolization_for_all_pages()

Sets the symbolizer to symbolize pointers to all pages as they are written to memory..

set_symbolized_target_range(*base*, *length*)

All pointers to the target range will be symbolized as they are written to memory.

Due to optimizations, the `_pages_` containing this range will be set as symbolization targets, not just the range itself.

resymbolize()

Re-symbolizes all pointers in memory. This can be called to symbolize any pointers to target regions that were written (and not mangled beyond recognition) before symbolization was set.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

class `angr.state_plugins.debug_variables.SimDebugVariable`(*state*, *addr*, *var_type*)

Bases: `object`

A `SimDebugVariable` will get dynamically created when querying for variable in a state with the `SimDebugVariablePlugin`. It features a link to the state, an address and a type.

Parameters

- **state** (`SimState`) –
- **var_type** (`VariableType`) –

__init__(*state*, *addr*, *var_type*)

Parameters

- **state** (`SimState`) –

```

    • var_type (VariableType) –
static from_cle_variable(state, cle_variable, dwarf_cfa)

    Return type
    SimDebugVariable

    Parameters
    • state (SimState) –
    • cle_variable (Variable) –

property mem_untyped: SimMemView
property mem: SimMemView
property string: SimMemView
with_type(sim_type)

    Return type
    SimMemView

    Parameters
    sim_type (SimType) –

property resolvable
property resolved
property concrete
store(value)
property deref: SimDebugVariable
array(i)

    Return type
    SimDebugVariable

member(member_name)

    Return type
    SimDebugVariable

    Parameters
    member_name (str) –

class angr.state_plugins.debug_variables.SimDebugVariablePlugin
    Bases: SimStatePlugin

```

This is the plugin you'll use to interact with (global/local) program variables. These variables have a name and a visibility scope which depends on the pc address of the state. With this plugin, you can access/modify the value of such variable or find its memory address. For creating program variables, or for importing them from cle, see the knowledge plugin `debug_variables`. Run `p.kb.dvars.load_from_dwarf()` before using this plugin.

Example

```
>>> p = angr.Project("various_variables", load_debug_info=True)
>>> p.kb.dvars.load_from_dwarf()
>>> state = # navigate to the state you want
>>> state.dvars.get_variable("pointer2").deref.mem
<int (32 bits) <BV32 0x1> at 0x404020>
```

get_variable(var_name)

Returns the visible variable (if any) with name var_name based on the current state.ip.

Return type

SimDebugVariable

Parameters

var_name (*str*) –

property dwarf_cfa

Returns the current cfa computation. Set this property to the correct value if needed.

property dwarf_cfa_approx

state: *angr.SimState*

10.4 Storage

class *angr.state_plugins.view.SimRegNameView*

Bases: *SimStatePlugin*

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with *SimStatePlugin.memo*

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (id(obj)) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by *state.merge()* after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n+1* merge conditions, since the first condition corresponds to self. To match elements up to conditions, say *zip([self] + others, merge_conditions)*

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`get(reg_name)`

state: `angr.SimState`

class `angr.state_plugins.view.SimMemView`(*ty=None, addr=None, state=None*)

Bases: `SimStatePlugin`

This is a convenient interface with which you can access a program’s memory.

The interface works like this:

- You first use [array index notation] to specify the address you’d like to load from
- If at that address is a pointer, you may access the `deref` property to return a `SimMemView` at the address present in memory.
- You then specify a type for the data by simply accessing a property of that name. For a list of supported types, look at `state.mem.types`.

- You can then *refine* the type. Any type may support any refinement it likes. Right now the only refinements supported are that you may access any member of a struct by its member name, and you may index into a string or array to access that element.
- If the address you specified initially points to an array of that type, you can say `.array(n)` to view the data as an array of *n* elements.
- Finally, extract the structured data with `.resolved` or `.concrete`. `.resolved` will return bitvector values, while `.concrete` will return integer, string, array, etc values, whatever best represents the data.
- Alternately, you may store a value to memory, by assigning to the chain of properties that you've constructed. Note that because of the way python works, `x = s.mem[...].prop`; `x = val` will NOT work, you must say `s.mem[...].prop = val`.

For example:

```
>>> s.mem[0x601048].long
<long (64 bits) <BV64 0x4008d0> at 0x601048>
>>> s.mem[0x601048].long.resolved
<BV64 0x4008d0>
>>> s.mem[0x601048].deref
<<untyped> <unresolvable> at 0x4008d0>
>>> s.mem[0x601048].deref.string.concrete
'SOSNEAKY'
```

Parameters

state (`SimState`) –

__init__ (`ty=None`, `addr=None`, `state=None`)

set_state (`state`)

Sets a new state (for example, if the state has been branched)

```

types = {'CharT': char, 'FILE_t': struct FILE_t, '_Bool': bool, '_ENTRY': struct
_ENTRY, '_IO_codecvt': struct _IO_codecvt, '_IO_iconv_t': struct _IO_iconv_t,
'_IO_lock_t': struct pthread_mutex_t, '_IO_marker': struct _IO_marker,
'_IO_wide_data': struct _IO_wide_data, '__clock_t': uint32_t, '__dev_t':
uint64_t, '__gid_t': unsigned int, '__ino64_t': unsigned long long, '__ino_t':
unsigned long, '__int128': int128_t, '__int256': int256_t, '__mbstate_t': struct
__mbstate_t, '__mode_t': unsigned int, '__nlink_t': unsigned int, '__off64_t':
long long, '__off_t': long, '__pid_t': int, '__suseconds_t': int64_t, '__time_t':
long, '__uid_t': unsigned int, '_obstack_chunk': struct _obstack_chunk, 'aiocb':
struct aiocb, 'aiocb64': struct aiocb64, 'aioinit': struct aioinit, 'argp':
struct argp, 'argp_child': struct argp_child, 'argp_option': struct argp_option,
'argp_parser_t': (int, char*, struct argp_state*) -> int, 'argp_state': struct
argp_state, 'basic_string': string_t, 'bool': bool, 'byte': uint8_t, 'cc_t':
char, 'char': char, 'clock_t': uint32_t, 'crypt_data': struct crypt_data,
'dirent': struct dirent, 'dirent64': struct dirent64, 'double': double,
'drand48_data': struct <anon>, 'dword': uint32_t, 'error_t': int, 'exit_status':
struct exit_status, 'float': float, 'fstab': struct fstab, 'group': struct group,
'hostent': struct hostent, 'hsearch_data': struct hsearch_data, 'if_nameindex':
struct if_nameindex, 'in_addr': struct in_addr, 'in_port_t': uint16_t, 'ino64_t':
unsigned long long, 'ino_t': unsigned long, 'int': int, 'int16_t': int16_t,
'int32_t': int32_t, 'int64_t': int64_t, 'int8_t': int8_t, 'iovec': struct
<anon>, 'itimerval': struct itimerval, 'lconv': struct lconv, 'long': long, 'long
double': double, 'long int': long, 'long long': long long, 'long long int': long
long, 'long signed': long, 'long unsigned int': unsigned long, 'mallinfo': struct
mallinfo, 'mallinfo2': struct mallinfo2, 'mntent': struct mntent, 'netent':
struct netent, 'ntptimeval': struct ntptimeval, 'obstack': struct obstack,
'off64_t': long long, 'off_t': long, 'option': struct option, 'passwd': struct
passwd, 'pid_t': int, 'printf_info': struct printf_info, 'protoent': struct
protoent, 'ptrdiff_t': long, 'qword': uint64_t, 'random_data': struct <anon>,
'rlim64_t': uint64_t, 'rlim_t': unsigned long, 'rlimit': struct rlimit,
'rlimit64': struct rlimit64, 'rusage': struct rusage, 'sa_family_t': unsigned
short, 'sched_param': struct sched_param, 'sembuf': struct sembuf, 'servent':
struct servent, 'sgttyb': struct sgttyb, 'short': short, 'short int': short,
'sigevent': struct sigevent, 'signed': int, 'signed char': char, 'signed int':
int, 'signed long': long, 'signed long int': long, 'signed long long': long long,
'signed long long int': long long, 'signed short': short, 'signed short int':
short, 'sigstack': struct sigstack, 'sigval': union sigval { sival_int int;
sival_ptr void* }, 'size_t': size_t, 'sockaddr': struct sockaddr, 'sockaddr_in':
struct sockaddr_in, 'speed_t': long, 'ssize': size_t, 'ssize_t': size_t, 'stat':
struct stat, 'stat64': struct stat64, 'string': string_t, 'struct iovec': struct
iovec, 'struct timespec': struct timespec, 'struct timeval': struct timeval,
'tcflag_t': unsigned long, 'termios': struct termios, 'time_t': long, 'timespec':
struct timespec, 'timeval': struct timeval, 'timex': struct timex, 'timezone':
struct timezone, 'tm': struct tm, 'tms': struct tms, 'uint16_t': uint16_t,
'uint32_t': uint32_t, 'uint64_t': uint64_t, 'uint8_t': uint8_t, 'uintptr_t':
unsigned long, 'unsigned': unsigned int, 'unsigned __int128': uint128_t, 'unsigned
__int256': uint256_t, 'unsigned char': char, 'unsigned int': unsigned int,
'unsigned long': unsigned long, 'unsigned long int': unsigned long, 'unsigned long
long': unsigned long long, 'unsigned long long int': unsigned long long, 'unsigned
short': unsigned short, 'unsigned short int': unsigned short, 'utimbuf': struct
utimbuf, 'utmp': struct utmp, 'utmpx': struct utmx, 'utsname': struct utsname,
'va_list': struct va_list[1], 'void': void, 'vtimes': struct vtimes, 'wchar_t':
short, 'winsize': struct winsize, 'word': uint16_t, 'wstring': wstring_t}

```

state: `angr.SimState = None`

struct: `StructMode`

with_type(*sim_type*)

Returns a copy of the `SimMemView` with a type.

Parameters

sim_type (*SimType*) – The new type.

Return type

SimMemView

Returns

The typed `SimMemView` copy.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

property resolvable

property resolved

property concrete

property deref: `SimMemView`

array(*n*)

Return type

`SimMemView`

member(*member_name*)

If self is a struct and `member_name` is a member of the struct, return that member element. Otherwise raise an exception.

Return type

`SimMemView`

Parameters

member_name (*str*) –

store(*value*)

class `angr.state_plugins.view.StructMode(view)`

Bases: `object`

`__init__`(*view*)

class `angr.storage.file.Flags`

Bases: `object`

`O_RDONLY` = 0

`O_WRONLY` = 1


```

O_RDWR = 2
O_ACCMODE = 3
O_APPEND = 1024
O_ASYNC = 8192
O_CLOEXEC = 524288
O_CREAT = 64
O_DIRECT = 16384
O_DIRECTORY = 65536
O_DSYNC = 4096
O_EXCL = 128
O_LARGEFILE = 32768
O_NOATIME = 262144
O_NOCTTY = 256
O_NOFOLLOW = 131072
O_NONBLOCK = 2048
O_NDELAY = 2048
O_PATH = 2097152
O_SYNC = 1052672
O_TMPFILE = 4259840
O_TRUNC = 512

```

```

class angr.storage.file.SimFileBase(name=None, writable=True, ident=None, concrete=False,
                                     file_exists=True, **kwargs)

```

Bases: [SimStatePlugin](#)

SimFiles are the storage mechanisms used by SimFileDescriptors.

Different types of SimFiles can have drastically different interfaces, and as a result there's not much that can be specified on this base class. All the read and write methods take a `pos` argument, which may have different semantics per-class. `0` will always be a valid position to use, though, and the next position you should use is part of the return tuple.

Some simfiles are “streams”, meaning that the position that reads come from is determined not by the position you pass in (it will in fact be ignored), but by an internal variable. This is stored as `.pos` if you care to read it. Don't write to it. The same lack-of-semantics applies to this field as well.

Variables

- **name** – The name of the file. Purely for cosmetic purposes
- **ident** – The identifier of the file, typically autogenerated from the name and a nonce. Purely for cosmetic purposes, but does appear in symbolic values autogenerated in the file.

- **seekable** – Bool indicating whether seek operations on this file should succeed. If this is True, then **pos** must be a number of bytes from the start of the file.
- **writable** – Bool indicating whether writing to this file is allowed.
- **pos** – If the file is a stream, this will be the current position. Otherwise, None.
- **concrete** – Whether or not this file contains mostly concrete data. Will be used by some SimProcedures to choose how to handle variable-length operations like fgets.
- **file_exists** – Set to False, if file does not exist, set to a claripy Bool if unknown, default True.

seekable = False

pos = None

__init__(*name=None, writable=True, ident=None, concrete=False, file_exists=True, **kwargs*)

static make_ident(*name*)

concretize(***kwargs*)

Return a concretization of the contents of the file. The type of the return value of this method will vary depending on which kind of SimFile you're using.

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(*pos, data, size=None, **kwargs*)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

property size

The number of data bytes stored by the file at present. May be a symbolic value.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.file.SimFile(name=None, content=None, size=None, has_end=None, seekable=True,
                               writable=True, ident=None, concrete=None, **kwargs)
```

Bases: `SimFileBase`, `DefaultMemory`

The normal `SimFile` is meant to model files on disk. It subclasses `SimSymbolicMemory` so loads and stores to/from it are very simple.

Parameters

- **name** – The name of the file
- **content** – Optional initial content for the file as a string or bitvector
- **size** – Optional size of the file. If content is not specified, it defaults to zero
- **has_end** – Whether the size boundary is treated as the end of the file or a frontier at which new content will be generated. If unspecified, will pick its value based on `options.FILES_HAVE_EOF`. Another caveat is that if the size is also unspecified this value will default to `False`.
- **seekable** – Optional bool indicating whether seek operations on this file should succeed, default `True`.
- **writable** – Whether writing to this file is allowed
- **concrete** – Whether or not this file contains mostly concrete data. Will be used by some `SimProcedures` to choose how to handle variable-length operations like `fgets`.

Variables

has_end – Whether this file has an EOF

```
__init__(name=None, content=None, size=None, has_end=None, seekable=True, writable=True,
         ident=None, concrete=None, **kwargs)
```

property category

reg, mem, or file.

Type

Return the category of this `SimMemory` instance. It can be one of the three following categories

set_state(state)

Sets a new state (for example, if the state has been branched)

property size

The number of data bytes stored by the file at present. May be a symbolic value.

concretize(**kwargs)

Return a concretization of the contents of the file, as a flat bytestring.

read(pos, size, **kwargs)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(*pos*, *data*, *size=None*, *events=True*, ***kwargs*)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen()`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimFileStream`(*name=None, content=None, pos=0, **kwargs*)

Bases: `SimFile`

A specialized `SimFile` that uses a flat memory backing, but functions as a stream, tracking its position internally.

The `pos` argument to the `read` and `write` methods will be ignored, and will return `None`. Instead, there is an attribute `pos` on the file itself, which will give you what you want.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **pos** – The initial position of the file, default zero
- **kwargs** – Any other keyword arguments will go on to the `SimFile` constructor.

Variables

pos – The current position in the file.

__init__(*name=None, content=None, pos=0, **kwargs*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(_, data, size=None, **kwargs)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimPackets`(*name*, *write_mode=None*, *content=None*, *writable=True*, *ident=None*, ***kwargs*)

Bases: `SimFileBase`

The `SimPackets` is meant to model inputs whose content is delivered a series of asynchronous chunks. The data is stored as a list of read or write results. For symbolic sizes, `state.libc.max_packet_size` will be respected. If the `SHORT_READS` option is enabled, reads will return a symbolic size constrained to be less than or equal to the requested size.

A `SimPackets` cannot be used for both reading and writing - for socket objects that can be both read and written to you should use a file descriptor to multiplex the read and write operations into two separate file storage mechanisms.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **write_mode** – Whether this file is opened in read or write mode. If this is unspecified it will be autodetected.
- **content** – Some initial content to use for the file. Can be a list of bytestrings or a list of tuples of content ASTs and size ASTs.

Variables

- **write_mode** – See the eponymous parameter
- **content** – A list of packets, as tuples of content ASTs and size ASTs.

__init__(*name*, *write_mode=None*, *content=None*, *writable=True*, *ident=None*, ***kwargs*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

property size

The number of data bytes stored by the file at present. May be a symbolic value.

concretize(***kwargs*)

Returns a list of the packets read or written as bytestrings.

read(*pos*, *size*, ***kwargs*)

Read a packet from the stream.

Parameters

- **pos** (*int*) – The packet number to read from the sequence of the stream. May be None to append to the stream.
- **size** – The size to read. May be symbolic.
- **short_reads** – Whether to replace the size with a symbolic value constrained to less than or equal to the original size. If unspecified, will be chosen based on the state option.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read) and the actual size of the read.

write(*pos*, *data*, *size=None*, *events=True*, ***kwargs*)

Write a packet to the stream.

Parameters

- **pos** (*int*) – The packet number to write in the sequence of the stream. May be None to append to the stream.
- **data** – The data to write, as a string or bitvector.
- **size** – The optional size to write. May be symbolic; must be constrained to at most the size of data.

Returns

The next packet to use after this

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
```

(continues on next page)

(continued from previous page)

```
common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen()

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimPacketsStream(name, pos=0, **kwargs)`

Bases: `SimPackets`

A specialized `SimPackets` that tracks its position internally.

The `pos` argument to the `read` and `write` methods will be ignored, and will return `None`. Instead, there is an attribute `pos` on the file itself, which will give you what you want.

Parameters

- **name** – The name of the file, for cosmetic purposes
- **pos** – The initial position of the file, default zero
- **kwargs** – Any other keyword arguments will go on to the `SimPackets` constructor.

Variables

pos – The current position in the file.

__init__(`name, pos=0, **kwargs`)

read(*pos*, *size*, ***kwargs*)

Read a packet from the stream.

Parameters

- **pos** (*int*) – The packet number to read from the sequence of the stream. May be None to append to the stream.
- **size** – The size to read. May be symbolic.
- **short_reads** – Whether to replace the size with a symbolic value constrained to less than or equal to the original size. If unspecified, will be chosen based on the state option.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read) and the actual size of the read.

write(_, *data*, *size=None*, ***kwargs*)

Write a packet to the stream.

Parameters

- **pos** (*int*) – The packet number to write in the sequence of the stream. May be None to append to the stream.
- **data** – The data to write, as a string or bitvector.
- **size** – The optional size to write. May be symbolic; must be constrained to at most the size of data.

Returns

The next packet to use after this

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```

self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)

```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimFileDescriptorBase`

Bases: `SimStatePlugin`

The base class for implementations of POSIX file descriptors.

All file descriptors should respect the `CONCRETIZE_SYMBOLIC_{READ,WRITE}_SIZES` state options.

read(*pos*, *size*, ***kwargs*)

Reads some data from the file, storing it into memory.

Parameters

- **pos** – The address to read data from file
- **size** – The requested length of the read

Returns

The real length of the read

write(*pos*, *size*, ***kwargs*)

Writes some data, loaded from the state, into the file.

Parameters

- **pos** – The address to read the data to write from in memory
- **size** – The requested size of the write

Returns

The real length of the write

read_data(*size*, ***kwargs*)

Reads some data from the file, returning the data.

Parameters

size – The requested length of the read

Returns

A tuple of the data read and the real length of the read

write_data(*data*, *size=None*, ***kwargs*)

Write some data, provided as an argument into the file.

Parameters

- **data** – A bitvector to write into the file
- **size** – The requested size of the write (may be symbolic)

Returns

The real length of the write

seek(*offset*, *whence='start'*)

Seek the file descriptor to a different position in the file.

Parameters

- **offset** – The offset to seek to, interpreted according to whence
- **whence** – What the offset is relative to; one of the strings “start”, “current”, or “end”

Returns

A symbolic boolean describing whether the seek succeeded or not

tell()

Return the current position, or None if the concept doesn’t make sense for the given file.

eof()

Return the EOF status. May be a symbolic boolean.

size()

Return the size of the data stored in the file in bytes, or None if the concept doesn’t make sense for the given file.

property read_storage

Return the SimFile backing reads from this fd

property write_storage

Return the SimFile backing writes to this fd

property read_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

property write_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

concretize(***kwargs*)

Return a concretization of the data in the underlying file. Has different return types to represent different data structures on a per-class basis.

Any arguments passed to this will be passed onto `state.solver.eval`.

property `file_exists`

This should be True in most cases. Only if we opened an fd of unknown existence, `ALL_FILES_EXIST` is False and `ANY_FILE_MIGHT_EXIST` is True, this is a symbolic boolean.

state: `angr.SimState`

class `angr.storage.file.SimFileDescriptor`(*simfile*, *flags=0*)

Bases: `SimFileDescriptorBase`

A simple file descriptor forwarding reads and writes to a `SimFile`. Contains information about the current opened state of the file, such as the flags or (if relevant) the current position.

Variables

- **file** – The `SimFile` described to by this descriptor
- **flags** – The mode that the file descriptor was opened with, a bitfield of flags

__init__(*simfile*, *flags=0*)

read_data(*size*, ***kwargs*)

Reads some data from the file, returning the data.

Parameters

size – The requested length of the read

Returns

A tuple of the data read and the real length of the read

write_data(*data*, *size=None*, ***kwargs*)

Write some data, provided as an argument into the file.

Parameters

- **data** – A bitvector to write into the file
- **size** – The requested size of the write (may be symbolic)

Returns

The real length of the write

seek(*offset*, *whence='start'*)

Seek the file descriptor to a different position in the file.

Parameters

- **offset** – The offset to seek to, interpreted according to *whence*
- **whence** – What the offset is relative to; one of the strings “start”, “current”, or “end”

Returns

A symbolic boolean describing whether the seek succeeded or not

eof()

Return the EOF status. May be a symbolic boolean.

tell()

Return the current position, or None if the concept doesn’t make sense for the given file.

size()

Return the size of the data stored in the file in bytes, or None if the concept doesn’t make sense for the given file.

concretize(kwargs)**

Return a concretization of the underlying file. Returns whatever format is preferred by the file.

property file_exists

This should be True in most cases. Only if we opened an fd of unknown existence, `ALL_FILES_EXIST` is False and `ANY_FILE_MIGHT_EXIST` is True, this is a symbolic boolean.

property read_storage

Return the SimFile backing reads from this fd

property write_storage

Return the SimFile backing writes to this fd

property read_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

property write_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

set_state(state)

Sets a new state (for example, if the state has been branched)

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen()`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimFileDescriptorDuplex(read_file, write_file)`

Bases: `SimFileDescriptorBase`

A file descriptor that refers to two file storage mechanisms, one to read from and one to write to. As a result, operations like `seek`, `eof`, etc no longer make sense.

Parameters

- **read_file** – The `SimFile` to read from
- **write_file** – The `SimFile` to write to

__init__(`read_file, write_file`)

read_data(`size, **kwargs`)

Reads some data from the file, returning the data.

Parameters

- **size** – The requested length of the read

Returns

A tuple of the data read and the real length of the read

write_data(*data*, *size=None*, ***kwargs*)

Write some data, provided as an argument into the file.

Parameters

- **data** – A bitvector to write into the file
- **size** – The requested size of the write (may be symbolic)

Returns

The real length of the write

set_state(*state*)

Sets a new state (for example, if the state has been branched)

eof()

Return the EOF status. May be a symbolic boolean.

tell()

Return the current position, or None if the concept doesn't make sense for the given file.

seek(*offset*, *whence='start'*)

Seek the file descriptor to a different position in the file.

Parameters

- **offset** – The offset to seek to, interpreted according to whence
- **whence** – What the offset is relative to; one of the strings “start”, “current”, or “end”

Returns

A symbolic boolean describing whether the seek succeeded or not

size()

Return the size of the data stored in the file in bytes, or None if the concept doesn't make sense for the given file.

concretize(***kwargs*)

Return a concretization of the underlying files, as a tuple of (read file, write file).

property read_storage

Return the SimFile backing reads from this fd

property write_storage

Return the SimFile backing writes to this fd

property read_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

property write_pos

Return the current position of the read file pointer.

If the underlying read file is a stream, this will return the position of the stream. Otherwise, will return the position of the file descriptor in the file.

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(others, merge_conditions, common_ancestor=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, merge_conditions can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

widen(_)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from merge should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.file.SimPacketsSlots(name, read_sizes, ident=None, **kwargs)`

Bases: `SimFileBase`

`SimPacketsSlots` is the new `SimDialogue`, if you’ve ever seen that before.

The idea is that in some cases, the only thing you really care about is getting the lengths of reads right, and some of them should be short reads, and some of them should be truncated. You provide to this class a list of read lengths, and it figures out the length of each read, and delivers some content.

This class will NOT respect the position argument you pass it - this storage is not stateless.

seekable = `False`

__init__(*name, read_sizes, ident=None, **kwargs*)

concretize(***kwargs*)

Return a concretization of the contents of the file. The type of the return value of this method will vary depending on which kind of `SimFile` you’re using.

read(*pos, size, **kwargs*)

Read some data from the file.

Parameters

- **pos** – The offset in the file to read from.
- **size** – The size to read. May be symbolic.

Returns

A tuple of the data read (a bitvector of the length that is the maximum length of the read), the actual size of the read, and the new file position pointer.

write(*pos, data, size=None, **kwargs*)

Write some data to the file.

Parameters

- **pos** – The offset in the file to write to. May be ignored if the file is a stream or device.
- **data** – The data to write as a bitvector
- **size** – The optional size of the data to write. If not provided will default to the length of the data. Must be constrained to less than or equal to the size of the data.

Returns

The new file position pointer.

property size

The number of data bytes stored by the file at present. May be a symbolic value.

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you "deepen" both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen()

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`angr.storage.memory_object.obj_bit_size(o)`

class `angr.storage.memory_object.SimMemoryObject(obj, base, endness, length=None, byte_width=8)`

Bases: `object`

A `SimMemoryObject` is a reference to a byte or several bytes in a specific object in memory. It should be used only by the bottom layer of memory.

__init__(*obj, base, endness, length=None, byte_width=8*)

is_bytes

base

object

length

endness

size()

property variables

property cache_key

property symbolic

property last_addr

concrete_bytes(*offset, size*)

Return type

`Optional[bytes]`

Parameters

- **offset** (`int`) –
- **size** (`int`) –

includes(*x*)

bytes_at(*addr, length, allow_concrete=False, endness='end_BE'*)

class `angr.storage.memory_object.SimLabeledMemoryObject(obj, base, endness, length=None, byte_width=8, label=None)`

Bases: `SimMemoryObject`

```
__init__(obj, base, endness, length=None, byte_width=8, label=None)
```

label

```
angr.storage.memory_object.bv_slice(value, offset, size, rev, bw)
```

Extremely cute utility to pretend you've serialized a value to stored bytes, sliced it a la python slicing, and then deserialized those bytes to an integer again.

Parameters

- **value** (**BV**) – The bitvector to slice
- **offset** (**int**) – The byte offset from the first stored byte to slice from, or a negative offset from the end.
- **size** (**int**) – The number of bytes to return. If None, return all bytes from the offset to the end. If larger than the number of bytes from the offset to the end, return all bytes from the offset to the end.
- **rev** (**bool**) – Whether the pretend-serialization should be little-endian
- **bw** (**int**) – The byte width

Return type

BV

Returns

The new bitvector

```
class angr.storage.pcap.PCAP(path, ip_port_tup, init=True)
```

Bases: **object**

```
__init__(path, ip_port_tup, init=True)
```

```
initialize(path)
```

```
recv(length)
```

```
copy()
```

```
class angr.concretization_strategies.SimConcretizationStrategy(filter=None, exact=True)
```

Bases: **object**

Concretization strategies control the resolution of symbolic memory indices in SimuVEX. By subclassing this class and setting it as a concretization strategy (on `state.memory.read_strategies` and `state.memory.write_strategies`), SimuVEX's memory index concretization behavior can be modified.

```
__init__(filter=None, exact=True)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

```
concretize(memory, addr, **kwargs)
```

Concretizes the address into a list of values. If this strategy cannot handle this address, returns None.

copy()

Returns a copy of the strategy, if there is data that should be kept separate between states. If not, returns self.

merge(others)

Merges this strategy with others (if there is data that should be kept separate between states. If not, is a no-op.

10.5 Memory Mixins

class `angr.storage.memory_mixins.MemoryMixin`(*memory_id=None, endness='Iend_BE'*)

Bases: `SimStatePlugin`

SUPPORTS_CONCRETE_LOAD = `False`

__init__(*memory_id=None, endness='Iend_BE'*)

copy(memo)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

property category

reg, mem, or file.

Type

Return the category of this `SimMemory` instance. It can be one of the three following categories

property variable_key_prefix

find(*addr, data, max_search, **kwargs*)

load(*addr, size=None, **kwargs*)

store(*addr, data, **kwargs*)

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

compare(*other*)

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

- **others** – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

permissions(*addr*, *permissions=None*, ***kwargs*)

map_region(*addr*, *length*, *permissions*, *init_zero=False*, ***kwargs*)

unmap_region(*addr*, *length*, ***kwargs*)

concrete_load(*addr*, *size*, *writing=False*, ***kwargs*)

Set `SUPPORTS_CONCRETE_LOAD` to `True` and implement `concrete_load` if reading concrete bytes is faster in this memory model.

Parameters

- **addr** – The address to load from.

- **size** – Size of the memory read.
- **writing** –

Return type

`memoryview`

Returns

A memoryview into the loaded bytes.

erase(*addr*, *size=None*, ***kwargs*)

Set [addr:addr+size) to uninitialized. In many cases this will be faster than overwriting those locations with new values. This is commonly used during static data flow analysis.

Parameters

- **addr** – The address to start erasing.
- **size** – The number of bytes for erasing.

Return type

`None`

Returns

`None`

replace_all(*old*, *new*)

Parameters

- **old** (*BV*) –
- **new** (*BV*) –

copy_contents(*dst*, *src*, *size*, *condition=None*, ***kwargs*)

Override this method to provide faster copying of large chunks of data.

Parameters

- **dst** – The destination of copying.
- **src** – The source of copying.
- **size** – The size of copying.
- **condition** – The storing condition.
- **kwargs** – Other parameters.

Returns

`None`

state: `angr.SimState`

class `angr.storage.memory_mixins.DefaultMemory`(*args, ***kwargs*)

Bases: `HexDumperMixin`, `SmartFindMixin`, `UnwrapperMixin`, `NameResolutionMixin`, `DataNormalizationMixin`, `SimplificationMixin`, `InspectMixinHigh`, `ActionsMixinHigh`, `UnderconstrainedMixin`, `SizeConcretizationMixin`, `SizeNormalizationMixin`, `AddressConcretizationMixin`, `ActionsMixinLow`, `ConditionalMixin`, `ConvenientMappingsMixin`, `DirtyAddrsMixin`, `StackAllocationMixin`, `ConcreteBackerMixin`, `ClemoryBackerMixin`, `DictBackerMixin`, `PrivilegedPagingMixin`, `UltraPagesMixin`, `DefaultFillerMixin`, `SymbolicMergerMixin`, `PagedMemoryMixin`


```

class angr.storage.memory_mixins.DefaultListPagesMemory(*args, **kwargs)
    Bases: HexDumperMixin, SmartFindMixin, UnwrapperMixin, NameResolutionMixin,
            DataNormalizationMixin, SimplificationMixin, ActionsMixinHigh, UnderconstrainedMixin,
            SizeConcretizationMixin, SizeNormalizationMixin, InspectMixinHigh,
            AddressConcretizationMixin, ActionsMixinLow, ConditionalMixin, ConvenientMappingsMixin,
            DirtyAddrsMixin, StackAllocationMixin, CMemoryBackerMixin, DictBackerMixin,
            PrivilegedPagingMixin, ListPagesMixin, DefaultFillerMixin, SymbolicMergerMixin,
            PagedMemoryMixin

class angr.storage.memory_mixins.FastMemory(uninitialized_read_handler=None, **kwargs)
    Bases: NameResolutionMixin, SimpleInterfaceMixin, SimplificationMixin, InspectMixinHigh,
            ConditionalMixin, ExplicitFillerMixin, DefaultFillerMixin, SlottedMemoryMixin

    state: angr.SimState

class angr.storage.memory_mixins.AbstractMemory(*args, **kwargs)
    Bases: UnwrapperMixin, NameResolutionMixin, DataNormalizationMixin,
            SimplificationMixin, InspectMixinHigh, ActionsMixinHigh, UnderconstrainedMixin,
            SizeConcretizationMixin, SizeNormalizationMixin, ActionsMixinLow, ConditionalMixin,
            RegionedAddressConcretizationMixin, RegionedMemoryMixin

    state: angr.SimState

class angr.storage.memory_mixins.RegionedMemory(related_function_addr=None, **kwargs)
    Bases: RegionCategoryMixin, MemoryRegionMetaMixin, StaticFindMixin,
            UnwrapperMixin, NameResolutionMixin, DataNormalizationMixin, SimplificationMixin,
            SizeConcretizationMixin, SizeNormalizationMixin, AddressConcretizationMixin,
            ConvenientMappingsMixin, DirtyAddrsMixin, CMemoryBackerMixin, DictBackerMixin,
            UltraPagesMixin, DefaultFillerMixin, AbstractMergerMixin, PagedMemoryMixin

class angr.storage.memory_mixins.LabeledMemory(*args, top_func=None, **kwargs)
    Bases: SizeNormalizationMixin, ListPagesWithLabelsMixin, DefaultFillerMixin,
            TopMergerMixin, LabelMergerMixin, PagedMemoryMixin

    LabeledMemory is used in static analysis. It allows storing values with labels, such as Definition.

class angr.storage.memory_mixins.MultiValuedMemory(*args,
                                                    skip_missing_values_during_merging=False,
                                                    **kwargs)

    Bases: SizeNormalizationMixin, MVListPagesMixin, DefaultFillerMixin,
            MultiValueMergerMixin, PagedMemoryMixin, PagedMemoryMultiValueMixin

class angr.storage.memory_mixins.KeyValueMemory(*args, **kwargs)
    Bases: KeyValueMemoryMixin

    state: angr.SimState

class angr.storage.memory_mixins.JavaVmMemory(memory_id='mem', stack=None, heap=None,
                                              vm_static_table=None, load_strategies=None,
                                              store_strategies=None, max_array_size=1000,
                                              **kwargs)

    Bases: JavaVmMemoryMixin

    state: angr.SimState

```

```
class angr.storage.memory_mixins.name_resolution_mixin.NameResolutionMixin(memory_id=None,
                                                                           end-
                                                                           ness='Iend_BE')
```

Bases: *MemoryMixin*

This mixin allows you to provide register names as load addresses, and will automatically translate this to an offset and size.

```
store(addr, data, size=None, **kwargs)
```

```
load(addr, size=None, **kwargs)
```

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.smart_find_mixin.SmartFindMixin(memory_id=None,
                                                                  endness='Iend_BE')
```

Bases: *MemoryMixin*

Memory mixin providing basic searching over concrete and symbolic data.

```
find(addr, data, max_search, default=None, endness=None, chunk_size=None, max_symbolic_bytes=None,
      condition=None, char_size=1, **kwargs)
```

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.default_filler_mixin.DefaultFillerMixin(memory_id=None,
                                                                           endness='Iend_BE')
```

Bases: *MemoryMixin*

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.default_filler_mixin.SpecialFillerMixin(special_memory_filler=None,
                                                                           **kwargs)
```

Bases: *MemoryMixin*

```
__init__(special_memory_filler=None, **kwargs)
```

```
copy(memo)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.default_filler_mixin.ExplicitFillerMixin(uninitialized_read_handler=None,
                                                                           **kwargs)
```

Bases: *MemoryMixin*

```
__init__(uninitialized_read_handler=None, **kwargs)
```

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.memory_mixins.bvv_conversion_mixin.DataNormalizationMixin(memory_id=None,
                                                                              end-
                                                                              ness='lend_BE')
```

Bases: `MemoryMixin`

Normalizes the data field for a store and the fallback field for a load to be BVs.

store(*addr*, *data*, *size=None*, ***kwargs*)

load(*addr*, *size=None*, *fallback=None*, ***kwargs*)

state: `angr.SimState`

```
class angr.storage.memory_mixins.hex_dumper_mixin.HexDumperMixin(memory_id=None,
                                                                    endness='lend_BE')
```

Bases: `MemoryMixin`

hex_dump(*start*, *size*, *word_size=4*, *words_per_row=4*, *endianness='lend_BE'*, *symbolic_char='?'*, *unprintable_char='.'*, *solve=False*, *extra_constraints=None*, *inspect=False*, *disable_actions=True*)

Returns a hex dump as a string. The solver, if enabled, is called once for every byte potentially making this function very slow. It is meant to be used mainly as a “visualization” for debugging.

Warning: May read and display more bytes than *size* due to rounding. Particularly, if size is less than, or not a multiple of *word_size*words_per_line*.

Parameters

- **start** – starting address from which to print
- **size** – number of bytes to display
- **word_size** – number of bytes to group together as one space-delimited unit
- **words_per_row** – number of words to display per row of output
- **endianness** – endianness to use when displaying each word (ASCII representation is unchanged)
- **symbolic_char** – the character to display when a byte is symbolic and has multiple solutions
- **unprintable_char** – the character to display when a byte is not printable
- **solve** – whether or not to attempt to solve (warning: can be very slow)
- **extra_constraints** – extra constraints to pass to the solver if solve is True

- **inspect** – whether or not to trigger SimInspect breakpoints for the memory load
- **disable_actions** – whether or not to disable SimActions for the memory load

Returns

hex dump as a string

state: `angr.SimState`

```
class angr.storage.memory_mixins.underconstrained_mixin.UnderconstrainedMixin(*args,
                                                                              **kwargs)
```

Bases: `MemoryMixin`

__init__(*args, **kwargs)

copy(memo=None, **kwargs)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

load(addr, **kwargs)

store(addr, data, **kwargs)

state: `angr.SimState`

```
class angr.storage.memory_mixins.simple_interface_mixin.SimpleInterfaceMixin(memory_id=None,
                                                                              end-
                                                                              ness='Iend_BE')
```

Bases: `MemoryMixin`

load(addr, size=None, endness=None, condition=None, fallback=None, **kwargs)

store(addr, data, size=None, endness=None, condition=None, **kwargs)

state: `angr.SimState`

```
class angr.storage.memory_mixins.actions_mixin.ActionsMixinHigh(memory_id=None,
                                                                  endness='Iend_BE')
```

Bases: `MemoryMixin`

load(addr, size=None, condition=None, fallback=None, disable_actions=False, action=None, **kwargs)

store(addr, data, size=None, disable_actions=False, action=None, condition=None, **kwargs)

state: `angr.SimState`

```
class angr.storage.memory_mixins.actions_mixin.ActionsMixinLow(memory_id=None,
                                                                endness='Iend_BE')
```

Bases: `MemoryMixin`

```
load(addr, action=None, **kwargs)
```

```
store(addr, data, action=None, **kwargs)
```

Parameters

action ([SimActionData](#) | *None*) –

state: [angr.SimState](#)

```
class angr.storage.memory_mixins.symbolic_merger_mixin.SymbolicMergerMixin(memory_id=None,
                                                                            end-
                                                                            ness='Iend_BE')
```

Bases: [MemoryMixin](#)

state: [angr.SimState](#)

```
class angr.storage.memory_mixins.size_resolution_mixin.SizeNormalizationMixin(memory_id=None,
                                                                                end-
                                                                                ness='Iend_BE')
```

Bases: [MemoryMixin](#)

Provides basic services related to normalizing sizes. After this mixin, sizes will always be a plain int. Assumes that the data is a BV.

- load will throw a `TypeError` if no size is provided
- store will default to `len(data)//byte_width` if no size is provided

```
load(addr, size=None, **kwargs)
```

```
store(addr, data, size=None, **kwargs)
```

state: [angr.SimState](#)

```
class angr.storage.memory_mixins.size_resolution_mixin.SizeConcretizationMixin(concretize_symbolic_write_size,
                                                                                max_concretize_count=256,
                                                                                max_symbolic_size=4194304,
                                                                                raise_memory_limit_error=False,
                                                                                size_limit=257,
                                                                                **kwargs)
```

Bases: [MemoryMixin](#)

This mixin allows memory to process symbolic sizes. It will not touch any sizes which are not ASTs with non-BVV ops. Assumes that the data is a BV.

- symbolic load sizes will be concretized as their maximum and a warning will be logged
- symbolic store sizes will be dispatched as several conditional stores with concrete sizes

Parameters

- **concretize_symbolic_write_size** (*bool*) –
- **max_concretize_count** (*int* | *None*) –
- **max_symbolic_size** (*int*) –
- **raise_memory_limit_error** (*bool*) –
- **size_limit** (*int*) –

```
__init__(concretize_symbolic_write_size=False, max_concretize_count=256,
        max_symbolic_size=4194304, raise_memory_limit_error=False, size_limit=257, **kwargs)
```

Parameters

- **concretize_symbolic_write_size** (*bool*) –
- **max_concretize_count** (*int* | *None*) –
- **max_symbolic_size** (*int*) –
- **raise_memory_limit_error** (*bool*) –
- **size_limit** (*int*) –

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

load(*addr*, *size=None*, **kwargs)

store(*addr*, *data*, *size=None*, *condition=None*, **kwargs)

state: `angr.SimState`

```
class angr.storage.memory_mixins.dirty_addrs_mixin.DirtyAddrsMixin(memory_id=None,
                                                                endness='Iend_BE')
```

Bases: `MemoryMixin`

store(*addr*, *data*, *size=None*, **kwargs)

state: `angr.SimState`

```
class angr.storage.memory_mixins.address_concretization_mixin.MultiwriteAnnotation
```

Bases: `Annotation`

property eliminatable

Returns whether this annotation can be eliminated in a simplification.

Returns

True if eliminatable, False otherwise

property relocateable

```
class angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin(read_strategies=None,
                                                                                          write_strategies=None,
                                                                                          **kwargs)
```

Bases: `MemoryMixin`

The address concretization mixin allows symbolic reads and writes to be handled sanely by dispatching them as a number of conditional concrete reads/writes. It provides a “concretization strategies” interface allowing the process of serializing symbolic addresses into concrete ones to be specified.

__init__(*read_strategies=None, write_strategies=None, **kwargs*)

set_state(*state*)

Sets a new state (for example, if the state has been branched)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others, merge_conditions, common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

concretize_write_addr(*addr*, *strategies=None*, *condition=None*)

Concretizes an address meant for writing.

Parameters

- **addr** – An expression for the address.
- **strategies** – A list of concretization strategies (to override the default).
- **condition** – Any extra constraints that should be observed when determining address satisfiability

Returns

A list of concrete addresses.

concretize_read_addr(*addr*, *strategies=None*, *condition=None*)

Concretizes an address meant for reading.

Parameters

- **addr** – An expression for the address.
- **strategies** – A list of concretization strategies (to override the default).

Returns

A list of concrete addresses.

load(*addr*, *size=None*, *condition=None*, ***kwargs*)

store(*addr*, *data*, *size=None*, *condition=None*, ***kwargs*)

permissions(*addr*, *permissions=None*, ***kwargs*)

map_region(*addr*, *length*, *permissions*, ***kwargs*)

unmap_region(*addr*, *length*, ***kwargs*)

concrete_load(*addr*, *size*, **args*, ***kwargs*)

Set `SUPPORTS_CONCRETE_LOAD` to `True` and implement `concrete_load` if reading concrete bytes is faster in this memory model.

Parameters

- **addr** – The address to load from.
- **size** – Size of the memory read.
- **writing** –

Returns

A memoryview into the loaded bytes.

state: `angr.SimState`

class `angr.storage.memory_mixins.clouseau_mixin.InspectMixinHigh`(*memory_id=None*,
endness='lend_BE')

Bases: `MemoryMixin`

store(*addr*, *data*, *size=None*, *condition=None*, *endness=None*, *inspect=True*, ***kwargs*)

load(*addr*, *size=None*, *condition=None*, *endness=None*, *inspect=True*, ***kwargs*)

state: `angr.SimState`


```
class angr.storage.memory_mixins.conditional_store_mixin.ConditionalMixin(memory_id=None,
                                                                           end-
                                                                           ness='Iend_BE')
```

Bases: *MemoryMixin*

load(addr, condition=None, fallback=None, **kwargs)

store(addr, data, size=None, condition=None, **kwargs)

state: angr.SimState

```
class angr.storage.memory_mixins.label_merger_mixin.LabelMergerMixin(*args, **kwargs)
```

Bases: *MemoryMixin*

A memory mixin for merging labels. Labels come from SimLabeledMemoryObject.

__init__(*args, **kwargs)

copy(memo=None)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (id(obj)) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: angr.SimState

```
class angr.storage.memory_mixins.simplification_mixin.SimplificationMixin(memory_id=None,
                                                                           end-
                                                                           ness='Iend_BE')
```

Bases: *MemoryMixin*

store(addr, data, **kwargs)

state: angr.SimState

```
class angr.storage.memory_mixins.unwrapper_mixin.UnwrapperMixin(memory_id=None,
                                                                  endness='Iend_BE')
```

Bases: *MemoryMixin*

This mixin processes SimActionObjects by passing on their .ast field.

store(addr, data, size=None, condition=None, **kwargs)

load(addr, size=None, condition=None, fallback=None, **kwargs)

find(addr, what, max_search, default=None, **kwargs)

copy_contents(dst, src, size, condition=None, **kwargs)

Override this method to provide faster copying of large chunks of data.

Parameters

- **dst** – The destination of copying.

- **src** – The source of copying.
- **size** – The size of copying.
- **condition** – The storing condition.
- **kwargs** – Other parameters.

Returns

None

state: `angr.SimState`

class `angr.storage.memory_mixins.convenient_mappings_mixin.ConvenientMappingsMixin(**kwargs)`
 Bases: `MemoryMixin`

Implements mappings between names and hashes of symbolic variables and these variables themselves.

__init__(***kwargs*)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

store(*addr, data, size=None, **kwargs*)

get_symbolic_addrs()

addrs_for_name(*n*)

Returns addresses that contain expressions that contain a variable named *n*.

addrs_for_hash(*h*)

Returns addresses that contain expressions that contain a variable with the hash of *h*.

replace_all(*old, new*)

Replaces all instances of expression *old* with expression *new*.

Parameters

- **old** (`BV`) – A claripy expression. Must contain at least one named variable (to make it possible to use the name index for speedup).
- **new** (`BV`) – The new variable to replace it with.

state: `angr.SimState`

class `angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MVListPage(memory=None, content=None, sinkhole=None, mo_cmp=None, **kwargs)`

Bases: [MemoryObjectSetMixin](#), [PageBase](#)

MVListPage allows storing multiple values at the same location, thus allowing weak updates.

Each store() may take a value or multiple values, and a “weak” parameter to specify if this store is a weak update or not. Each load() returns an iterator of all values stored at that location.

__init__(*memory=None, content=None, sinkhole=None, mo_cmp=None, **kwargs*)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

Return type

[MVListPage](#)

load(*addr, size=None, endness=None, page_addr=None, memory=None, cooperate=False, **kwargs*)

Return type

[List](#)[[Tuple](#)[[int](#), [Union](#)[[SimMemoryObject](#), [SimLabeledMemoryObject](#)]]]

store(*addr, data, size=None, endness=None, memory=None, cooperate=False, weak=False, **kwargs*)

erase(*addr, size=None, **kwargs*)

Set [`addr:addr+size`) to uninitialized. In many cases this will be faster than overwriting those locations with new values. This is commonly used during static data flow analysis.

Parameters

- **addr** – The address to start erasing.
- **size** – The number of bytes for erasing.

Return type

[None](#)

Returns

[None](#)

merge(*others, merge_conditions, common_ancestor=None, page_addr=None, memory=None, changed_offsets=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** (`List[MVListPage]`) – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged
- **page_addr** (`int | None`) –
- **changed_offsets** (`Set[int] | None`) –

Returns

True if the state plugins are actually merged.

Return type

`bool`

compare(*other*, *page_addr*=None, *memory*=None, *changed_offsets*=None)

Return type

`bool`

Parameters

- **other** (`MVListPage`) –
- **page_addr** (`int | None`) –

changed_bytes(*other*, *page_addr*=None)

Parameters

- **other** (`MVListPage`) –
- **page_addr** (`int | None`) –

content_gen(*index*)

state: `angr.SimState`

class `angr.storage.memory_mixins.paged_memory.pages.multi_values.MultiValues`(*v*=None, *offset_to_values*=None)

Bases: `object`

Represents a byte vector where each byte can have one or multiple values.

As an implementation optimization (so that we do not create excessive sets and dicts), `self._single_value` stores a claripy AST when this `MultiValues` object represents only one value at offset 0.

Parameters
v (*Bits* | *MultiValues* | *None* | *Dict[int, Set[Bits]]*) –

__init__ (*v=None, offset_to_values=None*)

Parameters
v (*Bits* | *MultiValues* | *None* | *Dict[int, Set[Bits]]*) –

add_value (*offset, value*)

Return type
None

Parameters

- **offset** (*int*) –
- **value** (*Bits*) –

one_value (*strip_annotations=False*)

Return type
Optional[Bits]

Parameters
strip_annotations (*bool*) –

merge (*mv*)

Return type
MultiValues

Parameters
mv (*MultiValues*) –

keys ()

Return type
Set[int]

values ()

Return type
Iterator[Set[Bits]]

items ()

Return type
Iterator[Tuple[int, Set[Bits]]]

count ()

Return type
int

extract (*offset, length, endness*)

Return type
MultiValues

Parameters

- **offset** (*int*) –
- **length** (*int*) –

- **endness** (*str*) –

concat(*other*)

Return type

MultiValues

Parameters

other (*MultiValues* | *Bits* | *bytes*) –

```
class angr.storage.memory_mixins.top_merger_mixin.TopMergerMixin(*args, top_func=None,
                                                                **kwargs)
```

Bases: *MemoryMixin*

A memory mixin for merging values in memory to TOP.

```
__init__(*args, top_func=None, **kwargs)
```

copy(*memo=None*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.memory_mixins.multi_value_merger_mixin.MultiValueMergerMixin(*args, element_limit=5,
                                                                                     annotation_limit=256,
                                                                                     top_func=None,
                                                                                     is_top_func=None,
                                                                                     phi_maker=None,
                                                                                     **kwargs)
```

Bases: *MemoryMixin*

```
__init__(*args, element_limit=5, annotation_limit=256, top_func=None, is_top_func=None,
        phi_maker=None, **kwargs)
```

copy(*memo=None*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin(page_size=4096,
                                          de-
                                          fault_permissions=3,
                                          permis-
                                          sions_map=None,
                                          page_kwargs=None,
                                          **kwargs)
```

Bases: `MemoryMixin`

A bottom-level storage mechanism. Dispatches reads to individual pages, the type of which is the `PAGE_TYPE` class variable.

SUPPORTS_CONCRETE_LOAD = `True`

PAGE_TYPE: `Type[TypeVar(PageType, bound= PageBase)] = None`

```
__init__(page_size=4096, default_permissions=3, permissions_map=None, page_kwargs=None,
          **kwargs)
```

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

load(*addr*, *size=None*, *endness=None*, ***kwargs*)

Parameters

- **addr** (*int*) –
- **size** (*int* | *None*) –

store(*addr*, *data*, *size=None*, *endness=None*, ***kwargs*)

Parameters

- **addr** (*int*) –
- **size** (*int* | *None*) –

erase(*addr*, *size=None*, ***kwargs*)

Set [`addr:addr+size`) to uninitialized. In many cases this will be faster than overwriting those locations with new values. This is commonly used during static data flow analysis.

Parameters

- **addr** – The address to start erasing.
- **size** – The number of bytes for erasing.

Return type

`None`

Returns

None

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* *others* and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** (`Iterable[PagedMemoryMixin]`) – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

compare(*other*)**Return type**

bool

Parameters

other (`PagedMemoryMixin`) –

permissions(*addr*, *permissions*=None, ***kwargs*)**map_region**(*addr*, *length*, *permissions*, *init_zero*=False, ***kwargs*)**unmap_region**(*addr*, *length*, ***kwargs*)

concrete_load(*addr*, *size*, *writing=False*, *with_bitmap=False*, ***kwargs*)

Set SUPPORTS_CONCRETE_LOAD to True and implement concrete_load if reading concrete bytes is faster in this memory model.

Parameters

- **addr** – The address to load from.
- **size** – Size of the memory read.
- **writing** –

Returns

A memoryview into the loaded bytes.

changed_bytes(*other*)

Return type

`Set[int]`

changed_pages(*other*)

Return type

`Dict[int, Optional[Set[int]]]`

copy_contents(*dst*, *src*, *size*, *condition=None*, ***kwargs*)

Override this method to provide faster copying of large chunks of data.

Parameters

- **dst** – The destination of copying.
- **src** – The source of copying.
- **size** – The size of copying.
- **condition** – The storing condition.
- **kwargs** – Other parameters.

Returns

None

flush_pages(*white_list*)

Flush all pages not included in the *white_list* by removing their pages. Note, this will not wipe them from memory if they were backed by a memory_backer, it will simply reset them to their initial state. Returns the list of pages that were cleared consisting of (*addr*, *length*) tuples. :type white_list: :param white_list: white list of regions in the form of (start, end) to exclude from the flush :return: a list of memory page ranges that were flushed :rtype: list

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.LabeledPagesMixin(page_size=4096,
                                                                                   de-
                                                                                   fault_permissions=3,
                                                                                   permis-
                                                                                   sions_map=None,
                                                                                   page_kwargs=None,
                                                                                   **kwargs)
```

Bases: `PagedMemoryMixin`

load_with_labels(*addr*, *size=None*, *endness=None*, ***kwargs*)

Return type

`Tuple[Base, Tuple[Tuple[int, int, int, Any]]]`

Parameters

- **addr** (*int*) –
- **size** (*int* / *None*) –

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.ListPagesMixin(page_size=4096,
de-
fault_permissions=3,
permis-
sions_map=None,
page_kwargs=None,
**kwargs)
```

Bases: `PagedMemoryMixin`

PAGE_TYPE

alias of `ListPage`

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.MVListPagesMixin(*args,
skip_missing_values_during
**kwargs)
```

Bases: `PagedMemoryMixin`

PAGE_TYPE

alias of `MVListPage`

__init__ (**args*, *skip_missing_values_during_merging=False*, ***kwargs*)

copy (*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

- memo** – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.ListPagesWithLabelsMixin(page_size=4096,
de-
fault_permissions
per-
mis-
sions_map=None
page_kwargs=No
**kwargs)
```

Bases: `LabeledPagesMixin`, `ListPagesMixin`

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.MVListPagesWithLabelsMixin(*args,
                                                                                               skip_missing_1,
                                                                                               **kwargs)
```

Bases: *LabeledPagesMixin*, *MVListPagesMixin*

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.paged_memory.paged_memory_mixin.UltraPagesMixin(page_size=4096,
                                                                                     de-
                                                                                     fault_permissions=3,
                                                                                     permis-
                                                                                     sions_map=None,
                                                                                     page_kwargs=None,
                                                                                     **kwargs)
```

Bases: *PagedMemoryMixin*

PAGE_TYPE

alias of *UltraPage*

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.paged_memory.page_backer_mixins.NotMemoryview(obj, offset,
                                                                                   size)
```

Bases: *object*

```
__init__(obj, offset, size)
```

```
class angr.storage.memory_mixins.paged_memory.page_backer_mixins.CleemoryBackerMixin(cle_memory_backer=None,
                                                                                       **kwargs)
```

Bases: *PagedMemoryMixin*

Parameters

cle_memory_backer (*None* | *Loader* | *Cleemory*) –

```
__init__(cle_memory_backer=None, **kwargs)
```

Parameters

cle_memory_backer (*None* | *Loader* | *Cleemory*) –

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
state: angr.SimState
```

```
class angr.storage.memory_mixins.paged_memory.page_backer_mixins.ConcreteBackerMixin(cle_memory_backer=None,
                                                                                       **kwargs)
```

Bases: [ClemoryBackerMixin](#)

Parameters

cle_memory_backer (*None* | [Loader](#) | [Clemory](#)) –

state: [angr.SimState](#)

```
class angr.storage.memory_mixins.paged_memory.page_backer_mixins.DictBackerMixin(dict_memory_backer=None,
                                                                                   **kwargs)
```

Bases: [PagedMemoryMixin](#)

```
__init__(dict_memory_backer=None, **kwargs)
```

state: [angr.SimState](#)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
class angr.storage.memory_mixins.paged_memory.stack_allocation_mixin.StackAllocationMixin(stack_end=None,
                                                                                          stack_size=None,
                                                                                          stack_perms=None,
                                                                                          **kwargs)
```

Bases: [PagedMemoryMixin](#)

This mixin adds automatic allocation for a stack region based on the `stack_end` and `stack_size` parameters.

```
__init__(stack_end=None, stack_size=None, stack_perms=None, **kwargs)
```

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
allocate_stack_pages(addr, size, **kwargs)
```

Pre-allocates pages for the stack without triggering any logic related to reading from them.

Parameters

- **addr** ([int](#)) – The highest address that should be mapped

- **size** (*int*) – The number of bytes to be allocated. byte 1 is the one at addr, byte 2 is the one before that, and so on.

Returns

A list of the new page objects

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.privileged_mixin.PrivilegedPagingMixin(page_size=4096,
de-
fault_permissions=3,
per-
mis-
sions_map=None,
page_kwargs=None,
**kwargs)
```

Bases: [PagedMemoryMixin](#)

A mixin for paged memory models which will raise `SimSegfaultExceptions` if `STRICT_PAGE_ACCESS` is enabled and a segfault condition is detected.

Segfault conditions include: - getting a page for reading which is non-readable - getting a page for writing which is non-writable - creating a page

The latter condition means that this should be inserted under any mixins which provide other implementations of `_initialize_page`.

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.pages.PageBase(*args, **kwargs)
```

Bases: [HistoryTrackingMixin](#), [RefcountMixin](#), [CooperationBase](#), [ISPOMixin](#), [PermissionsMixin](#), [MemoryMixin](#)

This is a fairly succinct definition of the contract between `PagedMemoryMixin` and its constituent pages:

- Pages must implement the `MemoryMixin` model for loads, stores, copying, merging, etc
- However, loading/storing may not necessarily use the same data domain as `PagedMemoryMixin`. In order to do more efficient loads/stores across pages, we use the `CooperationBase` interface which allows the page class to determine how to generate and unwrap the objects which are actually stored.
- To support COW, we use the `RefcountMixin` and the `ISPOMixin` (which adds the contract element that `memory=self` be passed to every method call)
- Pages have permissions associated with them, stored in the `PermissionsMixin`.

Read the docstrings for each of the constituent classes to understand the nuances of their functionalities

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.pages.refcount_mixin.RefcountMixin(**kwargs)
```

Bases: [MemoryMixin](#)

This mixin adds a locked reference counter and methods to manipulate it, to facilitate copy-on-write optimizations.

```
__init__(**kwargs)
```

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

acquire_unique()

Call this function to return a version of this page which can be used for writing, which may or may not be the same object as before. If you use this you must immediately replace the shared reference you previously had with the new unique copy.

acquire_shared()

Call this function to indicate that this page has had a reference added to it and must be copied before it can be acquired uniquely again. Creating the object implicitly starts it with one shared reference.

Return type

`None`

release_shared()

Call this function to indicate that this page has had a shared reference to it released

Return type

`None`

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.pages.permissions_mixin.PermissionsMixin(permissions=None,  
                                                                                       **kwargs)
```

Bases: `MemoryMixin`

This mixin adds a permissions field and properties for extracting the read/write/exec permissions. It does NOT add permissions checking.

```
__init__(permissions=None, **kwargs)
```

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

property `perm_read`

property `perm_write`

property `perm_exec`

state: `angr.SimState`

class `angr.storage.memory_mixins.paged_memory.pages.history_tracking_mixin.HistoryTrackingMixin(*args, **kwargs)`

Bases: `RefCountMixin`, `MemoryMixin`

Tracks the history of memory writes.

__init__(*args, **kwargs)

store(*addr*, *data*, *size=None*, **kwargs)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

acquire_unique()

Call this function to return a version of this page which can be used for writing, which may or may not be the same object as before. If you use this you must immediately replace the shared reference you previously had with the new unique copy.

parents()

changed_bytes(*other*, **kwargs)

Return type

`Optional[Set[int]]`

all_bytes_changed_in_history()

Return type

`SegmentList`

state: `angr.SimState`

class `angr.storage.memory_mixins.paged_memory.pages.ispo_mixin.ISPOMixin(memory_id=None, endness='lend_BE')`

Bases: `MemoryMixin`

An implementation of the International Stateless Persons Organisation, a mixin which should be applied as a bottom layer for memories which have no state and must redirect certain operations to a parent memory. Main usecase is for memory region classes which are stored within other memories, such as pages.

set_state(*state*)

Sets a new state (for example, if the state has been branched)

state: `angr.SimState`

class `angr.storage.memory_mixins.paged_memory.pages.cooperation.CooperationBase`

Bases: `object`

Any given subclass of this class which is not a subclass of `MemoryMixin` should have the property that any subclass it which is a subclass of `MemoryMixin` should all work with the same datatypes

class `angr.storage.memory_mixins.paged_memory.pages.cooperation.MemoryObjectMixin`

Bases: `CooperationBase`

Uses `SimMemoryObjects` in region storage. With this, `load` will return a list of tuple (address, MO) and `store` will take a MO.

class `angr.storage.memory_mixins.paged_memory.pages.cooperation.MemoryObjectSetMixin`

Bases: `CooperationBase`

Uses sets of `SimMemoryObjects` in region storage.

class `angr.storage.memory_mixins.paged_memory.pages.cooperation.BasicClaripyCooperation`

Bases: `CooperationBase`

Mix this (along with `PageBase`) into a storage class which supports loading and storing claripy bitvectors and it will be able to work as a page in the paged memory model.

class `angr.storage.memory_mixins.paged_memory.pages.list_page.ListPage`(*memory=None*,
content=None,
sinkhole=None,
mo_cmp=None,
***kwargs*)

Bases: `MemoryObjectMixin`, `PageBase`

This class implements a page memory mixin with lists as the main content store.

__init__(*memory=None*, *content=None*, *sinkhole=None*, *mo_cmp=None*, ***kwargs*)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

load(*addr*, *size=None*, *endness=None*, *page_addr=None*, *memory=None*, *cooperate=False*, ***kwargs*)

store(*addr*, *data*, *size=None*, *endness=None*, *memory=None*, *cooperate=False*, ***kwargs*)

erase(*addr*, *size=None*, ***kwargs*)

Set [`addr`:`addr+size`) to uninitialized. In many cases this will be faster than overwriting those locations with new values. This is commonly used during static data flow analysis.

Parameters

- **addr** – The address to start erasing.
- **size** – The number of bytes for erasing.

Return type

`None`

Returns

`None`

merge(*others*, *merge_conditions*, *common_ancestor*=*None*, *page_addr*=*None*, *memory*=*None*, *changed_offsets*=*None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you "deepen" both others and common_ancestor before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** (`List[ListPage]`) – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged
- **page_addr** (`int` | `None`) –
- **changed_offsets** (`Set[int]` | `None`) –

Returns

True if the state plugins are actually merged.

Return type

`bool`

changed_bytes(*other*, *page_addr*=*None*)

Parameters

- **other** (`ListPage`) –
- **page_addr** (`int` | `None`) –

state: `angr.SimState`

```
class angr.storage.memory_mixins.paged_memory.pages.ultra_page.UltraPage(memory=None,
                                                                           init_zero=False,
                                                                           **kwargs)
```

Bases: `MemoryObjectMixin`, `PageBase`

Default page implementation

SUPPORTS_CONCRETE_LOAD = `True`

__init__(*memory=None, init_zero=False, **kwargs*)

classmethod new_from_shared(*data, memory=None, **kwargs*)

copy(*memo*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

load(*addr, size=None, page_addr=None, endness=None, memory=None, cooperate=False, **kwargs*)

store(*addr, data, size=None, endness=None, memory=None, page_addr=None, cooperate=False, **kwargs*)

Parameters

- **data** (`int` | `SimMemoryObject`) –
- **size** (`int` | `None`) –

merge(*others, merge_conditions, common_ancestor=None, page_addr=None, memory=None, changed_offsets=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to resolve the similar issue that arises during copying because merging doesn’t produce a new reference to insert.

There will be `n` others and `n+1` merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and `common_ancestor` before calling sub-elements’ merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
```

(continues on next page)

(continued from previous page)

```
common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** (`List[UltraPage]`) – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged
- **page_addr** (`int` | `None`) –
- **changed_offsets** (`Set[int]` | `None`) –

Returns

True if the state plugins are actually merged.

Return type

`bool`

concrete_load(*addr, size, **kwargs*)

Set `SUPPORTS_CONCRETE_LOAD` to `True` and implement `concrete_load` if reading concrete bytes is faster in this memory model.

Parameters

- **addr** – The address to load from.
- **size** – Size of the memory read.
- **writing** –

Returns

A memoryview into the loaded bytes.

changed_bytes(*other, page_addr=None*)

Return type

`Set[int]`

state: `angr.SimState`

replace_all_with_offsets(*offsets, old, new, memory=None*)

Parameters

- **offsets** (`Iterable[int]`) –
- **old** (`BV`) –
- **new** (`BV`) –

```
class angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemoryMixin(write_targets_limit=2048, read_targets_limit=4096, stack_region_map=None, generic_region_map=None, stack_size=65536, cle_memory_backer=None, dict_memory_backer=None, regioned_memory_cls=None, **kwargs)
```

Bases: [MemoryMixin](#)

Regioned memory. This mixin manages multiple memory regions. Each address is represented as a tuple of (region ID, offset into the region), which is called a regioned address.

Converting absolute addresses into regioned addresses: We map an absolute address to a region by looking up which region this address belongs to in the region map. Currently this is only enabled for stack. Heap support has not landed yet.

When start analyzing a function, the user should call `set_stack_address_mapping()` to create a new region mapping. Likewise, when exiting from a function, the user should cancel the previous mapping by calling `unset_stack_address_mapping()`.

Parameters

- **write_targets_limit** (*int*) –
- **read_targets_limit** (*int*) –
- **stack_region_map** ([RegionMap](#) / *None*) –
- **generic_region_map** ([RegionMap](#) / *None*) –
- **stack_size** (*int*) –
- **cle_memory_backer** (*Optional*) –
- **dict_memory_backer** (*Dict* / *None*) –
- **regioned_memory_cls** (*type* / *None*) –

```
__init__(write_targets_limit=2048, read_targets_limit=4096, stack_region_map=None, generic_region_map=None, stack_size=65536, cle_memory_backer=None, dict_memory_backer=None, regioned_memory_cls=None, **kwargs)
```

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

```
load(addr, size=None, endness=None, condition=None, **kwargs)
```

Parameters

- **size** (*BV* | *int* | *None*) –
- **condition** (*Bool* | *None*) –

store(*addr*, *data*, *size=None*, *endness=None*, ***kwargs*)

Parameters

size (*int* | *None*) –

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both others and common_ancestor before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, merge_conditions can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** (*Iterable*[*RegionedMemoryMixin*]) – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

find(*addr*, *data*, *max_search*, ***kwargs*)

Parameters

addr (*int* | *Bits*) –

set_state(*state*)

Sets a new state (for example, if the state has been branched)

replace_all(*old*, *new*)

Parameters

- **old** (*BV*) –
- **new** (*BV*) –

set_stack_address_mapping(*absolute_address*, *region_id*, *related_function_address*=None)

Create a new mapping between an absolute address (which is the base address of a specific stack frame) and a region ID.

Parameters

- **absolute_address** (*int*) – The absolute memory address.
- **region_id** (*str*) – The region ID.
- **related_function_address** (*Optional*[*int*]) – Related function address.

unset_stack_address_mapping(*absolute_address*)

Remove a stack mapping.

Parameters

- **absolute_address** (*int*) – An absolute memory address that is the base address of the stack frame to destroy.

stack_id(*function_address*)

Return a memory region ID for a function. If the default region ID exists in the region mapping, an integer will be appended to the region name. In this way we can handle recursive function calls, or a function that appears more than once in the call frame.

This also means that *stack_id()* should only be called when creating a new stack frame for a function. You are not supposed to call this function every time you want to map a function address to a stack ID.

Parameters

- **function_address** (*int*) – Address of the function.

Return type

str

Returns

ID of the new memory region.

set_stack_size(*size*)

Parameters

- **size** (*int*) –

state: *angr.SimState*

```
class angr.storage.memory_mixins.regioned_memory.region_data.AddressWrapper(region, re-
                                                                           gion_base_addr,
                                                                           address,
                                                                           is_on_stack,
                                                                           func-
                                                                           tion_address)
```

Bases: *object*

AddressWrapper is used in SimAbstractMemory, which provides extra meta information for an address (or a ValueSet object) that is normalized from an integer/BVV/StridedInterval.

Parameters

- **region** (*str*) –
- **region_base_addr** (*int*) –
- **is_on_stack** (*bool*) –
- **function_address** (*int* | *None*) –

__init__ (*region, region_base_addr, address, is_on_stack, function_address*)

Constructor for the class AddressWrapper.

Parameters

- **region** (*str*) – Name of the memory regions it belongs to.
- **region_base_addr** (*int*) – Base address of the memory region
- **address** – An address (not a ValueSet object).
- **is_on_stack** (*bool*) – Whether this address is on a stack region or not.
- **function_address** (*Optional[int]*) – Related function address (if any).

region

region_base_addr

address

is_on_stack

function_address

to_valueset (*state*)

Convert to a ValueSet instance

Parameters

state – A state

Returns

The converted ValueSet instance

```
class angr.storage.memory_mixins.regioned_memory.region_data.RegionDescriptor(region_id,
                                                                              base_address,
                                                                              re-
                                                                              lated_function_address=None)
```

Bases: *object*

Descriptor for a memory region ID.

__init__ (*region_id, base_address, related_function_address=None*)

region_id

base_address

related_function_address

```
class angr.storage.memory_mixins.regioned_memory.region_data.RegionMap(is_stack)
```

Bases: *object*

Mostly used in SimAbstractMemory, RegionMap stores a series of mappings between concrete memory address ranges and memory regions, like stack frames and heap regions.

__init__(*is_stack*)

Constructor

Parameters

is_stack – Whether this is a region map for stack frames or not. Different strategies apply for stack regions.

property is_empty

property stack_base

property region_ids

copy(*memo=None, **kwargs*)

map(*absolute_address, region_id, related_function_address=None*)

Add a mapping between an absolute address and a region ID. If this is a stack region map, all stack regions beyond (lower than) this newly added regions will be discarded.

Parameters

- **absolute_address** – An absolute memory address.
- **region_id** – ID of the memory region.
- **related_function_address** – A related function address, mostly used for stack regions.

unmap_by_address(*absolute_address*)

Removes a mapping based on its absolute address.

Parameters

absolute_address – An absolute address

absolutize(*region_id, relative_address*)

Convert a relative address in some memory region to an absolute address.

Parameters

- **region_id** – The memory region ID
- **relative_address** – The relative memory offset in that memory region

Returns

An absolute address if converted, or an exception is raised when region id does not exist.

relativize(*absolute_address, target_region_id=None*)

Convert an absolute address to the memory offset in a memory region.

Note that if an address belongs to heap region is passed in to a stack region map, it will be converted to an offset included in the closest stack frame, and vice versa for passing a stack address to a heap region. Therefore you should only pass in address that belongs to the same category (stack or non-stack) of this region map.

Parameters

absolute_address – An absolute memory address

Returns

A tuple of the closest region ID, the relative offset, and the related function address.

class `angr.storage.memory_mixins.regioned_memory.region_category_mixin.RegionCategoryMixin`(*memory_id=None, end-ness='tend_BE'*)

Bases: `MemoryMixin`

property category

reg, mem, or file.

Type

Return the category of this SimMemory instance. It can be one of the three following categories

state: `angr.SimState`

class `angr.storage.memory_mixins.regioned_memory.static_find_mixin.StaticFindMixin`(*memory_id=None*,
endness='end_BE')

Bases: `SmartFindMixin`

Implements data finding for abstract memory.

find(*addr*, *data*, *max_search*, *default=None*, *endness=None*, *chunk_size=None*, *max_symbolic_bytes=None*,
condition=None, *char_size=1*, ***kwargs*)

state: `angr.SimState`

class `angr.storage.memory_mixins.regioned_memory.abstract_address_descriptor.AbstractAddressDescriptor`

Bases: `object`

AbstractAddressDescriptor describes a list of region+offset tuples. It provides a convenient way for accessing the cardinality (the total number of addresses) without enumerating or creating all addresses in static mode.

__init__()

property cardinality

add_regioned_address(*region*, *addr*)

Parameters

- **region** (*str*) –
- **addr** (*StridedInterval*) –

clear()

class `angr.storage.memory_mixins.regioned_memory.region_meta_mixin.MemoryRegionMetaMixin`(*related_function_addr=None*, ***kwargs*)

Bases: `MemoryMixin`

__init__(*related_function_addr=None*, ***kwargs*)

copy(*memo=None*, ***kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

property is_stack

property related_function_addr

get_abstract_locations(*addr*, *size*)

Get a list of abstract locations that is within the range of [*addr*, *addr* + *size*]

This implementation is pretty slow. But since this method won't be called frequently, we can live with the bad implementation for now.

Parameters

- **addr** – Starting address of the memory region.
- **size** – Size of the memory region, in bytes.

Returns

A list of covered `AbstractLocation` objects, or an empty list if there is none.

store(*addr*, *data*, *bbl_addr=None*, *stmt_id=None*, *ins_addr=None*, *endness=None*, ***kwargs*)

load(*addr*, *size=None*, *bbl_addr=None*, *stmt_idx=None*, *ins_addr=None*, ***kwargs*)

merge(*others*, *merge_conditions*, *common_ancestor=None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the "real owner", who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you "deepen" both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

`widen(others)`

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

`dbg_print(indent=0)`

Print out debugging information

state: `angr.SimState`

```
class angr.storage.memory_mixins.regioned_memory.abstract_merger_mixin.AbstractMergerMixin(memory_id=None,
                                                                                               end-
                                                                                               ness='Iend_BE')
```

Bases: `MemoryMixin`

state: `angr.SimState`

```
class angr.storage.memory_mixins.regioned_memory.regioned_address_concretization_mixin.RegionedAddressC
```

Bases: `MemoryMixin`

```
__init__(read_strategies=None, write_strategies=None, **kwargs)
```

`set_state(state)`

Sets a new state (for example, if the state has been branched)

`copy(memo=None, **kwargs)`

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin’s class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

`merge(others, merge_conditions, common_ancestor=None)`

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin’s referees as the “real owner”, who should be the one to actually merge it. This technique doesn’t work to

resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be `n` `others` and `n+1` merge conditions, since the first condition corresponds to `self`. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both `others` and `common_ancestor` before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, `merge_conditions` can be `None`, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

state: `angr.SimState`

class `angr.storage.memory_mixins.slotted_memory.SlottedMemoryMixin`(`width=None`, `**kwargs`)

Bases: `MemoryMixin`

__init__(`width=None`, `**kwargs`)

set_state(`state`)

Sets a new state (for example, if the state has been branched)

copy(`memo`)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=None)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* others and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both *others* and *common_ancestor* before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be None, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

bool

load(*addr*, *size*=None, *endness*=None, ***kwargs*)

store(*addr*, *data*, *size*=None, *endness*=None, ***kwargs*)

changed_bytes(*other*)

state: `angr.SimState`

```
class angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixin.TypedVariable(type_,
                                                                                       value)
```

Bases: `object`

__init__(*type_*, *value*)

type

value

```
class angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixin.KeyValueMemoryMixin(*args,
                                                                                          **kwargs)
```

Bases: *MemoryMixin*

```
__init__(*args, **kwargs)
```

```
load(key, none_if_missing=False, **kwargs)
```

```
store(key, data, type_=None, **kwargs)
```

```
copy(memo=None, **kwargs)
```

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

state: `angr.SimState`

```
class angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.JavaVmMemoryMixin(memory_id='mem',
                                                                                      stack=None,
                                                                                      heap=None,
                                                                                      vm_static_table=None,
                                                                                      load_strategies=None,
                                                                                      store_strategies=None,
                                                                                      max_array_size=1000,
                                                                                      **kwargs)
```

Bases: *MemoryMixin*

```
__init__(memory_id='mem', stack=None, heap=None, vm_static_table=None, load_strategies=None,
         store_strategies=None, max_array_size=1000, **kwargs)
```

```
static get_new_uuid()
```

Generate a unique id within the scope of the JavaVM memory. This, for example, is used for distinguishing memory objects of the same type (e.g. multiple instances of the same class).

```
store(addr, data, frame=0)
```

```
load(addr, frame=0, none_if_missing=False)
```

```
push_stack_frame()
```

```
pop_stack_frame()
```

property stack

```
store_array_element(array, idx, value)
```

```
store_array_elements(array, start_idx, data)
```

Stores either a single element or a range of elements in the array.

Parameters

- **array** – Reference to the array.
- **start_idx** – Starting index for the store.
- **data** – Either a single value or a list of values.

load_array_element(*array, idx*)

load_array_elements(*array, start_idx, no_of_elements*)

Loads either a single element or a range of elements from the array.

Parameters

- **array** – Reference to the array.
- **start_idx** – Starting index for the load.
- **no_of_elements** – Number of elements to load.

concretize_store_idx(*idx, strategies=None*)

Concretizes a store index.

Parameters

- **idx** – An expression for the index.
- **strategies** – A list of concretization strategies (to override the default).
- **min_idx** – Minimum value for a concretized index (inclusive).
- **max_idx** – Maximum value for a concretized index (exclusive).

Returns

A list of concrete indexes.

concretize_load_idx(*idx, strategies=None*)

Concretizes a load index.

Parameters

- **idx** – An expression for the index.
- **strategies** – A list of concretization strategies (to override the default).
- **min_idx** – Minimum value for a concretized index (inclusive).
- **max_idx** – Maximum value for a concretized index (exclusive).

Returns

A list of concrete indexes.

set_state(*state*)

Sets a new state (for example, if the state has been branched)

copy(*memo=None, **kwargs*)

Should return a copy of the plugin without any state attached. Should check the memo first, and add itself to memo if it ends up making a new copy.

In order to simplify using the memo, you should annotate implementations of this function with `SimStatePlugin.memo`

The base implementation of this function constructs a new instance of the plugin's class without calling its initializer. If you super-call down to it, make sure you instantiate all the fields in your copy method!

Parameters

memo – A dictionary mapping object identifiers (`id(obj)`) to their copied instance. Use this to avoid infinite recursion and diverged copies.

merge(*others*, *merge_conditions*, *common_ancestor*=*None*)

Should merge the state plugin with the provided others. This will be called by `state.merge()` after copying the target state, so this should mutate the current instance to merge with the others.

Note that when multiple instances of a single plugin object (for example, a file) are referenced in the state, it is important that merge only ever be called once. This should be solved by designating one of the plugin's referees as the “real owner”, who should be the one to actually merge it. This technique doesn't work to resolve the similar issue that arises during copying because merging doesn't produce a new reference to insert.

There will be *n* **others** and *n*+1 merge conditions, since the first condition corresponds to self. To match elements up to conditions, say `zip([self] + others, merge_conditions)`

When implementing this, make sure that you “deepen” both **others** and **common_ancestor** before calling sub-elements' merge methods, e.g.

```
self.foo.merge(
    [o.foo for o in others],
    merge_conditions,
    common_ancestor=common_ancestor.foo if common_ancestor is not None else None
)
```

During static analysis, *merge_conditions* can be *None*, in which case you should use `state.solver.union(values)`. TODO: fish please make this less bullshit

There is a utility `state.solver.ite_cases` which will help with constructing arbitrarily large merged ASTs. Use it like `self.bar = self.state.solver.ite_cases(zip(conditions[1:], [o.bar for o in others]), self.bar)`

Parameters

- **others** – the other state plugins to merge with
- **merge_conditions** – a symbolic condition for each of the plugins
- **common_ancestor** – a common ancestor of this plugin and the others being merged

Returns

True if the state plugins are actually merged.

Return type

`bool`

widen(*others*)

The widening operation for plugins. Widening is a special kind of merging that produces a more general state from several more specific states. It is used only during intensive static analysis. The same behavior regarding copying and mutation from `merge` should be followed.

Parameters

others – the other state plugin

Returns

True if the state plugin is actually widened.

Return type

`bool`

state: `angr.SimState`

10.6 Concretization Strategies

`class angr.concretization_strategies.single.SimConcretizationStrategySingle`(*filter=None*,
exact=True)

Bases: `SimConcretizationStrategy`

Concretization strategy that ensures a single solution for an address.

`class angr.concretization_strategies.eval.SimConcretizationStrategyEval`(*limit*, ***kwargs*)

Bases: `SimConcretizationStrategy`

Concretization strategy that resolves an address into some limited number of solutions. Always handles the concretization, but only returns a maximum of limit number of solutions. Therefore, should only be used as the fallback strategy.

`__init__`(*limit*, ***kwargs*)

Initializes the base `SimConcretizationStrategy`.

Parameters

- **filter** – A function, taking arguments of (`SimMemory`, `claripy.AST`) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: `True`) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

`class angr.concretization_strategies.norepeats.SimConcretizationStrategyNorepeats`(*repeat_expr*,
repeat_constraints=None,
***kwargs*)

Bases: `SimConcretizationStrategy`

Concretization strategy that resolves addresses, without repeating.

`__init__`(*repeat_expr*, *repeat_constraints=None*, ***kwargs*)

Initializes the base `SimConcretizationStrategy`.

Parameters

- **filter** – A function, taking arguments of (`SimMemory`, `claripy.AST`) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: `True`) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

`copy`()

Returns a copy of the strategy, if there is data that should be kept separate between states. If not, returns self.

`merge`(*others*)

Merges this strategy with others (if there is data that should be kept separate between states. If not, is a no-op.

```
class angr.concretization_strategies.solutions.SimConcretizationStrategySolutions(limit,
                                                                                   **kwargs)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that resolves an address into some limited number of solutions.

```
__init__(limit, **kwargs)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

```
class angr.concretization_strategies.nonzero_range.SimConcretizationStrategyNonzeroRange(limit,
                                                                                          **kwargs)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that resolves a range in a non-zero location.

```
__init__(limit, **kwargs)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

```
class angr.concretization_strategies.range.SimConcretizationStrategyRange(limit, **kwargs)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that resolves addresses to a range.

```
__init__(limit, **kwargs)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

```
class angr.concretization_strategies.max.SimConcretizationStrategyMax(max_addr=None)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that returns the maximum address.

Parameters

max_addr ([int](#) | [None](#)) –

```
__init__(max_addr=None)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.
- **max_addr** (*int* | *None*) –

```
class angr.concretization_strategies.norepeats_range.SimConcretizationStrategyNorepeatsRange(repeat_expr,
                                                                                          min=None,
                                                                                          gran-
                                                                                          u-
                                                                                          lar-
                                                                                          ity=None,
                                                                                          **kwargs)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that resolves a range, with no repeats.

```
__init__(repeat_expr, min=None, granularity=None, **kwargs)
```

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

copy()

Returns a copy of the strategy, if there is data that should be kept separate between states. If not, returns self.

merge(*others*)

Merges this strategy with others (if there is data that should be kept separate between states. If not, is a no-op.

```
class angr.concretization_strategies.nonzero.SimConcretizationStrategyNonzero(filter=None,
                                                                                   exact=True)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that returns any non-zero solution.

```
class angr.concretization_strategies.any.SimConcretizationStrategyAny(filter=None,
                                                                           exact=True)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that returns any single solution.

```
class angr.concretization_strategies.controlled_data.SimConcretizationStrategyControlledData(limit,
                                                                                             fixed_addrs,
                                                                                             **kwargs)
```

Bases: [SimConcretizationStrategy](#)

Concretization strategy that constraints the address to controlled data. Controlled data consists of symbolic data and the addresses given as arguments. memory.

`__init__(limit, fixed_addrs, **kwargs)`

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

class `angr.concretization_strategies.unlimited_range.SimConcretizationStrategyUnlimitedRange`(*limit*, ***kwargs*)

Bases: `SimConcretizationStrategy`

Concretization strategy that resolves addresses to a range without checking if the number of possible addresses is within the limit.

`__init__(limit, **kwargs)`

Initializes the base SimConcretizationStrategy.

Parameters

- **filter** – A function, taking arguments of (SimMemory, claripy.AST) that determines if this strategy can handle resolving the provided AST.
- **exact** – A flag (default: True) that determines if the convenience resolution functions provided by this class use exact or approximate resolution.

10.7 Simulation Manager

class `angr.sim_manager.SimulationManager`(*project*, *active_states=None*, *stashes=None*, *hierarchy=None*, *resilience=None*, *save_unsat=False*, *auto_drop=None*, *errored=None*, *completion_mode=<built-in function any>*, *techniques=None*, *suggestions=True*, ***kwargs*)

Bases: `object`

The Simulation Manager is the future future.

Simulation managers allow you to wrangle multiple states in a slick way. States are organized into “stashes”, which you can step forward, filter, merge, and move around as you wish. This allows you to, for example, step two different stashes of states at different rates, then merge them together.

Stashes can be accessed as attributes (i.e. `.active`). A multiplexed stash can be retrieved by prepending the name with *mp_*, e.g. `.mp_active`. A single state from the stash can be retrieved by prepending the name with *one_*, e.g. `.one_active`.

Note that you shouldn’t usually be constructing SimulationManagers directly - there is a convenient shortcut for creating them in `Project.factory`: see [angr.factory.AngrobjectFactory](#).

The most important methods you should look at are `step`, `explore`, and `use_technique`.

Parameters

- **project** (`angr.project.Project`) – A Project instance.
- **stashes** – A dictionary to use as the stash store.
- **active_states** – Active states to seed the “active” stash with.
- **hierarchy** – A StateHierarchy object to use to track the relationships between states.

- **resilience** – A set of errors to catch during stepping to put a state in the `errored` list. You may also provide the values `False`, `None` (default), or `True` to catch, respectively, no errors, all `angr`-specific errors, and a set of many common errors.
- **save_unsat** – Set to `True` in order to introduce unsatisfiable states into the `unsat` stash instead of discarding them immediately.
- **auto_drop** – A set of stash names which should be treated as garbage chutes.
- **completion_mode** – A function describing how multiple exploration techniques with the complete hook set will interact. By default, the builtin function `any`.
- **techniques** – A list of techniques that should be pre-set to use with this manager.
- **suggestions** – Whether to automatically install the `Suggestions` exploration technique. Default `True`.

Variables

- **errored** – Not a stash, but a list of `ErrorRecords`. Whenever a step raises an exception that we catch, the state and some information about the error are placed in this list. You can adjust the list of caught exceptions with the *resilience* parameter.
- **stashes** – All the stashes on this instance, as a dictionary.
- **completion_mode** – A function describing how multiple exploration techniques with the complete hook set will interact. By default, the builtin function `any`.

`ALL = '_ALL'`

`DROP = '_DROP'`

`__init__(project, active_states=None, stashes=None, hierarchy=None, resilience=None, save_unsat=False, auto_drop=None, errored=None, completion_mode=<built-in function any>, techniques=None, suggestions=True, **kwargs)`

`active: List[SimState]`

`stashed: List[SimState]`

`pruned: List[SimState]`

`unsat: List[SimState]`

`deadended: List[SimState]`

`unconstrained: List[SimState]`

`found: List[SimState]`

`one_active: SimState`

`one_stashed: SimState`

`one_pruned: SimState`

`one_unsat: SimState`

`one_deadended: SimState`

`one_unconstrained: SimState`

one_found: [*SimState*](#)

property errored

property stashes: [*DefaultDict\[str, List\[SimState\]\]*](#)

mulpyplex(*stashes)

Mulpyplex across several stashes.

Parameters

stashes – the stashes to mulpyplex

Returns

a mulpyplexed list of states from the stashes in question, in the specified order

copy(deep=False)

Make a copy of this simulation manager. Pass `deep=True` to copy all the states in it as well.

If the current callstack includes hooked methods, the already-called methods will not be included in the copy.

use_technique(tech)

Use an exploration technique with this SimulationManager.

Techniques can be found in [*angr.exploration_techniques*](#).

Parameters

tech ([*ExplorationTechnique*](#)) – An ExplorationTechnique object that contains code to modify this SimulationManager’s behavior.

Returns

The technique that was added, for convenience

remove_technique(tech)

Remove an exploration technique from a list of active techniques.

Parameters

tech ([*ExplorationTechnique*](#)) – An ExplorationTechnique object.

explore(stash='active', n=None, find=None, avoid=None, find_stash='found', avoid_stash='avoid', cfg=None, num_find=1, avoid_priority=False, **kwargs)

Tick stash “stash” forward (up to “n” times or until “num_find” states are found), looking for condition “find”, avoiding condition “avoid”. Stores found states into “find_stash” and avoided states into “avoid_stash”.

The “find” and “avoid” parameters may be any of:

- An address to find
- A set or list of addresses to find
- A function that takes a state and returns whether or not it matches.

If an angr CFG is passed in as the “cfg” parameter and “find” is either a number or a list or a set, then any states which cannot possibly reach a success state without going through a failure state will be preemptively avoided.

run(stash='active', n=None, until=None, **kwargs)

Run until the SimulationManager has reached a completed state, according to the current exploration techniques. If no exploration techniques that define a completion state are being used, run until there is nothing left to run.

Parameters

- **stash** – Operate on this stash
- **n** – Step at most this many times
- **until** – If provided, should be a function that takes a `SimulationManager` and returns `True` or `False`. Stepping will terminate when it is `True`.

Returns

The simulation manager, for chaining.

Return type

SimulationManager

`complete()`

Returns whether or not this manager has reached a “completed” state.

step(*stash='active', target_stash=None, n=None, selector_func=None, step_func=None, error_list=None, successor_func=None, until=None, filter_func=None, **run_args*)

Step a stash of states forward and categorize the successors appropriately.

The parameters to this function allow you to control everything about the stepping and categorization process.

Parameters

- **stash** – The name of the stash to step (default: ‘active’)
- **target_stash** – The name of the stash to put the results in (default: same as `stash`)
- **error_list** – The list to put `ErroredState` objects in (default: `self.errorred`)
- **selector_func** – If provided, should be a function that takes a state and returns a boolean. If `True`, the state will be stepped. Otherwise, it will be kept as-is.
- **step_func** – If provided, should be a function that takes a `SimulationManager` and returns a `SimulationManager`. Will be called with the `SimulationManager` at every step. Note that this function should not actually perform any stepping - it is meant to be a maintenance function called after each step.
- **successor_func** – If provided, should be a function that takes a state and return its successors. Otherwise, `project.factory.successors` will be used.
- **filter_func** – If provided, should be a function that takes a state and return the name of the stash, to which the state should be moved.
- **until** – (DEPRECATED) If provided, should be a function that takes a `SimulationManager` and returns `True` or `False`. Stepping will terminate when it is `True`.
- **n** – (DEPRECATED) The number of times to step (default: 1 if “until” is not provided)

Additionally, you can pass in any of the following keyword args for `project.factory.successors`:

Parameters

- **jumpkind** – The jumpkind of the previous exit
- **addr** – An address to execute at instead of the state’s ip.
- **stmt_whitelist** – A list of stmt indexes to which to confine execution.
- **last_stmt** – A statement index at which to stop execution.
- **thumb** – Whether the block should be lifted in ARM’s THUMB mode.

- **backup_state** – A state to read bytes from instead of using project memory.
- **opt_level** – The VEX optimization level to use.
- **insn_bytes** – A string of bytes to use for the block instead of the project.
- **size** – The maximum size of the block, in bytes.
- **num_inst** – The maximum number of instructions.
- **traceflags** – traceflags to be passed to VEX. Default: 0

Returns

The simulation manager, for chaining.

Return type

SimulationManager

step_state(state, successor_func=None, error_list=None, **run_args)

Don't use this function manually - it is meant to interface with exploration techniques.

filter(state, filter_func=None)

Don't use this function manually - it is meant to interface with exploration techniques.

selector(state, selector_func=None)

Don't use this function manually - it is meant to interface with exploration techniques.

successors(state, successor_func=None, **run_args)

Don't use this function manually - it is meant to interface with exploration techniques.

prune(filter_func=None, from_stash='active', to_stash='pruned')

Prune unsatisfiable states from a stash.

This function will move all unsatisfiable states in the given stash into a different stash.

Parameters

- **filter_func** – Only prune states that match this filter.
- **from_stash** – Prune states from this stash. (default: 'active')
- **to_stash** – Put pruned states in this stash. (default: 'pruned')

Returns

The simulation manager, for chaining.

Return type

SimulationManager

populate(stash, states)

Populate a stash with a collection of states.

Parameters

- **stash** – A stash to populate.
- **states** – A list of states with which to populate the stash.

absorb(simgr)

Collect all the states from simgr and put them in their corresponding stashes in this manager. This will not modify simgr.

move(*from_stash*, *to_stash*, *filter_func*=None)

Move states from one stash to another.

Parameters

- **from_stash** – Take matching states from this stash.
- **to_stash** – Put matching states into this stash.
- **filter_func** – Stash states that match this filter. Should be a function that takes a state and returns True or False. (default: stash all states)

Returns

The simulation manager, for chaining.

Return type

SimulationManager

stash(*filter_func*=None, *from_stash*='active', *to_stash*='stashed')

Stash some states. This is an alias for move(), with defaults for the stashes.

Parameters

- **filter_func** – Stash states that match this filter. Should be a function that takes a state and returns True or False. (default: stash all states)
- **from_stash** – Take matching states from this stash. (default: 'active')
- **to_stash** – Put matching states into this stash. (default: 'stashed')

Returns

The simulation manager, for chaining.

Return type

SimulationManager

unstash(*filter_func*=None, *to_stash*='active', *from_stash*='stashed')

Unstash some states. This is an alias for move(), with defaults for the stashes.

Parameters

- **filter_func** – Unstash states that match this filter. Should be a function that takes a state and returns True or False. (default: unstash all states)
- **from_stash** – take matching states from this stash. (default: 'stashed')
- **to_stash** – put matching states into this stash. (default: 'active')

Returns

The simulation manager, for chaining.

Return type

SimulationManager

drop(*filter_func*=None, *stash*='active')

Drops states from a stash. This is an alias for move(), with defaults for the stashes.

Parameters

- **filter_func** – Drop states that match this filter. Should be a function that takes a state and returns True or False. (default: drop all states)
- **stash** – Drop matching states from this stash. (default: 'active')

Returns

The simulation manager, for chaining.

Return type*SimulationManager***apply**(*state_func=None, stash_func=None, stash='active', to_stash=None*)

Applies a given function to a given stash.

Parameters

- **state_func** – A function to apply to every state. Should take a state and return a state. The returned state will take the place of the old state. If the function *doesn't* return a state, the old state will be used. If the function returns a list of states, they will replace the original states.
- **stash_func** – A function to apply to the whole stash. Should take a list of states and return a list of states. The resulting list will replace the stash. If both `state_func` and `stash_func` are provided `state_func` is applied first, then `stash_func` is applied on the results.
- **stash** – A stash to work with.
- **to_stash** – If specified, this stash will be used to store the resulting states instead.

Returns

The simulation manager, for chaining.

Return type*SimulationManager***split**(*stash_splitter=None, stash_ranker=None, state_ranker=None, limit=8, from_stash='active', to_stash='stashed'*)

Split a stash of states into two stashes depending on the specified options.

The stash `from_stash` will be split into two stashes depending on the other options passed in. If `to_stash` is provided, the second stash will be written there.

`stash_splitter` overrides `stash_ranker`, which in turn overrides `state_ranker`. If no functions are provided, the states are simply split according to the limit.

The sort done with `state_ranker` is ascending.

Parameters

- **stash_splitter** – A function that should take a list of states and return a tuple of two lists (the two resulting stashes).
- **stash_ranker** – A function that should take a list of states and return a sorted list of states. This list will then be split according to “limit”.
- **state_ranker** – An alternative to `stash_splitter`. States will be sorted with outputs of this function, which are to be used as a key. The first “limit” of them will be kept, the rest split off.
- **limit** – For use with `state_ranker`. The number of states to keep. Default: 8
- **from_stash** – The stash to split (default: ‘active’)
- **to_stash** – The stash to write to (default: ‘stashed’)

Returns

The simulation manager, for chaining.

Return type*SimulationManager*

merge(*merge_func=None, merge_key=None, stash='active', prune=True*)

Merge the states in a given stash.

Parameters

- **stash** – The stash (default: ‘active’)
- **merge_func** – If provided, instead of using `state.merge`, call this function with the states as the argument. Should return the merged state.
- **merge_key** – If provided, should be a function that takes a state and returns a key that will compare equal for all states that are allowed to be merged together, as a first approximation. By default: uses PC, callstack, and open file descriptors.
- **prune** – Whether to prune the stash prior to merging it

Returns

The simulation manager, for chaining.

Return type

SimulationManager

class `angr.sim_manager.ErrorRecord`(*state, error, traceback*)

Bases: `object`

A container class for a state and an error that was thrown during its execution. You can find these in `SimulationManager.errorred`.

Variables

- **state** – The state that encountered an error, at the point in time just before the erroring step began.
- **error** – The error that was thrown.
- **traceback** – The traceback for the error that was thrown.

__init__(*state, error, traceback*)

debug()

Launch a postmortem debug shell at the site of the error.

reraise()

class `angr.state_hierarchy.StateHierarchy`

Bases: `object`

The state hierarchy holds weak references to `SimStateHistory` objects in a directed acyclic graph. It is useful for queries about a state’s ancestry, notably “what is the best ancestor state for a merge among these states” and “what is the most recent unsatisfiable state while using `LAZY_SOLVES`”

__init__()

get_ref(*obj*)

dead_ref(*ref*)

defer_cleanup()

add_state(*s*)

add_history(*h*)

simplify()

full_simplify()

lineage(*h*)

Returns the lineage of histories leading up to *h*.

all_successors(*h*)

history_successors(*h*)

history_predecessors(*h*)

history_contains(*h*)

unreachable_state(*state*)

unreachable_history(*h*)

most_mergeable(*states*)

Find the “most mergeable” set of states from those provided.

Parameters

states – a list of states

Returns

a tuple of: (list of states to merge, those states’ common history, list of states to not merge yet)

10.8 Exploration Techniques

class `angr.exploration_techniques.ExplorationTechnique`

Bases: `object`

An `otiegnqvwk` is a set of hooks for a simulation manager that assists in the implementation of new techniques in symbolic exploration.

TODO: choose actual name for the functionality (techniques? strategies?)

Any number of these methods may be overridden by a subclass. To use an exploration technique, call `simgr.use_technique` with an *instance* of the technique.

`__init__()`

`setup(simgr)`

Perform any initialization on this manager you might need to do.

Parameters

`simgr` (`angr.SimulationManager`) – The simulation manager to which you have just been added

`step(simgr, stash=‘active’, **kwargs)`

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **`simgr`** (`angr.SimulationManager`) –

- **stash**(*str*) –

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr**(`angr.SimulationManager`) –
- **state**(`angr.SimState`) –

selector(*simgr*, *state*, ***kwargs*)

Determine if a state should participate in the current round of stepping. Return True if the state should be stepped, and False if the state should not be stepped. To defer to the original selection procedure, return the result of `simgr.selector(state, **kwargs)`.

If the user provided a `selector_func` in their step or run command, it will appear here.

Parameters

- **simgr**(`angr.SimulationManager`) –
- **state**(`angr.SimState`) –

step_state(*simgr*, *state*, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr**(`angr.SimulationManager`) –
- **state**(`angr.SimState`) –

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a *SimSuccessors* object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr**(`angr.SimulationManager`) –
- **state**(`angr.SimState`) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

simgr (`angr.SimulationManager`) –

class `angr.exploration_techniques.Slicecutor`(*annotated_cfg*, *force_taking_exit=False*,
force_sat=False)

Bases: `ExplorationTechnique`

The Slicecutor is an exploration that executes provided code slices.

Parameters

force_sat (`bool`) –

__init__(*annotated_cfg*, *force_taking_exit=False*, *force_sat=False*)

All parameters except *annotated_cfg* are optional.

Parameters

- **annotated_cfg** – The AnnotatedCFG that provides the code slice.
- **force_taking_exit** – Set to True if you want to create a successor based on our slice in case of unconstrained successors.
- **force_sat** (`bool`) – If a branch specified by the slice is unsatisfiable, set this option to True if you want to force it to be satisfiable and be taken anyway.

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (`angr.SimulationManager`) – The simulation manager to which you have just been added

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

step_state(*simgr*, *state*, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a `SimSuccessors` object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to

look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

successors(*simgr, state, **kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.DrillerCore`(*trace, fuzz_bitmap=None*)

Bases: [*ExplorationTechnique*](#)

An exploration technique that symbolically follows an input looking for new state transitions.

It has to be used with Tracer exploration technique. Results are put in ‘diverted’ stash.

__init__(*trace, fuzz_bitmap=None*)

:param trace : The basic block trace. :type fuzz_bitmap: :param fuzz_bitmap: AFL’s bitmap of state transitions. Defaults to saying every transition is worth satisfying.

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr, stash='active', **kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

class `angr.exploration_techniques.LoopSeer`(*cfg=None, functions=None, loops=None, use_header=False, bound=None, bound_reached=None, discard_stash='spinning', limit_concrete_loops=True*)

Bases: [*ExplorationTechnique*](#)

This exploration technique monitors exploration and maintains all loop-related data (well, currently it is just the loop trip counts, but feel free to add something else).

__init__(*cfg=None, functions=None, loops=None, use_header=False, bound=None, bound_reached=None, discard_stash='spinning', limit_concrete_loops=True*)

Parameters

- **cfg** – Normalized CFG is required.
- **functions** – Function(s) containing the loop(s) to be analyzed.
- **loops** – Specific group of Loop(s) to be analyzed, if this is None we run the LoopFinder analysis.
- **use_header** – Whether to use header based trip counter to compare with the bound limit.
- **bound** – Limit the number of iterations a loop may be executed.
- **bound_reached** – If provided, should be a function that takes the LoopSeer and the succ_state. Will be called when loop execution reach the given bound. Default to moving states that exceed the loop limit to a discard stash.
- **discard_stash** – Name of the stash containing states exceeding the loop limit.
- **limit_concrete_loops** – If False, do not limit a loop back-edge if it is the only successor (Defaults to True to maintain the original behavior)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (*angr.SimulationManager*) – The simulation manager to which you have just been added

filter(*simgr, state, **kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (*angr.SimulationManager*) –
- **state** (*angr.SimState*) –

successors(*simgr, state, **kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (*angr.SimulationManager*) –
- **state** (*angr.SimState*) –


```
class angr.exploration_techniques.Tracer(trace=None, resiliency=False, keep_predecessors=1,
                                         crash_addr=None, syscall_data=None, copy_states=False,
                                         fast_forward_to_entry=True, mode='strict', aslr=True,
                                         follow_unsat=False)
```

Bases: [ExplorationTechnique](#)

An exploration technique that follows an angr path with a concrete input. The tracing result is the state at the last address of the trace, which can be found in the ‘traced’ stash.

If the given concrete input makes the program crash, you should provide crash_addr, and the crashing state will be found in the ‘crashed’ stash.

Parameters

- **trace** – The basic block trace.
- **resiliency** – Should we continue to step forward even if qemu and angr disagree?
- **keep_predecessors** – Number of states before the final state we should log.
- **crash_addr** – If the trace resulted in a crash, provide the crashing instruction pointer here, and the ‘crashed’ stash will be populated with the crashing state.
- **syscall_data** – Data related to various syscalls recorded by tracer for replaying
- **copy_states** – Whether COPY_STATES should be enabled for the tracing state. It is off by default because most tracing workloads benefit greatly from not performing copying. You want to enable it if you want to see the missed states. It will be re-added for the last 2% of the trace in order to set the predecessors list correctly. If you turn this on you may want to enable the LAZY_SOLVES option.
- **mode** – Tracing mode.
- **aslr** – Whether there are aslr slides. if not, tracer uses trace address as state address.
- **follow_unsat** – Whether unsatisfiable states should be treated as potential successors or not.

Variables

predecessors – A list of states in the history before the final state.

```
__init__(trace=None, resiliency=False, keep_predecessors=1, crash_addr=None, syscall_data=None,
          copy_states=False, fast_forward_to_entry=True, mode='strict', aslr=True, follow_unsat=False)
```

```
set_fd_data(fd_data)
```

Set concrete bytes of various fds read by the program

Parameters

fd_data (*Dict*[*int*, *bytes*]) –

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

```
complete(simgr)
```

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques' completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

• `simgr` (`angr.SimulationManager`) –

filter(`simgr`, `state`, `**kwargs`)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- `simgr` (`angr.SimulationManager`) –
- `state` (`angr.SimState`) –

step(`simgr`, `stash='active'`, `**kwargs`)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- `simgr` (`angr.SimulationManager`) –
- `stash` (`str`) –

step_state(`simgr`, `state`, `**kwargs`)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a `SimSuccessors` object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the `filter` hook - `filter` is only applied to states returned from here in the None stash.

Parameters

- `simgr` (`angr.SimulationManager`) –
- `state` (`angr.SimState`) –

classmethod `crash_windup`(`state`, `crash_addr`)

```
class angr.exploration_techniques.Explorer(find=None, avoid=None, find_stash='found',
                                           avoid_stash='avoid', cfg=None, num_find=1,
                                           avoid_priority=False)
```

Bases: `ExplorationTechnique`

Search for up to “num_find” paths that satisfy condition “find”, avoiding condition “avoid”. Stashes found paths into “find_stash” and avoided paths into “avoid_stash”.

The “find” and “avoid” parameters may be any of:

- An address to find

- A set or list of addresses to find
- A function that takes a path and returns whether or not it matches.

If an `angr` CFG is passed in as the “`cfg`” parameter and “`find`” is either a number or a list or a set, then any paths which cannot possibly reach a success state without going through a failure state will be preemptively avoided.

If either the “`find`” or “`avoid`” parameter is a function returning a boolean, and a path triggers both conditions, it will be added to the find stash, unless “`avoid_priority`” is set to `True`.

```
__init__(find=None, avoid=None, find_stash='found', avoid_stash='avoid', cfg=None, num_find=1,
        avoid_priority=False)
```

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return `True` or `False`. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

simgr (`angr.SimulationManager`) –

class `angr.exploration_techniques.Threading`(*threads*=8, *local_stash*='thread_local')

Bases: [ExplorationTechnique](#)

Enable multithreading.

This is only useful in paths where a lot of time is taken inside `z3`, doing constraint solving. This is because of python’s GIL, which says that only one thread at a time may be executing python code.

__init__(*threads*=8, *local_stash*='thread_local')

step(*simgr*, *stash*='active', *error_list*=None, *target_stash*=None, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

inner_step(*state*, *simgr*, ***kwargs*)

successors(*simgr*, *state*, *engine*=None, ***kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the *kwargs* for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.DFS`(*deferred_stash*='deferred')

Bases: `ExplorationTechnique`

Depth-first search.

Will only keep one path active at a time, any others will be stashed in the ‘deferred’ stash. When we run out of active paths to step, we take the longest one from deferred and continue.

__init__(*deferred_stash*='deferred')

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

class `angr.exploration_techniques.LengthLimiter`(*max_length*, *drop*=False)

Bases: `ExplorationTechnique`

Length limiter on paths.

__init__(*max_length*, *drop*=False)

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

class `angr.exploration_techniques.Veritesting`(***options*)

Bases: `ExplorationTechnique`

Enable veritesting. This technique, described in a paper[1] from CMU, attempts to address the problem of state explosions in loops by performing smart merging.

[1] <https://users.ece.cmu.edu/~aavgerin/papers/veritesting-icse-2014.pdf>

__init__(***options*)

step_state(*simgr*, *state*, *successor_func*=None, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.Oppologist`

Bases: `ExplorationTechnique`

The Oppologist is an exploration technique that forces uncooperative code through qemu.

__init__()

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a *SimSuccessors* object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the *kwargs* for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a *successor_func* in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

```
class angr.exploration_techniques.Director(peek_blocks=100, peek_functions=5, goals=None,
                                          cfg_keep_states=False, goal_satisfied_callback=None,
                                          num_fallback_states=5)
```

Bases: [ExplorationTechnique](#)

An exploration technique for directed symbolic execution.

A control flow graph (using CFGEmulated) is built and refined during symbolic execution. Each time the execution reaches a block that is outside of the CFG, the CFG recovery will be triggered with that state, with a maximum recovery depth (100 by default). If we see a basic block during state stepping that is not yet in the control flow graph, we go back to control flow graph recovery and “peek” more blocks forward.

When stepping a simulation manager, all states are categorized into three different categories:

- Might reach the destination within the peek depth. Those states are prioritized.
- Will not reach the destination within the peek depth. Those states are de-prioritized. However, there is a little chance for those states to be explored as well in order to prevent over-fitting.

```
__init__(peek_blocks=100, peek_functions=5, goals=None, cfg_keep_states=False,
          goal_satisfied_callback=None, num_fallback_states=5)
```

Constructor.

```
step(simgr, stash='active', **kwargs)
```

Parameters

- **simgr** –
- **stash** –
- **kwargs** –

Returns

```
add_goal(goal)
```

Add a goal.

Parameters

goal ([BaseGoal](#)) – The goal to add.

Returns

None

```
class angr.exploration_techniques.ExecuteAddressGoal(addr)
```

Bases: [BaseGoal](#)

A goal that prioritizes states reaching (or are likely to reach) certain address in some specific steps.

```
__init__(addr)
```

```
check(cfg, state, peek_blocks)
```

Check if the specified address will be executed

Parameters

- **cfg** –
- **state** –
- **peek_blocks** ([int](#)) –

Returns

Return type

bool

check_state(state)

Check if the current address is the target address.

Parameters
state ([angr.SimState](#)) – The state to check.

Returns

True if the current address is the target address, False otherwise.

Return type

bool

class [angr.exploration_techniques.CallFunctionGoal](#)(*function*, *arguments*)

 Bases: [BaseGoal](#)

A goal that prioritizes states reaching certain function, and optionally with specific arguments. Note that constraints on arguments (and on function address as well) have to be identifiable on an accurate CFG. For example, you may have a CallFunctionGoal saying “call printf with the first argument being ‘Hello, world’”, and CFGEmulated must be able to figure out the first argument to printf is in fact “Hello, world”, not some symbolic strings that will be constrained to “Hello, world” during symbolic execution (or simulation, however you put it).

REQUIRE_CFG_STATES = True
__init__(*function*, *arguments*)

check(*cfg*, *state*, *peek_blocks*)

Check if the specified function will be reached with certain arguments.

Parameters

- **cfg** –
- **state** –
- **peek_blocks** –

Returns
check_state(state)

Check if the specific function is reached with certain arguments

Parameters
state ([angr.SimState](#)) – The state to check

Returns

True if the function is reached with certain arguments, False otherwise.

Return type

bool

class [angr.exploration_techniques.Spiller](#)(*src_stash*='active', *min*=5, *max*=10, *staging_stash*='spill_stage', *staging_min*=10, *staging_max*=20, *pickle_callback*=None, *unpickle_callback*=None, *post_pickle_callback*=None, *priority_key*=None, *vault*=None, *states_collection*=None)

 Bases: [ExplorationTechnique](#)

Automatically spill states out. It can spill out states to a different stash, spill them out to ANA, or first do the former and then (after enough states) the latter.

```
__init__(src_stash='active', min=5, max=10, staging_stash='spill_stage', staging_min=10,
         staging_max=20, pickle_callback=None, unpickle_callback=None, post_pickle_callback=None,
         priority_key=None, vault=None, states_collection=None)
```

Initializes the spiller.

Parameters

- **max** – the number of states that are *not* spilled
- **src_stash** – the stash from which to spill states (default: active)
- **staging_stash** – the stash *to* which to spill states (default: “spill_stage”)
- **staging_max** – the number of states that can be in the staging stash before things get spilled to ANA (default: None. If staging_stash is set, then this means unlimited, and ANA will not be used).
- **priority_key** – a function that takes a state and returns its numerical priority (MAX_INT is lowest priority). By default, self.state_priority will be used, which prioritizes by object ID.
- **vault** – an `angr.Vault` object to handle storing and loading of states. If not provided, an `angr.vaults.VaultShelf` will be created with a temporary file.

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –

```
static state_priority(state)
```

```
class angr.exploration_techniques.ManualMergepoint(address, wait_counter=10, prune=True)
```

Bases: [ExplorationTechnique](#)

```
__init__(address, wait_counter=10, prune=True)
```

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

```
mark_nofilter(simgr, stash)
```

```
mark_okfilter(simgr, stash)
```

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –


```
class angr.exploration_techniques.TechniqueBuilder(setup=None, step_state=None, step=None,
                                                    successors=None, filter=None, selector=None,
                                                    complete=None)
```

Bases: [ExplorationTechnique](#)

This meta technique could be used to hook a couple of simulation manager methods without actually creating a new exploration technique, for example:

```
class SomeComplexAnalysis(Analysis):
```

```
    def do_something():
```

```
        simgr = self.project.factory.simulation_manager() simgr.use_tech(ProxyTechnique(step_state=self._step_state))
        simgr.run()
```

```
    def _step_state(self, state):
```

```
        # Do stuff! pass
```

In the above example, the `_step_state` method can access all the necessary stuff, hidden in the analysis instance, without passing that instance to a one-shot-styled exploration technique.

```
__init__(setup=None, step_state=None, step=None, successors=None, filter=None, selector=None,
         complete=None)
```

```
class angr.exploration_techniques.StochasticSearch(start_state, restart_prob=0.0001)
```

Bases: [ExplorationTechnique](#)

Stochastic Search.

Will only keep one path active at a time, any others will be discarded. Before each pass through, weights are randomly assigned to each basic block. These weights form a probability distribution for determining which state remains after splits. When we run out of active paths to step, we start again from the start state.

```
__init__(start_state, restart_prob=0.0001)
```

Parameters

- **start_state** – The initial state from which exploration stems.
- **restart_prob** – The probability of randomly restarting the search (default 0.0001).

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

```
class angr.exploration_techniques.UniqueSearch(similarity_func=None, deferred_stash='deferred')
```

Bases: [ExplorationTechnique](#)

Unique Search.

Will only keep one path active at a time, any others will be deferred. The state that is explored depends on how unique it is relative to the other deferred states. A path's uniqueness is determined by its average similarity between the other (deferred) paths. Similarity is calculated based on the supplied *similarity_func*, which by default is: The (L2) distance between the counts of the state addresses in the history of the path.

__init__(*similarity_func=None, deferred_stash='deferred'*)

Parameters

- **similarity_func** – How to calculate similarity between two states.
- **deferred_stash** – Where to store the deferred states.

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (*angr.SimulationManager*) – The simulation manager to which you have just been added

step(*simgr, stash='active', **kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (*angr.SimulationManager*) –
- **stash** (*str*) –

static similarity(*state_a, state_b*)

The (L2) distance between the counts of the state addresses in the history of the path. :type state_a: :param state_a: The first state to compare :type state_b: :param state_b: The second state to compare

static sequence_matcher_similarity(*state_a, state_b*)

The *difflib.SequenceMatcher* ratio between the state addresses in the history of the path. :type state_a: :param state_a: The first state to compare :type state_b: :param state_b: The second state to compare

class `angr.exploration_techniques.Symbion`(*find=None, memory_concretize=None, register_concretize=None, timeout=0, find_stash='found'*)

Bases: [ExplorationTechnique](#)

The Symbion exploration technique uses the `SimEngineConcrete` available to step a `SimState`.

Parameters

- **find** – address or list of addresses that we want to reach, these will be translated into break-points inside the concrete process using the `ConcreteTarget` interface provided by the user inside the `SimEngineConcrete`.
- **memory_concretize** – list of tuples (address, symbolic variable) that are going to be written in the concrete process memory.
- **register_concretize** – list of tuples (reg_name, symbolic variable) that are going to be written
- **timeout** – how long we should wait the concrete target to reach the breakpoint

__init__(*find=None, memory_concretize=None, register_concretize=None, timeout=0, find_stash='found'*)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr (*angr.SimulationManager*) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

step_state(*simgr*, **args*, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

- **simgr** (`angr.SimulationManager`) –

class `angr.exploration_techniques.MemoryWatcher`(*min_memory*=512, *memory_stash*='lowmem')

Bases: [*ExplorationTechnique*](#)

Memory Watcher

Parameters

- **min_memory** (*int*, *optional*) – Minimum amount of free memory in MB before stopping execution (default: 95% memory use)
- **memory_stash** (*str*, *optional*) – What to call the low memory stash (default: 'lowmem')

At each step, keep an eye on how much memory is left on the system. Stash off states to effectively stop execution if we’re below a given threshold.

__init__(*min_memory*=512, *memory_stash*='lowmem')

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

class `angr.exploration_techniques.Bucketizer`

Bases: [ExplorationTechnique](#)

Loop bucketization: Pick $\log(n)$ paths out of n possible paths, and stash (or drop) everything else.

__init__()

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the `kwargs` for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

class `angr.exploration_techniques.LocalLoopSeer`(*bound*=None, *bound_reached*=None, *discard_stash*='spinning')

Bases: [ExplorationTechnique](#)

LocalLoopSeer monitors exploration and maintains all loop-related data without relying on a control flow graph.

__init__(*bound*=None, *bound_reached*=None, *discard_stash*='spinning')

Parameters

- **bound** – Limit the number of iterations a loop may be executed.
- **bound_reached** – If provided, should be a function that takes the LoopSeer and the `succ_state`. Will be called when loop execution reach the given bound. Default to moving states that exceed the loop limit to a discard stash.
- **discard_stash** – Name of the stash containing states exceeding the loop limit.

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a `SimSuccessors` object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the `kwargs` for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.Timeout`(*timeout=None*)

Bases: `ExplorationTechnique`

Timeout exploration technique that stops an active exploration if the run time exceeds a predefined timeout

__init__(*timeout=None*)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, *stash='active'*, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –

class `angr.exploration_techniques.Suggestions`

Bases: `ExplorationTechnique`

An exploration technique which analyzes failure cases and logs suggestions for how to mitigate them in future analyses.

__init__()

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –

static report(*state*, *event*)

class `angr.exploration_techniques.timeout.Timeout`(*timeout*=None)

Bases: `ExplorationTechnique`

Timeout exploration technique that stops an active exploration if the run time exceeds a predefined timeout

__init__(*timeout*=None)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –

class `angr.exploration_techniques.dfs.DFS`(*deferred_stash*='deferred')

Bases: `ExplorationTechnique`

Depth-first search.

Will only keep one path active at a time, any others will be stashed in the ‘deferred’ stash. When we run out of active paths to step, we take the longest one from deferred and continue.

__init__(*deferred_stash*='deferred')

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (`str`) –

```
class angr.exploration_techniques.explorer.Explorer(find=None, avoid=None, find_stash='found',
                                                    avoid_stash='avoid', cfg=None, num_find=1,
                                                    avoid_priority=False)
```

Bases: [ExplorationTechnique](#)

Search for up to “num_find” paths that satisfy condition “find”, avoiding condition “avoid”. Stashes found paths into “find_stash” and avoided paths into “avoid_stash”.

The “find” and “avoid” parameters may be any of:

- An address to find
- A set or list of addresses to find
- A function that takes a path and returns whether or not it matches.

If an angr CFG is passed in as the “cfg” parameter and “find” is either a number or a list or a set, then any paths which cannot possibly reach a success state without going through a failure state will be preemptively avoided.

If either the “find” or “avoid” parameter is a function returning a boolean, and a path triggers both conditions, it will be added to the find stash, unless “avoid_priority” is set to True.

```
__init__(find=None, avoid=None, find_stash='found', avoid_stash='avoid', cfg=None, num_find=1,
        avoid_priority=False)
```

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

simgr ([angr.SimulationManager](#)) –

class [angr.exploration_techniques.lengthlimiter.LengthLimiter](#)(*max_length*, *drop=False*)

Bases: [ExplorationTechnique](#)

Length limiter on paths.

__init__(*max_length*, *drop=False*)

step(*simgr*, *stash='active'*, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

class [angr.exploration_techniques.manual_mergepoint.ManualMergepoint](#)(*address*,
wait_counter=10,
prune=True)

Bases: [ExplorationTechnique](#)

__init__(*address*, *wait_counter=10*, *prune=True*)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

mark_nofilter(*simgr*, *stash*)

mark_okfilter(*simgr*, *stash*)

step(*simgr*, *stash='active'*, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

class [angr.exploration_techniques.spiller.PickledStatesBase](#)

Bases: [object](#)

The base class of pickled states

sort()

Sort pickled states.

add(*prio*, *sid*)

Add a newly pickled state.

Parameters

- **prio** (*int*) – Priority of the state.

- **sid** (*str*) – Persistent ID of the state.

Returns

None

pop_n(*n*)

Pop the top N states.

Parameters

- **n** (*int*) – Number of states to take.

Returns

A list of states.

class angr.exploration_techniques.spiller.PickledStatesList

Bases: *PickledStatesBase*

List-backed pickled state storage.

__init__()

sort()

Sort pickled states.

add(*prio*, *sid*)

Add a newly pickled state.

Parameters

- **prio** (*int*) – Priority of the state.
- **sid** (*str*) – Persistent ID of the state.

Returns

None

pop_n(*n*)

Pop the top N states.

Parameters

- **n** (*int*) – Number of states to take.

Returns

A list of states.

class angr.exploration_techniques.spiller.PickledStatesDb(*db_str='sqlite:///memory:'*)

Bases: *PickledStatesBase*

Database-backed pickled state storage.

__init__(*db_str='sqlite:///memory:'*)

sort()

Sort pickled states.

add(*prio*, *sid*, *taken=False*, *stash='spilled'*)

Add a newly pickled state.

Parameters

- **prio** (*int*) – Priority of the state.
- **sid** (*str*) – Persistent ID of the state.

Returns

None

pop_n(*n*, *stash*='spilled')

Pop the top N states.

Parameters

n (*int*) – Number of states to take.

Returns

A list of states.

get_recent_n(*n*, *stash*='spilled')

count()

```
class angr.exploration_techniques.spiller.Spiller(src_stash='active', min=5, max=10,
                                                  staging_stash='spill_stage', staging_min=10,
                                                  staging_max=20, pickle_callback=None,
                                                  unpickle_callback=None,
                                                  post_pickle_callback=None, priority_key=None,
                                                  vault=None, states_collection=None)
```

Bases: [ExplorationTechnique](#)

Automatically spill states out. It can spill out states to a different stash, spill them out to ANA, or first do the former and then (after enough states) the latter.

```
__init__(src_stash='active', min=5, max=10, staging_stash='spill_stage', staging_min=10,
         staging_max=20, pickle_callback=None, unpickle_callback=None, post_pickle_callback=None,
         priority_key=None, vault=None, states_collection=None)
```

Initializes the spiller.

Parameters

- **max** – the number of states that are *not* spilled
- **src_stash** – the stash from which to spill states (default: active)
- **staging_stash** – the stash *to* which to spill states (default: “spill_stage”)
- **staging_max** – the number of states that can be in the staging stash before things get spilled to ANA (default: None. If staging_stash is set, then this means unlimited, and ANA will not be used).
- **priority_key** – a function that takes a state and returns its numerical priority (MAX_INT is lowest priority). By default, self.state_priority will be used, which prioritizes by object ID.
- **vault** – an angr.Vault object to handle storing and loading of states. If not provided, an angr.vaults.VaultShelf will be created with a temporary file.

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

static state_priority(*state*)

class angr.exploration_techniques.spiller_db.**PickledState**(***kwargs*)

Bases: Base

id

priority

taken

stash

timestamp

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.exploration_techniques.threading.**Threading**(*threads*=8, *local_stash*='thread_local')

Bases: [ExplorationTechnique](#)

Enable multithreading.

This is only useful in paths where a lot of time is taken inside z3, doing constraint solving. This is because of python's GIL, which says that only one thread at a time may be executing python code.

__init__(*threads*=8, *local_stash*='thread_local')

step(*simgr*, *stash*='active', *error_list*=None, *target_stash*=None, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

inner_step(*state*, *simgr*, ***kwargs*)

successors(*simgr*, *state*, *engine*=None, ***kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

class `angr.exploration_techniques.veritestng.Veritestng`(**options)

Bases: [*ExplorationTechnique*](#)

Enable veritestng. This technique, described in a paper[1] from CMU, attempts to address the problem of state explosions in loops by performing smart merging.

[1] <https://users.ece.cmu.edu/~aavgerin/papers/veritestng-icse-2014.pdf>

__init__(**options)

step_state(simgr, state, successor_func=None, **kwargs)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.tracer.TracingMode`

Bases: [*object*](#)

Variables

- **Strict** – Strict mode, the default mode, where an exception is raised immediately if tracer's path deviates from the provided trace.
- **Permissive** – Permissive mode, where tracer attempts to force the path back to the provided trace when a deviation happens. This does not always work, especially when the cause of deviation is related to input that will later be used in exploit generation. But, it might work magically sometimes.
- **CatchDesync** – CatchDesync mode, catch desync because of `sim_procedures`. It might be a sign of something interesting.

Strict = 'strict'

Permissive = 'permissive'

CatchDesync = 'catch_desync'

exception `angr.exploration_techniques.tracer.TracerDesyncError`(msg, deviating_addr=None, deviating_trace_idx=None)

Bases: [*AngrTracerError*](#)

An error class to report tracing Tracing desynchronization error

__init__(msg, deviating_addr=None, deviating_trace_idx=None)

```
class angr.exploration_techniques.tracer.RepHook(mnemonic)
```

Bases: `object`

Hook rep movs/stos to speed up constraint solving TODO: This should be made an exploration technique later

```
__init__(mnemonic)
```

```
run(state)
```

```
class angr.exploration_techniques.tracer.Tracer(trace=None, resiliency=False, keep_predecessors=1,
                                                crash_addr=None, syscall_data=None,
                                                copy_states=False, fast_forward_to_entry=True,
                                                mode='strict', aslr=True, follow_unsat=False)
```

Bases: `ExplorationTechnique`

An exploration technique that follows an angr path with a concrete input. The tracing result is the state at the last address of the trace, which can be found in the ‘traced’ stash.

If the given concrete input makes the program crash, you should provide `crash_addr`, and the crashing state will be found in the ‘crashed’ stash.

Parameters

- **trace** – The basic block trace.
- **resiliency** – Should we continue to step forward even if qemu and angr disagree?
- **keep_predecessors** – Number of states before the final state we should log.
- **crash_addr** – If the trace resulted in a crash, provide the crashing instruction pointer here, and the ‘crashed’ stash will be populated with the crashing state.
- **syscall_data** – Data related to various syscalls recorded by tracer for replaying
- **copy_states** – Whether COPY_STATES should be enabled for the tracing state. It is off by default because most tracing workloads benefit greatly from not performing copying. You want to enable it if you want to see the missed states. It will be re-added for the last 2% of the trace in order to set the predecessors list correctly. If you turn this on you may want to enable the LAZY_SOLVES option.
- **mode** – Tracing mode.
- **aslr** – Whether there are aslr slides. if not, tracer uses trace address as state address.
- **follow_unsat** – Whether unsatisfiable states should be treated as potential successors or not.

Variables

predecessors – A list of states in the history before the final state.

```
__init__(trace=None, resiliency=False, keep_predecessors=1, crash_addr=None, syscall_data=None,
        copy_states=False, fast_forward_to_entry=True, mode='strict', aslr=True, follow_unsat=False)
```

```
set_fd_data(fd_data)
```

Set concrete bytes of various fds read by the program

Parameters

fd_data (`Dict[int, bytes]`) –

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

simgr (`angr.SimulationManager`) – The simulation manager to which you have just been added

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

simgr (`angr.SimulationManager`) –

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

step_state(*simgr*, *state*, ***kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a `SimSuccessors` object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

classmethod **crash_windup**(*state*, *crash_addr*)

```
class angr.exploration_techniques.driller_core.DrillerCore(trace, fuzz_bitmap=None)
```

Bases: [ExplorationTechnique](#)

An exploration technique that symbolically follows an input looking for new state transitions.

It has to be used with Tracer exploration technique. Results are put in ‘diverted’ stash.

```
__init__(trace, fuzz_bitmap=None)
```

:param trace : The basic block trace. :type fuzz_bitmap: :param fuzz_bitmap: AFL’s bitmap of state transitions. Defaults to saying every transition is worth satisfying.

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** ([str](#)) –

```
class angr.exploration_techniques.slicecutor.Slicecutor(annotated_cfg, force_taking_exit=False,
                                                         force_sat=False)
```

Bases: [ExplorationTechnique](#)

The Slicecutor is an exploration that executes provided code slices.

Parameters

force_sat ([bool](#)) –

```
__init__(annotated_cfg, force_taking_exit=False, force_sat=False)
```

All parameters except `annotated_cfg` are optional.

Parameters

- **annotated_cfg** – The AnnotatedCFG that provides the code slice.
- **force_taking_exit** – Set to True if you want to create a successor based on our slice in case of unconstrained successors.
- **force_sat** ([bool](#)) – If a branch specified by the slice is unsatisfiable, set this option to True if you want to force it to be satisfiable and be taken anyway.

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

```
filter(simgr, state, **kwargs)
```

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

step_state(*simgr, state, **kwargs*)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

successors(*simgr, state, **kwargs*)

Perform the process of stepping a state forward, returning a *SimSuccessors* object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the *kwargs* for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

class `angr.exploration_techniques.director.BaseGoal`(*sort*)

Bases: `object`

REQUIRE_CFG_STATES = `False`

__init__(*sort*)

check(*cfg, state, peek_blocks*)

Parameters

- **cfg** (`angr.analyses.CFGEmlated`) – An instance of *CFGEmlated*.
- **state** (`angr.SimState`) – The state to check.
- **peek_blocks** (`int`) – Number of blocks to peek ahead from the current point.

Returns

True if we can determine that this condition is definitely satisfiable if the path is taken, False otherwise.

Return type

bool

check_state(*state*)

Check if the current state satisfies the goal.

Parameters
state (*angr.SimState*) – The state to check.

Returns

True if it satisfies the goal, False otherwise.

Return type

bool

class *angr.exploration_techniques.director.ExecuteAddressGoal*(*addr*)

 Bases: *BaseGoal*

A goal that prioritizes states reaching (or are likely to reach) certain address in some specific steps.

__init__(*addr*)

check(*cfg, state, peek_blocks*)

Check if the specified address will be executed

Parameters

- **cfg** –
- **state** –
- **peek_blocks** (*int*) –

Returns
Return type

bool

check_state(*state*)

Check if the current address is the target address.

Parameters
state (*angr.SimState*) – The state to check.

Returns

True if the current address is the target address, False otherwise.

Return type

bool

class *angr.exploration_techniques.director.CallFunctionGoal*(*function, arguments*)

 Bases: *BaseGoal*

A goal that prioritizes states reaching certain function, and optionally with specific arguments. Note that constraints on arguments (and on function address as well) have to be identifiable on an accurate CFG. For example, you may have a CallFunctionGoal saying “call printf with the first argument being ‘Hello, world’”, and CFGEmulated must be able to figure out the first argument to printf is in fact “Hello, world”, not some symbolic strings that will be constrained to “Hello, world” during symbolic execution (or simulation, however you put it).

REQUIRE_CFG_STATES = **True**
__init__(*function, arguments*)

check(*cfg*, *state*, *peek_blocks*)

Check if the specified function will be reached with certain arguments.

Parameters

- **cfg** –
- **state** –
- **peek_blocks** –

Returns

check_state(*state*)

Check if the specific function is reached with certain arguments

Parameters

state ([angr.SimState](#)) – The state to check

Returns

True if the function is reached with certain arguments, False otherwise.

Return type

[bool](#)

```
class angr.exploration_techniques.director.Director(peek_blocks=100, peek_functions=5,
                                                    goals=None, cfg_keep_states=False,
                                                    goal_satisfied_callback=None,
                                                    num_fallback_states=5)
```

Bases: [ExplorationTechnique](#)

An exploration technique for directed symbolic execution.

A control flow graph (using CFGEmulated) is built and refined during symbolic execution. Each time the execution reaches a block that is outside of the CFG, the CFG recovery will be triggered with that state, with a maximum recovery depth (100 by default). If we see a basic block during state stepping that is not yet in the control flow graph, we go back to control flow graph recovery and “peek” more blocks forward.

When stepping a simulation manager, all states are categorized into three different categories:

- Might reach the destination within the peek depth. Those states are prioritized.
- Will not reach the destination within the peek depth. Those states are de-prioritized. However, there is a little chance for those states to be explored as well in order to prevent over-fitting.

```
__init__(peek_blocks=100, peek_functions=5, goals=None, cfg_keep_states=False,
          goal_satisfied_callback=None, num_fallback_states=5)
```

Constructor.

step(*simgr*, *stash*='active', ***kwargs*)

Parameters

- **simgr** –
- **stash** –
- **kwargs** –

Returns

add_goal(*goal*)

Add a goal.

Parameters

goal ([BaseGoal](#)) – The goal to add.

Returns

None

class `angr.exploration_techniques.oppologist.Oppologist`

Bases: [ExplorationTechnique](#)

The Oppologist is an exploration technique that forces uncooperative code through qemu.

__init__()

successors(*simgr, state, **kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

class `angr.exploration_techniques.loop_seer.LoopSeer`(*cfg=None, functions=None, loops=None, use_header=False, bound=None, bound_reached=None, discard_stash='spinning', limit_concrete_loops=True*)

Bases: [ExplorationTechnique](#)

This exploration technique monitors exploration and maintains all loop-related data (well, currently it is just the loop trip counts, but feel free to add something else).

__init__(*cfg=None, functions=None, loops=None, use_header=False, bound=None, bound_reached=None, discard_stash='spinning', limit_concrete_loops=True*)

Parameters

- **cfg** – Normalized CFG is required.
- **functions** – Function(s) containing the loop(s) to be analyzed.
- **loops** – Specific group of Loop(s) to be analyzed, if this is None we run the LoopFinder analysis.
- **use_header** – Whether to use header based trip counter to compare with the bound limit.
- **bound** – Limit the number of iterations a loop may be executed.
- **bound_reached** – If provided, should be a function that takes the LoopSeer and the succ_state. Will be called when loop execution reach the given bound. Default to moving states that exceed the loop limit to a discard stash.
- **discard_stash** – Name of the stash containing states exceeding the loop limit.

- **limit_concrete_loops** – If False, do not limit a loop back-edge if it is the only successor (Defaults to True to maintain the original behavior)

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

filter(*simgr, state, **kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

successors(*simgr, state, **kwargs*)

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

```
class angr.exploration_techniques.local_loop_seer.LocalLoopSeer(bound=None,
                                                                bound_reached=None,
                                                                discard_stash='spinning')
```

Bases: [ExplorationTechnique](#)

LocalLoopSeer monitors exploration and maintains all loop-related data without relying on a control flow graph.

```
__init__(bound=None, bound_reached=None, discard_stash='spinning')
```

Parameters

- **bound** – Limit the number of iterations a loop may be executed.
- **bound_reached** – If provided, should be a function that takes the LoopSeer and the succ_state. Will be called when loop execution reach the given bound. Default to moving states that exceed the loop limit to a discard stash.
- **discard_stash** – Name of the stash containing states exceeding the loop limit.

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

filter(*simgr*, *state*, ***kwargs*)

Perform filtering on which stash a state should be inserted into.

If the state should be filtered, return the name of the stash to move the state to. If you want to modify the state before filtering it, return a tuple of the stash to move the state to and the modified state. To defer to the original categorization procedure, return the result of `simgr.filter(state, **kwargs)`

If the user provided a `filter_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

successors(*simgr*, *state*, ***kwargs*)

Perform the process of stepping a state forward, returning a `SimSuccessors` object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the `kwargs` for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **state** ([angr.SimState](#)) –

class `angr.exploration_techniques.stochastic.StochasticSearch`(*start_state*, *restart_prob=0.0001*)

Bases: [ExplorationTechnique](#)

Stochastic Search.

Will only keep one path active at a time, any others will be discarded. Before each pass through, weights are randomly assigned to each basic block. These weights form a probability distribution for determining which state remains after splits. When we run out of active paths to step, we start again from the start state.

__init__(*start_state*, *restart_prob=0.0001*)

Parameters

- **start_state** – The initial state from which exploration stems.
- **restart_prob** – The probability of randomly restarting the search (default 0.0001).

step(*simgr*, *stash='active'*, ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** ([str](#)) –

```
class angr.exploration_techniques.unique.UniqueSearch(similarity_func=None,
                                                    deferred_stash='deferred')
```

Bases: [ExplorationTechnique](#)

Unique Search.

Will only keep one path active at a time, any others will be deferred. The state that is explored depends on how unique it is relative to the other deferred states. A path's uniqueness is determined by its average similarity between the other (deferred) paths. Similarity is calculated based on the supplied *similarity_func*, which by default is: The (L2) distance between the counts of the state addresses in the history of the path.

```
__init__(similarity_func=None, deferred_stash='deferred')
```

Parameters

- **similarity_func** – How to calculate similarity between two states.
- **deferred_stash** – Where to store the deferred states.

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

simgr ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

```
static similarity(state_a, state_b)
```

The (L2) distance between the counts of the state addresses in the history of the path. :type state_a: :param state_a: The first state to compare :type state_b: :param state_b: The second state to compare

```
static sequence_matcher_similarity(state_a, state_b)
```

The *difflib.SequenceMatcher* ratio between the state addresses in the history of the path. :type state_a: :param state_a: The first state to compare :type state_b: :param state_b: The second state to compare

```
class angr.exploration_techniques.tech_builder.TechniqueBuilder(setup=None, step_state=None,
                                                              step=None, successors=None,
                                                              filter=None, selector=None,
                                                              complete=None)
```

Bases: [ExplorationTechnique](#)

This meta technique could be used to hook a couple of simulation manager methods without actually creating a new exploration technique, for example:

```
class SomeComplexAnalysis(Analysis):
```

```
    def do_something():
```

```
        simgr = self.project.factory.simulation_manager()
        simgr.use_tech(ProxyTechnique(step_state=self._step_state))
        simgr.run()
```

```
    def _step_state(self, state):
```

```
        # Do stuff! pass
```

In the above example, the `_step_state` method can access all the necessary stuff, hidden in the analysis instance, without passing that instance to a one-shot-styled exploration technique.

```
__init__(setup=None, step_state=None, step=None, successors=None, filter=None, selector=None,
         complete=None)
```

```
angr.exploration_techniques.common.condition_to_lambda(condition, default=False)
```

Translates an integer, set, list or function into a lambda that checks if state's current basic block matches some condition.

Parameters

- **condition** – An integer, set, list or lambda to convert to a lambda.
- **default** – The default return value of the lambda (in case condition is None). Default: false.

Returns

A tuple of two items: a lambda that takes a state and returns the set of addresses that it matched from the condition, and a set that contains the normalized set of addresses to stop at, or None if no addresses were provided statically.

```
class angr.exploration_techniques.symbion.Symbion(find=None, memory_concretize=None,
                                                  register_concretize=None, timeout=0,
                                                  find_stash='found')
```

Bases: [ExplorationTechnique](#)

The Symbion exploration technique uses the SimEngineConcrete available to step a SimState.

Parameters

- **find** – address or list of addresses that we want to reach, these will be translated into break-points inside the concrete process using the ConcreteTarget interface provided by the user inside the SimEngineConcrete.
- **memory_concretize** – list of tuples (address, symbolic variable) that are going to be written in the concrete process memory.
- **register_concretize** – list of tuples (reg_name, symbolic variable) that are going to be written
- **timeout** – how long we should wait the concrete target to reach the breakpoint

```
__init__(find=None, memory_concretize=None, register_concretize=None, timeout=0, find_stash='found')
```

```
setup(simgr)
```

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** ([angr.SimulationManager](#)) – The simulation manager to which you have just been added

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** ([angr.SimulationManager](#)) –
- **stash** (*str*) –

step_state(*simgr*, *args, **kwargs)

Determine the categorization of state successors into stashes. The result should be a dict mapping stash names to the list of successor states that fall into that stash, or None as a stash name to use the original stash name.

If you would like to directly work with a *SimSuccessors* object, you can obtain it with `simgr.successors(state, **kwargs)`. This is not recommended, as it denies other hooks the opportunity to look at the successors. Therefore, the usual technique is to call `simgr.step_state(state, **kwargs)` and then mutate the returned dict before returning it yourself.

..note:: This takes precedence over the *filter* hook - *filter* is only applied to states returned from here in the None stash.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **state** (`angr.SimState`) –

complete(*simgr*)

Return whether or not this manager has reached a “completed” state, i.e. `SimulationManager.run()` should halt.

This is the one hook which is *not* subject to the nesting rules of hooks. You should *not* call `simgr.complete`, you should make your own decision and return True or False. Each of the techniques’ completion checkers will be called and the final result will be computed with `simgr.completion_mode`.

Parameters

- **simgr** (`angr.SimulationManager`) –

```
class angr.exploration_techniques.memory_watcher.MemoryWatcher(min_memory=512,
                                                             memory_stash='lowmem')
```

Bases: [ExplorationTechnique](#)

Memory Watcher

Parameters

- **min_memory** (`int`, *optional*) – Minimum amount of free memory in MB before stopping execution (default: 95% memory use)
- **memory_stash** (`str`, *optional*) – What to call the low memory stash (default: ‘lowmem’)

At each step, keep an eye on how much memory is left on the system. Stash off states to effectively stop execution if we’re below a given threshold.

```
__init__(min_memory=512, memory_stash='lowmem')
```

setup(*simgr*)

Perform any initialization on this manager you might need to do.

Parameters

- **simgr** (`angr.SimulationManager`) – The simulation manager to which you have just been added

step(*simgr*, stash='active', **kwargs)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- `simgr(angr.SimulationManager)` –
- `stash(str)` –

class `angr.exploration_techniques.bucketizer.Bucketizer`

Bases: [*ExplorationTechnique*](#)

Loop bucketization: Pick $\log(n)$ paths out of n possible paths, and stash (or drop) everything else.

`__init__()`

`successors(simgr, state, **kwargs)`

Perform the process of stepping a state forward, returning a SimSuccessors object.

To defer to the original succession procedure, return the result of `simgr.successors(state, **kwargs)`. Be careful about not calling this method (e.g. calling `project.factory.successors` manually) as it denies other hooks the opportunity to instrument the step. Instead, you can mutate the kwargs for the step before calling the original, and mutate the result before returning it yourself.

If the user provided a `successor_func` in their step or run command, it will appear here.

Parameters

- `simgr(angr.SimulationManager)` –
- `state(angr.SimState)` –

`angr.exploration_techniques.suggestions.ast_weight(ast, memo=None)`

class `angr.exploration_techniques.suggestions.Suggestions`

Bases: [*ExplorationTechnique*](#)

An exploration technique which analyzes failure cases and logs suggestions for how to mitigate them in future analyses.

`__init__()`

`step(simgr, stash='active', **kwargs)`

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- `simgr(angr.SimulationManager)` –
- `stash(str)` –

`static report(state, event)`

10.9 Simulation Engines

class `angr.engines.UberEngine(*args, **kwargs)`

Bases: [*SimEngineFailure*](#), [*SimEngineSyscall*](#), [*HooksMixin*](#), [*SimEngineUnicorn*](#), [*SuperFastpathMixin*](#), [*TrackActionsMixin*](#), [*SimInspectMixin*](#), [*HeavyResilienceMixin*](#), [*SootMixin*](#), [*HeavyVEXMixin*](#), [*TLSMixin*](#)

`irsb`

`state`

`stmt_idx`

`successors: Optional[SimSuccessors]`

`tmps`

class `angr.engines.UberEnginePcode(*args, **kwargs)`

Bases: `SimEngineFailure`, `SimEngineSyscall`, `HooksMixin`, `HeavyPcodeMixin`

class `angr.engines.engine.SimEngineBase(project=None, **kwargs)`

Bases: `object`

Even more basey of a base class for `SimEngine`. Used as a base by mixins which want access to the project but for which having method `process` (contained in `SimEngine`) doesn't make sense

`__init__`(`project=None`, `**kwargs`)

class `angr.engines.engine.SimEngine(project=None, **kwargs)`

Bases: `SimEngineBase`

A `SimEngine` is a class which understands how to perform execution on a state. This is a base class.

abstract process(`state`, `**kwargs`)

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

class `angr.engines.engine.TLSMixin(*args, **kwargs)`

Bases: `object`

Mix this class into any class that defines `__tls` to make all of the attributes named in that list into thread-local properties.

MAGIC MAGIC MAGIC

class `angr.engines.engine.TLSProperty(name)`

Bases: `object`

`__init__`(`name`)

class `angr.engines.engine.SuccessorsMixin(*args, **kwargs)`

Bases: `SimEngine`

A mixin for `SimEngine` which implements `process` to perform common operations related to symbolic execution and dispatches to a `process_successors` method to fill a `SimSuccessors` object with the results.

`__init__`(`*args`, `**kwargs`)

process(`state`, `*args`, `**kwargs`)

Perform execution with a state.

You should only override this method in a subclass in order to provide the correct method signature and docstring. You should override the `_process` method to do your actual execution.

Parameters

- **state** – The state with which to execute. This state will be copied before modification.
- **inline** – This is an inline execution. Do not bother copying the state.

- **force_addr** – Force execution to pretend that we’re working at this concrete address

Returns

A SimSuccessors object categorizing the execution’s successor states

process_successors(*successors*, ***kwargs*)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python’s method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

class `angr.engines.successors.SimSuccessors`(*addr*, *initial_state*)

Bases: `object`

This class serves as a categorization of all the kinds of result states that can come from a SimEngine run.

Variables

- **addr** (*int*) – The address at which execution is taking place, as a python int
- **initial_state** – The initial state for which execution produced these successors
- **engine** – The engine that produced these successors
- **sort** – A string identifying the type of engine that produced these successors
- **processed** (*bool*) – Whether or not the processing succeeded
- **description** (*str*) – A textual description of the execution step

The successor states produced by this run are categorized into several lists:

Variables

- **artifacts** (*dict*) – Any analysis byproducts (for example, an IRSB) that were produced during execution
- **successors** – The “normal” successors. IP may be symbolic, but must have reasonable number of solutions
- **unsat_successors** – Any successor which is unsatisfiable after its guard condition is added.
- **all_successors** – `successors + unsat_successors`
- **flat_successors** – The normal successors, but any symbolic IPs have been concretized. There is one state in this list for each possible value an IP may be concretized to for each successor state.
- **unconstrained_successors** – Any state for which during the flattening process we find too many solutions.

A more detailed description of the successor lists may be found here: <https://docs.angr.io/core-concepts/simulation#simsuccessors>

`__init__(addr, initial_state)`

`classmethod failure()`

`property is_empty`

`add_successor(state, target, guard, jumpkind, add_guard=True, exit_stmt_idx=None, exit_ins_addr=None, source=None)`

Add a successor state of the SimRun. This procedure stores method parameters into state.scratch, does some housekeeping, and calls out to helper functions to prepare the state and categorize it into the appropriate successor lists.

Parameters

- **state** (`SimState`) – The successor state.
- **target** – The target (of the jump/call/ret).
- **guard** – The guard expression.
- **jumpkind** (`str`) – The jumpkind (call, ret, jump, or whatnot).
- **add_guard** (`bool`) – Whether to add the guard constraint (default: True).
- **exit_stmt_idx** (`int`) – The ID of the exit statement, an integer by default. ‘default’ stands for the default exit, and None means it’s not from a statement (for example, from a SimProcedure).
- **exit_ins_addr** (`int`) – The instruction pointer of this exit, which is an integer by default.
- **source** (`int`) – The source of the jump (i.e., the address of the basic block).

`class angr.engines.procedure.ProcedureMixin`

Bases: `object`

A mixin for SimEngine which adds the `process_procedure` method for calling a SimProcedure and adding its results to a SimSuccessors.

`process_procedure(state, successors, procedure, ret_to=None, arguments=None, **kwargs)`

`class angr.engines.procedure.ProcedureEngine(*args, **kwargs)`

Bases: `ProcedureMixin`, `SuccessorsMixin`

A SimEngine that you may use if you only care about processing SimProcedures. *Requires* the procedure kwarg to be passed to process.

`process_successors(successors, procedure=None, **kwargs)`

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python’s method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate

- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

class `angr.engines.hook.HooksMixin(*args, **kwargs)`

Bases: [*SuccessorsMixin*](#), [*ProcedureMixin*](#)

A SimEngine mixin which adds a SimSuccessors handler which will look into the project's hooks and run the hook at the current address.

Will respond to the following parameters provided to the step stack:

- **procedure**: A SimProcedure instance to force-run instead of consulting the current hooks
- **ret_to**: An address to force-return-to at the end of the procedure

process_successors(*successors*, *procedure=None*, ***kwargs*)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

class `angr.engines.syscall.SimEngineSyscall(*args, **kwargs)`

Bases: [*SuccessorsMixin*](#), [*ProcedureMixin*](#)

A SimEngine mixin which adds a successors handling step that checks if a syscall was just requested and if so handles it as a step.

process_successors(*successors*, ***kwargs*)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

class `angr.engines.failure.SimEngineFailure(*args, **kwargs)`

Bases: [*SuccessorsMixin*](#), [*ProcedureMixin*](#)

process_successors(*successors*, ***kwargs*)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

class `angr.engines.soot.engine.SootMixin`(*args, ***kwargs*)

Bases: `SuccessorsMixin`, `ProcedureMixin`

Execution engine based on Soot.

lift_soot(*addr=None*, *the_binary=None*, ***kwargs*)

process_successors(*successors*, ***kwargs*)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

get_unconstrained_simprocedure()

classmethod **setup_callsite**(*state*, *args*, *ret_addr*, *ret_var=None*)

static **setup_arguments**(*state*, *args*)

static **prepare_return_state**(*state*, *ret_value=None*)

static **terminate_execution**(*statement*, *state*, *successors*)

static **prepare_native_return_state**(*native_state*)

Hook target for native function call returns.

Recovers and stores the return value from native memory and toggles the state, s.t. execution continues in the Soot engine.

```
class angr.engines.unicorn.SimEngineUnicorn(*args, **kwargs)
```

Bases: [SuccessorsMixin](#)

Concrete execution in the Unicorn Engine, a fork of qemu.

Responds to the following parameters in the step stack:

- **step**: How many basic blocks we want to execute
- **extra_stop_points**: A collection of addresses at which execution should halt

```
__init__(*args, **kwargs)
```

```
process_successors(successors, **kwargs)
```

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

```
class angr.engines.concrete.SimEngineConcrete(project)
```

Bases: [SuccessorsMixin](#)

Concrete execution using a concrete target provided by the user.

```
__init__(project)
```

```
process_successors(successors, extra_stop_points=None, memory_concretize=None,
                   register_concretize=None, timeout=0, *args, **kwargs)
```

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.

to_engine(*state*, *extra_stop_points*, *memory_concretize*, *register_concretize*, *timeout*)

Handle the concrete execution of the process This method takes care of: 1- Set the breakpoints on the addresses provided by the user 2- Concretize the symbolic variables and perform the write inside the concrete process 3- Continue the program execution.

Parameters

- **state** – The state with which to execute
- **extra_stop_points** – list of addresses where to stop the concrete execution and return to the simulated one
- **memory_concretize** – list of tuples (address, symbolic variable) that are going to be written in the concrete process memory.
- **register_concretize** – list of tuples (reg_name, symbolic variable) that are going to be written
- **timeout** – how long we should wait the concrete target to reach the breakpoint

Returns

None

static check_concrete_target_methods(*concrete_target*)

Check if the concrete target methods return the correct type of data :return: True if the concrete target is compliant

class `angr.engines.pcode.engine.HeavyPcodeMixin`(*args, **kwargs)

Bases: `SuccessorsMixin`, `PcodeLifterEngineMixin`, `PcodeEmulatorMixin`

Execution engine based on P-code, Ghidra's IR.

Responds to the following parameters to the step stack:

- **irsb**: The P-Code IRSB object to use for execution. If not provided one will be lifted.
- **skip_stmts**: The number of statements to skip in processing
- **last_stmt**: Do not execute any statements after this statement
- **thumb**: Whether the block should be forced to be lifted in ARM's THUMB mode. (FIXME)
- **extra_stop_points**:
An extra set of points at which to break basic blocks
- **insn_bytes**: A string of bytes to use for the block instead of the project.
- **size**: The maximum size of the block, in bytes.
- **num_inst**: The maximum number of instructions.

__init__(*args, **kwargs)

process_successors(*successors*, *irsb=None*, *insn_text=None*, *insn_bytes=None*, *thumb=False*, *size=None*, *num_inst=None*, *extra_stop_points=None*, **kwargs)

Implement this function to fill out the SimSuccessors object with the results of stepping state.

In order to implement a model where multiple mixins can potentially handle a request, a mixin may implement this method and then perform a `super()` call if it wants to pass on handling to the next mixin.

Keep in mind python's method resolution order when composing multiple classes implementing this method. In short: left-to-right, depth-first, but deferring any base classes which are shared by multiple subclasses (the merge point of a diamond pattern in the inheritance graph) until the last point where they

would be encountered in this depth-first search. For example, if you have classes A, B(A), C(B), D(A), E(C, D), then the method resolution order will be E, C, B, D, A.

Parameters

- **state** – The state to manipulate
- **successors** (*SimSuccessors*) – The successors object to fill out
- **kwargs** – Any extra arguments. Do not fail if you are passed unexpected arguments.
- **irsb** (*IRSB* | *None*) –
- **insn_text** (*str* | *None*) –
- **insn_bytes** (*bytes* | *None*) –
- **thumb** (*bool*) –
- **size** (*int* | *None*) –
- **num_inst** (*int* | *None*) –
- **extra_stop_points** (*Iterable[int]* | *None*) –

Return type

None

class `angr.engines.pcode.lifter.ExitStatement(dst, jumpkind)`

Bases: *object*

This class exists to ease compatibility with CFGFast’s processing of exit_statements. See `_scan_irsb` method.

Parameters

- **dst** (*int* | *None*) –
- **jumpkind** (*str*) –

`__init__`(dst, jumpkind)

Parameters

- **dst** (*int* | *None*) –
- **jumpkind** (*str*) –

dst: *Optional[int]*

jumpkind: *str*

class `angr.engines.pcode.lifter.PcodeDisassemblerBlock(addr, insns, thumb, arch)`

Bases: *DisassemblerBlock*

Helper class to represent a block of disassembled target architecture instructions

addr

insns

thumb

arch

class `angr.engines.pcode.lifter.PcodeDisassemblerInsn`(*pcode_insn*)

Bases: `DisassemblerInsn`

Helper class to represent a disassembled target architecture instruction

`__init__`(*pcode_insn*)

property **size**: `int`

property **address**: `int`

property **mnemonic**: `str`

property **op_str**: `str`

class `angr.engines.pcode.lifter.IRSB`(*data*, *mem_addr*, *arch*, *max_inst=None*, *max_bytes=None*, *bytes_offset=0*, *traceflags=0*, *opt_level=1*, *num_inst=None*, *num_bytes=None*, *strict_block_end=False*, *skip_stmts=False*, *collect_data_refs=False*)

Bases: `object`

IRSB stands for *Intermediate Representation Super-Block*. An IRSB in is a single-entry, multiple-exit code block.

Variables

- **arch** (`archinfo.Arch`) – The architecture this block is lifted under
- **statements** (list of `IRStmt`) – The statements in this block
- **next** (`IRExpr`) – The expression for the default exit target of this block
- **offsIP** (`int`) – The offset of the instruction pointer in the VEX guest state
- **stmts_used** (`int`) – The number of statements in this IRSB
- **jumpkind** (`str`) – The type of this block’s default jump (call, boring, syscall, etc) as a VEX enum string
- **direct_next** (`bool`) – Whether this block ends with a direct (not indirect) jump or branch
- **size** (`int`) – The size of this block in bytes
- **addr** (`int`) – The address of this basic block, i.e. the address in the first IMark

Parameters

- **data** (`str` | `bytes` | `None`) –
- **mem_addr** (`int`) –
- **arch** (`Arch`) –
- **max_inst** (`int` | `None`) –
- **max_bytes** (`int` | `None`) –
- **bytes_offset** (`int`) –
- **traceflags** (`int`) –
- **opt_level** (`int`) –
- **num_inst** (`int` | `None`) –
- **num_bytes** (`int` | `None`) –
- **strict_block_end** (`bool`) –

- `skip_stmts` (*bool*) –
- `collect_data_refs` (*bool*) –

`MAX_EXITS = 400`

`MAX_DATA_REFS = 2000`

`__init__(data, mem_addr, arch, max_inst=None, max_bytes=None, bytes_offset=0, traceflags=0, opt_level=1, num_inst=None, num_bytes=None, strict_block_end=False, skip_stmts=False, collect_data_refs=False)`

Parameters

- `data` (`Union[str, bytes, None]`) – The bytes to lift. Can be either a string of bytes or a cffi buffer object. You may also pass `None` to initialize an empty IRSB.
- `mem_addr` (*int*) – The address to lift the data at.
- `arch` (`Arch`) – The architecture to lift the data as.
- `max_inst` (`Optional[int]`) – The maximum number of instructions to lift. (See note below)
- `max_bytes` (`Optional[int]`) – The maximum number of bytes to use.
- `num_inst` (`Optional[int]`) – Replaces `max_inst` if `max_inst` is `None`. If set to `None` as well, no instruction limit is used.
- `num_bytes` (`Optional[int]`) – Replaces `max_bytes` if `max_bytes` is `None`. If set to `None` as well, no byte limit is used.
- `bytes_offset` (*int*) – The offset into `data` to start lifting at. Note that for ARM THUMB mode, both `mem_addr` and `bytes_offset` must be odd (typically `bytes_offset` is set to 1).
- `traceflags` (*int*) – Unused by P-Code lifter
- `opt_level` (*int*) – Unused by P-Code lifter
- `strict_block_end` (*bool*) – Unused by P-Code lifter
- `skip_stmts` (*bool*) –
- `collect_data_refs` (*bool*) –

Return type

`None`

Note: Explicitly specifying the number of instructions to lift (`max_inst`) may not always work exactly as expected. For example, on MIPS, it is meaningless to lift a branch or jump instruction without its delay slot. VEX attempts to Do The Right Thing by possibly decoding fewer instructions than requested. Specifically, this means that lifting a branch or jump on MIPS as a single instruction (`max_inst=1`) will result in an empty IRSB, and subsequent attempts to run this block will raise `SimIRSBError('Empty IRSB passed to SimIRSB.')`.

Note: If no instruction and byte limit is used, the lifter will continue lifting the block until the block ends properly or until it runs out of data to lift.

addr: *int*

```

arch: Arch
behaviors: Optional[BehaviorFactory]
data_refs: Sequence
default_exit_target: Optional
jumpkind: Optional[str]
next: Optional[int]

static empty_block(arch, addr, statements=None, nxt=None, tyenv=None, jumpkind=None,
                   direct_next=None, size=None)

```

Return type

IRSB

Parameters

- **arch** (*Arch*) –
- **addr** (*int*) –
- **statements** (*Sequence* / *None*) –
- **nxt** (*int* / *None*) –
- **jumpkind** (*str* / *None*) –
- **direct_next** (*bool* / *None*) –
- **size** (*int* / *None*) –

property has_statements: *bool*

property exit_statements: *Sequence[Tuple[int, int, ExitStatement]]*

copy()

Copy by creating an empty IRSB and then filling in the leftover attributes. Copy is made as deep as possible

Return type

IRSB

extend(*extendwith*)

Appends an irsb to the current irsb. The irsb that is appended is invalidated. The appended irsb's jumpkind and default exit are used. :type extendwith: *IRSB* :param extendwith: The IRSB to append to this IRSB

Return type

IRSB

Parameters

extendwith (*IRSB*) –

invalidate_direct_next()

Return type

None

pp()

Pretty-print the IRSB to stdout.

Return type

None

property tyenv

property stmts_used: `int`

property offsIP: `int`

property direct_next: `bool`

property expressions

Return an iterator of all expressions contained in the IRSB.

property instructions: `int`

The number of instructions in this block

property instruction_addresses: `Sequence[int]`

Addresses of instructions in this block.

property size: `int`

The size of this block, in bytes

property operations

A list of all operations done by the IRSB, as libVEX enum names

property all_constants

Returns all constants in the block (including incrementing of the program counter) as `pyvex.const.IRConst`.

property constants

The constants (excluding updates of the program counter) in the IRSB as `pyvex.const.IRConst`.

property constant_jump_targets

A set of the static jump targets of the basic block.

property constant_jump_targets_and_jumpkinds

A dict of the static jump targets of the basic block to their jumpkind.

property statements: `Iterable`

property disassembly: `PcodeDisassemblerBlock`

class `angr.engines.pcode.lifter.Lifter`(*arch*, *addr*)

Bases: `object`

A lifter is a class of methods for processing a block.

Variables

- **data** – The bytes to lift as either a python string of bytes or a cffi buffer object.
- **bytes_offset** – The offset into *data* to start lifting at.
- **max_bytes** – The maximum number of bytes to lift. If set to None, no byte limit is used.
- **max_inst** – The maximum number of instructions to lift. If set to None, no instruction limit is used.
- **opt_level** – Unused by P-Code lifter
- **traceflags** – Unused by P-Code lifter
- **allow_arch_optimizations** – Unused by P-Code lifter
- **strict_block_end** – Unused by P-Code lifter

- **skip_stmts** – Unused by P-Code lifter

Parameters

- **arch** (*Arch*) –
- **addr** (*int*) –

REQUIRE_DATA_C = False

REQUIRE_DATA_PY = False

__init__(*arch, addr*)

Parameters

- **arch** (*Arch*) –
- **addr** (*int*) –

arch: *Arch*

addr: *int*

data: *Union[str, bytes, None]*

bytes_offset: *Optional[int]*

opt_level: *int*

traceflags: *Optional[int]*

allow_arch_optimizations: *Optional[bool]*

strict_block_end: *Optional[bool]*

collect_data_refs: *bool*

max_inst: *Optional[int]*

max_bytes: *Optional[int]*

skip_stmts: *bool*

irsb: *IRSB*

lift()

Lifts the data using the information passed into `_lift`. Should be overridden in child classes.

Should set the lifted IRSB to `self.irsb`. If a lifter raises a `LiftingException` on the data, this signals that the lifter cannot lift this data and arch and the lifter is skipped. If a lifter can lift any amount of data, it should lift it and return the lifted block with a jumpkind of `Ijk_NoDecode`, signalling to pyvex that other lifters should be used on the undecodable data.

Return type

None

```
angr.engines.pcode.lifter.lift(data, addr, arch, max_bytes=None, max_inst=None, bytes_offset=0,
                               opt_level=1, traceflags=0, strict_block_end=True, inner=False,
                               skip_stmts=False, collect_data_refs=False)
```

Lift machine code in *data* to a P-code IRSB.

If a lifter raises a `LiftingException` on the data, it is skipped. If it succeeds and returns a block with a jumpkind of `Ijk_NoDecode`, all of the lifters are tried on the rest of the data and if they work, their output is appended to the first block.

Parameters

- **arch** (`Arch`) – The arch to lift the data as.
- **addr** (`int`) – The starting address of the block. Effects the IMarks.
- **data** (`Union[str, bytes, None]`) – The bytes to lift as either a python string of bytes or a cffi buffer object.
- **max_bytes** (`Optional[int]`) – The maximum number of bytes to lift. If set to `None`, no byte limit is used.
- **max_inst** (`Optional[int]`) – The maximum number of instructions to lift. If set to `None`, no instruction limit is used.
- **bytes_offset** (`int`) – The offset into *data* to start lifting at.
- **opt_level** (`int`) – Unused by P-Code lifter
- **traceflags** (`int`) – Unused by P-Code lifter
- **strict_block_end** (`bool`) –
- **inner** (`bool`) –
- **skip_stmts** (`bool`) –
- **collect_data_refs** (`bool`) –

Return type

IRSB

Note: Explicitly specifying the number of instructions to lift (*max_inst*) may not always work exactly as expected. For example, on MIPS, it is meaningless to lift a branch or jump instruction without its delay slot. VEX attempts to Do The Right Thing by possibly decoding fewer instructions than requested. Specifically, this means that lifting a branch or jump on MIPS as a single instruction (*max_inst=1*) will result in an empty IRSB, and subsequent attempts to run this block will raise *SimIRSBError('Empty IRSB passed to SimIRSB.')*

Note: If no instruction and byte limit is used, the lifter will continue lifting the block until the block ends properly or until it runs out of data to lift.

```
class angr.engines.pcode.lifter.PcodeBasicBlockLifter(arch)
```

Bases: `object`

Lifts basic blocks to P-code

Parameters

arch (`Arch`) –

__init__ (*arch*)

Parameters

arch (`Arch`) –

context: `Context`

behaviors: `BehaviorFactory`

lift(*irsb*, *baseaddr*, *data*, *bytes_offset*=0, *max_bytes*=None, *max_inst*=None, *branch_delay_slot*=False, *is_sparc32*=False)

Return type

`None`

Parameters

- **irsb** (`IRSB`) –
- **baseaddr** (`int`) –
- **data** (`bytes` | `bytearray`) –
- **bytes_offset** (`int`) –
- **max_bytes** (`int` | `None`) –
- **max_inst** (`int` | `None`) –
- **branch_delay_slot** (`bool`) –
- **is_sparc32** (`bool`) –

class `angr.engines.pcode.lifter.PcodeLifter`(*arch*, *addr*)

Bases: `Lifter`

Handles calling into pypcode to lift a block

Parameters

- **arch** (`Arch`) –
- **addr** (`int`) –

data: `Union[str, bytes, None]`

bytes_offset: `Optional[int]`

opt_level: `int`

traceflags: `Optional[int]`

allow_arch_optimizations: `Optional[bool]`

strict_block_end: `Optional[bool]`

collect_data_refs: `bool`

max_inst: `Optional[int]`

max_bytes: `Optional[int]`

skip_stmts: `bool`

irsb: `IRSB`

arch: `Arch`

addr: `int`

lift()

Lifts the data using the information passed into `_lift`. Should be overridden in child classes.

Should set the lifted IRSB to `self.irsb`. If a lifter raises a `LiftingException` on the data, this signals that the lifter cannot lift this data and arch and the lifter is skipped. If a lifter can lift any amount of data, it should lift it and return the lifted block with a jumpkind of `Ijk_NoDecode`, signalling to pyvex that other lifters should be used on the undecodable data.

Return type

`None`

```
class angr.engines.pcode.lifter.PcodeLifterEngineMixin(project=None, use_cache=None,
                                                    cache_size=50000, default_opt_level=1,
                                                    selfmodifying_code=None,
                                                    single_step=False,
                                                    default_strict_block_end=False, **kwargs)
```

Bases: [SimEngineBase](#)

Lifter mixin to lift from machine code to P-Code.

Parameters

- `use_cache` (`bool` | `None`) –
- `cache_size` (`int`) –
- `default_opt_level` (`int`) –
- `selfmodifying_code` (`bool` | `None`) –
- `single_step` (`bool`) –
- `default_strict_block_end` (`bool`) –

```
__init__(project=None, use_cache=None, cache_size=50000, default_opt_level=1,
        selfmodifying_code=None, single_step=False, default_strict_block_end=False, **kwargs)
```

Parameters

- `use_cache` (`bool` | `None`) –
- `cache_size` (`int`) –
- `default_opt_level` (`int`) –
- `selfmodifying_code` (`bool` | `None`) –
- `single_step` (`bool`) –
- `default_strict_block_end` (`bool`) –

clear_cache()

Return type

`None`

```
lift_vex(addr=None, state=None, clemory=None, insn_bytes=None, arch=None, size=None,
        num_inst=None, traceflags=0, thumb=False, extra_stop_points=None, opt_level=None,
        strict_block_end=None, skip_stmts=False, collect_data_refs=False, load_from_ro_regions=False,
        cross_insn_opt=None)
```

Temporary compatibility interface for integration with block code.

Parameters

- `addr` (`int` | `None`) –

- **state** (*SimState* | *None*) –
- **clemory** (*Clemory* | *None*) –
- **insn_bytes** (*bytes* | *None*) –
- **arch** (*Arch* | *None*) –
- **size** (*int* | *None*) –
- **num_inst** (*int* | *None*) –
- **traceflags** (*int*) –
- **thumb** (*bool*) –
- **extra_stop_points** (*Iterable*[*int*] | *None*) –
- **opt_level** (*int* | *None*) –
- **strict_block_end** (*bool* | *None*) –
- **skip_stmts** (*bool*) –
- **collect_data_refs** (*bool*) –
- **load_from_ro_regions** (*bool*) –
- **cross_insn_opt** (*bool* | *None*) –

lift_pcode(*addr=None, state=None, clemory=None, insn_bytes=None, arch=None, size=None, num_inst=None, traceflags=0, thumb=False, extra_stop_points=None, opt_level=None, strict_block_end=None, skip_stmts=False, collect_data_refs=False, load_from_ro_regions=False, cross_insn_opt=None*)

Lift an IRSB.

There are many possible valid sets of parameters. You at the very least must pass some source of data, some source of an architecture, and some source of an address.

Sources of data in order of priority: *insn_bytes*, *clemory*, *state*

Sources of an address, in order of priority: *addr*, *state*

Sources of an architecture, in order of priority: *arch*, *clemory*, *state*

Parameters

- **state** (*Optional*[*SimState*]) – A state to use as a data source.
- **clemory** (*Optional*[*Clemory*]) – A *cle.memory.Clemory* object to use as a data source.
- **addr** (*Optional*[*int*]) – The address at which to start the block.
- **thumb** (*bool*) – Whether the block should be lifted in ARM’s THUMB mode.
- **opt_level** (*Optional*[*int*]) – Unused for P-Code lifter
- **insn_bytes** (*Optional*[*bytes*]) – A string of bytes to use as a data source.
- **size** (*Optional*[*int*]) – The maximum size of the block, in bytes.
- **num_inst** (*Optional*[*int*]) – The maximum number of instructions.
- **traceflags** (*int*) – Unused by P-Code lifter
- **strict_block_end** (*Optional*[*bool*]) – Unused by P-Code lifter
- **load_from_ro_regions** (*bool*) – Unused by P-Code lifter
- **arch** (*Arch* | *None*) –

- **extra_stop_points** (*Iterable*[*int*] | *None*) –
- **skip_stmts** (*bool*) –
- **collect_data_refs** (*bool*) –
- **cross_insn_opt** (*bool* | *None*) –

class `angr.engines.pcode.emulate.PcodeEmulatorMixin(*args, **kwargs)`

Bases: *SimEngineBase*

Mixin for p-code execution.

__init__ (*args, **kwargs)

handle_pcode_block (*irsb*)

Execute a single P-Code IRSB.

Parameters

irsb (*IRSB*) – Block to be executed.

Return type

None

`angr.engines.pcode.behavior.make_bv_sizes_equal(bv1, bv2)`

Makes two BVs equal in length through sign extension.

Return type

Tuple[*BV*, *BV*]

Parameters

• **bv1** (*BV*) –

• **bv2** (*BV*) –

class `angr.engines.pcode.behavior.OpBehavior(opcode, is_unary, is_special=False)`

Bases: *object*

Base class for all operation behaviors.

Parameters

• **opcode** (*int*) –

• **is_unary** (*bool*) –

• **is_special** (*bool*) –

__init__ (*opcode*, *is_unary*, *is_special=False*)

Parameters

• **opcode** (*int*) –

• **is_unary** (*bool*) –

• **is_special** (*bool*) –

Return type

None

opcode: *int*

is_unary: *bool*

is_special: `bool`

evaluate_unary(*size_out*, *size_in*, *in1*)

Return type

`BV`

Parameters

- **size_out** (`int`) –
- **size_in** (`int`) –
- **in1** (`BV`) –

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

`BV`

Parameters

- **size_out** (`int`) –
- **size_in** (`int`) –
- **in1** (`BV`) –
- **in2** (`BV`) –

static generic_compare(*args*, *comparison*)

Return type

`BV`

Parameters

- **args** (`Iterable[BV]`) –
- **comparison** (`Callable[[BV, BV], BV]`) –

classmethod booleanize(*in1*)

Reduce input BV to a single bit of truth: out <- 1 if (in1 != 0) else 0.

Return type

`BV`

Parameters

in1 (`BV`) –

class `angr.engines.pcode.behavior.OpBehaviorCopy`

Bases: `OpBehavior`

Behavior for the COPY operation.

__init__()

evaluate_unary(*size_out*, *size_in*, *in1*)

Return type

`BV`

Parameters

- **size_out** (`int`) –
- **size_in** (`int`) –

```

        • in1 (BV) –
opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorEqual
    Bases: OpBehavior
    Behavior for the INT_EQUAL operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –

opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorNotEqual
    Bases: OpBehavior
    Behavior for the INT_NOTEQUAL operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –

opcode: int
is_unary: bool
is_special: bool

```

class `angr.engines.pcode.behavior.OpBehaviorIntSless`

Bases: *OpBehavior*

Behavior for the INT_SLESS operation.

`__init__()`

`evaluate_binary(size_out, size_in, in1, in2)`

Return type

BV

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –
- `in2(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.OpBehaviorIntSlessEqual`

Bases: *OpBehavior*

Behavior for the INT_SLESSEQUAL operation.

`__init__()`

`evaluate_binary(size_out, size_in, in1, in2)`

Return type

BV

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –
- `in2(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.OpBehaviorIntLess`

Bases: *OpBehavior*

Behavior for the INT_LESS operation.

`__init__()`

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class angr.engines.pcode.behavior.OpBehaviorIntLessEqual

Bases: *OpBehavior*

Behavior for the INT_LESSEQUAL operation.

__init__()

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class angr.engines.pcode.behavior.OpBehaviorIntZext

Bases: *OpBehavior*

Behavior for the INT_ZEXT operation.

__init__()

evaluate_unary(*size_out*, *size_in*, *in1*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –

```

        • in1 (BV) –

opcode: int

is_unary: bool

is_special: bool

class angr.engines.pcode.behavior.OpBehaviorIntSext
    Bases: OpBehavior
    Behavior for the INT_SEXT operation.
    __init__()
    evaluate_unary(size_out, size_in, in1)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –

opcode: int

is_unary: bool

is_special: bool

class angr.engines.pcode.behavior.OpBehaviorIntAdd
    Bases: OpBehavior
    Behavior for the INT_ADD operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –

opcode: int

is_unary: bool

is_special: bool

```



```
class angr.engines.pcode.behavior.OpBehaviorIntSub
```

Bases: *OpBehavior*

Behavior for the INT_SUB operation.

```
__init__()
```

```
evaluate_binary(size_out, size_in, in1, in2)
```

Return type

BV

Parameters

- `size_out` (*int*) –
- `size_in` (*int*) –
- `in1` (*BV*) –
- `in2` (*BV*) –

```
opcode: int
```

```
is_unary: bool
```

```
is_special: bool
```

```
class angr.engines.pcode.behavior.OpBehaviorIntCarry
```

Bases: *OpBehavior*

Behavior for the INT_CARRY operation.

```
__init__()
```

```
evaluate_binary(size_out, size_in, in1, in2)
```

Return type

BV

Parameters

- `size_out` (*int*) –
- `size_in` (*int*) –
- `in1` (*BV*) –
- `in2` (*BV*) –

```
opcode: int
```

```
is_unary: bool
```

```
is_special: bool
```

```
class angr.engines.pcode.behavior.OpBehaviorIntScarry
```

Bases: *OpBehavior*

Behavior for the INT_SCARRY operation.

```
__init__()
```

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class `angr.engines.pcode.behavior.OpBehaviorIntSborrow`

Bases: *OpBehavior*

Behavior for the INT_SBBORROW operation.

__init__()

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class `angr.engines.pcode.behavior.OpBehaviorInt2Comp`

Bases: *OpBehavior*

Behavior for the INT_2COMP operation.

__init__()

evaluate_unary(*size_out*, *size_in*, *in1*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –

```

        • in1 (BV) –

opcode: int

is_unary: bool

is_special: bool

class angr.engines.pcode.behavior.OpBehaviorIntNegate
    Bases: OpBehavior
    Behavior for the INT_NEGATE operation.
    __init__()
    evaluate_unary(size_out, size_in, in1)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –

opcode: int

is_unary: bool

is_special: bool

class angr.engines.pcode.behavior.OpBehaviorIntXor
    Bases: OpBehavior
    Behavior for the INT_XOR operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –

opcode: int

is_unary: bool

is_special: bool

```

class `angr.engines.pcode.behavior.OpBehaviorIntAnd`

Bases: *OpBehavior*

Behavior for the INT_AND operation.

`__init__()`

`evaluate_binary(size_out, size_in, in1, in2)`

Return type

BV

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –
- `in2(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.OpBehaviorIntOr`

Bases: *OpBehavior*

Behavior for the INT_OR operation.

`__init__()`

`evaluate_binary(size_out, size_in, in1, in2)`

Return type

BV

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –
- `in2(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.OpBehaviorIntLeft`

Bases: *OpBehavior*

Behavior for the INT_LEFT operation.

`__init__()`

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class angr.engines.pcode.behavior.OpBehaviorIntRight

Bases: *OpBehavior*

Behavior for the INT_RIGHT operation.

__init__()

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class angr.engines.pcode.behavior.OpBehaviorIntSright

Bases: *OpBehavior*

Behavior for the INT_SRIGHT operation.

__init__()

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –

```

        • in1 (BV) –
        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorIntMult
    Bases: OpBehavior
    Behavior for the INT_MULT operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorIntDiv
    Bases: OpBehavior
    Behavior for the INT_DIV operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool

```

```
class angr.engines.pcode.behavior.OpBehaviorIntSdiv
```

Bases: *OpBehavior*

Behavior for the INT_SDIV operation.

```
__init__()
```

```
evaluate_binary(size_out, size_in, in1, in2)
```

Return type

BV

Parameters

- `size_out` (*int*) –
- `size_in` (*int*) –
- `in1` (*BV*) –
- `in2` (*BV*) –

```
opcode: int
```

```
is_unary: bool
```

```
is_special: bool
```

```
class angr.engines.pcode.behavior.OpBehaviorIntRem
```

Bases: *OpBehavior*

Behavior for the INT_REM operation.

```
__init__()
```

```
evaluate_binary(size_out, size_in, in1, in2)
```

Return type

BV

Parameters

- `size_out` (*int*) –
- `size_in` (*int*) –
- `in1` (*BV*) –
- `in2` (*BV*) –

```
opcode: int
```

```
is_unary: bool
```

```
is_special: bool
```

```
class angr.engines.pcode.behavior.OpBehaviorIntSrem
```

Bases: *OpBehavior*

Behavior for the INT_SREM operation.

```
__init__()
```

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –
- **in2** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class `angr.engines.pcode.behavior.OpBehaviorBoolNegate`

Bases: *OpBehavior*

Behavior for the BOOL_NEGATE operation.

__init__()

evaluate_unary(*size_out*, *size_in*, *in1*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –

opcode: *int*

is_unary: *bool*

is_special: *bool*

class `angr.engines.pcode.behavior.OpBehaviorBoolXor`

Bases: *OpBehavior*

Behavior for the BOOL_XOR operation.

__init__()

evaluate_binary(*size_out*, *size_in*, *in1*, *in2*)

Return type

BV

Parameters

- **size_out** (*int*) –
- **size_in** (*int*) –
- **in1** (BV) –


```

        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorBoolAnd
    Bases: OpBehavior
    Behavior for the BOOL_AND operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool
class angr.engines.pcode.behavior.OpBehaviorBoolOr
    Bases: OpBehavior
    Behavior for the BOOL_OR operation.
    __init__()
    evaluate_binary(size_out, size_in, in1, in2)

        Return type
        BV

        Parameters
        • size_out (int) –
        • size_in (int) –
        • in1 (BV) –
        • in2 (BV) –
opcode: int
is_unary: bool
is_special: bool

```

```
class angr.engines.pcode.behavior.OpBehaviorFloatEqual
    Bases: OpBehavior
    Behavior for the FLOAT_EQUAL operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatNotEqual
    Bases: OpBehavior
    Behavior for the FLOAT_NOTEQUAL operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatLess
    Bases: OpBehavior
    Behavior for the FLOAT_LESS operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatLessEqual
    Bases: OpBehavior
    Behavior for the FLOAT_LESSEQUAL operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatNan
    Bases: OpBehavior
    Behavior for the FLOAT_NAN operation.
    __init__()
    opcode: int
    is_unary: bool
```

```

    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatAdd
    Bases: OpBehavior
    Behavior for the FLOAT_ADD operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatDiv
    Bases: OpBehavior
    Behavior for the FLOAT_DIV operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatMult
    Bases: OpBehavior
    Behavior for the FLOAT_MULT operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatSub
    Bases: OpBehavior
    Behavior for the FLOAT_SUB operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatNeg
    Bases: OpBehavior
    Behavior for the FLOAT_NEG operation.
    __init__()
    opcode: int

```

is_unary: `bool`

is_special: `bool`

class `angr.engines.pcode.behavior.OpBehaviorFloatAbs`

Bases: *OpBehavior*

Behavior for the FLOAT_ABS operation.

__init__()

opcode: `int`

is_unary: `bool`

is_special: `bool`

class `angr.engines.pcode.behavior.OpBehaviorFloatSqrt`

Bases: *OpBehavior*

Behavior for the FLOAT_SQRT operation.

__init__()

opcode: `int`

is_unary: `bool`

is_special: `bool`

class `angr.engines.pcode.behavior.OpBehaviorFloatInt2Float`

Bases: *OpBehavior*

Behavior for the FLOAT_INT2FLOAT operation.

__init__()

opcode: `int`

is_unary: `bool`

is_special: `bool`

class `angr.engines.pcode.behavior.OpBehaviorFloatFloat2Float`

Bases: *OpBehavior*

Behavior for the FLOAT_FLOAT2FLOAT operation.

__init__()

opcode: `int`

is_unary: `bool`

is_special: `bool`

class `angr.engines.pcode.behavior.OpBehaviorFloatTrunc`

Bases: *OpBehavior*

Behavior for the FLOAT_TRUNC operation.

__init__()

```

    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatCeil
    Bases: OpBehavior
    Behavior for the FLOAT_CEIL operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatFloor
    Bases: OpBehavior
    Behavior for the FLOAT_FLOOR operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorFloatRound
    Bases: OpBehavior
    Behavior for the FLOAT_ROUND operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorPiece
    Bases: OpBehavior
    Behavior for the PIECE operation.
    __init__()
    opcode: int
    is_unary: bool
    is_special: bool

class angr.engines.pcode.behavior.OpBehaviorSubpiece
    Bases: OpBehavior
    Behavior for the SUBPIECE operation.

```

`__init__()`

`evaluate_binary(size_out, size_in, in1, in2)`

Return type

`BV`

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –
- `in2(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.OpBehaviorPopcount`

Bases: `OpBehavior`

Behavior for the POPCOUNT operation.

`__init__()`

`evaluate_unary(size_out, size_in, in1)`

Return type

`BV`

Parameters

- `size_out(int)` –
- `size_in(int)` –
- `in1(BV)` –

`opcode: int`

`is_unary: bool`

`is_special: bool`

class `angr.engines.pcode.behavior.BehaviorFactory`

Bases: `object`

Returns the behavior object for a given opcode.

`__init__()`

`get_behavior_for_opcode(opcode)`

Return type

`OpBehavior`

Parameters

`opcode(int)` –

```

class angr.engines.pcode.cc.SimCCM68k(arch)
    Bases: SimCC
    Default CC for M68k

    Parameters
    arch (Arch) –

    ARG_REGS: List[str] = []

    FP_ARG_REGS: List[str] = []

    STACKARG_SP_DIFF = 4

    RETURN_VAL: SimFunctionArgument = <d0>

    RETURN_ADDR: SimFunctionArgument = [0x0]

class angr.engines.pcode.cc.SimCCRISCV(arch)
    Bases: SimCC
    Default CC for RISCV

    Parameters
    arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3', 'a4', 'a5', 'a6', 'a7']

    RETURN_ADDR: SimFunctionArgument = <ra>

    RETURN_VAL: SimFunctionArgument = <a0>

class angr.engines.pcode.cc.SimCCSPARC(arch)
    Bases: SimCC
    Default CC for SPARC

    Parameters
    arch (Arch) –

    ARG_REGS: List[str] = ['o0', 'o1', 'o2', 'o3', 'o4', 'o5']

    RETURN_VAL: SimFunctionArgument = <o0>

    RETURN_ADDR: SimFunctionArgument = <o7>

class angr.engines.pcode.cc.SimCCSH4(arch)
    Bases: SimCC
    Default CC for SH4

    Parameters
    arch (Arch) –

    ARG_REGS: List[str] = ['r4', 'r5']

    RETURN_VAL: SimFunctionArgument = <r0>

    RETURN_ADDR: SimFunctionArgument = <pr>

```

```

class angr.engines.pcode.cc.SimCCPARISC(arch)
    Bases: SimCC
    Default CC for PARISC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r26', 'r25']

    RETURN_VAL: SimFunctionArgument = <r28>

    RETURN_ADDR: SimFunctionArgument = <rp>

class angr.engines.pcode.cc.SimCCPowerPC(arch)
    Bases: SimCC
    Default CC for PowerPC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r3', 'r4', 'r5', 'r6', 'r7', 'r8', 'r9', 'r10']

    FP_ARG_REGS: List[str] = []

    STACKARG_SP_BUFF = 8

    RETURN_ADDR: SimFunctionArgument = <lr>

    RETURN_VAL: SimFunctionArgument = <r3>

class angr.engines.pcode.cc.SimCCXtensa(arch)
    Bases: SimCC
    Default CC for Xtensa

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['i2', 'i3', 'i4', 'i5', 'i6', 'i7']

    FP_ARG_REGS: List[str] = []

    RETURN_ADDR: SimFunctionArgument = <a0>

    RETURN_VAL: SimFunctionArgument = <o2>

angr.engines.pcode.cc.register_pcode_arch_default_cc(arch)

    Parameters
        arch (ArchPcode) –

```


10.10 Simulation Logging

class angr.state_plugins.sim_action.**SimAction**(*state, region_type*)

Bases: *SimEvent*

A SimAction represents a semantic action that an analyzed program performs.

TMP = 'tmp'

REG = 'reg'

MEM = 'mem'

__init__(*state, region_type*)

Initializes the SimAction.

Parameters

state – the state that’s the SimAction is taking place in.

property all_objects

property is_symbolic

property tmp_deps

property reg_deps

copy()

downsize()

Clears some low-level details (that take up memory) out of the SimAction.

class angr.state_plugins.sim_action.**SimActionExit**(*state, target, condition=None, exit_type=None*)

Bases: *SimAction*

An Exit action represents a (possibly conditional) jump.

CONDITIONAL = 'conditional'

DEFAULT = 'default'

__init__(*state, target, condition=None, exit_type=None*)

Initializes the SimAction.

Parameters

state – the state that’s the SimAction is taking place in.

property all_objects

property is_symbolic

class angr.state_plugins.sim_action.**SimActionConstraint**(*state, constraint, condition=None*)

Bases: *SimAction*

A constraint action represents an extra constraint added during execution of a path.

__init__(*state, constraint, condition=None*)

Initializes the SimAction.

Parameters

state – the state that’s the SimAction is taking place in.

property all_objects

property is_symbolic

class angr.state_plugins.sim_action.SimActionOperation(*state, op, exprs, result*)

Bases: [SimAction](#)

An action representing an operation between variables and/or constants.

__init__(*state, op, exprs, result*)

Initializes the SimAction.

Parameters

state – the state that’s the SimAction is taking place in.

property all_objects

property is_symbolic

class angr.state_plugins.sim_action.SimActionData(*state, region_type, action, tmp=None, addr=None, size=None, data=None, condition=None, fallback=None, fd=None*)

Bases: [SimAction](#)

A Data action represents a read or a write from memory, registers or a file.

READ = 'read'

WRITE = 'write'

OPERATE = 'operate'

__init__(*state, region_type, action, tmp=None, addr=None, size=None, data=None, condition=None, fallback=None, fd=None*)

Initializes the SimAction.

Parameters

state – the state that’s the SimAction is taking place in.

downsize()

Clears some low-level details (that take up memory) out of the SimAction.

property all_objects

property is_symbolic

property tmp_deps

property reg_deps

property storage

angr.state_plugins.sim_action_object.ast_stripping_op(*f, *args, **kwargs*)

angr.state_plugins.sim_action_object.ast_preserving_op(*f, *args, **kwargs*)

angr.state_plugins.sim_action_object.ast_stripping_decorator(*f*)

```
class angr.state_plugins.sim_action_object.SimActionObject(ast, reg_deps=None, tmp_deps=None,
                                                         deps=None, state=None)
```

Bases: `object`

A SimActionObject tracks an AST and its dependencies.

```
__init__(ast, reg_deps=None, tmp_deps=None, deps=None, state=None)
```

```
to_claripy()
```

```
copy()
```

```
SDiv(*args, **kwargs)
```

```
SMod(*args, **kwargs)
```

```
intersection(*args, **kwargs)
```

```
union(*args, **kwargs)
```

```
widen(*args, **kwargs)
```

```
angr.state_plugins.sim_action_object.make_methods()
```

```
class angr.state_plugins.sim_event.SimEvent(state, event_type, **kwargs)
```

Bases: `object`

A SimEvent is a log entry for some notable event during symbolic execution. It logs the location it was generated (ins_addr, bbl_addr, stmt_idx, and sim_procedure) as well as arbitrary tags (objects).

You may also be interested in SimAction, which is a specialization of SimEvent for CPU events.

```
__init__(state, event_type, **kwargs)
```

```
angr.state_plugins.sim_event.resource_event(state, exception)
```

10.11 Procedures

```
class angr.sim_procedure.SimProcedure(project=None, cc=None, prototype=None, symbolic_return=None,
                                       returns=None, is_syscall=False, is_stub=False, num_args=None,
                                       display_name=None, library_name=None, is_function=None,
                                       **kwargs)
```

Bases: `object`

A SimProcedure is a wonderful object which describes a procedure to run on a state.

You may subclass SimProcedure and override `run()`, replacing it with mutating `self.state` however you like, and then either returning a value or jumping away somehow.

A detailed discussion of programming SimProcedures may be found at <https://docs.angr.io/extending-angr/simprocedures>

Parameters

- **arch** – The architecture to use for this procedure
- **project** (`Project`) –
- **cc** (`SimCC`) –

- **prototype** (`SimTypeFunction`) –

The following parameters are optional:

Parameters

- **symbolic_return** – Whether the procedure’s return value should be stubbed into a single symbolic variable constrained to the real return value
- **returns** – Whether the procedure should return to its caller afterwards
- **is_syscall** – Whether this procedure is a syscall
- **num_args** – The number of arguments this procedure should extract
- **display_name** – The name to use when displaying this procedure
- **library_name** – The name of the library from which the function we’re emulating comes
- **cc** – The SimCC to use for this procedure
- **sim_kwargs** – Additional keyword arguments to be passed to `run()`
- **is_function** – Whether this procedure emulates a function
- **project** (`Project`) –
- **prototype** (`SimTypeFunction`) –

The following class variables should be set if necessary when implementing a new `SimProcedure`:

Variables

- **NO_RET** – Set this to true if control flow will never return from this function
- **DYNAMIC_RET** – Set this to true if whether the control flow returns from this function or not depends on the context (e.g., `libc`’s `error()` call). Must implement `dynamic_returns()` method.
- **ADDS_EXITS** – Set this to true if you do any control flow other than returning
- **IS_FUNCTION** – Does this procedure simulate a function? True by default
- **ARGS_MISMATCH** – Does this procedure have a different list of arguments than what is provided in the function specification? This may happen when we manually extract arguments in the `run()` method of a `SimProcedure`. False by default.
- **local_vars** – If you use `self.call()`, set this to a list of all the local variable names in your class. They will be restored on return.

Parameters

- **project** (`Project`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

The following instance variables are available when working with `simprocedures` from the inside or the outside:

Variables

- **project** – The associated `angr` project
- **arch** – The associated architecture
- **addr** – The linear address at which the procedure is executing
- **cc** – The calling convention in use for engaging with the ABI

- **canonical** – The canonical version of this SimProcedure. Procedures are deepcopied for many reasons, including to be able to store state related to a specific run and to be able to hook continuations.
- **kwargs** – Any extra keyword arguments used to construct the procedure; will be passed to run
- **display_name** – See the eponymous parameter
- **library_name** – See the eponymous parameter
- **abi** – If this is a syscall simprocedure, which ABI are we using to map the syscall numbers?
- **symbolic_return** – See the eponymous parameter
- **syscall_number** – If this procedure is a syscall, the number will be populated here.
- **returns** – See eponymous parameter and NO_RET cvar
- **is_syscall** – See eponymous parameter
- **is_function** – See eponymous parameter and cvar
- **is_stub** – See eponymous parameter
- **is_continuation** – Whether this procedure is the original or a continuation resulting from `self.call()`
- **continuations** – A mapping from name to each known continuation
- **run_func** – The name of the function implementing the procedure. “run” by default, but different in continuations.
- **num_args** – The number of arguments to the procedure. If not provided in the parameter, extracted from the definition of `self.run`

Parameters

- **project** (`Project`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

The following instance variables are only used in a copy of the procedure that is actually executing on a state:

Variables

- **state** – The SimState we should be mutating to perform the procedure
- **successors** – The SimSuccessors associated with the current step
- **arguments** – The function arguments, deserialized from the state
- **arg_session** – The ArgSession that was used to parse arguments out of the state, in case you need it for varargs
- **use_state_arguments** – Whether we’re using arguments extracted from the state or manually provided
- **ret_to** – The current return address
- **ret_expr** – The computed return value
- **call_ret_expr** – The return value from having used `self.call()`
- **inhibit_autoret** – Whether we should avoid automatically adding an exit for returning once the run function ends

- **arg_session** – The ArgSession object that was used to extract the runtime argument values. Useful for if you want to extract variadic args.

Parameters

- **project** (*Project*) –
- **cc** (*SimCC*) –
- **prototype** (*SimTypeFunction*) –

__init__ (*project=None, cc=None, prototype=None, symbolic_return=None, returns=None, is_syscall=False, is_stub=False, num_args=None, display_name=None, library_name=None, is_function=None, **kwargs*)

project: *Project*

arch: *Arch*

cc: *SimCC*

prototype: *SimTypeFunction*

state: *SimState*

arg_session: *Union[None, ArgSession, int]*

execute (*state, successors=None, arguments=None, ret_to=None*)

Call this method with a SimState and a SimSuccessors to execute the procedure.

Alternately, successors may be none if this is an inline call. In that case, you should provide arguments to the function.

make_continuation (*name*)

NO_RET = *False*

DYNAMIC_RET = *False*

ADDS_EXITS = *False*

IS_FUNCTION = *True*

ARGS_MISMATCH = *False*

ALT_NAMES = *None*

local_vars: *Tuple[str, ...] = ()*

run (**args, **kwargs*)

Implement the actual procedure here!

static_exits (*blocks, **kwargs*)

Get new exits by performing static analysis and heuristics. This is a fast and best-effort approach to get new exits for scenarios where states are not available (e.g. when building a fast CFG).

Parameters

blocks (*list*) – Blocks that are executed before reaching this SimProcedure.

Returns

A list of dicts. Each dict should contain the following entries: ‘address’, ‘jumpkind’, and ‘namehint’.

Return type

list

dynamic_returns(*blocks*, ***kwargs*)

Determines if a call to this function returns or not by performing static analysis and heuristics.

Parameters**blocks** – Blocks that are executed before reaching this SimProcedure.**Return type**

bool

Returns

True if the call returns, False otherwise.

property should_add_successors**set_args**(*args*)**va_arg**(*ty*, *index=None*)**inline_call**(*procedure*, **arguments*, ***kwargs*)Call another SimProcedure in-line to retrieve its return value. Returns an instance of the procedure with the `ret_expr` property set.**Parameters**

- **procedure** – The class of the procedure to execute
- **arguments** – Any additional positional args will be used as arguments to the procedure call
- **sim_kwargs** – Any additional keyword args will be passed as `sim_kwargs` to the procedure constructor

fix_prototype_returnty(*ret_size*)**ret**(*expr=None*)

Add an exit representing a return from this function. If this is not an inline call, grab a return address from the state and jump to it. If this is not an inline call, set a return expression with the calling convention.

call(*addr*, *args*, *continue_at*, *cc=None*, *prototype=None*, *jumpkind='Ijk_Call'*)

Add an exit representing calling another function via pointer.

Parameters

- **addr** – The address of the function to call
- **args** – The list of arguments to call the function with
- **continue_at** – Later, when the called function returns, execution of the current procedure will continue in the named method.
- **cc** – Optional: use this calling convention for calling the new function. Default is to use the current convention.
- **prototype** – Optional: The prototype to use for the call. Will default to all-ints.

jump(*addr*, *jumpkind='Ijk_Boring'*)

Add an exit representing jumping to an address.

exit(*exit_code*)

Add an exit representing terminating the program.

ty_ptr(*ty*)

property is_java

property argument_types

property return_type

class `angr.procedures.stubs.format_parser.FormatString`(*parser, components*)

Bases: `object`

Describes a format string.

SCANF_DELIMITERS = [`b'\t'`, `b'\n'`, `b'\x0b'`, `b'\r'`, `b' '`]

__init__(*parser, components*)

Takes a list of components which are either just strings or a `FormatSpecifier`.

property state

replace(*va_arg*)

Implement printf - based on the stored format specifier information, format the values from the arg getter function *args* into a string.

Parameters

va_arg – A function which takes a type and returns the next argument of that type

Returns

The result formatted string

interpret(*va_arg, addr=None, simfd=None*)

implement scanf - extract formatted data from memory or a file according to the stored format specifiers and store them into the pointers extracted from *args*.

Parameters

- **va_arg** – A function which, given a type, returns the next argument of that type
- **addr** – The address in the memory to extract data from, or...
- **simfd** – A file descriptor to use for reading data from

Returns

The number of arguments parsed

class `angr.procedures.stubs.format_parser.FormatSpecifier`(*string, length_spec, pad_chr, size, signed*)

Bases: `object`

Describes a format specifier within a format string.

__init__(*string, length_spec, pad_chr, size, signed*)

string

size

signed

length_spec

pad_chr

property spec_type

```
class angr.procedures.stubs.format_parser.FormatParser(project=None, cc=None, prototype=None,
                                                    symbolic_return=None, returns=None,
                                                    is_syscall=False, is_stub=False,
                                                    num_args=None, display_name=None,
                                                    library_name=None, is_function=None,
                                                    **kwargs)
```

Bases: [SimProcedure](#)

For SimProcedures relying on printf-style format strings.

Parameters

- **project** ([Project](#)) –
- **cc** ([SimCC](#)) –
- **prototype** ([SimTypeFunction](#)) –

ARGS_MISMATCH = True

```
basic_spec = {b'A': double, b'E': double, b'F': double, b'G': double, b'X': unsigned
int, b'a': double, b'c': char, b'd': int, b'e': double, b'f': double, b'g':
double, b'i': int, b'n': unsigned int*, b'o': unsigned int, b'p': unsigned int*,
b's': char*, b'u': unsigned int, b'x': unsigned int}
```

```
int_sign = {'signed': [b'd', b'i'], 'unsigned': [b'o', b'u', b'x', b'X']}
```

```
int_len_mod = {b'h': (short, unsigned short), b'hh': (char, char), b'j': (long
long, unsigned long long), b'l': (long, unsigned long), b'll': (long long,
unsigned long long), b't': (long, long), b'z': (size_t, size_t)}
```

```
other_types = {('string',): <function FormatParser.<lambda>>>}
```

```
flags = ['#', '0', '\\-', ' ', '\\+', "\\\"", 'I']
```

```
extract_components(fmt)
```

Extract the actual formats from the format string *fmt*.

Parameters

fmt ([List](#)) – A list of format chars.

Return type

[List](#)

Returns

a FormatString object

state: [SimState](#)

project: [angr.Project](#)

arch: [archinfo.arch.Arch](#)

cc: [angr.SimCC](#)

prototype: [angr.sim_type.SimTypeFunction](#)

arg_session: [Union\[None, ArgSession, int\]](#)

```
class angr.procedures.stubs.format_parser.ScanfFormatParser(project=None, cc=None,
                                                         prototype=None,
                                                         symbolic_return=None,
                                                         returns=None, is_syscall=False,
                                                         is_stub=False, num_args=None,
                                                         display_name=None,
                                                         library_name=None,
                                                         is_function=None, **kwargs)
```

Bases: [FormatParser](#)

For SimProcedures relying on scanf-style format strings.

```
basic_spec = {b'A': float, b'E': float, b'F': float, b'G': float, b'X': unsigned
int, b'a': float, b'c': char, b'd': int, b'e': float, b'f': float, b'g':
float, b'i': int, b'n': unsigned int*, b'o': unsigned int, b'p': unsigned int*,
b's': char*, b'u': unsigned int, b'x': unsigned int}
```

```
float_spec = [b'e', b'E', b'f', b'F', b'g', b'G', b'a', b'A']
```

```
float_len_mod = {b'l': <class 'angr.sim_type.SimTypeDouble'>, b'll': <class
'angr.sim_type.SimTypeDouble'>}
```

```
state: SimState
```

```
project: angr.Project
```

```
arch: archinfo.arch.Arch
```

```
cc: angr.SimCC
```

```
prototype: angr.sim_type.SimTypeFunction
```

```
arg_session: Union[None, ArgSession, int]
```

```
class angr.procedures.definitions.SimTypeCollection
```

Bases: [object](#)

A type collection is the mechanism for describing types. Types in a type collection can be referenced using

```
__init__()
```

```
set_names(*names)
```

```
add(name, t)
```

Add a type to the collection.

Parameters

- **name** ([str](#)) – Name of the type to add.
- **t** ([SimType](#)) – The SimType object to add to the collection.

Return type

[None](#)

```
get(name, bottom_on_missing=False)
```

Get a SimType object from the collection as identified by the name.

Parameters

- **name** ([str](#)) – Name of the type to get.

- **bottom_on_missing** (*bool*) – Return a `SimTypeBottom` object if the required type does not exist.

Return type

SimType

Returns

The `SimType` object.

init_str()

Return type

str

class `angr.procedures.definitions.SimLibrary`

Bases: *object*

A `SimLibrary` is the mechanism for describing a dynamic library’s API, its functions and metadata.

Any instance of this class (or its subclasses) found in the `angr.procedures.definitions` package will be automatically picked up and added to `angr.SIM_LIBRARIES` via all its names.

Variables

- **fallback_cc** – A mapping from architecture to the default calling convention that should be used if no other information is present. Contains some sane defaults for linux.
- **fallback_proc** – A `SimProcedure` class that should be used to provide stub procedures. By default, `ReturnUnconstrained`.

__init__()

copy()

Make a copy of this `SimLibrary`, allowing it to be mutated without affecting the global version.

Returns

A new `SimLibrary` object with the same library references but different dict/list references

update(*other*)

Augment this `SimLibrary` with the information from another `SimLibrary`

Parameters

other – The other `SimLibrary`

property name

The first common name of this library, e.g. `libc.so.6`, or ‘?????’ if none are known.

set_library_names(names*)**

Set some common names of this library by which it may be referred during linking

Parameters

names – Any number of string library names may be passed as varargs.

set_default_cc(*arch_name*, *cc_cls*)

Set the default calling convention used for this library under a given architecture

Parameters

arch_name – The string name of the architecture, i.e. the `.name` field from `archinfo`.

Param cc_cls

The `SimCC` class (not an instance!) to use

set_non_returning(*names)

Mark some functions in this class as never returning, i.e. loops forever or terminates execution

Parameters

names – Any number of string function names may be passed as varargs

set_prototype(name, proto)

Set the prototype of a function in the form of a SimTypeFunction containing argument and return types

Parameters

- **name** – The name of the function as a string
- **proto** – The prototype of the function as a SimTypeFunction

set_prototypes(protos)

Set the prototypes of many functions

Parameters

protos – Dictionary mapping function names to SimTypeFunction objects

set_c_prototype(c_decl)

Set the prototype of a function in the form of a C-style function declaration.

Parameters

c_decl (*str*) – The C-style declaration of the function.

Returns

A tuple of (function name, function prototype)

Return type

tuple

add(name, proc_cls, **kwargs)

Add a function implementation to the library.

Parameters

- **name** – The name of the function as a string
- **proc_cls** – The implementation of the function as a SimProcedure _class_, not instance
- **kwargs** – Any additional parameters to the procedure class constructor may be passed as kwargs

add_all_from_dict(dictionary, **kwargs)

Batch-add function implementations to the library.

Parameters

- **dictionary** – A mapping from name to procedure class, i.e. the first two arguments to add()
- **kwargs** – Any additional kwargs will be passed to the constructors of _each_ procedure class

add_alias(name, *alt_names)

Add some duplicate names for a given function. The original function's implementation must already be registered.

Parameters

- **name** – The name of the function for which an implementation is already present

- **alt_names** – Any number of alternate names may be passed as varargs

get(*name*, *arch*)

Get an implementation of the given function specialized for the given arch, or a stub procedure if none exists.

Parameters

- **name** – The name of the function as a string
- **arch** – The architecture to use, as either a string or an `archinfo.Arch` instance

Returns

A `SimProcedure` instance representing the function as found in the library

get_stub(*name*, *arch*)

Get a stub procedure for the given function, regardless of if a real implementation is available. This will apply any metadata, such as a default calling convention or a function prototype.

By stub, we pretty much always mean a `ReturnUnconstrained` `SimProcedure` with the appropriate display name and metadata set. This will appear in `state.history.descriptions` as `<SimProcedure display_name (stub)>`

Parameters

- **name** – The name of the function as a string
- **arch** – The architecture to use, as either a string or an `archinfo.Arch` instance

Returns

A `SimProcedure` instance representing a plausible stub as could be found in the library.

get_prototype(*name*, *arch=None*)

Get a prototype of the given function name, optionally specialize the prototype to a given architecture.

Parameters

- **name** (`str`) – Name of the function.
- **arch** – The architecture to specialize to.

Return type

`Optional[SimTypeFunction]`

Returns

Prototype of the function, or `None` if the prototype does not exist.

has_metadata(*name*)

Check if a function has either an implementation or any metadata associated with it

Parameters

name – The name of the function as a string

Returns

A bool indicating if anything is known about the function

has_implementation(*name*)

Check if a function has an implementation associated with it

Parameters

name – The name of the function as a string

Returns

A bool indicating if an implementation of the function is available

has_prototype(*func_name*)

Check if a function has a prototype associated with it.

Parameters

func_name (*str*) – The name of the function.

Returns

A bool indicating if a prototype of the function is available.

Return type

bool

class `angr.procedures.definitions.SimCppLibrary`

Bases: *SimLibrary*

SimCppLibrary is a specialized version of SimLibrary that will demangle C++ function names before looking for an implementation or prototype for it.

get(*name*, *arch*)

Get an implementation of the given function specialized for the given arch, or a stub procedure if none exists. Demangle the function name if it is a mangled C++ name.

Parameters

- **name** (*str*) – The name of the function as a string
- **arch** – The architecture to use, as either a string or an `archinfo.Arch` instance

Returns

A `SimProcedure` instance representing the function as found in the library

get_stub(*name*, *arch*)

Get a stub procedure for the given function, regardless of if a real implementation is available. This will apply any metadata, such as a default calling convention or a function prototype. Demangle the function name if it is a mangled C++ name.

Parameters

- **name** (*str*) – The name of the function as a string
- **arch** – The architecture to use, as either a string or an `archinfo.Arch` instance

Returns

A `SimProcedure` instance representing a plausible stub as could be found in the library.

get_prototype(*name*, *arch=None*)

Get a prototype of the given function name, optionally specialize the prototype to a given architecture. The function name will be demangled first.

Parameters

- **name** (*str*) – Name of the function.
- **arch** – The architecture to specialize to.

Return type

`Optional[SimTypeFunction]`

Returns

Prototype of the function, or `None` if the prototype does not exist.

has_metadata(*name*)

Check if a function has either an implementation or any metadata associated with it. Demangle the function name if it is a mangled C++ name.

Parameters

name – The name of the function as a string

Returns

A bool indicating if anything is known about the function

has_implementation(*name*)

Check if a function has an implementation associated with it. Demangle the function name if it is a mangled C++ name.

Parameters

name (*str*) – A mangled function name.

Returns

bool

has_prototype(*func_name*)

Check if a function has a prototype associated with it. Demangle the function name if it is a mangled C++ name.

Parameters

name (*str*) – A mangled function name.

Returns

bool

class angr.procedures.definitions.SimSyscallLibrary

Bases: *SimLibrary*

SimSyscallLibrary is a specialized version of SimLibrary for dealing not with a dynamic library’s API but rather an operating system’s syscall API. Because this interface is inherently lower-level than a dynamic library, many parts of this class has been changed to store data based on an “ABI name” (ABI = application binary interface, like an API but for when there’s no programming language) instead of an architecture. An ABI name is just an arbitrary string with which a calling convention and a syscall numbering is associated.

All the SimLibrary methods for adding functions still work, but now there’s an additional layer on top that associates them with numbers.

__init__()
copy()

Make a copy of this SimLibrary, allowing it to be mutated without affecting the global version.

Returns

A new SimLibrary object with the same library references but different dict/list references

update(*other*)

Augment this SimLibrary with the information from another SimLibrary

Parameters

other – The other SimLibrary

minimum_syscall_number(*abi*)
Parameters

abi – The abi to evaluate

Returns

The smallest syscall number known for the given abi

maximum_syscall_number(*abi*)

Parameters

abi – The abi to evaluate

Returns

The largest syscall number known for the given abi

add_number_mapping(*abi, number, name*)

Associate a syscall number with the name of a function present in the underlying SimLibrary

Parameters

- **abi** – The abi for which this mapping applies
- **number** – The syscall number
- **name** – The name of the function

add_number_mapping_from_dict(*abi, mapping*)

Batch-associate syscall numbers with names of functions present in the underlying SimLibrary

Parameters

- **abi** – The abi for which this mapping applies
- **mapping** – A dict mapping syscall numbers to function names

set_abi_cc(*abi, cc_cls*)

Set the default calling convention for an abi

Parameters

- **abi** – The name of the abi
- **cc_cls** – A SimCC `_class_`, not an instance, that should be used for syscalls using the abi

set_prototype(*abi, name, proto*)

Set the prototype of a function in the form of a SimTypeFunction containing argument and return types

Parameters

- **abi** (*str*) – ABI of the syscall.
- **name** (*str*) – The name of the syscall as a string
- **proto** (*SimTypeFunction*) – The prototype of the syscall as a SimTypeFunction

Return type

None

set_prototypes(*abi, protos*)

Set the prototypes of many syscalls.

Parameters

- **abi** (*str*) – ABI of the syscalls.
- **protos** (*Dict[str, SimTypeFunction]*) – Dictionary mapping syscall names to SimTypeFunction objects

Return type

None

get(*number*, *arch*, *abi_list*=())

The `get()` function for `SimSyscallLibrary` looks a little different from its original version.

Instead of providing a name, you provide a number, and you additionally provide a list of abi names that are applicable. The first abi for which the number is present in the mapping will be chosen. This allows for the easy abstractions of architectures like ARM or MIPS linux for which there are many ABIs that can be used at any time by using syscall numbers from various ranges. If no abi knows about the number, the stub procedure with the name “`sys_%d`” will be used.

Parameters

- **number** – The syscall number
- **arch** – The architecture being worked with, as either a string name or an `archinfo.Arch`
- **abi_list** – A list of ABI names that could be used

Returns

A `SimProcedure` representing the implementation of the given syscall, or a stub if no implementation is available

get_stub(*number*, *arch*, *abi_list*=())

Pretty much the intersection of `SimLibrary.get_stub()` and `SimSyscallLibrary.get()`.

Parameters

- **number** – The syscall number
- **arch** – The architecture being worked with, as either a string name or an `archinfo.Arch`
- **abi_list** – A list of ABI names that could be used

Returns

A `SimProcedure` representing a plausible stub that could model the syscall

get_prototype(*abi*, *name*, *arch*=None)

Get a prototype of the given syscall name and its ABI, optionally specialize the prototype to a given architecture.

Parameters

- **abi** (`str`) – ABI of the prototype to get.
- **name** (`str`) – Name of the syscall.
- **arch** – The architecture to specialize to.

Return type

`Optional[SimTypeFunction]`

Returns

Prototype of the syscall, or `None` if the prototype does not exist.

has_metadata(*number*, *arch*, *abi_list*=())

Pretty much the intersection of `SimLibrary.has_metadata()` and `SimSyscallLibrary.get()`.

Parameters

- **number** – The syscall number
- **arch** – The architecture being worked with, as either a string name or an `archinfo.Arch`
- **abi_list** – A list of ABI names that could be used

Returns

A bool of whether or not any implementation or metadata is known about the given syscall

has_implementation(*number*, *arch*, *abi_list*=())

Pretty much the intersection of `SimLibrary.has_implementation()` and `SimSyscallLibrary.get()`.

Parameters

- **number** – The syscall number
- **arch** – The architecture being worked with, as either a string name or an `archinfo.Arch`
- **abi_list** – A list of ABI names that could be used

Returns

A bool of whether or not an implementation of the syscall is available

has_prototype(*abi*, *name*)

Check if a function has a prototype associated with it. Demangle the function name if it is a mangled C++ name.

Parameters

- **abi** (*str*) – Name of the ABI.
- **name** (*str*) – The syscall name.

Return type

bool

Returns

bool

`angr.procedures.definitions.load_type_collections(skip=None)`

Return type

None

`angr.procedures.definitions.load_win32_type_collections()`

Return type

None

`angr.procedures.definitions.load_external_definitions()`

Load library definitions from specific directories. By default it parses `ANGR_EXTERNAL_DEFINITIONS_DIRS` as a semicolon separated list of directory paths. Then it loads all .py files in each directory. These .py files should declare `SimLibrary()` objects and call `.set_library_names()` to register themselves in `angr.SIM_LIBRARIES`.

`angr.procedures.definitions.load_win32api_definitions()`

`angr.procedures.definitions.load_all_definitions()`

10.12 Calling Conventions and Types

class `angr.calling_conventions.PointerWrapper`(*value*, *buffer*=False)

Bases: *object*

__init__(*value*, *buffer*=False)

class `angr.calling_conventions.AllocHelper`(*ptrsize*)

Bases: *object*

```

__init__(ptrsize)

alloc(size)

dump(val, state, loc=None)

translate(val, base)

apply(state, base)

size()

classmethod calc_size(val, arch)

classmethod stack_loc(val, arch, offset=0)

```

```

angr.calling_conventions.refine_locs_with_struct_type(arch, locs, arg_type, offset=0,
                                                    treat_bot_as_int=True)

```

Parameters

- **arch** (*Arch*) –
- **locs** (*List*) –
- **arg_type** (*SimType*) –
- **offset** (*int*) –

```

class angr.calling_conventions.SerializableIterator

```

Bases: *object*

```

getstate()

setstate(state)

```

```

class angr.calling_conventions.SerializableListIterator(lst)

```

Bases: *SerializableIterator*

```

__init__(lst)

getstate()

setstate(state)

```

```

class angr.calling_conventions.SerializableCounter(start, stride, mapping=<function
                                                    SerializableCounter.<lambda>>)

```

Bases: *SerializableIterator*

```

__init__(start, stride, mapping=<function SerializableCounter.<lambda>>)

getstate()

setstate(state)

```

```

class angr.calling_conventions.SimFunctionArgument(size, is_fp=False)

```

Bases: *object*

Represent a generic function argument.

Variables

- **size** (*int*) – The size of the argument, in number of bytes.

- **is_fp** (*bool*) – Whether loads from this location should return a floating point bitvector

__init__(*size*, *is_fp=False*)

check_value_set(*value*, *arch*)

check_value_get(*value*)

set_value(*state*, *value*, ***kwargs*)

get_value(*state*, ***kwargs*)

refine(*size*, *arch=None*, *offset=None*, *is_fp=None*)

get_footprint()

Return a list of SimRegArg and SimStackArgs that are the base components used for this location

Return type

`List[Union[SimRegArg, SimStackArg]]`

class `angr.calling_conventions.SimRegArg`(*reg_name*, *size*, *reg_offset=0*, *is_fp=False*,
clear_entire_reg=False)

Bases: `SimFunctionArgument`

Represents a function argument that has been passed in a register.

Variables

- **reg_name** (*string*) – The name of the represented register.
- **size** (*int*) – The size of the data to store, in number of bytes.
- **reg_offset** – The offset into the register to start storing data.
- **clear_entire_reg** – Whether a store to this register should zero the unused parts of the register.
- **is_fp** (*bool*) – Whether loads from this location should return a floating point bitvector

Parameters

- **reg_name** (*str*) –
- **size** (*int*) –

__init__(*reg_name*, *size*, *reg_offset=0*, *is_fp=False*, *clear_entire_reg=False*)

Parameters

- **reg_name** (*str*) –
- **size** (*int*) –

get_footprint()

Return a list of SimRegArg and SimStackArgs that are the base components used for this location

check_offset(*arch*)

set_value(*state*, *value*, ***kwargs*)

get_value(*state*, ***kwargs*)

refine(*size*, *arch=None*, *offset=None*, *is_fp=None*)

sse_extend()

class `angr.calling_conventions.SimStackArg(stack_offset, size, is_fp=False)`

Bases: `SimFunctionArgument`

Represents a function argument that has been passed on the stack.

Variables

- **stack_offset** (`int`) – The position of the argument relative to the stack pointer after the function prelude.
- **size** (`int`) – The size of the argument, in number of bytes.
- **is_fp** (`bool`) – Whether loads from this location should return a floating point bitvector

__init__(`stack_offset, size, is_fp=False`)

get_footprint()

Return a list of `SimRegArg` and `SimStackArgs` that are the base components used for this location

set_value(`state, value, stack_base=None, **kwargs`)

get_value(`state, stack_base=None, **kwargs`)

refine(`size, arch=None, offset=None, is_fp=None`)

class `angr.calling_conventions.SimComboArg(locations, is_fp=False)`

Bases: `SimFunctionArgument`

An argument which spans multiple storage locations. Locations should be given least-significant first.

__init__(`locations, is_fp=False`)

get_footprint()

Return a list of `SimRegArg` and `SimStackArgs` that are the base components used for this location

set_value(`state, value, **kwargs`)

get_value(`state, **kwargs`)

class `angr.calling_conventions.SimStructArg(struct, locs)`

Bases: `SimFunctionArgument`

An argument which de/serializes a struct from a list of storage locations

Variables

- **struct** – The simtype describing the structure
- **locs** – The storage locations to use

Parameters

- **struct** (`SimStruct`) –
- **locs** (`Dict[str, SimFunctionArgument]`) –

__init__(`struct, locs`)

Parameters

- **struct** (`SimStruct`) –
- **locs** (`Dict[str, SimFunctionArgument]`) –

get_footprint()

Return a list of SimRegArg and SimStackArgs that are the base components used for this location

get_value(state, **kwargs)

set_value(state, value, **kwargs)

class angr.calling_conventions.**SimArrayArg**(locs)

Bases: [SimFunctionArgument](#)

__init__(locs)

get_footprint()

Return a list of SimRegArg and SimStackArgs that are the base components used for this location

get_value(state, **kwargs)

set_value(state, value, **kwargs)

class angr.calling_conventions.**SimReferenceArgument**(ptr_loc, main_loc)

Bases: [SimFunctionArgument](#)

A function argument which is passed by reference.

Variables

- **ptr_loc** – The location the reference’s pointer is stored
- **main_loc** – A SimStackArgument describing how to load the argument’s value as if it were stored at offset zero on the stack. It will be passed `stack_base=ptr_loc.get_value(state)`

__init__(ptr_loc, main_loc)

get_footprint()

Return a list of SimRegArg and SimStackArgs that are the base components used for this location

get_value(state, **kwargs)

set_value(state, value, **kwargs)

class angr.calling_conventions.**ArgSession**(cc)

Bases: [object](#)

A class to keep track of the state accumulated in laying parameters out into memory

__init__(cc)

cc

fp_iter

int_iter

both_iter

getstate()

setstate(state)

```
class angr.calling_conventions.UsercallArgSession(cc)
```

Bases: `object`

An argsession for use with SimCCUsercall

```
__init__(cc)
```

```
cc
```

```
real_args
```

```
getstate()
```

```
setstate(state)
```

```
class angr.calling_conventions.SimCC(arch)
```

Bases: `object`

A calling convention allows you to extract from a state the data passed from function to function by calls and returns. Most of the methods provided by SimCC that operate on a state assume that the program is just after a call but just before stack frame allocation, though this may be overridden with the *stack_base* parameter to each individual method.

This is the base class for all calling conventions.

Parameters

arch (`Arch`) –

```
__init__(arch)
```

Parameters

arch (`Arch`) – The Archinfo arch for this CC

```
ARG_REGS: List[str] = []
```

```
FP_ARG_REGS: List[str] = []
```

```
STACKARG_SP_BUFF = 0
```

```
STACKARG_SP_DIFF = 0
```

```
CALLER_SAVED_REGS: List[str] = []
```

```
RETURN_ADDR: SimFunctionArgument = None
```

```
RETURN_VAL: SimFunctionArgument = None
```

```
OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = None
```

```
FP_RETURN_VAL: Optional[SimFunctionArgument] = None
```

```
ARCH = None
```

```
CALLEE_CLEANUP = False
```

```
STACK_ALIGNMENT = 1
```

```
property int_args
```

Iterate through all the possible arg positions that can only be used to store integer or pointer values.

Returns an iterator of SimFunctionArguments

property memory_args

Iterate through all the possible arg positions that can be used to store any kind of argument.

Returns an iterator of SimFunctionArguments

property fp_args

Iterate through all the possible arg positions that can only be used to store floating point values.

Returns an iterator of SimFunctionArguments

is_fp_arg(arg)

This should take a SimFunctionArgument instance and return whether or not that argument is a floating-point argument.

Returns True for MUST be a floating point arg,

False for MUST NOT be a floating point arg, None for when it can be either.

class ArgSession(cc)

Bases: `object`

A class to keep track of the state accumulated in laying parameters out into memory

cc

fp_iter

int_iter

both_iter

__init__(cc)

getstate()

setstate(state)

arg_session(ret_ty)

Return an arg session.

A session provides the control interface necessary to describe how integral and floating-point arguments are laid out into memory. The default behavior is that there are a finite list of int-only and fp-only argument slots, and an infinite number of generic slots, and when an argument of a given type is requested, the most slot available is used. If you need different behavior, subclass ArgSession.

You need to provide the return type of the function in order to kick off an arg layout session.

Parameters

ret_ty (`SimType` / `None`) –

return_in_implicit_outparam(ty)**stack_space(args)****Parameters**

args – A list of SimFunctionArguments

Returns

The number of bytes that should be allocated on the stack to store all these args, NOT INCLUDING the return address.

return_val(ty, perspective_returned=False)

The location the return value is stored, based on its type.

property return_addr

The location the return address is stored.

next_arg(*session*, *arg_type*)

Parameters

- **session** (*ArgSession*) –
- **arg_type** (*SimType*) –

static is_fp_value(*val*)

static guess_prototype(*args*, *prototype=None*)

Come up with a plausible *SimTypeFunction* for the given args (as would be passed to e.g. *setup_callsite*).

You can pass a variadic function prototype in the *base_type* parameter and all its arguments will be used, only guessing types for the variadic arguments.

arg_locs(*prototype*)

Return type

List[SimFunctionArgument]

get_args(*state*, *prototype*, *stack_base=None*)

set_return_val(*state*, *val*, *ty*, *stack_base=None*, *perspective_returned=False*)

setup_callsite(*state*, *ret_addr*, *args*, *prototype*, *stack_base=None*, *alloc_base=None*, *grow_like_stack=True*)

This function performs the actions of the caller getting ready to jump into a function.

Parameters

- **state** – The *SimState* to operate on
- **ret_addr** – The address to return to when the called function finishes
- **args** – The list of arguments that that the called function will see
- **prototype** – The signature of the call you’re making. Should include variadic args concretely.
- **stack_base** – An optional pointer to use as the top of the stack, circa the function entry point
- **alloc_base** – An optional pointer to use as the place to put excess argument data
- **grow_like_stack** – When allocating data at *alloc_base*, whether to allocate at decreasing addresses

The idea here is that you can provide almost any kind of python type in *args* and it’ll be translated to a binary format to be placed into simulated memory. Lists (representing arrays) must be entirely elements of the same type and size, while tuples (representing structs) can be elements of any type and size. If you’d like there to be a pointer to a given value, wrap the value in a *PointerWrapper*.

If *stack_base* is not provided, the current stack pointer will be used, and it will be updated. If *alloc_base* is not provided, the stack base will be used and *grow_like_stack* will implicitly be *True*.

grow_like_stack controls the behavior of allocating data at *alloc_base*. When data from args needs to be wrapped in a pointer, the pointer needs to point somewhere, so that data is dumped into memory at *alloc_base*. If you set *alloc_base* to point to somewhere other than the stack, set *grow_like_stack* to *False* so that sequential allocations happen at increasing addresses.

teardown_callsite(*state*, *return_val*=None, *prototype*=None, *force_callee_cleanup*=False)

This function performs the actions of the callee as it's getting ready to return. It returns the address to return to.

Parameters

- **state** – The state to mutate
- **return_val** – The value to return
- **prototype** – The prototype of the given function
- **force_callee_cleanup** – If we should clean up the stack allocation for the arguments even if it's not the callee's job to do so

TODO: support the `stack_base` parameter from `setup_callsite`...? Does that make sense in this context? Maybe it could make sense by saying that you pass it in as something like the “saved base pointer” value?

static find_cc(*arch*, *args*, *sp_delta*, *platform*='Linux')

Pinpoint the best-fit calling convention and return the corresponding SimCC instance, or None if no fit is found.

Parameters

- **arch** ([Arch](#)) – An ArchX instance. Can be obtained from `archinfo`.
- **args** ([List\[SimFunctionArgument\]](#)) – A list of arguments. It may be updated by the first matched calling convention to remove non-argument arguments.
- **sp_delta** ([int](#)) – The change of stack pointer before and after the call is made.
- **platform** ([str](#)) –

Return type

[Optional\[SimCC\]](#)

Returns

A calling convention instance, or None if none of the SimCC subclasses seems to fit the arguments provided.

get_arg_info(*state*, *prototype*)

This is just a simple wrapper that collects the information from various locations `prototype` is as passed to `self.arg_locs` and `self.get_args`:
 :param `angr.SimState state`: The state to evaluate and extract the values from
 :return: A list of tuples, where the `n`th tuple is (type, name, location, value) of the `n`th argument

class `angr.calling_conventions.SimLyingRegArg`(*name*, *size*=8)

Bases: [SimRegArg](#)

A register that LIES about the types it holds

__init__(*name*, *size*=8)

get_value(*state*, ***kwargs*)

set_value(*state*, *value*, ***kwargs*)

refine(*size*, *arch*=None, *offset*=None, *is_fp*=None)

class `angr.calling_conventions.SimCCUsercall`(*arch*, *args*, *ret_loc*)

Bases: [SimCC](#)

```

__init__(arch, args, ret_loc)

    Parameters
    arch – The Archinfo arch for this CC

ArgSession
    alias of UsercallArgSession

next_arg(session, arg_type)

return_val(ty, **kwargs)
    The location the return value is stored, based on its type.

class angr.calling_conventions.SimCCdecl(arch)
    Bases: SimCC

    Parameters
    arch (Arch) –

    ARG_REGS: List[str] = []

    FP_ARG_REGS: List[str] = []

    STACKARG_SP_DIFF = 4

    CALLER_SAVED_REGS: List[str] = ['eax', 'ecx', 'edx']

    RETURN_VAL: SimFunctionArgument = <eax>

    OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = <edx>

    FP_RETURN_VAL: Optional[SimFunctionArgument] = <st0>

    RETURN_ADDR: SimFunctionArgument = [0x0]

    ARCH
        alias of ArchX86

    next_arg(session, arg_type)

    STRUCT_RETURN_THRESHOLD = 32

    return_val(ty, perspective_returned=False)
        The location the return value is stored, based on its type.

    return_in_implicit_outparam(ty)

class angr.calling_conventions.SimCCMicrosoftCdecl(arch)
    Bases: SimCCdecl

    Parameters
    arch (Arch) –

    STRUCT_RETURN_THRESHOLD = 64

class angr.calling_conventions.SimCCStdcall(arch)
    Bases: SimCCMicrosoftCdecl

    Parameters
    arch (Arch) –

```

```

    CALLEE_CLEANUP = True

class angr.calling_conventions.SimCCMicrosoftFastcall(arch)
    Bases: SimCC
        Parameters
            arch (Arch) –

    ARG_REGS: List[str] = ['ecx', 'edx']

    STACKARG_SP_DIFF = 4

    RETURN_VAL: SimFunctionArgument = <eax>

    RETURN_ADDR: SimFunctionArgument = [0x0]

    ARCH
        alias of ArchX86

class angr.calling_conventions.MicrosoftAMD64ArgSession(cc)
    Bases: object
    __init__(cc)

class angr.calling_conventions.SimCCMicrosoftAMD64(arch)
    Bases: SimCC
        Parameters
            arch (Arch) –

    ARG_REGS: List[str] = ['rcx', 'rdx', 'r8', 'r9']

    FP_ARG_REGS: List[str] = ['xmm0', 'xmm1', 'xmm2', 'xmm3']

    STACKARG_SP_DIFF = 8

    STACKARG_SP_BUFF = 32

    RETURN_VAL: SimFunctionArgument = <rax>

    OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = <rdx>

    FP_RETURN_VAL: Optional[SimFunctionArgument] = <xmm0>

    RETURN_ADDR: SimFunctionArgument = [0x0]

    ARCH
        alias of ArchAMD64

    STACK_ALIGNMENT = 16

    ArgSession
        alias of MicrosoftAMD64ArgSession

    next_arg(session, arg_type)

    return_in_implicit_outparam(ty)

```

```

class angr.calling_conventions.SimCCSyscall(arch)
    Bases: SimCC
    The base class of all syscall CCs.

    Parameters
        arch (Arch) –

    ERROR_REG: SimRegArg = None

    SYSCALL_ERRNO_START = None

    static syscall_num(state)

        Return type
        int

    linux_syscall_update_error_reg(state, expr)

    set_return_val(state, val, ty, **kwargs)

class angr.calling_conventions.SimCCX86LinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['ebx', 'ecx', 'edx', 'esi', 'edi', 'ebp']

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <eax>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchX86

    static syscall_num(state)

class angr.calling_conventions.SimCCX86WindowsSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = []

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <eax>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchX86

    static syscall_num(state)

```

```

class angr.calling_conventions.SimCCSystemVAMD64(arch)
    Bases: SimCC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['rdi', 'rsi', 'rdx', 'rcx', 'r8', 'r9']

    FP_ARG_REGS: List[str] = ['xmm0', 'xmm1', 'xmm2', 'xmm3', 'xmm4', 'xmm5', 'xmm6',
                              'xmm7']

    STACKARG_SP_DIFF = 8

    CALLER_SAVED_REGS: List[str] = ['rdi', 'rsi', 'rdx', 'rcx', 'r8', 'r9', 'r10',
                                     'r11', 'rax']

    RETURN_ADDR: SimFunctionArgument = [0x0]

    RETURN_VAL: SimFunctionArgument = <rax>

    OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = <rdx>

    FP_RETURN_VAL: Optional[SimFunctionArgument] = <xmm0>

    OVERFLOW_FP_RETURN_VAL = <xmm1>

    ARCH
        alias of ArchAMD64

    STACK_ALIGNMENT = 16

    next_arg(session, arg_type)

    return_val(ty, perspective_returned=False)
        The location the return value is stored, based on its type.

    Parameters
        ty (SimType / None) –

    return_in_implicit_outparam(ty)

class angr.calling_conventions.SimCCAMD64LinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['rdi', 'rsi', 'rdx', 'r10', 'r8', 'r9']

    RETURN_VAL: SimFunctionArgument = <rax>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchAMD64

    CALLER_SAVED_REGS: List[str] = ['rax', 'rcx', 'r11']

    static syscall_num(state)

```

```

class angr.calling_conventions.SimCCAMD64WindowsSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = []

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <rax>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchAMD64

    static syscall_num(state)

class angr.calling_conventions.SimCCARM(arch)
    Bases: SimCC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r0', 'r1', 'r2', 'r3']

    FP_ARG_REGS: List[str] = []

    CALLER_SAVED_REGS: List[str] = []

    RETURN_ADDR: SimFunctionArgument = <lr>

    RETURN_VAL: SimFunctionArgument = <r0>

    OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = <r1>

    ARCH
        alias of ArchARM

    next_arg(session, arg_type)

class angr.calling_conventions.SimCCARMHF(arch)
    Bases: SimCCARM

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r0', 'r1', 'r2', 'r3']

    FP_ARG_REGS: List[str] = ['s0', 's1', 's2', 's3', 's4', 's5', 's6', 's7', 's8',
                              's9', 's10', 's11', 's12', 's13', 's14', 's15']

    FP_RETURN_VAL: Optional[SimFunctionArgument] = <s0>

    CALLER_SAVED_REGS: List[str] = []

    RETURN_ADDR: SimFunctionArgument = <lr>

    RETURN_VAL: SimFunctionArgument = <r0>

```

ARCH

alias of `ArchARMHF`

`class angr.calling_conventions.SimCCARMLinuxSyscall(arch)`

Bases: `SimCCSyscall`

Parameters

`arch` (`Arch`) –

`ARG_REGS: List[str] = ['r0', 'r1', 'r2', 'r3']`

`FP_ARG_REGS: List[str] = []`

`RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>`

`RETURN_VAL: SimFunctionArgument = <r0>`

ARCH

alias of `ArchARM`

`static syscall_num(state)`

`class angr.calling_conventions.SimCCAArch64(arch)`

Bases: `SimCC`

Parameters

`arch` (`Arch`) –

`ARG_REGS: List[str] = ['x0', 'x1', 'x2', 'x3', 'x4', 'x5', 'x6', 'x7']`

`FP_ARG_REGS: List[str] = []`

`RETURN_ADDR: SimFunctionArgument = <lr>`

`RETURN_VAL: SimFunctionArgument = <x0>`

ARCH

alias of `ArchAArch64`

`class angr.calling_conventions.SimCCAArch64LinuxSyscall(arch)`

Bases: `SimCCSyscall`

Parameters

`arch` (`Arch`) –

`ARG_REGS: List[str] = ['x0', 'x1', 'x2', 'x3', 'x4', 'x5', 'x6', 'x7']`

`FP_ARG_REGS: List[str] = []`

`RETURN_VAL: SimFunctionArgument = <x0>`

`RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>`

ARCH

alias of `ArchAArch64`

`static syscall_num(state)`


```
class angr.calling_conventions.SimCCRISCV64LinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3', 'a4', 'a5', 'a6', 'a7']

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <a0>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchRISCV64

    static syscall_num(state)
```

```
class angr.calling_conventions.SimCC032(arch)
    Bases: SimCC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3']

    FP_ARG_REGS: List[str] = ['f12', 'f13', 'f14', 'f15']

    STACKARG_SP_BUFF = 16

    CALLER_SAVED_REGS: List[str] = ['t9', 'gp']

    RETURN_ADDR: SimFunctionArgument = <ra>

    RETURN_VAL: SimFunctionArgument = <v0>

    OVERFLOW_RETURN_VAL: Optional[SimFunctionArgument] = <v1>

    ARCH
        alias of ArchMIPS32

    next_arg(session, arg_type)
```

```
class angr.calling_conventions.SimCC032LinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3']

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <v0>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchMIPS32
```

```

    ERROR_REG: SimRegArg = <a3>

    SYSCALL_ERRNO_START = -1133

    static syscall_num(state)

class angr.calling_conventions.SimCCN64(arch)
    Bases: SimCC

        Parameters
            arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3', 'a4', 'a5', 'a6', 'a7']

    CALLER_SAVED_REGS: List[str] = ['t9', 'gp']

    FP_ARG_REGS: List[str] = []

    STACKARG_SP_BUFF = 32

    RETURN_ADDR: SimFunctionArgument = <ra>

    RETURN_VAL: SimFunctionArgument = <v0>

    ARCH
        alias of ArchMIPS64

angr.calling_conventions.SimCCO64
    alias of SimCCN64

class angr.calling_conventions.SimCCN64LinuxSyscall(arch)
    Bases: SimCCSyscall

        Parameters
            arch (Arch) –

    ARG_REGS: List[str] = ['a0', 'a1', 'a2', 'a3', 'a4', 'a5', 'a6', 'a7']

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <v0>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchMIPS64

    ERROR_REG: SimRegArg = <a3>

    SYSCALL_ERRNO_START = -1133

    static syscall_num(state)

class angr.calling_conventions.SimCCPowerPC(arch)
    Bases: SimCC

        Parameters
            arch (Arch) –

    ARG_REGS: List[str] = ['r3', 'r4', 'r5', 'r6', 'r7', 'r8', 'r9', 'r10']

```

```

FP_ARG_REGS: List[str] = []

STACKARG_SP_BUFF = 8

RETURN_ADDR: SimFunctionArgument = <lr>

RETURN_VAL: SimFunctionArgument = <r3>

ARCH
    alias of ArchPPC32

class angr.calling_conventions.SimCCPowerPCLinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r3', 'r4', 'r5', 'r6', 'r7', 'r8', 'r9', 'r10']

    FP_ARG_REGS: List[str] = []

    RETURN_VAL: SimFunctionArgument = <r3>

    RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

    ARCH
        alias of ArchPPC32

    ERROR_REG: SimRegArg = <cr0_0>

    SYSCALL_ERRNO_START = -515

    static syscall_num(state)

class angr.calling_conventions.SimCCPowerPC64(arch)
    Bases: SimCC

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r3', 'r4', 'r5', 'r6', 'r7', 'r8', 'r9', 'r10']

    FP_ARG_REGS: List[str] = []

    STACKARG_SP_BUFF = 112

    RETURN_ADDR: SimFunctionArgument = <lr>

    RETURN_VAL: SimFunctionArgument = <r3>

    ARCH
        alias of ArchPPC64

class angr.calling_conventions.SimCCPowerPC64LinuxSyscall(arch)
    Bases: SimCCSyscall

    Parameters
        arch (Arch) –

    ARG_REGS: List[str] = ['r3', 'r4', 'r5', 'r6', 'r7', 'r8', 'r9', 'r10']

```

```

FP_ARG_REGS: List[str] = []

RETURN_VAL: SimFunctionArgument = <r3>

RETURN_ADDR: SimFunctionArgument = <ip_at_syscall>

ARCH
    alias of ArchPPC64

ERROR_REG: SimRegArg = <cr0_0>

SYSCALL_ERRNO_START = -515

static syscall_num(state)

class angr.calling_conventions.SimCCSoot(arch)
    Bases: SimCC
        Parameters
            arch (Arch) –
        ARCH
            alias of ArchSoot
        ARG_REGS: List[str] = []
        setup_callsite(state, ret_addr, args, prototype, stack_base=None, alloc_base=None,
                       grow_like_stack=True)

```

This function performs the actions of the caller getting ready to jump into a function.

Parameters

- **state** – The SimState to operate on
- **ret_addr** – The address to return to when the called function finishes
- **args** – The list of arguments that that the called function will see
- **prototype** – The signature of the call you’re making. Should include variadic args concretely.
- **stack_base** – An optional pointer to use as the top of the stack, circa the function entry point
- **alloc_base** – An optional pointer to use as the place to put excess argument data
- **grow_like_stack** – When allocating data at alloc_base, whether to allocate at decreasing addresses

The idea here is that you can provide almost any kind of python type in *args* and it’ll be translated to a binary format to be placed into simulated memory. Lists (representing arrays) must be entirely elements of the same type and size, while tuples (representing structs) can be elements of any type and size. If you’d like there to be a pointer to a given value, wrap the value in a *PointerWrapper*.

If *stack_base* is not provided, the current stack pointer will be used, and it will be updated. If *alloc_base* is not provided, the stack base will be used and *grow_like_stack* will implicitly be True.

grow_like_stack controls the behavior of allocating data at *alloc_base*. When data from *args* needs to be wrapped in a pointer, the pointer needs to point somewhere, so that data is dumped into memory at *alloc_base*. If you set *alloc_base* to point to somewhere other than the stack, set *grow_like_stack* to False so that sequential allocations happen at increasing addresses.

static guess_prototype(args, prototype=None)

Come up with a plausible SimTypeFunction for the given args (as would be passed to e.g. setup_callsite).

You can pass a variadic function prototype in the *base_type* parameter and all its arguments will be used, only guessing types for the variadic arguments.

class angr.calling_conventions.SimCCUnknown(arch)

Bases: *SimCC*

Represent an unknown calling convention.

Parameters

arch (*Arch*) –

class angr.calling_conventions.SimCCS390X(arch)

Bases: *SimCC*

Parameters

arch (*Arch*) –

ARG_REGS: *List[str]* = ['r2', 'r3', 'r4', 'r5', 'r6']

FP_ARG_REGS: *List[str]* = ['f0', 'f2', 'f4', 'f6']

STACKARG_SP_BUFF = 160

RETURN_ADDR: *SimFunctionArgument* = <r14>

RETURN_VAL: *SimFunctionArgument* = <r2>

ARCH

alias of *ArchS390X*

class angr.calling_conventions.SimCCS390XLinuxSyscall(arch)

Bases: *SimCCSyscall*

Parameters

arch (*Arch*) –

ARG_REGS: *List[str]* = ['r2', 'r3', 'r4', 'r5', 'r6', 'r7']

FP_ARG_REGS: *List[str]* = []

RETURN_VAL: *SimFunctionArgument* = <r2>

RETURN_ADDR: *SimFunctionArgument* = <ip_at_syscall>

ARCH

alias of *ArchS390X*

static syscall_num(state)

angr.calling_conventions.register_default_cc(arch, cc, platform='Linux')

Parameters

- **arch** (*str*) –
- **cc** (*Type[SimCC]*) –
- **platform** (*str*) –

`angr.calling_conventions.default_cc(arch, platform='Linux', language=None, syscall=False, **kwargs)`

Return the default calling convention for a given architecture, platform, and language combination.

Parameters

- **arch** (`str`) – The architecture name.
- **platform** (`Optional[str]`) – The platform name (e.g., “Linux” or “Win32”).
- **language** (`Optional[str]`) – The programming language name (e.g., “go”).
- **syscall** (`bool`) – Return syscall convention (True), or normal calling convention (False, default).

Return type

`Optional[Type[SimCC]]`

Returns

A default calling convention class if we can find one for the architecture, platform, and language combination, or None if nothing fits.

`angr.calling_conventions.unify_arch_name(arch)`

Return the unified architecture name.

Parameters

arch (`str`) – The architecture name.

Return type

`str`

Returns

A unified architecture name.

`angr.calling_conventions.register_syscall_cc(arch, os, cc)`

`class angr.sim_variable.SimVariable(ident=None, name=None, region=None, category=None, size=None)`

Bases: `Serializable`

Parameters

- **region** (`int` | `None`) –
- **size** (`int` | `None`) –

`__init__(ident=None, name=None, region=None, category=None, size=None)`

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (`str`) – Name of this variable.
- **region** (`int` | `None`) –
- **size** (`int` | `None`) –

ident

name

region: `Optional[int]`

category: `Optional[str]`

renamed

candidate_names

size

copy()

loc_repr(*arch*)

The representation that shows up in a GUI

Parameters

arch (*Arch*) –

property is_function_argument

class angr.sim_variable.**SimConstantVariable**(*ident=None, value=None, region=None, size=None*)

Bases: *SimVariable*

Parameters

region (*int* | *None*) –

__init__(*ident=None, value=None, region=None, size=None*)

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (*str*) – Name of this variable.

value

loc_repr(*arch*)

The representation that shows up in a GUI

copy()

Return type

SimConstantVariable

class angr.sim_variable.**SimTemporaryVariable**(*tmp_id, size=None*)

Bases: *SimVariable*

__init__(*tmp_id, size=None*)

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (*str*) – Name of this variable.

tmp_id

loc_repr(*arch*)

The representation that shows up in a GUI

copy()

Return type

SimTemporaryVariable

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(cmsg, **kwargs)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

class `angr.sim_variable.SimRegisterVariable`(*reg_offset, size, ident=None, name=None, region=None, category=None*)

Bases: *SimVariable*

Parameters

- **region** (*int* | *None*) –
- **category** (*str* | *None*) –

__init__(*reg_offset, size, ident=None, name=None, region=None, category=None*)

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (*str*) – Name of this variable.

reg: *int*

property bits

loc_repr(*arch*)

The representation that shows up in a GUI

copy()

Return type

SimRegisterVariable

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod `parse_from_cmessage(cmsg, **kwargs)`

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

class `angr.sim_variable.SimMemoryVariable(addr, size, ident=None, name=None, region=None, category=None)`

Bases: `SimVariable`

Parameters

- **region** (`int` | `None`) –
- **category** (`str` | `None`) –

__init__ (`addr, size, ident=None, name=None, region=None, category=None`)

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (`str`) – Name of this variable.

addr

loc_repr (`arch`)

The representation that shows up in a GUI

property `bits`

copy ()

Return type

`SimMemoryVariable`

serialize_to_cmessage ()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

`protobuf.cmessage`

classmethod `parse_from_cmessage(cmsg, **kwargs)`

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

```
class angr.sim_variable.SimStackVariable(offset, size, base='sp', base_addr=None, ident=None,
                                         name=None, region=None, category=None)
```

Bases: *SimMemoryVariable*

Parameters

- **region** (*int* | *None*) –
- **category** (*str* | *None*) –

```
__init__(offset, size, base='sp', base_addr=None, ident=None, name=None, region=None, category=None)
```

Parameters

- **ident** – A unique identifier provided by user or the program. Usually a string.
- **name** (*str*) – Name of this variable.

base

offset

base_addr

loc_repr(*arch*)

The representation that shows up in a GUI

copy()

Return type

SimStackVariable

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(*cmsg*, ***kwargs*)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

```
class angr.sim_variable.SimVariableSet
```

Bases: *MutableSet*

A collection of SimVariables.

```
__init__()
```

add(*item*)

Add an element.

add_register_variable(*reg_var*)

add_memory_variable(*mem_var*)

discard(*item*)

Remove an element. Do not raise an exception if absent.

discard_register_variable(*reg_var*)

discard_memory_variable(*mem_var*)

add_memory_variables(*addrs, size*)

copy()

complement(*other*)

Calculate the complement of *self* and *other*.

Parameters

other – Another SimVariableSet instance.

Returns

The complement result.

contains_register_variable(*reg_var*)

contains_memory_variable(*mem_var*)

class angr.sim_type.**SimType**(*label=None*)

Bases: `object`

SimType exists to track type information for SimProcedures.

base = True

__init__(*label=None*)

Parameters

label – the type label.

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

with_arch(*arch*)

c_repr(*name=None, full=0, memo=None, indent=0*)

copy()

extract_claripy(*bits*)

Given a bitvector *bits* which was loaded from memory in a big-endian fashion, return a more appropriate or structured representation of the data.

A type must have an arch associated in order to use this method.

class `angr.sim_type.TypeRef(name, ty)`

Bases: [SimType](#)

A TypeRef is a reference to a type with a name. This allows for interactivity in type analysis, by storing a type and having the option to update it later and have all references to it automatically update as well.

__init__(name, ty)

Parameters

label – the type label.

property name

This is a read-only property because it is desirable to store typerefs in a mapping from name to type, and we want the mapping to be in the loop for any updates.

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

with_arch(arch)

c_repr(name=None, full=0, memo=None, indent=0)

copy()

class `angr.sim_type.NamedTypeMixin(*args, name=None, **kwargs)`

Bases: [object](#)

SimType classes with this mixin in the class hierarchy allows setting custom class names. A typical use case is to represent same or similar type classes with different qualified names, such as “std::basic_string” vs “std::__cxx11::basic_string”. In such cases, .name stores the qualified name, and .unqualified_name() returns the unqualified name of the type.

Parameters

name ([str](#) | *None*) –

__init__(*args, name=None, **kwargs)

Parameters

name ([str](#) | *None*) –

property name: [str](#)

unqualified_name(lang='c++')

Return type

[str](#)

Parameters

lang ([str](#)) –

class `angr.sim_type.SimTypeBottom(label=None)`

Bases: [SimType](#)

SimTypeBottom basically represents a type error.

__init__(label=None)

Parameters

label – the type label.

c_repr(*name=None, full=0, memo=None, indent=0*)

copy()

class angr.sim_type.**SimTypeTop**(*size=None, label=None*)

Bases: [SimType](#)

SimTypeTop represents any type (mostly used with a pointer for void*).

__init__(*size=None, label=None*)

Parameters

label – the type label.

copy()

class angr.sim_type.**SimTypeReg**(*size, label=None*)

Bases: [SimType](#)

SimTypeReg is the base type for all types that are register-sized.

__init__(*size, label=None*)

Parameters

- **label** – the type label.
- **size** – the size of the type (e.g. 32bit, 8bit, etc.).

extract(*state, addr, concrete=False*)

store(*state, addr, value*)

copy()

class angr.sim_type.**SimTypeNum**(*size, signed=True, label=None*)

Bases: [SimType](#)

SimTypeNum is a numeric type of arbitrary length

__init__(*size, signed=True, label=None*)

Parameters

- **size** – The size of the integer, in bits
- **signed** – Whether the integer is signed or not
- **label** – A label for the type

extract(*state, addr, concrete=False*)

store(*state, addr, value*)

copy()

class angr.sim_type.**SimTypeInt**(*signed=True, label=None*)

Bases: [SimTypeReg](#)

SimTypeInt is a type that specifies a signed or unsigned C integer.

__init__(*signed=True, label=None*)

Parameters

- **signed** – True if signed, False if unsigned
- **label** – The type label

c_repr(*name=None, full=0, memo=None, indent=0*)

property size

The size of the type in bits.

extract(*state, addr, concrete=False*)

copy()

class `angr.sim_type.SimTypeShort`(*signed=True, label=None*)

Bases: [*SimTypeInt*](#)

class `angr.sim_type.SimTypeLong`(*signed=True, label=None*)

Bases: [*SimTypeInt*](#)

class `angr.sim_type.SimTypeLongLong`(*signed=True, label=None*)

Bases: [*SimTypeInt*](#)

class `angr.sim_type.SimTypeChar`(*signed=True, label=None*)

Bases: [*SimTypeReg*](#)

`SimTypeChar` is a type that specifies a character; this could be represented by a byte, but this is meant to be interpreted as a character.

__init__(*signed=True, label=None*)

Parameters

label – the type label.

store(*state, addr, value*)

extract(*state, addr, concrete=False*)

copy()

class `angr.sim_type.SimTypeWideChar`(*signed=True, label=None*)

Bases: [*SimTypeReg*](#)

`SimTypeWideChar` is a type that specifies a wide character (a UTF-16 character).

__init__(*signed=True, label=None*)

Parameters

label – the type label.

store(*state, addr, value*)

extract(*state, addr, concrete=False*)

copy()

class `angr.sim_type.SimTypeBool`(*signed=True, label=None*)

Bases: [*SimTypeChar*](#)

store(*state*, *addr*, *value*)

extract(*state*, *addr*, *concrete=False*)

class angr.sim_type.**SimTypeFd**(*label=None*)

Bases: [SimTypeReg](#)

SimTypeFd is a type that specifies a file descriptor.

__init__(*label=None*)

Parameters

label – the type label

copy()

class angr.sim_type.**SimTypePointer**(*pts_to*, *label=None*, *offset=0*)

Bases: [SimTypeReg](#)

SimTypePointer is a type that specifies a pointer to some other type.

__init__(*pts_to*, *label=None*, *offset=0*)

Parameters

- **label** – The type label.
- **pts_to** – The type to which this pointer points.

c_repr(*name=None*, *full=0*, *memo=None*, *indent=0*)

make(*pts_to*)

property size

The size of the type in bits.

copy()

class angr.sim_type.**SimTypeReference**(*refs*, *label=None*)

Bases: [SimTypeReg](#)

SimTypeReference is a type that specifies a reference to some other type.

__init__(*refs*, *label=None*)

Parameters

- **label** – the type label.
- **size** – the size of the type (e.g. 32bit, 8bit, etc.).

c_repr(*name=None*, *full=0*, *memo=None*, *indent=0*)

make(*refs*)

property size

The size of the type in bits.

copy()

class angr.sim_type.**SimTypeArray**(*elem_type*, *length=None*, *label=None*)

Bases: [SimType](#)

SimTypeArray is a type that specifies a series of data laid out in sequence.

__init__(*elem_type*, *length=None*, *label=None*)

Parameters

- **label** – The type label.
- **elem_type** – The type of each element in the array.
- **length** – An expression of the length of the array, if known.

c_repr(*name=None*, *full=0*, *memo=None*, *indent=0*)

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

copy()

extract(*state*, *addr*, *concrete=False*)

store(*state*, *addr*, *values*)

angr.sim_type.**SimTypeFixedSizeArray**

alias of [SimTypeArray](#)

class angr.sim_type.**SimTypeString**(*length=None*, *label=None*, *name=None*)

Bases: [NamedTypeMixin](#), [SimTypeArray](#)

SimTypeString is a type that represents a C-style string, i.e. a NUL-terminated array of bytes.

Parameters

name (*str* | *None*) –

__init__(*length=None*, *label=None*, *name=None*)

Parameters

- **label** – The type label.
- **length** – An expression of the length of the string, if known.
- **name** (*str* | *None*) –

extract(*state*, *addr*, *concrete=False*)

Parameters

state ([SimState](#)) –

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

copy()

class angr.sim_type.**SimTypeWString**(*length=None*, *label=None*, *name=None*)

Bases: [NamedTypeMixin](#), [SimTypeArray](#)

A wide-character null-terminated string, where each character is 2 bytes.

Parameters

name (*str* | *None*) –

__init__ (*length=None, label=None, name=None*)

Parameters

- **label** – The type label.
- **elem_type** – The type of each element in the array.
- **length** – An expression of the length of the array, if known.
- **name** (*str* | *None*) –

extract (*state, addr, concrete=False*)

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

copy()

class `angr.sim_type.SimTypeFunction` (*args, returnty, label=None, arg_names=None, variadic=False*)

Bases: [SimType](#)

`SimTypeFunction` is a type that specifies an actual function (i.e. not a pointer) with certain types of arguments and a certain return value.

Parameters

- **args** (*List[SimType]*) –
- **returnty** (*SimType* | *None*) –

base = `False`

__init__ (*args, returnty, label=None, arg_names=None, variadic=False*)

Parameters

- **label** – The type label
- **args** (*List[SimType]*) – A tuple of types representing the arguments to the function
- **returnty** (*Optional[SimType]*) – The return type of the function, or none for void
- **variadic** – Whether the function accepts varargs

c_repr (*name=None, full=0, memo=None, indent=0*)

property size

The size of the type in bits.

copy()

class `angr.sim_type.SimTypeCppFunction` (*args, returnty, label=None, arg_names=None, ctor=False, dtor=False*)

Bases: [SimTypeFunction](#)

`SimTypeCppFunction` is a type that specifies an actual C++-style function with information about arguments, return value, and more C++-specific properties.

Variables

- **ctor** – Whether the function is a constructor or not.
- **dtor** – Whether the function is a destructor or not.

Parameters

- **args** (*List[SimType]*) –
- **returnty** (*SimType | None*) –
- **arg_names** (*Tuple[str]*) –
- **ctor** (*bool*) –
- **dtor** (*bool*) –

__init__ (*args, returnty, label=None, arg_names=None, ctor=False, dtor=False*)

Parameters

- **label** – The type label
- **args** – A tuple of types representing the arguments to the function
- **returnty** – The return type of the function, or none for void
- **variadic** – Whether the function accepts varargs
- **arg_names** (*Tuple[str] | None*) –
- **ctor** (*bool*) –
- **dtor** (*bool*) –

copy()

args: *List[SimType]*

returnty: *Optional[SimType]*

class `angr.sim_type.SimTypeLength` (*signed=False, addr=None, length=None, label=None*)

Bases: *SimTypeLong*

`SimTypeLength` is a type that specifies the length of some buffer in memory.

...I'm not really sure what the original design of this class was going for

__init__ (*signed=False, addr=None, length=None, label=None*)

Parameters

- **signed** – Whether the value is signed or not
- **label** – The type label.
- **addr** – The memory address (expression).
- **length** – The length (expression).

property `size`

The size of the type in bits.

copy()

```
class angr.sim_type.SimTypeFloat(size=32)
```

Bases: [SimTypeReg](#)

An IEEE754 single-precision floating point number

```
__init__(size=32)
```

Parameters

- **label** – the type label.
- **size** – the size of the type (e.g. 32bit, 8bit, etc.).

```
sort = FLOAT
```

```
signed = True
```

```
extract(state, addr, concrete=False)
```

```
store(state, addr, value)
```

```
copy()
```

```
class angr.sim_type.SimTypeDouble(align_double=True)
```

Bases: [SimTypeFloat](#)

An IEEE754 double-precision floating point number

```
__init__(align_double=True)
```

Parameters

- **label** – the type label.
- **size** – the size of the type (e.g. 32bit, 8bit, etc.).

```
sort = DOUBLE
```

```
property alignment
```

The alignment of the type in bytes.

```
copy()
```

```
class angr.sim_type.SimStruct(fields, name=None, pack=False, align=None)
```

Bases: [NamedTypeMixin](#), [SimType](#)

Parameters

fields ([Dict](#)[[str](#), [SimType](#)] | [OrderedDict](#)) –

```
__init__(fields, name=None, pack=False, align=None)
```

Parameters

- **label** – the type label.
- **fields** ([Dict](#)[[str](#), [SimType](#)] | [OrderedDict](#)) –

```
property packed
```

```
property offsets: Dict[str, int]
```

```
extract(state, addr, concrete=False)
```

c_repr(*name=None, full=0, memo=None, indent=0*)

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

store(*state, addr, value*)

copy()

class `angr.sim_type.SimStructValue`(*struct, values=None*)

Bases: `object`

A SimStruct type paired with some real values

__init__(*struct, values=None*)

Parameters

- **struct** – A SimStruct instance describing the type of this struct
- **values** – A mapping from struct fields to values

property struct

copy()

class `angr.sim_type.SimUnion`(*members, name=None, label=None*)

Bases: `NamedTypeMixin, SimType`

fields = ('members', 'name')

__init__(*members, name=None, label=None*)

Parameters

- **members** – The members of the union, as a mapping name -> type
- **name** – The name of the union

property size

The size of the type in bits.

property alignment

The alignment of the type in bytes.

extract(*state, addr, concrete=False*)

c_repr(*name=None, full=0, memo=None, indent=0*)

copy()

class `angr.sim_type.SimUnionValue`(*union, values=None*)

Bases: `object`

A SimStruct type paired with some real values

__init__(*union, values=None*)

Parameters

- **union** – A SimUnion instance describing the type of this union
- **values** – A mapping from union members to values

copy()

class angr.sim_type.SimCppClass(*members=None, function_members=None, vtable_ptrs=None, name=None, pack=False, align=None*)

Bases: *SimStruct*

Parameters

- **members** (*Dict[str, SimType] | None*) –
- **function_members** (*Dict[str, SimTypeCppFunction] | None*) –
- **name** (*str | None*) –
- **pack** (*bool*) –

__init__(*members=None, function_members=None, vtable_ptrs=None, name=None, pack=False, align=None*)

Parameters

- **label** – the type label.
- **members** (*Dict[str, SimType] | None*) –
- **function_members** (*Dict[str, SimTypeCppFunction] | None*) –
- **name** (*str | None*) –
- **pack** (*bool*) –

property members

extract(*state, addr, concrete=False*)

store(*state, addr, value*)

copy()

class angr.sim_type.SimCppClassValue(*class_type, values*)

Bases: *object*

A SimCppClass type paired with some real values

__init__(*class_type, values*)

copy()

class angr.sim_type.SimTypeNumOffset(*size, signed=True, label=None, offset=0*)

Bases: *SimTypeNum*

like SimTypeNum, but supports an offset of 1 to 7 to a byte aligned address to allow structs with bitfields

`__init__(size, signed=True, label=None, offset=0)`

Parameters

- **size** – The size of the integer, in bits
- **signed** – Whether the integer is signed or not
- **label** – A label for the type

`extract(state, addr, concrete=False)`

Parameters

state (`SimState`) –

`store(state, addr, value)`

`copy()`

`class angr.sim_type.SimTypeRef(name, original_type)`

Bases: `SimType`

`SimTypeRef` is a to-be-resolved reference to another `SimType`.

`SimTypeRef` is not `SimTypeReference`.

Parameters

original_type (`Type[SimStruct]`) –

`__init__(name, original_type)`

Parameters

- **label** – the type label.
- **original_type** (`Type[SimStruct]`) –

property name: `str`

`set_size(v)`

Parameters

v (`int`) –

`c_repr(name=None, full=0, memo=None, indent=0)`

Return type

`str`

`angr.sim_type.register_types(types)`

Pass in some types and they will be registered to the global type store.

The argument may be either a mapping from name to `SimType`, or a plain `SimType`. The plain `SimType` must be either a struct or union type with a name present.

```
>>> register_types(parse_types("typedef int x; typedef float y;"))
>>> register_types(parse_type("struct abcd { int ab; float cd; }"))
```

`angr.sim_type.do_preprocess(defn, include_path=())`

Run a string through the C preprocessor that ships with pycparser but is weirdly inaccessible?

`angr.sim_type.parse_signature(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a single function prototype and return its type

`angr.sim_type.parse_defns(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a series of C definitions, returns a mapping from variable name to variable type object

`angr.sim_type.parse_types(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a series of C definitions, returns a mapping from type name to type object

`angr.sim_type.parse_file(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a series of C definitions, returns a tuple of two type mappings, one for variable definitions and one for type definitions.

Parameters

predefined_types (*Dict*[*Any*, *SimType*] | *None*) –

`angr.sim_type.type_parser_singleton()`

Return type

Optional[*CParser*]

`angr.sim_type.parse_type(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a simple type expression into a *SimType*

```
>>> parse_type('int *')
```

`angr.sim_type.parse_type_with_name(defn, preprocess=True, predefined_types=None, arch=None)`

Parse a simple type expression into a *SimType*, returning a tuple of the type object and any associated name that might be found in the place a name would go in a type declaration.

```
>>> parse_type_with_name('int *foo')
```

Parameters

predefined_types (*Dict*[*Any*, *SimType*] | *None*) –

`angr.sim_type.normalize_cpp_function_name(name)`

Return type

str

Parameters

name (*str*) –

`angr.sim_type.parse_cpp_file(cpp_decl, with_param_names=False)`

Parameters

with_param_names (*bool*) –

`angr.sim_type.dereference_simtype(t, type_collections, memo=None)`

Return type

SimType

Parameters

- **t** (*SimType*) –
- **type_collections** (*List*[*SimTypeCollection*]) –
- **memo** (*Dict*[*str*, *SimType*] | *None*) –

```
class angr.callable.Callable(project, addr, prototype=None, concrete_only=False, perform_merge=True,  
                           base_state=None, toc=None, cc=None, add_options=None,  
                           remove_options=None)
```

Bases: `object`

Callable is a representation of a function in the binary that can be interacted with like a native python function.

If you set `perform_merge=True` (the default), the result will be returned to you, and you can get the result state with `callable.result_state`.

Otherwise, you can get the resulting simulation manager at `callable.result_path_group`.

```
__init__(project, addr, prototype=None, concrete_only=False, perform_merge=True, base_state=None,  
         toc=None, cc=None, add_options=None, remove_options=None)
```

Parameters

- **project** – The project to operate on
- **addr** – The address of the function to use

The following parameters are optional:

Parameters

- **prototype** – The signature of the calls you would like to make. This really shouldn't be optional.
- **concrete_only** – Throw an exception if the execution splits into multiple paths
- **perform_merge** – Merge all result states into one at the end (only relevant if `concrete_only=False`)
- **base_state** – The state from which to do these runs
- **toc** – The address of the table of contents for ppc64
- **cc** – The SimCC to use for a calling convention

```
set_base_state(state)
```

Swap out the state you'd like to use to perform the call :type state: :param state: The state to use to perform the call

```
perform_call(*args, prototype=None)
```

```
call_c(c_args)
```

Call this Callable with a string of C-style arguments.

Parameters

c_args (`str`) – C-style arguments.

Returns

The return value from the call.

Return type

`claripy.Ast`

10.13 Knowledge Base

Representing the artifacts of a project.

class `angr.knowledge_base.knowledge_base.KnowledgeBase`(*project*, *obj=None*, *name=None*)

Bases: `object`

Represents a “model” of knowledge about an artifact.

Contains things like a CFG, data references, etc.

functions: `FunctionManager`

variables: `VariableManager`

structured_code: `StructuredCodeManager`

defs: `KeyDefinitionManager`

cfgs: `CFGManager`

types: `TypesStore`

propagations: `PropagationManager`

xrefs: `XRefManager`

__init__(*project*, *obj=None*, *name=None*)

property `callgraph`

property `unresolved_indirect_jumps`

property `resolved_indirect_jumps`

has_plugin(*name*)

get_plugin(*name*)

register_plugin(*name*, *plugin*)

release_plugin(*name*)

K = ~K

get_knowledge(*requested_plugin_cls*)

Type inference safe method to request a knowledge base plugin Explicitly passing the type of the requested plugin achieves two things: 1. Every location using this plugin can be easily found with an IDE by searching explicit references to the type 2. Basic type inference can deduce the result type and properly type check usages of it

If there isn’t already an instance of this class None will be returned to make it clear to the caller that there is no existing knowledge of this type yet. The code that initially creates this knowledge should use the `register_plugin` method to register the initial knowledge state :type requested_plugin_cls: `Type[TypeVar(K, bound= KnowledgeBasePlugin)]` :param requested_plugin_cls: :rtype: `Optional[TypeVar(K, bound= KnowledgeBasePlugin)]` :return: Instance of the requested plugin class or null if it is not a known plugin

Parameters

requested_plugin_cls (`Type[K]`) –

Return type

K | None

request_knowledge(*requested_plugin_cls*)

Return type

TypeVar(*K*, bound= *KnowledgeBasePlugin*)

Parameters

requested_plugin_cls (*Type*[*K*]) –

class `angr.knowledge_plugins.patches.Patch`(*addr*, *new_bytes*, *comment=None*)

Bases: *object*

Parameters

comment (*str* | None) –

__init__(*addr*, *new_bytes*, *comment=None*)

Parameters

comment (*str* | None) –

class `angr.knowledge_plugins.patches.PatchManager`(*kb*)

Bases: *KnowledgeBasePlugin*

A placeholder-style implementation for a binary patch manager. This class should be significantly changed in the future when all data about loaded binary objects are loaded into angr knowledge base from CLE. As of now, it only stores byte-level replacements.

Patches should not overlap, but it's user's responsibility to check for and avoid overlapping patches.

__init__(*kb*)

add_patch(*addr*, *new_bytes*, *comment=None*)

Parameters

comment (*str* | None) –

add_patch_obj(*patch*)

Parameters

patch (*Patch*) –

remove_patch(*addr*)

patch_addrs()

get_patch(*addr*)

Get patch at the given address.

Parameters

addr (*int*) – The address of the patch.

Returns

The patch if there is one starting at the address, or None if there isn't any.

Return type

Patch or None

get_all_patches(*addr*, *size*)

Retrieve all patches that cover a region specified by [*addr*, *addr*+*size*).

Parameters

- **addr** (*int*) – The address of the beginning of the region.
- **size** (*int*) – Size of the region.

Returns

A list of patches.

Return type

list

keys()

items()

values()

copy()

static overlap(*a0, a1, b0, b1*)

apply_patches_to_binary(*binary_bytes=None, patches=None*)

Return type

bytes

Parameters

- **binary_bytes** (*bytes* | *None*) –
- **patches** (*List[Patch]* | *None*) –

apply_patches_to_state(*state*)

property patched_entry_state

class `angr.knowledge_plugins.plugin.KnowledgeBasePlugin`(*kb*)

Bases: *object*

Parameters

kb (*KnowledgeBase*) –

__init__(*kb*)

Parameters

kb (*KnowledgeBase*) –

copy()

static register_default(*name, cls*)

class `angr.knowledge_plugins.callsite_prototypes.CallsitePrototypes`(*kb*)

Bases: *KnowledgeBasePlugin*

CallsitePrototypes manages callee prototypes at call sites.

__init__(*kb*)

set_prototype(*callsite_block_addr, cc, prototype, manual=False*)

Return type

None

Parameters

- `callsite_block_addr` (*int*) –
- `cc` (*SimCC*) –
- `prototype` (*SimTypeFunction*) –
- `manual` (*bool*) –

`get_cc(callsite_block_addr)`

Return type

Optional[*SimCC*]

Parameters

`callsite_block_addr` (*int*) –

`get_prototype(callsite_block_addr)`

Return type

Optional[*SimTypeFunction*]

Parameters

`callsite_block_addr` (*int*) –

`get_prototype_type(callsite_block_addr)`

Return type

Optional[*bool*]

Parameters

`callsite_block_addr` (*int*) –

`has_prototype(callsite_block_addr)`

Return type

bool

Parameters

`callsite_block_addr` (*int*) –

`copy()`

`class angr.knowledge_plugins.cfg.MemoryDataSort`

Bases: *object*

`Unspecified` = `None`

`Unknown` = `'unknown'`

`Integer` = `'integer'`

`PointerArray` = `'pointer-array'`

`String` = `'string'`

`UnicodeString` = `'unicode'`

`SegmentBoundary` = `'segment-boundary'`

`CodeReference` = `'code reference'`

`GOTPLTEntry` = `'GOT PLT Entry'`

```
ELFHeader = 'elf-header'
```

```
FloatingPoint = 'fp'
```

```
class angr.knowledge_plugins.cfg.MemoryData(address, size, sort, pointer_addr=None, max_size=None,
                                           reference_size=None)
```

Bases: [Serializable](#)

MemoryData describes the syntactic content of a single address of memory.

reference_size reflects the size of *content*. It can be different from *size*, which is the actual size of the memory data item in memory. The intended way to get the actual content in memory is *self.content[:self.size]*.

Parameters

- **address** (*int*) –
- **size** (*int*) –
- **sort** (*str* | *None*) –
- **pointer_addr** (*int* | *None*) –
- **max_size** (*int* | *None*) –
- **reference_size** (*int* | *None*) –

```
__init__(address, size, sort, pointer_addr=None, max_size=None, reference_size=None)
```

Parameters

- **address** (*int*) –
- **size** (*int*) –
- **sort** (*str* | *None*) –
- **pointer_addr** (*int* | *None*) –
- **max_size** (*int* | *None*) –
- **reference_size** (*int* | *None*) –

```
addr: int
```

```
size: int
```

```
reference_size: int
```

```
sort: Optional[str]
```

```
max_size: Optional[int]
```

```
pointer_addr: Optional[int]
```

```
content: Optional[bytes]
```

```
property address
```

```
copy()
```

Make a copy of the MemoryData.

Returns

A copy of the MemoryData instance.

Return type*MemoryData***fill_content(loader)**

Load data to fill self.content.

Parameters**loader** – The project loader.**Returns**

None

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(cmsg, **kwargs)

Parse a protobuf cmessage and create a class object.

Parameters**cmsg** – The probobuf cmessage object.**Returns**

A unserialized class object.

Return type

cls

```
class angr.knowledge_plugins.cfg.CFGNode(addr, size, cfg, simprocedure_name=None, no_ret=False,
                                         function_address=None, block_id=None, irsb=None,
                                         soot_block=None, instruction_addrs=None, thumb=False,
                                         byte_string=None, is_syscall=None, name=None)
```

Bases: *Serializable*

This class stands for each single node in CFG.

```
__init__(addr, size, cfg, simprocedure_name=None, no_ret=False, function_address=None,
         block_id=None, irsb=None, soot_block=None, instruction_addrs=None, thumb=False,
         byte_string=None, is_syscall=None, name=None)
```

Note: simprocedure_name is not used to recreate the SimProcedure object. It's only there for better `__repr__`.

addr**size****simprocedure_name****no_ret****function_address****thumb****byte_string:** *Optional*[bytes]

`is_syscall`

`instruction_addrs`

`irsb`

`soot_block`

`has_return`

`block_id: Union[angr.analyses.cfg.cfg_job_base.BlockID, int]`

`property name`

`property successors`

`property predecessors`

`successors_and_jumpkinds(excluding_fakeret=True)`

`predecessors_and_jumpkinds(excluding_fakeret=True)`

`get_data_references(kb=None)`

Get the known data references for this CFGNode via the knowledge base.

Parameters

kb – Which knowledge base to use; uses the global KB by default if none is provided

Returns

Generator yielding xrefs to this CFGNode’s block.

Return type

iter

`property accessed_data_references`

Property providing a view of all the known data references for this CFGNode via the global knowledge base

Returns

Generator yielding xrefs to this CFGNode’s block.

Return type

iter

`property is_simprocedure`

`property callstack_key`

`serialize_to_cmessage()`

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

`classmethod parse_from_cmessage(cmsg, cfg=None)`

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

copy()

merge(*other*)

Merges this node with the other, returning a new node that spans the both.

to_codenode()

property block

syscall_name

```
class angr.knowledge_plugins.cfg.CFGNode(addr, size, cfg, simprocedure_name=None, no_ret=False,
                                         function_address=None, block_id=None, irsb=None,
                                         instruction_addrs=None, thumb=False, byte_string=None,
                                         is_syscall=None, name=None, input_state=None,
                                         final_states=None, syscall_name=None, looping_times=0,
                                         depth=None, callstack_key=None,
                                         creation_failure_info=None)
```

Bases: [CFGNode](#)

The CFGNode that is used in CFGEmulated.

Parameters

- **block_id** ([angr.analyses.cfg.cfg_job_base.BlockID](#) | *int*) –
- **byte_string** (*bytes* | *None*) –

```
__init__(addr, size, cfg, simprocedure_name=None, no_ret=False, function_address=None,
         block_id=None, irsb=None, instruction_addrs=None, thumb=False, byte_string=None,
         is_syscall=None, name=None, input_state=None, final_states=None, syscall_name=None,
         looping_times=0, depth=None, callstack_key=None, creation_failure_info=None)
```

Note: `simprocedure_name` is not used to recreate the `SimProcedure` object. It's only there for better `__repr__`.

input_state

looping_times

depth

creation_failure_info

final_states

return_target

syscall

property callstack_key

property creation_failed

downsize()

Drop saved states.

copy()

```
class angr.knowledge_plugins.cfg.IndirectJump(addr, ins_addr, func_addr, jumpkind, stmt_idx,
                                              resolved_targets=None, jumptable=False,
                                              jumptable_addr=None, jumptable_size=None,
                                              jumptable_entry_size=None, jumptable_entries=None,
                                              type_=255)
```

Bases: [Serializable](#)

Parameters

- **addr** (*int*) –
- **ins_addr** (*int*) –
- **func_addr** (*int*) –
- **jumpkind** (*str*) –
- **stmt_idx** (*int*) –
- **resolved_targets** (*List[int] | None*) –
- **jumptable** (*bool*) –
- **jumptable_addr** (*int | None*) –
- **jumptable_size** (*int | None*) –
- **jumptable_entry_size** (*int | None*) –
- **jumptable_entries** (*List[int] | None*) –
- **type_** (*int | None*) –

```
__init__(addr, ins_addr, func_addr, jumpkind, stmt_idx, resolved_targets=None, jumptable=False,
          jumptable_addr=None, jumptable_size=None, jumptable_entry_size=None,
          jumptable_entries=None, type_=255)
```

Parameters

- **addr** (*int*) –
- **ins_addr** (*int*) –
- **func_addr** (*int*) –
- **jumpkind** (*str*) –
- **stmt_idx** (*int*) –
- **resolved_targets** (*List[int] | None*) –
- **jumptable** (*bool*) –
- **jumptable_addr** (*int | None*) –
- **jumptable_size** (*int | None*) –
- **jumptable_entry_size** (*int | None*) –
- **jumptable_entries** (*List[int] | None*) –
- **type_** (*int | None*) –

```

    addr
    ins_addr
    func_addr
    jumpkind
    stmt_idx
    resolved_targets
    jumpable
    jumpable_addr
    jumpable_size
    jumpable_entry_size
    jumpable_entries
    type

```

```
class angr.knowledge_plugins.cfg.IndirectJumpType
```

```
    Bases: object
```

```
    Jumpable_AddressLoadedFromMemory = 0
```

```
    Jumpable_AddressComputed = 1
```

```
    Vtable = 3
```

```
    Unknown = 255
```

```
class angr.knowledge_plugins.cfg.CFGModel(ident, cfg_manager=None, is_arm=False)
```

```
    Bases: Serializable
```

This class describes a Control Flow Graph for a specific range of code.

```
    __init__(ident, cfg_manager=None, is_arm=False)
```

```
    ident
```

```
    is_arm
```

```
    graph
```

```
    jump_tables: Dict[int, IndirectJump]
```

```
    memory_data: Dict[int, MemoryData]
```

```
    insn_addr_to_memory_data: Dict[int, MemoryData]
```

```
    normalized
```

```
    edges_to_repair
```

```
    property project
```

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(cmsg, cfg_manager=None, loader=None)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

copy()
add_node(block_id, node)
Return type

None

Parameters

- **block_id** (*int*) –
- **node** (*CFGNode*) –

remove_node(block_id, node)

Remove the given CFGNode instance. Note that this method *does not* remove the node from the graph.

Parameters

- **block_id** (*int*) – The Unique ID of the CFGNode.
- **node** (*CFGNode*) – The CFGNode instance to remove.

Return type

None

Returns

None

get_node(block_id)

Get a single node from node key.

Parameters

block_id (*BlockID*) – Block ID of the node.

Returns

The CFGNode

Return type

CFGNode

get_any_node(*addr*, *is_syscall*=None, *anyaddr*=False, *force_fastpath*=False)

Get an arbitrary CFGNode (without considering their contexts) from our graph.

Parameters

- **addr** (*int*) – Address of the beginning of the basic block. Set anyaddr to True to support arbitrary address.
- **is_syscall** (*Optional[bool]*) – Whether you want to get the syscall node or any other node. This is due to the fact that syscall SimProcedures have the same address as the target it returns to. None means get either, True means get a syscall node, False means get something that isn't a syscall node.
- **anyaddr** (*bool*) – If anyaddr is True, then addr doesn't have to be the beginning address of a basic block. By default the entire graph.nodes() will be iterated, and the first node containing the specific address is returned, which can be slow.
- **force_fastpath** (*bool*) – If force_fastpath is True, it will only perform a dict lookup in the _nodes_by_addr dict.

Return type

Optional[CFGNode]

Returns

A CFGNode if there is any that satisfies given conditions, or None otherwise

get_all_nodes(*addr*, *is_syscall*=None, *anyaddr*=False)

Get all CFGNodes whose address is the specified one.

Parameters

- **addr** (*int*) – Address of the node
- **is_syscall** (*Optional[bool]*) – True returns the syscall node, False returns the normal CFGNode, None returns both
- **anyaddr** (*bool*) –

Return type

List[CFGNode]

Returns

all CFGNodes

get_all_nodes_intersecting_region(*addr*, *size*=1)

Get all CFGNodes that intersect the given region.

Parameters

- **addr** (*int*) – Minimum address of target region.
- **size** (*int*) – Size of region, in bytes.

Return type

Set[CFGNode]

nodes()

An iterator of all nodes in the graph.

Returns

The iterator.

Return type

iterator

get_predecessors(*cfgnode*, *excluding_fakeret*=True, *jumpkind*=None)

Get predecessors of a node in the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all predecessors that is connected to the node with a fakeret edge.
- **jumpkind** (*Optional[str]*) – Only return predecessors with the specified jumpkind. This argument will be ignored if set to None.

Return type

List[CFGNode]

Returns

A list of predecessors

get_successors(*node*, *excluding_fakeret*=True, *jumpkind*=None)

Get successors of a node in the control flow graph.

Parameters

- **node** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all successors that is connected to the node with a fakeret edge.
- **jumpkind** (*str / None*) – Only return successors with the specified jumpkind. This argument will be ignored if set to None.
- **jumpkind** –

Returns

A list of successors

Return type

list

get_successors_and_jumpkinds(*node*, *excluding_fakeret*=True)

Get a list of tuples where the first element is the successor of the CFG node and the second element is the jumpkind of the successor.

Parameters

- **node** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all successors that are fall-through successors.

Returns

A list of successors and their corresponding jumpkinds.

Return type

list

get_successors_and_jumpkind(*node*, *excluding_fakeret*=True)

Get a list of tuples where the first element is the successor of the CFG node and the second element is the jumpkind of the successor.

Parameters

- **node** (*CFGNode*) – The node.

- **excluding_fakeret** (*bool*) – True if you want to exclude all successors that are fall-through successors.

Returns

A list of successors and their corresponding jumpkinds.

Return type

list

get_predecessors_and_jumpkinds(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the predecessor of the CFG node and the second element is the jumpkind of the predecessor.

Parameters

- **node** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all predecessors that are fall-through predecessors.

Return type

List[Tuple[CFGNode, str]]

Returns

A list of predecessors and their corresponding jumpkinds.

get_predecessors_and_jumpkind(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the predecessor of the CFG node and the second element is the jumpkind of the predecessor.

Parameters

- **node** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all predecessors that are fall-through predecessors.

Return type

List[Tuple[CFGNode, str]]

Returns

A list of predecessors and their corresponding jumpkinds.

get_all_predecessors(*cfgnode*, *depth_limit=None*)

Get all predecessors of a specific node on the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The CFGNode object
- **depth_limit** (*int*) – Optional depth limit for the depth-first search

Returns

A list of predecessors in the CFG

Return type

list

get_all_successors(*cfgnode*, *depth_limit=None*)

Get all successors of a specific node on the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The CFGNode object

- **depth_limit** (*int*) – Optional depth limit for the depth-first search

Returns

A list of successors in the CFG

Return type

list

get_branching_nodes()

Returns all nodes that has an out degree ≥ 2

get_exit_stmt_idx(*src_block*, *dst_block*)

Get the corresponding exit statement ID for control flow to reach destination block from source block. The exit statement ID was put on the edge when creating the CFG. Note that there must be a direct edge between the two blocks, otherwise an exception will be raised.

Returns

The exit statement ID

add_memory_data(*data_addr*, *data_type*, *data_size=None*)

Add a MemoryData entry to self.memory_data.

Parameters

- **data_addr** (*int*) – Address of the data
- **data_type** (*Optional[MemoryDataSort]*) – Type of the memory data
- **data_size** (*Optional[int]*) – Size of the memory data, or None if unknown for now.

Return type

bool

Returns

True if a new memory data entry is added, False otherwise.

tidy_data_references(*memory_data_addrs=None*, *exec_mem_regions=None*, *xrefs=None*, *seg_list=None*, *data_type_guessing_handlers=None*)

Go through all data references (or the ones as specified by *memory_data_addrs*) and determine their sizes and types if possible.

Parameters

- **memory_data_addrs** (*Optional[List[int]]*) – A list of addresses of memory data, or None if tidying all known memory data entries.
- **exec_mem_regions** (*Optional[List[Tuple[int, int]]]*) – A list of start and end addresses of executable memory regions.
- **seg_list** (*Optional[SegmentList]*) – The segment list that CFGFast uses during CFG recovery.
- **data_type_guessing_handlers** (*Optional[List[Callable]]*) – A list of Python functions that will guess data types. They will be called in sequence to determine data types for memory data whose type is unknown.
- **xrefs** (*XRefManager / None*) –

Return type

bool

Returns

True if new data entries are found, False otherwise.

remove_node_and_graph_node(*node*)

Like *remove_node*, but also removes node from the graph.

Parameters

node (*CFGNode*) – The node to remove.

Return type

None

get_intersecting_functions(*addr, size=1, kb=None*)

Find all functions with nodes intersecting [*addr, addr + size*).

Parameters

- **addr** (*int*) – Minimum address of target region.
- **size** (*int*) – Size of region, in bytes.
- **kb** (*Optional[KnowledgeBase]*) – Knowledge base to search for functions in.

Return type

Set[Function]

find_function_for_reflow_into_addr(*addr, kb=None*)

Look for a function that flows into a new node at *addr*.

Parameters

- **addr** (*int*) – Address of new block.
- **kb** (*Optional[KnowledgeBase]*) – Knowledge base to search for functions in.

Return type

Optional[Function]

clear_region_for_reflow(*addr, size=1, kb=None*)

Remove nodes in the graph intersecting region [*addr, addr + size*).

Any functions that intersect the range, and their associated nodes in the CFG, will also be removed from the knowledge base for analysis.

Parameters

- **addr** (*int*) – Minimum address of target region.
- **size** (*int*) – Size of the region, in bytes.
- **kb** (*Optional[KnowledgeBase]*) – Knowledge base to search for functions in.

Return type

None

class `angr.knowledge_plugins.cfg.CFGManager`(*kb*)

Bases: *KnowledgeBasePlugin*

This is the CFG manager, it manages CFGs

__init__(*kb*)

new_model(*prefix*)

copy()

get_most_accurate()

Return type

`Optional[CFGModel]`

Returns

The most accurate CFG present in the CFGManager, or None if it does not hold any.

class `angr.knowledge_plugins.cfg.cfg_model.CFGModel`(*ident*, *cfg_manager=None*, *is_arm=False*)

Bases: `Serializable`

This class describes a Control Flow Graph for a specific range of code.

__init__(*ident*, *cfg_manager=None*, *is_arm=False*)

ident

is_arm

graph

jump_tables: `Dict[int, IndirectJump]`

memory_data: `Dict[int, MemoryData]`

insn_addr_to_memory_data: `Dict[int, MemoryData]`

normalized

edges_to_repair

property project

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

`protobuf.cmessage`

classmethod `parse_from_cmessage`(*cmsg*, *cfg_manager=None*, *loader=None*)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

`cls`

copy()

add_node(*block_id*, *node*)

Return type

`None`

Parameters

- **block_id** (*int*) –
- **node** (*CFGNode*) –

remove_node(*block_id*, *node*)

Remove the given CFGNode instance. Note that this method *does not* remove the node from the graph.

Parameters

- **block_id** (*int*) – The Unique ID of the CFGNode.
- **node** (*CFGNode*) – The CFGNode instance to remove.

Return type

None

Returns

None

get_node(*block_id*)

Get a single node from node key.

Parameters

block_id (*BlockID*) – Block ID of the node.

Returns

The CFGNode

Return type

CFGNode

get_any_node(*addr*, *is_syscall=None*, *anyaddr=False*, *force_fastpath=False*)

Get an arbitrary CFGNode (without considering their contexts) from our graph.

Parameters

- **addr** (*int*) – Address of the beginning of the basic block. Set anyaddr to True to support arbitrary address.
- **is_syscall** (*Optional[bool]*) – Whether you want to get the syscall node or any other node. This is due to the fact that syscall SimProcedures have the same address as the target it returns to. None means get either, True means get a syscall node, False means get something that isn't a syscall node.
- **anyaddr** (*bool*) – If anyaddr is True, then addr doesn't have to be the beginning address of a basic block. By default the entire graph.nodes() will be iterated, and the first node containing the specific address is returned, which can be slow.
- **force_fastpath** (*bool*) – If force_fastpath is True, it will only perform a dict lookup in the _nodes_by_addr dict.

Return type

Optional[CFGNode]

Returns

A CFGNode if there is any that satisfies given conditions, or None otherwise

get_all_nodes(*addr*, *is_syscall=None*, *anyaddr=False*)

Get all CFGNodes whose address is the specified one.

Parameters

- **addr** (*int*) – Address of the node

- **is_syscall** (*Optional[bool]*) – True returns the syscall node, False returns the normal CFGNode, None returns both
- **anyaddr** (*bool*) –

Return type

List[CFGNode]

Returns

all CFGNodes

get_all_nodes_intersecting_region(*addr, size=1*)

Get all CFGNodes that intersect the given region.

Parameters

- **addr** (*int*) – Minimum address of target region.
- **size** (*int*) – Size of region, in bytes.

Return type

Set[CFGNode]

nodes()

An iterator of all nodes in the graph.

Returns

The iterator.

Return type

iterator

get_predecessors(*cfgnode, excluding_fakeret=True, jumpkind=None*)

Get predecessors of a node in the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all predecessors that is connected to the node with a fakeret edge.
- **jumpkind** (*Optional[str]*) – Only return predecessors with the specified jumpkind. This argument will be ignored if set to None.

Return type

List[CFGNode]

Returns

A list of predecessors

get_successors(*node, excluding_fakeret=True, jumpkind=None*)

Get successors of a node in the control flow graph.

Parameters

- **node** (*CFGNode*) – The node.
- **excluding_fakeret** (*bool*) – True if you want to exclude all successors that is connected to the node with a fakeret edge.
- **jumpkind** (*str / None*) – Only return successors with the specified jumpkind. This argument will be ignored if set to None.
- **jumpkind** –

Returns

A list of successors

Return type

`list`

get_successors_and_jumpkinds(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the successor of the CFG node and the second element is the jumpkind of the successor.

Parameters

- **node** (`CFGNode`) – The node.
- **excluding_fakeret** (`bool`) – True if you want to exclude all successors that are fall-through successors.

Returns

A list of successors and their corresponding jumpkinds.

Return type

`list`

get_successors_and_jumpkind(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the successor of the CFG node and the second element is the jumpkind of the successor.

Parameters

- **node** (`CFGNode`) – The node.
- **excluding_fakeret** (`bool`) – True if you want to exclude all successors that are fall-through successors.

Returns

A list of successors and their corresponding jumpkinds.

Return type

`list`

get_predecessors_and_jumpkinds(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the predecessor of the CFG node and the second element is the jumpkind of the predecessor.

Parameters

- **node** (`CFGNode`) – The node.
- **excluding_fakeret** (`bool`) – True if you want to exclude all predecessors that are fall-through predecessors.

Return type

`List[Tuple[CFGNode, str]]`

Returns

A list of predecessors and their corresponding jumpkinds.

get_predecessors_and_jumpkind(*node*, *excluding_fakeret=True*)

Get a list of tuples where the first element is the predecessor of the CFG node and the second element is the jumpkind of the predecessor.

Parameters

- **node** (`CFGNode`) – The node.

- **excluding_fakeret** (*bool*) – True if you want to exclude all predecessors that are fall-through predecessors.

Return type

List[Tuple[CFGNode, str]]

Returns

A list of predecessors and their corresponding jumpkinds.

get_all_predecessors(*cfgnode, depth_limit=None*)

Get all predecessors of a specific node on the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The CFGNode object
- **depth_limit** (*int*) – Optional depth limit for the depth-first search

Returns

A list of predecessors in the CFG

Return type

list

get_all_successors(*cfgnode, depth_limit=None*)

Get all successors of a specific node on the control flow graph.

Parameters

- **cfgnode** (*CFGNode*) – The CFGNode object
- **depth_limit** (*int*) – Optional depth limit for the depth-first search

Returns

A list of successors in the CFG

Return type

list

get_branching_nodes()

Returns all nodes that has an out degree ≥ 2

get_exit_stmt_idx(*src_block, dst_block*)

Get the corresponding exit statement ID for control flow to reach destination block from source block. The exit statement ID was put on the edge when creating the CFG. Note that there must be a direct edge between the two blocks, otherwise an exception will be raised.

Returns

The exit statement ID

add_memory_data(*data_addr, data_type, data_size=None*)

Add a MemoryData entry to self.memory_data.

Parameters

- **data_addr** (*int*) – Address of the data
- **data_type** (*Optional[MemoryDataSort]*) – Type of the memory data
- **data_size** (*Optional[int]*) – Size of the memory data, or None if unknown for now.

Return type

bool

Returns

True if a new memory data entry is added, False otherwise.

tidy_data_references(*memory_data_addrs=None, exec_mem_regions=None, xrefs=None, seg_list=None, data_type_guessing_handlers=None*)

Go through all data references (or the ones as specified by *memory_data_addrs*) and determine their sizes and types if possible.

Parameters

- **memory_data_addrs** (*Optional[List[int]]*) – A list of addresses of memory data, or None if tidying all known memory data entries.
- **exec_mem_regions** (*Optional[List[Tuple[int, int]]]*) – A list of start and end addresses of executable memory regions.
- **seg_list** (*Optional[SegmentList]*) – The segment list that CFGFast uses during CFG recovery.
- **data_type_guessing_handlers** (*Optional[List[Callable]]*) – A list of Python functions that will guess data types. They will be called in sequence to determine data types for memory data whose type is unknown.
- **xrefs** (*XRefManager / None*) –

Return type

bool

Returns

True if new data entries are found, False otherwise.

remove_node_and_graph_node(*node*)

Like *remove_node*, but also removes node from the graph.

Parameters

- **node** (*CFGNode*) – The node to remove.

Return type

None

get_intersecting_functions(*addr, size=1, kb=None*)

Find all functions with nodes intersecting [addr, addr + size).

Parameters

- **addr** (*int*) – Minimum address of target region.
- **size** (*int*) – Size of region, in bytes.
- **kb** (*Optional[KnowledgeBase]*) – Knowledge base to search for functions in.

Return type

Set[Function]

find_function_for_reflow_into_addr(*addr, kb=None*)

Look for a function that flows into a new node at addr.

Parameters

- **addr** (*int*) – Address of new block.
- **kb** (*Optional[KnowledgeBase]*) – Knowledge base to search for functions in.

Return type`Optional[Function]`**clear_region_for_reflow**(*addr*, *size=1*, *kb=None*)Remove nodes in the graph intersecting region [*addr*, *addr* + *size*).

Any functions that intersect the range, and their associated nodes in the CFG, will also be removed from the knowledge base for analysis.

Parameters

- **addr** (`int`) – Minimum address of target region.
- **size** (`int`) – Size of the region, in bytes.
- **kb** (`Optional[KnowledgeBase]`) – Knowledge base to search for functions in.

Return type`None`**class** `angr.knowledge_plugins.cfg.memory_data.MemoryDataSort`Bases: `object`**Unspecified** = `None`**Unknown** = `'unknown'`**Integer** = `'integer'`**PointerArray** = `'pointer-array'`**String** = `'string'`**UnicodeString** = `'unicode'`**SegmentBoundary** = `'segment-boundary'`**CodeReference** = `'code reference'`**GOTPLTEEntry** = `'GOT PLT Entry'`**ELFHeader** = `'elf-header'`**FloatingPoint** = `'fp'`**class** `angr.knowledge_plugins.cfg.memory_data.MemoryData`(*address*, *size*, *sort*, *pointer_addr=None*,
max_size=None, *reference_size=None*)Bases: `Serializable``MemoryData` describes the syntactic content of a single address of memory.*reference_size* reflects the size of *content*. It can be different from *size*, which is the actual size of the memory data item in memory. The intended way to get the actual content in memory is `self.content[:self.size]`.**Parameters**

- **address** (`int`) –
- **size** (`int`) –
- **sort** (`str` | `None`) –
- **pointer_addr** (`int` | `None`) –
- **max_size** (`int` | `None`) –

- `reference_size(int)` –

`__init__(address, size, sort, pointer_addr=None, max_size=None, reference_size=None)`

Parameters

- `address(int)` –
- `size(int)` –
- `sort(str | None)` –
- `pointer_addr(int | None)` –
- `max_size(int | None)` –
- `reference_size(int | None)` –

`addr: int`

`size: int`

`reference_size: int`

`sort: Optional[str]`

`max_size: Optional[int]`

`pointer_addr: Optional[int]`

`content: Optional[bytes]`

property address

`copy()`

Make a copy of the MemoryData.

Returns

A copy of the MemoryData instance.

Return type

MemoryData

`fill_content(loader)`

Load data to fill self.content.

Parameters

loader – The project loader.

Returns

None

`serialize_to_cmessage()`

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod `parse_from_cmessage(cmsg, **kwargs)`

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

class `angr.knowledge_plugins.cfg.cfg_manager.CFGManager(kb)`

Bases: [KnowledgeBasePlugin](#)

This is the CFG manager, it manages CFGs

`__init__(kb)`

`new_model(prefix)`

`copy()`

`get_most_accurate()`

Return type

[Optional](#)[[CFGModel](#)]

Returns

The most accurate CFG present in the CFGManager, or None if it does not hold any.

class `angr.knowledge_plugins.cfg.cfg_node.CFGNodeCreationFailure(exc_info=None, to_copy=None)`

Bases: [object](#)

This class contains additional information for whenever creating a CFGNode failed. It includes a full traceback and the exception messages.

`__init__(exc_info=None, to_copy=None)`

`short_reason`

`long_reason`

`traceback`

class `angr.knowledge_plugins.cfg.cfg_node.CFGNode(addr, size, cfg, simprocedure_name=None, no_ret=False, function_address=None, block_id=None, irsb=None, soot_block=None, instruction_addrs=None, thumb=False, byte_string=None, is_syscall=None, name=None)`

Bases: [Serializable](#)

This class stands for each single node in CFG.

Parameters

- **block_id** ([angr.analyses.cfg.cfg_job_base.BlockID](#) | [int](#)) –
- **byte_string** ([bytes](#) | [None](#)) –

```
__init__(addr, size, cfg, simprocedure_name=None, no_ret=False, function_address=None,
         block_id=None, irsb=None, soot_block=None, instruction_addrs=None, thumb=False,
         byte_string=None, is_syscall=None, name=None)
```

Note: `simprocedure_name` is not used to recreate the `SimProcedure` object. It's only there for better `__repr__`.

`addr`

`size`

`simprocedure_name`

`no_ret`

`function_address`

`thumb`

`byte_string`: `Optional[bytes]`

`is_syscall`

`instruction_addrs`

`irsb`

`soot_block`

`has_return`

`block_id`: `Union[angr.analyses.cfg.cfg_job_base.BlockID, int]`

`property name`

`property successors`

`property predecessors`

`successors_and_jumpkinds` (*excluding_fakeret=True*)

`predecessors_and_jumpkinds` (*excluding_fakeret=True*)

`get_data_references` (*kb=None*)

Get the known data references for this `CFGNode` via the knowledge base.

Parameters

kb – Which knowledge base to use; uses the global KB by default if none is provided

Returns

Generator yielding xrefs to this `CFGNode`'s block.

Return type

iter

property accessed_data_references

Property providing a view of all the known data references for this `CFGNode` via the global knowledge base

Returns

Generator yielding xrefs to this `CFGNode`'s block.

Return type

iter

property `is_simprocedure`

property `callstack_key`

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod `parse_from_cmessage(cmsg, cfg=None)`

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

copy()

merge(other)

Merges this node with the other, returning a new node that spans the both.

to_codenode()

property `block`

property `syscall_name`

```
class angr.knowledge_plugins.cfg.cfg_node.CFGNode(addr, size, cfg, simprocedure_name=None,
                                                  no_ret=False, function_address=None,
                                                  block_id=None, irsb=None,
                                                  instruction_addrs=None, thumb=False,
                                                  byte_string=None, is_syscall=None, name=None,
                                                  input_state=None, final_states=None,
                                                  syscall_name=None, looping_times=0,
                                                  depth=None, callstack_key=None,
                                                  creation_failure_info=None)
```

Bases: [CFGNode](#)

The CFGNode that is used in CFGEmulated.

Parameters

- **block_id** ([angr.analyses.cfg.cfg_job_base.BlockID](#) | `int`) –
- **byte_string** (`bytes` | `None`) –

```
__init__(addr, size, cfg, simprocedure_name=None, no_ret=False, function_address=None,
         block_id=None, irsb=None, instruction_addrs=None, thumb=False, byte_string=None,
         is_syscall=None, name=None, input_state=None, final_states=None, syscall_name=None,
         looping_times=0, depth=None, callstack_key=None, creation_failure_info=None)
```

Note: `simprocedure_name` is not used to recreate the `SimProcedure` object. It's only there for better `__repr__`.

```

input_state
looping_times
depth
creation_failure_info
final_states
return_target
syscall
property callstack_key
property creation_failed
downsize()
    Drop saved states.
copy()

```

```
class angr.knowledge_plugins.cfg.indirect_jump.IndirectJumpType
```

```
    Bases: object
```

```
    Jumptable_AddressLoadedFromMemory = 0
```

```
    Jumptable_AddressComputed = 1
```

```
    Vtable = 3
```

```
    Unknown = 255
```

```
class angr.knowledge_plugins.cfg.indirect_jump.IndirectJump(addr, ins_addr, func_addr, jumpkind,
                                                             stmt_idx, resolved_targets=None,
                                                             jumptable=False,
                                                             jumptable_addr=None,
                                                             jumptable_size=None,
                                                             jumptable_entry_size=None,
                                                             jumptable_entries=None, type_=255)
```

```
    Bases: Serializable
```

Parameters

- **addr** (*int*) –
- **ins_addr** (*int*) –
- **func_addr** (*int*) –
- **jumpkind** (*str*) –
- **stmt_idx** (*int*) –
- **resolved_targets** (*List[int] | None*) –
- **jumptable** (*bool*) –
- **jumptable_addr** (*int | None*) –
- **jumptable_size** (*int | None*) –

- `jumpable_entry_size` (`int` | `None`) –
- `jumpable_entries` (`List[int]` | `None`) –
- `type_` (`int` | `None`) –

`__init__` (`addr`, `ins_addr`, `func_addr`, `jumpkind`, `stmt_idx`, `resolved_targets=None`, `jumpable=False`, `jumpable_addr=None`, `jumpable_size=None`, `jumpable_entry_size=None`, `jumpable_entries=None`, `type_=255`)

Parameters

- `addr` (`int`) –
- `ins_addr` (`int`) –
- `func_addr` (`int`) –
- `jumpkind` (`str`) –
- `stmt_idx` (`int`) –
- `resolved_targets` (`List[int]` | `None`) –
- `jumpable` (`bool`) –
- `jumpable_addr` (`int` | `None`) –
- `jumpable_size` (`int` | `None`) –
- `jumpable_entry_size` (`int` | `None`) –
- `jumpable_entries` (`List[int]` | `None`) –
- `type_` (`int` | `None`) –

`addr`

`ins_addr`

`func_addr`

`jumpkind`

`stmt_idx`

`resolved_targets`

`jumpable`

`jumpable_addr`

`jumpable_size`

`jumpable_entry_size`

`jumpable_entries`

`type`

`class` `angr.knowledge_plugins.types.TypesStore` (`kb`)

Bases: `KnowledgeBasePlugin`, `UserDict`

A kb plugin that stores a mapping from name to TypeRef. It will return types from `angr.sim_type.ALL_TYPES` as a default.

`__init__(kb)`

`copy()`

`iter_own()`

Iterate over all the names which are stored in this object - i.e. `values()` without `ALL_TYPES`

`rename(old, new)`

`unique_type_name()`

Return type

`str`

class `angr.knowledge_plugins.comments.Comments(kb)`

Bases: `KnowledgeBasePlugin, dict`

Tracks comments via a Dict of Address -> Text

Parameters

kb (`KnowledgeBase`) –

`copy()` → a shallow copy of D

class `angr.knowledge_plugins.data.Data(kb)`

Bases: `KnowledgeBasePlugin`

The knowledge what purpose this plugin serves has been lost to the passing of time but the linter does not care for these failures of mere mortals and demands a docstring anyway. The pact has been made, and no violations of the rules will be tolerated, even if the spirit does not match the letter. Making the plugin smaller has only increased the weight of the failure, and thus this file has drawn its ire.

The only thing left to do is to attempt to find meaning in the meaninglessness, as the only act of rebellion against the uncaring forces that bind us. For is this not what being human is all about?

Parameters

kb (`KnowledgeBase`) –

`copy()`

class `angr.knowledge_plugins.indirect_jumps.IndirectJumps(kb)`

Bases: `KnowledgeBasePlugin, dict`

This plugin tracks the targets of indirect jumps

`__init__(kb)`

`copy()` → a shallow copy of D

`update_resolved_addrs(indirect_address, resolved_addresses)`

Parameters

- **indirect_address** (`int`) –
- **resolved_addresses** (`List[int]`) –

class `angr.knowledge_plugins.labels.Labels(kb)`

Bases: `KnowledgeBasePlugin`

`__init__(kb)`

items()

get(addr)

Get a label as string for a given address Same as .labels[x]

lookup(name)

Returns an address to a given label To show all available labels, iterate over .labels or list(b.kb.labels)

copy()

get_unique_label(label)

Get a unique label name from the given label name.

Parameters

label (*str*) – The desired label name.

Returns

A unique label name.

class `angr.knowledge_plugins.functions.function_manager.FunctionDict(backref, *args, **kwargs)`

Bases: `SortedDict`

FunctionDict is a dict where the keys are function starting addresses and map to the associated **Function**.

__init__(*backref, *args, **kwargs*)

Initialize sorted dict instance.

Optional key-function argument defines a callable that, like the *key* argument to the built-in *sorted* function, extracts a comparison key from each dictionary key. If no function is specified, the default compares the dictionary keys directly. The key-function argument must be provided as a positional argument and must come before all other arguments.

Optional iterable argument provides an initial sequence of pairs to initialize the sorted dict. Each pair in the sequence defines the key and corresponding value. If a key is seen more than once, the last value associated with it is stored in the new sorted dict.

Optional mapping argument provides an initial mapping of items to initialize the sorted dict.

If keyword arguments are given, the keywords themselves, with their associated values, are added as items to the dictionary. If a key is specified both in the positional argument and as a keyword argument, the value associated with the keyword is stored in the sorted dict.

Sorted dict keys must be hashable, per the requirement for Python's dictionaries. Keys (or the result of the key-function) must also be comparable, per the requirement for sorted lists.

```
>>> d = {'alpha': 1, 'beta': 2}
>>> SortedDict([('alpha', 1), ('beta', 2)]) == d
True
>>> SortedDict({'alpha': 1, 'beta': 2}) == d
True
>>> SortedDict(alpha=1, beta=2) == d
True
```

get(addr)

Return the value for key if key is in the dictionary, else default.

floor_addr(addr)

ceiling_addr(addr)

class `angr.knowledge_plugins.functions.function_manager.FunctionManager`(*kb*)

Bases: *KnowledgeBasePlugin*, *Mapping*

This is a function boundaries management tool. It takes in intermediate results during CFG generation, and manages a function map of the binary.

__init__(*kb*)

copy()

clear()

get_by_addr(*addr*)

Return type
Function

get_by_name(*name*)

Return type
Generator[*Function*, *None*, *None*]

Parameters
name (*str*) –

contains_addr(*addr*)

Decide if an address is handled by the function manager.

Note: this function is non-conformant with python programming idioms, but its needed for performance reasons.

Parameters
addr (*int*) – Address of the function.

ceiling_func(*addr*)

Return the function who has the least address that is greater than or equal to *addr*.

Parameters
addr (*int*) – The address to query.

Returns
A *Function* instance, or *None* if there is no other function after *addr*.

Return type
Function or *None*

floor_func(*addr*)

Return the function who has the greatest address that is less than or equal to *addr*.

Parameters
addr (*int*) – The address to query.

Returns
A *Function* instance, or *None* if there is no other function before *addr*.

Return type
Function or *None*

query(*query*)

Query for a function using selectors to disambiguate. Supported variations: *rtype*: *Optional*[*Function*]

::<name> Function <name> in the main object ::<addr>::<name> Function <name> at <addr>
::<obj>::<name> Function <name> in <obj>

Parameters

query (*str*) –

Return type

Function | None

function(*addr=None, name=None, create=False, syscall=False, plt=None*)

Get a function object from the function manager.

Pass either *addr* or *name* with the appropriate values.

Parameters

- **addr** (*int*) – Address of the function.
- **name** (*str*) – Name of the function.
- **create** (*bool*) – Whether to create the function or not if the function does not exist.
- **syscall** (*bool*) – True to create the function as a syscall, False otherwise.
- **plt** (*bool* or *None*) – True to find the PLT stub, False to find a non-PLT stub, None to disable this restriction.

Returns

The Function instance, or None if the function is not found and create is False.

Return type

Function or None

dbg_draw(*prefix='dbg_function_'*)

rebuild_callgraph()

```
class angr.knowledge_plugins.functions.function.Function(function_manager, addr, name=None,
                                                         syscall=None, is_simprocedure=None,
                                                         binary_name=None, is_plt=None,
                                                         returning=None, alignment=False)
```

Bases: *Serializable*

A representation of a function and various information about it.

Parameters

- **is_simprocedure** (*bool* | *None*) –
- **is_plt** (*bool* | *None*) –

```
__init__(function_manager, addr, name=None, syscall=None, is_simprocedure=None,
          binary_name=None, is_plt=None, returning=None, alignment=False)
```

Function constructor. If the optional parameters are not provided, they will be automatically determined upon the creation of a Function object.

Parameters

- **addr** – The address of the function.
- **is_simprocedure** (*bool* | *None*) –
- **is_plt** (*bool* | *None*) –

The following parameters are optional.

Parameters

- **name** (*str*) – The name of the function.
- **syscall** (*bool*) – Whether this function is a syscall or not.
- **is_simprocedure** (*bool*) – Whether this function is a SimProcedure or not.
- **binary_name** (*str*) – Name of the binary where this function is.
- **is_plt** (*bool*) – If this function is a PLT entry.
- **returning** (*bool*) – If this function returns.
- **alignment** (*bool*) – If this function acts as an alignment filler. Such functions usually only contain nops.

transition_graph

normalized

addr

startpoint

is_alignment

bp_on_stack

retaddr_on_stack

sp_delta

prototype: *Optional[SimTypeFunction]*

prototype_libname: *Optional[str]*

is_prototype_guessed: *bool*

prepared_registers

prepared_stack_variables

registers_read_afterwards

info

tags

ran_cca

is_syscall

is_simprocedure

is_plt

is_default_name

from_signature

binary_name

calling_convention: *Optional[SimCC]*

property alignment

property name

property project

property returning

property blocks

An iterator of all local blocks in the current function.

Returns

angr.lifter.Block instances.

property cyclomatic_complexity

The cyclomatic complexity of the function.

Cyclomatic complexity is a software metric used to indicate the complexity of a program. It is a quantitative measure of the number of linearly independent paths through a program's source code. It is computed using the formula: $M = E - N + 2P$, where E = the number of edges in the graph, N = the number of nodes in the graph, P = the number of connected components.

The cyclomatic complexity value is lazily computed and cached for future use. Initially this value is None until it is computed for the first time

Returns

The cyclomatic complexity of the function.

Return type

int

property xrefs

An iterator of all xrefs of the current function.

Returns

angr.knowledge_plugins.xrefs.xref.XRef instances.

property block_addrs

An iterator of all local block addresses in the current function.

Returns

block addresses.

property block_addrs_set

Return a set of block addresses for a better performance of inclusion tests.

Returns

A set of block addresses.

Return type

set

get_block(addr, size=None, byte_string=None)

Getting a block out of the current function.

Parameters

- **addr** (int) – The address of the block.
- **size** (int) – The size of the block. This is optional. If not provided, angr will load
- **byte_string** (Optional[bytes]) –

Returns**get_block_size**(*addr*)**Return type**`Optional[int]`**Parameters****addr** (*int*) –**property nodes:** `Iterable[CodeNode]`**get_node**(*addr*)**Return type**`Block`**property has_unresolved_jumps****property has_unresolved_calls****property operations**

All of the operations that are done by this functions.

property code_constants

All of the constants that are used by this functions's code.

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type`protobuf.cmessage`**classmethod parse_from_cmessage**(*cmsg*, ***kwargs*)**Parameters****cmsg** –**Return Function**

The function instantiated out of the cmsg data.

string_references(*minimum_length=2*)

All of the constant string references used by this function.

Parameters**minimum_length** – The minimum length of strings to find (default is 1)**Returns**

A generator yielding tuples of (address, string) where is address is the location of the string in memory.

property local_runtime_values

Tries to find all runtime values of this function which do not come from inputs. These values are generated by starting from a blank state and reanalyzing the basic blocks once each. Function calls are skipped, and back edges are never taken so these values are often unreliable, This function is good at finding simple constant addresses which the function will use or calculate.

Returns

a set of constants

property `num_arguments`

property `endpoints`

property `endpoints_with_type`

property `ret_sites`

property `jumpout_sites`

property `retout_sites`

property `callout_sites`

property `size`

property `binary`

Get the object this function belongs to. :return: The object this function belongs to.

property `offset`: `int`

the function's binary offset (i.e., non-rebased address)

Type

return

property `symbol`: `None` | `Symbol`

the function's Symbol, if any

Type

return

property `pseudocode`: `str`

the function's pseudocode

Type

return

add_jumpout_site(*node*)

Add a custom jumpout site.

Parameters

node – The address of the basic block that control flow leaves during this transition.

Returns

None

add_retout_site(*node*)

Add a custom retout site.

Retout (returning to outside of the function) sites are very rare. It mostly occurs during CFG recovery when we incorrectly identify the beginning of a function in the first iteration, and then correctly identify that function later in the same iteration (function alignments can lead to this bizarre case). We will mark all edges going out of the header of that function as a outside edge, because all successors now belong to the incorrectly-identified function. This identification error will be fixed in the second iteration of CFG recovery. However, we still want to keep track of jumpouts/retouts during the first iteration so other logic in CFG recovery still work.

Parameters

node – The address of the basic block that control flow leaves the current function after a call.

Returns

None

mark_nonreturning_calls_endpoints()

Iterate through all call edges in transition graph. For each call a non-returning function, mark the source basic block as an endpoint.

This method should only be executed once all functions are recovered and analyzed by CFG recovery, so we know whether each function returns or not.

Returns

None

get_call_sites()

Gets a list of all the basic blocks that end in calls.

Return type

`Iterable[int]`

Returns

A view of the addresses of the blocks that end in calls.

get_call_target(*callsite_addr*)

Get the target of a call.

Parameters

callsite_addr – The address of a basic block that ends in a call.

Returns

The target of said call, or None if callsite_addr is not a callsite.

get_call_return(*callsite_addr*)

Get the hypothetical return address of a call.

Parameters

callsite_addr – The address of the basic block that ends in a call.

Returns

The likely return target of said call, or None if callsite_addr is not a callsite.

property graph

Get a local transition graph. A local transition graph is a transition graph that only contains nodes that belong to the current function. All edges, except for the edges going out from the current function or coming from outside the current function, are included.

The generated graph is cached in self._local_transition_graph.

Returns

A local transition graph.

Return type

`networkx.DiGraph`

graph_ex(*exception_edges=True*)

Get a local transition graph with a custom configuration. A local transition graph is a transition graph that only contains nodes that belong to the current function. This method allows user to exclude certain types of edges together with the nodes that are only reachable through such edges, such as exception edges.

The generated graph is not cached.

Parameters

exception_edges (*bool*) – Should exception edges and the nodes that are only reachable through exception edges be kept.

Returns

A local transition graph with a special configuration.

Return type

networkx.DiGraph

transition_graph_ex(exception_edges=True)

Get a transition graph with a custom configuration. This method allows user to exclude certain types of edges together with the nodes that are only reachable through such edges, such as exception edges.

The generated graph is not cached.

Parameters

exception_edges (*bool*) – Should exception edges and the nodes that are only reachable through exception edges be kept.

Returns

A local transition graph with a special configuration.

Return type

networkx.DiGraph

subgraph(ins_addrs)

Generate a sub control flow graph of instruction addresses based on self.graph

Parameters

ins_addrs (*iterable*) – A collection of instruction addresses that should be included in the subgraph.

Return networkx.DiGraph

A subgraph.

instruction_size(insn_addr)

Get the size of the instruction specified by *insn_addr*.

Parameters

insn_addr (*int*) – Address of the instruction

Return int

Size of the instruction in bytes, or None if the instruction is not found.

addr_to_instruction_addr(addr)

Obtain the address of the instruction that covers @addr.

Parameters

addr (*int*) – An address.

Returns

Address of the instruction that covers @addr, or None if this addr is not covered by any instruction of this function.

Return type

int or None

dbg_print()

Returns a representation of the list of basic blocks in this function.

dbg_draw(*filename*)

Draw the graph and save it to a PNG file.

property arguments

property has_return

property callable

normalize()

Make sure all basic blocks in the transition graph of this function do not overlap. You will end up with a CFG that IDA Pro generates.

This method does not touch the CFG result. You may call `CFG{Emulated, Fast}.normalize()` for that matter.

Returns

None

find_declaration(*ignore_binary_name=False, binary_name_hint=None*)

Find the most likely function declaration from the embedded collection of prototypes, set it to `self.prototype`, and update `self.calling_convention` with the declaration.

Parameters

- **ignore_binary_name** (`bool`) – Do not rely on the executable or library where the function belongs to determine its source library. This is useful when working on statically linked binaries (because all functions will belong to the main executable). We will search for all libraries in `angr` to find the first declaration match.
- **binary_name_hint** (`Optional[str]`) – Substring of the library name where this function might be originally coming from. Useful for FLIRT-identified functions in statically linked binaries.

Return type

`bool`

Returns

True if a declaration is found and `self.prototype` and `self.calling_convention` are updated. False if we fail to find a matching function declaration, in which case `self.prototype` or `self.calling_convention` will be kept untouched.

property demangled_name

get_unambiguous_name(*display_name=None*)

Get a disambiguated function name.

Parameters

display_name (`Optional[str]`) – Name to display, otherwise the function name.

Return type

`str`

Returns

The function name in the form: `::<name>` when the function binary is the main object. `::<obj>::<name>` when the function binary is not the main object. `::<addr>::<name>` when the function binary is an unnamed non-main object, or when multiple functions with the same name are defined in the function binary.

apply_definition(*definition*, *calling_convention*=None)

Return type

None

Parameters

- **definition** (*str*) –
- **calling_convention** (SimCC / Type[SimCC] / None) –

functions_called()

Return type

Set[Function]

Returns

The set of all functions that can be reached from the function represented by self.

copy()

pp(***kwargs*)

Pretty-print the function disassembly.

class angr.knowledge_plugins.functions.function_parser.**FunctionParser**

Bases: object

The implementation of the serialization methods for the <Function> class.

static serialize(*function*)

:return :

static parse_from_cmsg(*cmsg*, *function_manager*=None, *project*=None, *all_func_addrs*=None)

Parameters

cmsg – The data to instantiate the <Function> from.

Return Function

class angr.knowledge_plugins.functions.soot_function.**SootFunction**(*function_manager*, *addr*,
name=None, *syscall*=None)

Bases: Function

A representation of a function and various information about it.

__init__(*function_manager*, *addr*, *name*=None, *syscall*=None)

Function constructor for Soot

Parameters

- **addr** – The address of the function.
- **name** – (Optional) The name of the function.
- **syscall** – (Optional) Whether this function is a syscall or not.

transition_graph

normalized

addr

is_syscall

`is_plt`
`is_simprocedure`
`binary_name`
`bp_on_stack`
`retaddr_on_stack`
`sp_delta`
`calling_convention: Optional[SimCC]`
`prototype: Optional[SimTypeFunction]`
`prepared_registers`
`prepared_stack_variables`
`registers_read_afterwards`
`startpoint`
`info`
`tags`
`normalize()`

Make sure all basic blocks in the transition graph of this function do not overlap. You will end up with a CFG that IDA Pro generates.

This method does not touch the CFG result. You may call `CFG{Emulated, Fast}.normalize()` for that matter.

Returns

None

`is_default_name`
`from_signature`
`prototype_libname: Optional[str]`
`is_alignment`
`is_prototype_guessed: bool`
`ran_cca`

`class angr.knowledge_plugins.variables.variable_access.VariableAccessSort`

Bases: `object`

Provides enums for variable access types.

`WRITE = 0`

`READ = 1`

`REFERENCE = 2`

```
class angr.knowledge_plugins.variables.variable_access.VariableAccess(variable, access_type,  
                                                                    location, offset,  
                                                                    atom_hash=None)
```

Bases: `Serializable`

Describes a variable access.

```
__init__(variable, access_type, location, offset, atom_hash=None)
```

variable: `SimVariable`

access_type: `int`

location: `CodeLocation`

offset: `Optional[int]`

atom_hash: `Optional[int]`

```
serialize_to_cmessage()
```

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

```
classmethod parse_from_cmessage(cmsg, variable_by_ident=None, **kwargs)
```

Parse a protobuf cmessage and create a class object.

Parameters

- **cmsg** – The probobuf cmessage object.
- **variable_by_ident** (`Dict[str, SimVariable]` | `None`) –

Returns

A unserialized class object.

Return type

cls

```
class angr.knowledge_plugins.variables.variable_manager.VariableType
```

Bases: `object`

Describes variable types.

REGISTER = 0

MEMORY = 1

```
class angr.knowledge_plugins.variables.variable_manager.LiveVariables(register_region,  
                                                                    stack_region)
```

Bases: `object`

A collection of live variables at a program point.

```
__init__(register_region, stack_region)
```

register_region

stack_region

```
class angr.knowledge_plugins.variables.variable_manager.VariableManagerInternal(manager,
                                                                              func_addr=None)
```

Bases: [Serializable](#)

Manage variables for a function. It is meant to be used internally by VariableManager, but it's common to be given a reference to one in response to a query for "the variables for a given function". Maybe a better name would be "VariableManagerScope".

```
__init__(manager, func_addr=None)
```

```
set_manager(manager)
```

Parameters

manager ([VariableManager](#)) –

```
serialize_to_cmessage()
```

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

```
classmethod parse_from_cmessage(cmsg, variable_manager=None, func_addr=None, **kwargs)
```

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

```
next_variable_ident(sort)
```

```
add_variable(sort, start, variable)
```

Parameters

variable ([SimVariable](#)) –

```
set_variable(sort, start, variable)
```

Parameters

variable ([SimVariable](#)) –

```
write_to(variable, offset, location, overwrite=False, atom=None)
```

```
read_from(variable, offset, location, overwrite=False, atom=None)
```

```
reference_at(variable, offset, location, overwrite=False, atom=None)
```

```
record_variable(location, variable, offset, overwrite=False, atom=None)
```

Parameters

location ([CodeLocation](#)) –

remove_variable_by_atom(*location*, *variable*, *atom*)

Parameters

- **location** (*CodeLocation*) –
- **variable** (*SimVariable*) –

make_phi_node(*block_addr*, **variables*)

Create a phi variable for variables at block *block_addr*.

Parameters

- **block_addr** (*int*) – The address of the current block.
- **variables** – Variables that the phi variable represents.

Returns

The created phi variable.

set_live_variables(*addr*, *register_region*, *stack_region*)

find_variables_by_insn(*ins_addr*, *sort*)

is_variable_used_at(*variable*, *loc*)

Return type

bool

Parameters

- **variable** (*SimVariable*) –
- **loc** (*Tuple[int, int]*) –

find_variable_by_stmt(*block_addr*, *stmt_idx*, *sort*, *block_idx=None*)

Parameters

block_idx (*int* | *None*) –

find_variables_by_stmt(*block_addr*, *stmt_idx*, *sort*, *block_idx=None*)

Return type

List[Tuple[SimVariable, int]]

Parameters

- **block_addr** (*int*) –
- **stmt_idx** (*int*) –
- **sort** (*str*) –
- **block_idx** (*int* | *None*) –

find_variable_by_atom(*block_addr*, *stmt_idx*, *atom*, *block_idx=None*)

Parameters

block_idx (*int* | *None*) –

find_variables_by_atom(*block_addr*, *stmt_idx*, *atom*, *block_idx=None*)

Return type

Set[Tuple[SimVariable, int]]

Parameters

block_idx (*int* | *None*) –

find_variables_by_stack_offset (*offset*)

Return type

Set[*SimVariable*]

Parameters

offset (*int*) –

find_variables_by_register (*reg*)

Return type

Set[*SimVariable*]

Parameters

reg (*str* | *int*) –

get_variable_accesses (*variable*, *same_name=False*)

Return type

List[*VariableAccess*]

Parameters

- **variable** (*SimVariable*) –
- **same_name** (*bool*) –

get_variables (*sort=None*, *collapse_same_ident=False*)

Get a list of variables.

Parameters

- **sort** (*Optional*[*Literal*['stack', 'reg']]) – Sort of the variable to get.
- **collapse_same_ident** – Whether variables of the same identifier should be collapsed or not.

Return type

List[*Union*[*SimStackVariable*, *SimRegisterVariable*]]

Returns

A list of variables.

get_unified_variables (*sort=None*)

Get a list of unified variables.

Parameters

sort (*Optional*[*Literal*['stack', 'reg']]) – Sort of the variable to get.

Return type

List[*Union*[*SimStackVariable*, *SimRegisterVariable*]]

Returns

A list of variables.

get_global_variables (*addr*)

Get global variable by the address of the variable.

Parameters

addr (*int*) – Address of the variable.

Returns

A set of variables or an empty set if no variable exists.

is_phi_variable(*var*)

Test if *var* is a phi variable.

Parameters

var (*SimVariable*) – The variable instance.

Returns

True if *var* is a phi variable, False otherwise.

Return type

bool

get_phi_subvariables(*var*)

Get sub-variables that phi variable *var* represents.

Parameters

var (*SimVariable*) – The variable instance.

Returns

A set of sub-variables, or an empty set if *var* is not a phi variable.

Return type

set

get_phi_variables(*block_addr*)

Get a dict of phi variables and their corresponding variables.

Parameters

block_addr (*int*) – Address of the block.

Returns

A dict of phi variables or an empty dict if there are no phi variables at the block.

Return type

dict

get_variables_without_writes()

Get all variables that have never been written to.

Return type

List[SimVariable]

Returns

A list of variables that are never written to.

input_variables(*exclude_specials=True*)

Get all variables that have never been written to.

Returns

A list of variables that are never written to.

Parameters

exclude_specials (*bool*) –

assign_variable_names(*labels=None, types=None*)

Assign default names to all SSA variables.

Parameters

labels – Known labels in the binary.

Returns

None

assign_unified_variable_names(*labels=None, arg_names=None, reset=False*)

Assign default names to all unified variables.

Parameters

- **labels** – Known labels in the binary.
- **arg_names** (*Optional[List[str]]*) – Known argument names.
- **reset** (*bool*) – Reset all variable names or not.

Return type

None

set_variable_type(*var, ty, name=None, override_bot=True, all_unified=False, mark_manual=False*)

Return type

None

Parameters

- **var** (*SimVariable*) –
- **ty** (*SimType*) –
- **name** (*str | None*) –
- **override_bot** (*bool*) –
- **all_unified** (*bool*) –
- **mark_manual** (*bool*) –

get_variable_type(*var*)

Return type

Optional[SimType]

remove_types()

unify_variables()

Map SSA variables to a unified variable. Fill in self._unified_variables.

Return type

None

set_unified_variable(*variable, unified*)

Set the unified variable for a given SSA variable.

Parameters

- **variable** (*SimVariable*) – The SSA variable.
- **unified** (*SimVariable*) – The unified variable.

Return type

None

Returns

None

unified_variable(*variable*)

Return the unified variable for a given SSA variable,

Parameters

variable (*SimVariable*) – The SSA variable.

Return type

Optional[SimVariable]

Returns

The unified variable, or None if there is no such SSA variable.

class angr.knowledge_plugins.variables.variable_manager.**VariableManager**(*kb*)

Bases: *KnowledgeBasePlugin*

Manage variables.

__init__(*kb*)

has_function_manager(*key*)

Return type

bool

Parameters

key (*int*) –

get_function_manager(*func_addr*)

Return type

VariableManagerInternal

initialize_variable_names()

Return type

None

get_variable_accesses(*variable*, *same_name=False*)

Get a list of all references to the given variable.

Parameters

- **variable** (*SimVariable*) – The variable.
- **same_name** (*bool*) – Whether to include all variables with the same variable name, or just based on the variable identifier.

Return type

List[VariableAccess]

Returns

All references to the variable.

copy()

static convert_variable_list(*vlist*, *manager*)

Parameters

- **vlist** (*List[Variable]*) –
- **manager** (*VariableManagerInternal*) –

load_from_dwarf(*cu_list=None*)

Parameters

cu_list (*List[CompilationUnit] | None*) –

class `angr.knowledge_plugins.debug_variables.DebugVariableContainer`

Bases: `object`

Variable tree for variables with same name to lock up which variable is visible at a given program counter address.

__init__()

It is recommended to use `DebugVariableManager.add_variable()` instead

from_pc(*pc*)

Returns the visible variable (if any) for a given pc address.

Return type

`Variable`

class `angr.knowledge_plugins.debug_variables.DebugVariable`(*low_pc, high_pc, cle_variable*)

Bases: `DebugVariableContainer`

Variables

- **low_pc** – Start of the visibility scope of the variable as program counter address (rebased)
- **high_pc** – End of the visibility scope of the variable as program counter address (rebased)
- **cle_variable** – Original variable from cle

Parameters

- **low_pc** (*int*) –
- **high_pc** (*int*) –
- **cle_variable** (*Variable*) –

__init__(*low_pc, high_pc, cle_variable*)

It is recommended to use `DebugVariableManager.add_variable()` instead

Parameters

- **low_pc** (*int*) –
- **high_pc** (*int*) –
- **cle_variable** (*Variable*) –

from_pc(*pc*)

Returns the visible variable (if any) for a given pc address.

Return type

`Variable`

contains(*dvar*)

Return type

`bool`

Parameters

dvar (*DebugVariable*) –

test_unsupported_overlap(*dvar*)

Test for an unsupported overlapping

Parameters

dvar (*DebugVariable*) – Second DebugVariable to compare with

Return type

bool

Returns

True if there is an unsupported overlapping

class `angr.knowledge_plugins.debug_variables.DebugVariableManager`(*kb*)

Bases: *KnowledgeBasePlugin*

Structure to manage and access variables with different visibility scopes.

Parameters

kb (*KnowledgeBase*) –

__init__(*kb*)

Parameters

kb (*KnowledgeBase*) –

from_name_and_pc(*var_name*, *pc_addr*)

Get a variable from its string in the scope of pc.

Return type

Variable

Parameters

- **var_name** (*str*) –
- **pc_addr** (*int*) –

from_name(*var_name*)

Get the variable container for all variables named var_name

Parameters

var_name (*str*) – name for a variable

Return type

DebugVariableContainer

add_variable(*cle_var*, *low_pc*, *high_pc*)

Add/load a variable

Parameters

- **cle_variable** – The variable to add
- **low_pc** (*int*) – Start of the visibility scope of the variable as program counter address (rebased)
- **high_pc** (*int*) – End of the visibility scope of the variable as program counter address (rebased)
- **cle_var** (*Variable*) –

add_variable_list(*vlist*, *low_pc*, *high_pc*)

Add all variables in a list with the same visibility range

Parameters

- **vlist** (`List[Variable]`) – A list of cle variables to add
- **low_pc** (`int`) – Start of the visibility scope as program counter address (rebased)
- **high_pc** (`int`) – End of the visibility scope as program counter address (rebased)

load_from_dwarf(*elf_object=None*, *cu=None*)

Automatically load all variables (global/local) from the DWARF debugging info

Parameters

- **elf_object** (`Optional[ELF]`) – Optional, when only one elf object should be considered (e.g. `p.loader.main_object`)
- **cu** (`Optional[CompilationUnit]`) – Optional, when only one compilation unit should be considered

class `angr.knowledge_plugins.structured_code.manager.StructuredCodeManager`(*kb*)

Bases: `KnowledgeBasePlugin`

__init__(*kb*)

discard(*key*)

available_flavors(*item*)

copy()

class `angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel`(*func_addr=None*,
track_liveness=True)

Bases: `object`

Models the definitions, uses, and memory of a `ReachingDefinitionState` object

Parameters

- **func_addr** (`int | None`) –
- **track_liveness** (`bool`) –

__init__(*func_addr=None*, *track_liveness=True*)

Parameters

- **func_addr** (`int | None`) –
- **track_liveness** (`bool`) –

add_def(*d*)

Return type

`None`

Parameters

d (`Definition`) –

kill_def(*d*)

Return type

None

Parameters

d (*Definition*) –

at_new_stmt(*codeloc*)

Return type

None

Parameters

codeloc (*CodeLocation*) –

at_new_block(*code_loc*, *pred_codelocs*)

Return type

None

Parameters

- **code_loc** (*CodeLocation*) –
- **pred_codelocs** (*List*[*CodeLocation*]) –

make_liveness_snapshot()

Return type

None

find_defs_at(*code_loc*, *op*=*ObservationPointType.OP_BEFORE*)

Return type

Set[*Definition*]

Parameters

- **code_loc** (*CodeLocation*) –
- **op** (*int*) –

get_defs(*atom*, *code_loc*, *op*)

Return type

Set[*Definition*]

Parameters

- **atom** (*Atom*) –
- **code_loc** (*CodeLocation*) –
- **op** (*int*) –

copy()

Return type

ReachingDefinitionsModel

merge(*model*)

Parameters

model (*ReachingDefinitionsModel*) –

get_observation_by_insn(*ins_addr*, *kind*)

Return type

`Optional[LiveDefinitions]`

Parameters

- **ins_addr** (`int` / `CodeLocation`) –
- **kind** (`ObservationPointType`) –

get_observation_by_node(*node_addr*, *kind*, *node_idx=None*)

Return type

`Optional[LiveDefinitions]`

Parameters

- **node_addr** (`int` / `CodeLocation`) –
- **kind** (`ObservationPointType`) –
- **node_idx** (`int` / `None`) –

get_observation_by_stmt(*arg1*, *arg2*, *arg3=None*, *, *block_idx=None*)

get_observation_by_exit(*node_addr*, *stmt_idx*, *src_node_idx=None*)

Return type

`Optional[LiveDefinitions]`

Parameters

- **node_addr** (`int`) –
- **stmt_idx** (`int`) –
- **src_node_idx** (`int` / `None`) –

class `angr.knowledge_plugins.key_definitions.KeyDefinitionManager`(*kb*)

Bases: `KnowledgeBasePlugin`

`KeyDefinitionManager` manages and caches reaching definition models for each function.

For each function, by default we cache the entire reaching definitions model with observed results at the following locations: - Before each call instruction: ('insn', address of the call instruction, OP_BEFORE) - After returning from each call: ('node', address of the block that ends with a call, OP_AFTER)

Parameters

kb (`KnowledgeBase`) –

__init__(*kb*)

Parameters

kb (`KnowledgeBase`) –

has_model(*func_addr*)

Parameters

func_addr (`int`) –

get_model(*func_addr*)

Parameters

func_addr (`int`) –

`copy()`

Return type

KeyDefinitionManager

```
class angr.knowledge_plugins.key_definitions.LiveDefinitions(arch, track_tmps=False,
    canonical_size=8, registers=None,
    stack=None, memory=None,
    heap=None, tmpls=None,
    others=None, register_uses=None,
    stack_uses=None, heap_uses=None,
    memory_uses=None,
    tmp_uses=None, other_uses=None,
    element_limit=5)
```

Bases: `object`

A LiveDefinitions instance contains definitions and uses for register, stack, memory, and temporary variables, uncovered during the analysis.

Parameters

- **arch** (*Arch*) –
- **track_tmpls** (*bool*) –

INITIAL_SP_32BIT = 2147418112

INITIAL_SP_64BIT = 140737488289792

```
__init__(arch, track_tmpls=False, canonical_size=8, registers=None, stack=None, memory=None,
    heap=None, tmpls=None, others=None, register_uses=None, stack_uses=None, heap_uses=None,
    memory_uses=None, tmp_uses=None, other_uses=None, element_limit=5)
```

Parameters

- **arch** (*Arch*) –
- **track_tmpls** (*bool*) –

project: *Optional*[Project]

arch

track_tmpls

registers: *MultiValuedMemory*

stack: *MultiValuedMemory*

memory: *MultiValuedMemory*

heap: *MultiValuedMemory*

tmpls: *Dict*[int, *Set*[*Definition*]]

others: *Dict*[*Atom*, *MultiValues*]

register_uses

stack_uses

```

heap_uses
memory_uses
tmp_uses: Dict[int, Set[CodeLocation]]
other_uses
uses_by_codeloc: Dict[CodeLocation, Set[Definition]]
property register_definitions
property stack_definitions
property memory_definitions
property heap_definitions
copy(discard_tmpdefs=False)

    Return type
        LiveDefinitions
reset_uses()
static top(bits)
    Get a TOP value.

    Parameters
        bits (int) – Width of the TOP value (in bits).

    Returns
        The TOP value.
static is_top(expr)
    Check if the given expression is a TOP value.

    Parameters
        expr – The given expression.

    Return type
        bool

    Returns
        True if the expression is TOP, False otherwise.
stack_address(offset)

    Return type
        Optional[BV]

    Parameters
        offset (int) –

static is_stack_address(addr)

    Return type
        bool

    Parameters
        addr (Base) –

```


static `get_stack_offset(addr, had_stack_base=False)`

Return type

`Optional[int]`

Parameters

`addr` (*Base*) –

static `annotate_with_def(symvar, definition)`

Parameters

- `symvar` (*BV*) –
- `definition` (*Definition*) –

Return type

BV

Returns

static `extract_defs(symvar)`

Return type

`Generator[Definition, None, None]`

Parameters

`symvar` (*Base*) –

static `extract_defs_from_annotations(annos)`

Return type

`Set[Definition]`

Parameters

`annos` (*Iterable[Annotation]*) –

static `extract_defs_from_mv(mv)`

Return type

`Generator[Definition, None, None]`

Parameters

`mv` (*MultiValues*) –

get_sp()

Return the concrete value contained by the stack pointer.

Return type

int

get_sp_offset()

Return the offset of the stack pointer.

Return type

`Optional[int]`

get_stack_address(offset)

Return type

`Optional[int]`

Parameters

`offset` (*Base*) –

stack_offset_to_stack_addr(*offset*)

Return type

`int`

merge(**others*)

Return type

`Tuple[LiveDefinitions, bool]`

Parameters

others (`LiveDefinitions`) –

compare(*other*)

Return type

`bool`

Parameters

other (`LiveDefinitions`) –

kill_definitions(*atom*)

Overwrite existing definitions w.r.t ‘atom’ with a dummy definition instance. A dummy definition will not be removed during simplification.

Parameters

atom (`Atom`) –

Return type

`None`

Returns

`None`

kill_and_add_definition(*atom*, *code_loc*, *data*, *dummy=False*, *tags=None*, *endness=None*, *annotated=False*)

Return type

`Optional[MultiValues]`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **data** (`MultiValues`) –
- **tags** (`Set[Tag]` | `None`) –

add_use(*atom*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_use_by_def(*definition*, *code_loc*, *expr*=None)

Return type

`None`

Parameters

- **definition** (`Definition`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

get_definitions(*thing*)

Return type

`Set[Definition[Atom]]`

Parameters

thing (`Atom` | `Definition[Atom]` | `Iterable[Atom]` | `Iterable[Definition[Atom]]` | `MultiValues`) –

get_tmp_definitions(*tmp_idx*)

Return type

`Set[Definition]`

Parameters

tmp_idx (`int`) –

get_register_definitions(*reg_offset*, *size*)

Return type

`Set[Definition]`

Parameters

- **reg_offset** (`int`) –
- **size** (`int`) –

get_stack_values(*stack_offset*, *size*, *endness*)

Return type

`Optional[MultiValues]`

Parameters

- **stack_offset** (`int`) –
- **size** (`int`) –
- **endness** (`str`) –

get_stack_definitions(*stack_offset*, *size*)

Return type

`Set[Definition]`

Parameters

- **stack_offset** (`int`) –
- **size** (`int`) –

`get_heap_definitions(heap_addr, size)`

Return type

`Set[Definition]`

Parameters

- `heap_addr` (`int`) –
- `size` (`int`) –

`get_memory_definitions(addr, size)`

Return type

`Set[Definition]`

Parameters

- `addr` (`int`) –
- `size` (`int`) –

`get_definitions_from_atoms(**kwargs)`

`get_value_from_definition(**kwargs)`

`get_one_value_from_definition(**kwargs)`

`get_concrete_value_from_definition(**kwargs)`

`get_value_from_atom(**kwargs)`

`get_one_value_from_atom(**kwargs)`

`get_concrete_value_from_atom(**kwargs)`

`get_values(spec)`

Return type

`Optional[MultiValues]`

Parameters

`spec` (`Atom` | `Definition[Atom]` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –

`get_one_value(spec, strip_annotations=False)`

Return type

`Optional[BV]`

Parameters

- `spec` (`Atom` | `Definition` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –
- `strip_annotations` (`bool`) –

`get_concrete_value(spec, cast_to=<class 'int'>)`

Return type

`Union[int, bytes, None]`

Parameters

- **spec** (`Atom` | `Definition[Atom]` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –
- **cast_to** (`Type[int]` | `Type[bytes]`) –

add_register_use(*reg_offset*, *size*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **reg_offset** (`int`) –
- **size** (`int`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_register_use_by_def(*def_*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **def_** (`Definition`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_stack_use(*atom*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **atom** (`MemoryLocation`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_stack_use_by_def(*def_*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **def_** (`Definition`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_heap_use(*atom*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **atom** (`MemoryLocation`) –

- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_heap_use_by_def(def_, code_loc, expr=None)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use(atom, code_loc, expr=None)`

Return type

`None`

Parameters

- `atom` (`MemoryLocation`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use_by_def(def_, code_loc, expr=None)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_tmp_use(atom, code_loc)`

Return type

`None`

Parameters

- `atom` (`Tmp`) –
- `code_loc` (`CodeLocation`) –

`add_tmp_use_by_def(def_, code_loc)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –

`deref(pointer, size, endness=Endness.BE)`

```

static is_heap_address(addr)

    Return type
    bool

    Parameters
    addr (Base) –

static get_heap_offset(addr)

    Return type
    Optional[int]

    Parameters
    addr (Base) –

heap_address(offset)

    Return type
    BV

    Parameters
    offset (int / HeapAddress) –

class angr.knowledge_plugins.key_definitions.DerefSize(value)
    Bases: Enum
    An enum for specialized kinds of dereferences

    NULL_TERMINATE - Dereference until the first byte which could be a literal null. Return a value
    including the
    terminator.

    NULL_TERMINATE = 1

class angr.knowledge_plugins.key_definitions.Uses(uses_by_definition=None,
    uses_by_location=None)

    Bases: object
    Describes uses (including the use location and the use expression) for definitions.

    Parameters
    • uses_by_definition (DefaultChainMapCOW / None) –
    • uses_by_location (DefaultChainMapCOW / None) –

    __init__(uses_by_definition=None, uses_by_location=None)

    Parameters
    • uses_by_definition (DefaultChainMapCOW / None) –
    • uses_by_location (DefaultChainMapCOW / None) –

add_use(definition, codeloc, expr=None)
    Add a use for a given definition.

    Parameters
    • definition (Definition) – The definition that is used.
    • codeloc (CodeLocation) – The code location where the use occurs.
    • expr (Optional[Any]) – The expression that uses the specified definition at this location.

```

get_uses(*definition*)

Retrieve the uses of a given definition.

Parameters

definition (*Definition*) – The definition for which we get the uses.

Return type

Set[CodeLocation]

get_uses_with_expr(*definition*)

Retrieve the uses and the corresponding expressions of a given definition.

Parameters

definition (*Definition*) – The definition for which we get the uses and the corresponding expressions.

Return type

Set[Tuple[CodeLocation, Optional[Any]]]

remove_use(*definition, codeloc, expr=None*)

Remove one use of a given definition.

Parameters

- **definition** (*Definition*) – The definition of which to remove the uses.
- **codeloc** (*CodeLocation*) – The code location where the use is.
- **expr** (*Optional[Any]*) – The expression that uses the definition at the given location.

Return type

None

Returns

None

remove_uses(*definition*)

Remove all uses of a given definition.

Parameters

definition (*Definition*) – The definition of which to remove the uses.

Returns

None

get_uses_by_location(*codeloc, exprs=False*)

Retrieve all definitions that are used at a given location.

Parameters

- **codeloc** (*CodeLocation*) – The code location.
- **exprs** (*bool*) –

Return type

Union[Set[Definition], Set[Tuple[Definition, Optional[Any]]]

Returns

A set of definitions that are used at the given location.

get_uses_by_insaddr(*ins_addr, exprs=False*)

Retrieve all definitions that are used at a given location specified by the instruction address.

Parameters

- **ins_addr** (*int*) – The instruction address.
- **exprs** (*bool*) –

Return type

`Union[Set[Definition], Set[Tuple[Definition, Optional[Any]]]]`

Returns

A set of definitions that are used at the given location.

copy()

Copy the instance.

Return type

Uses

Returns

Return a new <Uses> instance containing the same data.

merge(*other*)

Merge an instance of <Uses> into the current instance.

Parameters

other (*Uses*) – The other <Uses> from which the data will be added to the current instance.

Return type

bool

Returns

True if any merge occurred, False otherwise

class `angr.knowledge_plugins.key_definitions.Definition`(*atom*, *codeloc*, *dummy=False*, *tags=None*)

Bases: `Generic[A]`

An atom definition.

Variables

- **atom** – The atom being defined.
- **codeloc** – Where this definition is created in the original binary code.
- **dummy** – Tell whether the definition should be considered dummy or not. During simplification by AILment, definitions marked as dummy will not be removed.
- **tags** – A set of tags containing information about the definition gathered during analyses.

__init__(*atom*, *codeloc*, *dummy=False*, *tags=None*)

Parameters

- **atom** (*A*) –
- **codeloc** (*CodeLocation*) –
- **dummy** (*bool*) –
- **tags** (*Set[Tag]* | *None*) –

atom: `TypeVar(A, bound= Atom)`

codeloc: `CodeLocation`

dummy: `bool`

tags

property offset: `int`

property size: `int`

matches(***kwargs*)

Return whether this definition has certain characteristics.

Return type

`bool`

class `angr.knowledge_plugins.key_definitions.atoms.AtomKind(value)`

Bases: `Enum`

An enum indicating the class of an atom

REGISTER = 1

MEMORY = 2

TMP = 3

GUARD = 4

CONSTANT = 5

class `angr.knowledge_plugins.key_definitions.atoms.Atom(size)`

Bases: `object`

This class represents a data storage location manipulated by IR instructions.

It could either be a Tmp (temporary variable), a Register, a MemoryLocation.

__init__(*size*)

Parameters

size – The size of the atom in bytes

size

property bits: `int`

static from_ail_expr(*expr, arch, full_reg=False*)

Return type

`Register`

Parameters

- **expr** (`Expression`) –
- **arch** (`Arch`) –
- **full_reg** (`bool`) –

static from_argument(*argument, arch, full_reg=False, sp=None*)

Instantiate an *Atom* from a given argument.

Parameters

- **argument** (`SimFunctionArgument`) – The argument to create a new atom from.
- **arch** (`Arch`) – The argument representing archinfo architecture for argument.

- **full_reg** – Whether to return an atom indicating the entire register if the argument only specifies a slice of the register.
- **sp** (`Optional[int]`) – The current stack offset. Optional. Only used when argument is a `SimStackArg`.

Return type`Union[Register, MemoryLocation]`**static reg**(*thing*, *size=None*, *arch=None*)

Create a Register atom.

Parameters

- **thing** (`Union[str, RegisterOffset]`) – The register offset (e.g., `project.arch.registers["rax"][0]`) or the register name (e.g., "rax").
- **size** (`Optional[int]`) – Size of the register atom. Must be provided when creating the atom using a register offset.
- **arch** (`Optional[Arch]`) – The architecture. Must be provided when creating the atom using a register name.

Return type`Register`**Returns**

The Register Atom object.

static register(*thing*, *size=None*, *arch=None*)

Create a Register atom.

Parameters

- **thing** (`Union[str, RegisterOffset]`) – The register offset (e.g., `project.arch.registers["rax"][0]`) or the register name (e.g., "rax").
- **size** (`Optional[int]`) – Size of the register atom. Must be provided when creating the atom using a register offset.
- **arch** (`Optional[Arch]`) – The architecture. Must be provided when creating the atom using a register name.

Return type`Register`**Returns**

The Register Atom object.

static mem(*addr*, *size*, *endness=None*)

Create a MemoryLocation atom,

Parameters

- **addr** (`Union[SpOffset, HeapAddress, int]`) – The memory location. Can be an `SpOffset` for stack variables, an `int` for global memory variables, or a `HeapAddress` for items on the heap.
- **size** (`int`) – Size of the atom.
- **endness** (`Optional[str]`) – Optional, either "Iend_LE" or "Iend_BE".

Return type`MemoryLocation`

Returns

The MemoryLocation Atom object.

static memory(*addr*, *size*, *endness=None*)

Create a MemoryLocation atom,

Parameters

- **addr** (`Union[SpOffset, HeapAddress, int]`) – The memory location. Can be an SpOffset for stack variables, an int for global memory variables, or a HeapAddress for items on the heap.
- **size** (`int`) – Size of the atom.
- **endness** (`Optional[str]`) – Optional, either “lend_LE” or “lend_BE”.

Return type

`MemoryLocation`

Returns

The MemoryLocation Atom object.

class `angr.knowledge_plugins.key_definitions.atoms.GuardUse`(*target*)

Bases: `Atom`

Implements a guard use.

__init__(*target*)

Parameters

size – The size of the atom in bytes

target

class `angr.knowledge_plugins.key_definitions.atoms.ConstantSrc`(*value*, *size*)

Bases: `Atom`

Represents a constant.

Parameters

- **value** (`int`) –
- **size** (`int`) –

__init__(*value*, *size*)

Parameters

- **size** (`int`) – The size of the atom in bytes
- **value** (`int`) –

value: `int`

class `angr.knowledge_plugins.key_definitions.atoms.Tmp`(*tmp_idx*, *size*)

Bases: `Atom`

Represents a variable used by the IR to store intermediate values.

Parameters

- **tmp_idx** (`int`) –
- **size** (`int`) –

```
__init__(tmp_idx, size)
```

Parameters

- **size** (*int*) – The size of the atom in bytes
- **tmp_idx** (*int*) –

```
tmp_idx
```

```
class angr.knowledge_plugins.key_definitions.atoms.Register(reg_offset, size, arch=None)
```

Bases: *Atom*

Represents a given CPU register.

As an IR abstracts the CPU design to target different architectures, registers are represented as a separated memory space. Thus a register is defined by its offset from the base of this memory and its size.

Variables

- **reg_offset** (*int*) – The offset from the base to define its place in the memory bloc.
- **size** (*int*) – The size, in number of bytes.

Parameters

- **reg_offset** (*RegisterOffset*) –
- **size** (*int*) –
- **arch** (*Arch* | *None*) –

```
__init__(reg_offset, size, arch=None)
```

Parameters

- **size** (*int*) – The size of the atom in bytes
- **reg_offset** (*RegisterOffset*) –
- **arch** (*Arch* | *None*) –

```
reg_offset
```

```
arch
```

```
property name: str
```

```
class angr.knowledge_plugins.key_definitions.atoms.MemoryLocation(addr, size, endness=None)
```

Bases: *Atom*

Represents a memory slice.

It is characterized by its address and its size.

Parameters

- **addr** (*SpOffset* | *HeapAddress* | *int*) –
- **size** (*int*) –
- **endness** (*str* | *None*) –

```
__init__(addr, size, endness=None)
```

Parameters

- **addr** (*int*) – The address of the beginning memory location slice.
- **size** (*int*) – The size of the represented memory location, in bytes.
- **endness** (*str* / *None*) –

```
addr: Union[SpOffset, int, BV]
```

```
endness
```

```
property is_on_stack: bool
```

True if this memory location is located on the stack.

```
property symbolic: bool
```

```
class angr.knowledge_plugins.key_definitions.constants.ObservationPointType(value)
```

Bases: *IntEnum*

Enum to replace the previously generic constants This makes it possible to annotate where they are expected by typing something as *ObservationPointType* instead of *Literal[0,1]*

```
OP_BEFORE = 0
```

```
OP_AFTER = 1
```

```
class angr.knowledge_plugins.key_definitions.definition.DefinitionMatchPredicate(kind=None,
                                                                              bbl_addr=None,
                                                                              ins_addr=None,
                                                                              variable=None,
                                                                              variable_manager=None,
                                                                              stack_offset=None,
                                                                              reg_name=None,
                                                                              heap_offset=None,
                                                                              global_addr=None,
                                                                              tmp_idx=None,
                                                                              const_val=None,
                                                                              extern=None)
```

Bases: *object*

A dataclass indicating several facts which much all must match in order for a definition to match. Largely an internal class; don't worry about this.

Parameters

- **kind** (*AtomKind* / *Type[Atom]* / *None*) –
- **bbl_addr** (*int* / *None*) –
- **ins_addr** (*int* / *None*) –
- **variable** (*SimVariable* / *None*) –
- **variable_manager** (*VariableManagerInternal* / *None* / *Literal[False]*) –
- **stack_offset** (*int* / *None*) –

```

    • reg_name(str | int | None) –
    • heap_offset(int | None) –
    • global_addr(int | None) –
    • tmp_idx(int | None) –
    • const_val(int | None) –
    • extern(bool | None) –
kind: Union[AtomKind, Type[Atom], None] = None
bbl_addr: Optional[int] = None
ins_addr: Optional[int] = None
variable: Optional[SimVariable] = None
variable_manager: Union[VariableManagerInternal, None, Literal[False]] = None
stack_offset: Optional[int] = None
reg_name: Union[str, int, None] = None
heap_offset: Optional[int] = None
global_addr: Optional[int] = None
tmp_idx: Optional[int] = None
const_val: Optional[int] = None
extern: Optional[bool] = None
static construct(predicate=None, **kwargs)

    Return type
        DefinitionMatchPredicate

    Parameters
        predicate (DefinitionMatchPredicate | None) –

normalize()

matches(defn)

    Return type
        bool

    Parameters
        defn (Definition) –

__init__(kind=None, bbl_addr=None, ins_addr=None, variable=None, variable_manager=None,
        stack_offset=None, reg_name=None, heap_offset=None, global_addr=None, tmp_idx=None,
        const_val=None, extern=None)

    Parameters
        • kind (AtomKind | Type[Atom] | None) –
        • bbl_addr (int | None) –
        • ins_addr (int | None) –

```

- **variable** (`SimVariable` | `None`) –
- **variable_manager** (`VariableManagerInternal` | `None` | `Literal[False]`) –
- **stack_offset** (`int` | `None`) –
- **reg_name** (`str` | `int` | `None`) –
- **heap_offset** (`int` | `None`) –
- **global_addr** (`int` | `None`) –
- **tmp_idx** (`int` | `None`) –
- **const_val** (`int` | `None`) –
- **extern** (`bool` | `None`) –

Return type

`None`

```
class angr.knowledge_plugins.key_definitions.definition.Definition(atom, codeloc,
                                                                dummy=False, tags=None)
```

Bases: `Generic[A]`

An atom definition.

Variables

- **atom** – The atom being defined.
- **codeloc** – Where this definition is created in the original binary code.
- **dummy** – Tell whether the definition should be considered dummy or not. During simplification by AILment, definitions marked as dummy will not be removed.
- **tags** – A set of tags containing information about the definition gathered during analyses.

```
__init__(atom, codeloc, dummy=False, tags=None)
```

Parameters

- **atom** (`A`) –
- **codeloc** (`CodeLocation`) –
- **dummy** (`bool`) –
- **tags** (`Set[Tag]` | `None`) –

```
atom: TypeVar(A, bound=Atom)
```

```
codeloc: CodeLocation
```

```
dummy: bool
```

```
tags
```

```
property offset: int
```

```
property size: int
```

```
matches(**kwargs)
```

Return whether this definition has certain characteristics.

Return type

`bool`


```
class angr.knowledge_plugins.key_definitions.environment.Environment(environment=None)
```

Bases: `object`

Represent the environment in which a program runs. It's a mapping of variable names, to *claripy.ast.Base* that should contain possible addresses, or <UNDEFINED>, at which their respective values are stored.

Note: The <Environment> object does not store the values associated with variables themselves.

Parameters

environment (`Dict[str | Undefined, Set[Base]]`) –

__init__(environment=None)

Parameters

environment (`Dict[str | Undefined, Set[Base]] | None`) –

get(names)

Parameters

names (`Set[str]`) – Potential values for the name of the environment variable to get the pointers of.

Return type

`Tuple[Set[Base], bool]`

Returns

The potential addresses of the values the environment variable can take; And a boolean value telling whether all the names were known of the internal representation (i.e. will be False if one of the queried variable was not found).

set(name, pointers)

Parameters

- **name** (`Union[str, Undefined]`) – Name of the environment variable to which we will associate the pointers.
- **pointers** (`Set[Base]`) – New addresses where the new values of the environment variable are located.

merge(*others)

Return type

`Tuple[Environment, bool]`

Parameters

others (`Environment`) –

compare(other)

Return type

`bool`

Parameters

other (`Environment`) –

```
class angr.knowledge_plugins.key_definitions.heap_address.HeapAddress(value)
```

Bases: `object`

The representation of an address on the heap.

Parameters

value (`int | Undefined`) –

`__init__(value)`

Parameters

`value` (`int` / `Undefined`) –

property value

`class angr.knowledge_plugins.key_definitions.key_definition_manager.RDAObserverControl(func_addr, call_site_block_addr, call_site_ins_addrs)`

Bases: `object`

Parameters

- `func_addr` (`int`) –
- `call_site_block_addrs` (`Iterable[int]`) –
- `call_site_ins_addrs` (`Iterable[int]`) –

`__init__(func_addr, call_site_block_addrs, call_site_ins_addrs)`

Parameters

- `func_addr` (`int`) –
- `call_site_block_addrs` (`Iterable[int]`) –
- `call_site_ins_addrs` (`Iterable[int]`) –

`rda_observe_callback(ob_type, **kwargs)`

`class angr.knowledge_plugins.key_definitions.key_definition_manager.KeyDefinitionManager(kb)`

Bases: `KnowledgeBasePlugin`

KeyDefinitionManager manages and caches reaching definition models for each function.

For each function, by default we cache the entire reaching definitions model with observed results at the following locations: - Before each call instruction: ('insn', address of the call instruction, OP_BEFORE) - After returning from each call: ('node', address of the block that ends with a call, OP_AFTER)

Parameters

`kb` (`KnowledgeBase`) –

`__init__(kb)`

Parameters

`kb` (`KnowledgeBase`) –

`has_model(func_addr)`

Parameters

`func_addr` (`int`) –

`get_model(func_addr)`

Parameters

`func_addr` (`int`) –

`copy()`

Return type

`KeyDefinitionManager`

```
class angr.knowledge_plugins.key_definitions.live_definitions.DerefSize(value)
```

Bases: `Enum`

An enum for specialized kinds of dereferences

NULL_TERMINATE - Dereference until the first byte which could be a literal null. Return a value including the terminator.

NULL_TERMINATE = 1

```
class angr.knowledge_plugins.key_definitions.live_definitions.DefinitionAnnotation(definition)
```

Bases: `Annotation`

An annotation that attaches a *Definition* to an AST.

__init__(*definition*)

definition

property relocatable

Returns whether this annotation can be relocated in a simplification.

Returns

True if it can be relocated, false otherwise.

property eliminatable

Returns whether this annotation can be eliminated in a simplification.

Returns

True if eliminatable, False otherwise

```
class angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions(arch,
                                                                              track_tmps=False,
                                                                              canoni-
                                                                              cal_size=8,
                                                                              regis-
                                                                              ters=None,
                                                                              stack=None,
                                                                              mem-
                                                                              ory=None,
                                                                              heap=None,
                                                                              tmpls=None,
                                                                              others=None,
                                                                              regis-
                                                                              ter_uses=None,
                                                                              stack_uses=None,
                                                                              heap_uses=None,
                                                                              mem-
                                                                              ory_uses=None,
                                                                              tmp_uses=None,
                                                                              other_uses=None,
                                                                              ele-
                                                                              ment_limit=5)
```

Bases: `object`

A LiveDefinitions instance contains definitions and uses for register, stack, memory, and temporary variables, uncovered during the analysis.

Parameters

- **arch** (*Arch*) –
- **track_tmps** (*bool*) –
- **registers** (*MultiValuedMemory*) –
- **stack** (*MultiValuedMemory*) –
- **memory** (*MultiValuedMemory*) –
- **heap** (*MultiValuedMemory*) –
- **tmpls** (*Dict[int, Set[Definition]]*) –
- **others** (*Dict[Atom, MultiValues]*) –
- **tmp_uses** (*Dict[int, Set[CodeLocation]]*) –

INITIAL_SP_32BIT = 2147418112

INITIAL_SP_64BIT = 140737488289792

`__init__(arch, track_tmpls=False, canonical_size=8, registers=None, stack=None, memory=None, heap=None, tmpls=None, others=None, register_uses=None, stack_uses=None, heap_uses=None, memory_uses=None, tmp_uses=None, other_uses=None, element_limit=5)`

Parameters

- **arch** (*Arch*) –
- **track_tmpls** (*bool*) –

project: *Optional[Project]*

arch

track_tmpls

registers: *MultiValuedMemory*

stack: *MultiValuedMemory*

memory: *MultiValuedMemory*

heap: *MultiValuedMemory*

tmpls: *Dict[int, Set[Definition]]*

others: *Dict[Atom, MultiValues]*

register_uses

stack_uses

heap_uses

memory_uses

tmp_uses: *Dict[int, Set[CodeLocation]]*

other_uses

`uses_by_codeloc: Dict[CodeLocation, Set[Definition]]`

`property register_definitions`

`property stack_definitions`

`property memory_definitions`

`property heap_definitions`

`copy(discard_tmpdefs=False)`

Return type

`LiveDefinitions`

`reset_uses()`

static `top(bits)`

Get a TOP value.

Parameters

bits (`int`) – Width of the TOP value (in bits).

Returns

The TOP value.

static `is_top(expr)`

Check if the given expression is a TOP value.

Parameters

expr – The given expression.

Return type

`bool`

Returns

True if the expression is TOP, False otherwise.

`stack_address(offset)`

Return type

`Optional[BV]`

Parameters

offset (`int`) –

static `is_stack_address(addr)`

Return type

`bool`

Parameters

addr (`Base`) –

static `get_stack_offset(addr, had_stack_base=False)`

Return type

`Optional[int]`

Parameters

addr (`Base`) –

static `annotate_with_def`(*symvar*, *definition*)

Parameters

- **symvar** (*BV*) –
- **definition** (*Definition*) –

Return type

BV

Returns

static `extract_defs`(*symvar*)

Return type

Generator[*Definition*, *None*, *None*]

Parameters

symvar (*Base*) –

static `extract_defs_from_annotations`(*annos*)

Return type

Set[*Definition*]

Parameters

annos (*Iterable*[*Annotation*]) –

static `extract_defs_from_mv`(*mv*)

Return type

Generator[*Definition*, *None*, *None*]

Parameters

mv (*MultiValues*) –

`get_sp`()

Return the concrete value contained by the stack pointer.

Return type

int

`get_sp_offset`()

Return the offset of the stack pointer.

Return type

Optional[*int*]

`get_stack_address`(*offset*)

Return type

Optional[*int*]

Parameters

offset (*Base*) –

`stack_offset_to_stack_addr`(*offset*)

Return type

int

merge(*others)

Return type

`Tuple[LiveDefinitions, bool]`

Parameters

others (`LiveDefinitions`) –

compare(other)

Return type

`bool`

Parameters

other (`LiveDefinitions`) –

kill_definitions(atom)

Overwrite existing definitions w.r.t ‘atom’ with a dummy definition instance. A dummy definition will not be removed during simplification.

Parameters

atom (`Atom`) –

Return type

`None`

Returns

`None`

kill_and_add_definition(atom, code_loc, data, dummy=False, tags=None, endness=None, annotated=False)

Return type

`Optional[MultiValues]`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **data** (`MultiValues`) –
- **tags** (`Set[Tag]` | `None`) –

add_use(atom, code_loc, expr=None)

Return type

`None`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_use_by_def(definition, code_loc, expr=None)

Return type

`None`

Parameters

- **definition** (*Definition*) –
- **code_loc** (*CodeLocation*) –
- **expr** (*Any* | *None*) –

get_definitions(*thing*)

Return type

Set[Definition[Atom]]

Parameters

thing (*Atom* | *Definition[Atom]* | *Iterable[Atom]* | *Iterable[Definition[Atom]]* | *MultiValues*) –

get_tmp_definitions(*tmp_idx*)

Return type

Set[Definition]

Parameters

tmp_idx (*int*) –

get_register_definitions(*reg_offset, size*)

Return type

Set[Definition]

Parameters

- **reg_offset** (*int*) –
- **size** (*int*) –

get_stack_values(*stack_offset, size, endness*)

Return type

Optional[MultiValues]

Parameters

- **stack_offset** (*int*) –
- **size** (*int*) –
- **endness** (*str*) –

get_stack_definitions(*stack_offset, size*)

Return type

Set[Definition]

Parameters

- **stack_offset** (*int*) –
- **size** (*int*) –

get_heap_definitions(*heap_addr, size*)

Return type

Set[Definition]

Parameters

- **heap_addr** (*int*) –

- `size(int)` –

`get_memory_definitions(addr, size)`

Return type
`Set[Definition]`

Parameters

- `addr(int)` –
- `size(int)` –

`get_definitions_from_atoms(**kwargs)`

`get_value_from_definition(**kwargs)`

`get_one_value_from_definition(**kwargs)`

`get_concrete_value_from_definition(**kwargs)`

`get_value_from_atom(**kwargs)`

`get_one_value_from_atom(**kwargs)`

`get_concrete_value_from_atom(**kwargs)`

`get_values(spec)`

Return type
`Optional[MultiValues]`

Parameters

`spec` (`Atom` | `Definition[Atom]` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –

`get_one_value(spec, strip_annotations=False)`

Return type
`Optional[BV]`

Parameters

- `spec` (`Atom` | `Definition` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –
- `strip_annotations(bool)` –

`get_concrete_value(spec, cast_to=<class 'int'>)`

Return type
`Union[int, bytes, None]`

Parameters

- `spec` (`Atom` | `Definition[Atom]` | `Iterable[Atom]` | `Iterable[Definition[Atom]]`) –
- `cast_to` (`Type[int]` | `Type[bytes]`) –

`add_register_use(reg_offset, size, code_loc, expr=None)`

Return type
`None`

Parameters

- `reg_offset` (*int*) –
- `size` (*int*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_register_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (*Definition*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_stack_use(atom, code_loc, expr=None)`

Return type

None

Parameters

- `atom` (*MemoryLocation*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_stack_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (*Definition*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_heap_use(atom, code_loc, expr=None)`

Return type

None

Parameters

- `atom` (*MemoryLocation*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_heap_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use(atom, code_loc, expr=None)`

Return type

`None`

Parameters

- `atom` (`MemoryLocation`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use_by_def(def_, code_loc, expr=None)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_tmp_use(atom, code_loc)`

Return type

`None`

Parameters

- `atom` (`Tmp`) –
- `code_loc` (`CodeLocation`) –

`add_tmp_use_by_def(def_, code_loc)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –

`deref(pointer, size, endness=Endness.BE)`

`static is_heap_address(addr)`

Return type

`bool`

Parameters

`addr` (`Base`) –

static `get_heap_offset(addr)`

Return type
`Optional[int]`

Parameters
`addr` (*Base*) –

heap_address(offset)

Return type
`BV`

Parameters
`offset` (*int* / *HeapAddress*) –

class `angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel` (*func_addr=None*,
track_liveness=True)

Bases: `object`

Models the definitions, uses, and memory of a `ReachingDefinitionState` object

Parameters

- `func_addr` (*int* / *None*) –
- `track_liveness` (*bool*) –

__init__ (*func_addr=None*, *track_liveness=True*)

Parameters

- `func_addr` (*int* / *None*) –
- `track_liveness` (*bool*) –

add_def(d)

Return type
`None`

Parameters
`d` (*Definition*) –

kill_def(d)

Return type
`None`

Parameters
`d` (*Definition*) –

at_new_stmt(codeloc)

Return type
`None`

Parameters
`codeloc` (*CodeLocation*) –

at_new_block(code_loc, pred_codelocs)

Return type
`None`

Parameters

- `code_loc` (`CodeLocation`) –
- `pred_codelocs` (`List[CodeLocation]`) –

`make_liveness_snapshot()`

Return type

`None`

`find_defs_at(code_loc, op=ObservationPointType.OP_BEFORE)`

Return type

`Set[Definition]`

Parameters

- `code_loc` (`CodeLocation`) –
- `op` (`int`) –

`get_defs(atom, code_loc, op)`

Return type

`Set[Definition]`

Parameters

- `atom` (`Atom`) –
- `code_loc` (`CodeLocation`) –
- `op` (`int`) –

`copy()`

Return type

`ReachingDefinitionsModel`

`merge(model)`

Parameters

`model` (`ReachingDefinitionsModel`) –

`get_observation_by_insn(ins_addr, kind)`

Return type

`Optional[LiveDefinitions]`

Parameters

- `ins_addr` (`int` | `CodeLocation`) –
- `kind` (`ObservationPointType`) –

`get_observation_by_node(node_addr, kind, node_idx=None)`

Return type

`Optional[LiveDefinitions]`

Parameters

- `node_addr` (`int` | `CodeLocation`) –
- `kind` (`ObservationPointType`) –

- `node_idx` (`int` | `None`) –

`get_observation_by_stmt`(`arg1`, `arg2`, `arg3=None`, *, `block_idx=None`)

`get_observation_by_exit`(`node_addr`, `stmt_idx`, `src_node_idx=None`)

Return type

`Optional[LiveDefinitions]`

Parameters

- `node_addr` (`int`) –
- `stmt_idx` (`int`) –
- `src_node_idx` (`int` | `None`) –

Classes to structure the different types of <Tag>s that can be attached to <Definition>s.

- **Tag**

- **FunctionTag**

- * `ParameterTag`
- * `LocalVariableTag`
- * `ReturnValueTag`

- `InitialValueTag`

`class` `angr.knowledge_plugins.key_definitions.tag.Tag`(`metadata=None`)

Bases: `object`

A tag for a Definition that can carry different kinds of metadata.

Parameters

`metadata` (`object`) –

`__init__`(`metadata=None`)

Parameters

`metadata` (`object` | `None`) –

`class` `angr.knowledge_plugins.key_definitions.tag.FunctionTag`(`function=None`, `metadata=None`)

Bases: `Tag`

A tag for a definition created (or used) in the context of a function.

Parameters

- `function` (`int`) –
- `metadata` (`object`) –

`__init__`(`function=None`, `metadata=None`)

Parameters

- `function` (`int` | `None`) –
- `metadata` (`object` | `None`) –

```
class angr.knowledge_plugins.key_definitions.tag.SideEffectTag(function=None, metadata=None)
```

Bases: [FunctionTag](#)

A tag for a definition created or used as a side-effect of a function.

Example: The <MemoryLocation> pointed by *rdi* during a *sprintf*.

Parameters

- **function** (*int*) –
- **metadata** (*object*) –

```
class angr.knowledge_plugins.key_definitions.tag.ParameterTag(function=None, metadata=None)
```

Bases: [FunctionTag](#)

A tag for a definition of a parameter.

Parameters

- **function** (*int*) –
- **metadata** (*object*) –

```
class angr.knowledge_plugins.key_definitions.tag.LocalVariableTag(function=None,
                                                                metadata=None)
```

Bases: [FunctionTag](#)

A tag for a definition of a local variable of a function.

Parameters

- **function** (*int*) –
- **metadata** (*object*) –

```
class angr.knowledge_plugins.key_definitions.tag.ReturnValueTag(function=None,
                                                                metadata=None)
```

Bases: [FunctionTag](#)

A tag for a definition of a return value of a function.

Parameters

- **function** (*int*) –
- **metadata** (*object*) –

```
class angr.knowledge_plugins.key_definitions.tag.InitialValueTag(metadata=None)
```

Bases: [Tag](#)

A tag for a definition of an initial value

Parameters

- metadata** (*object*) –

```
class angr.knowledge_plugins.key_definitions.tag.UnknownSizeTag(metadata=None)
```

Bases: [Tag](#)

A tag for a definition of an initial value

Parameters

- metadata** (*object*) –

class `angr.knowledge_plugins.key_definitions.undefined.Undefined`

Bases: `object`

A TOP-like value indicating an unknown data source. Should live next to raw integers in DataSets.

class `angr.knowledge_plugins.key_definitions.unknown_size.UnknownSize`

Bases: `object`

A value indicating an unknown size for elements of DataSets. Should “behave” like an integer.

class `angr.knowledge_plugins.key_definitions.uses.Uses`(*uses_by_definition=None*,
uses_by_location=None)

Bases: `object`

Describes uses (including the use location and the use expression) for definitions.

Parameters

- **uses_by_definition** (`DefaultChainMapCOW` / `None`) –
- **uses_by_location** (`DefaultChainMapCOW` / `None`) –

__init__(*uses_by_definition=None*, *uses_by_location=None*)

Parameters

- **uses_by_definition** (`DefaultChainMapCOW` / `None`) –
- **uses_by_location** (`DefaultChainMapCOW` / `None`) –

add_use(*definition*, *codeloc*, *expr=None*)

Add a use for a given definition.

Parameters

- **definition** (`Definition`) – The definition that is used.
- **codeloc** (`CodeLocation`) – The code location where the use occurs.
- **expr** (`Optional[Any]`) – The expression that uses the specified definition at this location.

get_uses(*definition*)

Retrieve the uses of a given definition.

Parameters

- **definition** (`Definition`) – The definition for which we get the uses.

Return type

`Set[CodeLocation]`

get_uses_with_expr(*definition*)

Retrieve the uses and the corresponding expressions of a given definition.

Parameters

- **definition** (`Definition`) – The definition for which we get the uses and the corresponding expressions.

Return type

`Set[Tuple[CodeLocation, Optional[Any]]]`

remove_use(*definition*, *codeloc*, *expr=None*)

Remove one use of a given definition.

Parameters

- **definition** (*Definition*) – The definition of which to remove the uses.
- **codeloc** (*CodeLocation*) – The code location where the use is.
- **expr** (*Optional[Any]*) – The expression that uses the definition at the given location.

Return type

None

Returns

None

remove_uses(*definition*)

Remove all uses of a given definition.

Parameters

definition (*Definition*) – The definition of which to remove the uses.

Returns

None

get_uses_by_location(*codeloc*, *exprs=False*)

Retrieve all definitions that are used at a given location.

Parameters

- **codeloc** (*CodeLocation*) – The code location.
- **exprs** (*bool*) –

Return type

Union[Set[Definition], Set[Tuple[Definition, Optional[Any]]]]

Returns

A set of definitions that are used at the given location.

get_uses_by_insaddr(*ins_addr*, *exprs=False*)

Retrieve all definitions that are used at a given location specified by the instruction address.

Parameters

- **ins_addr** (*int*) – The instruction address.
- **exprs** (*bool*) –

Return type

Union[Set[Definition], Set[Tuple[Definition, Optional[Any]]]]

Returns

A set of definitions that are used at the given location.

copy()

Copy the instance.

Return type

Uses

Returns

Return a new <Uses> instance containing the same data.

merge(*other*)

Merge an instance of <Uses> into the current instance.

Parameters

other (*Uses*) – The other <Uses> from which the data will be added to the current instance.

Return type

`bool`

Returns

True if any merge occurred, False otherwise

`angr.knowledge_plugins.sync.sync_controller.import_binsync()`

`angr.knowledge_plugins.sync.sync_controller.make_state(f)`

Build a writeable State instance and pass to *f* as the *state* kwarg if the *state* kwarg is None. Function *f* should have at least two kwargs, *user* and *state*.

`angr.knowledge_plugins.sync.sync_controller.make_ro_state(f)`

Build a read-only State instance and pass to *f* as the *state* kwarg if the *state* kwarg is None. Function *f* should have at least two kwargs, *user* and *state*.

`angr.knowledge_plugins.sync.sync_controller.init_checker(f)`

class `angr.knowledge_plugins.sync.sync_controller.SyncController(kb)`

Bases: `KnowledgeBasePlugin`

SyncController interfaces with a binsync client to push changes upwards and pull changes downwards.

Variables

client (`binsync.Client`) – The binsync client.

__init__ (*kb*)

connect (*user*, *path*, *bin_hash*="", *init_repo*=False, *ssh_agent_pid*=None, *ssh_auth_sock*=None, *remote_url*=None)

property `connected`

commit ()

update ()

copy ()

pull ()

property `has_remote`

users ()

status ()

tally (*users*=None)

push_function (*func*, *user*=None, *state*=None)

Push a function upwards.

Parameters

func (`Function`) – The angr Function object to push upwards.

Returns

True if updates are made. False otherwise.

Return type

`bool`

push_comment(*addr*, *comment*, *decompiled=False*, *user=None*, *state=None*)

push_comments(*comments*, *user=None*, *state=None*)

Push a bunch of comments upwards.

Parameters

comments (*list*) – A list of BinSync Comments

Returns

bool

push_stack_variables(*stack_variables*, *var_manager*, *user=None*, *state=None*)

Parameters

- **stack_variables** (*List[SimStackVariable]*) –
- **var_manager** (*VariableManagerInternal*) –

Returns

push_stack_variable(*func_addr*, *offset*, *name*, *type_*, *size_*, *user=None*, *state=None*)

pull_function(*addr*, *user=None*, *state=None*)

Pull a function downwards.

Parameters

- **addr** (*int*) – Address of the function.
- **user** (*str*) – Name of the user.

Returns

The binsync.data.Function object if pulling succeeds, or None if pulling fails.

Return type

binsync.data.Function | None

pull_comment(*addr*, *user=None*, *state=None*)

Pull a comment downwards.

Parameters

- **addr** (*int*) – Address of the comment.
- **user** (*str*) – Name of the user.

Returns

a Comment object from BinSync, or None

Return type

binsync.data.Comment | None

pull_comments(*func_addr*, *user=None*, *state=None*)

Pull comments downwards.

Parameters

- **start_addr** (*int*) – Where we want to pull comments.
- **end_addr** (*int*) – Where we want to stop pulling comments (exclusive).

Returns

An iterator.

Return type

Iterable

pull_patches(*user=None, state=None*)

Pull patches.

Parameters

user (*str*) – Name of the user to patches from.

Returns

An iterator

Return type

Iterable

pull_stack_variables(*func_addr, user=None, state=None*)

Pull stack variables from a function.

@param func_addr: Function address to pull from @param user: @param state: @return:

get_func_addr_from_addr(*addr*)

```
class angr.knowledge_plugins.xrefs.xref.XRef(ins_addr=None, block_addr=None, stmt_idx=None,
                                             insn_op_idx=None, memory_data=None, dst=None,
                                             xref_type=None)
```

Bases: [Serializable](#)

XRef describes a reference to a MemoryData instance (if a MemoryData instance is available) or just an address.

Parameters

- **ins_addr** (*int* | *None*) –
- **block_addr** (*int* | *None*) –
- **stmt_idx** (*int* | *None*) –
- **insn_op_idx** (*int* | *None*) –
- **dst** (*int* | *None*) –

```
__init__(ins_addr=None, block_addr=None, stmt_idx=None, insn_op_idx=None, memory_data=None,
         dst=None, xref_type=None)
```

Parameters

- **ins_addr** (*int* | *None*) –
- **block_addr** (*int* | *None*) –
- **stmt_idx** (*int* | *None*) –
- **insn_op_idx** (*int* | *None*) –
- **dst** (*int* | *None*) –

ins_addr: [Optional](#)[*int*]

insn_op_idx: [Optional](#)[*int*]

block_addr: [Optional](#)[*int*]

stmt_idx: [Optional](#)[*int*]

memory_data

type

dst

property type_string

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

protobuf.cmessage

classmethod parse_from_cmessage(*cmsg*, *bits=None*, ***kwargs*)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

copy()

insn_op_type

class `angr.knowledge_plugins.xrefs.xref_types.XRefType`

Bases: `object`

Offset = 0

Read = 1

Write = 2

static to_string(*ty*)

class `angr.knowledge_plugins.xrefs.xref_manager.XRefManager`(*kb*)

Bases: `KnowledgeBasePlugin`, `Serializable`

__init__(*kb*)

copy()

add_xref(*xref*)

add_xrefs(*xrefs*)

get_xrefs_by_ins_addr(*ins_addr*)

get_xrefs_by_dst(*dst*)

get_xrefs_by_dst_region(*start*, *end*)

Get a set of XRef objects that point to a given address region bounded by start and end. Will only return absolute xrefs, not relative ones (like SP offsets)

get_xrefs_by_ins_addr_region(*start*, *end*)

Get a set of XRef objects that originate at a given address region bounded by start and end. Useful for finding references from a basic block or function.

Return type

`Set[XRef]`

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

`protobuf.cmessage`

classmethod parse_from_cmessage(*cmsg*, *cfg_model=None*, *kb=None*, ***kwargs*)

Parse a protobuf cmessage and create a class object.

Parameters

cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

`cls`

class `angr.code_location.CodeLocation`(*block_addr*, *stmt_idx*, *sim_procedure=None*, *ins_addr=None*, *context=None*, *block_idx=None*, ***kwargs*)

Bases: `object`

Stands for a specific program point by specifying basic block address and statement ID (for IRSBs), or SimProcedure name (for SimProcedures).

Parameters

- **block_addr** (`int`) –
- **stmt_idx** (`int` | `None`) –
- **ins_addr** (`int` | `None`) –
- **context** (`Any`) –
- **block_idx** (`int`) –

__init__(*block_addr*, *stmt_idx*, *sim_procedure=None*, *ins_addr=None*, *context=None*, *block_idx=None*, ***kwargs*)

Constructor.

Parameters

- **block_addr** (`int`) – Address of the block
- **stmt_idx** (`Optional[int]`) – Statement ID. None for SimProcedures or if the code location is meant to refer to the entire block.
- **sim_procedure** (`class`) – The corresponding SimProcedure class.

- **ins_addr** (`Optional[int]`) – The instruction address.
- **context** (`Optional[Any]`) – A tuple that represents the context of this `CodeLocation` in contextful mode, or `None` in contextless mode.
- **kwargs** – Optional arguments, will be stored, but not used in `__eq__` or `__hash__`.
- **block_idx** (`int` | `None`) –

block_addr: `int`

stmt_idx: `Optional[int]`

sim_procedure

ins_addr: `Optional[int]`

context: `Optional[Tuple[int]]`

block_idx

info: `Optional[Dict]`

property short_repr

class `angr.code_location.ExternalCodeLocation`(*call_string=None*)

Bases: `CodeLocation`

Stands for a program point that originates from outside an analysis' scope. i.e. a value loaded from rdi in a callee where the caller has not been analyzed.

Parameters

call_string (`Tuple[int, ...]` | `None`) –

__init__(*call_string=None*)

Constructor.

Parameters

- **block_addr** – Address of the block
- **stmt_idx** – Statement ID. `None` for `SimProcedures` or if the code location is meant to refer to the entire block.
- **sim_procedure** (*class*) – The corresponding `SimProcedure` class.
- **ins_addr** – The instruction address.
- **context** – A tuple that represents the context of this `CodeLocation` in contextful mode, or `None` in contextless mode.
- **kwargs** – Optional arguments, will be stored, but not used in `__eq__` or `__hash__`.
- **call_string** (`Tuple[int, ...]` | `None`) –

call_string

class `angr.keyed_region.StoredObject`(*start, obj, size*)

Bases: `object`

__init__(*start, obj, size*)

start

obj

size: `Union[UnknownSize, int]`

property obj_id

class `angr.keyed_region.RegionObject`(*start, size, objects=None*)

Bases: `object`

Represents one or more objects occupying one or more bytes in KeyedRegion.

__init__(*start, size, objects=None*)

start

size

stored_objects

property is_empty

property end

property internal_objects

includes(*offset*)

split(*split_at*)

add_object(*obj*)

set_object(*obj*)

copy()

class `angr.keyed_region.KeyedRegion`(*tree=None, phi_node_contains=None, canonical_size=8*)

Bases: `object`

KeyedRegion keeps a mapping between stack offsets and all objects covering that offset. It assumes no variable in this region overlap with another variable in this region.

Registers and function frames can all be viewed as a keyed region.

__init__(*tree=None, phi_node_contains=None, canonical_size=8*)

copy()

merge(*other, replacements=None*)

Merge another KeyedRegion into this KeyedRegion.

Parameters

other (`KeyedRegion`) – The other instance to merge with.

Returns

None

merge_to_top(*other, replacements=None, top=None*)

Merge another KeyedRegion into this KeyedRegion, but mark all variables with different values as TOP.

Parameters

- **other** – The other instance to merge with.

- **replacements** –

Returns

self

replace(*replacements*)

Replace variables with other variables.

Parameters

replacements (*dict*) – A dict of variable replacements.

Returns

self

dbg_repr()

Get a debugging representation of this keyed region. :return: A string of debugging output.

add_variable(*start*, *variable*)

Add a variable to this region at the given offset.

Parameters

- **start** (*int*) –
- **variable** (*SimVariable*) –

Returns

None

add_object(*start*, *obj*, *object_size*)

Add/Store an object to this region at the given offset.

Parameters

- **start** –
- **obj** –
- **object_size** (*int*) – Size of the object

Returns

set_variable(*start*, *variable*)

Add a variable to this region at the given offset, and remove all other variables that are fully covered by this variable.

Parameters

- **start** (*int*) –
- **variable** (*SimVariable*) –

Returns

None

set_object(*start*, *obj*, *object_size*)

Add an object to this region at the given offset, and remove all other objects that are fully covered by this object.

Parameters

- **start** –
- **obj** –
- **object_size** –

Returns

get_base_addr(*addr*)

Get the base offset (the key we are using to index objects covering the given offset) of a specific offset.

Parameters

addr (*int*) –

Returns

Return type

int or None

get_variables_by_offset(*start*)

Find variables covering the given region offset.

Parameters

start (*int*) –

Returns

A set of variables.

Return type

set

get_objects_by_offset(*start*)

Find objects covering the given region offset.

Parameters

start –

Returns

get_all_variables()

Get all variables covering the current region.

Returns

A set of all variables.

10.14 Serialization

class `angr.serializable.Serializable`

Bases: `object`

The base class of all protobuf-serializable classes in angr.

serialize_to_cmessage()

Serialize the class object and returns a protobuf cmessage object.

Returns

A protobuf cmessage object.

Return type

`protobuf.cmessage`

serialize()

Serialize the class object and returns a bytes object.

Returns

A bytes object.

Return type

bytes

classmethod **parse_from_cmessage**(*cmsg*, ***kwargs*)

Parse a protobuf cmessage and create a class object.

Parameters
cmsg – The probobuf cmessage object.

Returns

A unserialized class object.

Return type

cls

classmethod **parse**(*s*, ***kwargs*)

Parse a bytes object and create a class object.

Parameters
s (*bytes*) – A bytes object.

Returns

A class object.

Return type

cls

class angr.vaults.**VaultPickler**(*vault*, *file*, **args*, *assigned_objects=()*, ***kwargs*)

Bases: Pickler

__init__(*vault*, *file*, **args*, *assigned_objects=()*, ***kwargs*)

A persistence-aware pickler. It will check for persistence of any objects except for those with IDs in ‘assigned_objects’.

persistent_id(*obj*)

class angr.vaults.**VaultUnpickler**(*vault*, *file*, **args*, ***kwargs*)

Bases: Unpickler

__init__(*vault*, *file*, **args*, ***kwargs*)

persistent_load(*pid*)

class angr.vaults.**Vault**

Bases: MutableMapping

The vault is a serializer for angr.

keys()

Should return the IDs stored by the vault.

__init__()

is_stored(*i*)

Checks if the provided id is already in the vault.

load(*oid*)

store(*o*)

dumps(*o*)

Returns a serialized string representing the object, post-deduplication.

Parameters

o – the object

loads(*s*)

Deserializes a string representation of the object.

Parameters

s – the string

static close()**class** `angr.vaults.VaultDict(d=None)`

Bases: `Vault`

A Vault that uses a dictionary for storage.

__init__(*d=None*)**is_stored**(*i*)

Checks if the provided id is already in the vault.

keys()

Should return the IDs stored by the vault.

class `angr.vaults.VaultDir(d=None)`

Bases: `Vault`

A Vault that uses a directory for storage.

__init__(*d=None*)**keys()**

Should return the IDs stored by the vault.

class `angr.vaults.VaultShelf(path=None)`

Bases: `VaultDict`

A Vault that uses a `shelve.Shelf` for storage.

__init__(*path=None*)**close()****class** `angr.vaults.VaultDirShelf(d=None)`

Bases: `VaultDict`

A Vault that uses a directory for storage, where every object is stored into a single `shelve.Shelf` instance. `VaultDir` creates a file for each object. `VaultDirShelf` creates only one file for a stored object and everything else it references.

__init__(*d=None*)**store**(*o*)**load**(*oid*)**keys()**

Should return the IDs stored by the vault.

10.15 Analysis

```

angr.analyses.register_analysis(cls, name)

class angr.analyses.analysis.AnalysisLogEntry(message, exc_info=False)
    Bases: object
    __init__(message, exc_info=False)

class angr.analyses.analysis.AnalysesHub(project)
    Bases: PluginVendor[A]
    This class contains functions for all the registered and runnable analyses,
    __init__(project)
    reload_analyses(**kwargs)

class angr.analyses.analysis.KnownAnalysesPlugin(*args, **kwargs)
    Bases: Protocol
    Identifier: Type[Identifier]
    CalleeCleanupFinder: Type[CalleeCleanupFinder]
    VSA_DDG: Type[VSA_DDG]
    CDG: Type[CDG]
    BinDiff: Type[BinDiff]
    CFGEmulated: Type[CFGEmulated]
    CFB: Type[CFBlanket]
    CFBlanket: Type[CFBlanket]
    CFG: Type[CFG]
    CFGFast: Type[CFGFast]
    StaticHooker: Type[StaticHooker]
    DDG: Type[DDG]
    CongruencyCheck: Type[CongruencyCheck]
    Reassembler: Type[Reassembler]
    BackwardSlice: Type[BackwardSlice]
    BinaryOptimizer: Type[BinaryOptimizer]
    VFG: Type[VFG]
    LoopFinder: Type[LoopFinder]
    Disassembly: Type[Disassembly]
    Veritesting: Type[Veritesting]

```

```

CodeTagging: Type[CodeTagging]
BoyScout: Type[BoyScout]
VariableRecoveryFast: Type[VariableRecoveryFast]
VariableRecovery: Type[VariableRecovery]
ReachingDefinitions: Type[ReachingDefinitionsAnalysis]
CompleteCallingConventions: Type[CompleteCallingConventionsAnalysis]
Clinic: Type[Clinic]
Propagator: Type[PropagatorAnalysis]
CallingConvention: Type[CallingConventionAnalysis]
Decompiler: Type[Decompiler]
XRefs: Type[XRefsAnalysis]
__init__(*args, **kwargs)

```

```
class angr.analyses.analysis.AnalysesHubWithDefault(project)
```

Bases: [AnalysesHub](#), [KnownAnalysesPlugin](#)

This class has type-hinting for all built-in analyses plugin

```
class angr.analyses.analysis.AnalysisFactory(project, analysis_cls)
```

Bases: [Generic](#)[A]

```
__init__(project, analysis_cls)
```

Parameters

- **project** ([Project](#)) –
- **analysis_cls** ([Type](#)[A]) –

```
prep(fail_fast=False, kb=None, progress_callback=None, show_progressbar=False)
```

Return type

[Type](#)[[TypeVar](#)(A, bound= [Analysis](#))]

Parameters

- **kb** ([KnowledgeBase](#) / [None](#)) –
- **progress_callback** ([Callable](#) / [None](#)) –
- **show_progressbar** ([bool](#)) –

```
class angr.analyses.analysis.Analysis
```

Bases: [object](#)

This class represents an analysis on the program.

Variables

- **project** – The project for this analysis.
- **kb** ([KnowledgeBase](#)) – The knowledgebase object.

- **_progress_callback** – A callback function for receiving the progress of this analysis. It only takes one argument, which is a float number from 0.0 to 100.0 indicating the current progress.
- **_show_progressbar** (*bool*) – If a progressbar should be shown during the analysis. It's independent from `_progress_callback`.
- **_progressbar** (*progress.Progress*) – The progress bar object.

project: *Project*

kb: *KnowledgeBase*

errors = []

named_errors = {}

```
class angr.analyses.forward_analysis.forward_analysis.ForwardAnalysis(order_jobs=False,
                                                                    allow_merging=False,
                                                                    allow_widening=False,
                                                                    status_callback=None,
                                                                    graph_visitor=None)
```

Bases: *Generic*[*AnalysisState*, *NodeType*, *JobType*, *JobKey*]

This is my very first attempt to build a static forward analysis framework that can serve as the base of multiple static analyses in angr, including CFG analysis, VFG analysis, DDG, etc.

In short, `ForwardAnalysis` performs a forward data-flow analysis by traversing a graph, compute on abstract values, and store results in abstract states. The user can specify what graph to traverse, how a graph should be traversed, how abstract values and abstract states are defined, etc.

`ForwardAnalysis` has a few options to toggle, making it suitable to be the base class of several different styles of forward data-flow analysis implementations.

`ForwardAnalysis` supports a special mode when no graph is available for traversal (for example, when a CFG is being initialized and constructed, no other graph can be used). In that case, the graph traversal functionality is disabled, and the optimal graph traversal order is not guaranteed. The user can provide a job sorting method to sort the jobs in queue and optimize traversal order.

Feel free to discuss with me (Fish) if you have any suggestions or complaints.

```
__init__(order_jobs=False, allow_merging=False, allow_widening=False, status_callback=None,
         graph_visitor=None)
```

Constructor

Parameters

- **order_jobs** (*bool*) – If all jobs should be ordered or not.
- **allow_merging** (*bool*) – If job merging is allowed.
- **allow_widening** (*bool*) – If job widening is allowed.
- **graph_visitor** (*GraphVisitor* or *None*) – A graph visitor to provide successors.
- **status_callback** (*Callable*[[*Type*[*ForwardAnalysis*]], *Any*] | *None*) –

Returns

None

property should_abort

Should the analysis be terminated. :return: True/False

property graph: `DiGraph`

property jobs

abort()

Abort the analysis :return: None

has_job(job)

Checks whether there exists another job which has the same job key. :type job: `TypeVar(JobType)` :param job: The job to check.

Return type

`bool`

Returns

True if there exists another job with the same key, False otherwise.

Parameters

job (`JobType`) –

downsize()

class `angr.analyses.forward_analysis.job_info.JobInfo(key, job)`

Bases: `Generic[JobType, JobKey]`

Stores information of each job.

__init__(*key, job*)

Parameters

- **key** (`JobKey`) –
- **job** (`JobType`) –

property job: `JobType`

Get the latest available job.

Returns

The latest available job.

property merged_jobs

property widened_jobs

add_job(*job, merged=False, widened=False*)

Appended a new job to this JobInfo node. :type job: :param job: The new job to append. :param bool merged: Whether it is a merged job or not. :param bool widened: Whether it is a widened job or not.

class `angr.analyses.forward_analysis.visitors.call_graph.CallGraphVisitor(callgraph)`

Bases: `GraphVisitor`

Parameters

callgraph (`networkx.DiGraph`) –

__init__(*callgraph*)

successors(*node*)

Get successors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of successors.

Return type

`list`

predecessors(*node*)

Get predecessors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of predecessors.

sort_nodes(*nodes=None*)

Get a list of all nodes sorted in an optimal traversal order.

Parameters

nodes (*iterable*) – A collection of nodes to sort. If none, all nodes in the graph will be used to sort.

Returns

A list of sorted nodes.

class `angr.analyses.forward_analysis.visitors.function_graph.FunctionGraphVisitor`(*func*,
graph=None)

Bases: `GraphVisitor`

Parameters

func (*knowledge.Function*) –

__init__(*func*, *graph=None*)

resume_with_new_graph(*graph*)

We can only reasonably reuse existing results if the node index of the already traversed nodes are the same as the ones from the new graph. Otherwise, we always restart.

Return type

`bool`

Returns

True if we are resuming, False if `reset()` is called.

Parameters

graph (*DiGraph*) –

successors(*node*)

Get successors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of successors.

Return type

`list`

predecessors(*node*)

Get predecessors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of predecessors.

sort_nodes(*nodes=None*)

Get a list of all nodes sorted in an optimal traversal order.

Parameters

nodes (*iterable*) – A collection of nodes to sort. If none, all nodes in the graph will be used to sort.

Returns

A list of sorted nodes.

back_edges()

Get a list of back edges. This function is optional. If not overridden, the traverser cannot achieve an optimal graph traversal order.

Return type

`List[Tuple[TypeVar(NodeType), TypeVar(NodeType)]]`

Returns

A list of back edges (source -> destination).

class `angr.analyses.forward_analysis.visitors.graph.GraphVisitor`

Bases: `Generic[NodeType]`

A graph visitor takes a node in the graph and returns its successors. Typically, it visits a control flow graph, and returns successors of a CFGNode each time. This is the base class of all graph visitors.

__init__()

successors(*node*)

Get successors of a node. The node should be in the graph.

Parameters

node (`TypeVar(NodeType)`) – The node to work with.

Returns

A list of successors.

Return type

`list`

predecessors(*node*)

Get predecessors of a node. The node should be in the graph.

Parameters

node (`TypeVar(NodeType)`) – The node to work with.

Return type

`List[TypeVar(NodeType)]`

Returns

A list of predecessors.

sort_nodes(*nodes=None*)

Get a list of all nodes sorted in an optimal traversal order.

Parameters

nodes (*iterable*) – A collection of nodes to sort. If none, all nodes in the graph will be used to sort.

Return type

`List[TypeVar(NodeType)]`

Returns

A list of sorted nodes.

back_edges()

Get a list of back edges. This function is optional. If not overridden, the traverser cannot achieve an optimal graph traversal order.

Return type

`List[Tuple[TypeVar(NodeType), TypeVar(NodeType)]]`

Returns

A list of back edges (source -> destination).

nodes()

Return an iterator of nodes following an optimal traversal order.

Return type

`Iterator[TypeVar(NodeType)]`

Returns
nodes_iter(kwargs)**
reset()

Reset the internal node traversal state. Must be called prior to visiting future nodes.

Returns

None

next_node()

Get the next node to visit.

Return type

`Optional[TypeVar(NodeType)]`

Returns

A node in the graph.

all_successors(node, skip_reached_fixedpoint=False)

Returns all successors to the specific node.

Parameters

node (`TypeVar(NodeType)`) – A node in the graph.

Returns

A set of nodes that are all successors to the given node.

Return type

`set`

revisit_successors(node, include_self=True)

Revisit a node in the future. As a result, the successors to this node will be revisited as well.

Parameters

node (`TypeVar(NodeType)`) – The node to revisit in the future.

Return type

`None`

Returns

`None`

revisit_node(*node*)

Revisit a node in the future. Do not include its successors immediately.

Parameters

node (`TypeVar(NodeType)`) – The node to revisit in the future.

Return type

`None`

Returns

`None`

reached_fixedpoint(*node*)

Mark a node as reached fixed-point. This node as well as all its successors will not be visited in the future.

Parameters

node (`TypeVar(NodeType)`) – The node to mark as reached fixed-point.

Return type

`None`

Returns

`None`

class `angr.analyses.forward_analysis.visitors.loop.LoopVisitor(loop)`

Bases: `GraphVisitor`

Parameters

loop (`angr.analyses.loopfinder.Loop`) – The loop to visit.

__init__(*loop*)

successors(*node*)

Get successors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of successors.

Return type

`list`

predecessors(*node*)

Get predecessors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of predecessors.

sort_nodes(*nodes=None*)

Get a list of all nodes sorted in an optimal traversal order.

Parameters

nodes (*iterable*) – A collection of nodes to sort. If none, all nodes in the graph will be used to sort.

Returns

A list of sorted nodes.

class `angr.analyses.forward_analysis.visitors.single_node_graph.SingleNodeGraphVisitor`(*node*)

Bases: `GraphVisitor`

Parameters

node – The single node that should be in the graph.

__init__(*node*)

node

node_returned

reset()

Reset the internal node traversal state. Must be called prior to visiting future nodes.

Returns

None

next_node()

Get the next node to visit.

Returns

A node in the graph.

successors(*node*)

Get successors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of successors.

Return type

`list`

predecessors(*node*)

Get predecessors of a node. The node should be in the graph.

Parameters

node – The node to work with.

Returns

A list of predecessors.

sort_nodes(*nodes=None*)

Get a list of all nodes sorted in an optimal traversal order.

Parameters

nodes (*iterable*) – A collection of nodes to sort. If none, all nodes in the graph will be used to sort.

Returns

A list of sorted nodes.

```
class angr.analyses.backward_slice.BackwardSlice(cfg, cdg, ddg, targets=None, cfg_node=None,
                                                stmt_id=None, control_flow_slice=False,
                                                same_function=False, no_construct=False)
```

Bases: [Analysis](#)

Represents a backward slice of the program.

```
__init__(cfg, cdg, ddg, targets=None, cfg_node=None, stmt_id=None, control_flow_slice=False,
        same_function=False, no_construct=False)
```

Create a backward slice from a specific statement based on provided control flow graph (CFG), control dependence graph (CDG), and data dependence graph (DDG).

The data dependence graph can be either CFG-based, or Value-set analysis based. A CFG-based DDG is much faster to generate, but it only reflects those states while generating the CFG, and it is neither sound nor accurate. The VSA based DDG (called VSA_DDG) is based on static analysis, which gives you a much better result.

Parameters

- **cfg** – The control flow graph.
- **cdg** – The control dependence graph.
- **ddg** – The data dependence graph.
- **targets** – A list of “target” that specify targets of the backward slices. Each target can be a tuple in form of (cfg_node, stmt_idx), or a CodeLocation instance.
- **cfg_node** – Deprecated. The target CFGNode to reach. It should exist in the CFG.
- **stmt_id** – Deprecated. The target statement to reach.
- **control_flow_slice** – True/False, indicates whether we should slice only based on CFG. Sometimes when acquiring DDG is difficult or impossible, you can just create a slice on your CFG. Well, if you don’t even have a CFG, then...
- **no_construct** – Only used for testing and debugging to easily create a BackwardSlice object.

```
dbg_repr(max_display=10)
```

Debugging output of this slice.

Parameters

max_display – The maximum number of SimRun slices to show.

Returns

A string representation.

```
dbg_repr_run(run_addr)
```

Debugging output of a single SimRun slice.

Parameters

run_addr – Address of the SimRun.

Returns

A string representation.

```
annotated_cfg(start_point=None)
```

Returns an AnnotatedCFG based on slicing result.

is_taint_related_to_ip(*simrun_addr*, *stmt_idx*, *taint_type*, *simrun_whitelist=None*)

Query in taint graph to check if a specific taint will taint the IP in the future or not. The taint is specified with the tuple (*simrun_addr*, *stmt_idx*, *taint_type*).

Parameters

- **simrun_addr** – Address of the SimRun.
- **stmt_idx** – Statement ID.
- **taint_type** – Type of the taint, might be one of the following: ‘reg’, ‘tmp’, ‘mem’.
- **simrun_whitelist** – A list of SimRun addresses that are whitelisted, i.e. the tainted exit will be ignored if it is in those SimRuns.

Returns

True/False

is_taint_impacting_stack_pointers(*simrun_addr*, *stmt_idx*, *taint_type*, *simrun_whitelist=None*)

Query in taint graph to check if a specific taint will taint the stack pointer in the future or not. The taint is specified with the tuple (*simrun_addr*, *stmt_idx*, *taint_type*).

Parameters

- **simrun_addr** – Address of the SimRun.
- **stmt_idx** – Statement ID.
- **taint_type** – Type of the taint, might be one of the following: ‘reg’, ‘tmp’, ‘mem’.
- **simrun_whitelist** – A list of SimRun addresses that are whitelisted.

Returns

True/False.

project: Project

kb: KnowledgeBase

exception `angr.analyses.bindiff.UnmatchedStatementsException`

Bases: `Exception`

class `angr.analyses.bindiff.Difference`(*diff_type*, *value_a*, *value_b*)

Bases: `object`

`__init__`(*diff_type*, *value_a*, *value_b*)

class `angr.analyses.bindiff.ConstantChange`(*offset*, *value_a*, *value_b*)

Bases: `object`

`__init__`(*offset*, *value_a*, *value_b*)

`angr.analyses.bindiff.differing_constants`(*block_a*, *block_b*)

Compares two basic blocks and finds all the constants that differ from the first block to the second.

Parameters

- **block_a** – The first block to compare.
- **block_b** – The second block to compare.

Returns

Returns a list of differing constants in the form of `ConstantChange`, which has the offset in the block and the respective constants.

`angr.analyses.bindiff.compare_statement_dict(statement_1, statement_2)`

class `angr.analyses.bindiff.NormalizedBlock(block, function)`

Bases: `object`

`__init__(block, function)`

class `angr.analyses.bindiff.NormalizedFunction(function)`

Bases: `object`

Parameters

function (`Function`) –

`__init__(function)`

Parameters

function (`Function`) –

class `angr.analyses.bindiff.FunctionDiff(function_a, function_b, bindiff=None)`

Bases: `object`

This class computes the a diff between two functions.

Parameters

- **function_a** (`Function`) –

- **function_b** (`Function`) –

`__init__(function_a, function_b, bindiff=None)`

Parameters

- **function_a** (`Function`) – The first angr Function object to diff.

- **function_b** (`Function`) – The second angr Function object.

- **bindiff** – An optional Bindiff object. Used for some extra normalization during basic block comparison.

property `probably_identical`

Whether or not these two functions are identical.

Type

returns

property `identical_blocks`

A list of block matches which appear to be identical

Type

returns

property `differing_blocks`

A list of block matches which appear to differ

Type

returns

property `blocks_with_differing_constants`

A list of block matches which appear to differ

Type

return

property `block_matches`

property `unmatched_blocks`

static `get_normalized_block(addr, function)`

Parameters

- **addr** – Where to start the normalized block.
- **function** – A function containing the block address.

Returns

A normalized basic block.

block_similarity(*block_a*, *block_b*)

Parameters

- **block_a** – The first block address.
- **block_b** – The second block address.

Returns

The similarity of the basic blocks, normalized for the base address of the block and function call addresses.

blocks_probably_identical(*block_a*, *block_b*, *check_constants=False*)

Parameters

- **block_a** – The first block address.
- **block_b** – The second block address.
- **check_constants** – Whether or not to require matching constants in blocks.

Returns

Whether or not the blocks appear to be identical.

class `angr.analyses.bindiff.Bindiff`(*other_project*, *enable_advanced_backward_slicing=False*, *cfg_a=None*, *cfg_b=None*)

Bases: [Analysis](#)

This class computes the a diff between two binaries represented by angr Projects

__init__(*other_project*, *enable_advanced_backward_slicing=False*, *cfg_a=None*, *cfg_b=None*)

Parameters

other_project – The second project to diff

functions_probably_identical(*func_a_addr*, *func_b_addr*, *check_consts=False*)

Compare two functions and return True if they appear identical.

Parameters

- **func_a_addr** – The address of the first function (in the first binary).
- **func_b_addr** – The address of the second function (in the second binary).

Returns

Whether or not the functions appear to be identical.

property identical_functions

A list of function matches that appear to be identical

Type

returns

property differing_functions

A list of function matches that appear to differ

Type

returns

differing_functions_with_consts()

Returns

A list of function matches that appear to differ including just by constants

property differing_blocks

A list of block matches that appear to differ

Type

returns

property identical_blocks

return A list of all block matches that appear to be identical

property blocks_with_differing_constants

A dict of block matches with differing constants to the tuple of constants

Type

return

property unmatched_functions

get_function_diff(*function_addr_a*, *function_addr_b*)

Parameters

- **function_addr_a** – The address of the first function (in the first binary)
- **function_addr_b** – The address of the second function (in the second binary)

Returns

the FunctionDiff of the two functions

project: Project

kb: KnowledgeBase

class angr.analyses.boyscout.**BoyScout**(*cookiesize=1*)

Bases: *Analysis*

Try to determine the architecture and endianness of a binary blob

__init__(*cookiesize=1*)

project: Project

kb: KnowledgeBase

```

class angr.analyses.calling_convention.CallSiteFact(return_value_used)
    Bases: object
    Store facts about each call site.
    __init__(return_value_used)

class angr.analyses.calling_convention.UpdateArgumentsOption
    Bases: object
    Enums for controlling the argument updating behavior in _adjust_cc.
    DoNotUpdate = 0
    AlwaysUpdate = 1
    UpdateWhenCCHasNoArgs = 2

class angr.analyses.calling_convention.CallingConventionAnalysis(func, cfg=None,
                                                                analyze_callsites=False,
                                                                caller_func_addr=None,
                                                                callsite_block_addr=None,
                                                                callsite_insn_addr=None,
                                                                func_graph=None)

```

Bases: *Analysis*

Analyze the calling convention of a function and guess a probable prototype.

The calling convention of a function can be inferred at both its call sites and the function itself. At call sites, we consider all register and stack variables that are not alive after the function call as parameters to this function. In the function itself, we consider all register and stack variables that are read but without initialization as parameters. Then we synthesize the information from both locations and make a reasonable inference of calling convention of this function.

Variables

- **_function** – The function to recover calling convention for.
- **_variable_manager** – A handy accessor to the variable manager.
- **_cfg** – A reference of the CFGModel of the current binary. It is used to discover call sites of the current function in order to perform analysis at call sites.
- **analyze_callsites** – True if we should analyze all call sites of the current function to determine the calling convention and arguments. This can be time-consuming if there are many call sites to analyze.
- **cc** – The recovered calling convention for the function.

Parameters

- **func** (*Function* | *int* | *str* | *None*) –
- **cfg** (*CFGModel* | *None*) –
- **analyze_callsites** (*bool*) –
- **caller_func_addr** (*int* | *None*) –
- **callsite_block_addr** (*int* | *None*) –
- **callsite_insn_addr** (*int* | *None*) –
- **func_graph** (*DiGraph* | *None*) –

```
__init__(func, cfg=None, analyze_callsites=False, caller_func_addr=None, callsite_block_addr=None,
        callsite_insn_addr=None, func_graph=None)
```

Parameters

- **func** (`Function` | `int` | `str` | `None`) –
- **cfg** (`CFGModel` | `None`) –
- **analyze_callsites** (`bool`) –
- **caller_func_addr** (`int` | `None`) –
- **callsite_block_addr** (`int` | `None`) –
- **callsite_insn_addr** (`int` | `None`) –
- **func_graph** (`DiGraph` | `None`) –

project: `Project`

kb: `KnowledgeBase`

is_va_start_amd64(`func`)

Return type

`Tuple[bool, Optional[int]]`

Parameters

func (`Function`) –

```
class angr.analyses.complete_calling_conventions.CompleteCallingConventionsAnalysis(recover_variables=False,
    low_priority=False,
    force=False,
    cfg=None,
    ana-
    lyze_callsites=False,
    skip_signature_matched_
    max_function_blocks=None,
    max_function_size=None,
    work-
    ers=0,
    cc_callback=None,
    priori-
    tize_func_addrs=None,
    skip_other_funcs=False,
    auto_start=True,
    func_graphs=None)
```

Bases: `Analysis`

Implements full-binary calling convention analysis. During the initial analysis of a binary, you may set *recover_variables* to `True` so that it will perform variable recovery on each function before performing calling convention analysis.

Parameters

- **cfg** (`CFGModel` | `None`) –
- **analyze_callsites** (`bool`) –
- **skip_signature_matched_functions** (`bool`) –
- **max_function_blocks** (`int` | `None`) –

- **max_function_size** (*int* | *None*) –
- **workers** (*int*) –
- **cc_callback** (*Callable* | *None*) –
- **prioritize_func_addrs** (*Iterable*[*int*] | *None*) –
- **skip_other_funcs** (*bool*) –
- **auto_start** (*bool*) –
- **func_graphs** (*Dict*[*int*, *networkx.DiGraph*] | *None*) –

__init__ (*recover_variables=False*, *low_priority=False*, *force=False*, *cfg=None*, *analyze_callsites=False*, *skip_signature_matched_functions=False*, *max_function_blocks=None*, *max_function_size=None*, *workers=0*, *cc_callback=None*, *prioritize_func_addrs=None*, *skip_other_funcs=False*, *auto_start=True*, *func_graphs=None*)

Parameters

- **recover_variables** – Recover variables on each function before performing calling convention analysis.
- **low_priority** – Run in the background - periodically release GIL.
- **force** – Perform calling convention analysis on functions even if they have calling conventions or prototypes already specified (or previously recovered).
- **cfg** (*Optional*[*CFGModel*]) – The control flow graph model, which will be passed to *CallingConventionAnalysis*.
- **analyze_callsites** (*bool*) – Consider artifacts at call sites when performing calling convention analysis.
- **skip_signature_matched_functions** (*bool*) – Do not perform calling convention analysis on functions that match against existing FLIRT signatures.
- **max_function_blocks** (*Optional*[*int*]) – Do not perform calling convention analysis on functions with more than the specified number of blocks. Setting it to *None* disables this check.
- **max_function_size** (*Optional*[*int*]) – Do not perform calling convention analysis on functions whose sizes are more than *max_function_size*. Setting it to *None* disables this check.
- **workers** (*int*) – Number of multiprocessing workers.
- **cc_callback** (*Callable* | *None*) –
- **prioritize_func_addrs** (*Iterable*[*int*] | *None*) –
- **skip_other_funcs** (*bool*) –
- **auto_start** (*bool*) –
- **func_graphs** (*Dict*[*int*, *DiGraph*] | *None*) –

work()

project: *Project*

kb: *KnowledgeBase*

prioritize_functions(*func_addrs_to_prioritize*)

Prioritize the analysis of specified functions.

Parameters

func_addrs_to_prioritize ([Iterable](#)[[int](#)]) – A collection of function addresses to analyze first.

static function_needs_variable_recovery(*func*)

Check if running variable recovery on the function is the only way to determine the calling convention of the this function.

We do not need to run variable recovery to determine the calling convention of a function if: - The function is a SimProcedure. - The function is a PLT stub. - The function is a library function and we already know its prototype.

Parameters

func – The function object.

Returns

True if we must run VariableRecovery before we can determine what the calling convention of this function is. False otherwise.

Return type

[bool](#)

exception `angr.analyses.soot_class_hierarchy.SootClassHierarchyError`(*msg*)

Bases: [Exception](#)

__init__(*msg*)

exception `angr.analyses.soot_class_hierarchy.NoConcreteDispatch`(*msg*)

Bases: [SootClassHierarchyError](#)

__init__(*msg*)

class `angr.analyses.soot_class_hierarchy.SootClassHierarchy`

Bases: [Analysis](#)

Generate complete hierarchy.

__init__()

init_hierarchy()

has_super_class(*cls*)

is_subclass_including(*cls_child*, *cls_parent*)

is_subclass(*cls_child*, *cls_parent*)

is_visible_method(*cls*, *method*)

is_visible_class(*cls_from*, *cls_to*)

get_super_classes(*cls*)

get_super_classes_including(*cls*)

get_implementers(*interface*)

get_sub_interfaces_including(*interface*)

```

get_sub_interfaces(interface)

get_sub_classes(cls)

get_sub_classes_including(cls)

resolve_abstract_dispatch(cls, method)

resolve_concrete_dispatch(cls, method)

resolve_special_dispatch(method, container)

resolve_invoke(invoke_expr, method, container)

project: Project

kb: KnowledgeBase

class angr.analyses.cfg.cfb.CFBlanketView(cfb)
    Bases: object
    A view into the control-flow blanket.
    __init__(cfb)

class angr.analyses.cfg.cfb.MemoryRegion(addr, size, type_, object_, cle_region)
    Bases: object
    __init__(addr, size, type_, object_, cle_region)

class angr.analyses.cfg.cfb.Unknown(addr, size, bytes_=None, object_=None, segment=None,
                                   section=None)
    Bases: object
    __init__(addr, size, bytes_=None, object_=None, segment=None, section=None)

class angr.analyses.cfg.cfb.CFBlanket(exclude_region_types=None, on_object_added=None)
    Bases: Analysis
    A Control-Flow Blanket is a representation for storing all instructions, data entries, and bytes of a full program.
    Region types: - section - segment - extern - tls - kernel

    Parameters
        • exclude_region_types (Set[str] | None) –
        • on_object_added (Callable[[int, Any], None] | None) –
    __init__(exclude_region_types=None, on_object_added=None)

    Parameters
        • on_object_added (Optional[Callable[[int, Any], None]]) – Callable with parameters (addr, obj) called after an object is added to the blanket.
        • exclude_region_types (Set[str] | None) –

property regions
    Return all memory regions.

floor_addr(addr)

```

floor_item(*addr*)

floor_items(*addr=None, reverse=False*)

ceiling_addr(*addr*)

ceiling_item(*addr*)

ceiling_items(*addr=None, reverse=False, include_first=True*)

add_obj(*addr, obj*)

Adds an object *obj* to the blanket at the specified address *addr*

add_function(*func*)

Add a function *func* and all blocks of this function to the blanket.

dbg_repr()

The debugging representation of this CFBlanket.

Returns

The debugging representation of this CFBlanket.

Return type

`str`

project: `Project`

kb: `KnowledgeBase`

exception `angr.analyses.cfg.cfg.OutOfdatedError`

Bases: `Exception`

class `angr.analyses.cfg.cfg.CFG(**kwargs)`

Bases: `CFGFast`

tl;dr: CFG is just a wrapper around CFGFast for compatibility issues. It will be fully replaced by CFGFast in future releases. Feel free to use CFG if you intend to use CFGFast. Please use CFGEmulated if you *have to* use the old, slow, dynamically-generated version of CFG.

For multiple historical reasons, Angr's CFG is accurate but slow, which does not meet what most people expect. We developed CFGFast for light-speed CFG recovery, and renamed the old CFG class to CFGEmulated. For compability concerns, CFG was kept as an alias to CFGEmulated.

However, so many new users of Angr would load up a binary and generate a CFG immediately after running “pip install Angr”, and draw the conclusion that “Angr's CFG is so slow - Angr must be unusable!” Therefore, we made the hard decision: CFG will be an alias to CFGFast, instead of CFGEmulated.

To ease the transition of your existing code and script, the following changes are made:

- A CFG class, which is a sub class of CFGFast, is created.
- You will see both a warning message printed out to stderr and an exception raised by Angr if you are passing CFG any parameter that only CFGEmulated supports. This exception is not a sub class of AngrError, so you wouldn't capture it with your old code by mistake.
- In the near future, this wrapper class will be removed completely, and CFG will be a simple alias to CFGFast.

We expect most interfaces are the same between CFGFast and CFGEmulated. Apparently some functionalities (like context-sensitivity, and state keeping) only exist in CFGEmulated, which is when you want to use CFGEmulated instead.

`__init__(**kwargs)`

Parameters

- **binary** – The binary to recover CFG on. By default the main binary is used.
- **objects** – A list of objects to recover the CFG on. By default it will recover the CFG of all loaded objects.
- **regions** (*iterable*) – A list of tuples in the form of (start address, end address) describing memory regions that the CFG should cover.
- **pickle_intermediate_results** (*bool*) – If we want to store the intermediate results or not.
- **symbols** (*bool*) – Get function beginnings from symbols in the binary.
- **function_prologues** (*bool*) – Scan the binary for function prologues, and use those positions as function beginnings
- **resolve_indirect_jumps** (*bool*) – Try to resolve indirect jumps. This is necessary to resolve jump targets from jump tables, etc.
- **force_segment** (*bool*) – Force CFGFast to rely on binary segments instead of sections.
- **force_complete_scan** (*bool*) – Perform a complete scan on the binary and maximize the number of identified code blocks.
- **data_references** (*bool*) – Enables the collection of references to data used by individual instructions. This does not collect ‘cross-references’, particularly those that involve multiple instructions. For that, see *cross_references*
- **cross_references** (*bool*) – Whether CFGFast should collect “cross-references” from the entire program or not. This will populate the knowledge base with references to and from each recognizable address constant found in the code. Note that, because this performs constant propagation on the entire program, it may be much slower and consume more memory. This option implies *data_references=True*.
- **normalize** (*bool*) – Normalize the CFG as well as all function graphs after CFG recovery.
- **start_at_entry** (*bool*) – Begin CFG recovery at the entry point of this project. Setting it to False prevents CFGFast from viewing the entry point as one of the starting points of code scanning.
- **function_starts** (*list*) – A list of extra function starting points. CFGFast will try to resume scanning from each address in the list.
- **extra_memory_regions** (*list*) – A list of 2-tuple (start-address, end-address) that shows extra memory regions. Integers falling inside will be considered as pointers.
- **indirect_jump_resolvers** (*list*) – A custom list of indirect jump resolvers. If this list is None or empty, default indirect jump resolvers specific to this architecture and binary types will be loaded.
- **base_state** – A state to use as a backer for all memory loads
- **detect_tail_calls** (*bool*) – Enable aggressive tail-call optimization detection.
- **elf_eh_frame** (*bool*) – Retrieve function starts (and maybe sizes later) from the .eh_frame of ELF binaries.
- **skip_unmapped_addrs** – Ignore all branches into unmapped regions. True by default. You may want to set it to False if you are analyzing manually patched binaries or malware samples.

- **indirect_calls_always_return** – Should CFG assume indirect calls must return or not. Assuming indirect calls must return will significantly reduce the number of constant propagation runs, but may reduce the overall CFG recovery precision when facing non-returning indirect calls. By default, we only assume indirect calls always return for large binaries (region > 50KB).
- **jumptable_resolver_resolves_calls** – Whether JumpTableResolver should resolve indirect calls or not. Most indirect calls in C++ binaries or UEFI binaries cannot be resolved using jump table resolver and must be resolved using their specific resolvers. By default, we will only disable JumpTableResolver from resolving indirect calls for large binaries (region > 50 KB).
- **start** (*int*) – (Deprecated) The beginning address of CFG recovery.
- **end** (*int*) – (Deprecated) The end address of CFG recovery.
- **arch_options** (*CFGArchOptions*) – Architecture-specific options.
- **extra_arch_options** (*dict*) – Any key-value pair in kwargs will be seen as an arch-specific option and will be used to set the option value in self._arch_options.

Extra parameters that `angr.Analysis` takes:

Parameters

- **progress_callback** – Specify a callback function to get the progress during CFG recovery.
- **show_progressbar** (*bool*) – Should CFGFast show a progressbar during CFG recovery or not.

Returns

None

class `angr.analyses.cfg.cfg_emulated.CFGJob(*args, **kwargs)`

Bases: `CFGJobBase`

The job class that `CFGEmulated` uses.

__init__ (**args, **kwargs*)

property `block_id`

property `is_syscall`

class `angr.analyses.cfg.cfg_emulated.PendingJob(caller_func_addr, returning_source, state, src_block_id, src_exit_stmt_idx, src_exit_ins_addr, call_stack)`

Bases: `object`

A `PendingJob` is whatever will be put into our `pending_exit` list. A pending exit is an entry that created by the returning of a call or syscall. It is “pending” since we cannot immediately figure out whether this entry will be executed or not. If the corresponding call/syscall intentionally doesn’t return, then the pending exit will be removed. If the corresponding call/syscall returns, then the pending exit will be removed as well (since a real entry is created from the returning and will be analyzed later). If the corresponding call/syscall might return, but for some reason (for example, an unsupported instruction is met during the analysis) our analysis does not return properly, then the pending exit will be picked up and put into `remaining_jobs` list.

__init__ (*caller_func_addr, returning_source, state, src_block_id, src_exit_stmt_idx, src_exit_ins_addr, call_stack*)

Parameters

- **returning_source** – Address of the callee function. It might be None if address of the callee is not resolvable.
- **state** – The state after returning from the callee function. Of course there is no way to get a precise state without emulating the execution of the callee, but at least we can properly adjust the stack and registers to imitate the real returned state.
- **call_stack** – A callstack.

```
class angr.analyses.cfg.cfg_emulated.CFGEEmulated(context_sensitivity_level=1, start=None,
                                                  avoid_runs=None, enable_function_hints=False,
                                                  call_depth=None, call_tracing_filter=None,
                                                  initial_state=None, starts=None, keep_state=False,
                                                  indirect_jump_target_limit=100000,
                                                  resolve_indirect_jumps=True,
                                                  enable_advanced_backward_slicing=False,
                                                  enable_symbolic_back_traversal=False,
                                                  indirect_jump_resolvers=None,
                                                  additional_edges=None, no_construct=False,
                                                  normalize=False, max_iterations=1,
                                                  address_whitelist=None, base_graph=None,
                                                  iropt_level=None, max_steps=None,
                                                  state_add_options=None,
                                                  state_remove_options=None, model=None)
```

Bases: [ForwardAnalysis](#), [CFGBase](#)

This class represents a control-flow graph.

tag: `Optional[str] = 'CFGEEmulated'`

```
__init__(context_sensitivity_level=1, start=None, avoid_runs=None, enable_function_hints=False,
          call_depth=None, call_tracing_filter=None, initial_state=None, starts=None, keep_state=False,
          indirect_jump_target_limit=100000, resolve_indirect_jumps=True,
          enable_advanced_backward_slicing=False, enable_symbolic_back_traversal=False,
          indirect_jump_resolvers=None, additional_edges=None, no_construct=False, normalize=False,
          max_iterations=1, address_whitelist=None, base_graph=None, iropt_level=None,
          max_steps=None, state_add_options=None, state_remove_options=None, model=None)
```

All parameters are optional.

Parameters

- **context_sensitivity_level** – The level of context-sensitivity of this CFG (see documentation for further details). It ranges from 0 to infinity. Default 1.
- **avoid_runs** – A list of runs to avoid.
- **enable_function_hints** – Whether to use function hints (constants that might be used as exit targets) or not.
- **call_depth** – How deep in the call stack to trace.
- **call_tracing_filter** – Filter to apply on a given path and jumpkind to determine if it should be skipped when call_depth is reached.
- **initial_state** – An initial state to use to begin analysis.
- **starts** (*iterable*) – A collection of starting points to begin analysis. It can contain the following three different types of entries: an address specified as an integer, a 2-tuple that includes an integer address and a jumpkind, or a SimState instance. Unsupported entries in starts will lead to an AngrCFGError being raised.

- **keep_state** – Whether to keep the SimStates for each CFGNode.
- **resolve_indirect_jumps** – Whether to enable the indirect jump resolvers for resolving indirect jumps
- **enable_advanced_backward_slicing** – Whether to enable an intensive technique for resolving indirect jumps
- **enable_symbolic_back_traversal** – Whether to enable an intensive technique for resolving indirect jumps
- **indirect_jump_resolvers** (*list*) – A custom list of indirect jump resolvers. If this list is None or empty, default indirect jump resolvers specific to this architecture and binary types will be loaded.
- **additional_edges** – A dict mapping addresses of basic blocks to addresses of successors to manually include and analyze forward from.
- **no_construct** (*bool*) – Skip the construction procedure. Only used in unit-testing.
- **normalize** (*bool*) – If the CFG as well as all Function graphs should be normalized or not.
- **max_iterations** (*int*) – The maximum number of iterations that each basic block should be “executed”. 1 by default. Larger numbers of iterations are usually required for complex analyses like loop analysis.
- **address_whitelist** (*iterable*) – A list of allowed addresses. Any basic blocks outside of this collection of addresses will be ignored.
- **base_graph** (*networkx.DiGraph*) – A basic control flow graph to follow. Each node inside this graph must have the following properties: *addr* and *size*. CFG recovery will strictly follow nodes and edges shown in the graph, and discard any control flow that does not follow an existing edge in the base graph. For example, you can pass in a Function local transition graph as the base graph, and CFGEmulated will traverse nodes and edges and extract useful information.
- **iropt_level** (*int*) – The optimization level of VEX IR (0, 1, 2). The default level will be used if *iropt_level* is None.
- **max_steps** (*int*) – The maximum number of basic blocks to recover for the longest path from each start before pausing the recovery procedure.
- **state_add_options** – State options that will be added to the initial state.
- **state_remove_options** – State options that will be removed from the initial state.

copy()

Make a copy of the CFG.

Return type

CFGEmulated

Returns

A copy of the CFG instance.

resume(starts=None, max_steps=None)

Resume a paused or terminated control flow graph recovery.

Parameters

- **starts** (*iterable*) – A collection of new starts to resume from. If *starts* is None, we will resume CFG recovery from where it was paused before.

- **max_steps** (*int*) – The maximum number of blocks on the longest path starting from each start before pausing the recovery.

Returns

None

remove_cycles()

Forces graph to become acyclic, removes all loop back edges and edges between overlapped loop headers and their successors.

downsize()

Remove saved states from all CFGNodes to reduce memory usage.

Returns

None

unroll_loops(*max_loop_unrolling_times*)

Unroll loops for each function. The resulting CFG may still contain loops due to recursion, function calls, etc.

Parameters

- **max_loop_unrolling_times** (*int*) – The maximum iterations of unrolling.

Returns

None

force_unroll_loops(*max_loop_unrolling_times*)

Unroll loops globally. The resulting CFG does not contain any loop, but this method is slow on large graphs.

Parameters

- **max_loop_unrolling_times** (*int*) – The maximum iterations of unrolling.

Returns

None

immediate_dominators(*start*, *target_graph=None*)

Get all immediate dominators of sub graph from given node upwards.

Parameters

- **start** (*str*) – id of the node to navigate forwards from.
- **target_graph** (*networkx.classes.digraph.DiGraph*) – graph to analyse, default is self.graph.

Returns

each node of graph as index values, with element as respective node's immediate dominator.

Return type

dict

immediate_postdominators(*end*, *target_graph=None*)

Get all immediate postdominators of sub graph from given node upwards.

Parameters

- **start** (*str*) – id of the node to navigate forwards from.
- **target_graph** (*networkx.classes.digraph.DiGraph*) – graph to analyse, default is self.graph.

Returns

each node of graph as index values, with element as respective node's immediate dominator.

Return type

dict

remove_fakerets()

Get rid of fake returns (i.e., Ijk_FakeRet edges) from this CFG

Returns

None

get_topological_order(*cfg_node*)

Get the topological order of a CFG Node.

Parameters

cfg_node – A CFGNode instance.

Returns

An integer representing its order, or None if the CFGNode does not exist in the graph.

get_subgraph(*starting_node*, *block_addresses*)

Get a sub-graph out of a bunch of basic block addresses.

Parameters

- **starting_node** (*CFGNode*) – The beginning of the subgraph
- **block_addresses** (*iterable*) – A collection of block addresses that should be included in the subgraph if there is a path between *starting_node* and a CFGNode with the specified address, and all nodes on the path should also be included in the subgraph.

Returns

A new CFG that only contain the specific subgraph.

Return type

CFGEmulated

get_function_subgraph(*start*, *max_call_depth=None*)

Get a sub-graph of a certain function.

Parameters

- **start** – The function start. Currently it should be an integer.
- **max_call_depth** – Call depth limit. None indicates no limit.

Returns

A CFG instance which is a sub-graph of self.graph

property context_sensitivity_level

property graph

property unresolvables

Get those SimRuns that have non-resolvable exits.

Returns

A set of SimRuns

Return type

set

property deadends

Get all CFGNodes that has an out-degree of 0

Returns

A list of CFGNode instances

Return type

list

```
class angr.analyses.cfg.cfg_base.CFGBase(sort, context_sensitivity_level, normalize=False, binary=None,
                                         objects=None, regions=None, exclude_sparse_regions=True,
                                         skip_specific_regions=True, force_segment=False,
                                         base_state=None, resolve_indirect_jumps=True,
                                         indirect_jump_resolvers=None,
                                         indirect_jump_target_limit=100000, detect_tail_calls=False,
                                         low_priority=False, skip_unmapped_addrs=True,
                                         sp_tracking_track_memory=True, model=None)
```

Bases: [Analysis](#)

The base class for control flow graphs.

tag: [Optional\[str\]](#) = None

```
__init__(sort, context_sensitivity_level, normalize=False, binary=None, objects=None, regions=None,
          exclude_sparse_regions=True, skip_specific_regions=True, force_segment=False,
          base_state=None, resolve_indirect_jumps=True, indirect_jump_resolvers=None,
          indirect_jump_target_limit=100000, detect_tail_calls=False, low_priority=False,
          skip_unmapped_addrs=True, sp_tracking_track_memory=True, model=None)
```

Parameters

- **sort** ([str](#)) – ‘fast’ or ‘emulated’.
- **context_sensitivity_level** ([int](#)) – The level of context-sensitivity of this CFG (see documentation for further details). It ranges from 0 to infinity.
- **normalize** ([bool](#)) – Whether the CFG as well as all Function graphs should be normalized.
- **binary** ([cle.backends.Backend](#)) – The binary to recover CFG on. By default, the main binary is used.
- **objects** – A list of objects to recover the CFG on. By default, it will recover the CFG of all loaded objects.
- **regions** ([iterable](#)) – A list of tuples in the form of (start address, end address) describing memory regions that the CFG should cover.
- **force_segment** ([bool](#)) – Force CFGFast to rely on binary segments instead of sections.
- **base_state** ([angr.SimState](#)) – A state to use as a backer for all memory loads.
- **resolve_indirect_jumps** ([bool](#)) – Whether to try to resolve indirect jumps. This is necessary to resolve jump targets from jump tables, etc.
- **indirect_jump_resolvers** ([list](#)) – A custom list of indirect jump resolvers. If this list is None or empty, default indirect jump resolvers specific to this architecture and binary types will be loaded.
- **indirect_jump_target_limit** ([int](#)) – Maximum indirect jump targets to be recovered.
- **skip_unmapped_addrs** – Ignore all branches into unmapped regions. True by default. You may want to set it to False if you are analyzing manually patched binaries or malware samples.

- **detect_tail_calls** (*bool*) – Aggressive tail-call optimization detection. This option is only respected in `make_functions()`.
- **sp_tracking_track_memory** (*bool*) – Whether or not to track memory writes if tracking the stack pointer. This increases the accuracy of stack pointer tracking, especially for architectures without a base pointer. Only used if `detect_tail_calls` is enabled.
- **model** (*None* or *CFGModel*) – The *CFGModel* instance to write to. A new *CFGModel* instance will be created and registered with the knowledge base if *model* is *None*.

Returns

None

property model: *CFGModel*

Get the *CFGModel* instance. :return: The *CFGModel* instance that this analysis currently uses.

property normalized

property context_sensitivity_level

property functions

A reference to the *FunctionManager* in the current knowledge base.

Returns

FunctionManager with all functions

Return type

`angr.knowledge_plugins.FunctionManager`

make_copy(*copy_to*)

Copy self attributes to the new object.

Parameters

copy_to (*CFGBase*) – The target to copy to.

Returns

None

copy()

output()

generate_index()

Generate an index of all nodes in the graph in order to speed up `get_any_node()` with `anyaddr=True`.

Returns

None

get_predecessors(***kwargs*)

get_successors(***kwargs*)

get_successors_and_jumpkind(***kwargs*)

get_all_predecessors(***kwargs*)

get_all_successors(***kwargs*)

get_node(***kwargs*)

get_any_node(***kwargs*)

get_all_nodes(**kwargs)

nodes(**kwargs)

nodes_iter(**kwargs)

get_loop_back_edges()

get_branching_nodes(**kwargs)

get_exit_stmt_idx(**kwargs)

property graph: `networkx.DiGraph[CFGNode]`

remove_edge(*block_from*, *block_to*)

is_thumb_addr(*addr*)

normalize()

Normalize the CFG, making sure that there are no overlapping basic blocks.

Note that this method will not alter transition graphs of each function in `self.kb.functions`. You may call `normalize()` on each Function object to normalize their transition graphs.

Returns

None

mark_function_alignments()

Find all potential function alignments and mark them.

Note that it is not always correct to simply remove them, because these functions may not be actual alignments but part of an actual function, and is incorrectly marked as an individual function because of failures in resolving indirect jumps. An example is in the test binary `x86_64/dir_gcc_-00 0x40541d` (indirect jump at `0x4051b0`). If the indirect jump cannot be correctly resolved, removing function `0x40541d` will cause a missing label failure in reassembler.

Returns

None

make_functions()

Revisit the entire control flow graph, create Function instances accordingly, and correctly put blocks into each function.

Although Function objects are created during the CFG recovery, they are neither sound nor accurate. With a pre-constructed CFG, this method rebuilds all functions bearing the following rules:

- A block may only belong to one function.
- Small functions lying inside the startpoint and the endpoint of another function will be merged with the other function
- Tail call optimizations are detected.
- PLT stubs are aligned by 16.

Returns

None

exception `angr.analyses.cfg.cfg_fast.ContinueScanningNotification`

Bases: `RuntimeError`

A notification raised by `_next_code_addr_core()` to indicate no code address is found and `_next_code_addr_core()` should be invoked again.

class `angr.analyses.cfg.cfg_fast.ARMDecodingMode`

Bases: `object`

Enums indicating decoding mode for ARM code.

ARM = 0

THUMB = 1

class `angr.analyses.cfg.cfg_fast.DecodingAssumption(addr, size, mode)`

Bases: `object`

Describes the decoding mode (ARM/THUMB) for a given basic block identified by its address.

Parameters

- **addr** (*int*) –
- **size** (*int*) –
- **mode** (*int*) –

__init__(*addr, size, mode*)

Parameters

- **addr** (*int*) –
- **size** (*int*) –
- **mode** (*int*) –

add_data_seg(*addr, size*)

Return type

`None`

Parameters

- **addr** (*int*) –
- **size** (*int*) –

class `angr.analyses.cfg.cfg_fast.FunctionReturn(callee_func_addr, caller_func_addr, call_site_addr, return_to)`

Bases: `object`

FunctionReturn describes a function call in a specific location and its return location. Hashable and equatable

__init__(*callee_func_addr, caller_func_addr, call_site_addr, return_to*)

callee_func_addr

caller_func_addr

call_site_addr

return_to

class `angr.analyses.cfg.cfg_fast.PendingJobs`(*functions*, *deregister_job_callback*)

Bases: `object`

A collection of pending jobs during CFG recovery.

__init__(*functions*, *deregister_job_callback*)

add_job(*job*)

pop_job(*returning=True*)

Pop a job from the pending jobs list.

When `returning == True`, we prioritize the jobs whose functions are known to be returning (`function.returning` is `True`). As an optimization, we are sorting the pending jobs list according to `job.function.returning`.

Parameters

returning (*bool*) – Only pop a pending job if the corresponding function returns.

Returns

A pending job if we can find one, or `None` if we cannot find any that satisfies the requirement.

Return type

`angr.analyses.cfg.cfg_fast.CFGJob`

cleanup()

Remove those pending exits if: a) they are the return exits of non-returning `SimProcedures` b) they are the return exits of non-returning syscalls b) they are the return exits of non-returning functions

Returns

`None`

add_returning_function(*func_addr*)

Mark a function as returning.

Parameters

func_addr (*int*) – Address of the function that returns.

Returns

`None`

add_nonreturning_function(*func_addr*)

Mark a function as not returning.

Parameters

func_addr (*int*) – Address of the function that does not return.

Returns

`None`

clear_updated_functions()

Clear the `updated_functions` set.

Returns

`None`

class `angr.analyses.cfg.cfg_fast.FunctionEdge`

Bases: `object`

Describes an edge in functions' transition graphs. Base class for all types of edges.

apply(*cfg*)

src_func_addr

stmt_idx

ins_addr

```
class angr.analyses.cfg.cfg_fast.FunctionTransitionEdge(src_node, dst_addr, src_func_addr,
                                                    to_outside=False, dst_func_addr=None,
                                                    stmt_idx=None, ins_addr=None,
                                                    is_exception=False)
```

Bases: [*FunctionEdge*](#)

Describes a transition edge in functions' transition graphs.

```
__init__(src_node, dst_addr, src_func_addr, to_outside=False, dst_func_addr=None, stmt_idx=None,
        ins_addr=None, is_exception=False)
```

src_node

dst_addr

to_outside

dst_func_addr

is_exception

apply(*cfg*)

```
class angr.analyses.cfg.cfg_fast.FunctionCallEdge(src_node, dst_addr, ret_addr, src_func_addr,
                                                syscall=False, stmt_idx=None, ins_addr=None)
```

Bases: [*FunctionEdge*](#)

Describes a call edge in functions' transition graphs.

```
__init__(src_node, dst_addr, ret_addr, src_func_addr, syscall=False, stmt_idx=None, ins_addr=None)
```

src_node

dst_addr

ret_addr

syscall

apply(*cfg*)

```
class angr.analyses.cfg.cfg_fast.FunctionFakeRetEdge(src_node, dst_addr, src_func_addr,
                                                    confirmed=None)
```

Bases: [*FunctionEdge*](#)

Describes a FakeReturn (also called fall-through) edge in functions' transition graphs.

```
__init__(src_node, dst_addr, src_func_addr, confirmed=None)
```

src_node

dst_addr

confirmed

apply(*cfg*)

class angr.analyses.cfg.cfg_fast.**FunctionReturnEdge**(*ret_from_addr, ret_to_addr, dst_func_addr*)

Bases: [FunctionEdge](#)

Describes a return (from a function call or a syscall) edge in functions' transition graphs.

__init__(*ret_from_addr, ret_to_addr, dst_func_addr*)

ret_from_addr

ret_to_addr

dst_func_addr

apply(*cfg*)

class angr.analyses.cfg.cfg_fast.**CFGJobType**(*value*)

Bases: [Enum](#)

Defines the type of work of a CFGJob

NORMAL = 0

FUNCTION_PROLOGUE = 1

COMPLETE_SCANNING = 2

IFUNC_HINTS = 3

DATAREF_HINTS = 4

class angr.analyses.cfg.cfg_fast.**CFGJob**(*addr, func_addr, jumpkind, ret_target=None, last_addr=None, src_node=None, src_ins_addr=None, src_stmt_idx=None, returning_source=None, syscall=False, func_edges=None, job_type=CFGJobType.NORMAL, gp=None*)

Bases: [object](#)

Defines a job to work on during the CFG recovery

Parameters

- **addr** (*int*) –
- **func_addr** (*int*) –
- **jumpkind** (*str*) –
- **ret_target** (*int* / *None*) –
- **last_addr** (*int* / *None*) –
- **src_node** ([CFGNode](#) / *None*) –
- **src_ins_addr** (*int* / *None*) –
- **src_stmt_idx** (*int* / *None*) –
- **syscall** (*bool*) –
- **func_edges** (*List* / *None*) –
- **job_type** ([CFGJobType](#)) –

- `gp(int | None)` –

```
__init__(addr, func_addr, jumpkind, ret_target=None, last_addr=None, src_node=None,
         src_ins_addr=None, src_stmt_idx=None, returning_source=None, syscall=False,
         func_edges=None, job_type=CFGJobType.NORMAL, gp=None)
```

Parameters

- `addr(int)` –
- `func_addr(int)` –
- `jumpkind(str)` –
- `ret_target(int | None)` –
- `last_addr(int | None)` –
- `src_node(CFGNode | None)` –
- `src_ins_addr(int | None)` –
- `src_stmt_idx(int | None)` –
- `syscall(bool)` –
- `func_edges(List | None)` –
- `job_type(CFGJobType)` –
- `gp(int | None)` –

`addr`

`func_addr`

`jumpkind`

`ret_target`

`last_addr`

`src_node`

`src_ins_addr`

`src_stmt_idx`

`returning_source`

`syscall`

`job_type`

`gp`

`add_function_edge(edge)`

`apply_function_edges(cfg, clear=False)`

```
class angr.analyses.cfg.cfg_fast.CFGFast(binary=None, objects=None, regions=None,
                                         pickle_intermediate_results=False, symbols=True,
                                         function_prologues=True, resolve_indirect_jumps=True,
                                         force_segment=False, force_smart_scan=True,
                                         force_complete_scan=False,
                                         indirect_jump_target_limit=100000, data_references=True,
                                         cross_references=False, normalize=False,
                                         start_at_entry=True, function_starts=None,
                                         extra_memory_regions=None,
                                         data_type_guessing_handlers=None, arch_options=None,
                                         indirect_jump_resolvers=None, base_state=None,
                                         exclude_sparse_regions=True, skip_specific_regions=True,
                                         heuristic_plt_resolving=None, detect_tail_calls=False,
                                         low_priority=False, cfb=None, model=None,
                                         elf_eh_frame=True, exceptions=True,
                                         skip_unmapped_addrs=True, nodecode_window_size=512,
                                         nodecode_threshold=0.3, nodecode_step=16483,
                                         indirect_calls_always_return=None,
                                         jumptable_resolver_resolves_calls=None, start=None,
                                         end=None, collect_data_references=None,
                                         extra_cross_references=None, **extra_arch_options)
```

Bases: [ForwardAnalysis](#)[[CFGNode](#), [CFGNode](#), [CFGJob](#), [int](#)], [CFGBase](#)

We find functions inside the given binary, and build a control-flow graph in very fast manners: instead of simulating program executions, keeping track of states, and performing expensive data-flow analysis, CFGFast will only perform light-weight analyses combined with some heuristics, and with some strong assumptions.

In order to identify as many functions as possible, and as accurate as possible, the following operation sequence is followed:

Active scanning

- If the binary has “function symbols” (TODO: this term is not accurate enough), they are starting points of the code scanning
- If the binary does not have any “function symbol”, we will first perform a function prologue scanning on the entire binary, and start from those places that look like function beginnings
- Otherwise, the binary’s entry point will be the starting point for scanning

Passive scanning

- After all active scans are done, we will go through the whole image and scan all code pieces

Due to the nature of those techniques that are used here, a base address is often not required to use this analysis routine. However, with a correct base address, CFG recovery will almost always yield a much better result. A custom analysis, called GirlScout, is specifically made to recover the base address of a binary blob. After the base address is determined, you may want to reload the binary with the new base address by creating a new Project object, and then re-recover the CFG.

```
PRINTABLES = b'0123456789abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ!"#$%&\n\r\t*+,-./:;<=>?@[\\]^_`{|}~ \t\n\r'
```

```
SPECIAL_THUNKS = {'AMD64':
```

```
{b'\xe8\x07\x00\x00\x00\xf3\x90\x0f\xae\xe8\xeb\xf9H\x89\x04$\xc3': ('jmp', 'rax'),
b'\xe8\x07\x00\x00\x00\xf3\x90\x0f\xae\xe8\xeb\xf9H\x8dd$\x08\xc3': ('ret', )}}
```

```
tag: Optional[str] = 'CFGFast'
```

```
__init__(binary=None, objects=None, regions=None, pickle_intermediate_results=False, symbols=True,
        function_prologues=True, resolve_indirect_jumps=True, force_segment=False,
        force_smart_scan=True, force_complete_scan=False, indirect_jump_target_limit=100000,
        data_references=True, cross_references=False, normalize=False, start_at_entry=True,
        function_starts=None, extra_memory_regions=None, data_type_guessing_handlers=None,
        arch_options=None, indirect_jump_resolvers=None, base_state=None,
        exclude_sparse_regions=True, skip_specific_regions=True, heuristic_plt_resolving=None,
        detect_tail_calls=False, low_priority=False, cfb=None, model=None, elf_eh_frame=True,
        exceptions=True, skip_unmapped_addrs=True, nodecode_window_size=512,
        nodecode_threshold=0.3, nodecode_step=16483, indirect_calls_always_return=None,
        jumptable_resolver_resolves_calls=None, start=None, end=None, collect_data_references=None,
        extra_cross_references=None, **extra_arch_options)
```

Parameters

- **binary** – The binary to recover CFG on. By default the main binary is used.
- **objects** – A list of objects to recover the CFG on. By default it will recover the CFG of all loaded objects.
- **regions** (*iterable*) – A list of tuples in the form of (start address, end address) describing memory regions that the CFG should cover.
- **pickle_intermediate_results** (*bool*) – If we want to store the intermediate results or not.
- **symbols** (*bool*) – Get function beginnings from symbols in the binary.
- **function_prologues** (*bool*) – Scan the binary for function prologues, and use those positions as function beginnings
- **resolve_indirect_jumps** (*bool*) – Try to resolve indirect jumps. This is necessary to resolve jump targets from jump tables, etc.
- **force_segment** (*bool*) – Force CFGFast to rely on binary segments instead of sections.
- **force_complete_scan** (*bool*) – Perform a complete scan on the binary and maximize the number of identified code blocks.
- **data_references** (*bool*) – Enables the collection of references to data used by individual instructions. This does not collect ‘cross-references’, particularly those that involve multiple instructions. For that, see *cross_references*
- **cross_references** (*bool*) – Whether CFGFast should collect “cross-references” from the entire program or not. This will populate the knowledge base with references to and from each recognizable address constant found in the code. Note that, because this performs constant propagation on the entire program, it may be much slower and consume more memory. This option implies *data_references=True*.
- **normalize** (*bool*) – Normalize the CFG as well as all function graphs after CFG recovery.
- **start_at_entry** (*bool*) – Begin CFG recovery at the entry point of this project. Setting it to False prevents CFGFast from viewing the entry point as one of the starting points of code scanning.
- **function_starts** (*list*) – A list of extra function starting points. CFGFast will try to resume scanning from each address in the list.
- **extra_memory_regions** (*list*) – A list of 2-tuple (start-address, end-address) that shows extra memory regions. Integers falling inside will be considered as pointers.

- **indirect_jump_resolvers** (*list*) – A custom list of indirect jump resolvers. If this list is None or empty, default indirect jump resolvers specific to this architecture and binary types will be loaded.
- **base_state** – A state to use as a backer for all memory loads
- **detect_tail_calls** (*bool*) – Enable aggressive tail-call optimization detection.
- **elf_eh_frame** (*bool*) – Retrieve function starts (and maybe sizes later) from the .eh_frame of ELF binaries.
- **skip_unmapped_addrs** – Ignore all branches into unmapped regions. True by default. You may want to set it to False if you are analyzing manually patched binaries or malware samples.
- **indirect_calls_always_return** (*Optional[bool]*) – Should CFG assume indirect calls must return or not. Assuming indirect calls must return will significantly reduce the number of constant propagation runs, but may reduce the overall CFG recovery precision when facing non-returning indirect calls. By default, we only assume indirect calls always return for large binaries (region > 50KB).
- **jumptable_resolver_resolves_calls** (*Optional[bool]*) – Whether JumpTableResolver should resolve indirect calls or not. Most indirect calls in C++ binaries or UEFI binaries cannot be resolved using jump table resolver and must be resolved using their specific resolvers. By default, we will only disable JumpTableResolver from resolving indirect calls for large binaries (region > 50 KB).
- **start** (*int*) – (Deprecated) The beginning address of CFG recovery.
- **end** (*int*) – (Deprecated) The end address of CFG recovery.
- **arch_options** (*CFGArchOptions*) – Architecture-specific options.
- **extra_arch_options** (*dict*) – Any key-value pair in kwargs will be seen as an arch-specific option and will be used to set the option value in self._arch_options.

Extra parameters that angr.Analysis takes:

Parameters

- **progress_callback** – Specify a callback function to get the progress during CFG recovery.
- **show_progressbar** (*bool*) – Should CFGFast show a progressbar during CFG recovery or not.
- **indirect_calls_always_return** (*bool | None*) –
- **jumptable_resolver_resolves_calls** (*bool | None*) –

Returns

None

property graph

property memory_data

property jump_tables

property insn_addr_to_memory_data

do_full_xrefs(*overlay_state=None*)

Perform xref recovery on all functions.

Parameters

overlay (*SimState*) – An overlay state for loading constant data.

Returns

None

copy()

indirect_jumps: Dict[int, IndirectJump]

project: Project

kb: KnowledgeBase

output()

generate_code_cover(***kwargs*)

class angr.analyses.cfg.cfg_arch_options.CFGArchOptions(*arch, **options*)

Bases: *object*

Stores architecture-specific options and settings, as well as the detailed explanation of those options and settings.

Suppose *ao* is the CFGArchOptions object, and there is an option called *ret_jumpkind_heuristics*, you can access it by *ao.ret_jumpkind_heuristics* and set its value via *ao.ret_jumpkind_heuristics = True*

Variables

- **OPTIONS** (*dict*) – A dict of all default options for different architectures.
- **arch** (*archinfo.Arch*) – The architecture object.
- **_options** (*dict*) – Values of all CFG options that are specific to the current architecture.

```
OPTIONS = {'ARMCortexM': {'pattern_match_ifuncs': (<class 'bool'>, True),
'ret_jumpkind_heuristics': (<class 'bool'>, True), 'switch_mode_on_nodect':
(<class 'bool'>, False)}, 'ARMEL': {'pattern_match_ifuncs': (<class 'bool'>, True),
'ret_jumpkind_heuristics': (<class 'bool'>, True), 'switch_mode_on_nodect':
(<class 'bool'>, True)}, 'ARMHF': {'pattern_match_ifuncs': (<class 'bool'>, True),
'ret_jumpkind_heuristics': (<class 'bool'>, True), 'switch_mode_on_nodect':
(<class 'bool'>, True)}}
```

__init__(*arch, **options*)

Constructor.

Parameters

- **arch** (*archinfo.Arch*) – The architecture instance.
- **options** (*dict*) – Architecture-specific options, which will be used to initialize this object.

arch = None

class angr.analyses.cfg.cfg_job_base.BlockID(*addr, callsite_tuples, jump_type*)

Bases: *object*

A context-sensitive key for a SimRun object.

__init__(*addr, callsite_tuples, jump_type*)

callsite_repr()

static new(*addr*, *callstack_suffix*, *jumpkind*)

property func_addr

class `angr.analyses.cfg.cfg_job_base.FunctionKey`(*addr*, *callsite_tuples*)

Bases: `object`

A context-sensitive key for a function.

__init__(*addr*, *callsite_tuples*)

callsite_repr()

static new(*addr*, *callsite_tuples*)

class `angr.analyses.cfg.cfg_job_base.CFGJobBase`(*addr*, *state*, *context_sensitivity_level*, *block_id=None*, *src_block_id=None*, *src_exit_stmt_idx=None*, *src_ins_addr=None*, *jumpkind=None*, *call_stack=None*, *is_narrowing=False*, *skip=False*, *final_return_address=None*)

Bases: `object`

Describes an entry in CFG or VFG. Only used internally by the analysis.

Parameters

- **state** (`SimState`) –
- **jumpkind** (`str` | `None`) –

__init__(*addr*, *state*, *context_sensitivity_level*, *block_id=None*, *src_block_id=None*, *src_exit_stmt_idx=None*, *src_ins_addr=None*, *jumpkind=None*, *call_stack=None*, *is_narrowing=False*, *skip=False*, *final_return_address=None*)

Parameters

- **state** (`SimState`) –
- **jumpkind** (`str` | `None`) –

property call_stack

call_stack_copy()

get_call_stack_suffix()

property func_addr

property current_stack_pointer

class `angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got.AMD64ElfGotResolver`(*project*)

Bases: `IndirectJumpResolver`

A timeless indirect jump resolver that resolves GOT entries on AMD64 ELF binaries.

__init__(*project*)

filter(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

`bool`

resolve(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*, *func_graph_complete=True*, ***kwargs*)

Resolve an indirect jump.

Parameters

- **cfg** – The CFG analysis object.
- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.
- **func_graph_complete** (*bool*) – True if the function graph is complete at this point (except for nodes that this indirect jump node dominates).

Returns

A tuple of a boolean indicating whether the resolution is successful or not, and a list of resolved targets (ints).

Return type

`tuple`

class `angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast.ArmElfFastResolver`(*project*)

Bases: `IndirectJumpResolver`

Resolves indirect jumps in ARM ELF binaries

__init__(*project*)

filter(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.

- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

bool

resolve(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*, *func_graph_complete=True*, ***kwargs*)

The main resolving function.

Parameters

- **cfg** – A CFG instance.
- **addr** (*int*) – Address of the IRSB.
- **func_addr** (*int*) – Address of the function.
- **block** – The IRSB.
- **jumpkind** (*str*) – The jumpkind.
- **func_graph_complete** (*bool*) –

Returns

Return type

tuple

class `angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat.X86PeIatResolver`(*project*)

Bases: *IndirectJumpResolver*

A timeless indirect jump resolver for IAT in x86 PEs.

__init__(*project*)

filter(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

bool

resolve(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*, *func_graph_complete=True*, ***kwargs*)

Resolve an indirect jump.

Parameters

- **cfg** – The CFG analysis object.

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.
- **func_graph_complete** (*bool*) – True if the function graph is complete at this point (except for nodes that this indirect jump node dominates).

Returns

A tuple of a boolean indicating whether the resolution is successful or not, and a list of resolved targets (ints).

Return type

`tuple`

`angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.enable_profiling()`

`angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.disable_profiling()`

class `angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.OverwriteTmpValueCallback(gp_value)`

Bases: `object`

Overwrites temporary values during resolution

`__init__(gp_value)`

`overwrite_tmp_value(state)`

class `angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.MipsElfFastResolver(project)`

Bases: `IndirectJumpResolver`

A timeless indirect jump resolver for R9-based indirect function calls in MIPS ELFs.

`__init__(project)`

filter(*cfg, addr, func_addr, block, jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

`bool`

resolve(*cfg, addr, func_addr, block, jumpkind, func_graph_complete=True, **kwargs*)

Wrapper for `_resolve` that slowly increments the `max_depth` used by `Blade` for finding sources until we can resolve the `addr` or we reach the default `max_depth`

Parameters

- **cfg** – A CFG instance.
- **addr** (*int*) – IRSB address.
- **func_addr** (*int*) – The function address.
- **block** (*pyvex.IRSB*) – The IRSB.
- **jumpkind** (*str*) – The jumpkind.
- **func_graph_complete** (*bool*) –

Returns

If it was resolved and targets alongside it

Return type

tuple

class `angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic_plt.X86ElfPicPltResolver`(*project*)

Bases: *IndirectJumpResolver*

In X86 ELF position-independent code, PLT stubs uses ebx to resolve library calls, where ebx stores the address to the beginning of the GOT. We resolve the target by forcing ebx to be the beginning of the GOT and simulate the execution in fast path mode.

__init__(*project*)

filter(*cfg, addr, func_addr, block, jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's *pyvex.IRSB* if *pyvex* is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

bool

resolve(*cfg, addr, func_addr, block, jumpkind, func_graph_complete=True, **kwargs*)

Resolve an indirect jump.

Parameters

- **cfg** – The CFG analysis object.
- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's *pyvex.IRSB* if *pyvex* is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

- **func_graph_complete** (*bool*) – True if the function graph is complete at this point (except for nodes that this indirect jump node dominates).

Returns

A tuple of a boolean indicating whether the resolution is successful or not, and a list of resolved targets (*ints*).

Return type

tuple

`angr.analyses.cfg.indirect_jump_resolvers.default_resolvers.default_indirect_jump_resolvers`(*obj*, *project*)

exception `angr.analyses.cfg.indirect_jump_resolvers.jumptable.NotAJumpTableNotification`

Bases: *AngrError*

Exception raised to indicate this is not (or does not appear to be) a jump table.

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.UninitReadMeta`

Bases: *object*

Uninitialized read remapping details.

uninit_read_base = 201326592

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTransformationTypes`(*value*)

Bases: *int*, *Enum*

Address transformation operations.

Assignment = 0

SignedExtension = 1

UnsignedExtension = 2

Truncation = 3

Or1 = 4

ShiftLeft = 5

ShiftRight = 6

Add = 7

Load = 8

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTransformation`(*op*, *operands*, *first_load=False*)

Bases: *object*

Describe and record an address transformation operation.

Parameters

- **op** (*AddressTransformationTypes*) –
- **operands** (*List*) –
- **first_load** (*bool*) –


```
__init__(op, operands, first_load=False)
```

Parameters

- **op** (*AddressTransformationTypes*) –
- **operands** (*List*) –
- **first_load** (*bool*) –

```
class angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressOperand
```

Bases: *object*

The class for the singleton class AddressSingleton. It represents the address being transformed before using as an indirect jump target.

```
class angr.analyses.cfg.indirect_jump_resolvers.jumptable.Tmp(tmp_idx)
```

Bases: *object*

For modeling Tmp variables.

```
__init__(tmp_idx)
```

```
class angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTargetBaseAddr(stmt_loc, stmt,  
                                                                           tmp,  
                                                                           base_addr=None,  
                                                                           tmp_l=None)
```

Bases: *object*

Model for jump targets and their data origin.

```
__init__(stmt_loc, stmt, tmp, base_addr=None, tmp_l=None)
```

property base_addr_available

```
class angr.analyses.cfg.indirect_jump_resolvers.jumptable.ConstantValueManager(project, kb,  
                                                                           func)
```

Bases: *object*

Manages the loading of registers who hold constant values.

Parameters

func (*Function*) –

```
__init__(project, kb, func)
```

Parameters

func (*Function*) –

project

kb

func

mapping

reg_read_callback(*state*)

Parameters

state (*SimState*) –

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableProcessorState(arch)`

Bases: `object`

The state used in JumpTableProcessor.

__init__(*arch*)

arch

is_jumptable

stmts_to_instrument

regs_to_initialize

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.RegOffsetAnnotation(reg_offset)`

Bases: `Annotation`

Register Offset annotation.

Parameters

reg_offset (`RegisterOffset`) –

__init__(*reg_offset*)

Parameters

reg_offset (`RegisterOffset`) –

reg_offset

property relocatable

Returns whether this annotation can be relocated in a simplification.

Returns

True if it can be relocated, false otherwise.

property eliminatable

Returns whether this annotation can be eliminated in a simplification.

Returns

True if eliminatable, False otherwise

class `angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableProcessor(project, indirect_jump_node_pred_addrs, bp_sp_diff=256)`

Bases: `SimEngineLightVEXMixin`, `SimEngineLight`

Implements a simple and stupid data dependency tracking for stack and register variables.

Also determines which statements to instrument during static execution of the slice later. For example, the following example is not uncommon in non-optimized binaries:

```

    mov    [rbp+var_54], 1
loc_4051a6:
    cmp    [rbp+var_54], 6
    ja     loc_405412 (default)
loc_4051b0:
    mov    eax, [rbp+var_54]
    mov    rax, qword [rax*8+0x223a01]
    jmp    rax

```

We want to instrument the first instruction and replace the constant 1 with a symbolic variable, otherwise we will not be able to recover all jump targets later in block 0x4051b0.

Parameters

indirect_jump_node_pred_addrs (*Set[int]*) –

__init__(*project, indirect_jump_node_pred_addrs, bp_sp_diff=256*)

Parameters

indirect_jump_node_pred_addrs (*Set[int]*) –

class `angr.analyses.cfg.indirect_jump_resolvers.jumtable.StoreHook`

Bases: `object`

Hook for memory stores.

static hook(*state*)

class `angr.analyses.cfg.indirect_jump_resolvers.jumtable.LoadHook`

Bases: `object`

Hook for memory loads.

__init__()

hook_before(*state*)

hook_after(*state*)

class `angr.analyses.cfg.indirect_jump_resolvers.jumtable.PutHook`

Bases: `object`

Hook for register writes.

static hook(*state*)

class `angr.analyses.cfg.indirect_jump_resolvers.jumtable.RegisterInitializerHook`(*reg_offset,*
reg_bits,
value)

Bases: `object`

Hook for register init.

__init__(*reg_offset, reg_bits, value*)

hook(*state*)

class `angr.analyses.cfg.indirect_jump_resolvers.jumtable.BSSHook`(*project, bss_regions*)

Bases: `object`

Hook for BSS read/write.

__init__(*project, bss_regions*)

bss_memory_read_hook(*state*)

bss_memory_write_hook(*state*)

`class angr.analyses.cfg.indirect_jump_resolvers.jumptable.MIPSGPHook(gp_offset, gp)`

Bases: `object`

Hooks all reads from and writes into the gp register for MIPS32 binaries.

Parameters

- `gp_offset` (*int*) –
- `gp` (*int*) –

`__init__(gp_offset, gp)`

Parameters

- `gp_offset` (*int*) –
- `gp` (*int*) –

`gp_register_read_hook(state)`

`gp_register_write_hook(state)`

`class angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableResolver(project, resolve_calls=True)`

Bases: `IndirectJumpResolver`

A generic jump table resolver.

This is a fast jump table resolution. For performance concerns, we made the following assumptions:

- The final jump target comes from the memory.
- The final jump target must be directly read out of the memory, without any further modification or altering.

Progressively larger program slices will be analyzed to determine jump table location and size. If the size of the table cannot be determined, a *guess* will be made based on how many entries in the table *appear* valid.

Parameters

`resolve_calls` (*bool*) –

`__init__(project, resolve_calls=True)`

Parameters

`resolve_calls` (*bool*) –

`filter(cfg, addr, func_addr, block, jumpkind)`

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- `addr` (*int*) – Basic block address of this indirect jump.
- `func_addr` (*int*) – Address of the function that this indirect jump belongs to.
- `block` – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- `jumpkind` (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

`bool`

resolve(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*, *func_graph_complete*=*True*, ***kwargs*)

Resolves jump tables.

Parameters

- **cfg** – A CFG instance.
- **addr** (*int*) – IRSB address.
- **func_addr** (*int*) – The function address.
- **block** (*pyvex.IRSB*) – The IRSB.
- **func_graph_complete** (*bool*) –

Returns

A bool indicating whether the indirect jump is resolved successfully, and a list of resolved targets

Return type

`tuple`

`angr.analyses.cfg.indirect_jump_resolvers.const_resolver.exists_in_replacements`(*replacements*,
block_loc,
tmp_var)

class `angr.analyses.cfg.indirect_jump_resolvers.const_resolver.ConstantResolver`(*project*)

Bases: `IndirectJumpResolver`

Resolve an indirect jump by running a constant propagation on the entire function and check if the indirect jump can be resolved to a constant value. This resolver must be run after all other more specific resolvers.

__init__(*project*)

filter(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*)

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's `pyvex.IRSB` if `pyvex` is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

`bool`

resolve(*cfg*, *addr*, *func_addr*, *block*, *jumpkind*, *func_graph_complete*=*True*, ***kwargs*)

This function does the actual resolve. Our process is easy: Propagate all values inside the function specified, then extract the `tmp_var` used for the indirect jump from the basic block. Use the `tmp_var` to locate the constant value stored in the `replacements`. If not present, returns False tuple.

Parameters

- **cfg** – CFG with specified function
- **addr** (*int*) – Address of indirect jump
- **func_addr** (*int*) – Address of function of indirect jump
- **block** (*Block*) – Block of indirect jump (Block object)
- **jumpkind** (*str*) – VEX jumpkind (Ijk_Boring or Ijk_Call)
- **func_graph_complete** (*bool*) –

Returns

Bool tuple with replacement address

```
class angr.analyses.cfg.indirect_jump_resolvers.resolver.IndirectJumpResolver(project, timeless=False, base_state=None)
```

Bases: *object*

```
__init__(project, timeless=False, base_state=None)
```

```
filter(cfg, addr, func_addr, block, jumpkind)
```

Check if this resolution method may be able to resolve the indirect jump or not.

Parameters

- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's *pyvex.IRSB* if *pyvex* is used as the backend.
- **jumpkind** (*str*) – The jumpkind.

Returns

True if it is possible for this resolution method to resolve the specific indirect jump, False otherwise.

Return type

bool

```
resolve(cfg, addr, func_addr, block, jumpkind, func_graph_complete=True, **kwargs)
```

Resolve an indirect jump.

Parameters

- **cfg** – The CFG analysis object.
- **addr** (*int*) – Basic block address of this indirect jump.
- **func_addr** (*int*) – Address of the function that this indirect jump belongs to.
- **block** – The basic block. The type is determined by the backend being used. It's *pyvex.IRSB* if *pyvex* is used as the backend.
- **jumpkind** (*str*) – The jumpkind.
- **func_graph_complete** (*bool*) – True if the function graph is complete at this point (except for nodes that this indirect jump node dominates).

Returns

A tuple of a boolean indicating whether the resolution is successful or not, and a list of resolved targets (*ints*).

Return type

tuple

```
class angr.analyses.cfg.cfg_fast_soot.CFGFastSoot(support_jni=False, **kwargs)
```

Bases: *CFGFast*

```
__init__(support_jni=False, **kwargs)
```

Parameters

- **binary** – The binary to recover CFG on. By default the main binary is used.
- **objects** – A list of objects to recover the CFG on. By default it will recover the CFG of all loaded objects.
- **regions** (*iterable*) – A list of tuples in the form of (start address, end address) describing memory regions that the CFG should cover.
- **pickle_intermediate_results** (*bool*) – If we want to store the intermediate results or not.
- **symbols** (*bool*) – Get function beginnings from symbols in the binary.
- **function_prologues** (*bool*) – Scan the binary for function prologues, and use those positions as function beginnings
- **resolve_indirect_jumps** (*bool*) – Try to resolve indirect jumps. This is necessary to resolve jump targets from jump tables, etc.
- **force_segment** (*bool*) – Force CFGFast to rely on binary segments instead of sections.
- **force_complete_scan** (*bool*) – Perform a complete scan on the binary and maximize the number of identified code blocks.
- **data_references** (*bool*) – Enables the collection of references to data used by individual instructions. This does not collect ‘cross-references’, particularly those that involve multiple instructions. For that, see *cross_references*
- **cross_references** (*bool*) – Whether CFGFast should collect “cross-references” from the entire program or not. This will populate the knowledge base with references to and from each recognizable address constant found in the code. Note that, because this performs constant propagation on the entire program, it may be much slower and consume more memory. This option implies *data_references=True*.
- **normalize** (*bool*) – Normalize the CFG as well as all function graphs after CFG recovery.
- **start_at_entry** (*bool*) – Begin CFG recovery at the entry point of this project. Setting it to False prevents CFGFast from viewing the entry point as one of the starting points of code scanning.
- **function_starts** (*list*) – A list of extra function starting points. CFGFast will try to resume scanning from each address in the list.
- **extra_memory_regions** (*list*) – A list of 2-tuple (start-address, end-address) that shows extra memory regions. Integers falling inside will be considered as pointers.
- **indirect_jump_resolvers** (*list*) – A custom list of indirect jump resolvers. If this list is None or empty, default indirect jump resolvers specific to this architecture and binary types will be loaded.
- **base_state** – A state to use as a backer for all memory loads
- **detect_tail_calls** (*bool*) – Enable aggressive tail-call optimization detection.

- **elf_eh_frame** (*bool*) – Retrieve function starts (and maybe sizes later) from the .eh_frame of ELF binaries.
- **skip_unmapped_addrs** – Ignore all branches into unmapped regions. True by default. You may want to set it to False if you are analyzing manually patched binaries or malware samples.
- **indirect_calls_always_return** – Should CFG assume indirect calls must return or not. Assuming indirect calls must return will significantly reduce the number of constant propagation runs, but may reduce the overall CFG recovery precision when facing non-returning indirect calls. By default, we only assume indirect calls always return for large binaries (region > 50KB).
- **jumptable_resolver_resolves_calls** – Whether JumpTableResolver should resolve indirect calls or not. Most indirect calls in C++ binaries or UEFI binaries cannot be resolved using jump table resolver and must be resolved using their specific resolvers. By default, we will only disable JumpTableResolver from resolving indirect calls for large binaries (region > 50 KB).
- **start** (*int*) – (Deprecated) The beginning address of CFG recovery.
- **end** (*int*) – (Deprecated) The end address of CFG recovery.
- **arch_options** (*CFGArchOptions*) – Architecture-specific options.
- **extra_arch_options** (*dict*) – Any key-value pair in kwargs will be seen as an arch-specific option and will be used to set the option value in self._arch_options.

Extra parameters that `angr.Analysis` takes:

Parameters

- **progress_callback** – Specify a callback function to get the progress during CFG recovery.
- **show_progressbar** (*bool*) – Should CFGFast show a progressbar during CFG recovery or not.

Returns

None

normalize()

Normalize the CFG, making sure that there are no overlapping basic blocks.

Note that this method will not alter transition graphs of each function in `self.kb.functions`. You may call `normalize()` on each Function object to normalize their transition graphs.

Returns

None

make_functions()

Revisit the entire control flow graph, create Function instances accordingly, and correctly put blocks into each function.

Although Function objects are created during the CFG recovery, they are neither sound nor accurate. With a pre-constructed CFG, this method rebuilds all functions bearing the following rules:

- A block may only belong to one function.
- Small functions lying inside the startpoint and the endpoint of another function will be merged with the other function
- Tail call optimizations are detected.

- PLT stubs are aligned by 16.

Returns

None

indirect_jumps: Dict[int, IndirectJump]

project: Project

kb: KnowledgeBase

class `angr.analyses.cdg.CDG`(*cfg*, *start=None*, *no_construct=False*)

Bases: `Analysis`

Implements a control dependence graph.

__init__(*cfg*, *start=None*, *no_construct=False*)

Constructor.

Parameters

- **cfg** – The control flow graph upon which this control dependence graph will build
- **start** – The starting point to begin constructing the control dependence graph
- **no_construct** – Skip the construction step. Only used in unit-testing.

property graph

get_post_dominators()

Return the post-dom tree

get_dependants(*run*)

Return a list of nodes that are control dependent on the given node in the control dependence graph

get_guardians(*run*)

Return a list of nodes on whom the specific node is control dependent in the control dependence graph

project: Project

kb: KnowledgeBase

exception `angr.analyses.datagraph_meta.DataGraphError`

Bases: `Exception`

class `angr.analyses.datagraph_meta.DataGraphMeta`

Bases: `object`

__init__()

get_irsb_at(*addr*)

pp(*imarks=False*)

Pretty print the graph. @imarks determine whether the printed graph represents instructions (coarse grained) for easier navigation, or exact statements.

class `angr.analyses.code_tagging.CodeTags`

Bases: `object`

HAS_XOR = 'HAS_XOR'

HAS_BITSHIFTS = 'HAS_BITSHIFTS'

HAS_SQL = 'HAS_SQL'

LARGE_SWITCH = 'LARGE_SWITCH'

class `angr.analyses.code_tagging.CodeTagging(func)`

Bases: `Analysis`

__init__(func)

analyze()

has_xor()

Detects if there is any xor operation in the function.

Returns

Tags

has_bitshifts()

Detects if there is any bitwise operation in the function.

Returns

Tags.

has_sql()

Detects if there is any reference to strings that look like SQL queries.

project: `Project`

kb: `KnowledgeBase`

class `angr.angrdb.db.AngrDB(project=None)`

Bases: `object`

AngrDB provides a storage solution for an angr project, its knowledge bases, and some other types of data. It is designed to use an SQL-based database as the storage backend.

ALL_TABLES = ['objects']

VERSION = 1

__init__(project=None)

static `open_db(db_str='sqlite:///memory:')`

static `session_scope(Session)`

static `save_info(session, key, value)`

Save an information entry to the database.

Parameters

- **session** –
- **key** –
- **value** –

Returns

static `get_info(session, key)`

Get an information entry from the database.

Parameters

- **session** –
- **key** –

Returns

`update_dbinfo(session, extra_info=None)`

Update the information in database.

Parameters

- **session** –
- **extra_info** (`Dict[str, str]` | `None`) –

Returns

`get_dbinfo(session, extra_info=None)`

Get database information.

Parameters

- **session** –
- **extra_info** (`Dict[str, str]` | `None`) –

Returns

A dict of information entries.

`db_compatible(version)`

Checks if the given database version is compatible with the current AngrDB class.

Parameters

version (`int`) – The version of the database.

Returns

True if compatible, False otherwise.

Return type

`bool`

`dump(db_path, kbs=None, extra_info=None)`

Parameters

- **kbs** (`List[KnowledgeBase]` | `None`) –
- **extra_info** (`Dict[str, Any]` | `None`) –

`load(db_path, kb_names=None, other_kbs=None, extra_info=None)`

Parameters

- **db_path** (`str`) –
- **kb_names** (`List[str]` | `None`) –
- **other_kbs** (`Dict[str, KnowledgeBase]` | `None`) –
- **extra_info** (`Dict[str, Any]` | `None`) –

class `angr.angrdb.models.DbInformation(**kwargs)`

Bases: `Base`

Stores information related to the current database. Basically a key-value store.

id

key

value

__init__(**kwargs)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class `angr.angrdb.models.DbObject(**kwargs)`

Bases: `Base`

Models a binary object.

id

main_object

path

content

backend

backend_args

__init__(**kwargs)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class `angr.angrdb.models.DbKnowledgeBase(**kwargs)`

Bases: `Base`

Models a knowledge base.

id

name

cfgs

funcs

xrefs

comments

labels

var_collections

structured_code

__init__(**kwargs)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.angrdb.models.DbCFGModel(**kwargs)

Bases: Base

Models a CFGFast instance.

id

kb_id

kb

ident

blob

__init__(**kwargs)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.angrdb.models.DbFunction(**kwargs)

Bases: Base

Models a Function instance.

id

kb_id

kb

addr

blob

__init__(**kwargs)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.angrdb.models.DbVariableCollection(**kwargs)

Bases: Base

Models a VariableManagerInternal instance.

id

kb_id

kb

func_addr

ident

blob

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class `angr.angrdb.models.DbStructuredCode`(***kwargs*)

Bases: `Base`

Models a `StructuredCode` instance.

id

kb_id

kb

func_addr

flavor

expr_comments

stmt_comments

configuration

const_formats

ite_exprs

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in kwargs.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class `angr.angrdb.models.DbXRefs`(***kwargs*)

Bases: `Base`

Models an `XRefManager` instance.

id

kb_id

kb

blob

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in **kwargs**.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.angrdb.models.**DbComment**(***kwargs*)

Bases: Base

Models a comment.

id

kb_id

kb

addr

comment

type

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in **kwargs**.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class angr.angrdb.models.**DbLabel**(***kwargs*)

Bases: Base

Models a label.

id

kb_id

kb

addr

name

__init__(***kwargs*)

A simple constructor that allows initialization from kwargs.

Sets attributes on the constructed instance using the names and values in **kwargs**.

Only keys that are present as attributes of the instance's class are allowed. These could be, for example, any mapped columns or relationships.

class `angr.angrdb.serializers.cfg_model.CFGModelSerializer`

Bases: `object`

Serialize/unserialize a CFGModel.

static dump(*session, db_kb, ident, cfg_model*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) – The database object for KnowledgeBase.
- **ident** (`str`) – Identifier of the CFG model.
- **cfg_model** (`CFGModel`) – The CFG model to dump.

Returns

None

static load(*session, db_kb, ident, cfg_manager, loader=None*)

class `angr.angrdb.serializers.comments.CommentsSerializer`

Bases: `object`

Serialize/unserialize comments to/from a database session.

static dump(*session, db_kb, comments*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) –
- **comments** (`Comments`) –

Returns

None

static load(*session, db_kb, kb*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) –
- **kb** (`KnowledgeBase`) –

Returns

class `angr.angrdb.serializers.funcs.FunctionManagerSerializer`

Bases: `object`

Serialize/unserialize a function manager and its functions.

static dump(*session, db_kb, func_manager*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) –
- **func_manager** (`FunctionManager`) –

Returns

static load(*session*, *db_kb*, *kb*)

Parameters

- **session** –
- **db_kb** (*DbKnowledgeBase*) –
- **kb** (*KnowledgeBase*) –

Returns

A loaded function manager.

class `angr.angrdb.serializers.kb.KnowledgeBaseSerializer`

Bases: *object*

Serialize/unserialize a KnowledgeBase object.

static dump(*session*, *kb*)

Parameters

- **session** – The database session object.
- **kb** (*KnowledgeBase*) – The KnowledgeBase instance to serialize.

Returns

None

static load(*session*, *project*, *name*)

Parameters

session –

Returns

class `angr.angrdb.serializers.labels.LabelsSerializer`

Bases: *object*

Serialize/unserialize labels to/from a database session.

static dump(*session*, *db_kb*, *labels*)

Parameters

- **session** –
- **db_kb** (*DbKnowledgeBase*) –
- **labels** (*Labels*) –

Returns

None

static load(*session*, *db_kb*, *kb*)

Parameters

- **session** –
- **db_kb** (*DbKnowledgeBase*) –
- **kb** (*KnowledgeBase*) –

Returns

class `angr.angrdb.serializers.loader.LoaderSerializer`

Bases: `object`

Serialize/unserialize a CLE Loader object into/from an angr DB.

```
backend2name = {<class 'cle.backends.blob.Blob'>: 'blob', <class
'cle.backends.elf.elf.ELF'>: 'elf', <class 'cle.backends.elf.elfcore.ELFCore'>:
'elfcore', <class 'cle.backends.cgc.cgc.CGC'>: 'cgc', <class
'cle.backends.cgc.backedcgc.BackedCGC'>: 'backedcgc', <class
'cle.backends.coff.Coff'>: 'COFF', <class 'cle.backends.ihex.Hex'>: 'hex', <class
'cle.backends.java.apk.Apk'>: 'apk', <class 'cle.backends.java.jar.Jar'>: 'jar',
<class 'cle.backends.macho.macho.MachO'>: 'mach-o', <class
'cle.backends.minidump.Minidump'>: 'minidump', <class
'cle.backends.named_region.NamedRegion'>: 'named_region', <class
'cle.backends.pe.pe.PE'>: 'pe', <class 'cle.backends.srec.SRec'>: 'srec', <class
'cle.backends.static_archive.StaticArchive'>: 'AR', <class 'cle.backends.te.TE'>:
'te', <class 'cle.backends.uefi_firmware.UefiFirmware'>: 'uefi', <class
'cle.backends.xbe.XBE'>: 'xbe'}
```

static dump(*session, loader*)

static load(*session*)

class `angr.angrdb.serializers.xrefs.XRefsSerializer`

Bases: `object`

Serialize/unserialize an XRefs object to/from a database session.

static dump(*session, db_kb, xrefs*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) –
- **xrefs** (`XRefManager`) –

Returns

static load(*session, db_kb, kb, cfg_model=None*)

Parameters

- **session** –
- **db_kb** (`DbKnowledgeBase`) –
- **kb** (`KnowledgeBase`) –
- **cfg_model** (`CFGModel`) –

Returns

class `angr.angrdb.serializers.variables.VariableManagerSerializer`

Bases: `object`

Serialize/unserialize a variable manager and its variables.

static dump(*session, db_kb, var_manager*)

Parameters

- **db_kb** (`DbKnowledgeBase`) –

```

    • var_manager (VariableManager) –
static dump_internal(session, db_kb, internal_manager, func_addr, ident=None)

Parameters
    • db_kb (DbKnowledgeBase) –
    • internal_manager (VariableManagerInternal) –
    • func_addr (int) –
static load(session, db_kb, kb, ident=None)

Parameters
    • db_kb (DbKnowledgeBase) –
    • kb (KnowledgeBase) –
static load_internal(db_varcoll, variable_manager)

Return type
    VariableManagerInternal

Parameters
    • variable_manager (VariableManager) –
class angr.angrdb.serializers.structured_code.StructuredCodeManagerSerializer
Bases: object
Serialize/unserialize a structured code manager.
static dump(session, db_kb, code_manager)

Parameters
    • session –
    • db_kb (DbKnowledgeBase) –
    • code_manager (StructuredCodeManager) –

Returns
static dict_strkey_to_intkey(d)

Return type
    Dict[int, Any]

Parameters
    • d (Dict[str, Any]) –
static load(session, db_kb, kb)

Parameters
    • session –
    • db_kb (DbKnowledgeBase) –
    • kb (KnowledgeBase) –

Return type
    StructuredCodeManager

```

Returns

A loaded structured code manager

```
class angr.analyses.decompiler.structuring.recursive_structurer.RecursiveStructurer(region,
                                                                 cond_proc=None,
                                                                 func=None,
                                                                 struc-
                                                                 turer_cls=None,
                                                                 im-
                                                                 prove_structurer=True,
                                                                 **kwargs)
```

Bases: [Analysis](#)

Recursively structure a region and all of its subregions.

Parameters

- **func** ([Function](#) | *None*) –
- **structurer_cls** ([Type](#) | *None*) –

```
__init__(region, cond_proc=None, func=None, structurer_cls=None, improve_structurer=True, **kwargs)
```

Parameters

- **func** ([Function](#) | *None*) –
- **structurer_cls** ([Type](#) | *None*) –

project: [Project](#)

kb: [KnowledgeBase](#)

```
angr.analyses.decompiler.structuring.structurer_class_from_name(name)
```

Return type

[Optional](#)[[Type](#)]

Parameters

name ([str](#)) –

```
class angr.analyses.decompiler.structuring.dream.DreamStructurer(region, parent_map=None,
                                                                 condition_processor=None,
                                                                 func=None,
                                                                 case_entry_to_switch_head=None,
                                                                 parent_region=None,
                                                                 **kwargs)
```

Bases: [StructurerBase](#)

Structure a region using a structuring algorithm that is similar to the one in Dream decompiler (described in the “no more gotos” paper). Note that this implementation has quite a few improvements over the original described version and *should not* be used to evaluate the performance of the original algorithm described in that paper.

The current function graph is provided so that we can detect certain edge cases, for example, jump table entries no longer exist due to empty node removal during structuring or prior steps.

Parameters

- **func** ([Function](#) | *None*) –
- **case_entry_to_switch_head** ([Dict](#)[[int](#), [int](#)] | *None*) –

```

NAME: str = 'dream'

__init__(region, parent_map=None, condition_processor=None, func=None,
          case_entry_to_switch_head=None, parent_region=None, **kwargs)

    Parameters
        • func (Function | None) –
        • case_entry_to_switch_head (Dict[int, int] | None) –
exception angr.analyses.decompiler.structuring.structurer_nodes.EmptyBlockNotice
    Bases: Exception
class angr.analyses.decompiler.structuring.structurer_nodes.MultiNode(nodes, addr=None,
                                                                    idx=None)

    Bases: object
    __init__(nodes, addr=None, idx=None)

    nodes
    addr
    idx
    copy()
    dbg_repr(indent=0)
class angr.analyses.decompiler.structuring.structurer_nodes.BaseNode
    Bases: object
    static test_empty_node(node)
    static test_empty_condition_node(cond_node)
    addr: Optional[int]
    dbg_repr(indent=0)
class angr.analyses.decompiler.structuring.structurer_nodes.SequenceNode(addr, nodes=None)
    Bases: BaseNode
        Parameters
            addr (int | None) –
        __init__(addr, nodes=None)
            Parameters
                addr (int | None) –
    addr: Optional[int]
    nodes
    add_node(node)
    insert_node(pos, node)
    remove_node(node)

```

`node_position(node)`

`copy()`

`dbg_repr(indent=0)`

class `angr.analyses.decompiler.structuring.structurer_nodes.CodeNode(node, reaching_condition)`

Bases: `BaseNode`

`__init__(node, reaching_condition)`

`node`

`reaching_condition`

`property addr`

`property idx`

`dbg_repr(indent=0)`

`copy()`

class `angr.analyses.decompiler.structuring.structurer_nodes.ConditionNode(addr, reaching_condition, condition, true_node, false_node=None)`

Bases: `BaseNode`

Parameters

`addr` (`int` | `None`) –

`__init__(addr, reaching_condition, condition, true_node, false_node=None)`

`addr`: `Optional[int]`

`reaching_condition`

`condition`

`true_node`

`false_node`

`dbg_repr(indent=0)`

`node`

class `angr.analyses.decompiler.structuring.structurer_nodes.CascadingConditionNode(addr, condition_and_nodes, else_node=None)`

Bases: `BaseNode`

Parameters

- `addr` (`int` | `None`) –
- `condition_and_nodes` (`List[Tuple[Any, BaseNode]]`) –
- `else_node` (`BaseNode`) –

```
__init__(addr, condition_and_nodes, else_node=None)
```

Parameters

- **condition_and_nodes** (*List*[*Tuple*[*Any*, *BaseNode*]]) –
- **else_node** (*BaseNode* | *None*) –

```
addr: Optional[int]
```

```
condition_and_nodes
```

```
else_node
```

```
class angr.analyses.decompiler.structuring.structurer_nodes.LoopNode(sort, condition,
                                                                    sequence_node,
                                                                    addr=None,
                                                                    continue_addr=None,
                                                                    initializer=None,
                                                                    iterator=None)
```

Bases: *BaseNode*

Parameters

addr (*int* | *None*) –

```
__init__(sort, condition, sequence_node, addr=None, continue_addr=None, initializer=None,
         iterator=None)
```

```
sort
```

```
condition
```

```
sequence_node
```

```
initializer
```

```
iterator
```

```
copy()
```

```
property addr
```

```
property continue_addr
```

```
dbg_repr(indent=0)
```

```
class angr.analyses.decompiler.structuring.structurer_nodes.BreakNode(addr, target)
```

Bases: *BaseNode*

Parameters

addr (*int* | *None*) –

```
__init__(addr, target)
```

```
addr: Optional[int]
```

```
target
```

```
dbg_repr(indent=0)
```

```
class angr.analyses.decompiler.structuring.structurer_nodes.ContinueNode(addr, target)
```

Bases: *BaseNode*

Parameters

addr (*int* | *None*) –

__init__ (*addr*, *target*)

addr: *Optional*[*int*]

target

dbg_repr (*indent=0*)

```
class angr.analyses.decompiler.structuring.structurer_nodes.ConditionalBreakNode(addr,
                                                                                   condition,
                                                                                   target)
```

Bases: *BreakNode*

Parameters

addr (*int* | *None*) –

__init__ (*addr*, *condition*, *target*)

condition

dbg_repr (*indent=0*)

```
class angr.analyses.decompiler.structuring.structurer_nodes.SwitchCaseNode(switch_expr,
                                                                              cases,
                                                                              default_node,
                                                                              addr=None)
```

Bases: *BaseNode*

Parameters

- **cases** (*OrderedDict*[*int* | *Tuple*[*int*, ...], *SequenceNode*]) –

- **addr** (*int* | *None*) –

__init__ (*switch_expr*, *cases*, *default_node*, *addr=None*)

Parameters

cases (*OrderedDict*[*int* | *Tuple*[*int*, ...], *SequenceNode*]) –

switch_expr

cases: *OrderedDict*[*Union*[*int*, *Tuple*[*int*, ...]], *SequenceNode*]

default_node

addr: *Optional*[*int*]

```
class angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCaseNode(addr,
                                                                                       head,
                                                                                       cases)
```

Bases: *BaseNode*

Describes an incomplete set of switch-case nodes. Usually an intermediate result. Should always be restructured into a `SwitchCaseNode` by the end of structuring. Only used in Phoenix structurer.

Parameters

- **addr** (*int* | *None*) –
- **cases** (*List*) –

__init__ (*addr*, *head*, *cases*)

Parameters

- **cases** (*List*) –

addr: *Optional*[*int*]

head

cases: *List*

class `angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCaseHeadStatement` (**args*, ***kwargs*)

Bases: *Statement*

Describes a switch-case head. This is only created by LoweredSwitchSimplifier.

__init__ (*idx*, *switch_variable*, *case_addrs*, ***kwargs*)

switch_variable

case_addrs: *List*[*Tuple*[*Block*, *Union*[*int*, *str*], *int*, *Optional*[*int*], *int*]]

addr

class `angr.analyses.decompiler.structuring.structurer_base.StructurerBase` (*region*, *parent_map=None*, *condition_processor=None*, *func=None*, *case_entry_to_switch_head=None*, *parent_region=None*, *improve_structurer=True*, ***kwargs*)

Bases: *Analysis*

The base class for analysis passes that structures a region.

The current function graph is provided so that we can detect certain edge cases, for example, jump table entries no longer exist due to empty node removal during structuring or prior steps.

Parameters

- **func** (*Function* | *None*) –
- **case_entry_to_switch_head** (*Dict*[*int*, *int*] | *None*) –

NAME: *str* = *None*

__init__ (*region*, *parent_map=None*, *condition_processor=None*, *func=None*, *case_entry_to_switch_head=None*, *parent_region=None*, *improve_structurer=True*, ***kwargs*)

Parameters

- `func` (`Function` | `None`) –
- `case_entry_to_switch_head` (`Dict[int, int]` | `None`) –

`static replace_nodes(graph, old_node_0, new_node, old_node_1=None, self_loop=True)`

`static replace_node_in_node(parent_node, old_node, new_node)`

Return type

`None`

Parameters

- `parent_node` (`BaseNode`) –
- `old_node` (`BaseNode` | `Block`) –
- `new_node` (`BaseNode` | `Block`) –

`static is_a_jump_target(stmt, addr)`

Return type

`bool`

Parameters

- `stmt` (`ConditionalJump` | `Jump`) –
- `addr` (`int`) –

exception `angr.analyses.decompiler.structuring.phoenix.GraphChangedNotification`

Bases: `Exception`

A notification for graph that is currently worked on being changed. Once this notification is caught, the graph schema matching process for the current region restarts.

class `angr.analyses.decompiler.structuring.phoenix.MultiStmtExprMode(value)`

Bases: `str`, `Enum`

Mode of multi-statement expression creation during structuring.

`NEVER = 'Never'`

`ALWAYS = 'Always'`

`MAX_ONE_CALL = 'Only when less than one call'`

class `angr.analyses.decompiler.structuring.phoenix.PhoenixStructurer(region, parent_map=None, condition_processor=None, func=None, case_entry_to_switch_head=None, parent_region=None, improve_structurer=True, use_multistmtexprs=MultiStmtExprMode.MA, **kwargs)`

Bases: `StructurerBase`

Structure a region using a structuring algorithm that is similar to the one in Phoenix decompiler (described in the “phoenix decompiler” paper). Note that this implementation has quite a few improvements over the original described version and *should not* be used to evaluate the performance of the original algorithm described in that paper.

Parameters

- **func** ([Function](#) | *None*) –
- **case_entry_to_switch_head** ([Dict](#)[*int*, *int*] | *None*) –
- **use_multistmtexprs** ([MultiStmtExprMode](#)) –

NAME: `str` = 'phoenix'

__init__(*region*, *parent_map*=*None*, *condition_processor*=*None*, *func*=*None*,
case_entry_to_switch_head=*None*, *parent_region*=*None*, *improve_structurer*=*True*,
use_multistmtexprs=*MultiStmtExprMode*.*MAX_ONE_CALL*, ***kwargs*)

Parameters

- **func** ([Function](#) | *None*) –
- **case_entry_to_switch_head** ([Dict](#)[*int*, *int*] | *None*) –
- **use_multistmtexprs** ([MultiStmtExprMode](#)) –

static dump_graph(*graph*, *path*)

Return type

None

Parameters

- **graph** (*DiGraph*) –
- **path** (*str*) –

project: *Project*

kb: *KnowledgeBase*

exception `angr.analyses.decompiler.ail_simplifier.HasCallNotification`

Bases: [Exception](#)

Notifies the existence of a call statement.

class `angr.analyses.decompiler.ail_simplifier.AILBlockTempCollector`(***kwargs*)

Bases: [AILBlockWalker](#)

Collects any temporaries used in a block.

__init__(***kwargs*)

class `angr.analyses.decompiler.ail_simplifier.AILSimplifier`(*func*, *func_graph*=*None*,
remove_dead_memdefs=*False*,
stack_arg_offsets=*None*,
unify_variables=*False*,
ail_manager=*None*, *gp*=*None*,
narrow_expressions=*False*,
only_consts=*False*,
fold_callexprs_into_conditions=*False*,
use_callee_saved_regs_at_return=*True*)

Bases: [Analysis](#)

Perform function-level simplifications.

Parameters

- **stack_arg_offsets** (*Set*[*Tuple*[*int*, *int*]] | *None*) –
- **ail_manager** (*Manager* | *None*) –
- **gp** (*int* | *None*) –

__init__ (*func*, *func_graph*=*None*, *remove_dead_memdefs*=*False*, *stack_arg_offsets*=*None*, *unify_variables*=*False*, *ail_manager*=*None*, *gp*=*None*, *narrow_expressions*=*False*, *only_consts*=*False*, *fold_callexprs_into_conditions*=*False*, *use_callee_saved_regs_at_return*=*True*)

Parameters

- **stack_arg_offsets** (*Set*[*Tuple*[*int*, *int*]] | *None*) –
- **ail_manager** (*Manager* | *None*) –
- **gp** (*int* | *None*) –

project: *Project*

kb: *KnowledgeBase*

exception *angr*.*analyses*.*decompiler*.*ailgraph_walker*.**RemoveNodeNotice**

Bases: *Exception*

class *angr*.*analyses*.*decompiler*.*ailgraph_walker*.**AILGraphWalker** (*graph*, *handler*, *replace_nodes*=*False*)

Bases: *object*

Walks an AIL graph and optionally replaces each node with a new node.

Parameters

- replace_nodes** (*bool*) –

__init__ (*graph*, *handler*, *replace_nodes*=*False*)

Parameters

- replace_nodes** (*bool*) –

walk()

class *angr*.*analyses*.*decompiler*.*block_simplifier*.**HasCallExprWalker**

Bases: *AILBlockWalkerBase*

Test if an expression contains a call expression inside.

__init__()

class *angr*.*analyses*.*decompiler*.*block_simplifier*.**BlockSimplifier** (*block*, *func_addr*=*None*, *remove_dead_memdefs*=*False*, *stack_pointer_tracker*=*None*, *peephole_optimizations*=*None*, *stack_arg_offsets*=*None*, *cached_reaching_definitions*=*None*, *cached_propagator*=*None*)

Bases: *Analysis*

Simplify an AIL block.

Parameters

- **block** (*Block* | *None*) –

- **func_addr** (*int* | *None*) –
- **peephole_optimizations** (*Iterable*[*Type*[*PeepholeOptimizationStmtBase*] | *Type*[*PeepholeOptimizationExprBase*]] | *None*) –
- **stack_arg_offsets** (*Set*[*Tuple*[*int*, *int*]] | *None*) –

__init__ (*block*, *func_addr*=*None*, *remove_dead_memdefs*=*False*, *stack_pointer_tracker*=*None*, *peephole_optimizations*=*None*, *stack_arg_offsets*=*None*, *cached_reaching_definitions*=*None*, *cached_propagator*=*None*)

Parameters

- **block** (*Optional*[*Block*]) – The AIL block to simplify. Setting it to *None* to skip calling *self._analyze()*, which is useful in test cases.
- **func_addr** (*int* | *None*) –
- **peephole_optimizations** (*Iterable*[*Type*[*PeepholeOptimizationStmtBase*] | *Type*[*PeepholeOptimizationExprBase*]] | *None*) –
- **stack_arg_offsets** (*Set*[*Tuple*[*int*, *int*]] | *None*) –

project: *Project*

kb: *KnowledgeBase*

class *angr.analyses.decompiler.callsite_maker.CallSiteMaker* (*block*, *reaching_definitions*=*None*, *stack_pointer_tracker*=*None*, *ail_manager*=*None*)

Bases: *Analysis*

Add calling convention, declaration, and args to a call site.

__init__ (*block*, *reaching_definitions*=*None*, *stack_pointer_tracker*=*None*, *ail_manager*=*None*)

project: *Project*

kb: *KnowledgeBase*

class *angr.analyses.decompiler.ccall_rewriters.rewriter_base.CCallRewriterBase* (*ccall*, *arch*)

Bases: *object*

The base class for CCall rewriters.

Parameters

ccall (*VEXCallExpression*) –

__init__ (*ccall*, *arch*)

Parameters

ccall (*VEXCallExpression*) –

arch

result: *Optional*[*Expression*]

class *angr.analyses.decompiler.ccall_rewriters.amd64_ccalls.AMD64CCallRewriter* (*ccall*, *arch*)

Bases: *CCallRewriterBase*

Implements ccall rewriter for AMD64.

Parameters

ccall (*VEXCallExpression*) –

```

class angr.analyses.decompiler.clinic.BlockCache(rd, prop)
    Bases: tuple
    prop
        Alias for field number 1
    rd
        Alias for field number 0

class angr.analyses.decompiler.clinic.ClinicMode(value)
    Bases: Enum
    Analysis mode for Clinic.
    DECOMPILE = 1
    COLLECT_DATA_REFS = 2

class angr.analyses.decompiler.clinic.DataRefDesc(data_addr, data_size, block_addr, stmt_idx,
                                                ins_addr, data_type_str)
    Bases: object
    The fields of this class is compatible with items inside IRSB.data_refs.

    Parameters
        • data_addr (int) –
        • data_size (int) –
        • block_addr (int) –
        • stmt_idx (int) –
        • ins_addr (int) –
        • data_type_str (str) –

    data_addr: int
    data_size: int
    block_addr: int
    stmt_idx: int
    ins_addr: int
    data_type_str: str

    __init__(data_addr, data_size, block_addr, stmt_idx, ins_addr, data_type_str)

    Parameters
        • data_addr (int) –
        • data_size (int) –
        • block_addr (int) –
        • stmt_idx (int) –
        • ins_addr (int) –
        • data_type_str (str) –

```

Return type

None

```
class angr.analyses.decompiler.clinic.Clinic(func, remove_dead_memdefs=False,
                                           exception_edges=False, sp_tracker_track_memory=True,
                                           fold_callexprs_into_conditions=False,
                                           insert_labels=True, optimization_passes=None,
                                           cfg=None, peephole_optimizations=None,
                                           must_struct=None, variable_kb=None,
                                           reset_variable_names=False,
                                           rewrite_ites_to_diamonds=True, cache=None,
                                           mode=ClinicMode.DECOMPILE)
```

Bases: [Analysis](#)

A Clinic deals with AILments.

Parameters

- **peephole_optimizations** ([Iterable](#)[[Type](#)[[PeepholeOptimizationStmtBase](#)] | [Type](#)[[PeepholeOptimizationExprBase](#)]] | None) –
- **must_struct** ([Set](#)[[str](#)] | None) –
- **cache** ([DecompilationCache](#) | None) –
- **mode** ([ClinicMode](#)) –

```
__init__(func, remove_dead_memdefs=False, exception_edges=False, sp_tracker_track_memory=True,
          fold_callexprs_into_conditions=False, insert_labels=True, optimization_passes=None, cfg=None,
          peephole_optimizations=None, must_struct=None, variable_kb=None,
          reset_variable_names=False, rewrite_ites_to_diamonds=True, cache=None,
          mode=ClinicMode.DECOMPILE)
```

Parameters

- **peephole_optimizations** ([Iterable](#)[[Type](#)[[PeepholeOptimizationStmtBase](#)] | [Type](#)[[PeepholeOptimizationExprBase](#)]] | None) –
- **must_struct** ([Set](#)[[str](#)] | None) –
- **cache** ([DecompilationCache](#) | None) –
- **mode** ([ClinicMode](#)) –

block(*addr*, *size*)

Get the converted block at the given specific address with the given size.

Parameters

- **addr** ([int](#)) –
- **size** ([int](#)) –

Returns

dbg_repr()

Returns

copy_graph()

Return type

DiGraph

parse_variable_addr(*addr*)

Return type

`Optional[Tuple[Any, Any]]`

Parameters

addr (*Expression*) –

new_block_addr()

Return a block address that does not conflict with any existing blocks.

Return type

`int`

Returns

The block address.

static remove_empty_nodes(*graph*)

Return type

`DiGraph`

Parameters

graph (*DiGraph*) –

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.decompiler.condition_processor.ConditionProcessor`(*arch*, *condition_mapping=None*)

Bases: `object`

Convert between claripy AST and AIL expressions. Also calculates reaching conditions of all nodes on a graph.

__init__(*arch*, *condition_mapping=None*)

clear()

recover_edge_condition(*graph*, *src*, *dst*)

Parameters

graph (*DiGraph*) –

recover_edge_conditions(*region*, *graph=None*)

Return type

`Dict`

recover_reaching_conditions(*region*, *graph=None*, *with_successors=False*, *case_entry_to_switch_head=None*)

Parameters

case_entry_to_switch_head (`Dict[int, int] | None`) –

remove_claripy_bool_ast(*node*, *memo=None*)

classmethod **get_last_statement**(*block*)

This is the buggy version of `get_last_statements`, because, you know, there can always be more than one last statement due to the existence of branching statements (like, If-then-else). All methods using `get_last_statement()` should switch to `get_last_statements()` and properly handle multiple last statements.


```

classmethod get_last_statements(block)

    Return type
    List[Optional[Statement]]

EXC_COUNTER = 1000

convert_claripy_bool_ast(cond, memo=None)
    Convert recovered reaching conditions from claripy ASTs to ailment Expressions

    Returns
    None

convert_claripy_bool_ast_core(cond, memo)

claripy_ast_from_ail_condition(condition, nobool=False)

    Return type
    Bool

    Parameters
    nobool (bool) –

static claripy_ast_to_sympy_expr(ast, memo=None)

static sympy_expr_to_claripy_ast(expr, memo)

    Parameters
    memo (Dict) –

static simplify_condition(cond, depth_limit=8, variables_limit=8)

static simplify_condition_deprecated(cond)

create_jump_target_var(jumptable_head_addr)

    Parameters
    jumptable_head_addr (int) –

class angr.analyses.decompiler.decompilation_options.DecompilationOption(name, description,
                                                                           value_type, cls,
                                                                           param,
                                                                           value_range=None,
                                                                           category='General',
                                                                           default_value=None,
                                                                           clears_cache=True,
                                                                           candi-
                                                                           date_values=None,
                                                                           convert=None)

Bases: object

Describes a decompilation option.

    Parameters
    • candidate_values (List | None) –
    • convert (Callable | None) –

```

```
__init__(name, description, value_type, cls, param, value_range=None, category='General',
         default_value=None, clears_cache=True, candidate_values=None, convert=None)
```

Parameters

- **candidate_values** (*List* | *None*) –
- **convert** (*Callable* | *None*) –

angr.analyses.decompiler.decompilation_options.0

alias of *DecompilationOption*

angr.analyses.decompiler.decompilation_options.get_structurer_option()

Return type

Optional[*DecompilationOption*]

class angr.analyses.decompiler.decompilation_cache.**DecompilationCache**(*addr*)

Bases: *object*

Caches key data structures that can be used later for refining decompilation results, such as retyping variables.

__init__(*addr*)

addr

type_constraints: *Optional*[*Set*]

func_typevar

var_to_typevar: *Optional*[*Dict*]

codegen: *Optional*[*BaseStructuredCodeGenerator*]

clinic: *Optional*[*Clinic*]

ite_exprs: *Optional*[*Set*[*Tuple*[*int*, *Any*]]]

binop_operators: *Optional*[*Dict*[*OpDescriptor*, *str*]]

property local_types

```
class angr.analyses.decompiler.decompiler.Decompiler(func, cfg=None, options=None,
                                                    optimization_passes=None,
                                                    sp_tracker_track_memory=True,
                                                    variable_kb=None,
                                                    peephole_optimizations=None,
                                                    vars_must_struct=None, flavor='pseudocode',
                                                    expr_comments=None, stmt_comments=None,
                                                    ite_exprs=None, binop_operators=None,
                                                    decompile=True, regen_clinic=True,
                                                    update_memory_data=True,
                                                    generate_code=True)
```

Bases: *Analysis*

The decompiler analysis.

Run this on a Function object for which a normalized CFG has been constructed. The fully processed output can be found in result.codegen.text

Parameters

- **func** (*Function* | *str* | *int*) –
- **cfg** (*CFGFast* | *CFGModel* | *None*) –
- **peephole_optimizations** (*Iterable*[*Type*[*PeepholeOptimizationStmtBase*] | *Type*[*PeepholeOptimizationExprBase*]] | *None*) –
- **vars_must_struct** (*Set*[*str*] | *None*) –
- **update_memory_data** (*bool*) –
- **generate_code** (*bool*) –

__init__ (*func*, *cfg*=*None*, *options*=*None*, *optimization_passes*=*None*, *sp_tracker_track_memory*=*True*, *variable_kb*=*None*, *peephole_optimizations*=*None*, *vars_must_struct*=*None*, *flavor*='pseudocode', *expr_comments*=*None*, *stmt_comments*=*None*, *ite_exprs*=*None*, *binop_operators*=*None*, *decompile*=*True*, *regen_clinic*=*True*, *update_memory_data*=*True*, *generate_code*=*True*)

Parameters

- **func** (*Function* | *str* | *int*) –
- **cfg** (*CFGFast* | *CFGModel* | *None*) –
- **peephole_optimizations** (*Iterable*[*Type*[*PeepholeOptimizationStmtBase*] | *Type*[*PeepholeOptimizationExprBase*]] | *None*) –
- **vars_must_struct** (*Set*[*str*] | *None*) –
- **update_memory_data** (*bool*) –
- **generate_code** (*bool*) –

reflow_variable_types (*type_constraints*, *func_typevar*, *var_to_typevar*, *codegen*)

Re-run type inference on an existing variable recovery result, then rerun codegen to generate new results.

Returns

Parameters

- **type_constraints** (*Set*) –
- **var_to_typevar** (*Dict*) –

find_data_references_and_update_memory_data (*seq_node*)

Parameters

seq_node (*SequenceNode*) –

static options_to_params (*options*)

Convert decompilation options to a dict of params.

Parameters

options (*List*[*Tuple*[*DecompilationOption*, *Any*]]) – The decompilation options.

Return type

Dict[*str*, *Any*]

Returns

A dict of keyword arguments.

project: *Project*

kb: *KnowledgeBase*

class `angr.analyses.decompiler.empty_node_remover.EmptyNodeRemover`(*node*, *claripy_ast_conditions=True*)

Bases: `object`

Rewrites a node and its children to remove empty nodes.

The following optimizations are performed at the same time: - Convert `if (A) { } else { ... }` to `if(!A) { ... }` else `{ }`

Variables

`_claripy_ast_conditions` – True if all node conditions are claripy ASTs. False if all node conditions are AIL expressions.

Parameters

`claripy_ast_conditions` (*bool*) –

`__init__`(*node*, *claripy_ast_conditions=True*)

Parameters

`claripy_ast_conditions` (*bool*) –

class `angr.analyses.decompiler.expression_narrower.ExpressionNarrowingWalker`(*target_expr*)

Bases: `AILBlockWalkerBase`

Walks a statement or an expression and extracts the operations that are applied on the given expression.

For example, for target expression `rax`, `(rax & 0xff) + 0x1` means the following operations are applied on `rax`: `rax & 0xff` `(rax & 0xff) + 0x1`

The previous expression is always used in the succeeding expression.

Parameters

`target_expr` (*Expression*) –

`__init__`(*target_expr*)

Parameters

`target_expr` (*Expression*) –

class `angr.analyses.decompiler.graph_region.GraphRegion`(*head*, *graph*, *successors*, *graph_with_successors*, *cyclic*, *full_graph*, *cyclic_ancestor=False*)

Bases: `object`

GraphRegion represents a region of nodes.

Variables

- **`head`** – The head of the region.
- **`graph`** – The region graph.
- **`successors`** – A set of successors of nodes in the graph. These successors do not belong to the current region.
- **`graph_with_successors`** – The region graph that includes successor nodes.

Parameters

- **`successors`** (*Set* | *None*) –
- **`graph_with_successors`** (*DiGraph* | *None*) –
- **`full_graph`** (*DiGraph* | *None*) –

- **cyclic_ancestor** (*bool*) –

__init__ (*head, graph, successors, graph_with_successors, cyclic, full_graph, cyclic_ancestor=False*)

Parameters

- **successors** (*Set | None*) –
- **graph_with_successors** (*DiGraph | None*) –
- **full_graph** (*DiGraph | None*) –
- **cyclic_ancestor** (*bool*) –

head

graph

successors

graph_with_successors

full_graph

cyclic

cyclic_ancestor

copy()

Return type
GraphRegion

recursive_copy (*nodes_map=None*)

property addr

static dbg_get_repr (*obj, ident=0*)

dbg_print (*ident=0*)

replace_region (*sub_region, updated_sub_region, replace_with, virtualized_edges*)

Parameters

- **sub_region** (*GraphRegion*) –
- **updated_sub_region** (*GraphRegion*) –
- **virtualized_edges** (*Set[Tuple[Any, Any]]*) –

replace_region_with_region (*sub_region, replace_with*)

Parameters

- **sub_region** (*GraphRegion*) –
- **replace_with** (*GraphRegion*) –

class `angr.analyses.decompiler.jump_target_collector.JumpTargetCollector` (*node*)

Bases: `object`

Collect all jump targets.

__init__ (*node*)

class `angr.analyses.decompiler.jumptable_entry_condition_rewriter.JumpTableEntryConditionRewriter`(*jumpta*

Bases: `SequenceWalker`

Remove artificial jump table entry conditions that ConditionProcessor introduced when dealing with jump tables.

`__init__`(*jumptable_entry_conds*)

`angr.analyses.decompiler.optimization_passes.get_optimization_passes`(*arch, platform*)

`angr.analyses.decompiler.optimization_passes.get_default_optimization_passes`(*arch, platform,*
enable_opts=None,
disable_opts=None)

Parameters

- **arch** (*Arch* | *str*) –
- **platform** (*str* | *None*) –

`angr.analyses.decompiler.optimization_passes.register_optimization_pass`(*opt_pass,*
enable_by_default)

Parameters

enable_by_default (*bool*) –

class `angr.analyses.decompiler.optimization_passes.const_derefs.BlockWalker`(*project*)

Bases: `AILBlockWalker`

Parameters

project (*Project*) –

`__init__`(*project*)

Parameters

project (*Project*) –

`walk`(*block*)

Parameters

block (*Block*) –

class `angr.analyses.decompiler.optimization_passes.const_derefs.ConstantDereferencesSimplifier`(*func,*
***kwargs*)

Bases: `OptimizationPass`

Makes the following simplifications:

`*(const_addr) ==> *(value) iff const_addr == value`

ARCHES = `None`

PLATFORMS = `None`

STAGE: `int` = `1`

NAME = `'Simplify constant dereferences'`

```
DESCRIPTION = 'Makes the following simplifications::\n\n *((const_addr)) ==>
*(value) iff *const_addr == value'
```

```
__init__(func, **kwargs)
```

exception

`angr.analyses.decompiler.optimization_passes.optimization_pass.MultipleBlocksException`

Bases: `Exception`

An exception that is raised in `_get_block()` where multiple blocks satisfy the criteria but only one block was requested.

class `angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPassStage(value)`

Bases: `Enum`

Enums about optimization pass stages.

Note that the region identification pass (`RegionIdentifier`) may modify existing AIL blocks *without updating the topology of the original AIL graph*. For example, loop successor refinement may modify create a new AIL block with an artificial address, and alter existing jump targets of jump statements and conditional jump statements to point to this new block. However, loop successor refinement does not update the topology of the original AIL graph, which means this new AIL block does not exist in the original AIL graph. As a result, until this behavior of `RegionIdentifier` changes in the future, `DURING_REGION_IDENTIFICATION` optimization passes should not modify existing jump targets.

```
AFTER_AIL_GRAPH_CREATION = 0
```

```
AFTER_SINGLE_BLOCK_SIMPLIFICATION = 1
```

```
AFTER_MAKING_CALLSITES = 2
```

```
AFTER_GLOBAL_SIMPLIFICATION = 3
```

```
AFTER_VARIABLE_RECOVERY = 4
```

```
BEFORE_REGION_IDENTIFICATION = 5
```

```
DURING_REGION_IDENTIFICATION = 6
```

```
AFTER_STRUCTURING = 7
```

class `angr.analyses.decompiler.optimization_passes.optimization_pass.BaseOptimizationPass(func)`

Bases: `object`

The base class for any optimization pass.

```
ARCHES = []
```

```
PLATFORMS = []
```

```
STAGE: int = None
```

```
STRUCTURING: Optional[str] = None
```

```
NAME = 'N/A'
```

```
DESCRIPTION = 'N/A'
```

```
__init__(func)
```

property project

property kb

analyze()

```
class angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass(func,
                                                                                      blocks_by_addr=None,
                                                                                      blocks_by_addr_and_idx=None,
                                                                                      graph=None,
                                                                                      variable_kb=None,
                                                                                      region_identifier=None,
                                                                                      reaching_definitions=None,
                                                                                      **kwargs)
```

Bases: [BaseOptimizationPass](#)

The base class for any function-level graph optimization pass.

```
__init__(func, blocks_by_addr=None, blocks_by_addr_and_idx=None, graph=None, variable_kb=None,
          region_identifier=None, reaching_definitions=None, **kwargs)
```

property blocks_by_addr: [Dict\[int, Set\[Block\]\]](#)

property blocks_by_addr_and_idx: [Dict\[Tuple\[int, int | None\], Block\]](#)

new_block_addr()

Return a block address that does not conflict with any existing blocks.

Return type

[int](#)

Returns

The block address.

```
class angr.analyses.decompiler.optimization_passes.optimization_pass.SequenceOptimizationPass(func,
                                                                                             seq=None,
                                                                                             **kwargs)
```

Bases: [BaseOptimizationPass](#)

The base class for any sequence node optimization pass.

ARCHES = []

PLATFORMS = []

STAGE: [int](#) = None

```
__init__(func, seq=None, **kwargs)
```



```
class angr.analyses.decompiler.optimization_passes.optimization_pass.StructuringOptimizationPass(func,
pre-
vent_new
strictly_
re-
cover_st
max_opt
sim-
plify_ail
re-
quire_g
**kwargs
```

Bases: *OptimizationPass*

The base class for any optimization pass that requires structuring. Optimization passes that inherit from this class should directly depend on structuring artifacts, such as regions and gotos. Otherwise, they should use *OptimizationPass*. This is the heaviest (computation time) optimization pass class.

ARCHES = None

PLATFORMS = None

STAGE: int = 6

__init__(func, prevent_new_gotos=True, strictly_less_gotos=False, recover_structure_fails=True, max_opt_iters=1, simplify_ail=True, require_gotos=True, **kwargs)

analyze()

Wrapper for *_analyze()* that verifies the graph is structurable before and after the optimization.

angr.analyses.decompiler.optimization_passes.stack_canary_simplifier.s2u(s, bits)

```
class angr.analyses.decompiler.optimization_passes.stack_canary_simplifier.StackCanarySimplifier(func,
**kwargs
```

Bases: *OptimizationPass*

Removes stack canary checks from decompilation results.

ARCHES = ['X86', 'AMD64']

PLATFORMS = ['cgc', 'linux']

STAGE: int = 3

NAME = 'Simplify stack canaries'

DESCRIPTION = 'Removes stack canary checks from decompilation results.'

__init__(func, **kwargs)

```
class angr.analyses.decompiler.optimization_passes.base_ptr_save_simplifier.BasePointerSaveSimplifier(func,
*)
```

Bases: *OptimizationPass*

Removes the effects of base pointer stack storage at function invocation and restoring at function return.

ARCHES = ['X86', 'AMD64', 'ARMEL', 'ARMHF', 'ARMCortexM', 'MIPS32', 'MIPS64']

```

PLATFORMS = ['cgc', 'linux']

STAGE: int = 3

NAME = 'Simplify base pointer saving'

DESCRIPTION = 'Removes the effects of base pointer stack storage at function
invocation and restoring at function return.'

__init__(func, **kwargs)

class angr.analyses.decompiler.optimization_passes.div_simplifier.DivSimplifierAILEngine
    Bases: SimplifierAILEngine
    An AIL pass for the div simplifier

class angr.analyses.decompiler.optimization_passes.div_simplifier.DivSimplifier(func,
                                                                                   **kwargs)
    Bases: OptimizationPass
    Simplifies various division optimizations back to “div”.

    ARCHES = ['X86', 'AMD64', 'ARMCortexM', 'ARMHF', 'ARMEL']

    PLATFORMS = None

    STAGE: int = 3

    NAME = 'Simplify arithmetic division'

    DESCRIPTION = 'Simplifies various division optimizations back to "div".'

    __init__(func, **kwargs)

exception
angr.analyses.decompiler.optimization_passes.ite_expr_converter.NodeFoundNotification
    Bases: Exception
    A notification that the target node has been found.

class angr.analyses.decompiler.optimization_passes.ite_expr_converter.BlockLocator(block)
    Bases: RegionWalker
    Recursively locate block in a GraphRegion instance.
    It might be reasonable to move this class into its own file.

    __init__(block)

    walk_node(region, node)

class angr.analyses.decompiler.optimization_passes.ite_expr_converter.ExpressionReplacer(block_addr,
                                                                                          tar-
                                                                                          get_expr,
                                                                                          call-
                                                                                          back)
    Bases: AILBlockWalker
    Replace expressions.

```

```
__init__(block_addr, target_expr, callback)
```

```
class angr.analyses.decompiler.optimization_passes.ite_expr_converter.ITEExprConverter(func,
                                                                 ite_exprs=None,
                                                                 **kwargs)
```

Bases: *OptimizationPass*

Transform specific expressions into If-Then-Else expressions, or tertiary expressions in C when given a single-use expression address. Requires outside analysis to provide the target expressions.

```
ARCHES = ['X86', 'AMD64', 'ARMEL', 'ARMHF', 'ARMCortexM', 'MIPS32', 'MIPS64']
```

```
PLATFORMS = ['windows', 'linux', 'cgc']
```

```
STAGE: int = 6
```

```
NAME = 'Transform single-use expressions that were assigned to in different If-Else
branches into ternary expressions'
```

```
DESCRIPTION = 'Transform specific expressions into If-Then-Else expressions, or
tertiary expressions in C when\n given a single-use expression address. Requires
outside analysis to provide the target expressions.'
```

```
__init__(func, ite_exprs=None, **kwargs)
```

```
class angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier.Case(original_node,
                                                                 node_type,
                                                                 variable_hash,
                                                                 expr,
                                                                 value,
                                                                 target,
                                                                 target_idx,
                                                                 next_addr)
```

Bases: *object*

Describes a case in a switch-case construct.

Parameters

- **node_type** (*str* | *None*) –
- **value** (*int* | *str*) –
- **target_idx** (*int* | *None*) –

```
__init__(original_node, node_type, variable_hash, expr, value, target, target_idx, next_addr)
```

Parameters

- **node_type** (*str* | *None*) –
- **value** (*int* | *str*) –
- **target_idx** (*int* | *None*) –

```
original_node
```

```
node_type
```

`variable_hash`

`expr`

`value`

`target`

`target_idx`

`next_addr`

`class` `angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier.StableVarExprHasher`(*expr*)

Bases: `AILBlockWalkerBase`

Obtain a stable hash of an AIL expression with respect to all variables and all operations applied on variables.

Parameters

`expr` (*Expression*) –

`__init__`(*expr*)

Parameters

`expr` (*Expression*) –

`class` `angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier.LoweredSwitchSimplifier`(*func*)

blo

blo

gra

***p*

Bases: `OptimizationPass`

Recognize and simplify lowered switch-case constructs.

`ARCHES` = ['AMD64']

`PLATFORMS` = ['linux', 'windows']

`STAGE`: `int` = 6

`NAME` = 'Convert lowered switch-cases (if-else) to switch-cases'

`DESCRIPTION` = 'Convert lowered switch-cases (if-else) to switch-cases. Only works when the Phoenix structuring algorithm is in use.'

`STRUCTURING`: `Optional[str]` = ['phoenix']

`__init__`(*func*, *blocks_by_addr*=None, *blocks_by_addr_and_idx*=None, *graph*=None, ***kwargs*)

`static restore_graph`(*node*, *last_stmt*, *graph*, *full_graph*)

Parameters

- `last_stmt` (*IncompleteSwitchCaseHeadStatement*) –
- `graph` (*DiGraph*) –
- `full_graph` (*DiGraph*) –

```

static cases_issubset(cases_0, cases_1)
    Test if cases_0 is a subset of cases_1.

    Return type
        bool

    Parameters
        • cases_0 (List[Case]) –
        • cases_1 (List[Case]) –

class
    angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifierAILEngine
        Bases: SimplifierAILEngine
        An AIL pass for the multi simplifier

class angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifier(func,
                                                                                       **kwargs)

    Bases: OptimizationPass
    Implements several different arithmetic optimizations.
    ARCHES = ['X86', 'AMD64']
    PLATFORMS = ['linux', 'windows']
    STAGE: int = 3
    NAME = 'Simplify various arithmetic expressions'
    DESCRIPTION = 'Implements several different arithmetic optimizations.'
    __init__(func, **kwargs)

class angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifierAILEngine
    Bases: SimplifierAILEngine

class angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifier(func,
                                                                                       **kwargs)

    Bases: OptimizationPass
    Simplifies optimized forms of modulo computation back to “mod”.
    ARCHES = ['X86', 'AMD64', 'ARMCortexM', 'ARMHF', 'ARMEL']
    PLATFORMS = ['linux', 'windows']
    STAGE: int = 3
    NAME = 'Simplify optimized mod forms'
    DESCRIPTION = 'Simplifies optimized forms of modulo computation back to "mod".'
    __init__(func, **kwargs)

class angr.analyses.decompiler.optimization_passes.engine_base.SimplifierAILState(arch,
                                                                                       variables=None)

```

Bases: `object`

The abstract state used in SimplifierAILEngine.

`__init__(arch, variables=None)`

`copy()`

`merge(*others)`

`store_variable(old, new)`

`get_variable(old)`

`remove_variable(old)`

`filter_variables(atom)`

class `angr.analyses.decompiler.optimization_passes.engine_base.SimplifierAILEngine`

Bases: `SimEngineLightAILMixin`, `SimEngineLight`

Essentially implements a peephole optimization engine for AIL statements (because we do not perform memory or register loads).

`__init__()`

`process(state, *args, **kwargs)`

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

class `angr.analyses.decompiler.optimization_passes.expr_op_swapper.OuterWalker(desc)`

Bases: `SequenceWalker`

A sequence walker that finds nodes and invokes expression replacer to replace expressions.

`__init__(desc)`

class `angr.analyses.decompiler.optimization_passes.expr_op_swapper.ExpressionReplacer(block_addr, tar-
get_expr_predicate,
call-
back)`

Bases: `AILBlockWalker`

Replace expressions.

`__init__(block_addr, target_expr_predicate, callback)`

class `angr.analyses.decompiler.optimization_passes.expr_op_swapper.OpDescriptor(block_addr, stmt_idx,
ins_addr,
op)`

Bases: `object`

Describes a specific operator.

Parameters

- `block_addr` (*int*) –
- `stmt_idx` (*int*) –
- `ins_addr` (*int*) –
- `op` (*str*) –

`__init__`(*block_addr*, *stmt_idx*, *ins_addr*, *op*)

Parameters

- `block_addr` (*int*) –
- `stmt_idx` (*int*) –
- `ins_addr` (*int*) –
- `op` (*str*) –

```
class angr.analyses.decompiler.optimization_passes.expr_op_swapper.ExprOpSwapper(func,
                                                                              binop_operators=None,
                                                                              **kwargs)
```

Bases: [SequenceOptimizationPass](#)

Swap operands (and the operator accordingly) in a BinOp expression.

Parameters

`binop_operators` (*Dict*[*OpDescriptor*, *str*] | *None*) –

ARCHES = ['X86', 'AMD64', 'ARMEL', 'ARMHF', 'ARMCortexM', 'MIPS32', 'MIPS64']

PLATFORMS = ['windows', 'linux', 'cgc']

STAGE: *int* = 7

NAME = 'Swap operands of expressions as requested'

DESCRIPTION = 'Swap operands (and the operator accordingly) in a BinOp expression.'

`__init__`(*func*, *binop_operators*=*None*, ***kwargs*)

Parameters

`binop_operators` (*Dict*[*OpDescriptor*, *str*] | *None*) –

```
angr.analyses.decompiler.optimization_passes.register_save_area_simplifier.s2u(s, bits)
```

```
class angr.analyses.decompiler.optimization_passes.register_save_area_simplifier.RegisterSaveAreaSimplifier
```

Bases: [OptimizationPass](#)

Optimizes away register spilling effects, including callee-saved registers.

ARCHES = *None*

PLATFORMS = *None*

STAGE: *int* = 1

NAME = 'Simplify register save areas'

DESCRIPTION = 'Optimizes away register spilling effects, including callee-saved registers.'

__init__(func, **kwargs)

class angr.analyses.decompiler.optimization_passes.ret_addr_save_simplifier.RetAddrSaveSimplifier(func, **kwargs)

Bases: *OptimizationPass*

Removes code in function prologues and epilogues for saving and restoring return address registers (ra, lr, etc.), generally seen in non-leaf functions.

ARCHES = ['MIPS32', 'MIPS64']

PLATFORMS = ['linux']

STAGE: int = 3

NAME = 'Simplify return address storage'

DESCRIPTION = 'Removes code in function prologues and epilogues for saving and restoring return address registers (ra, lr, etc.),\n generally seen in non-leaf functions.'

__init__(func, **kwargs)

class angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_simplifier.X86GccGetPcSimplifier(func, **kwargs)

Bases: *OptimizationPass*

Simplifies __x86.get_pc_thunk calls.

ARCHES = ['X86']

PLATFORMS = ['linux']

STAGE: int = 1

NAME = 'Simplify getpc()'

DESCRIPTION = 'Simplifies __x86.get_pc_thunk calls.'

__init__(func, **kwargs)

class angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationStmtBase(project, kb, func_addr=None)

Bases: *object*

The base class for all peephole optimizations that are applied on AIL statements.

Parameters

- **project** (*Project* / *None*) –
- **kb** (*KnowledgeBase* / *None*) –
- **func_addr** (*int* / *None*) –

NAME = 'Peephole Optimization - Statement'


```
DESCRIPTION = 'Peephole Optimization - Statement'
```

```
stmt_classes = None
```

```
__init__(project, kb, func_addr=None)
```

Parameters

- **project** (`Project` / `None`) –
- **kb** (`KnowledgeBase` / `None`) –
- **func_addr** (`int` / `None`) –

```
project: Optional[Project]
```

```
kb: Optional[KnowledgeBase]
```

```
func_addr: Optional[int]
```

```
optimize(stmt, stmt_idx=None, block=None, **kwargs)
```

Parameters

```
stmt_idx (int / None) –
```

```
class angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationMultiStmtBase(project,
                                                                                             kb,
                                                                                             func_addr=None)
```

Bases: `object`

The base class for all peephole optimizations that are applied on multiple AIL statements at once.

Parameters

- **project** (`Project` / `None`) –
- **kb** (`KnowledgeBase` / `None`) –
- **func_addr** (`int` / `None`) –

```
NAME = 'Peephole Optimization - Multi-statement'
```

```
DESCRIPTION = 'Peephole Optimization - Multi-statement'
```

```
stmt_classes = None
```

```
__init__(project, kb, func_addr=None)
```

Parameters

- **project** (`Project` / `None`) –
- **kb** (`KnowledgeBase` / `None`) –
- **func_addr** (`int` / `None`) –

```
project: Optional[Project]
```

```
kb: Optional[KnowledgeBase]
```

```
func_addr: Optional[int]
```

optimize(*stmts*, *stmt_idx=None*, *block=None*, ***kwargs*)

Parameters

- **stmts** (*List[Statement]*) –
- **stmt_idx** (*int* | *None*) –

class `angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationExprBase`(*project*,
kb,
func_addr=None)

Bases: `object`

The base class for all peephole optimizations that are applied on AIL expressions.

Parameters

- **project** (*Project* | *None*) –
- **kb** (*KnowledgeBase* | *None*) –
- **func_addr** (*int* | *None*) –

NAME = 'Peephole Optimization - Expression'

DESCRIPTION = 'Peephole Optimization - Expression'

expr_classes = *None*

__init__(*project*, *kb*, *func_addr=None*)

Parameters

- **project** (*Project* | *None*) –
- **kb** (*KnowledgeBase* | *None*) –
- **func_addr** (*int* | *None*) –

project: *Optional[Project]*

kb: *Optional[KnowledgeBase]*

func_addr: *Optional[int]*

optimize(*expr*, ***kwargs*)

static find_definition(*ail_expr*, *stmt_idx*, *block*)

Return type

None

Parameters

- **ail_expr** (*Expression*) –
- **stmt_idx** (*int*) –
- **block** (*Block*) –

static is_bool_expr(*ail_expr*)

```
class angr.analyses.decompiler.region_identifier.RegionIdentifier(func, cond_proc=None,
                                                              graph=None,
                                                              update_graph=True,
                                                              largest_successor_tree_outside_loop=True,
                                                              force_loop_single_exit=True,
                                                              complete_successors=False)
```

Bases: [Analysis](#)

Identifies regions within a function graph and creates a recursive GraphRegion object. Note, that the analysis may modify the graph in-place. If you want to keep the original graph, set the *update_graph* parameter to False.

```
__init__(func, cond_proc=None, graph=None, update_graph=True,
         largest_successor_tree_outside_loop=True, force_loop_single_exit=True,
         complete_successors=False)
```

```
static slice_graph(graph, node, frontier, include_frontier=False)
```

Generate a slice of the graph from the head node to the given frontier.

Parameters

- **graph** (*networkx.DiGraph*) – The graph to work on.
- **node** – The starting node in the graph.
- **frontier** – A list of frontier nodes.
- **include_frontier** (*bool*) – Whether the frontier nodes are included in the slice or not.

Returns

A subgraph.

Return type

networkx.DiGraph

project: *Project*

kb: *KnowledgeBase*

```
class angr.analyses.decompiler.region_simplifiers.cascading_cond_transformer.CascadingConditionTransformer
```

Bases: [SequenceWalker](#)

Identifies and transforms *if { ... } else { if { ... } else { ... } }* to *if { ... } else if { ... } else if { ... }*.

```
__init__(node)
```

```
class angr.analyses.decompiler.region_simplifiers.cascading_ifs.CascadingIfsRemover(node)
```

Bases: [SequenceWalker](#)

Coalesce cascading If constructs. Transforming the following construct:

```
if (cond_a) {
    if (cond_b) {
        true_body
    } else { }
} else { }
```

into:

```
if (cond_a and cond_b) {
    true_body
} else { }
```

```
__init__(node)
```

```
class angr.analyses.decompiler.region_simplifiers.expr_folding.LocationBase
```

```
    Bases: object
```

```
class angr.analyses.decompiler.region_simplifiers.expr_folding.StatementLocation(block_addr,
                                                                                block_idx,
                                                                                stmt_idx)
```

```
    Bases: LocationBase
```

```
    __init__(block_addr, block_idx, stmt_idx)
```

```
    block_addr
```

```
    block_idx
```

```
    stmt_idx
```

```
    copy()
```

```
class angr.analyses.decompiler.region_simplifiers.expr_folding.ExpressionLocation(block_addr,
                                                                                block_idx,
                                                                                stmt_idx,
                                                                                expr_idx)
```

```
    Bases: LocationBase
```

```
    __init__(block_addr, block_idx, stmt_idx, expr_idx)
```

```
    block_addr
```

```
    block_idx
```

```
    stmt_idx
```

```
    expr_idx
```

```
    statement_location()
```

```
        Return type
```

```
            StatementLocation
```

```
class angr.analyses.decompiler.region_simplifiers.expr_folding.ConditionLocation(cond_node_addr,
                                                                                case_idx=None)
```

```
    Bases: LocationBase
```

```
        Parameters
```

```
            case_idx (int | None) –
```

```
    __init__(cond_node_addr, case_idx=None)
```

```
        Parameters
```

```
            case_idx (int | None) –
```

```
    node_addr
```

case_idx

class angr.analyses.decompiler.region_simplifiers.expr_folding.**ConditionalBreakLocation**(node_addr)

Bases: [LocationBase](#)

__init__(node_addr)

node_addr

class angr.analyses.decompiler.region_simplifiers.expr_folding.**MultiStatementExpressionAssignmentFinder**

Bases: [AILBlockWalker](#)

Process statements in MultiStatementExpression objects and find assignments.

__init__(stmt_handler)

class angr.analyses.decompiler.region_simplifiers.expr_folding.**ExpressionUseFinder**

Bases: [AILBlockWalker](#)

Find where each variable is used.

Additionally, determine if the expression being walked has load expressions inside. Such expressions can only be safely folded if there are no Store statements between the expression defining location and its use sites. For example, we can only safely fold variable assignments that use Load() when there are no Store()s between the assignment and its use site. Otherwise, the loaded expression may get updated later by a Store() statement.

Here is a real AIL block:

```
v16 = ((int)v23->field_5) + 1 & 255;
v23->field_5 = ((char)(((int)v23->field_5) + 1 & 255));
v13 = printf("Recieved packet %d for connection with %d\n", v16, a0 & 255);
```

In this case, folding v16 into the last printf() expression would be incorrect, since v23->field_5 is updated by the second statement.

__init__()

uses: DefaultDict[SimVariable, Set[Tuple[Expression, Optional[ExpressionLocation]]]]

has_load

class angr.analyses.decompiler.region_simplifiers.expr_folding.**ExpressionCounter**(node, variable_manager)

Bases: [SequenceWalker](#)

Find all expressions that are assigned once and only used once.

__init__(node, variable_manager)

class angr.analyses.decompiler.region_simplifiers.expr_folding.**ExpressionReplacer**(assignments, uses, variable_manager)

Bases: [AILBlockWalker](#)

Parameters

- **assignments** (*Dict*) –
- **uses** (*Dict*) –

__init__(*assignments, uses, variable_manager*)

Parameters

- **assignments** (*Dict*) –
- **uses** (*Dict*) –

class `angr.analyses.decompiler.region_simplifiers.expr_folding.ExpressionFolder`(*assignments, uses, node, variable_manager*)

Bases: *SequenceWalker*

Parameters

- **assignments** (*Dict*) –
- **uses** (*Dict*) –

__init__(*assignments, uses, node, variable_manager*)

Parameters

- **assignments** (*Dict*) –
- **uses** (*Dict*) –

class `angr.analyses.decompiler.region_simplifiers.expr_folding.StoreStatementFinder`(*node, intervals*)

Bases: *SequenceWalker*

Determine if there are any Store statements between two given statements.

This class overrides `_handle_Sequence()` and `_handle_MultiNode()` to ensure they traverse nodes from top to bottom.

Parameters

intervals (*Iterable[Tuple[StatementLocation, LocationBase]]*) –

__init__(*node, intervals*)

Parameters

intervals (*Iterable[Tuple[StatementLocation, LocationBase]]*) –

has_store(*start, end*)

Return type

bool

Parameters

- **start** (*StatementLocation*) –
- **end** (*StatementLocation*) –

class `angr.analyses.decompiler.region_simplifiers.goto.GotoSimplifier`(*node, function=None, kb=None*)

Bases: *SequenceWalker*

Remove unnecessary Jump statements. This simplifier also has the side effect of detecting Gotos that can't be reduced in the structuring and eventual decompilation output. Because of this, when this analysis is run, gotos in decompilation will be detected and stored in the `kb.gotos`. See the `_handle_irreducible_goto` function below.

TODO: Move the recording of Gotos outside this function

```
__init__(node, function=None, kb=None)
```

```
class angr.analyses.decompiler.region_simplifiers.if_.IfSimplifier(node)
```

Bases: [SequenceWalker](#)

Remove unnecessary jump or conditional jump statements if they jump to the successor right afterwards.

```
__init__(node)
```

```
class angr.analyses.decompiler.region_simplifiers.iffalse.IfElseFlattener(node, functions)
```

Bases: [SequenceWalker](#)

Remove unnecessary else branches and make the else node a direct successor of the previous If node if the If node always returns.

```
__init__(node, functions)
```

```
class angr.analyses.decompiler.region_simplifiers.loop.LoopSimplifier(node, functions)
```

Bases: [SequenceWalker](#)

Simplifies loops.

```
__init__(node, functions)
```

```
class angr.analyses.decompiler.region_simplifiers.node_address_finder.NodeAddressFinder(node)
```

Bases: [SequenceWalker](#)

Walk the entire node and collect all addresses of nodes.

```
__init__(node)
```

```
class angr.analyses.decompiler.region_simplifiers.region_simplifier.RegionSimplifier(func,
                                                                                      re-
                                                                                      gion,
                                                                                      vari-
                                                                                      able_kb=None,
                                                                                      sim-
                                                                                      plify_switches=True,
                                                                                      sim-
                                                                                      plify_ifelse=True)
```

Bases: [Analysis](#)

Simplifies a given region.

Parameters

- **simplify_switches** (*bool*) –
- **simplify_ifelse** (*bool*) –

```
__init__(func, region, variable_kb=None, simplify_switches=True, simplify_ifelse=True)
```

Parameters

- **simplify_switches** (*bool*) –
- **simplify_ifelse** (*bool*) –

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.CmpOp`(*value*)

Bases: `Enum`

All supported comparison operators.

LT = 0

GT = 1

EQ = 2

NE = 3

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.ConditionalRegion`(*variable*,
op,
value,
node,
parent=None)

Bases: `object`

Describes a conditional region.

Parameters

- **op** (`CmpOp`) –
- **value** (`int`) –
- **node** (`ConditionNode` / `Block`) –

__init__ (*variable*, *op*, *value*, *node*, *parent*=None)

Parameters

- **op** (`CmpOp`) –
- **value** (`int`) –
- **node** (`ConditionNode` / `Block`) –

variable

op

value

node

parent

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.SwitchCaseRegion`(*variable*,
node,
parent=None)

Bases: `object`

Describes an already-recovered switch region.

Parameters

- **node** (`SwitchCaseNode`) –

`__init__(variable, node, parent=None)`

Parameters

node (`SwitchCaseNode`) –

variable

node

parent

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.SwitchClusterFinder`(*node*)

Bases: `SequenceWalker`

Find comparisons and switches in order to identify switch clusters.

`__init__(node)`

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.SwitchClusterReplacer`(*region*, *to_replace*, *replace_with*)

Bases: `SequenceWalker`

Replace an identified switch cluster with a newly created SwitchCase node.

`__init__(region, to_replace, replace_with)`

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.is_simple_jump_node`(*node*, *case_addr*, *target*, *gets=None*)

Return type

`bool`

Parameters

targets (`Set[int]` | `None`) –

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.filter_cond_regions`(*cond_regions*, *case_addr*)

Remove all conditional regions that cannot be merged into switch(es).

Return type

`List[ConditionalRegion]`

Parameters

- **cond_regions** (`List[ConditionalRegion]`) –
- **case_addr** (`Set[int]`) –

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.update_switch_case_list`(*cases*, *old_case_id*, *new_case_id*)

Update cases in-place. Make new_case_id directly jump to old_case_id.

Return type

`None`

Parameters

- **cases** (*List[Tuple[int | Tuple[int, ...], SequenceNode]]*) –
- **old_case_id** (*int | Tuple[int, ...]*) –
- **new_case_id** (*int*) –

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.simplify_switch_clusters`(*region*,
var2condnodes,
var2switches)

Identify switch clusters and simplify each of them.

Parameters

- **region** – The region to simplify.
- **var2condnodes** (*Dict[Any, List[ConditionalRegion]]*) – A dict that stores the mapping from (potential) switch variables to conditional regions.
- **var2switches** (*Dict[Any, List[SwitchCaseRegion]]*) – A dict that stores the mapping from switch variables to switch-case regions.

Returns

None

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.simplify_lowered_switches`(*region*,
var2condnodes,
func2switches)

Identify a lowered switch and simplify it into a switch-case if possible.

Parameters

- **region** (*SequenceNode*) – The region to simplify.
- **var2condnodes** (*Dict[Any, List[ConditionalRegion]]*) – A dict that stores the mapping from (potential) switch variables to conditional regions.

Returns

None

`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.simplify_lowered_switches_core`(*region*,
var2condnodes,
func2switches)

Return type

bool

Parameters

region (*SequenceNode*) –

class `angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.FindFirstNodeInSet`(*node_set*)

Bases: *SequenceWalker*

Find the first node out of a set of node appearing in a SequenceNode (and its tree).

Parameters

node_set (*Set[BaseNode]*) –

`__init__(node_set)`

Parameters

node_set (`Set[BaseNode]`) –

class `angr.analyses.decompiler.region_simplifiers.switch_expr_simplifier.SwitchExpressionSimplifier`(*node*)

Bases: `SequenceWalker`

Identifies switch expressions that adds or minuses a constant, removes the constant from the switch expression, and adjust all case expressions accordingly.

`__init__(node)`

class `angr.analyses.decompiler.region_walker.RegionWalker`

Bases: `object`

A simple traverser class that walks `GraphRegion` instances.

`__init__()`

`walk(region)`

Parameters

region (`GraphRegion`) –

`walk_node(region, node)`

class `angr.analyses.decompiler.redundant_label_remover.RedundantLabelRemover`(*node*,
jump_targets)

Bases: `object`

Remove redundant labels.

This optimization pass contains two separate passes. The first pass (`self._walker0`) finds all redundant labels (e.g., two or more labels for the same location) and records the replacement label for redundant labels in `self._new_jump_target`. The second pass (`self._walker1`) removes all redundant labels that (a) are not referenced anywhere (determined by `jump_targets`), or (b) are deemed replaceable by the first pass.

Parameters

jump_targets (`Set[Tuple[int, int | None]]`) –

`__init__(node, jump_targets)`

Parameters

jump_targets (`Set[Tuple[int, int | None]]`) –

class `angr.analyses.decompiler.sequence_walker.SequenceWalker`(*handlers=None*,
exception_on_unsupported=False,
update_seqnode_in_place=True,
force_forward_scan=False)

Bases: `object`

Walks a `SequenceNode` and all its nodes, recursively.

Parameters

force_forward_scan (*bool*) –

`__init__(handlers=None, exception_on_unsupported=False, update_seqnode_in_place=True,
force_forward_scan=False)`

Parameters

force_forward_scan (*bool*) –

walk(*sequence*)

class `angr.analyses.decompiler.structured_codegen.base.PositionMappingElement`(*start*, *length*,
obj)

Bases: `object`

__init__(*start*, *length*, *obj*)

start: `int`

length: `int`

obj

class `angr.analyses.decompiler.structured_codegen.base.PositionMapping`

Bases: `object`

DUPLICATION_CHECK = `True`

__init__()

items()

add_mapping(*start_pos*, *length*, *obj*)

get_node(*pos*)

Parameters

pos (`int`) –

get_element(*pos*)

Return type

`Optional[PositionMappingElement]`

Parameters

pos (`int`) –

class `angr.analyses.decompiler.structured_codegen.base.InstructionMappingElement`(*ins_addr*,
posmap_pos)

Bases: `object`

__init__(*ins_addr*, *posmap_pos*)

ins_addr: `int`

posmap_pos: `int`

class `angr.analyses.decompiler.structured_codegen.base.InstructionMapping`

Bases: `object`

__init__()

items()

add_mapping(*ins_addr*, *posmap_pos*)

get_nearest_pos(*ins_addr*)

Return type
Optional[int]

Parameters
ins_addr (int) –

class angr.analyses.decompiler.structured_codegen.base.**BaseStructuredCodeGenerator**(*flavor=None*)

Bases: object

__init__(*flavor=None*)

reapply_options(*options*)

regenerate_text()

Return type
None

reload_variable_types()

Return type
None

angr.analyses.decompiler.structured_codegen.c.**unpack_typeref**(*ty*)

angr.analyses.decompiler.structured_codegen.c.**unpack_pointer**(*ty*)

Return type
Optional[SimType]

angr.analyses.decompiler.structured_codegen.c.**unpack_array**(*ty*)

Return type
Optional[SimType]

angr.analyses.decompiler.structured_codegen.c.**squash_array_reference**(*ty*)

angr.analyses.decompiler.structured_codegen.c.**qualifies_for_simple_cast**(*ty1*, *ty2*)

angr.analyses.decompiler.structured_codegen.c.**qualifies_for_implicit_cast**(*ty1*, *ty2*)

angr.analyses.decompiler.structured_codegen.c.**extract_terms**(*expr*)

Return type
Tuple[int, List[Tuple[int, CExpression]]]

Parameters
expr (CExpression) –

angr.analyses.decompiler.structured_codegen.c.**is_machine_word_size_type**(*type_*, *arch*)

Return type
bool

Parameters

- **type_** (SimType) –
- **arch** (Arch) –

`angr.analyses.decompiler.structured_codegen.c.guess_value_type(value, project)`

Return type

`Optional[SimType]`

Parameters

- **value** (`int`) –
- **project** (`Project`) –

`angr.analyses.decompiler.structured_codegen.c.type_to_c_repr_chunks`(*ty*, *name=None*,
name_type=None,
full=False, *indent_str=""*)

Helper generator function to turn a SimType into generated tuples of (C-string, AST node).

Parameters

ty (`SimType`) –

class `angr.analyses.decompiler.structured_codegen.c.CConstruct`(*codegen*)

Bases: `object`

Represents a program construct in C. Acts as the base class for all other representation constructions.

`__init__`(*codegen*)

codegen: `StructuredCodeGenerator`

`c_repr`(*indent=0*, *pos_to_node=None*, *pos_to_addr=None*, *addr_to_pos=None*)

Creates the C representation of the code and displays it by constructing a large string. This function is called by each program function that needs to be decompiled. The `map_pos_to_node` and `map_pos_to_addr` act as position maps for the location of each variable and statement to be tracked for later GUI operations. The `map_pos_to_addr` also contains expressions that are nested inside of statements.

`c_repr_chunks`(*indent=0*, *asexpr=False*)

static `indent_str`(*indent=0*)

class `angr.analyses.decompiler.structured_codegen.c.CFunction`(*addr*, *name*, *functy*, *arg_list*,
statements, *variables_in_use*,
variable_manager,
demangled_name=None,
show_demangled_name=True,
omit_header=False, ***kwargs*)

Bases: `CConstruct`

Represents a function in C.

Parameters

- **functy** (`SimTypeFunction`) –
- **arg_list** (`List[CVariable]`) –

`__init__`(*addr*, *name*, *functy*, *arg_list*, *statements*, *variables_in_use*, *variable_manager*,
demangled_name=None, *show_demangled_name=True*, *omit_header=False*, ***kwargs*)

Parameters

- **functy** (`SimTypeFunction`) –
- **arg_list** (`List[CVariable]`) –

```

    addr
    name
    functy
    arg_list
    statements
    variables_in_use
    variable_manager: VariableManagerInternal
    demangled_name
    unified_local_vars: Dict[SimVariable, Set[Tuple[CVariable, SimType]]]
    show_demangled_name
    omit_header
    get_unified_local_vars()

    Return type
    Dict[SimVariable, Set[Tuple[CVariable, SimType]]]
    variable_list_repr_chunks(indent=0)
    c_repr_chunks(indent=0, asexpr=False)
    headerless_c_repr_chunks(indent=0)
    full_c_repr_chunks(indent=0, asexpr=False)
class angr.analyses.decompiler.structured_codegen.c.CStatement(codegen)
    Bases: CConstruct
    Represents a statement in C.

    Parameters
    codegen (StructuredCodeGenerator) –
class angr.analyses.decompiler.structured_codegen.c.CExpression(collapsed=False, **kwargs)
    Bases: CConstruct
    Base class for C expressions.
    __init__(collapsed=False, **kwargs)
    collapsed
    property type
    set_type(v)
class angr.analyses.decompiler.structured_codegen.c.CStatements(statements, **kwargs)
    Bases: CStatement
    Represents a sequence of statements in C.
    __init__(statements, **kwargs)

```

statements

c_repr_chunks(*indent=0, asexpr=False*)

class angr.analyses.decompiler.structured_codegen.c.**CAILBlock**(*block, **kwargs*)

Bases: [CStatement](#)

Represents a block of AIL statements.

__init__(*block, **kwargs*)

block

c_repr_chunks(*indent=0, asexpr=False*)

class angr.analyses.decompiler.structured_codegen.c.**CLoop**(*codegen*)

Bases: [CStatement](#)

Represents a loop in C.

Parameters

codegen ([StructuredCodeGenerator](#)) –

class angr.analyses.decompiler.structured_codegen.c.**CWhileLoop**(*condition, body, tags=None, **kwargs*)

Bases: [CLoop](#)

Represents a while loop in C.

__init__(*condition, body, tags=None, **kwargs*)

condition

body

tags

c_repr_chunks(*indent=0, asexpr=False*)

class angr.analyses.decompiler.structured_codegen.c.**CDoWhileLoop**(*condition, body, tags=None, **kwargs*)

Bases: [CLoop](#)

Represents a do-while loop in C.

__init__(*condition, body, tags=None, **kwargs*)

condition

body

tags

c_repr_chunks(*indent=0, asexpr=False*)

class angr.analyses.decompiler.structured_codegen.c.**CForLoop**(*initializer, condition, iterator, body, tags=None, **kwargs*)

Bases: [CStatement](#)

Represents a for-loop in C.


```
__init__(initializer, condition, iterator, body, tags=None, **kwargs)
```

```
initializer
```

```
condition
```

```
iterator
```

```
body
```

```
tags
```

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CIfElse(condition_and_nodes,
                                                         else_node=None,
                                                         simplify_else_scope=False,
                                                         cstyle_ifs=True, tags=None,
                                                         **kwargs)
```

Bases: [CStatement](#)

Represents an if-else construct in C.

Parameters

condition_and_nodes ([List](#)[[Tuple](#)[[CExpression](#), [CStatement](#) | [None](#)]]) –

```
__init__(condition_and_nodes, else_node=None, simplify_else_scope=False, cstyle_ifs=True, tags=None,
          **kwargs)
```

Parameters

condition_and_nodes ([List](#)[[Tuple](#)[[CExpression](#), [CStatement](#) | [None](#)]]) –

```
condition_and_nodes
```

```
else_node
```

```
simplify_else_scope
```

```
cstyle_ifs
```

```
tags
```

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CIfBreak(condition, cstyle_ifs=True,
                                                            tags=None, **kwargs)
```

Bases: [CStatement](#)

Represents an if-break statement in C.

```
__init__(condition, cstyle_ifs=True, tags=None, **kwargs)
```

```
condition
```

```
cstyle_ifs
```

```
tags
```

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CBreak(tags=None, **kwargs)
```

Bases: [CStatement](#)

Represents a break statement in C.

```
__init__(tags=None, **kwargs)
```

tags

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CContinue(tags=None, **kwargs)
```

Bases: [CStatement](#)

Represents a continue statement in C.

```
__init__(tags=None, **kwargs)
```

tags

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CSwitchCase(switch, cases, default,
                                                                tags=None, **kwargs)
```

Bases: [CStatement](#)

Represents a switch-case statement in C.

```
__init__(switch, cases, default, tags=None, **kwargs)
```

switch

```
cases: List[Tuple[Union[int, Tuple[int]], CStatements]]
```

default

tags

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CAssignment(lhs, rhs, tags=None, **kwargs)
```

Bases: [CStatement](#)

a = b

```
__init__(lhs, rhs, tags=None, **kwargs)
```

lhs

rhs

tags

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CFunctionCall(callee_target, callee_func,
                                                                    args, returning=True,
                                                                    ret_expr=None, tags=None,
                                                                    is_expr=False,
                                                                    show_demangled_name=True,
                                                                    show_disambiguated_name=True,
                                                                    **kwargs)
```

Bases: *CStatement*, *CExpression*

func(arg0, arg1)

Variables

- **callee_func** (*Function*) – The function getting called.
- **is_expr** – True if the return value of the function is written to ret_expr; Essentially, ret_expr = call().

Parameters

- **is_expr** (*bool*) –
- **show_disambiguated_name** (*bool*) –

__init__(callee_target, callee_func, args, returning=True, ret_expr=None, tags=None, is_expr=False, show_demangled_name=True, show_disambiguated_name=True, **kwargs)

Parameters

- **is_expr** (*bool*) –
- **show_disambiguated_name** (*bool*) –

callee_target

callee_func: *Optional*[*Function*]

args

returning

ret_expr

tags

is_expr

show_demangled_name

show_disambiguated_name

property prototype: *SimTypeFunction* | *None*

property type

c_repr_chunks(indent=0, asexpr=False)

Parameters

- **indent** – Number of whitespace indentation characters.
- **asexpr** (*bool*) – True if this call is used as an expression (which means we will skip the generation of semicolons and newlines at the end of the call).

class angr.analyses.decompiler.structured_codegen.c.**CReturn**(retval, tags=None, **kwargs)

Bases: *CStatement*

__init__(retval, tags=None, **kwargs)

retval

tags

c_repr_chunks(*indent=0, asexpr=False*)

class `angr.analyses.decompiler.structured_codegen.c.CGoto`(*target, target_idx, tags=None, **kwargs*)

Bases: `CStatement`

__init__(*target, target_idx, tags=None, **kwargs*)

target: `Union[int, CExpression]`

target_idx

tags

c_repr_chunks(*indent=0, asexpr=False*)

class `angr.analyses.decompiler.structured_codegen.c.CUnsupportedStatement`(*stmt, **kwargs*)

Bases: `CStatement`

A wrapper for unsupported AIL statement.

__init__(*stmt, **kwargs*)

stmt

c_repr_chunks(*indent=0, asexpr=False*)

class `angr.analyses.decompiler.structured_codegen.c.CLabel`(*name, ins_addr, block_idx, tags=None, **kwargs*)

Bases: `CStatement`

Represents a label in C code.

Parameters

- **name** (*str*) –
- **ins_addr** (*int*) –
- **block_idx** (*int* | *None*) –

__init__(*name, ins_addr, block_idx, tags=None, **kwargs*)

Parameters

- **name** (*str*) –
- **ins_addr** (*int*) –
- **block_idx** (*int* | *None*) –

name

ins_addr

block_idx

tags

c_repr_chunks(*indent=0, asexpr=False*)

```
class angr.analyses.decompiler.structured_codegen.c.CStructField(struct_type, offset, field,
                                                                tags=None, **kwargs)
```

Bases: [CExpression](#)

Parameters

struct_type ([SimStruct](#)) –

__init__ (*struct_type*, *offset*, *field*, *tags*=None, ***kwargs*)

Parameters

struct_type ([SimStruct](#)) –

struct_type

offset

field

tags

property type

c_repr_chunks (*indent*=0, *asexpr*=False)

```
class angr.analyses.decompiler.structured_codegen.c.CFakeVariable(name, ty, tags=None,
                                                                **kwargs)
```

Bases: [CExpression](#)

An uninterpreted name to display in the decompilation output. Pretty much always represents an error?

Parameters

- **name** (*str*) –

- **ty** ([SimType](#)) –

__init__ (*name*, *ty*, *tags*=None, ***kwargs*)

Parameters

- **name** (*str*) –

- **ty** ([SimType](#)) –

name

tags

property type

c_repr_chunks (*indent*=0, *asexpr*=False)

```
class angr.analyses.decompiler.structured_codegen.c.CVariable(variable, unified_variable=None,
                                                                variable_type=None, tags=None,
                                                                **kwargs)
```

Bases: [CExpression](#)

CVariable represents access to a variable with the specified type (*variable_type*).

variable must be a SimVariable.

Parameters

variable ([SimVariable](#)) –

```
__init__(variable, unified_variable=None, variable_type=None, tags=None, **kwargs)
```

Parameters

variable (`SimVariable`) –

variable: `SimVariable`

unified_variable: `Optional[SimVariable]`

variable_type: `SimType`

tags

property type

property name

c_repr_chunks (`indent=0, asexpr=False`)

```
class angr.analyses.decompiler.structured_codegen.c.CIndexedVariable(variable, index,
                                                                    variable_type=None,
                                                                    tags=None, **kwargs)
```

Bases: `CExpression`

Represent a variable (an array) that is indexed.

Parameters

- **variable** (`CExpression`) –

- **index** (`CExpression`) –

```
__init__(variable, index, variable_type=None, tags=None, **kwargs)
```

Parameters

- **variable** (`CExpression`) –

- **index** (`CExpression`) –

property type

c_repr_chunks (`indent=0, asexpr=False`)

collapsed

```
class angr.analyses.decompiler.structured_codegen.c.CVariableField(variable, field,
                                                                    var_is_ptr=False,
                                                                    tags=None, **kwargs)
```

Bases: `CExpression`

Represent a field of a variable.

Parameters

- **variable** (`CExpression`) –

- **field** (`CStructField`) –

- **var_is_ptr** (`bool`) –

```
__init__(variable, field, var_is_ptr=False, tags=None, **kwargs)
```

Parameters

- **variable** (`CExpression`) –
- **field** (`CStructField`) –
- **var_is_ptr** (`bool`) –

property type

```
c_repr_chunks(indent=0, asexpr=False)
```

collapsed

```
class angr.analyses.decompiler.structured_codegen.c.CUnaryOp(op, operand, tags=None, **kwargs)
```

Bases: `CExpression`

Unary operations.

Parameters

operand (`CExpression`) –

```
__init__(op, operand, tags=None, **kwargs)
```

Parameters

operand (`CExpression`) –

op

operand

tags

property type

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CBinaryOp(op, lhs, rhs, tags=None, **kwargs)
```

Bases: `CExpression`

Binary operations.

Parameters

tags (`dict` | `None`) –

```
__init__(op, lhs, rhs, tags=None, **kwargs)
```

Parameters

tags (`dict` | `None`) –

op

lhs

rhs

tags

common_type

static `compute_common_type`(*op*, *lhs_ty*, *rhs_ty*)

Return type

SimType

Parameters

- *op* (*str*) –
- *lhs_ty* (*SimType*) –
- *rhs_ty* (*SimType*) –

property `type`

property `op_precedence`

c_repr_chunks(*indent=0*, *asexpr=False*)

class `angr.analyses.decompiler.structured_codegen.c.CTypeCast`(*src_type*, *dst_type*, *expr*,
tags=None, ***kwargs*)

Bases: *CExpression*

Parameters

- *src_type* (*SimType* | *None*) –
- *dst_type* (*SimType*) –
- *expr* (*CExpression*) –

__init__(*src_type*, *dst_type*, *expr*, *tags=None*, ***kwargs*)

Parameters

- *src_type* (*SimType* | *None*) –
- *dst_type* (*SimType*) –
- *expr* (*CExpression*) –

src_type

dst_type

expr

tags

property `type`

c_repr_chunks(*indent=0*, *asexpr=False*)

class `angr.analyses.decompiler.structured_codegen.c.CConstant`(*value*, *type_*,
reference_values=None,
tags=None, ***kwargs*)

Bases: *CExpression*

Parameters

- *type_* (*SimType*) –
- *tags* (*Dict* | *None*) –


```
__init__(value, type_, reference_values=None, tags=None, **kwargs)
```

Parameters

- **type_** ([SimType](#)) –
- **tags** ([Dict](#) | [None](#)) –

value

reference_values

tags

property fmt

property fmt_hex

property fmt_neg

property fmt_char

property fmt_float

property fmt_double

property type

static str_to_c_str(_str, prefix="")

Parameters

- **prefix** ([str](#)) –

c_repr_chunks(indent=0, asexpr=False)

fmt_int(value)

Format an integer using the format setup of the current node.

Parameters

- **value** ([int](#)) – The integer value to format.

Return type

[str](#)

Returns

The formatted string.

```
class angr.analyses.decompiler.structured_codegen.c.CRegister(reg, tags=None, **kwargs)
```

Bases: [CExpression](#)

```
__init__(reg, tags=None, **kwargs)
```

reg

tags

property type

c_repr_chunks(indent=0, asexpr=False)

```
class angr.analyses.decompiler.structured_codegen.c.CITE(cond, iftrue, iffalse, tags=None,
                                                    **kwargs)
```

Bases: [CExpression](#)

```
__init__(cond, iftrue, iffalse, tags=None, **kwargs)
```

cond

iftrue

iffalse

tags

property type

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CMultiStatementExpression(stmts, expr,
                                                                              tags=None,
                                                                              **kwargs)
```

Bases: [CExpression](#)

```
(stmt0, stmt1, stmt2, expr)
```

Parameters

- **stmts** ([CStatements](#)) –
- **expr** ([CExpression](#)) –

```
__init__(stmts, expr, tags=None, **kwargs)
```

Parameters

- **stmts** ([CStatements](#)) –
- **expr** ([CExpression](#)) –

stmts

expr

tags

property type

```
c_repr_chunks(indent=0, asexpr=False)
```

```
class angr.analyses.decompiler.structured_codegen.c.CDirtyExpression(dirty, **kwargs)
```

Bases: [CExpression](#)

Ideally all dirty expressions should be handled and converted to proper conversions during conversion from VEX to AIL. Eventually this class should not be used at all.

```
__init__(dirty, **kwargs)
```

dirty

property type

```
c_repr_chunks(indent=0, asexpr=False)
```

class `angr.analyses.decompiler.structured_codegen.c.CClosingObject`(*opening_symbol*)

Bases: `object`

A class to represent all objects that can be closed by it's correspodning character. Examples: (), {}, []

`__init__`(*opening_symbol*)

opening_symbol

class `angr.analyses.decompiler.structured_codegen.c.CArrayTypeLength`(*text*)

Bases: `object`

A class to represent the type information of fixed-size array lengths. Examples: In “char foo[20]”, this would be the “[20]”.

`__init__`(*text*)

text

class `angr.analyses.decompiler.structured_codegen.c.CStructFieldNameDef`(*name*)

Bases: `object`

A class to represent the name of a defined field in a struct. Needed because it's not a CVariable or a CStructField (because CStructField is the access of a CStructField). Example: In “struct foo { int bar; }, this would be “bar”.

`__init__`(*name*)

name

class `angr.analyses.decompiler.structured_codegen.c.CStructuredCodeGenerator`(*func*, *sequence*,
indent=0,
cfg=None, *variable_kb*=None,
func_args=None,
binop_depth_cutoff=16,
show_casts=True,
braces_on_own_lines=True,
use_compound_assignments=True,
show_local_types=True,
comment_gotos=False,
cstyle_null_cmp=True,
flavor=None,
stmt_comments=None,
expr_comments=None,
show_externs=True,
externs=None,
const_formats=None,
show_demangled_name=True,
show_disambiguated_name=True,
ail_graph=None,
simplify_else_scope=True,
cstyle_ifs=True,
omit_func_header=False)

Bases: `BaseStructuredCodeGenerator`, `Analysis`

Parameters

- **func_args** (*List*[*SimVariable*] | *None*) –

- **binop_depth_cutoff** (*int*) –

__init__ (*func*, *sequence*, *indent*=0, *cfg*=*None*, *variable_kb*=*None*, *func_args*=*None*, *binop_depth_cutoff*=16, *show_casts*=*True*, *braces_on_own_lines*=*True*, *use_compound_assignments*=*True*, *show_local_types*=*True*, *comment_gotos*=*False*, *cstyle_null_cmp*=*True*, *flavor*=*None*, *stmt_comments*=*None*, *expr_comments*=*None*, *show_externs*=*True*, *externs*=*None*, *const_formats*=*None*, *show_demangled_name*=*True*, *show_disambiguated_name*=*True*, *ail_graph*=*None*, *simplify_else_scope*=*True*, *cstyle_ifs*=*True*, *omit_func_header*=*False*)

Parameters

- **func_args** (*List*[*SimVariable*] | *None*) –

- **binop_depth_cutoff** (*int*) –

reapply_options (*options*)

cleanup ()

Remove existing rendering results.

regenerate_text ()

Re-render text and re-generate all sorts of mapping information.

Return type

None

RENDER_TYPE

alias of *Tuple*[*str*, *PositionMapping*, *PositionMapping*, *InstructionMapping*, *Dict*[*Any*, *Set*[*Any*]]]

render_text (*cfunc*)

Return type

Tuple[*str*, *PositionMapping*, *PositionMapping*, *InstructionMapping*, *Dict*[*Any*, *Set*[*Any*]]]

Parameters

- **cfunc** (*CFunction*) –

reload_variable_types ()

Return type

None

default_simtype_from_size (*n*, *signed*=*True*)

Return type

SimType

Parameters

- **n** (*int*) –

- **signed** (*bool*) –

project: *Project*

kb: *KnowledgeBase*

```
class angr.analyses.decompiler.structured_codegen.c.CStructuredCodeWalker
```

```
    Bases: object
```

```
    classmethod handle(obj)
```

```
    classmethod handle_default(obj)
```

```
    classmethod handle_CFunction(obj)
```

```
    classmethod handle_CStatements(obj)
```

```
    classmethod handle_CWhileLoop(obj)
```

```
    classmethod handle_CDoWhileLoop(obj)
```

```
    classmethod handle_CForLoop(obj)
```

```
    classmethod handle_CIfElse(obj)
```

```
    classmethod handle_CIfBreak(obj)
```

```
    classmethod handle_CSwitchCase(obj)
```

```
    classmethod handle_CAssignment(obj)
```

```
    classmethod handle_CFunctionCall(obj)
```

```
    classmethod handle_CReturn(obj)
```

```
    classmethod handle_CGoto(obj)
```

```
    classmethod handle_CIndexedVariable(obj)
```

```
    classmethod handle_CVariableField(obj)
```

```
    classmethod handle_CUnaryOp(obj)
```

```
    classmethod handle_CBinaryOp(obj)
```

```
    classmethod handle_CTypeCast(obj)
```

```
    classmethod handle_CITE(obj)
```

```
class angr.analyses.decompiler.structured_codegen.c.MakeTypecastsImplicit
```

```
    Bases: CStructuredCodeWalker
```

```
    classmethod collapse(dst_ty, child)
```

```
        Return type
```

```
        CExpression
```

```
        Parameters
```

- *dst_ty* (*SimType*) –
- *child* (*CExpression*) –

```
    classmethod handle_CAssignment(obj)
```

classmethod `handle_CFunctionCall(obj)`

Parameters

`obj` (`CFunctionCall`) –

classmethod `handle_CReturn(obj)`

Parameters

`obj` (`CReturn`) –

classmethod `handle_CBinaryOp(obj)`

Parameters

`obj` (`CBinaryOp`) –

classmethod `handle_CTypeCast(obj)`

Parameters

`obj` (`CTypeCast`) –

class `angr.analyses.decompiler.structured_codegen.c.FieldReferenceCleanup`

Bases: `CStructuredCodeWalker`

classmethod `handle_CTypeCast(obj)`

class `angr.analyses.decompiler.structured_codegen.c.PointerArithmeticFixer`

Bases: `CStructuredCodeWalker`

Before calling this fixer class, pointer arithmetics are purely integer-based and ignoring the pointer type.

For example, in the following case:

```
struct A* a_ptr; // assume struct A is 24 bytes in size
a_ptr = a_ptr + 24;
```

It means adding 24 to the address of `a_ptr`, without considering the size of struct A. This fixer class will make pointer arithmetics aware of the pointer type. In this case, the fixer class will convert the code to `a_ptr = a_ptr + 1`.

classmethod `handle_CBinaryOp(obj)`

`angr.analyses.decompiler.structured_codegen.c.StructuredCodeGenerator`

alias of `CStructuredCodeGenerator`

class `angr.analyses.decompiler.structured_codegen.dwarf_import.ImportedLine(addr)`

Bases: `object`

__init__(`addr`)

class `angr.analyses.decompiler.structured_codegen.dwarf_import.ImportSourceCode(function, flavor='source', source_root=None, encoding='utf-8')`

Bases: `BaseStructuredCodeGenerator`, `Analysis`

__init__(`function`, `flavor='source'`, `source_root=None`, `encoding='utf-8'`)

regenerate_text()

project: `Project`

kb: `KnowledgeBase`

```
class angr.analyses.decompiler.structured_codegen.dummy.DummyStructuredCodeGenerator(flavor,
                                                                                   expr_comments=None,
                                                                                   stmt_comments=None,
                                                                                   con-
                                                                                   figu-
                                                                                   ra-
                                                                                   tion=None,
                                                                                   const_formats=None)
```

Bases: `BaseStructuredCodeGenerator`

A dummy structured code generator that only stores user-specified information.

Parameters

flavor (*str*) –

```
__init__(flavor, expr_comments=None, stmt_comments=None, configuration=None, const_formats=None)
```

Parameters

flavor (*str*) –

```
angr.analyses.decompiler.utils.remove_last_statement(node)
```

```
angr.analyses.decompiler.utils.append_statement(node, stmt)
```

```
angr.analyses.decompiler.utils.replace_last_statement(node, old_stmt, new_stmt)
```

```
angr.analyses.decompiler.utils.extract_jump_targets(stmt)
```

Extract concrete goto targets from a Jump or a ConditionalJump statement.

Parameters

stmt – The statement to analyze.

Returns

A list of known concrete jump targets.

Return type

`list`

```
angr.analyses.decompiler.utils.switch_extract_cmp_bounds(last_stmt)
```

Check the last statement of the switch-case header node, and extract lower+upper bounds for the comparison.

Parameters

last_stmt (`ConditionalJump`) – The last statement of the switch-case header node.

Return type

`Optional[Tuple[Any, int, int]]`

Returns

A tuple of (comparison expression, lower bound, upper bound), or None

```
angr.analyses.decompiler.utils.get_ast_subexprs(claripy_ast)
```

```
angr.analyses.decompiler.utils.insert_node(parent, insert_location, node, node_idx, label=None)
```

Parameters

- **insert_location** (*str*) –

- **node_idx** (*int* | `Tuple[int]` | None) –

`angr.analyses.decompiler.utils.to_ail_supergraph(transition_graph)`

Takes an AIL graph and converts it into a AIL graph that treats calls and redundant jumps as parts of a bigger block instead of transitions. Calls to returning functions do not terminate basic blocks.

Based on `region_identifier` `super_graph`

Return type

`DiGraph`

Returns

A converted super transition graph

Parameters

transition_graph (`DiGraph`) –

`angr.analyses.decompiler.utils.is_empty_node(node)`

Return type

`bool`

`angr.analyses.decompiler.utils.is_empty_or_label_only_node(node)`

Return type

`bool`

`angr.analyses.decompiler.utils.has_nonlabel_statements(block)`

Return type

`bool`

Parameters

block (`Block`) –

`angr.analyses.decompiler.utils.first_nonlabel_statement(block)`

Return type

`Optional[Statement]`

Parameters

block (`Block` / `MultiNode`) –

`angr.analyses.decompiler.utils.last_nonlabel_statement(block)`

Return type

`Optional[Statement]`

Parameters

block (`Block`) –

`angr.analyses.decompiler.utils.first_nonlabel_node(seq)`

Return type

`Union[BaseNode, Block, None]`

Parameters

seq (`SequenceNode`) –

`angr.analyses.decompiler.utils.remove_labels(graph)`

Parameters

graph (`DiGraph`) –

`angr.analyses.decompiler.utils.add_labels(graph)`

Parameters

graph (*DiGraph*) –

`angr.analyses.decompiler.utils.update_labels(graph)`

A utility function to recreate the labels for every node in an AIL graph. This useful when you are working with a graph where only `_some_` of the nodes have labels.

Parameters

graph (*DiGraph*) –

`angr.analyses.decompiler.utils.structured_node_is_simple_return(node, graph)`

Return type

`bool`

Parameters

- **node** (*SequenceNode* / *MultiNode*) –
- **graph** (*DiGraph*) –

Will check if a “simple return” is contained within the node a simple returns looks like this: `if (cond) {
// simple return ... return 0;`

10.15.1 }

Returns true on any block ending in linear statements and a return.

`angr.analyses.decompiler.utils.is_statement_terminating(stmt, functions)`

Return type

`bool`

Parameters

stmt (*Statement*) –

`angr.analyses.decompiler.utils.peephole_optimize_exprs(block, expr_opts)`

`angr.analyses.decompiler.utils.peephole_optimize_expr(expr, expr_opts)`

`angr.analyses.decompiler.utils.copy_graph(graph)`

Copy AIL Graph.

Returns

A copy of the AIL graph.

Parameters

graph (*DiGraph*) –

`angr.analyses.decompiler.utils.peephole_optimize_stmts(block, stmt_opts)`

`angr.analyses.decompiler.utils.match_stmt_classes(all_stmts, idx, stmt_class_seq)`

Return type

`bool`

Parameters

- **all_stmts** (*List*) –

- **idx** (*int*) –
- **stmt_class_seq** (*Iterable[type]*) –

`angr.analyses.decompiler.utils.peephole_optimize_multistmts(block, stmt_opts)`

`angr.analyses.decompiler.utils.decompile_functions(path, functions=None, structurer=None, catch_errors=False)`

Decompile a binary into a set of functions.

Parameters

- **path** – The path to the binary to decompile.
- **functions** – The functions to decompile. If None, all functions will be decompiled.
- **structurer** – The structuring algorithms to use.
- **catch_errors** – The structuring algorithms to use.

Return type

Optional[str]

Returns

The decompilation of all functions appended in order.

`angr.analyses.decompiler.utils.calls_in_graph(graph)`

Counts the number of calls in an graph full of AIL Blocks

Return type

int

Parameters

graph (*DiGraph*) –

`angr.analyses.decompiler.utils.find_block_by_addr(graph, addr)`

Parameters

- **graph** (*DiGraph*) –
- **addr** (*int*) –

`angr.analyses.decompiler.utils.sequence_to_blocks(seq)`

Converts a sequence node (BaseNode) to a list of ailment blocks contained in it and all its children.

Return type

List[Block]

Parameters

seq (*BaseNode*) –

`angr.analyses.decompiler.utils.sequence_to_statements(seq, exclude=(<class 'ailment.statement.Jump'>, <class 'ailment.statement.Jump'>))`

Converts a sequence node (BaseNode) to a list of ailment Statements contained in it and all its children. May exclude certain types of statements.

Return type

List[Statement]

Parameters

seq (*BaseNode*) –

```
class angr.analyses.ddg.AST(op, *operands)
    Bases: object
    A mini implementation for AST
    __init__(op, *operands)

class angr.analyses.ddg.ProgramVariable(variable, location, initial=False, arch=None)
    Bases: object
    Describes a variable in the program at a specific location.

    Variables
    • variable (SimVariable) – The variable.
    • location (CodeLocation) – Location of the variable.
    __init__(variable, location, initial=False, arch=None)

    property short_repr

class angr.analyses.ddg.DDGJob(cfg_node, call_depth)
    Bases: object
    __init__(cfg_node, call_depth)

class angr.analyses.ddg.LiveDefinitions
    Bases: object
    A collection of live definitions with some handy interfaces for definition killing and lookups.
    __init__()
    Constructor.

    branch()
    Create a branch of the current live definition collection.

    Returns
    A new LiveDefinition instance.

    Return type
    angr.analyses.ddg.LiveDefinitions

    copy()
    Make a hard copy of self.

    Returns
    A new LiveDefinition instance.

    Return type
    angr.analyses.ddg.LiveDefinitions

    add_def(variable, location, size_threshold=32)
    Add a new definition of variable.

    Parameters
    • variable (SimVariable) – The variable being defined.
    • location (CodeLocation) – Location of the variable being defined.
    • size_threshold (int) – The maximum bytes to consider for the variable.
```

Returns

True if the definition was new, False otherwise

Return type

bool

add_defs(*variable*, *locations*, *size_threshold*=32)

Add a collection of new definitions of a variable.

Parameters

- **variable** (*SimVariable*) – The variable being defined.
- **locations** (*iterable*) – A collection of locations where the variable was defined.
- **size_threshold** (*int*) – The maximum bytes to consider for the variable.

Returns

True if any of the definition was new, False otherwise

Return type

bool

kill_def(*variable*, *location*, *size_threshold*=32)

Add a new definition for variable and kill all previous definitions.

Parameters

- **variable** (*SimVariable*) – The variable to kill.
- **location** (*CodeLocation*) – The location where this variable is defined.
- **size_threshold** (*int*) – The maximum bytes to consider for the variable.

Returns

None

lookup_defs(*variable*, *size_threshold*=32)

Find all definitions of the variable.

Parameters

- **variable** (*SimVariable*) – The variable to lookup for.
- **size_threshold** (*int*) – The maximum bytes to consider for the variable. For example, if the variable is 100 byte long, only the first *size_threshold* bytes are considered.

Returns

A set of code locations where the variable is defined.

Return type

set

items()

An iterator that returns all live definitions.

Returns

The iterator.

Return type

iter

itervariables()

An iterator that returns all live variables.

Returns

The iterator.

Return type

iter

```
class angr.analyses.ddg.DDGViewItem(ddg, variable, simplified=False)
```

Bases: `object`

```
__init__(ddg, variable, simplified=False)
```

property depends_on

property dependents

```
class angr.analyses.ddg.DDGViewInstruction(cfg, ddg, insn_addr, simplified=False)
```

Bases: `object`

```
__init__(cfg, ddg, insn_addr, simplified=False)
```

property definitions: `List[DDGViewItem]`

Get all definitions located at the current instruction address.

Returns

A list of ProgramVariable instances.

```
class angr.analyses.ddg.DDGView(cfg, ddg, simplified=False)
```

Bases: `object`

A view of the data dependence graph.

```
__init__(cfg, ddg, simplified=False)
```

```
class angr.analyses.ddg.DDG(cfg, start=None, call_depth=None, block_addrs=None)
```

Bases: `Analysis`

This is a fast data dependence graph directly generated from our CFG analysis result. The only reason for its existence is the speed. There is zero guarantee for being sound or accurate. You are supposed to use it only when you want to track the simplest data dependence, and you do not care about soundness or accuracy.

For a better data dependence graph, please consider performing a better static analysis first (like Value-set Analysis), and then construct a dependence graph on top of the analysis result (for example, the VFG in angr).

The DDG is based on a CFG, which should ideally be a CFGEmulated generated with the following options:

- `keep_state=True` to keep all input states
- `state_add_options=angr.options.refs` to store memory, register, and temporary value accesses

You may want to consider a high value for `context_sensitivity_level` as well when generating the CFG.

Also note that since we are using states from CFG, any improvement in analysis performed on CFG (like a points-to analysis) will directly benefit the DDG.

```
__init__(cfg, start=None, call_depth=None, block_addrs=None)
```

Parameters

- **cfg** – Control flow graph. Please make sure each node has an associated *state* with it, e.g. by passing the `keep_state=True` and `state_add_options=angr.options.refs` arguments to `CFGEmulated`.
- **start** – An address, Specifies where we start the generation of this data dependence graph.
- **call_depth** – None or integers. A non-negative integer specifies how deep we would like to track in the call tree. None disables call_depth limit.
- **block_addrs** (*iterable or None*) – A collection of block addresses that the DDG analysis should be performed on.

property graph

A networkx DiGraph instance representing the dependence relations between statements. :rtype: networkx.DiGraph

Type

returns

property data_graph

Get the data dependence graph.

Returns

A networkx DiGraph instance representing data dependence.

Return type

networkx.DiGraph

property simplified_data_graph

return:

property ast_graph

pp()

Pretty printing.

dbg_repr()

Representation for debugging.

get_predecessors(*code_location*)

Returns all predecessors of the code location.

Parameters

code_location – A CodeLocation instance.

Returns

A list of all predecessors.

function_dependency_graph(*func*)

Get a dependency graph for the function *func*.

Parameters

func – The Function object in `CFG.function_manager`.

Returns

A networkx.DiGraph instance.

data_sub_graph(*pv*, *simplified=True*, *killing_edges=False*, *excluding_types=None*)

Get a subgraph from the data graph or the simplified data graph that starts from node *pv*.

Parameters

- **pv** (`ProgramVariable`) – The starting point of the subgraph.
- **simplified** (`bool`) – When True, the simplified data graph is used, otherwise the data graph is used.
- **killling_edges** (`bool`) – Are killing edges included or not.
- **excluding_types** (`iterable`) – Excluding edges whose types are among those excluded types.

Returns

A subgraph.

Return type

`networkx.MultiDiGraph`

find_definitions(*variable*, *location=None*, *simplified_graph=True*)

Find all definitions of the given variable.

Parameters

- **variable** (`SimVariable`) –
- **simplified_graph** (`bool`) – True if you just want to search in the simplified graph instead of the normal graph. Usually the simplified graph suffices for finding definitions of register or memory variables.

Returns

A collection of all variable definitions to the specific variable.

Return type

`list`

find_consumers(*var_def*, *simplified_graph=True*)

Find all consumers to the specified variable definition.

Parameters

- **var_def** (`ProgramVariable`) – The variable definition.
- **simplified_graph** (`bool`) – True if we want to search in the simplified graph, False otherwise.

Returns

A collection of all consumers to the specified variable definition.

Return type

`list`

find_killers(*var_def*, *simplified_graph=True*)

Find all killers to the specified variable definition.

Parameters

- **var_def** (`ProgramVariable`) – The variable definition.
- **simplified_graph** (`bool`) – True if we want to search in the simplified graph, False otherwise.

Returns

A collection of all killers to the specified variable definition.

Return type

`list`

find_sources(*var_def*, *simplified_graph=True*)

Find all sources to the specified variable definition.

Parameters

- **var_def** ([ProgramVariable](#)) – The variable definition.
- **simplified_graph** (*bool*) – True if we want to search in the simplified graph, False otherwise.

Returns

A collection of all sources to the specified variable definition.

Return type

[list](#)

project: [Project](#)

kb: [KnowledgeBase](#)

class [angr.analyses.flirt.FlirtAnalysis](#)(*sig=None*)

Bases: [Analysis](#)

FlirtAnalysis accomplishes two purposes:

- If a FLIRT signature file is specified, it will match the given signature file against the current binary and rename recognized functions accordingly.
- If no FLIRT signature file is specified, it will use strings to determine possible libraries embedded in the current binary, and then match all possible signatures for the architecture.

Parameters

sig ([FlirtSignature](#) | *str* | *None*) –

__init__(*sig=None*)

Parameters

sig ([FlirtSignature](#) | *str* | *None*) –

project: [Project](#)

kb: [KnowledgeBase](#)

class [angr.engines.light.data.ArithmeticExpression](#)(*op*, *operands*)

Bases: [object](#)

Add = 0

Sub = 1

Or = 2

And = 4

RShift = 8

LShift = 16

Mul = 32

Xor = 64


```

CONST_TYPES = (<class 'int'>, <class 'ailment.expression.Const'>)

__init__(op, operands)

op

operands

static try_unpack_const(expr)

class angr.engines.light.data.RegisterOffset(bits, reg, offset)
    Bases: object
    __init__(bits, reg, offset)

    reg

    offset

    property bits

    property symbolic

class angr.engines.light.data.SpOffset(bits, offset, is_base=False)
    Bases: RegisterOffset
    __init__(bits, offset, is_base=False)

    is_base

class angr.engines.light.engine.SimEngineLightMixin(*args, logger=None, **kwargs)
    Bases: object
    A mixin base class for engines meant to perform static analysis
    __init__(*args, logger=None, **kwargs)

    static sp_offset(bits, offset)

        Parameters

        • bits (int) –

        • offset (int) –

    static extract_offset_to_sp(spoffset_expr)
        Extract the offset to the original stack pointer.

        Parameters
        spoffset_expr (Base) – The claripy AST to parse.

        Return type
        Optional[int]

        Returns
        The offset to the original stack pointer, or None if spoffset_expr is not a supported type of
        SpOffset expression.

class angr.engines.light.engine.SimEngineLight
    Bases: SimEngineLightMixin, SimEngine
    A full-featured engine base class, suitable for static analysis

```

__init__()

process(*state*, **args*, ***kwargs*)

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

class `angr.engines.light.engine.SimEngineLightVEXMixin(*args, logger=None, **kwargs)`

Bases: [`SimEngineLightMixin`](#)

A mixin for doing static analysis on VEX

class `angr.engines.light.engine.SimEngineLightAILMixin(*args, logger=None, **kwargs)`

Bases: [`SimEngineLightMixin`](#)

A mixin for doing static analysis on AIL

`angr.engines.light.engine.SimEngineLightVEX`

alias of [`SimEngineLightVEXMixin`](#)

`angr.engines.light.engine.SimEngineLightAIL`

alias of [`SimEngineLightAILMixin`](#)

class `angr.analyses.propagator.values.Top(size)`

Bases: `object`

__init__(*size*)

size

property bits

class `angr.analyses.propagator.values.Bottom`

Bases: `object`

class `angr.analyses.propagator.vex_vars.VEXVariable`

Bases: `object`

class `angr.analyses.propagator.vex_vars.VEXMemVar(addr, size)`

Bases: `object`

__init__(*addr*, *size*)

addr

size

class `angr.analyses.propagator.vex_vars.VEXReg(offset, size)`

Bases: [`VEXVariable`](#)

__init__(*offset*, *size*)

offset

size

```
class angr.analyses.propagator.vex_vars.VEXTmp(tmp)
```

Bases: *VEXVariable*

```
__init__(tmp)
```

```
tmp
```

```
class angr.analyses.propagator.engine_base.SimEnginePropagatorBase(stack_pointer_tracker=None,
                                                                    project=None,
                                                                    propagate_tmps=True,
                                                                    arch=None,
                                                                    reaching_definitions=None,
                                                                    immediate_stmt_removal=False,
                                                                    bp_as_gpr=False)
```

Bases: *SimEngineLight*

Parameters

- **reaching_definitions** (*ReachingDefinitionsModel* / *None*) –
- **immediate_stmt_removal** (*bool*) –
- **bp_as_gpr** (*bool*) –

```
__init__(stack_pointer_tracker=None, project=None, propagate_tmps=True, arch=None,
         reaching_definitions=None, immediate_stmt_removal=False, bp_as_gpr=False)
```

Parameters

- **reaching_definitions** (*ReachingDefinitionsModel* / *None*) –
- **immediate_stmt_removal** (*bool*) –
- **bp_as_gpr** (*bool*) –

```
process(state, *args, **kwargs)
```

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

```
class angr.analyses.propagator.engine_vex.SimEnginePropagatorVEX(stack_pointer_tracker=None,
                                                                    project=None,
                                                                    propagate_tmps=True,
                                                                    arch=None,
                                                                    reaching_definitions=None,
                                                                    immediate_stmt_removal=False,
                                                                    bp_as_gpr=False)
```

Bases: *TopCheckerMixin*, *SimEngineLightVEXMixin*, *SimEnginePropagatorBase*

Parameters

- **reaching_definitions** (*ReachingDefinitionsModel* / *None*) –
- **immediate_stmt_removal** (*bool*) –
- **bp_as_gpr** (*bool*) –

state: `PropagatorVEXState`

```
class angr.analyses.propagator.engine_ail.SimEnginePropagatorAIL(stack_pointer_tracker=None,
                                                                project=None,
                                                                propagate_tmps=True,
                                                                arch=None,
                                                                reaching_definitions=None, im-
                                                                mediate_stmt_removal=False,
                                                                bp_as_gpr=False)
```

Bases: `SimEngineLightAILMixin`, `SimEnginePropagatorBase`

The AIL engine for Propagator.

Parameters

- **reaching_definitions** (`ReachingDefinitionsModel` / `None`) –
- **immediate_stmt_removal** (`bool`) –
- **bp_as_gpr** (`bool`) –

state: `PropagatorAILState`

extract_offset_to_sp(*expr*)

Extract the offset to the original stack pointer.

Parameters

- **spoffset_expr** – The claripy AST to parse.
- **expr** (`Base` / `StackBaseOffset`) –

Return type

`Optional[int]`

Returns

The offset to the original stack pointer, or `None` if *spoffset_expr* is not a supported type of `SpOffset` expression.

is_using_outdated_def(*expr*, *expr_defat*, *current_loc*, *avoid*=`None`)

Return type

`Tuple[bool, bool]`

Parameters

- **expr** (`Expression`) –
- **expr_defat** (`CodeLocation` / `None`) –
- **current_loc** (`CodeLocation`) –
- **avoid** (`Expression` / `None`) –

should_force_replace(*stmt*, *new_expr*)

Determine if the expression should be replaced.

We always replace the expression if:

- the current statement is an indirect jump. this is to ensure the dynamically calculated jump targets are always using the originally defined expressions, which usually leads to better decompilation output.
- the current statement is a return to make void functions (even when we incorrectly determine that they return something) look better in general.

- the current statement has a shift-right operation and the source expression has a shift-right operation. this is to support the peephole optimizations for division and modulo.

Parameters

- **stmt** ([Statement](#)) –
- **new_expr** ([Expression](#)) –

Return type

[bool](#)

Returns

static **has_tmpexpr**(*expr*)

Return type

[bool](#)

Parameters

- **expr** ([Expression](#)) –

```
class angr.analyses.propagator.outdated_definition_walker.OutdatedDefinitionWalker(expr,
                                                                                   expr_defat,
                                                                                   current_loc,
                                                                                   state,
                                                                                   arch,
                                                                                   avoid=None,
                                                                                   extract_offset_to_sp=None,
                                                                                   rda=None)
```

Bases: [AILBlockWalker](#)

Walks an AIL expression to find outdated definitions.

Parameters

- **expr_defat** ([CodeLocation](#)) –
- **current_loc** ([CodeLocation](#)) –
- **state** ([PropagatorAILState](#)) –
- **arch** ([Arch](#)) –
- **avoid** ([Expression](#) | [None](#)) –
- **extract_offset_to_sp** ([Callable](#)) –
- **rda** ([ReachingDefinitionsModel](#)) –

__init__(*expr*, *expr_defat*, *current_loc*, *state*, *arch*, *avoid*=None, *extract_offset_to_sp*=None, *rda*=None)

Parameters

- **expr_defat** ([CodeLocation](#)) –
- **current_loc** ([CodeLocation](#)) –
- **state** ([PropagatorAILState](#)) –
- **arch** ([Arch](#)) –
- **avoid** ([Expression](#) | [None](#)) –

- `extract_offset_to_sp(Callable | None)` –
- `rda(ReachingDefinitionsModel | None)` –

class `angr.analyses.propagator.tmpvar_finder.TmpvarFinder(expr)`

Bases: `AILBlockWalkerBase`

Walks an AIL expression to find Tmp expressions.

Parameters

expr (`Expression`) –

`__init__(expr)`

Parameters

expr (`Expression`) –

class `angr.analyses.propagator.propagator.PropagatorAnalysis(func=None, block=None, func_graph=None, base_state=None, max_iterations=30, load_callback=None, stack_pointer_tracker=None, only_consts=False, completed_funcs=None, do_binops=True, store_tops=True, vex_cross_insn_opt=False, func_addr=None, gp=None, cache_results=False, key_prefix=None, reaching_definitions=None, immediate_stmt_removal=False, profiling=False)`

Bases: `ForwardAnalysis`, `Analysis`

`PropagatorAnalysis` implements copy propagation. It propagates values (either constant values or variables) and expressions inside a block or across a function.

`PropagatorAnalysis` supports both VEX and AIL. The VEX propagator only performs constant propagation. The AIL propagator performs both constant propagation and copy propagation of depth-N expressions.

`PropagatorAnalysis` performs certain arithmetic operations between constants, including but are not limited to:

- addition
- subtraction
- multiplication
- division
- xor

It also performs the following memory operations:

- Loading values from a known address
- Writing values to a stack variable

```
__init__(func=None, block=None, func_graph=None, base_state=None, max_iterations=30,
         load_callback=None, stack_pointer_tracker=None, only_consts=False, completed_funcs=None,
         do_binops=True, store_tops=True, vex_cross_insn_opt=False, func_addr=None, gp=None,
         cache_results=False, key_prefix=None, reaching_definitions=None,
         immediate_stmt_removal=False, profiling=False)
```

Constructor

Parameters

- **order_jobs** (*bool*) – If all jobs should be ordered or not.
- **allow_merging** (*bool*) – If job merging is allowed.
- **allow_widening** (*bool*) – If job widening is allowed.
- **graph_visitor** (*GraphVisitor* or *None*) – A graph visitor to provide successors.
- **func_addr** (*int* | *None*) –
- **gp** (*int* | *None*) –
- **cache_results** (*bool*) –
- **key_prefix** (*str* | *None*) –
- **reaching_definitions** (*ReachingDefinitionsModel* | *None*) –
- **immediate_stmt_removal** (*bool*) –
- **profiling** (*bool*) –

Returns

None

```
property prop_key: Tuple[str | None, str, int, bool, bool, bool]
```

Gets a key that represents the function and the “flavor” of the propagation result.

```
property replacements
```

```
project: Project
```

```
kb: KnowledgeBase
```

```
class angr.analyses.propagator.top_checker_mixin.TopCheckerMixin(*args, logger=None,
                                                                **kwargs)
```

Bases: *SimEngineLightMixin*

```
class angr.analyses.reaching_definitions.LiveDefinitions(arch, track_tmps=False,
                                                         canonical_size=8, registers=None,
                                                         stack=None, memory=None, heap=None,
                                                         tmpls=None, others=None,
                                                         register_uses=None, stack_uses=None,
                                                         heap_uses=None, memory_uses=None,
                                                         tmp_uses=None, other_uses=None,
                                                         element_limit=5)
```

Bases: *object*

A LiveDefinitions instance contains definitions and uses for register, stack, memory, and temporary variables, uncovered during the analysis.

Parameters

- **arch** (*Arch*) –

- `track_tmps` (*bool*) –
- `registers` (*MultiValuedMemory*) –
- `stack` (*MultiValuedMemory*) –
- `memory` (*MultiValuedMemory*) –
- `heap` (*MultiValuedMemory*) –
- `tmpls` (*Dict[int, Set[Definition]]*) –
- `others` (*Dict[Atom, MultiValues]*) –
- `tmp_uses` (*Dict[int, Set[CodeLocation]]*) –

`INITIAL_SP_32BIT = 2147418112`

`INITIAL_SP_64BIT = 140737488289792`

`__init__(arch, track_tmpls=False, canonical_size=8, registers=None, stack=None, memory=None, heap=None, tmpls=None, others=None, register_uses=None, stack_uses=None, heap_uses=None, memory_uses=None, tmp_uses=None, other_uses=None, element_limit=5)`

Parameters

- `arch` (*Arch*) –
- `track_tmpls` (*bool*) –

`project: Optional[Project]`

`arch`

`track_tmpls`

`registers: MultiValuedMemory`

`stack: MultiValuedMemory`

`memory: MultiValuedMemory`

`heap: MultiValuedMemory`

`tmpls: Dict[int, Set[Definition]]`

`others: Dict[Atom, MultiValues]`

`register_uses`

`stack_uses`

`heap_uses`

`memory_uses`

`tmp_uses: Dict[int, Set[CodeLocation]]`

`other_uses`

`uses_by_codeloc: Dict[CodeLocation, Set[Definition]]`

`property register_definitions`

property `stack_definitions`

property `memory_definitions`

property `heap_definitions`

copy(*discard_tmpdefs=False*)

Return type

LiveDefinitions

reset_uses()

static top(*bits*)

Get a TOP value.

Parameters

bits (*int*) – Width of the TOP value (in bits).

Returns

The TOP value.

static is_top(*expr*)

Check if the given expression is a TOP value.

Parameters

expr – The given expression.

Return type

bool

Returns

True if the expression is TOP, False otherwise.

stack_address(*offset*)

Return type

Optional[BV]

Parameters

offset (*int*) –

static is_stack_address(*addr*)

Return type

bool

Parameters

addr (*Base*) –

static get_stack_offset(*addr, had_stack_base=False*)

Return type

Optional[int]

Parameters

addr (*Base*) –

static annotate_with_def(*symvar, definition*)

Parameters

- **symvar** (*BV*) –

- **definition** (*Definition*) –

Return type

BV

Returns

static **extract_defs**(*symvar*)

Return type

Generator[Definition, None, None]

Parameters

symvar (*Base*) –

static **extract_defs_from_annotations**(*annos*)

Return type

Set[Definition]

Parameters

annos (*Iterable[Annotation]*) –

static **extract_defs_from_mv**(*mv*)

Return type

Generator[Definition, None, None]

Parameters

mv (*MultiValues*) –

get_sp()

Return the concrete value contained by the stack pointer.

Return type

int

get_sp_offset()

Return the offset of the stack pointer.

Return type

Optional[int]

get_stack_address(*offset*)

Return type

Optional[int]

Parameters

offset (*Base*) –

stack_offset_to_stack_addr(*offset*)

Return type

int

merge(**others*)

Return type

Tuple[LiveDefinitions, bool]

Parameters

others (*LiveDefinitions*) –

compare(*other*)

Return type

`bool`

Parameters

other (`LiveDefinitions`) –

kill_definitions(*atom*)

Overwrite existing definitions w.r.t ‘atom’ with a dummy definition instance. A dummy definition will not be removed during simplification.

Parameters

atom (`Atom`) –

Return type

`None`

Returns

`None`

kill_and_add_definition(*atom*, *code_loc*, *data*, *dummy=False*, *tags=None*, *endness=None*, *annotated=False*)

Return type

`Optional[MultiValues]`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **data** (`MultiValues`) –
- **tags** (`Set[Tag]` | `None`) –

add_use(*atom*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **atom** (`Atom`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

add_use_by_def(*definition*, *code_loc*, *expr=None*)

Return type

`None`

Parameters

- **definition** (`Definition`) –
- **code_loc** (`CodeLocation`) –
- **expr** (`Any` | `None`) –

get_definitions(*thing*)

Return type

`Set[Definition[Atom]]`

Parameters

thing (Atom / Definition[Atom] / Iterable[Atom] /
Iterable[Definition[Atom]] / MultiValues) –

get_tmp_definitions(*tmp_idx*)

Return type

`Set[Definition]`

Parameters

tmp_idx (*int*) –

get_register_definitions(*reg_offset, size*)

Return type

`Set[Definition]`

Parameters

- **reg_offset** (*int*) –
- **size** (*int*) –

get_stack_values(*stack_offset, size, endness*)

Return type

`Optional[MultiValues]`

Parameters

- **stack_offset** (*int*) –
- **size** (*int*) –
- **endness** (*str*) –

get_stack_definitions(*stack_offset, size*)

Return type

`Set[Definition]`

Parameters

- **stack_offset** (*int*) –
- **size** (*int*) –

get_heap_definitions(*heap_addr, size*)

Return type

`Set[Definition]`

Parameters

- **heap_addr** (*int*) –
- **size** (*int*) –

`get_memory_definitions(addr, size)`

Return type

`Set[Definition]`

Parameters

- `addr` (`int`) –
- `size` (`int`) –

`get_definitions_from_atoms(**kwargs)`

`get_value_from_definition(**kwargs)`

`get_one_value_from_definition(**kwargs)`

`get_concrete_value_from_definition(**kwargs)`

`get_value_from_atom(**kwargs)`

`get_one_value_from_atom(**kwargs)`

`get_concrete_value_from_atom(**kwargs)`

`get_values(spec)`

Return type

`Optional[MultiValues]`

Parameters

`spec` (`Atom` / `Definition[Atom]` / `Iterable[Atom]` / `Iterable[Definition[Atom]]`) –

`get_one_value(spec, strip_annotations=False)`

Return type

`Optional[BV]`

Parameters

- `spec` (`Atom` / `Definition` / `Iterable[Atom]` / `Iterable[Definition[Atom]]`) –
- `strip_annotations` (`bool`) –

`get_concrete_value(spec, cast_to=<class 'int'>)`

Return type

`Union[int, bytes, None]`

Parameters

- `spec` (`Atom` / `Definition[Atom]` / `Iterable[Atom]` / `Iterable[Definition[Atom]]`) –
- `cast_to` (`Type[int]` / `Type[bytes]`) –

`add_register_use(reg_offset, size, code_loc, expr=None)`

Return type

`None`

Parameters

- `reg_offset` (*int*) –
- `size` (*int*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_register_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (*Definition*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_stack_use(atom, code_loc, expr=None)`

Return type

None

Parameters

- `atom` (*MemoryLocation*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_stack_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (*Definition*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_heap_use(atom, code_loc, expr=None)`

Return type

None

Parameters

- `atom` (*MemoryLocation*) –
- `code_loc` (*CodeLocation*) –
- `expr` (*Any* | *None*) –

`add_heap_use_by_def(def_, code_loc, expr=None)`

Return type

None

Parameters

- `def_` (*Definition*) –

- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use(atom, code_loc, expr=None)`

Return type

`None`

Parameters

- `atom` (`MemoryLocation`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_memory_use_by_def(def_, code_loc, expr=None)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –
- `expr` (`Any` | `None`) –

`add_tmp_use(atom, code_loc)`

Return type

`None`

Parameters

- `atom` (`Tmp`) –
- `code_loc` (`CodeLocation`) –

`add_tmp_use_by_def(def_, code_loc)`

Return type

`None`

Parameters

- `def_` (`Definition`) –
- `code_loc` (`CodeLocation`) –

`deref(pointer, size, endness=Endness.BE)`

`static is_heap_address(addr)`

Return type

`bool`

Parameters

`addr` (`Base`) –

`static get_heap_offset(addr)`

Return type

`Optional[int]`

Parameters

addr (*Base*) –

heap_address(*offset*)

Return type

BV

Parameters

offset (*int* / *HeapAddress*) –

class `angr.analyses.reaching_definitions.ObservationPointType`(*value*)

Bases: *IntEnum*

Enum to replace the previously generic constants This makes it possible to annotate where they are expected by typing something as `ObservationPointType` instead of `Literal[0,1]`

OP_BEFORE = 0

OP_AFTER = 1

class `angr.analyses.reaching_definitions.AtomKind`(*value*)

Bases: *Enum*

An enum indicating the class of an atom

REGISTER = 1

MEMORY = 2

TMP = 3

GUARD = 4

CONSTANT = 5

class `angr.analyses.reaching_definitions.Atom`(*size*)

Bases: *object*

This class represents a data storage location manipulated by IR instructions.

It could either be a `Tmp` (temporary variable), a `Register`, a `MemoryLocation`.

__init__(*size*)

Parameters

size – The size of the atom in bytes

size

property **bits**: *int*

static **from_ail_expr**(*expr*, *arch*, *full_reg=False*)

Return type

Register

Parameters

• **expr** (*Expression*) –

• **arch** (*Arch*) –

• **full_reg** (*bool*) –

static from_argument(*argument*, *arch*, *full_reg=False*, *sp=None*)

Instantiate an *Atom* from a given argument.

Parameters

- **argument** (*SimFunctionArgument*) – The argument to create a new atom from.
- **arch** (*Arch*) – The argument representing archinfo architecture for argument.
- **full_reg** – Whether to return an atom indicating the entire register if the argument only specifies a slice of the register.
- **sp** (*Optional[int]*) – The current stack offset. Optional. Only used when argument is a *SimStackArg*.

Return type

Union[Register, MemoryLocation]

static reg(*thing*, *size=None*, *arch=None*)

Create a Register atom.

Parameters

- **thing** (*Union[str, RegisterOffset]*) – The register offset (e.g., `project.arch.registers["rax"][0]`) or the register name (e.g., "rax").
- **size** (*Optional[int]*) – Size of the register atom. Must be provided when creating the atom using a register offset.
- **arch** (*Optional[Arch]*) – The architecture. Must be provided when creating the atom using a register name.

Return type

Register

Returns

The Register Atom object.

static register(*thing*, *size=None*, *arch=None*)

Create a Register atom.

Parameters

- **thing** (*Union[str, RegisterOffset]*) – The register offset (e.g., `project.arch.registers["rax"][0]`) or the register name (e.g., "rax").
- **size** (*Optional[int]*) – Size of the register atom. Must be provided when creating the atom using a register offset.
- **arch** (*Optional[Arch]*) – The architecture. Must be provided when creating the atom using a register name.

Return type

Register

Returns

The Register Atom object.

static mem(*addr*, *size*, *endness=None*)

Create a MemoryLocation atom,

Parameters

- **addr** (`Union[SpOffset, HeapAddress, int]`) – The memory location. Can be an `SpOffset` for stack variables, an `int` for global memory variables, or a `HeapAddress` for items on the heap.
- **size** (`int`) – Size of the atom.
- **endness** (`Optional[str]`) – Optional, either “`Iend_LE`” or “`Iend_BE`”.

Return type

`MemoryLocation`

Returns

The `MemoryLocation` Atom object.

static `memory(addr, size, endness=None)`

Create a `MemoryLocation` atom,

Parameters

- **addr** (`Union[SpOffset, HeapAddress, int]`) – The memory location. Can be an `SpOffset` for stack variables, an `int` for global memory variables, or a `HeapAddress` for items on the heap.
- **size** (`int`) – Size of the atom.
- **endness** (`Optional[str]`) – Optional, either “`Iend_LE`” or “`Iend_BE`”.

Return type

`MemoryLocation`

Returns

The `MemoryLocation` Atom object.

class `angr.analyses.reaching_definitions.Register(reg_offset, size, arch=None)`

Bases: `Atom`

Represents a given CPU register.

As an IR abstracts the CPU design to target different architectures, registers are represented as a separated memory space. Thus a register is defined by its offset from the base of this memory and its size.

Variables

- **reg_offset** (`int`) – The offset from the base to define its place in the memory bloc.
- **size** (`int`) – The size, in number of bytes.

Parameters

- **reg_offset** (`RegisterOffset`) –
- **size** (`int`) –
- **arch** (`Arch` | `None`) –

`__init__(reg_offset, size, arch=None)`

Parameters

- **size** (`int`) – The size of the atom in bytes
- **reg_offset** (`RegisterOffset`) –
- **arch** (`Arch` | `None`) –

`reg_offset`

arch

property name: `str`

class `angr.analyses.reaching_definitions.MemoryLocation(addr, size, endness=None)`

Bases: `Atom`

Represents a memory slice.

It is characterized by its address and its size.

Parameters

- `addr` (`SpOffset` / `int` / `BV`) –
- `size` (`int`) –
- `endness` (`str` / `None`) –

`__init__`(`addr`, `size`, `endness=None`)

Parameters

- `addr` (`int`) – The address of the beginning memory location slice.
- `size` (`int`) – The size of the represented memory location, in bytes.
- `endness` (`str` / `None`) –

`addr`: `Union[SpOffset, int, BV]`

`endness`

property `is_on_stack`: `bool`

True if this memory location is located on the stack.

property `symbolic`: `bool`

class `angr.analyses.reaching_definitions.Tmp(tmp_idx, size)`

Bases: `Atom`

Represents a variable used by the IR to store intermediate values.

Parameters

- `tmp_idx` (`int`) –
- `size` (`int`) –

`__init__`(`tmp_idx`, `size`)

Parameters

- `size` (`int`) – The size of the atom in bytes
- `tmp_idx` (`int`) –

`tmp_idx`

class `angr.analyses.reaching_definitions.GuardUse(target)`

Bases: `Atom`

Implements a guard use.

`__init__(target)`

Parameters

size – The size of the atom in bytes

target

class `angr.analyses.reaching_definitions.ConstantSrc(value, size)`

Bases: `Atom`

Represents a constant.

Parameters

- **value** (`int`) –
- **size** (`int`) –

`__init__(value, size)`

Parameters

- **size** (`int`) – The size of the atom in bytes
- **value** (`int`) –

value: `int`

class `angr.analyses.reaching_definitions.Definition(atom, codeloc, dummy=False, tags=None)`

Bases: `Generic[A]`

An atom definition.

Variables

- **atom** – The atom being defined.
- **codeloc** – Where this definition is created in the original binary code.
- **dummy** – Tell whether the definition should be considered dummy or not. During simplification by AILment, definitions marked as dummy will not be removed.
- **tags** – A set of tags containing information about the definition gathered during analyses.

`__init__(atom, codeloc, dummy=False, tags=None)`

Parameters

- **atom** (`A`) –
- **codeloc** (`CodeLocation`) –
- **dummy** (`bool`) –
- **tags** (`Set[Tag]` | `None`) –

atom: `TypeVar(A, bound= Atom)`

codeloc: `CodeLocation`

dummy: `bool`

tags

property offset: `int`

property size: `int`

matches(***kwargs*)

Return whether this definition has certain characteristics.

Return type

`bool`

```
class angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis(subject=None,
                                                                    func_graph=None,
                                                                    max_iterations=30,
                                                                    track_tmps=False,
                                                                    track_consts=True,
                                                                    observation_points=None,
                                                                    init_state=None,
                                                                    init_context=None,
                                                                    state_initializer=None,
                                                                    cc=None,
                                                                    function_handler=None,
                                                                    observe_all=False,
                                                                    visited_blocks=None,
                                                                    dep_graph=True,
                                                                    observe_callback=None,
                                                                    canonical_size=8,
                                                                    stack_pointer_tracker=None,
                                                                    use_callee_saved_regs_at_return=True,
                                                                    interfunction_level=0,
                                                                    track_liveness=True,
                                                                    func_addr=None,
                                                                    element_limit=5)
```

Bases: `ForwardAnalysis[ReachingDefinitionsState, NodeType, object, object]`, `Analysis`

ReachingDefinitionsAnalysis is a text-book implementation of a static data-flow analysis that works on either a function or a block. It supports both VEX and AIL. By registering observers to observation points, users may use this analysis to generate use-def chains, def-use chains, and reaching definitions, and perform other traditional data-flow analyses such as liveness analysis.

- I’ve always wanted to find a better name for this analysis. Now I gave up and decided to live with this name for the foreseeable future (until a better name is proposed by someone else).
- Aliasing is definitely a problem, and I forgot how aliasing is resolved in this implementation. I’ll leave this as a post-graduation TODO.
- Some more documentation and examples would be nice.

```
__init__(subject=None, func_graph=None, max_iterations=30, track_tmps=False, track_consts=True,
          observation_points=None, init_state=None, init_context=None, state_initializer=None, cc=None,
          function_handler=None, observe_all=False, visited_blocks=None, dep_graph=True,
          observe_callback=None, canonical_size=8, stack_pointer_tracker=None,
          use_callee_saved_regs_at_return=True, interfunction_level=0, track_liveness=True,
          func_addr=None, element_limit=5)
```

Parameters

- **subject** (`Union[Subject, Block, Block, Function, str, None]`) – The subject of the analysis: a function, or a single basic block
- **func_graph** – Alternative graph for `function.graph`.

- **max_iterations** – The maximum number of iterations before the analysis is terminated.
- **track_tmps** – Whether or not temporary variables should be taken into consideration during the analysis.
- **observation_points** (*iterable*) – A collection of tuples of (“node”|”insn”, ins_addr, OP_TYPE) defining where reaching definitions should be copied and stored. OP_TYPE can be OP_BEFORE or OP_AFTER.
- **init_state** (*Optional[ReachingDefinitionsState]*) – An optional initialization state. The analysis creates and works on a copy. Default to None: the analysis then initialize its own abstract state, based on the given <Subject>.
- **init_context** – If init_state is not given, this is used to initialize the context field of the initial state’s CodeLocation. The only default-supported type which may go here is a tuple of integers, i.e. a callstack. Anything else requires a custom FunctionHandler.
- **cc** – Calling convention of the function.
- **function_handler** (*Optional[FunctionHandler]*) – The function handler to update the analysis state and results on function calls.
- **observe_all** – Observe every statement, both before and after.
- **visited_blocks** – A set of previously visited blocks.
- **dep_graph** (*Union[DepGraph, bool, None]*) – An initial dependency graph to add the result of the analysis to. Set it to None to skip dependency graph generation.
- **canonical_size** – The sizes (in bytes) that objects with an UNKNOWN_SIZE are treated as for operations where sizes are necessary.
- **dep_graph** – Set this to True to generate a dependency graph for the subject. It will be available as *result.dep_graph*.
- **interfunction_level** (*int*) – The number of functions we should recurse into. This parameter is only used if function_handler is not provided.
- **track_liveness** (*bool*) – Whether to track liveness information. This can consume sizeable amounts of RAM on large functions. (e.g. ~15GB for a function with 4k nodes)
- **state_initializer** (*RDStateInitializer | None*) –
- **func_addr** (*int | None*) –
- **element_limit** (*int*) –

property **observed_results**: *Dict[Tuple[str, int, int], LiveDefinitions]*

property **all_definitions**

property **all_uses**

property **one_result**

property **dep_graph**: *DepGraph*

property **visited_blocks**

get_reaching_definitions(***kwargs*)

get_reaching_definitions_by_insn(*ins_addr, op_type*)

get_reaching_definitions_by_node(*node_addr, op_type*)

node_observe(*node_addr*, *state*, *op_type*, *node_idx=None*)

Parameters

- **node_addr** (*int*) – Address of the node.
- **state** (*ReachingDefinitionsState*) – The analysis state.
- **op_type** (*ObservationPointType*) – Type of the observation point. Must be one of the following: OP_BEFORE, OP_AFTER.
- **node_idx** (*Optional[int]*) – ID of the node. Used in AIL to differentiate blocks with the same address.

Return type

None

insn_observe(*insn_addr*, *stmt*, *block*, *state*, *op_type*)

Parameters

- **insn_addr** (*int*) – Address of the instruction.
- **stmt** (*Union[Statement, IRStmt]*) – The statement.
- **block** (*Union[Block, Block]*) – The current block.
- **state** (*ReachingDefinitionsState*) – The abstract analysis state.
- **op_type** (*ObservationPointType*) – Type of the observation point. Must be one of the following: OP_BEFORE, OP_AFTER.

Return type

None

stmt_observe(*stmt_idx*, *stmt*, *block*, *state*, *op_type*)

Parameters

- **stmt_idx** (*int*) –
- **stmt** (*Union[Statement, IRStmt]*) –
- **block** (*Union[Block, Block]*) –
- **state** (*ReachingDefinitionsState*) –
- **op_type** (*ObservationPointType*) –

Return type

None

Returns

exit_observe(*node_addr*, *exit_stmt_idx*, *block*, *state*, *node_idx=None*)

Parameters

- **node_addr** (*int*) –
- **exit_stmt_idx** (*int*) –
- **block** (*Block | Block*) –
- **state** (*ReachingDefinitionsState*) –
- **node_idx** (*int | None*) –

property subject

project: Project

kb: KnowledgeBase

callsites_to(*target*)

Return type

`Iterable[FunctionCallRelationships]`

Parameters

target (`int` | `str` | `Function`) –

class `angr.analyses.reaching_definitions.ReachingDefinitionsModel`(*func_addr=None*,
track_liveness=True)

Bases: `object`

Models the definitions, uses, and memory of a ReachingDefinitionState object

Parameters

- **func_addr** (`int` | `None`) –

- **track_liveness** (`bool`) –

__init__(*func_addr=None*, *track_liveness=True*)

Parameters

- **func_addr** (`int` | `None`) –

- **track_liveness** (`bool`) –

add_def(*d*)

Return type

`None`

Parameters

d (`Definition`) –

kill_def(*d*)

Return type

`None`

Parameters

d (`Definition`) –

at_new_stmt(*codeloc*)

Return type

`None`

Parameters

codeloc (`CodeLocation`) –

at_new_block(*code_loc*, *pred_codelocs*)

Return type

`None`

Parameters

- `code_loc` (`CodeLocation`) –
- `pred_codelocs` (`List[CodeLocation]`) –

`make_liveness_snapshot()`

Return type
`None`

`find_defs_at(code_loc, op=ObservationPointType.OP_BEFORE)`

Return type
`Set[Definition]`

Parameters

- `code_loc` (`CodeLocation`) –
- `op` (`int`) –

`get_defs(atom, code_loc, op)`

Return type
`Set[Definition]`

Parameters

- `atom` (`Atom`) –
- `code_loc` (`CodeLocation`) –
- `op` (`int`) –

`copy()`

Return type
`ReachingDefinitionsModel`

`merge(model)`

Parameters
`model` (`ReachingDefinitionsModel`) –

`get_observation_by_insn(ins_addr, kind)`

Return type
`Optional[LiveDefinitions]`

Parameters

- `ins_addr` (`int` | `CodeLocation`) –
- `kind` (`ObservationPointType`) –

`get_observation_by_node(node_addr, kind, node_idx=None)`

Return type
`Optional[LiveDefinitions]`

Parameters

- `node_addr` (`int` | `CodeLocation`) –
- `kind` (`ObservationPointType`) –
- `node_idx` (`int` | `None`) –

`get_observation_by_stmt`(*arg1*, *arg2*, *arg3*=None, *, *block_idx*=None)

`get_observation_by_exit`(*node_addr*, *stmt_idx*, *src_node_idx*=None)

Return type

`Optional[LiveDefinitions]`

Parameters

- **node_addr** (*int*) –
- **stmt_idx** (*int*) –
- **src_node_idx** (*int* | None) –

```
class angr.analyses.reaching_definitions.ReachingDefinitionsState(codeloc, arch, subject,
                                                                track_tmps=False,
                                                                track_consts=False,
                                                                analysis=None,
                                                                rtoc_value=None,
                                                                live_definitions=None,
                                                                canonical_size=8,
                                                                heap_allocator=None,
                                                                environment=None,
                                                                sp_adjusted=False,
                                                                all_definitions=None,
                                                                initializer=None,
                                                                element_limit=5)
```

Bases: `object`

Represents the internal state of the ReachingDefinitionsAnalysis.

It contains a data class LiveDefinitions, which stores both definitions and uses for register, stack, memory, and temporary variables, uncovered during the analysis.

Parameters

- **subject** (*Subject*) – The subject being analyzed.
- **track_tmps** (*bool*) – Only tells whether or not temporary variables should be taken into consideration when representing the state of the analysis. Should be set to true when the analysis has counted uses and definitions for temporary variables, false otherwise.
- **analysis** (`Optional[ReachingDefinitionsAnalysis]`) – The analysis that generated the state represented by this object.
- **rtoc_value** – When the targeted architecture is ppc64, the initial function needs to know the *rtoc_value*.
- **live_definitions** (`Optional[LiveDefinitions]`) –
- **canonical_size** (*int*) – The sizes (in bytes) that objects with an UNKNOWN_SIZE are treated as for operations where sizes are necessary.
- **heap_allocator** (`Optional[HeapAllocator]`) – Mechanism to model the management of heap memory.
- **environment** (`Optional[Environment]`) – Representation of the environment of the analyzed program.
- **codeloc** (*CodeLocation*) –
- **arch** (*Arch*) –

- `track_consts` (*bool*) –
- `sp_adjusted` (*bool*) –
- `all_definitions` (*Set[Definition]* | *None*) –
- `initializer` (*RDASStateInitializer* | *None*) –
- `element_limit` (*int*) –

Variables

`arch` – The architecture targeted by the program.

`__init__` (*codeloc*, *arch*, *subject*, *track_tmps=False*, *track_consts=False*, *analysis=None*, *rtoc_value=None*, *live_definitions=None*, *canonical_size=8*, *heap_allocator=None*, *environment=None*, *sp_adjusted=False*, *all_definitions=None*, *initializer=None*, *element_limit=5*)

Parameters

- `codeloc` (*CodeLocation*) –
- `arch` (*Arch*) –
- `subject` (*Subject*) –
- `track_tmps` (*bool*) –
- `track_consts` (*bool*) –
- `analysis` (*ReachingDefinitionsAnalysis* | *None*) –
- `live_definitions` (*LiveDefinitions* | *None*) –
- `canonical_size` (*int*) –
- `heap_allocator` (*HeapAllocator* | *None*) –
- `environment` (*Environment* | *None*) –
- `sp_adjusted` (*bool*) –
- `all_definitions` (*Set[Definition]* | *None*) –
- `initializer` (*RDASStateInitializer* | *None*) –
- `element_limit` (*int*) –

`codeloc`

`arch:` *Arch*

`analysis`

`all_definitions:` *Set[Definition]*

`heap_allocator`

`codeloc_uses:` *Set[Definition]*

`exit_observed:` *bool*

`live_definitions`

`top` (*bits*)

Parameters

`bits` (*int*) –

is_top(*args)

heap_address(offset)

Return type

BV

Parameters

offset (int / HeapAddress) –

static is_heap_address(addr)

Return type

bool

Parameters

addr (Base) –

static get_heap_offset(addr)

Return type

Optional[int]

Parameters

addr (Base) –

stack_address(offset)

Return type

BV

Parameters

offset (int) –

is_stack_address(addr)

Return type

bool

Parameters

addr (Base) –

get_stack_offset(addr)

Return type

Optional[int]

Parameters

addr (Base) –

annotate_with_def(symvar, definition)

Parameters

- symvar (Base) –
- definition (Definition) –

Return type

Base

Returns

annotate_mv_with_def(*mv*, *definition*)

Return type

MultiValues

Parameters

- **mv** (*MultiValues*) –
- **definition** (*Definition*) –

extract_defs(*symvar*)

Return type

Iterator[*Definition*]

Parameters

symvar (*Base*) –

property **tmps**

property **tmp_uses**

property **register_uses**

property **registers**: *MultiValuedMemory*

property **stack**: *MultiValuedMemory*

property **stack_uses**

property **heap**: *MultiValuedMemory*

property **heap_uses**

property **memory_uses**

property **memory**: *MultiValuedMemory*

property **uses_by_codeloc**

get_sp()

Return type

int

get_stack_address(*offset*)

Return type

int

Parameters

offset (*Base*) –

property **environment**

property **dep_graph**

copy(*discard_tmpdefs=False*)

Return type

ReachingDefinitionsState

merge(*others)

Return type

`Tuple[ReachingDefinitionsState, bool]`

compare(other)

Return type

`bool`

Parameters

other (`ReachingDefinitionsState`) –

move_codelocs(new_codeloc)

Return type

`None`

Parameters

new_codeloc (`CodeLocation`) –

kill_definitions(atom)

Overwrite existing definitions w.r.t ‘atom’ with a dummy definition instance. A dummy definition will not be removed during simplification.

Return type

`None`

Parameters

atom (`Atom`) –

kill_and_add_definition(atom, data, dummy=False, tags=None, endness=None, annotated=False, uses=None, override_codeloc=None)

Return type

`Tuple[Optional[MultiValues], Set[Definition]]`

Parameters

- **atom** (`Atom`) –
- **data** (`MultiValues`) –
- **tags** (`Set[Tag]` | `None`) –
- **annotated** (`bool`) –
- **uses** (`Set[Definition]` | `None`) –
- **override_codeloc** (`CodeLocation` | `None`) –

add_use(atom, expr=None)

Return type

`None`

Parameters

- **atom** (`Atom`) –
- **expr** (`Any` | `None`) –

`add_use_by_def(definition, expr=None)`

Return type

`None`

Parameters

- **definition** (`Definition`) –
- **expr** (`Any` | `None`) –

`add_tmp_use(tmp, expr=None)`

Return type

`None`

Parameters

- **tmp** (`int`) –
- **expr** (`Any` | `None`) –

`add_tmp_use_by_defs(defs, expr=None)`

Return type

`None`

Parameters

- **defs** (`Iterable`[`Definition`]) –
- **expr** (`Any` | `None`) –

`add_register_use(reg_offset, size, expr=None)`

Return type

`None`

Parameters

- **reg_offset** (`int`) –
- **size** (`int`) –
- **expr** (`Any` | `None`) –

`add_register_use_by_defs(defs, expr=None)`

Return type

`None`

Parameters

- **defs** (`Iterable`[`Definition`]) –
- **expr** (`Any` | `None`) –

`add_stack_use(stack_offset, size, expr=None)`

Return type

`None`

Parameters

- **stack_offset** (`int`) –
- **size** (`int`) –

- **expr** (*Any* | *None*) –

add_stack_use_by_defs(*defs*, *expr=None*)

Parameters

- **defs** (*Iterable*[*Definition*]) –
- **expr** (*Any* | *None*) –

add_heap_use(*heap_offset*, *size*, *expr=None*)

Return type

None

Parameters

- **heap_offset** (*int*) –
- **size** (*int*) –
- **expr** (*Any* | *None*) –

add_heap_use_by_defs(*defs*, *expr=None*)

Parameters

- **defs** (*Iterable*[*Definition*]) –
- **expr** (*Any* | *None*) –

add_memory_use_by_def(*definition*, *expr=None*)

Parameters

- **definition** (*Definition*) –
- **expr** (*Any* | *None*) –

add_memory_use_by_defs(*defs*, *expr=None*)

Parameters

- **defs** (*Iterable*[*Definition*]) –
- **expr** (*Any* | *None*) –

get_definitions(*atom*)

Return type

Set[*Definition*]

Parameters

atom (*Atom* | *Definition* | *Iterable*[*Atom*] | *Iterable*[*Definition*]) –

get_values(*spec*)

Return type

Optional[*MultiValues*]

Parameters

spec (*Atom* | *Definition* | *Iterable*[*Atom*]) –

`get_one_value(spec, strip_annotations=False)`

Return type

`Optional[BV]`

Parameters

- `spec` (`Atom` / `Definition`) –
- `strip_annotations` (`bool`) –

`get_concrete_value(spec, cast_to=<class 'int'>)`

Return type

`Union[int, bytes, None]`

Parameters

- `spec` (`Atom` / `Definition[Atom]` / `Iterable[Atom]`) –
- `cast_to` (`Type[int]` / `Type[bytes]`) –

`mark_guard(target)`

`mark_const(value, size)`

Parameters

- `value` (`int`) –
- `size` (`int`) –

`downsize()`

`pointer_to_atoms(**kwargs)`

`pointer_to_atom(**kwargs)`

`deref(pointer, size, endness=Endness.BE)`

Parameters

- `pointer` (`MultiValues` / `Atom` / `Definition` / `Iterable[Atom]` / `Iterable[Definition]` / `int` / `BV` / `HeapAddress` / `SpOffset`) –
- `size` (`int` / `DerefSize`) –
- `endness` (`str`) –

`class angr.analyses.reaching_definitions.FunctionHandler(interfunction_level=0)`

Bases: `object`

A mechanism for summarizing a function call's effect on a program for `ReachingDefinitionsAnalysis`.

Parameters

`interfunction_level` (`int`) –

`__init__`(`interfunction_level=0`)

Parameters

`interfunction_level` (`int`) –

hook(*analysis*)

Attach this instance of the function handler to an instance of RDA.

Return type

FunctionHandler

Parameters

analysis (*ReachingDefinitionsAnalysis*) –

make_function_codeloc(*target, callsite, callsite_func_addr*)

The RDA engine will call this function to transform a callsite CodeLocation into a callee CodeLocation.

Parameters

- **target** (*None* | *int* | *MultiValues*) –
- **callsite** (*CodeLocation*) –
- **callsite_func_addr** (*int* | *None*) –

handle_function(*state, data*)

The main entry point for the function handler. Called with a RDA state and a FunctionCallData, it is expected to update the state and the data as per the contracts described on FunctionCallData.

You can override this method to take full control over how data is processed, or override any of the following to use the higher-level interface (*data.depends()*):

- *handle_impl_<function name>* - used for *<function name>*.
- *handle_local_function* - used for any function (excluding plt stubs) whose address is inside the main binary.
- *handle_external_function* - used for any function or plt stub whose address is outside the main binary.
- *handle_indirect_function* - used for any function whose target cannot be resolved.
- *handle_generic_function* - used as a default if none of the above are overridden.

Each of them take the same signature as *handle_function*.

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_generic_function(*state, data*)

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_indirect_function(*state, data*)

Return type

None

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_local_function(*state*, *data*)

Return type

`None`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **data** (`FunctionCallData`) –

handle_external_function(*state*, *data*)

Return type

`None`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **data** (`FunctionCallData`) –

recurse_analysis(*state*, *data*)

Precondition: `data.function` MUST NOT BE NONE in order to call this method.

Return type

`None`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **data** (`FunctionCallData`) –

static c_args_as_atoms(*state*, *cc*, *prototype*)

Return type

`List[Set[Atom]]`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

static c_return_as_atoms(*state*, *cc*, *prototype*)

Return type

`Set[Atom]`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

static caller_saved_regs_as_atoms(*state*, *cc*)

Return type

`Set[Register]`

Parameters

- **state** (`ReachingDefinitionsState`) –

- `cc` (`SimCC`) –

`static stack_pointer_as_atom(state)`

Return type

`Register`

```
class angr.analyses.reaching_definitions.FunctionCallData(
    callsite_codeloc, function_codeloc,
    address_multi, address=None,
    symbol=None, function=None,
    name=None, cc=None, prototype=None,
    args_atoms=None, args_values=None,
    ret_atoms=None, redefine_locals=True,
    visited_blocks=None, effects=<factory>,
    ret_values=None,
    ret_values_deps=None,
    caller_will_handle_single_ret=False,
    guessed_cc=False,
    guessed_prototype=False,
    retaddr_popped=False)
```

Bases: `object`

A bundle of intermediate data used when computing the sum effect of a function during ReachingDefinitions-Analysis.

RDA engine contract:

- Construct one of these before calling `FunctionHandler.handle_function`. Fill it with as many fields as you can realistically provide without duplicating effort.
- Provide `callsite_codeloc` as either the call statement (AIL) or the default exit of the default statement of the calling block (VEX)
- Provide `function_codeloc` as the callee address with `stmt_idx=0`.

Function handler contract:

- If `redefine_locals` is unset, do not adjust any artifacts of the function call abstraction, such as the stack pointer, the caller saved registers, etc.
- If `caller_will_handle_single_ret` is set, and there is a single entry in `ret_atoms`, do not apply to the state effects modifying this atom. Instead, set `ret_values` and `ret_values_deps` to the values and deps which are used constructing these values.

Parameters

- `callsite_codeloc` (`CodeLocation`) –
- `function_codeloc` (`CodeLocation`) –
- `address_multi` (`MultiValues` / `None`) –
- `address` (`int` / `None`) –
- `symbol` (`Symbol` / `None`) –
- `function` (`Function` / `None`) –
- `name` (`str` / `None`) –
- `cc` (`SimCC` / `None`) –
- `prototype` (`SimTypeFunction` / `None`) –

- `args_atoms` (`List[Set[Atom]]` | `None`) –
- `args_values` (`List[MultiValues]` | `None`) –
- `ret_atoms` (`Set[Atom]` | `None`) –
- `redefine_locals` (`bool`) –
- `visited_blocks` (`Set[int]` | `None`) –
- `effects` (`List[FunctionEffect]`) –
- `ret_values` (`MultiValues` | `None`) –
- `ret_values_deps` (`Set[Definition]` | `None`) –
- `caller_will_handle_single_ret` (`bool`) –
- `guessed_cc` (`bool`) –
- `guessed_prototype` (`bool`) –
- `retaddr_popped` (`bool`) –

`callsite_codeloc`: `CodeLocation`

`function_codeloc`: `CodeLocation`

`address_multi`: `Optional[MultiValues]`

`address`: `Optional[int]` = `None`

`symbol`: `Optional[Symbol]` = `None`

`function`: `Optional[Function]` = `None`

`name`: `Optional[str]` = `None`

`cc`: `Optional[SimCC]` = `None`

`prototype`: `Optional[SimTypeFunction]` = `None`

`args_atoms`: `Optional[List[Set[Atom]]]` = `None`

`args_values`: `Optional[List[MultiValues]]` = `None`

`ret_atoms`: `Optional[Set[Atom]]` = `None`

`redefine_locals`: `bool` = `True`

`visited_blocks`: `Optional[Set[int]]` = `None`

`effects`: `List[FunctionEffect]`

`ret_values`: `Optional[MultiValues]` = `None`

`ret_values_deps`: `Optional[Set[Definition]]` = `None`

`caller_will_handle_single_ret`: `bool` = `False`

`guessed_cc`: `bool` = `False`

`guessed_prototype`: `bool` = `False`

retaddr_popped: `bool` = `False`

has_clobbered(*dest*)

Determines whether the given atom already has effects applied

Return type

`bool`

Parameters

dest (`Atom`) –

depends(*dest*, **sources*, *value=None*, *apply_at_callsite=False*, *tags=None*)

Mark a single effect of the current function, including the atom being modified, the input atoms on which that output atom depends, the precise (or imprecise!) value to store, and whether the effect should be applied during the function or afterwards, at the callsite.

The tags are used to annotate the Definition of the Atom that will be created, when the function effects are applied to the state.

The atom being modified may be `None` to mark uses of the source atoms which do not have any explicit sinks.

Parameters

- **dest** (`Atom` | `Iterable[Atom]` | `None`) –
- **sources** (`Atom` | `Iterable[Atom]`) –
- **value** (`MultiValues` | `BV` | `bytes` | `int` | `None`) –
- **apply_at_callsite** (`bool`) –
- **tags** (`Set[Tag]` | `None`) –

reset_prototype(*prototype*, *state*, *soft_reset=False*)

Return type

`Set[Atom]`

Parameters

- **prototype** (`SimTypeFunction`) –
- **state** (`ReachingDefinitionsState`) –
- **soft_reset** (`bool`) –

__init__(*callsite_codeloc*, *function_codeloc*, *address_multi*, *address=None*, *symbol=None*, *function=None*, *name=None*, *cc=None*, *prototype=None*, *args_atoms=None*, *args_values=None*, *ret_atoms=None*, *redefine_locals=True*, *visited_blocks=None*, *effects=<factory>*, *ret_values=None*, *ret_values_deps=None*, *caller_will_handle_single_ret=False*, *guessed_cc=False*, *guessed_prototype=False*, *retaddr_popped=False*)

Parameters

- **callsite_codeloc** (`CodeLocation`) –
- **function_codeloc** (`CodeLocation`) –
- **address_multi** (`MultiValues` | `None`) –
- **address** (`int` | `None`) –
- **symbol** (`Symbol` | `None`) –
- **function** (`Function` | `None`) –

- **name** (*str* / *None*) –
- **cc** (*SimCC* / *None*) –
- **prototype** (*SimTypeFunction* / *None*) –
- **args_atoms** (*List[Set[Atom]]* / *None*) –
- **args_values** (*List[MultiValues]* / *None*) –
- **ret_atoms** (*Set[Atom]* / *None*) –
- **redefine_locals** (*bool*) –
- **visited_blocks** (*Set[int]* / *None*) –
- **effects** (*List[FunctionEffect]*) –
- **ret_values** (*MultiValues* / *None*) –
- **ret_values_deps** (*Set[Definition]* / *None*) –
- **caller_will_handle_single_ret** (*bool*) –
- **guessed_cc** (*bool*) –
- **guessed_prototype** (*bool*) –
- **retaddr_popped** (*bool*) –

Return type

None

`angr.analyses.reaching_definitions.get_all_definitions(region)`

Return type

Set[Definition]

Parameters

region (*MultiValuedMemory*) –

`class angr.analyses.reaching_definitions.call_trace.CallSite(caller_func_addr, block_addr, callee_func_addr)`

Bases: *object*

Describes a call site on a CFG.

Parameters

- **caller_func_addr** (*int*) –
- **block_addr** (*int* / *None*) –
- **callee_func_addr** (*int*) –

`__init__(caller_func_addr, block_addr, callee_func_addr)`

Parameters

- **caller_func_addr** (*int*) –
- **block_addr** (*int* / *None*) –
- **callee_func_addr** (*int*) –

caller_func_addr

`callee_func_addr`

`block_addr`

class `angr.analyses.reaching_definitions.call_trace.CallTrace`(*target*)

Bases: `object`

Describes a series of functions calls to get from one function (`current_function_address()`) to another function or a basic block (`self.target`).

Parameters

target (*int*) –

`__init__`(*target*)

Parameters

target (*int*) –

`target`

`callsites`: `List[CallSite]`

`current_function_address`()

Return type

`int`

`step_back`(*caller_func_addr*, *block_addr*, *callee_func_addr*)

Return type

`CallTrace`

Parameters

• **caller_func_addr** (*int*) –

• **block_addr** (*int* | *None*) –

`includes_function`(*func_addr*)

Return type

`bool`

Parameters

func_addr (*int*) –

`copy`()

Return type

`CallTrace`

class `angr.analyses.reaching_definitions.engine_vex.SimEngineRDVEX`(*project*, *functions=None*, *function_handler=None*)

Bases: `SimEngineLightVEXMixin`, `SimEngineLight`

Implements the VEX execution engine for reaching definition analysis.

`__init__`(*project*, *functions=None*, *function_handler=None*)

state: `ReachingDefinitionsState`

process(*state*, **args*, *block=None*, *fail_fast=False*, *visited_blocks=None*, *dep_graph=None*, ***kwargs*)

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

```
class angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis(subject=None,
                                                                                       func_graph=None,
                                                                                       max_iterations=5,
                                                                                       track_tmps=False,
                                                                                       track_consts=True,
                                                                                       ob-
                                                                                       ser-
                                                                                       va-
                                                                                       tion_points=None,
                                                                                       init_state=None,
                                                                                       init_context=None,
                                                                                       state_initializer=
                                                                                       cc=None,
                                                                                       func-
                                                                                       tion_handler=None,
                                                                                       ob-
                                                                                       serve_all=False,
                                                                                       vis-
                                                                                       ited_blocks=None,
                                                                                       dep_graph=True,
                                                                                       ob-
                                                                                       serve_callback=None,
                                                                                       canon-
                                                                                       i-
                                                                                       cal_size=8,
                                                                                       stack_pointer_tra-
                                                                                       use_callee_saved
                                                                                       in-
                                                                                       ter-
                                                                                       func-
                                                                                       tion_level=0,
                                                                                       track_liveness=Ti
                                                                                       func_addr=None,
                                                                                       el-
                                                                                       e-
                                                                                       ment_limit=5)
```

Bases: [ForwardAnalysis](#)[[ReachingDefinitionsState](#), [NodeType](#), [object](#), [object](#)], [Analysis](#)

ReachingDefinitionsAnalysis is a text-book implementation of a static data-flow analysis that works on either a function or a block. It supports both VEX and AIL. By registering observers to observation points, users may use this analysis to generate use-def chains, def-use chains, and reaching definitions, and perform other traditional data-flow analyses such as liveness analysis.

- I’ve always wanted to find a better name for this analysis. Now I gave up and decided to live with this name for the foreseeable future (until a better name is proposed by someone else).
- Aliasing is definitely a problem, and I forgot how aliasing is resolved in this implementation. I’ll leave this

as a post-graduation TODO.

- Some more documentation and examples would be nice.

```
__init__(subject=None, func_graph=None, max_iterations=30, track_tmps=False, track_consts=True,
         observation_points=None, init_state=None, init_context=None, state_initializer=None, cc=None,
         function_handler=None, observe_all=False, visited_blocks=None, dep_graph=True,
         observe_callback=None, canonical_size=8, stack_pointer_tracker=None,
         use_callee_saved_regs_at_return=True, interfunction_level=0, track_liveness=True,
         func_addr=None, element_limit=5)
```

Parameters

- **subject** (`Union[Subject, Block, Block, Function, str, None]`) – The subject of the analysis: a function, or a single basic block
- **func_graph** – Alternative graph for function.graph.
- **max_iterations** – The maximum number of iterations before the analysis is terminated.
- **track_tmps** – Whether or not temporary variables should be taken into consideration during the analysis.
- **observation_points** (`iterable`) – A collection of tuples of (“node”|”insn”, ins_addr, OP_TYPE) defining where reaching definitions should be copied and stored. OP_TYPE can be OP_BEFORE or OP_AFTER.
- **init_state** (`Optional[ReachingDefinitionsState]`) – An optional initialization state. The analysis creates and works on a copy. Default to None: the analysis then initialize its own abstract state, based on the given <Subject>.
- **init_context** – If init_state is not given, this is used to initialize the context field of the initial state’s CodeLocation. The only default-supported type which may go here is a tuple of integers, i.e. a callstack. Anything else requires a custom FunctionHandler.
- **cc** – Calling convention of the function.
- **function_handler** (`Optional[FunctionHandler]`) – The function handler to update the analysis state and results on function calls.
- **observe_all** – Observe every statement, both before and after.
- **visited_blocks** – A set of previously visited blocks.
- **dep_graph** (`Union[DepGraph, bool, None]`) – An initial dependency graph to add the result of the analysis to. Set it to None to skip dependency graph generation.
- **canonical_size** – The sizes (in bytes) that objects with an UNKNOWN_SIZE are treated as for operations where sizes are necessary.
- **dep_graph** – Set this to True to generate a dependency graph for the subject. It will be available as *result.dep_graph*.
- **interfunction_level** (`int`) – The number of functions we should recurse into. This parameter is only used if function_handler is not provided.
- **track_liveness** (`bool`) – Whether to track liveness information. This can consume sizeable amounts of RAM on large functions. (e.g. ~15GB for a function with 4k nodes)
- **state_initializer** (`RDASStateInitializer | None`) –
- **func_addr** (`int | None`) –
- **element_limit** (`int`) –

```

model: ReachingDefinitionsModel

function_calls: Dict[CodeLocation, FunctionCallRelationships]

property observed_results: Dict[Tuple[str, int, int], LiveDefinitions]

property all_definitions

property all_uses

property one_result

property dep_graph: DepGraph

property visited_blocks

get_reaching_definitions(**kwargs)

get_reaching_definitions_by_insn(insn_addr, op_type)

get_reaching_definitions_by_node(node_addr, op_type)

node_observe(node_addr, state, op_type, node_idx=None)

```

Parameters

- **node_addr** (`int`) – Address of the node.
- **state** (`ReachingDefinitionsState`) – The analysis state.
- **op_type** (`ObservationPointType`) – Type of the observation point. Must be one of the following: `OP_BEFORE`, `OP_AFTER`.
- **node_idx** (`Optional[int]`) – ID of the node. Used in AIL to differentiate blocks with the same address.

Return type

`None`

```
insn_observe(insn_addr, stmt, block, state, op_type)
```

Parameters

- **insn_addr** (`int`) – Address of the instruction.
- **stmt** (`Union[Statement, IRStmt]`) – The statement.
- **block** (`Union[Block, Block]`) – The current block.
- **state** (`ReachingDefinitionsState`) – The abstract analysis state.
- **op_type** (`ObservationPointType`) – Type of the observation point. Must be one of the following: `OP_BEFORE`, `OP_AFTER`.

Return type

`None`

```
stmt_observe(stmt_idx, stmt, block, state, op_type)
```

Parameters

- **stmt_idx** (`int`) –
- **stmt** (`Union[Statement, IRStmt]`) –
- **block** (`Union[Block, Block]`) –

- **state** (*ReachingDefinitionsState*) –
- **op_type** (*ObservationPointType*) –

Return type

None

Returns

exit_observe(*node_addr*, *exit_stmt_idx*, *block*, *state*, *node_idx=None*)

Parameters

- **node_addr** (*int*) –
- **exit_stmt_idx** (*int*) –
- **block** (*Block* / *Block*) –
- **state** (*ReachingDefinitionsState*) –
- **node_idx** (*int* / *None*) –

property subject

project: *Project*

kb: *KnowledgeBase*

callsites_to(*target*)

Return type

Iterable[FunctionCallRelationships]

Parameters

target (*int* / *str* / *Function*) –

```
class angr.analyses.reaching_definitions.dep_graph.FunctionCallRelationships(callsite, target,
                                                                              args_defns,
                                                                              other_input_defns,
                                                                              ret_defns,
                                                                              other_output_defns)
```

Bases: *object*

Parameters

- **callsite** (*CodeLocation*) –
- **target** (*int* / *None*) –
- **args_defns** (*List[Set[Definition]]*) –
- **other_input_defns** (*Set[Definition]*) –
- **ret_defns** (*Set[Definition]*) –
- **other_output_defns** (*Set[Definition]*) –

callsite: *CodeLocation*

target: *Optional[int]*

args_defns: *List[Set[Definition]]*

other_input_defns: *Set[Definition]*

```
ret_defns: Set[Definition]
```

```
other_output_defns: Set[Definition]
```

```
__init__(callsite, target, args_defns, other_input_defns, ret_defns, other_output_defns)
```

Parameters

- **callsite** (`CodeLocation`) –
- **target** (`int` | `None`) –
- **args_defns** (`List[Set[Definition]]`) –
- **other_input_defns** (`Set[Definition]`) –
- **ret_defns** (`Set[Definition]`) –
- **other_output_defns** (`Set[Definition]`) –

Return type

`None`

```
class angr.analyses.reaching_definitions.dep_graph.DepGraph(graph=None)
```

Bases: `object`

The representation of a dependency graph: a directed graph, where nodes are definitions, and edges represent uses.

Mostly a wrapper around a `<networkx.DiGraph>`.

Parameters

graph (`networkx.DiGraph[Definition]` | `None`) –

```
__init__(graph=None)
```

Parameters

graph – A graph where nodes are definitions, and edges represent uses.

```
property graph: networkx.DiGraph[Definition]
```

```
add_node(node)
```

Parameters

node (`Definition`) – The definition to add to the definition-use graph.

Return type

`None`

```
add_edge(source, destination, **labels)
```

The edge to add to the definition-use graph. Will create nodes that are not yet present.

Parameters

- **source** (`Definition`) – The “source” definition, used by the “destination”.
- **destination** (`Definition`) – The “destination” definition, using the variable defined by “source”.
- **labels** – Optional keyword arguments to represent edge labels.

Return type

`None`

nodes()

Return type

`networkx.classes.reportviews.NodeView`[[Definition](#)]

predecessors(*node*)

Parameters

node ([Definition](#)) – The definition to get the predecessors of.

Return type

`Iterator`[[Definition](#)]

transitive_closure(*definition*)

Compute the “transitive closure” of a given definition. Obtained by transitively aggregating the ancestors of this definition in the graph.

Note: Each definition is memoized to avoid any kind of recomputation across the lifetime of this object.

Parameters

definition – The Definition to get transitive closure for.

Returns

A graph of the transitive closure of the given definition.

Return type

`networkx.DiGraph`[[Definition](#)][[Atom](#)]

contains_atom(*atom*)

Return type

`bool`

Parameters

atom ([Atom](#)) –

add_dependencies_for_concrete_pointers_of(*values, definition, cfg, loader*)

When a given definition holds concrete pointers, make sure the <MemoryLocation>s they point to are present in the dependency graph; Adds them if necessary.

Parameters

- **values** (`Iterable`[`Union`[`Base`, `int`]]) –
- **definition** ([Definition](#)) – The definition which has data that can contain concrete pointers.
- **cfg** ([CFGModel](#)) – The CFG, containing information about memory data.
- **loader** ([Loader](#)) –

find_definitions(*kwargs*)**

Filter the definitions present in the graph based on various criteria. Parameters can be any valid keyword args to [DefinitionMatchPredicate](#)

Return type

`List`[[Definition](#)]

find_all_predecessors(*starts, **kwargs*)

Filter the ancestors of the given start node or nodes that match various criteria. Parameters can be any valid keyword args to [DefinitionMatchPredicate](#)

find_all_successors(*starts*, ***kwargs*)

Filter the descendents of the given start node or nodes that match various criteria. Parameters can be any valid keyword args to *DefinitionMatchPredicate*

Return type

`List[Definition]`

Parameters

starts (`Definition` / `Iterable[Definition]`) –

find_path(*starts*, *ends*, ***kwargs*)

Find a path between the given start node or nodes and the given end node or nodes. All the intermediate steps in the path must match the criteria given in *kwargs*. The *kwargs* can be any valid parameters to *DefinitionMatchPredicate*.

This algorithm has exponential time and space complexity. Use at your own risk. Want to do better? Do it yourself or use *networkx* and eat the cost of indirection and/or cloning.

Return type

`Optional[Tuple[Definition, ...]]`

Parameters

- **starts** (`Definition` / `Iterable[Definition]`) –

- **ends** (`Definition` / `Iterable[Definition]`) –

find_paths(*starts*, *ends*, ***kwargs*)

Find all non-overlapping simple paths between the given start node or nodes and the given end node or nodes. All the intermediate steps in the path must match the criteria given in *kwargs*. The *kwargs* can be any valid parameters to *DefinitionMatchPredicate*.

This algorithm has exponential time and space complexity. Use at your own risk. Want to do better? Do it yourself or use *networkx* and eat the cost of indirection and/or cloning.

Return type

`Iterator[Tuple[Definition, ...]]`

Parameters

- **starts** (`Definition` / `Iterable[Definition]`) –

- **ends** (`Definition` / `Iterable[Definition]`) –

class `angr.analyses.reaching_definitions.heap_allocator.HeapAllocator`(*canonical_size*)

Bases: `object`

A simple modelisation to help represent heap memory management during a `<ReachingDefinitionsAnalysis>`:
 - Act as if allocations were always done in consecutive memory segments;
 - Take care of the size not to screw potential pointer arithmetic (avoid overlapping segments).

The content of the heap itself is modeled using a `<KeyedRegion>` attribute in the `<LiveDefinitions>` state; This class serves to generate consistent heap addresses to be used by the aforementioned.

Note: This has **NOT** been made to help detect heap vulnerabilities.

Parameters

canonical_size (`int`) –

__init__(*canonical_size*)

Parameters

canonical_size (`int`) – The concrete size an `<UNKNOWN_SIZE>` defaults to.

allocate(*size*)

Gives an address for a new memory chunk of <size> bytes.

Parameters

size ([Union](#)[[int](#), [UnknownSize](#)]) – The requested size for the chunk, in number of bytes.

Return type

[HeapAddress](#)

Returns

The address of the chunk.

free(*address*)

Mark the chunk pointed by <address> as freed.

Parameters

address ([Union](#)[[Undefined](#), [HeapAddress](#)]) – The address of the chunk to free.

property allocated_addresses

The list of addresses that are currently allocated on the heap.

Type

return

`angr.analyses.reaching_definitions.function_handler.get_exit_livedefinitions(func,
rda_model)`

Get LiveDefinitions at all exits of a function, merge them, and return.

Parameters

- **func** ([Function](#)) –
- **rda_model** ([ReachingDefinitionsModel](#)) –

`class angr.analyses.reaching_definitions.function_handler.FunctionEffect(dest,
sources, value=None,
sources_defns=None,
apply_at_callsite=False,
tags=None)`

Bases: [object](#)

A single effect that a function summary may apply to the state. This is largely an implementation detail; use *FunctionCallData.depends* instead.

Parameters

- **dest** ([Atom](#) | *None*) –
- **sources** ([Set](#)[[Atom](#)]) –
- **value** ([MultiValues](#) | *None*) –
- **sources_defns** ([Set](#)[[Definition](#)] | *None*) –
- **apply_at_callsite** (*bool*) –
- **tags** ([Set](#)[[Tag](#)] | *None*) –

dest: [Optional](#)[[Atom](#)]

sources: [Set](#)[[Atom](#)]


```

value: Optional[MultiValues] = None
sources_defns: Optional[Set[Definition]] = None
apply_at_callsite: bool = False
tags: Optional[Set[Tag]] = None
__init__(dest, sources, value=None, sources_defns=None, apply_at_callsite=False, tags=None)

```

Parameters

- **dest** (`Atom` / `None`) –
- **sources** (`Set` [`Atom`]) –
- **value** (`MultiValues` / `None`) –
- **sources_defns** (`Set` [`Definition`] / `None`) –
- **apply_at_callsite** (`bool`) –
- **tags** (`Set` [`Tag`] / `None`) –

Return type

`None`

```

class angr.analyses.reaching_definitions.function_handler.FunctionCallData(callsite_codeloc,
                                                                           function_codeloc,
                                                                           address_multi,
                                                                           address=None,
                                                                           symbol=None,
                                                                           function=None,
                                                                           name=None,
                                                                           cc=None,
                                                                           prototype=None,
                                                                           args_atoms=None,
                                                                           args_values=None,
                                                                           ret_atoms=None,
                                                                           rede-
                                                                           fine_locals=True,
                                                                           vis-
                                                                           ited_blocks=None,
                                                                           ef-
                                                                           fects=<factory>,
                                                                           ret_values=None,
                                                                           ret_values_deps=None,
                                                                           caller_will_handle_single_ret=False,
                                                                           guessed_cc=False,
                                                                           guessed_prototype=False,
                                                                           re-
                                                                           taddr_popped=False)

```

Bases: `object`

A bundle of intermediate data used when computing the sum effect of a function during ReachingDefinitions-Analysis.

RDA engine contract:

- Construct one of these before calling `FunctionHandler.handle_function`. Fill it with as many fields as you can realistically provide without duplicating effort.

- Provide `callsite_codeloc` as either the call statement (AIL) or the default exit of the default statement of the calling block (VEX)
- Provide `function_codeloc` as the callee address with `stmt_idx=0``.

Function handler contract:

- If `redefine_locals` is unset, do not adjust any artifacts of the function call abstraction, such as the stack pointer, the caller saved registers, etc.
- If `caller_will_handle_single_ret` is set, and there is a single entry in `ret_atoms`, do not apply to the state effects modifying this atom. Instead, set `ret_values` and `ret_values_deps` to the values and deps which are used constructing these values.

Parameters

- `callsite_codeloc` (`CodeLocation`) –
- `function_codeloc` (`CodeLocation`) –
- `address_multi` (`MultiValues` | `None`) –
- `address` (`int` | `None`) –
- `symbol` (`Symbol` | `None`) –
- `function` (`Function` | `None`) –
- `name` (`str` | `None`) –
- `cc` (`SimCC` | `None`) –
- `prototype` (`SimTypeFunction` | `None`) –
- `args_atoms` (`List[Set[Atom]]` | `None`) –
- `args_values` (`List[MultiValues]` | `None`) –
- `ret_atoms` (`Set[Atom]` | `None`) –
- `redefine_locals` (`bool`) –
- `visited_blocks` (`Set[int]` | `None`) –
- `effects` (`List[FunctionEffect]`) –
- `ret_values` (`MultiValues` | `None`) –
- `ret_values_deps` (`Set[Definition]` | `None`) –
- `caller_will_handle_single_ret` (`bool`) –
- `guessed_cc` (`bool`) –
- `guessed_prototype` (`bool`) –
- `retaddr_popped` (`bool`) –

`callsite_codeloc`: `CodeLocation`

`function_codeloc`: `CodeLocation`

`address_multi`: `Optional[MultiValues]`

`address`: `Optional[int] = None`

```

symbol: Optional[Symbol] = None
function: Optional[Function] = None
name: Optional[str] = None
cc: Optional[SimCC] = None
prototype: Optional[SimTypeFunction] = None
args_atoms: Optional[List[Set[Atom]]] = None
args_values: Optional[List[MultiValues]] = None
ret_atoms: Optional[Set[Atom]] = None
redefine_locals: bool = True
visited_blocks: Optional[Set[int]] = None
effects: List[FunctionEffect]
ret_values: Optional[MultiValues] = None
ret_values_deps: Optional[Set[Definition]] = None
caller_will_handle_single_ret: bool = False
guessed_cc: bool = False
guessed_prototype: bool = False
retaddr_popped: bool = False

```

has_clobbered(*dest*)

Determines whether the given atom already has effects applied

Return type

`bool`

Parameters

dest (`Atom`) –

depends(*dest*, **sources*, *value=None*, *apply_at_callsite=False*, *tags=None*)

Mark a single effect of the current function, including the atom being modified, the input atoms on which that output atom depends, the precise (or imprecise!) value to store, and whether the effect should be applied during the function or afterwards, at the callsite.

The tags are used to annotate the Definition of the Atom that will be created, when the function effects are applied to the state.

The atom being modified may be None to mark uses of the source atoms which do not have any explicit sinks.

Parameters

- **dest** (`Atom` | `Iterable[Atom]` | `None`) –
- **sources** (`Atom` | `Iterable[Atom]`) –
- **value** (`MultiValues` | `BV` | `bytes` | `int` | `None`) –
- **apply_at_callsite** (`bool`) –

- **tags** (*Set[Tag] | None*) –

reset_prototype(*prototype, state, soft_reset=False*)

Return type

Set[Atom]

Parameters

- **prototype** (*SimTypeFunction*) –
- **state** (*ReachingDefinitionsState*) –
- **soft_reset** (*bool*) –

__init__(*callsite_codeloc, function_codeloc, address_multi, address=None, symbol=None, function=None, name=None, cc=None, prototype=None, args_atoms=None, args_values=None, ret_atoms=None, redefine_locals=True, visited_blocks=None, effects=<factory>, ret_values=None, ret_values_deps=None, caller_will_handle_single_ret=False, guessed_cc=False, guessed_prototype=False, retaddr_popped=False*)

Parameters

- **callsite_codeloc** (*CodeLocation*) –
- **function_codeloc** (*CodeLocation*) –
- **address_multi** (*MultiValues | None*) –
- **address** (*int | None*) –
- **symbol** (*Symbol | None*) –
- **function** (*Function | None*) –
- **name** (*str | None*) –
- **cc** (*SimCC | None*) –
- **prototype** (*SimTypeFunction | None*) –
- **args_atoms** (*List[Set[Atom]] | None*) –
- **args_values** (*List[MultiValues] | None*) –
- **ret_atoms** (*Set[Atom] | None*) –
- **redefine_locals** (*bool*) –
- **visited_blocks** (*Set[int] | None*) –
- **effects** (*List[FunctionEffect]*) –
- **ret_values** (*MultiValues | None*) –
- **ret_values_deps** (*Set[Definition] | None*) –
- **caller_will_handle_single_ret** (*bool*) –
- **guessed_cc** (*bool*) –
- **guessed_prototype** (*bool*) –
- **retaddr_popped** (*bool*) –

Return type

None

```
class angr.analyses.reaching_definitions.function_handler.FunctionCallDataUnwrapped(inner)
    Bases: FunctionCallData
```

A subclass of FunctionCallData which asserts that many of its members are non-None at construction time. Typechecks be gone!

Parameters

inner (*FunctionCallData*) –

address_multi: *MultiValues*

__init__ (*inner*)

Parameters

inner (*FunctionCallData*) –

```
static decorate(wrapper, *, wrapped=<function FunctionCallDataUnwrapped.decorate>,
                 assigned=('__module__', '__name__', '__qualname__', '__doc__', '__annotations__'),
                 updated=('__dict__', ))
```

Update a wrapper function to look like the wrapped function

wrapper is the function to be updated *wrapped* is the original function *assigned* is a tuple naming the attributes assigned directly from the wrapped function to the wrapper function (defaults to `functools.WRAPPER_ASSIGNMENTS`) *updated* is a tuple naming the attributes of the wrapper that are updated with the corresponding attribute from the wrapped function (defaults to `functools.WRAPPER_UPDATES`)

```
class angr.analyses.reaching_definitions.function_handler.FunctionHandler(interfunction_level=0)
    Bases: object
```

A mechanism for summarizing a function call's effect on a program for ReachingDefinitionsAnalysis.

Parameters

interfunction_level (*int*) –

__init__ (*interfunction_level*=0)

Parameters

interfunction_level (*int*) –

hook (*analysis*)

Attach this instance of the function handler to an instance of RDA.

Return type

FunctionHandler

Parameters

analysis (*ReachingDefinitionsAnalysis*) –

make_function_codeloc (*target*, *callsite*, *callsite_func_addr*)

The RDA engine will call this function to transform a callsite CodeLocation into a callee CodeLocation.

Parameters

- **target** (*None* | *int* | *MultiValues*) –
- **callsite** (*CodeLocation*) –
- **callsite_func_addr** (*int* | *None*) –

handle_function(*state*, *data*)

The main entry point for the function handler. Called with a RDA state and a FunctionCallData, it is expected to update the state and the data as per the contracts described on FunctionCallData.

You can override this method to take full control over how data is processed, or override any of the following to use the higher-level interface (*data.depends()*):

- *handle_impl_<function name>* - used for *<function name>*.
- *handle_local_function* - used for any function (excluding plt stubs) whose address is inside the main binary.
- *handle_external_function* - used for any function or plt stub whose address is outside the main binary.
- *handle_indirect_function* - used for any function whose target cannot be resolved.
- *handle_generic_function* - used as a default if none of the above are overridden.

Each of them take the same signature as *handle_function*.

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_generic_function(*state*, *data*)

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_indirect_function(*state*, *data*)

Return type

None

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_local_function(*state*, *data*)

Return type

None

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

handle_external_function(*state*, *data*)

Return type

None

Parameters

- **state** (*ReachingDefinitionsState*) –
- **data** (*FunctionCallData*) –

recurse_analysis(*state*, *data*)

Precondition: `data.function` MUST NOT BE NONE in order to call this method.

Return type

`None`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **data** (`FunctionCallData`) –

static c_args_as_atoms(*state*, *cc*, *prototype*)

Return type

`List[Set[Atom]]`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

static c_return_as_atoms(*state*, *cc*, *prototype*)

Return type

`Set[Atom]`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **cc** (`SimCC`) –
- **prototype** (`SimTypeFunction`) –

static caller_saved_regs_as_atoms(*state*, *cc*)

Return type

`Set[Register]`

Parameters

- **state** (`ReachingDefinitionsState`) –
- **cc** (`SimCC`) –

static stack_pointer_as_atom(*state*)

Return type

`Register`

```
class angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState(codeloc, arch,
                                                                           subject,
                                                                           track_tmps=False,
                                                                           track_consts=False,
                                                                           analysis=None,
                                                                           rtoc_value=None,
                                                                           live_definitions=None,
                                                                           canonical_size=8,
                                                                           heap_allocator=None,
                                                                           environ-
                                                                           ment=None,
                                                                           sp_adjusted=False,
                                                                           all_definitions=None,
                                                                           initializer=None,
                                                                           element_limit=5)
```

Bases: `object`

Represents the internal state of the ReachingDefinitionsAnalysis.

It contains a data class LiveDefinitions, which stores both definitions and uses for register, stack, memory, and temporary variables, uncovered during the analysis.

Parameters

- **subject** (*Subject*) – The subject being analyzed.
- **track_tmps** (*bool*) – Only tells whether or not temporary variables should be taken into consideration when representing the state of the analysis. Should be set to true when the analysis has counted uses and definitions for temporary variables, false otherwise.
- **analysis** (*Optional[ReachingDefinitionsAnalysis]*) – The analysis that generated the state represented by this object.
- **rtoc_value** – When the targeted architecture is ppc64, the initial function needs to know the *rtoc_value*.
- **live_definitions** (*Optional[LiveDefinitions]*) –
- **canonical_size** (*int*) – The sizes (in bytes) that objects with an UNKNOWN_SIZE are treated as for operations where sizes are necessary.
- **heap_allocator** (*Optional[HeapAllocator]*) – Mechanism to model the management of heap memory.
- **environment** (*Optional[Environment]*) – Representation of the environment of the analyzed program.
- **codeloc** (*CodeLocation*) –
- **arch** (*Arch*) –
- **track_consts** (*bool*) –
- **sp_adjusted** (*bool*) –
- **all_definitions** (*Set[Definition]*) –
- **initializer** (*RDStateInitializer | None*) –
- **element_limit** (*int*) –

Variables

arch – The architecture targeted by the program.


```
__init__(codeloc, arch, subject, track_tmps=False, track_consts=False, analysis=None, rtoc_value=None,
         live_definitions=None, canonical_size=8, heap_allocator=None, environment=None,
         sp_adjusted=False, all_definitions=None, initializer=None, element_limit=5)
```

Parameters

- **codeloc** (`CodeLocation`) –
- **arch** (`Arch`) –
- **subject** (`Subject`) –
- **track_tmps** (`bool`) –
- **track_consts** (`bool`) –
- **analysis** (`ReachingDefinitionsAnalysis` | `None`) –
- **live_definitions** (`LiveDefinitions` | `None`) –
- **canonical_size** (`int`) –
- **heap_allocator** (`HeapAllocator` | `None`) –
- **environment** (`Environment` | `None`) –
- **sp_adjusted** (`bool`) –
- **all_definitions** (`Set[Definition]` | `None`) –
- **initializer** (`RDStateInitializer` | `None`) –
- **element_limit** (`int`) –

codeloc

arch: `Arch`

analysis

all_definitions: `Set[Definition]`

heap_allocator

codeloc_uses: `Set[Definition]`

exit_observed: `bool`

live_definitions

top(`bits`)

Parameters

- bits** (`int`) –

is_top(*`args`)

heap_address(`offset`)

Return type

`BV`

Parameters

- offset** (`int` | `HeapAddress`) –

static `is_heap_address(addr)`

Return type

`bool`

Parameters

`addr` (*Base*) –

static `get_heap_offset(addr)`

Return type

`Optional[int]`

Parameters

`addr` (*Base*) –

stack_address(offset)

Return type

`BV`

Parameters

`offset` (*int*) –

is_stack_address(addr)

Return type

`bool`

Parameters

`addr` (*Base*) –

get_stack_offset(addr)

Return type

`Optional[int]`

Parameters

`addr` (*Base*) –

annotate_with_def(symvar, definition)

Parameters

- `symvar` (*Base*) –
- `definition` (*Definition*) –

Return type

`Base`

Returns

annotate_mv_with_def(mv, definition)

Return type

`MultiValues`

Parameters

- `mv` (*MultiValues*) –
- `definition` (*Definition*) –

```

extract_defs(symvar)

    Return type
    Iterator[Definition]

    Parameters
    symvar (Base) –

property tmps

property tmp_uses

property register_uses

property registers: MultiValuedMemory

property stack: MultiValuedMemory

property stack_uses

property heap: MultiValuedMemory

property heap_uses

property memory_uses

property memory: MultiValuedMemory

property uses_by_codeloc

get_sp()

    Return type
    int

get_stack_address(offset)

    Return type
    int

    Parameters
    offset (Base) –

property environment

property dep_graph

copy(discard_tmpdefs=False)

    Return type
    ReachingDefinitionsState

merge(*others)

    Return type
    Tuple[ReachingDefinitionsState, bool]

compare(other)

    Return type
    bool

```

Parameters**other** (*ReachingDefinitionsState*) –**move_codelocs**(*new_codeloc*)**Return type***None***Parameters****new_codeloc** (*CodeLocation*) –**kill_definitions**(*atom*)

Overwrite existing definitions w.r.t ‘atom’ with a dummy definition instance. A dummy definition will not be removed during simplification.

Return type*None***Parameters****atom** (*Atom*) –

kill_and_add_definition(*atom*, *data*, *dummy=False*, *tags=None*, *endness=None*, *annotated=False*, *uses=None*, *override_codeloc=None*)

Return type*Tuple*[*Optional*[*MultiValues*], *Set*[*Definition*]]**Parameters**

- **atom** (*Atom*) –
- **data** (*MultiValues*) –
- **tags** (*Set*[*Tag*] | *None*) –
- **annotated** (*bool*) –
- **uses** (*Set*[*Definition*] | *None*) –
- **override_codeloc** (*CodeLocation* | *None*) –

add_use(*atom*, *expr=None*)**Return type***None***Parameters**

- **atom** (*Atom*) –
- **expr** (*Any* | *None*) –

add_use_by_def(*definition*, *expr=None*)**Return type***None***Parameters**

- **definition** (*Definition*) –
- **expr** (*Any* | *None*) –

`add_tmp_use(tmp, expr=None)`

Return type

`None`

Parameters

- `tmp` (`int`) –
- `expr` (`Any` | `None`) –

`add_tmp_use_by_defs(defs, expr=None)`

Return type

`None`

Parameters

- `defs` (`Iterable`[`Definition`]) –
- `expr` (`Any` | `None`) –

`add_register_use(reg_offset, size, expr=None)`

Return type

`None`

Parameters

- `reg_offset` (`int`) –
- `size` (`int`) –
- `expr` (`Any` | `None`) –

`add_register_use_by_defs(defs, expr=None)`

Return type

`None`

Parameters

- `defs` (`Iterable`[`Definition`]) –
- `expr` (`Any` | `None`) –

`add_stack_use(stack_offset, size, expr=None)`

Return type

`None`

Parameters

- `stack_offset` (`int`) –
- `size` (`int`) –
- `expr` (`Any` | `None`) –

`add_stack_use_by_defs(defs, expr=None)`

Parameters

- `defs` (`Iterable`[`Definition`]) –
- `expr` (`Any` | `None`) –

add_heap_use(*heap_offset*, *size*, *expr*=None)

Return type

None

Parameters

- **heap_offset** (*int*) –
- **size** (*int*) –
- **expr** (*Any* | None) –

add_heap_use_by_defs(*defs*, *expr*=None)

Parameters

- **defs** (*Iterable*[*Definition*]) –
- **expr** (*Any* | None) –

add_memory_use_by_def(*definition*, *expr*=None)

Parameters

- **definition** (*Definition*) –
- **expr** (*Any* | None) –

add_memory_use_by_defs(*defs*, *expr*=None)

Parameters

- **defs** (*Iterable*[*Definition*]) –
- **expr** (*Any* | None) –

get_definitions(*atom*)

Return type

Set[*Definition*]

Parameters

atom (*Atom* | *Definition* | *Iterable*[*Atom*] | *Iterable*[*Definition*]) –

get_values(*spec*)

Return type

Optional[*MultiValues*]

Parameters

spec (*Atom* | *Definition* | *Iterable*[*Atom*]) –

get_one_value(*spec*, *strip_annotations*=False)

Return type

Optional[BV]

Parameters

- **spec** (*Atom* | *Definition*) –
- **strip_annotations** (*bool*) –

`get_concrete_value(spec, cast_to=<class 'int'>)`

Return type

`Union[int, bytes, None]`

Parameters

- `spec` (`Atom` | `Definition[Atom]` | `Iterable[Atom]`) –
- `cast_to` (`Type[int]` | `Type[bytes]`) –

`mark_guard(target)`

`mark_const(value, size)`

Parameters

- `value` (`int`) –
- `size` (`int`) –

`downsize()`

`pointer_to_atoms(**kwargs)`

`pointer_to_atom(**kwargs)`

`deref(pointer, size, endness=Endness.BE)`

Parameters

- `pointer` (`MultiValues` | `Atom` | `Definition` | `Iterable[Atom]` | `Iterable[Definition]` | `int` | `BV` | `HeapAddress` | `SpOffset`) –
- `size` (`int` | `DerefSize`) –
- `endness` (`str`) –

`class angr.analyses.reaching_definitions.subject.SubjectType(value)`

Bases: `Enum`

An enumeration.

`Function = 1`

`Block = 2`

`CallTrace = 3`

`class angr.analyses.reaching_definitions.subject.Subject(content, func_graph=None, cc=None)`

Bases: `object`

`__init__(content, func_graph=None, cc=None)`

The thing being analysed, and the way (visitor) to analyse it.

Parameters

- `content` (`Union[ailment.Block, angr.Block, Function]`) – Thing to be analysed.
- `func_graph` (`networkx.DiGraph`) – Alternative graph for function.graph.
- `cc` (`SimCC`) – Calling convention of the function.

property cc

property content

property func_graph

property type

property visitor: *FunctionGraphVisitor* | *SingleNodeGraphVisitor*

```
class angr.analyses.reaching_definitions.engine_ail.SimEngineRDAIL(project,
                                                                    function_handler=None,
                                                                    stack_pointer_tracker=None,
                                                                    use_callee_saved_regs_at_return=True,
                                                                    bp_as_gpr=False)
```

Bases: *SimEngineLightAILMixin*, *SimEngineLight*

Parameters

- **function_handler** (*FunctionHandler* | *None*) –
- **bp_as_gpr** (*bool*) –

arch: *Arch*

state: *ReachingDefinitionsState*

```
__init__(project, function_handler=None, stack_pointer_tracker=None,
         use_callee_saved_regs_at_return=True, bp_as_gpr=False)
```

Parameters

- **function_handler** (*FunctionHandler* | *None*) –
- **bp_as_gpr** (*bool*) –

```
process(state, *args, dep_graph=None, visited_blocks=None, block=None, fail_fast=False, **kwargs)
```

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

```
class angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink(target,
                                                                      transitions=None)
```

Bases: *object*

The representation of a slice of a CFG.

```
__init__(target, transitions=None)
```

Parameters

- **target** (*angr.knowledge_plugins.functions.function.Function*) – The targeted sink, to which every path in the slice leads.
- **transitions** (*Dict[int, List[int]]*) – A mapping representing transitions in the graph. Indexes are source addresses and values a list of destination addresses, for which there exists a transition in the slice from source to destination.

property transitions

The transitions in the slice.

Type

return Dict[int,List[int]]

property transitions_as_tuples

The list of transitions as pairs of (source, destination).

Type

return List[Tuple[int,int]]

property target

return angr.knowledge_plugins.functions.function.Function: The targeted sink function, from which the slice is constructed.

property nodes: List[int]

The complete list of addresses present in the slice.

Type

return

property entrypoints

Entrypoints are all source addresses that are not the destination address of any transition.

Return List[int]

The list of entrypoints addresses.

add_transitions(transitions)

Add the given transitions to the current slice.

Parameters

transitions (Dict[int,List[int]]) – The list of transitions to be added to *self.transitions*.

Return Dict[int,List[int]]

Return the updated list of transitions.

is_empty()

Test if a given slice does not contain any transition.

Return bool

True if the <CFGSliceToSink> instance does not contain any transitions. False otherwise.

path_between(source, destination, visited=None)

Check the existence of a path in the slice between two given node addresses.

Parameters

- **source** (int) – The source address.
- **destination** (int) – The destination address.
- **visited** (Optional[Set[Any]]) – Used to avoid infinite recursion if loops are present in the slice.

Return type

bool

Returns

True if there is a path between the source and the destination in the CFG, False if not, or if we have been unable to decide (because of loops).

`angr.analyses.cfg_slice_to_sink.graph.slice_callgraph(callgraph, cfg_slice_to_sink)`

Slice a callgraph, keeping only the nodes present in the <CFGSliceToSink> representation, and the transitions for which a path exists.

Note that this function mutates the graph passed as an argument.

Parameters

- **callgraph** (*networkx.MultiDiGraph*) – The callgraph to update.
- **cfg_slice_to_sink** (*CFGSliceToSink*) – The representation of the slice, containing the data to update the callgraph from.

`angr.analyses.cfg_slice_to_sink.graph.slice_cfg_graph(graph, cfg_slice_to_sink)`

Slice a CFG graph, keeping only the transitions and nodes present in the <CFGSliceToSink> representation.

Note that this function mutates the graph passed as an argument.

Parameters

- **graph** (*networkx.DiGraph*) – The graph to slice.
- **cfg_slice_to_sink** (*CFGSliceToSink*) – The representation of the slice, containing the data to update the CFG from.

Return *networkx.DiGraph*

The sliced graph.

`angr.analyses.cfg_slice_to_sink.graph.slice_function_graph(function_graph, cfg_slice_to_sink)`

Slice a function graph, keeping only the nodes present in the <CFGSliceToSink> representation.

Because the <CFGSliceToSink> is build from the CFG, and the function graph is *NOT* a subgraph of the CFG, edges of the function graph will no be present in the <CFGSliceToSink> transitions. However, we use the fact that if there is an edge between two nodes in the function graph, then there must exist a path between these two nodes in the slice; Proof idea: - The <CFGSliceToSink> is backward and recursively constructed; - If a node is in the slice, then all its predecessors will be (transitively); - If there is an edge between two nodes in the function graph, there is a path between them in the CFG; - So: The origin node is a transitive predecessor of the destination one, hence if destination is in the slice, then origin will be too.

In consequence, in the end, removing the only nodes not present in the slice, and their related transitions gives us the expected result: a function graph representing (a higher view of) the flow in the slice.

Note that this function mutates the graph passed as an argument.

Parameters

- **graph** (*networkx.DiGraph*) – The graph to slice.
- **cfg_slice_to_sink** (*CFGSliceToSink*) – The representation of the slice, containing the data to update the CFG from.

Return *networkx.DiGraph*

The sliced graph.

Some utility functions to manage our representation of transitions:

A dictionary, indexed by int (source addresses), which values are list of ints (target addresses).

`angr.analyses.cfg_slice_to_sink.transitions.merge_transitions(transitions, existing_transitions)`

Merge two dictionaries of transitions together.

Parameters

- **transitions** (*Dict[int, List[int]]*) – Some transitions.

- **existing_transitions** (*Dict[int, List[int]]*) – Other transitions.

Return *Dict[int, List[int]]*

The merge of the two parameters.

class *angr.analyses.stack_pointer_tracker.BottomType*

Bases: *object*

The bottom value for register values.

class *angr.analyses.stack_pointer_tracker.Constant(val)*

Bases: *object*

Represents a constant value.

__init__ (*val*)

val

class *angr.analyses.stack_pointer_tracker.Register(offset, bitlen)*

Bases: *object*

Represent a register.

__init__ (*offset, bitlen*)

offset

bitlen

class *angr.analyses.stack_pointer_tracker.OffsetVal(reg, offset)*

Bases: *object*

Represent a value with an offset added.

__init__ (*reg, offset*)

property *reg*

property *offset*

class *angr.analyses.stack_pointer_tracker.Eq(val0, val1)*

Bases: *object*

Represent an equivalence condition.

__init__ (*val0, val1*)

val0

val1

class *angr.analyses.stack_pointer_tracker.FrozenStackPointerTrackerState(regs, memory, is_tracking_memory)*

Bases: *object*

Abstract state for StackPointerTracker analysis with registers and memory values being in frozensets.

__init__ (*regs, memory, is_tracking_memory*)

regs

memory

is_tracking_memory

unfreeze()

merge(*other*)

class `angr.analyses.stack_pointer_tracker.StackPointerTrackerState`(*regs*, *memory*,
is_tracking_memory)

Bases: `object`

Abstract state for StackPointerTracker analysis.

__init__(*regs*, *memory*, *is_tracking_memory*)

regs

memory

is_tracking_memory

give_up_on_memory_tracking()

store(*addr*, *val*)

load(*addr*)

get(*reg*)

put(*reg*, *val*)

copy()

freeze()

merge(*other*)

exception `angr.analyses.stack_pointer_tracker.CouldNotResolveException`

Bases: `Exception`

An exception used in StackPointerTracker analysis to represent internal resolving failures.

class `angr.analyses.stack_pointer_tracker.StackPointerTracker`(*func*, *reg_offsets*, *block=None*,
track_memory=True,
cross_insn_opt=True)

Bases: `Analysis`, `ForwardAnalysis`

Track the offset of stack pointer at the end of each basic block of a function.

__init__(*func*, *reg_offsets*, *block=None*, *track_memory=True*, *cross_insn_opt=True*)

Parameters

- **func** (`Function` | `None`) –
- **reg_offsets** (`Set[int]`) –
- **block** (`Block` | `None`) –

offset_after(*addr*, *reg*)

```

offset_before(addr, reg)

offset_after_block(block_addr, reg)

offset_before_block(block_addr, reg)

constant_after(addr, reg)

constant_before(addr, reg)

constant_after_block(block_addr, reg)

constant_before_block(block_addr, reg)

property inconsistent

inconsistent_for(reg)

project: Project

kb: KnowledgeBase

class angr.analyses.variable_recovery.annotations.StackLocationAnnotation(offset)
    Bases: Annotation
    __init__(offset)

    property eliminatable
        Returns whether this annotation can be eliminated in a simplification.

        Returns
            True if eliminatable, False otherwise

    property relocatable
        Returns whether this annotation can be relocated in a simplification.

        Returns
            True if it can be relocated, false otherwise.

class angr.analyses.variable_recovery.annotations.VariableSourceAnnotation(block_addr,
                                                                           stmt_idx,
                                                                           ins_addr)
    Bases: Annotation
    __init__(block_addr, stmt_idx, ins_addr)

    property eliminatable
        Returns whether this annotation can be eliminated in a simplification.

        Returns
            True if eliminatable, False otherwise

    property relocatable
        Returns whether this annotation can be relocated in a simplification.

        Returns
            True if it can be relocated, false otherwise.

    static from_state(state)

```

`angr.analyses.variable_recovery.variable_recovery_base.parse_stack_pointer(sp)`

Convert multiple supported forms of stack pointer representations into stack offsets.

Parameters

sp – A stack pointer representation.

Returns

A stack pointer offset.

Return type

`int`

`class angr.analyses.variable_recovery.variable_recovery_base.VariableAnnotation(addr_and_variables)`

Bases: `Annotation`

Parameters

addr_and_variables (`List[Tuple[int, SimVariable]]`) –

`__init__(addr_and_variables)`

Parameters

addr_and_variables (`List[Tuple[int, SimVariable]]`) –

addr_and_variables

property relocatable

Returns whether this annotation can be relocated in a simplification.

Returns

True if it can be relocated, false otherwise.

property eliminatable

Returns whether this annotation can be eliminated in a simplification.

Returns

True if eliminatable, False otherwise

`class angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase(func, max_iterations, store_live_variables)`

Bases: `Analysis`

The base class for VariableRecovery and VariableRecoveryFast.

Parameters

store_live_variables (`bool`) –

`__init__(func, max_iterations, store_live_variables)`

Parameters

store_live_variables (`bool`) –

get_variable_definitions(`block_addr`)

Get variables that are defined at the specified block.

Parameters

block_addr (`int`) – Address of the block.

Returns

A set of variables.

```
initialize_dominance_frontiers()
```

```
project: Project
```

```
kb: KnowledgeBase
```

```
class angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryStateBase(block_addr,
                                                                                       anal-
                                                                                       y-
                                                                                       sis,
                                                                                       arch,
                                                                                       func,
                                                                                       stack_region=None,
                                                                                       reg-
                                                                                       is-
                                                                                       ter_region=None,
                                                                                       global_region=None,
                                                                                       type-
                                                                                       vars=None,
                                                                                       type_constraints=None,
                                                                                       func_typevar=None,
                                                                                       de-
                                                                                       layed_type_constraints=None,
                                                                                       stack_offset_typevars=None,
                                                                                       project=None)
```

Bases: `object`

The base abstract state for variable recovery analysis.

```
__init__(block_addr, analysis, arch, func, stack_region=None, register_region=None, global_region=None,
          typevars=None, type_constraints=None, func_typevar=None, delayed_type_constraints=None,
          stack_offset_typevars=None, project=None)
```

```
static top(bits)
```

Return type

`BV`

```
static is_top(thing)
```

Return type

`bool`

```
static extract_variables(expr)
```

Return type

`Generator[Tuple[int, Union[SimVariable, SpOffset]], None, None]`

Parameters

expr (`Base`) –

```
static annotate_with_variables(expr, addr_and_variables)
```

Return type

`Base`

Parameters

• **expr** (`Base`) –

- `addr_and_variables` (*Iterable*[*Tuple*[*int*, *SimVariable* | *SpOffset*]]) –

`stack_address`(*offset*)

Return type

Base

Parameters

`offset` (*int*) –

`static is_stack_address`(*addr*)

Return type

bool

Parameters

`addr` (*Base*) –

`is_global_variable_address`(*addr*)

Return type

bool

Parameters

`addr` (*Base*) –

`static extract_stack_offset_from_addr`(*addr*)

Return type

Optional[*Base*]

Parameters

`addr` (*Base*) –

`get_stack_offset`(*addr*)

Return type

Optional[*int*]

Parameters

`addr` (*Base*) –

`stack_addr_from_offset`(*offset*)

Return type

int

Parameters

`offset` (*int*) –

`property func_addr`

`property dominance_frontiers`

`property variable_manager`

`property variables`

`get_variable_definitions`(*block_addr*)

Get variables that are defined at the specified block.

Parameters

`block_addr` (*int*) – Address of the block.

Returns

A set of variables.

add_type_constraint(*constraint*)

Add a new type constraint.

Parameters

constraint –

Returns

add_type_constraint_for_function(*func_typevar*, *constraint*)

Add a new type constraint for a specified function.

Parameters

- **func_typevar** –
- **constraint** –

Returns

downsize()

Remove unnecessary members.

Return type

None

Returns

None

static downsize_region(*region*)

Get rid of unnecessary references in region so that it won't avoid garbage collection on those referenced objects.

Parameters

region (*MultiValuedMemory*) – A MultiValuedMemory region.

Return type

MultiValuedMemory

Returns

None

```
class angr.analyses.variable_recovery.variable_recovery_fast.VariableRecoveryFastState(block_addr,
                                                                                       anal-
                                                                                       y-
                                                                                       sis,
                                                                                       arch,
                                                                                       func,
                                                                                       stack_region=None,
                                                                                       reg-
                                                                                       is-
                                                                                       ter_region=None,
                                                                                       global_region=None,
                                                                                       type-
                                                                                       vars=None,
                                                                                       type_constraints=None,
                                                                                       func_typevar=None,
                                                                                       de-
                                                                                       layed_type_constraints=None,
                                                                                       stack_offset_typevars=None,
                                                                                       project=None,
                                                                                       ret_val_size=None)
```

Bases: [VariableRecoveryStateBase](#)

The abstract state of variable recovery analysis.

Variables

- **stack_region** ([KeyedRegion](#)) – The stack store.
- **register_region** ([KeyedRegion](#)) – The register store.

```
__init__(block_addr, analysis, arch, func, stack_region=None, register_region=None, global_region=None,
          typevars=None, type_constraints=None, func_typevar=None, delayed_type_constraints=None,
          stack_offset_typevars=None, project=None, ret_val_size=None)
```

copy()

```
merge(others, successor=None)
```

Merge two abstract states.

For any node A whose dominance frontier that the current node (at the current program location) belongs to, we create a phi variable V' for each variable V that is defined in A, and then replace all existence of V with V' in the merged abstract state.

Parameters

others ([Tuple](#)[[VariableRecoveryFastState](#)]) – Other abstract states to merge.

Return type

[Tuple](#)[[VariableRecoveryFastState](#), bool]

Returns

The merged abstract state.

downsize()

Remove unnecessary members.

Return type

[None](#)

Returns

[None](#)

```
class angr.analyses.variable_recovery.variable_recovery_fast.VariableRecoveryFast(func,
                                         func_graph=None,
                                         max_iterations=2,
                                         low_priority=False,
                                         track_sp=True,
                                         func_args=None,
                                         store_live_variables=False,
                                         unify_variables=True)
```

Bases: [ForwardAnalysis](#), [VariableRecoveryBase](#)

Recover “variables” from a function by keeping track of stack pointer offsets and pattern matching VEX statements.

If calling conventions are recovered prior to running `VariableRecoveryFast`, variables can be recognized more accurately. However, it is not a requirement. In this case, the function graph you pass must contain information indicating the call-out sites inside the analyzed function. These graph edges must be annotated with either `"type": "call"` or `"outside": True`.

```
__init__(func, func_graph=None, max_iterations=2, low_priority=False, track_sp=True, func_args=None,
         store_live_variables=False, unify_variables=True)
```

Constructor

Parameters

- **order_jobs** (*bool*) – If all jobs should be ordered or not.
- **allow_merging** (*bool*) – If job merging is allowed.
- **allow_widening** (*bool*) – If job widening is allowed.
- **graph_visitor** ([GraphVisitor](#) or *None*) – A graph visitor to provide successors.
- **func** ([Function](#) | *str* | *int*) –
- **func_graph** (*DiGraph* | *None*) –
- **max_iterations** (*int*) –
- **func_args** (*List*[[SimVariable](#)] | *None*) –

Returns

None

project: [Project](#)

kb: [KnowledgeBase](#)

```
class angr.analyses.variable_recovery.variable_recovery.VariableRecoveryState(block_addr,
                                     analysis, arch,
                                     func, con-
                                     crete_states,
                                     stack_region=None,
                                     regis-
                                     ter_region=None)
```

Bases: [VariableRecoveryStateBase](#)

The abstract state of variable recovery analysis.

Variables

variable_manager ([angr.knowledge.variable_manager.VariableManager](#)) – The variable manager.

```
__init__(block_addr, analysis, arch, func, concrete_states, stack_region=None, register_region=None)
```

```
property concrete_states
```

```
get_concrete_state(addr)
```

Parameters

addr –

Returns

```
copy()
```

```
register_callbacks(concrete_states)
```

Parameters

concrete_states –

Returns

```
merge(others, successor=None)
```

Merge two abstract states.

Parameters

others ([Tuple](#)[[VariableRecoveryState](#)]) – Other abstract states to merge.

Returns

The merged abstract state.

Return type

[VariableRecoveryState](#), and a boolean that indicates if any merge has happened.

```
class angr.analyses.variable_recovery.variable_recovery.VariableRecovery(func,
                                                                    max_iterations=20,
                                                                    store_live_variables=False)
```

Bases: [ForwardAnalysis](#), [VariableRecoveryBase](#)

Recover “variables” from a function using forced execution.

While variables play a very important role in programming, it does not really exist after compiling. However, we can still identify and recovery their counterparts in binaries. It is worth noting that not every variable in source code can be identified in binaries, and not every recognized variable in binaries have a corresponding variable in the original source code. In short, there is no guarantee that the variables we identified/recognized in a binary are the same variables in its source code.

This analysis uses heuristics to identify and recovers the following types of variables: - Register variables. - Stack variables. - Heap variables. (not implemented yet) - Global variables. (not implemented yet)

This analysis takes a function as input, and performs a data-flow analysis on nodes. It runs concrete execution on every statement and hooks all register/memory accesses to discover all places that are accessing variables. It is slow, but has a more accurate analysis result. For a fast but inaccurate variable recovery, you may consider using [VariableRecoveryFast](#).

This analysis follows SSA, which means every write creates a new variable in registers or memory (stack, heap, etc.). Things may get tricky when overlapping variable (in memory, as you cannot really have overlapping accesses to registers) accesses exist, and in such cases, a new variable will be created, and this new variable will overlap with one or more existing variables. A decision procedure (which is pretty much TODO) is required at the end of this analysis to resolve the conflicts between overlapping variables.

```

__init__(func, max_iterations=20, store_live_variables=False)

    Parameters
        func (knowledge.Function) – The function to analyze.

project: Project

kb: KnowledgeBase

class angr.analyses.variable_recovery.engine_ail.SimEngineVRAIL(*args, call_info=None,
                                                                **kwargs)

    Bases: SimEngineLightAILMixin, SimEngineVRBase

    The engine for variable recovery on AIL.

    state: VariableRecoveryFastState

    block: Block

    __init__(*args, call_info=None, **kwargs)

class angr.analyses.variable_recovery.engine_vex.SimEngineVRVEX(*args, call_info=None,
                                                                **kwargs)

    Bases: SimEngineLightVEXMixin, SimEngineVRBase

    Implements the VEX engine for variable recovery analysis.

    state: VariableRecoveryStateBase

    __init__(*args, call_info=None, **kwargs)

class angr.analyses.variable_recovery.engine_base.RichR(data, variable=None, typevar=None,
                                                         type_constraints=None)

    Bases: object

    A rich representation of calculation results. The variable recovery data domain.

    Parameters
        • data (Base) –
        • typevar (TypeVariable | None) –

    __init__(data, variable=None, typevar=None, type_constraints=None)

    Parameters
        • data (Base) –
        • typevar (TypeVariable | None) –

data: Base

variable

typevar

type_constraints

property bits

```

class `angr.analyses.variable_recovery.engine_base.SimEngineVRBase`(*project*, *kb*)

Bases: `SimEngineLight`

The base class for variable recovery analyses. Contains methods for basic interactions with the state, like loading and storing data.

state: `VariableRecoveryStateBase`

__init__(*project*, *kb*)

property `func_addr`

process(*state*, **args*, ***kwargs*)

The main entry point for an engine. Should take a state and return a result.

Parameters

state – The state to proceed from

Returns

The result. Whatever you want ;)

class `angr.analyses.variable_recovery.irsb_scanner.VEXIRSBScanner`(**args*, ***kwargs*)

Bases: `SimEngineLightVEXMixin`

Scan the VEX IRSB to determine if any argument-passing registers should be narrowed by detecting cases of loading the whole register and immediately narrowing the register before writing to the tmp.

__init__(**args*, ***kwargs*)

class `angr.analyses.typehoon.lifter.TypeLifter`(*bits*)

Bases: `object`

Lift SimTypes to type constants.

Parameters

bits (*int*) –

__init__(*bits*)

Parameters

bits (*int*) –

bits

memo

lift(*ty*)

Parameters

ty (*SimType*) –

class `angr.analyses.typehoon.simple_solver.SketchNodeBase`

Bases: `object`

The base class for nodes in a sketch.

class `angr.analyses.typehoon.simple_solver.SketchNode`(*typevar*)

Bases: `SketchNodeBase`

Represents a node in a sketch graph.

Parameters

typevar (*TypeVariable* / *DerivedTypeVariable*) –

```

__init__(typevar)

    Parameters
    typevar (TypeVariable / DerivedTypeVariable) –

typevar: Union[TypeVariable, DerivedTypeVariable]

upper_bound

lower_bound

class angr.analyses.typehoon.simple_solver.RecursiveRefNode(target)
    Bases: SketchNodeBase
    Represents a cycle in a sketch graph.
    This is equivalent to sketches.LabelNode in the reference implementation of retpd.

    Parameters
    target (DerivedTypeVariable) –

__init__(target)

    Parameters
    target (DerivedTypeVariable) –

class angr.analyses.typehoon.simple_solver.Sketch(solver, root)
    Bases: object
    Describes the sketch of a type variable.

    Parameters
    • solver (SimpleSolver) –
    • root (TypeVariable) –

__init__(solver, root)

    Parameters
    • solver (SimpleSolver) –
    • root (TypeVariable) –

root: SketchNode

graph

node_mapping: Dict[Union[TypeVariable, DerivedTypeVariable], SketchNodeBase]

solver

lookup(typevar)

    Return type
    Optional[SketchNodeBase]

    Parameters
    typevar (TypeVariable / DerivedTypeVariable) –

```

add_edge(*src*, *dst*, *label*)

Parameters

- **src** (*SketchNodeBase*) –
- **dst** (*SketchNodeBase*) –

add_constraint(*constraint*)

Return type

None

Parameters

constraint (*TypeConstraint*) –

static flatten_typevar(*derived_typevar*)

Return type

Union[DerivedTypeVariable, TypeVariable, TypeConstant]

Parameters

derived_typevar (*TypeVariable* / *TypeConstant* / *DerivedTypeVariable*) –

class `angr.analyses.typehoon.simple_solver.ConstraintGraphTag`(*value*)

Bases: *Enum*

An enumeration.

LEFT = 0

RIGHT = 1

UNKNOWN = 2

class `angr.analyses.typehoon.simple_solver.FORGOTTEN`(*value*)

Bases: *Enum*

An enumeration.

PRE_FORGOTTEN = 0

POST_FORGOTTEN = 1

class `angr.analyses.typehoon.simple_solver.ConstraintGraphNode`(*typevar*, *variance*, *tag*, *forgotten*)

Bases: *object*

Parameters

- **typevar** (*TypeVariable* / *DerivedTypeVariable*) –
- **variance** (*Variance*) –
- **tag** (*ConstraintGraphTag*) –
- **forgotten** (*FORGOTTEN*) –

__init__(*typevar*, *variance*, *tag*, *forgotten*)

Parameters

- **typevar** (*TypeVariable* / *DerivedTypeVariable*) –
- **variance** (*Variance*) –
- **tag** (*ConstraintGraphTag*) –

- **forgotten** (*FORGOTTEN*) –

typevar

variance

tag

forgotten

forget_last_label()

Return type
Optional[Tuple[ConstraintGraphNode, BaseLabel]]

recall(label)

Return type
ConstraintGraphNode

Parameters
label (*BaseLabel*) –

inverse()

Return type
ConstraintGraphNode

inverse_wo_tag()

Invert the variance only.

Return type
ConstraintGraphNode

class `angr.analyses.typehoon.simple_solver.SimpleSolver`(*bits, constraints, typevars*)

Bases: `object`

SimpleSolver is, by its name, a simple solver. Most of this solver is based on the (complex) simplification logic that the retpd paper describes and the retpd re-implementation (<https://github.com/GrammaTech/retpd>) implements. Additionally, we add some improvements to allow type propagation of known struct names, among a few other improvements.

Parameters
bits (*int*) –

__init__(*bits, constraints, typevars*)

Parameters
bits (*int*) –

solve()

Steps:

For each type variable, - Infer the shape in its sketch - Build the constraint graph - Collect all constraints - Apply constraints to derive the lower and upper bounds

infer_shapes(*typevars, constraints*)

Computing sketches from constraint sets. Implements Algorithm E.1 in the retpd paper.

Return type
Tuple[Dict, Dict[TypeVariable, Sketch]]

Parameters

- **typevars** (*Set*[*TypeVariable*]) –
- **constraints** (*Set*[*TypeConstraint*]) –

compute_quotient_graph(*constraints*)

Compute the quotient graph (the constraint graph modulo \sim in Algorithm E.1 in the retydp paper) with respect to a given set of type constraints.

Parameters

- constraints** (*Set*[*TypeConstraint*]) –

join(*t1*, *t2*)

Return type
TypeConstant

Parameters

- **t1** (*TypeConstant* / *TypeVariable*) –
- **t2** (*TypeConstant* / *TypeVariable*) –

meet(*t1*, *t2*)

Return type
TypeConstant

Parameters

- **t1** (*TypeConstant* / *TypeVariable*) –
- **t2** (*TypeConstant* / *TypeVariable*) –

static abstract(*t*)

Return type
Union[*TypeConstant*, *TypeVariable*]

Parameters

- t** (*TypeConstant* / *TypeVariable*) –

determine(*equivalent_classes*, *sketches*, *solution*, *nodes=None*)

Determine C-like types from sketches.

Parameters

- **equivalent_classes** (*Dict*[*TypeVariable*, *TypeVariable*]) – A dictionary mapping each type variable from its representative in the equivalence class over \sim .
- **sketches** – A dictionary storing sketches for each type variable.
- **solution** (*Dict*) – The dictionary storing C-like types for each type variable. Output.
- **nodes** (*Optional*[*Set*[*SketchNode*]]) – Optional. Nodes that should be considered in the sketch.

Return type
None

Returns
None

class `angr.analyses.typehoon.translator.SimTypeTempRef`(*typevar*)

Bases: *SimType*

`__init__(typevar)`

Parameters

label – the type label.

`c_repr()`

class `angr.analyses.typehoon.translator.TypeTranslator`(*arch=None*)

Bases: `object`

Translate type variables to SimType equivalence.

`__init__(arch=None)`

`struct_name()`

`tc2simtype(tc)`

`simtype2tc(simtype)`

Return type

`TypeConstant`

Parameters

simtype (`SimType`) –

`backpatch(st, translated)`

Parameters

- **st** (`sim_type.SimType`) –
- **translated** (`dict`) –

Returns

class `angr.analyses.typehoon.typevars.TypeConstraint`

Bases: `object`

`pp_str(mapping)`

Return type

`str`

Parameters

mapping (`Dict`[`TypeVariable`, `Any`]) –

class `angr.analyses.typehoon.typevars.Equivalence`(*type_a*, *type_b*)

Bases: `TypeConstraint`

`__init__(type_a, type_b)`

type_a

type_b

`pp_str(mapping)`

Return type

`str`

Parameters

mapping (`Dict`[`TypeVariable`, `Any`]) –

class `angr.analyses.typehoon.typevars.Existence`(*type_*)

Bases: `TypeConstraint`

`__init__`(*type_*)

`type_`

`pp_str`(*mapping*)

Return type

`str`

Parameters

mapping (`Dict`[`TypeVariable`, `Any`]) –

replace(*replacements*)

class `angr.analyses.typehoon.typevars.Subtype`(*sub_type*, *super_type*)

Bases: `TypeConstraint`

Parameters

- **sub_type** (`TypeConstant` / `TypeVariable` / `DerivedTypeVariable`) –

- **super_type** (`TypeConstant` / `TypeVariable` / `DerivedTypeVariable`) –

`__init__`(*sub_type*, *super_type*)

Parameters

- **sub_type** (`TypeConstant` / `TypeVariable` / `DerivedTypeVariable`) –

- **super_type** (`TypeConstant` / `TypeVariable` / `DerivedTypeVariable`) –

`super_type`

`sub_type`

`pp_str`(*mapping*)

Return type

`str`

Parameters

mapping (`Dict`[`TypeVariable`, `Any`]) –

replace(*replacements*)

class `angr.analyses.typehoon.typevars.Add`(*type_0*, *type_1*, *type_r*)

Bases: `TypeConstraint`

Describes the constraint that `type_r == type_0 + type_1`

`__init__`(*type_0*, *type_1*, *type_r*)

`type_0`

`type_1`

`type_r`

```

pp_str(mapping)

    Return type
    str

    Parameters
    mapping (Dict[TypeVariable, Any]) –

replace(replacements)

class angr.analyses.typehoon.typevars.Sub(type_0, type_1, type_r)
    Bases: TypeConstraint
    Describes the constraint that type_r == type0 - type1
    __init__(type_0, type_1, type_r)

    type_0
    type_1
    type_r
    pp_str(mapping)

    Return type
    str

    Parameters
    mapping (Dict[TypeVariable, Any]) –

    replace(replacements)

class angr.analyses.typehoon.typevars.TypeVariable(idx=None, name=None)
    Bases: object
    Parameters
        • idx (int | None) –
        • name (str | None) –
    __init__(idx=None, name=None)

    Parameters
        • idx (int | None) –
        • name (str | None) –
    idx: int
    name
    pp_str(mapping)

    Return type
    str

    Parameters
    mapping (Dict[TypeVariable, Any]) –

```

```
class angr.analyses.typehoon.typevars.DerivedTypeVariable(type_var, label, labels=None,
                                                         idx=None)
```

Bases: *TypeVariable*

Parameters

- **type_var** (*TypeVariable* / *TypeConstant*) –
- **labels** (*Iterable*[*BaseLabel*] / *None*) –
- **idx** (*int*) –

```
__init__(type_var, label, labels=None, idx=None)
```

Parameters

- **type_var** (*TypeVariable* / *DerivedTypeVariable* / *None*) –
- **labels** (*Iterable*[*BaseLabel*] / *None*) –

type_var: *Union*[*TypeVariable*, *TypeConstant*]

labels: *Tuple*[*BaseLabel*]

one_label()

Return type

Optional[*BaseLabel*]

path()

Return type

Tuple[*BaseLabel*]

longest_prefix()

Return type

Union[*TypeVariable*, *DerivedTypeVariable*, *None*]

pp_str(*mapping*)

Return type

str

Parameters

- **mapping** (*Dict*[*TypeVariable*, *Any*]) –

replace(*replacements*)

```
class angr.analyses.typehoon.typevars.TypeVariables
```

Bases: *object*

```
__init__()
```

copy()

add_type_variable(*var, code_loc, typevar*)

Parameters

- **var** (*SimVariable*) –
- **typevar** (*TypeVariable*) –

```

    get_type_variable(var, codeloc)

    has_type_variable_for(var, codeloc)

    Parameters
    var (SimVariable) –
class angr.analyses.typehoon.typevars.BaseLabel
    Bases: object
    property variance: Variance
class angr.analyses.typehoon.typevars.FuncIn(loc)
    Bases: BaseLabel
    __init__(loc)
    loc
class angr.analyses.typehoon.typevars.FuncOut(loc)
    Bases: BaseLabel
    __init__(loc)
    loc
class angr.analyses.typehoon.typevars.Load
    Bases: BaseLabel
class angr.analyses.typehoon.typevars.Store
    Bases: BaseLabel
    property variance: Variance
class angr.analyses.typehoon.typevars.AddN(n)
    Bases: BaseLabel
    __init__(n)
    n
class angr.analyses.typehoon.typevars.SubN(n)
    Bases: BaseLabel
    __init__(n)
    n
class angr.analyses.typehoon.typevars.ConvertTo(to_bits)
    Bases: BaseLabel
    __init__(to_bits)
    to_bits
class angr.analyses.typehoon.typevars.ReinterpretAs(to_type, to_bits)
    Bases: BaseLabel
    __init__(to_type, to_bits)

```

to_type

to_bits

class `angr.analyses.typehoon.typevars.HasField(bits, offset)`

Bases: `BaseLabel`

__init__(bits, offset)

bits

offset

class `angr.analyses.typehoon.typevars.IsArray`

Bases: `BaseLabel`

class `angr.analyses.typehoon.typehoon.Typehoon(constraints, func_var, ground_truth=None, var_mapping=None, must_struct=None)`

Bases: `Analysis`

A spiritual tribute to the long-standing typehoon project that @jmg (John Grosen) worked on during his days in the angr team. Now I feel really bad of asking the poor guy to work directly on VEX IR without any fancy static analysis support as we have right now...

Typehoon analysis implements a pushdown system that simplifies and solves type constraints. Our type constraints are largely an implementation of the paper Polymorphic Type Inference for Machine Code by Noonan, Loginov, and Cok from GrammaTech (with missing functionality support and bugs, of course). Type constraints are collected by running VariableRecoveryFast (maybe VariableRecovery later as well) on a function, and then solved using this analysis.

User may specify ground truth, which will override all types at certain program points during constraint solving.

Parameters

- **var_mapping** (`Dict[SimVariable, Set[TypeVariable]]` | `None`) –
- **must_struct** (`Set[TypeVariable]` | `None`) –

__init__(constraints, func_var, ground_truth=None, var_mapping=None, must_struct=None)

Parameters

- **constraints** –
- **ground_truth** – A set of SimType-style solutions for some or all type variables. They will be respected during type solving.
- **var_mapping** (`Optional[Dict[SimVariable, Set[TypeVariable]]]`) –
- **must_struct** (`Optional[Set[TypeVariable]]`) –

update_variable_types(func_addr, var_to_typevars)

Parameters

func_addr (`int` | `str`) –

pp_constraints()

Pretty-print constraints between *variables* using the variable mapping.

Return type

`None`

pp_solution()

Pretty-print solutions using the variable mapping.

Return type

`None`

project: `Project`

kb: `KnowledgeBase`

All type constants used in type inference. They can be mapped, translated, or rewritten to C-style types.

`angr.analyses.typehoon.typeconsts.memoize(f)`

class `angr.analyses.typehoon.typeconsts.TypeConstant`

Bases: `object`

SIZE = `None`

pp_str(*mapping*)

Return type

`str`

property size: `int`

class `angr.analyses.typehoon.typeconsts.TopType`

Bases: `TypeConstant`

class `angr.analyses.typehoon.typeconsts.BottomType`

Bases: `TypeConstant`

class `angr.analyses.typehoon.typeconsts.Int`

Bases: `TypeConstant`

class `angr.analyses.typehoon.typeconsts.Int1`

Bases: `Int`

SIZE = `1`

class `angr.analyses.typehoon.typeconsts.Int8`

Bases: `Int`

SIZE = `1`

class `angr.analyses.typehoon.typeconsts.Int16`

Bases: `Int`

SIZE = `2`

class `angr.analyses.typehoon.typeconsts.Int32`

Bases: `Int`

SIZE = `4`

class `angr.analyses.typehoon.typeconsts.Int64`

Bases: `Int`

SIZE = `8`

```

class angr.analyses.typehoon.typeconsts.Int128
    Bases: Int
    SIZE = 16

class angr.analyses.typehoon.typeconsts.FloatBase
    Bases: TypeConstant

class angr.analyses.typehoon.typeconsts.Float
    Bases: FloatBase
    SIZE = 4

class angr.analyses.typehoon.typeconsts.Double
    Bases: FloatBase
    SIZE = 8

class angr.analyses.typehoon.typeconsts.Pointer(basetype)
    Bases: TypeConstant

    Parameters
    basetype (TypeConstant | None) –

    __init__(basetype)

    Parameters
    basetype (TypeConstant | None) –

    new(basetype)

class angr.analyses.typehoon.typeconsts.Pointer32(basetype=None)
    Bases: Pointer, Int32
    32-bit pointers.
    __init__(basetype=None)

class angr.analyses.typehoon.typeconsts.Pointer64(basetype=None)
    Bases: Pointer, Int64
    64-bit pointers.
    __init__(basetype=None)

class angr.analyses.typehoon.typeconsts.Array(element=None, count=None)
    Bases: TypeConstant
    __init__(element=None, count=None)

class angr.analyses.typehoon.typeconsts.Struct(fields=None, name=None, field_names=None)
    Bases: TypeConstant
    __init__(fields=None, name=None, field_names=None)

class angr.analyses.typehoon.typeconsts.Function(params, outputs)
    Bases: TypeConstant

    Parameters
    • params (List) –

```

```

    • outputs (List) –
__init__(params, outputs)

Parameters
    • params (List) –
    • outputs (List) –

class angr.analyses.typehoon.typeconsts.TypeVariableReference(typevar)
    Bases: TypeConstant
    __init__(typevar)

angr.analyses.typehoon.typeconsts.int_type(bits)

    Return type
    Optional[Int]

    Parameters
    bits (int) –

angr.analyses.typehoon.typeconsts.float_type(bits)

    Return type
    Optional[FloatBase]

    Parameters
    bits (int) –

class angr.analyses.identifier.identify.FuncInfo
    Bases: object
    __init__()

class angr.analyses.identifier.identify.Identifier(cfg=None, require_predecessors=True,
                                                    only_find=None)
    Bases: Analysis
    __init__(cfg=None, require_predecessors=True, only_find=None)
    run(only_find=None)
    can_call_same_name(addr, name)
    get_func_info(func)
    static constrain_all_zero(before_state, state, regs)
    identify_func(function)
    check_tests(cfg_func, match_func)
    map_callsites()
    do_trace(addr_trace, reverse_accesses, func_info)
    get_call_args(func, callsite)

```

static `get_reg_name(arch, reg_offset)`

Parameters

- **arch** – the architecture
- **reg_offset** – Tries to find the name of a register given the offset in the registers.

Returns

The register name

find_stack_vars_x86(func)

static `make_initial_state(project, stack_length)`

Returns

an initial state with a symbolic stack and good options for rop

static `make_symbolic_state(project, reg_list, stack_length=80)`

converts an input state into a state with symbolic registers :return: the symbolic state

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.loopfinder.Loop(entry, entry_edges, break_edges, continue_edges, body_nodes, graph, subloops)`

Bases: `object`

__init__(*entry, entry_edges, break_edges, continue_edges, body_nodes, graph, subloops*)

class `angr.analyses.loopfinder.LoopFinder(functions=None, normalize=True)`

Bases: `Analysis`

Extracts all the loops from all the functions in a binary.

__init__(*functions=None, normalize=True*)

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.loop_analysis.VariableTypes`

Bases: `object`

Iterator = 'Iterator'

HasNext = 'HasNext'

Next = 'Next'

class `angr.analyses.loop_analysis.AnnotatedVariable(variable, type_)`

Bases: `object`

__init__(*variable, type_*)

variable

type

class `angr.analyses.loop_analysis.Condition(op, val0, val1)`

Bases: `object`

```

    Equal = '=='
    NotEqual = '!='

    __init__(op, val0, val1)

    classmethod from_opstr(opstr)

class angr.analyses.loop_analysis.SootBlockProcessor(state, block, loop, defuse)
    Bases: object
    __init__(state, block, loop, defuse)

    process()

class angr.analyses.loop_analysis.LoopAnalysisState(block)
    Bases: object
    __init__(block)

    copy()

    merge(state)

    add_loop_exit_stmt(stmt_idx, condition=None)

class angr.analyses.loop_analysis.LoopAnalysis(loop, defuse)
    Bases: ForwardAnalysis, Analysis

    Analyze a loop and recover important information about the loop (e.g., invariants, induction variables) in a static manner.

    __init__(loop, defuse)
        Constructor

        Parameters
            • order_jobs (bool) – If all jobs should be ordered or not.
            • allow_merging (bool) – If job merging is allowed.
            • allow_widening (bool) – If job widening is allowed.
            • graph_visitor (GraphVisitor or None) – A graph visitor to provide successors.

        Returns
            None

    project: Project

    kb: KnowledgeBase

exception angr.analyses.veritesting.VeritestingError
    Bases: Exception

class angr.analyses.veritesting.CallTracingFilter(project, depth, blacklist=None)
    Bases: object

    Filter to apply during CFG creation on a given state and jumpkind to determine if it should be skipped at a certain depth

```

```
whitelist = {<class 'angr.procedures.libc.strcmp.strcmp'>, <class
'angr.procedures.cgc.transmit.transmit'>, <class 'angr.procedures.libc.atoi.atoi'>,
<class 'angr.procedures.posix.read.read'>, <class
'angr.procedures.cgc.receive.receive'>, <class
'angr.procedures.libc.strlen.strlen'>, <class 'angr.procedures.libc.fgetc.fgetc'>,
<class 'angr.procedures.glibc.__ctype_b_loc.__ctype_b_loc'>}
```

```
cfg_cache = {}
```

```
__init__(project, depth, blacklist=None)
```

```
filter(call_target_state, jumpkind)
```

The call will be skipped if it returns True.

Parameters

- **call_target_state** – The new state of the call target.
- **jumpkind** – The Jumpkind of this call.

Returns

True if we want to skip this call, False otherwise.

```
class angr.analyses.veritestesting.Veritestesting(input_state, boundaries=None, loop_unrolling_limit=10,
enable_function_inlining=False, terminator=None,
deviation_filter=None)
```

Bases: [Analysis](#)

An exploration technique made for condensing chunks of code to single (nested) if-then-else constraints via CFG accurate to conduct Static Symbolic Execution SSE (conversion to single constraint)

```
cfg_cache = {}
```

```
all_stashes = ('successful', 'errored', 'deadended', 'deviated', 'unconstrained')
```

```
__init__(input_state, boundaries=None, loop_unrolling_limit=10, enable_function_inlining=False,
terminator=None, deviation_filter=None)
```

SSE stands for Static Symbolic Execution, and we also implemented an extended version of Veritestesting (Avgerinos, Thanassis, et al, ICSE 2014).

Parameters

- **input_state** – The initial state to begin the execution with.
- **boundaries** – Addresses where execution should stop.
- **loop_unrolling_limit** – The maximum times that Veritestesting should unroll a loop for.
- **enable_function_inlining** – Whether we should enable function inlining and syscall inlining.
- **terminator** – A callback function that takes a state as parameter. Veritestesting will terminate if this function returns True.
- **deviation_filter** – A callback function that takes a state as parameter. Veritestesting will put the state into “deviated” stash if this function returns True.

```
is_not_in_cfg(s)
```

Returns if s.addr is not a proper node in our CFG.

Parameters

- **s** ([SimState](#)) – The SimState instance to test.

Returns bool

False if our CFG contains p.addr, True otherwise.

is_overbound(state)

Filter out all states that run out of boundaries or loop too many times.

param SimState state: SimState instance to check returns bool: True if outside of mem/loop_ctr boundary

project: Project

kb: KnowledgeBase

class angr.analyses.vfg.VFGJob(*args, **kwargs)

Bases: CFGJobBase

A job descriptor that contains local variables used during VFG analysis.

__init__(*args, **kwargs)

Return type

None

property block_id: BlockID | None

callstack_repr(kb)

Parameters

kb (KnowledgeBase) –

class angr.analyses.vfg.PendingJob(block_id, state, call_stack, src_block_id, src_stmt_idx, src_ins_addr)

Bases: object

Describes a pending job during VFG analysis.

Parameters

- **block_id** (BlockID) –
- **state** (SimState) –
- **call_stack** (CallStack) –
- **src_block_id** (BlockID) –
- **src_stmt_idx** (int) –
- **src_ins_addr** (int) –

__init__(block_id, state, call_stack, src_block_id, src_stmt_idx, src_ins_addr)

Parameters

- **block_id** (BlockID) –
- **state** (SimState) –
- **call_stack** (CallStack) –
- **src_block_id** (BlockID) –
- **src_stmt_idx** (int) –
- **src_ins_addr** (int) –

Return type

None

block_id

state

call_stack

src_block_id

src_stmt_idx

src_ins_addr

class `angr.analyses.vfg.AnalysisTask`

Bases: `object`

An analysis task describes a task that should be done before popping this task out of the task stack and discard it.

`__init__()`

Return type

None

property done

class `angr.analyses.vfg.FunctionAnalysis(function_address, return_address)`

Bases: `AnalysisTask`

Analyze a function, generate fix-point states from all endpoints of that function, and then merge them to one state.

Parameters

- **`function_address`** (`int`) –
- **`return_address`** (`int` | `None`) –

`__init__` (`function_address`, `return_address`)

Parameters

- **`function_address`** (`int`) –
- **`return_address`** (`int` | `None`) –

Return type

None

property done: `bool`

class `angr.analyses.vfg.CallAnalysis(address, return_address, function_analysis_tasks=None, mergeable_plugins=None)`

Bases: `AnalysisTask`

Analyze a call by analyze all functions this call might be calling, collect all final states generated by analyzing those functions, and merge them into one state.

Parameters

- **`address`** (`int`) –

- **return_address** (*None*) –
- **function_analysis_tasks** (*List[Any] | None*) –
- **mergeable_plugins** (*Tuple[str, str] | None*) –

__init__ (*address, return_address, function_analysis_tasks=None, mergeable_plugins=None*)

Parameters

- **address** (*int*) –
- **return_address** (*None*) –
- **function_analysis_tasks** (*List[Any] | None*) –
- **mergeable_plugins** (*Tuple[str, str] | None*) –

Return type

None

property done: *bool*

register_function_analysis (*task*)

Return type

None

Parameters

task (*FunctionAnalysis*) –

add_final_job (*job*)

Return type

None

Parameters

job (*VFGJob*) –

merge_jobs ()

Return type

VFGJob

class *angr.analyses.vfg.VFGNode* (*addr, key, state=None*)

Bases: *object*

A descriptor of nodes in a Value-Flow Graph

Parameters

- **addr** (*int*) –
- **key** (*BlockID*) –
- **state** (*SimState | None*) –

__init__ (*addr, key, state=None*)

Constructor.

Parameters

- **addr** (*int*) –
- **key** (*BlockID*) –
- **state** (*SimState*) –

Return type

None

append_state(*s*, *is_widened_state=False*)

Appended a new state to this VFGNode. :type *s*: :param *s*: The new state to append :type *is_widened_state*: :param *is_widened_state*: Whether it is a widened state or not.

```
class angr.analyses.vfg.VFG(cfg=None, context_sensitivity_level=2, start=None, function_start=None,
    interfunction_level=0, initial_state=None, avoid_runs=None,
    remove_options=None, timeout=None, max_iterations_before_widening=8,
    max_iterations=40, widening_interval=3, final_state_callback=None,
    status_callback=None, record_function_final_states=False)
```

Bases: [ForwardAnalysis](#)[[SimState](#), [VFGNode](#), [VFGJob](#), [BlockID](#)], [Analysis](#)

This class represents a control-flow graph with static analysis result.

Perform abstract interpretation analysis starting from the given function address. The output is an invariant at the beginning (or the end) of each basic block.

Steps:

- Generate a CFG first if CFG is not provided.
- Identify all merge points (denote the set of merge points as *Pw*) in the CFG.
- Cut those loop back edges (can be derived from *Pw*) so that we gain an acyclic CFG.
- **Identify all variables that are 1) from memory loading 2) from initial values, or 3) phi functions.**

Denote

the set of those variables as *S_{var}*.

- **Start real AI analysis and try to compute a fix point of each merge point. Perform widening/narrowing only on**
variables in *S_{var}*.

```
__init__(cfg=None, context_sensitivity_level=2, start=None, function_start=None, interfunction_level=0,
    initial_state=None, avoid_runs=None, remove_options=None, timeout=None,
    max_iterations_before_widening=8, max_iterations=40, widening_interval=3,
    final_state_callback=None, status_callback=None, record_function_final_states=False)
```

Parameters

- **cfg** ([Optional](#)[[CFGEmulated](#)]) – The control-flow graph to base this analysis on. If none is provided, we will construct a [CFGEmulated](#).
- **context_sensitivity_level** ([int](#)) – The level of context-sensitivity of this VFG. It ranges from 0 to infinity. Default 2.
- **function_start** ([Optional](#)[[int](#)]) – The address of the function to analyze.
- **interfunction_level** ([int](#)) – The level of interfunction-ness to be
- **initial_state** ([Optional](#)[[SimState](#)]) – A state to use as the initial one
- **avoid_runs** ([Optional](#)[[List](#)[[int](#)]]) – A list of runs to avoid
- **remove_options** ([Optional](#)[[Set](#)[[str](#)]]) – State options to remove from the initial state. It only works when *initial_state* is None
- **timeout** ([int](#)) –
- **final_state_callback** ([Optional](#)[[Callable](#)[[[SimState](#), [CallStack](#)], [Any](#)]]) – call-back function when countering final state

- **status_callback** (`Optional[Callable[[VFG], Any]]`) – callback function used in `_analysis_core_baremetal`
- **start** (`int | None`) –
- **max_iterations_before_widening** (`int`) –
- **max_iterations** (`int`) –
- **widening_interval** (`int`) –
- **record_function_final_states** (`bool`) –

Return type

`None`

property `function_initial_states`

property `function_final_states`

get_any_node(*addr*)

Get any VFG node corresponding to the basic block at @*addr*. Note that depending on the context sensitivity level, there might be multiple nodes corresponding to different contexts. This function will return the first one it encounters, which might not be what you want.

Return type

`Optional[VFGNode]`

Parameters

addr (`int`) –

get_all_nodes(*addr*)

Return type

`Generator[VFGNode, None, None]`

irsb_from_node(*node*)

copy()

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.vsa_ddg.DefUseChain`(*def_loc*, *use_loc*, *variable*)

Bases: `object`

Stand for a def-use chain. it is generated by the DDG itself.

__init__(*def_loc*, *use_loc*, *variable*)

Constructor.

Parameters

- **def_loc** –
- **use_loc** –
- **variable** –

Returns

```
class angr.analyses.vsa_ddg.VSA_DDГ(vfg=None, start_addr=None, interfunction_level=0,
                                     context_sensitivity_level=2, keep_data=False)
```

Bases: [Analysis](#)

A Data dependency graph based on VSA states. That means we don't (and shouldn't) expect any symbolic expressions.

```
__init__(vfg=None, start_addr=None, interfunction_level=0, context_sensitivity_level=2,
          keep_data=False)
```

Constructor.

Parameters

- **vfg** – An already constructed VFG. If not specified, a new VFG will be created with other specified parameters. *vfg* and *start_addr* cannot both be unspecified.
- **start_addr** – The address where to start the analysis (typically, a function's entry point).
- **interfunction_level** – See VFG analysis.
- **context_sensitivity_level** – See VFG analysis.
- **keep_data** – Whether we keep set of addresses as edges in the graph, or just the cardinality of the sets, which can be used as a “weight”.

```
get_predecessors(code_location)
```

Returns all predecessors of *code_location*.

Parameters

code_location – A CodeLocation instance.

Returns

A list of all predecessors.

```
get_all_nodes(simrun_addr, stmt_idx)
```

Get all DDG nodes matching the given basic block address and statement index.

project: Project

kb: KnowledgeBase

```
class angr.analyses.vtable.Vtable(vaddr, size, func_addrs=None)
```

Bases: [object](#)

This contains the addr, size and function addresses of a Vtable

```
__init__(vaddr, size, func_addrs=None)
```

```
class angr.analyses.vtable.VtableFinder
```

Bases: [Analysis](#)

This analysis locates Vtables in a binary based on heuristics taken from - “Reconstruction of Class Hierarchies for Decompilation of C++ Programs”

```
__init__()
```

```
is_cross_referenced(addr)
```

```
is_function(addr)
```

```
analyze()
```

```
create_extract_vtable(start_addr, sec_size)
```

```
project: Project
```

```
kb: KnowledgeBase
```

```
class angr.analyses.find_objects_static.PossibleObject(size, addr, class_name=None)
```

Bases: [object](#)

This holds the address and class name of possible class instances. The address that it holds is mapped outside the binary so it is only valid in this analysis. TO DO: map the address to its uses in the registers/memory locations in the instructions

```
__init__(size, addr, class_name=None)
```

```
class angr.analyses.find_objects_static.NewFunctionHandler(max_addr=None,
                                                           new_func_addr=None, project=None)
```

Bases: [FunctionHandler](#)

This handles calls to the function new(), by recording the size parameter passed to it and also assigns a new

address outside the mapped binary to the newly created space(possible object).

It also tracks if the function called right after new() is passed the same ‘this’ pointer and is a constructor, if so we mark it as an instance of the class the constructor belongs to.(only for non stripped binaries)

```
__init__(max_addr=None, new_func_addr=None, project=None)
```

```
hook(analysis)
```

Attach this instance of the function handler to an instance of RDA.

```
handle_local_function(state, data)
```

Parameters

- **state** ([ReachingDefinitionsState](#)) –
- **data** ([FunctionCallData](#)) –

```
class angr.analyses.find_objects_static.StaticObjectFinder
```

Bases: [Analysis](#)

This analysis tries to find objects on the heap based on calls to new(), and subsequent calls to constructors with the ‘this’ pointer

```
__init__()
```

```
project: Project
```

```
kb: KnowledgeBase
```

```
class angr.analyses.class_identifier.ClassIdentifier
```

Bases: [Analysis](#)

This is a class identifier for non stripped or partially stripped binaries, it identifies classes based on the demangled function names, and also assigns functions to their respective classes based on their names. It also uses the results from the VtableFinder analysis to assign the corresponding vtable to the classes.

self.classes contains a mapping between class names and SimCppClass objects

e.g. A::tool() and A::qux() belong to the class A

```

    __init__()

    project: Project

    kb: KnowledgeBase

class angr.analyses.disassembly.DisassemblyPiece
    Bases: object
    addr = None

    ident = nan

    render(formatting=None)

    getpiece(formatting, column)

    width(formatting)

    height(formatting)

    static color(string, coloring, formatting)

    highlight(string, formatting=None)

class angr.analyses.disassembly.FunctionStart(func)
    Bases: DisassemblyPiece

    __init__(func)
        Constructor.

        Parameters
            func (angr.knowledge.Function) – The function instance.

    height(formatting)

class angr.analyses.disassembly.Label(addr, name)
    Bases: DisassemblyPiece

    __init__(addr, name)

class angr.analyses.disassembly.IROp(addr, seq, obj, irsb)
    Bases: DisassemblyPiece

    Parameters
        • addr (int) –
        • seq (int) –
        • obj (IRStmt | PcodeOp) –
        • irsb (IRSB | IRSB) –

    __init__(addr, seq, obj, irsb)

    Parameters
        • addr (int) –
        • seq (int) –
        • obj (IRStmt | PcodeOp) –

```

```

        • irsb(IRSB / IRSB) –
addr: int
seq: int
obj: Union[IRStmt, PcodeOp]
irsb: Union[IRSB, IRSB]
class angr.analyses.disassembly.BlockStart(block, parentfunc, project)
    Bases: DisassemblyPiece
    __init__(block, parentfunc, project)
class angr.analyses.disassembly.Hook(block)
    Bases: DisassemblyPiece
    __init__(block)
class angr.analyses.disassembly.Instruction(insn, parentblock, project=None)
    Bases: DisassemblyPiece
    __init__(insn, parentblock, project=None)
    property mnemonic
    reload_format()
    dissect_instruction()
    dissect_instruction_for_arm()
    static split_arm_op_string(op_str)

        Parameters
        op_str (str) –
    dissect_instruction_by_default()
    static split_op_string(insn_str)
class angr.analyses.disassembly.SootExpression(expr)
    Bases: DisassemblyPiece
    __init__(expr)
class angr.analyses.disassembly.SootExpressionTarget(target_stmt_idx)
    Bases: SootExpression
    __init__(target_stmt_idx)
class angr.analyses.disassembly.SootExpressionStaticFieldRef(field)
    Bases: SootExpression
    __init__(field)
class angr.analyses.disassembly.SootExpressionInvoke(invoke_type, expr)
    Bases: SootExpression

```

```

    Virtual = 'virtual'

    Static = 'static'

    Special = 'special'

    __init__(invoke_type, expr)

class angr.analyses.disassembly.SootStatement(block_addr, raw_stmt)
    Bases: DisassemblyPiece
    __init__(block_addr, raw_stmt)

    property stmt_idx

class angr.analyses.disassembly.Opcode(parentinsn)
    Bases: DisassemblyPiece
    __init__(parentinsn)

class angr.analyses.disassembly.Operand(op_num, children, parentinsn)
    Bases: DisassemblyPiece
    __init__(op_num, children, parentinsn)

    property cs_operand

    static build(operand_type, op_num, children, parentinsn)

class angr.analyses.disassembly.ConstantOperand(op_num, children, parentinsn)
    Bases: Operand

class angr.analyses.disassembly.RegisterOperand(op_num, children, parentinsn)
    Bases: Operand
    property register

class angr.analyses.disassembly.MemoryOperand(op_num, children, parentinsn)
    Bases: Operand
    __init__(op_num, children, parentinsn)

class angr.analyses.disassembly.OperandPiece
    Bases: DisassemblyPiece
    addr = None

    parentop = None

    ident = None

class angr.analyses.disassembly.Register(reg, prefix='')
    Bases: OperandPiece
    __init__(reg, prefix='')

class angr.analyses.disassembly.Value(val, render_with_sign)
    Bases: OperandPiece
    __init__(val, render_with_sign)

```


property project

class `angr.analyses.disassembly.Comment(addr, text)`

Bases: `DisassemblyPiece`

`__init__`(*addr, text*)

`height`(*formatting*)

class `angr.analyses.disassembly.FuncComment(func)`

Bases: `DisassemblyPiece`

`__init__`(*func*)

class `angr.analyses.disassembly.Disassembly(function=None, ranges=None, thumb=False, include_ir=False, block_bytes=None)`

Bases: `Analysis`

Produce formatted machine code disassembly.

Parameters

- **function** (`Function` | `None`) –
- **ranges** (`Sequence[Tuple[int, int]]` | `None`) –
- **thumb** (`bool`) –
- **include_ir** (`bool`) –
- **block_bytes** (`bytes` | `None`) –

`__init__`(*function=None, ranges=None, thumb=False, include_ir=False, block_bytes=None*)

Parameters

- **function** (`Function` | `None`) –
- **ranges** (`Sequence[Tuple[int, int]]` | `None`) –
- **thumb** (`bool`) –
- **include_ir** (`bool`) –
- **block_bytes** (`bytes` | `None`) –

project: `Project`

kb: `KnowledgeBase`

func_lookup(*block*)

parse_block(*block*)

Parse instructions for a given block node

Return type

`None`

Parameters

block (`BlockNode`) –

render(*formatting=None, show_edges=True, show_addresses=True, show_bytes=False, ascii_only=None, color=True*)

Render the disassembly to a string, with optional edges and addresses.

Color will be added by default, if enabled. To disable color pass an empty formatting dict.

Return type

`str`

Parameters

- **show_edges** (*bool*) –
- **show_addresses** (*bool*) –
- **show_bytes** (*bool*) –
- **ascii_only** (*bool | None*) –
- **color** (*bool*) –

`angr.analyses.disassembly_utils.decode_instruction(arch, instr)`

exception `angr.analyses.reassembler.BinaryError`

Bases: `Exception`

exception `angr.analyses.reassembler.InstructionError`

Bases: `BinaryError`

exception `angr.analyses.reassembler.ReassemblerFailureNotice`

Bases: `BinaryError`

`angr.analyses.reassembler.string_escape(s)`

`angr.analyses.reassembler.fill_reg_map()`

`angr.analyses.reassembler.split_operands(s)`

`angr.analyses.reassembler.is_hex(s)`

class `angr.analyses.reassembler.Label(binary, name, original_addr=None)`

Bases: `object`

g_label_ctr = `count(0)`

__init__(*binary, name, original_addr=None*)

property `operand_str`

property `offset`

static `new_label(binary, name=None, function_name=None, original_addr=None, data_label=False)`

class `angr.analyses.reassembler.DataLabel(binary, original_addr, name=None)`

Bases: `Label`

__init__(*binary, original_addr, name=None*)

property `operand_str`

class `angr.analyses.reassembler.FunctionLabel(binary, function_name, original_addr, plt=False)`

Bases: `Label`

```

    __init__(binary, function_name, original_addr, plt=False)

    property function_name

    property operand_str

class angr.analyses.reassembler.ObjectLabel(binary, symbol_name, original_addr, plt=False)
    Bases: Label
    __init__(binary, symbol_name, original_addr, plt=False)

    property symbol_name

    property operand_str

class angr.analyses.reassembler.NotypeLabel(binary, symbol_name, original_addr, plt=False)
    Bases: Label
    __init__(binary, symbol_name, original_addr, plt=False)

    property symbol_name

    property operand_str

class angr.analyses.reassembler.SymbolManager(binary, cfg)
    Bases: object
    SymbolManager manages all symbols in the binary.

    __init__(binary, cfg)
        Constructor.

        Parameters
        • binary (Reassembler) – The Binary analysis instance.
        • cfg (angr.analyses.CFG) – The CFG analysis instance.

        Returns
        None

    get_unique_symbol_name(symbol_name)

    new_label(addr, name=None, is_function=None, force=False)

    label_got(addr, label)
        Mark a certain label as assigned (to an instruction or a block of data).

        Parameters
        • addr (int) – The address of the label.
        • label (angr.analyses.reassembler.Label) – The label that is just assigned.

        Returns
        None

class angr.analyses.reassembler.Operand(binary, insn_addr, insn_size, capstone_operand, operand_str,
                                          mnemonic, operand_offset, syntax=None)

    Bases: object

```

__init__(*binary*, *insn_addr*, *insn_size*, *capstone_operand*, *operand_str*, *mnemonic*, *operand_offset*, *syntax=None*)

Constructor.

Parameters

- **binary** (*Reassembler*) – The Binary analysis.
- **insn_addr** (*int*) – Address of the instruction.
- **capstone_operand** –
- **operand_str** (*str*) – the string representation of this operand
- **mnemonic** (*str*) – Mnemonic of the instruction that this operand belongs to.
- **operand_offset** (*int*) – offset of the operand into the instruction.
- **syntax** (*str*) – Provide a way to override the default syntax coming from *binary*.

Returns

None

assembly()

property is_immediate

property symbolized

class `angr.analyses.reassembler.Instruction`(*binary*, *addr*, *size*, *insn_bytes*, *capstone_instr*)

Bases: *object*

High-level representation of an instruction in the binary

__init__(*binary*, *addr*, *size*, *insn_bytes*, *capstone_instr*)

Parameters

- **binary** (*Reassembler*) – The Binary analysis
- **addr** (*int*) – Address of the instruction
- **size** (*int*) – Size of the instruction
- **insn_bytes** (*str*) – Instruction bytes
- **capstone_instr** – Capstone Instr object.

Returns

None

assign_labels()

dbg_comments()

assembly(*comments=False*, *symbolized=True*)

Returns

class `angr.analyses.reassembler.BasicBlock`(*binary*, *addr*, *size*, *x86_getpc_retsite=False*)

Bases: *object*

BasicBlock represents a basic block in the binary.

Parameters

x86_getpc_retsite (*bool*) –

`__init__(binary, addr, size, x86_getpc_retsite=False)`

Constructor.

Parameters

- **binary** ([Reassembler](#)) – The Binary analysis.
- **addr** ([int](#)) – Address of the block
- **size** ([int](#)) – Size of the block
- **x86_getpc_retsite** ([bool](#)) –

Returns

None

assign_labels()

assembly(*comments=False, symbolized=True*)

instruction_addresses()

class `angr.analyses.reassembler.Procedure`(*binary, function=None, addr=None, size=None, name=None, section='.text', asm_code=None*)

Bases: [object](#)

Procedure in the binary.

`__init__(binary, function=None, addr=None, size=None, name=None, section='.text', asm_code=None)`

Constructor.

Parameters

- **binary** ([Reassembler](#)) – The Binary analysis.
- **function** ([angr.knowledge.Function](#)) – The function it represents
- **addr** ([int](#)) – Address of the function. Not required if *function* is provided.
- **size** ([int](#)) – Size of the function. Not required if *function* is provided.
- **section** ([str](#)) – Which section this function comes from.

Returns

None

property name

Get function name from the labels of the very first block. :return: Function name if there is any, None otherwise :rtype: string

property is_plt

If this function is a PLT entry or not. :return: True if this function is a PLT entry, False otherwise :rtype: bool

assign_labels()

assembly(*comments=False, symbolized=True*)

Get the assembly manifest of the procedure.

Parameters

- **comments** –
- **symbolized** –

Returns

A list of tuples (address, basic block assembly), ordered by basic block addresses

Return type

`list`

instruction_addresses()

Get all instruction addresses in the binary.

Returns

A list of sorted instruction addresses.

Return type

`list`

class `angr.analyses.reassembler.ProcedureChunk`(*project*, *addr*, *size*)

Bases: `Procedure`

Procedure chunk.

__init__(*project*, *addr*, *size*)

Constructor.

Parameters

- **project** –
- **addr** –
- **size** –

Returns

class `angr.analyses.reassembler.Data`(*binary*, *memory_data*=None, *section*=None, *section_name*=None, *name*=None, *size*=None, *sort*=None, *addr*=None, *initial_content*=None)

Bases: `object`

__init__(*binary*, *memory_data*=None, *section*=None, *section_name*=None, *name*=None, *size*=None, *sort*=None, *addr*=None, *initial_content*=None)

property content

shrink(*new_size*)

Reduce the size of this block

Parameters

new_size (`int`) – The new size

Returns

None

desymbolize()

We believe this was a pointer and symbolized it before. Now we want to desymbolize it.

The following actions are performed: - Reload content from memory - Mark the sort as ‘unknown’

Returns

None

assign_labels()

assembly(*comments=False, symbolized=True*)

class angr.analyses.reassembler.**Relocation**(*addr, ref_addr, sort*)

Bases: `object`

__init__(*addr, ref_addr, sort*)

class angr.analyses.reassembler.**Reassembler**(*syntax='intel', remove_cgc_attachments=True, log_relocations=True*)

Bases: `Analysis`

High-level representation of a binary with a linear representation of all instructions and data regions. After calling “symbolize”, it essentially acts as a binary reassembler.

Tested on CGC, x86 and x86-64 binaries.

Disclaimer: The reassembler is an empirical solution. Don’t be surprised if it does not work on some binaries.

__init__(*syntax='intel', remove_cgc_attachments=True, log_relocations=True*)

property instructions

Get a list of all instructions in the binary

Returns

A list of (address, instruction)

Return type

`tuple`

property relocations

property inserted_asm_before_label

property inserted_asm_after_label

property main_executable_regions

return:

property main_nonexecutable_regions

return:

section_alignment(*section_name*)

Get the alignment for the specific section. If the section is not found, 16 is used as default.

Parameters

section_name (`str`) – The section.

Returns

The alignment in bytes.

Return type

`int`

main_executable_regions_contain(*addr*)

Parameters

addr –

Returns

main_executable_region_limbos_contain(addr)

Sometimes there exists a pointer that points to a few bytes before the beginning of a section, or a few bytes after the beginning of the section. We take care of that here.

Parameters

addr (*int*) – The address to check.

Returns

A 2-tuple of (bool, the closest base address)

Return type

tuple

main_nonexecutable_regions_contain(addr)**Parameters**

addr (*int*) – The address to check.

Returns

True if the address is inside a non-executable region, False otherwise.

Return type

bool

main_nonexecutable_region_limbos_contain(addr, tolerance_before=64, tolerance_after=64)

Sometimes there exists a pointer that points to a few bytes before the beginning of a section, or a few bytes after the beginning of the section. We take care of that here.

Parameters

addr (*int*) – The address to check.

Returns

A 2-tuple of (bool, the closest base address)

Return type

tuple

register_instruction_reference(insn_addr, ref_addr, sort, operand_offset)**register_data_reference(data_addr, ref_addr)****add_label(name, addr)**

Add a new label to the symbol manager.

Parameters

- **name** (*str*) – Name of the label.
- **addr** (*int*) – Address of the label.

Returns

None

insert_asm(addr, asm_code, before_label=False)

Insert some assembly code at the specific address. There must be an instruction starting at that address.

Parameters

- **addr** (*int*) – Address of insertion
- **asm_code** (*str*) – The assembly code to insert

Returns

None

append_procedure(*name*, *asm_code*)

Add a new procedure with specific name and assembly code.

Parameters

- **name** (*str*) – The name of the new procedure.
- **asm_code** (*str*) – The assembly code of the procedure

Returns

None

append_data(*name*, *initial_content*, *size*, *readonly=False*, *sort='unknown'*)

Append a new data entry into the binary with specific name, content, and size.

Parameters

- **name** (*str*) – Name of the data entry. Will be used as the label.
- **initial_content** (*bytes*) – The initial content of the data entry.
- **size** (*int*) – Size of the data entry.
- **readonly** (*bool*) – If the data entry belongs to the readonly region.
- **sort** (*str*) – Type of the data.

Returns

None

remove_instruction(*ins_addr*)

Parameters

ins_addr –

Returns

randomize_procedures()

Returns

symbolize()

assembly(*comments=False*, *symbolized=True*)

remove_cgc_attachments()

Remove CGC attachments.

Returns

True if CGC attachments are found and removed, False otherwise

Return type

bool

remove_unnecessary_stuff()

Remove unnecessary functions and data

Returns

None

remove_unnecessary_stuff_glibc()

project: Project

kb: `KnowledgeBase`

fast_memory_load(*addr*, *size*, *data_type*, *endness*='lend_LE')

Load memory bytes from loader's memory backend.

Parameters

- **addr** (*int*) – The address to begin memory loading.
- **size** (*int*) – Size in bytes.
- **data_type** – Type of the data.
- **endness** (*str*) – Endianness of this memory load.

Returns

Data read out of the memory.

Return type

int or *bytes* or *str* or *None*

class `angr.analyses.congruency_check.CongruencyCheck`(*throw*=*False*)

Bases: `Analysis`

This is an analysis to ensure that angr executes things identically with different execution backends (i.e., unicorn vs vex).

__init__(*throw*=*False*)

Initializes a `CongruencyCheck` analysis.

Parameters

throw – whether to raise an exception if an incongruency is found.

set_state_options(*left_add_options*=*None*, *left_remove_options*=*None*, *right_add_options*=*None*, *right_remove_options*=*None*)

Checks that the specified state options result in the same states over the next *depth* states.

set_states(*left_state*, *right_state*)

Checks that the specified paths stay the same over the next *depth* states.

set_simgr(*simgr*)

run(*depth*=*None*)

Checks that the paths in the specified path group stay the same over the next *depth* bytes.

The path group should have a “left” and a “right” stash, each with a single path.

compare_path_group(*pg*)

compare_states(*sl*, *sr*)

Compares two states for similarity.

compare_paths(*pl*, *pr*)

project: `Project`

kb: `KnowledgeBase`

```
class angr.analyses.static_hooker.StaticHooker(library, binary=None)
```

Bases: [Analysis](#)

This analysis works on statically linked binaries - it finds the library functions statically linked into the binary and hooks them with the appropriate simprocedures.

Right now it only works on unstripped binaries, but hey! There's room to grow!

```
__init__(library, binary=None)
```

project: [Project](#)

kb: [KnowledgeBase](#)

```
class angr.analyses.binary_optimizer.ConstantPropagation(constant, constant_assignment_loc,
                                                         constant_consuming_loc)
```

Bases: [object](#)

```
__init__(constant, constant_assignment_loc, constant_consuming_loc)
```

```
class angr.analyses.binary_optimizer.RedundantStackVariable(argument, stack_variable,
                                                            stack_variable_consuming_locs)
```

Bases: [object](#)

```
__init__(argument, stack_variable, stack_variable_consuming_locs)
```

```
class angr.analyses.binary_optimizer.RegisterReallocation(stack_variable, register_variable,
                                                         stack_variable_sources,
                                                         stack_variable_consumers,
                                                         prologue_addr, prologue_size,
                                                         epilogue_addr, epilogue_size)
```

Bases: [object](#)

```
__init__(stack_variable, register_variable, stack_variable_sources, stack_variable_consumers,
          prologue_addr, prologue_size, epilogue_addr, epilogue_size)
```

Constructor.

Parameters

- **stack_variable** ([SimStackVariable](#)) –
- **register_variable** ([SimRegisterVariable](#)) –
- **stack_variable_sources** ([list](#)) –
- **stack_variable_consumers** ([list](#)) –
- **prologue_addr** ([int](#)) –
- **prologue_size** ([int](#)) –
- **epilogue_addr** ([int](#)) –
- **epilogue_size** ([int](#)) –

```
class angr.analyses.binary_optimizer.DeadAssignment(pv)
```

Bases: [object](#)

```
__init__(pv)
```

Constructor.

Parameters

pv ([angr.analyses.ddg.ProgramVariable](#)) – The assignment to remove.

class `angr.analyses.binary_optimizer.BinaryOptimizer`(*cfg, techniques*)

Bases: [Analysis](#)

This is a collection of binary optimization techniques we used in Mechanical Phish during the finals of Cyber Grand Challenge. It focuses on dealing with some serious speed-impacting code constructs, and *sort of* worked on *some* CGC binaries compiled with O0. Use this analysis as a reference of how to use data dependency graph and such.

There is no guarantee that BinaryOptimizer will ever work on non-CGC binaries. Feel free to give us PR or MR, but please *do not* ask for support of non-CGC binaries.

BLOCKS_THRESHOLD = 500

__init__(*cfg, techniques*)

optimize()

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.callee_cleanup_finder.CalleeCleanupFinder`(*starts=None, hook_all=False*)

Bases: [Analysis](#)

__init__(*starts=None, hook_all=False*)

analyze(*addr*)

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.dominance_frontier.DominanceFrontier`(*func, exception_edges=False*)

Bases: [Analysis](#)

Computes the dominance frontier of all nodes in a function graph, and provides an easy-to-use interface for querying the frontier information.

__init__(*func, exception_edges=False*)

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.init_finder.SimEngineInitFinderVEX`(*project, replacements, overlay, pointers_only=False*)

Bases: [SimEngineLightVEXMixin](#), [SimEngineLight](#)

The VEX engine class for InitFinder.

__init__(*project, replacements, overlay, pointers_only=False*)

static is_concrete(*expr*)

Return type

`bool`

```
class angr.analyses.init_finder.InitializationFinder(func=None, func_graph=None, block=None,
                                                    max_iterations=1, replacements=None,
                                                    overlay=None, pointers_only=False)
```

Bases: [ForwardAnalysis](#), [Analysis](#)

Finds possible initializations for global data sections and generate an overlay to be used in other analyses later on.

```
__init__(func=None, func_graph=None, block=None, max_iterations=1, replacements=None,
         overlay=None, pointers_only=False)
```

Constructor

Parameters

- **order_jobs** (*bool*) – If all jobs should be ordered or not.
- **allow_merging** (*bool*) – If job merging is allowed.
- **allow_widening** (*bool*) – If job widening is allowed.
- **graph_visitor** ([GraphVisitor](#) or *None*) – A graph visitor to provide successors.

Returns

None

project: [Project](#)

kb: [KnowledgeBase](#)

```
class angr.analyses.xrefs.SimEngineXRefsVEX(xref_manager, project=None, replacements=None)
```

Bases: [SimEngineLightVEXMixin](#), [SimEngineLight](#)

The VEX engine class for XRefs analysis.

```
__init__(xref_manager, project=None, replacements=None)
```

```
add_xref(xref_type, from_loc, to_loc)
```

```
static extract_value_if_concrete(expr)
```

Extract the concrete value from *expr* if it is a concrete claripy AST.

Parameters

expr – A claripy AST.

Return type

[Optional\[int\]](#)

Returns

A concrete value or *None* if nothing concrete can be extracted.

```
class angr.analyses.xrefs.XRefsAnalysis(func=None, func_graph=None, block=None, max_iterations=1,
                                       replacements=None)
```

Bases: [ForwardAnalysis](#), [Analysis](#)

XRefsAnalysis recovers in-depth x-refs (cross-references) in disassembly code.

Here is an example:

```
.text:
000023C8          LDR    R2, =time_now
000023CA          LDR    R3, [R2]
```

(continues on next page)

(continued from previous page)

```
000023CC      ADDS    R3, #1
000023CE      STR     R3, [R2]
000023D0      BX      LR

.bss:
1FFF36F4 time_now      % 4
```

You will have the following x-refs for `time_now`:

```
23c8 - offset
23ca - read access
23ce - write access
```

__init__ (*func=None, func_graph=None, block=None, max_iterations=1, replacements=None*)

Constructor

Parameters

- **order_jobs** (*bool*) – If all jobs should be ordered or not.
- **allow_merging** (*bool*) – If job merging is allowed.
- **allow_widening** (*bool*) – If job widening is allowed.
- **graph_visitor** (*GraphVisitor* or *None*) – A graph visitor to provide successors.

Returns

None

project: `Project`

kb: `KnowledgeBase`

class `angr.analyses.proximity_graph.ProxiNodeTypes`

Bases: `object`

Node Type Enums

Empty = 0

String = 1

Function = 2

FunctionCall = 3

Integer = 4

Unknown = 5

Variable = 6

class `angr.analyses.proximity_graph.BaseProxiNode` (*type_, ref_at=None*)

Bases: `object`

Base class for all nodes in a proximity graph.

Parameters

- **type_** (*int*) –

```

    • ref_at (Set[int] | None) –
__init__ (type_, ref_at=None)

Parameters
    • type_ (int) –
    • ref_at (Set[int] | None) –
class angr.analyses.proximity_graph.FunctionProxiNode(func, ref_at=None)
Bases: BaseProxiNode
Proximity node showing current and expanded function calls in graph.

Parameters
    ref_at (Set[int] | None) –
__init__ (func, ref_at=None)

Parameters
    ref_at (Set[int] | None) –
class angr.analyses.proximity_graph.VariableProxiNode(addr, name, ref_at=None)
Bases: BaseProxiNode
Variable arg node

Parameters
    ref_at (Set[int] | None) –
__init__ (addr, name, ref_at=None)

Parameters
    ref_at (Set[int] | None) –
class angr.analyses.proximity_graph.StringProxiNode(addr, content, ref_at=None)
Bases: BaseProxiNode
String arg node

Parameters
    ref_at (Set[int] | None) –
__init__ (addr, content, ref_at=None)

Parameters
    ref_at (Set[int] | None) –
class angr.analyses.proximity_graph.CallProxiNode(callee, ref_at=None, args=None)
Bases: BaseProxiNode
Call node

Parameters
    • ref_at (Set[int] | None) –
    • args (Tuple[BaseProxiNode] | None) –
__init__ (callee, ref_at=None, args=None)

Parameters
    • ref_at (Set[int] | None) –

```

- **args** (*Tuple*[*BaseProxiNode*] | *None*) –

class `angr.analyses.proximity_graph.IntegerProxiNode`(*value*, *ref_at=None*)

Bases: *BaseProxiNode*

Int arg node

Parameters

- **value** (*int*) –
- **ref_at** (*Set*[*int*] | *None*) –

__init__(*value*, *ref_at=None*)

Parameters

- **value** (*int*) –
- **ref_at** (*Set*[*int*] | *None*) –

class `angr.analyses.proximity_graph.UnknownProxiNode`(*dummy_value*)

Bases: *BaseProxiNode*

Unknown arg node

Parameters

dummy_value (*str*) –

__init__(*dummy_value*)

Parameters

dummy_value (*str*) –

class `angr.analyses.proximity_graph.ProximityGraphAnalysis`(*func*, *cfg_model*, *xrefs*,
decompilation=None,
expand_funcs=None)

Bases: *Analysis*

Generate a proximity graph.

Parameters

- **func** (*Function*) –
- **cfg_model** (*CFGModel*) –
- **xrefs** (*XRefManager*) –
- **decompilation** (*Decompiler* | *None*) –
- **expand_funcs** (*Set*[*int*] | *None*) –

__init__(*func*, *cfg_model*, *xrefs*, *decompilation=None*, *expand_funcs=None*)

Parameters

- **func** (*Function*) –
- **cfg_model** (*CFGModel*) –
- **xrefs** (*XRefManager*) –
- **decompilation** (*Decompiler* | *None*) –
- **expand_funcs** (*Set*[*int*] | *None*) –

project: `Project`

kb: `KnowledgeBase`

Defines analysis that will generate a dynamic data-dependency graph

class `angr.analyses.data_dep.data_dependency_analysis.NodalAnnotation`(*node*)

Bases: `Annotation`

Allows a node to be stored as an annotation to a BV in a DefaultMemory instance

Parameters

node (`BaseDepNode`) –

__init__(*node*)

Parameters

node (`BaseDepNode`) –

property relocatable: `bool`

Can not be relocated in a simplification

property eliminatable

Can not be eliminated in a simplification

class `angr.analyses.data_dep.data_dependency_analysis.DataDependencyGraphAnalysis`(*end_state*,
start_from=None,
end_at=None,
block_addrs=None)

Bases: `Analysis`

This is a DYNAMIC data dependency graph that utilizes a given SimState to produce a DDG graph that is accurate to the path the program took during execution.

This analysis utilizes the SimActionData objects present in the provided SimState's action history to generate the dependency graph.

Parameters

- **end_state** (`SimState`) –
- **start_from** (`int` | `None`) –
- **end_at** (`int` | `None`) –
- **block_addrs** (`List[int]` | `None`) –

__init__(*end_state*, *start_from=None*, *end_at=None*, *block_addrs=None*)

Parameters

- **end_state** (`SimState`) – Simulation state used to extract all SimActionData
- **start_from** (`Optional[int]`) – An address or None, Specifies where to start generation of DDG
- **end_at** (`Optional[int]`) – An address or None, Specifies where to end generation of DDG
- **block_addrs** (`List[int]` | `None`) – List of block addresses that the DDG analysis should be run on
- **block_addrs** –

```

property graph: DiGraph | None
property simplified_graph: DiGraph | None
property sub_graph: DiGraph | None
get_data_dep(g_node, include_tmp_nodes, backwards)

```

Return type
Optional[DiGraph]

Parameters

- *g_node* (BaseDepNode) –
- *include_tmp_nodes* (bool) –
- *backwards* (bool) –

```
project: Project
```

```
kb: KnowledgeBase
```

```
class angr.analyses.data_dep.sim_act_location.SimActLocation(bbl_addr, ins_addr, stmt_idx)
```

Bases: object

Structure-like class used to bundle the instruction address and statement index of a given SimAction in order to uniquely identify a given SimAction

Parameters

- *bbl_addr* (int) –
- *ins_addr* (int) –
- *stmt_idx* (int) –

```
__init__(bbl_addr, ins_addr, stmt_idx)
```

Parameters

- *bbl_addr* (int) –
- *ins_addr* (int) –
- *stmt_idx* (int) –

```
class angr.analyses.data_dep.sim_act_location.ParsedInstruction(ins_addr, min_stmt_idx,
                                                                max_stmt_idx)
```

Bases: object

Used by parser to facilitate linking with recent ancestors in an efficient manner

Parameters

- *ins_addr* (int) –
- *min_stmt_idx* (int) –
- *max_stmt_idx* (int) –

```
__init__(ins_addr, min_stmt_idx, max_stmt_idx)
```

Parameters

- *ins_addr* (int) –

- `min_stmt_idx(int)` –
- `max_stmt_idx(int)` –

class `angr.analyses.data_dep.dep_nodes.DepNodeTypes`

Bases: `object`

Enumeration of types of BaseDepNode supported by this analysis

Memory = 1

Register = 2

Tmp = 3

Constant = 4

class `angr.analyses.data_dep.dep_nodes.BaseDepNode(type_, sim_act)`

Bases: `object`

Base class for all nodes in a data-dependency graph

Parameters

- `type_(int)` –
- `sim_act(SimActionData)` –

`__init__(type_, sim_act)`

Parameters

- `type_(int)` –
- `sim_act(SimActionData)` –

`value_tuple()`

Return type

`Tuple[BV, int]`

Returns

A tuple containing the node's value as a BV and as an evaluated integer

property ast: `BV`

property type: `int`

Getter :return: An integer defined in DepNodeTypes, represents the subclass type of this DepNode.

class `angr.analyses.data_dep.dep_nodes.ConstantDepNode(sim_act, value)`

Bases: `BaseDepNode`

Used to create a DepNode that will hold a constant, numeric value Uniquely identified by its value

Parameters

- `sim_act(SimActionData)` –
- `value(int)` –

`__init__(sim_act, value)`

Parameters

- `sim_act(SimActionData)` –

- **value** (*int*) –

class `angr.analyses.data_dep.dep_nodes.MemDepNode`(*sim_act*, *addr*)

Bases: [*BaseDepNode*](#)

Used to represent SimActions of type MEM

Parameters

- **sim_act** ([*SimActionData*](#)) –
- **addr** (*int*) –

__init__(*sim_act*, *addr*)

Parameters

- **sim_act** ([*SimActionData*](#)) –
- **addr** (*int*) –

property **width**: *int*

classmethod **cast_to_mem**(*base_dep_node*)

Casts a BaseDepNode into a MemDepNode

Parameters

base_dep_node ([*BaseDepNode*](#)) –

class `angr.analyses.data_dep.dep_nodes.VarDepNode`(*type_*, *sim_act*, *reg*, *arch_name=""*)

Bases: [*BaseDepNode*](#)

Abstract class for representing SimActions of TYPE reg or tmp

Parameters

- **type_** (*int*) –
- **sim_act** ([*SimActionData*](#)) –
- **reg** (*int*) –
- **arch_name** (*str*) –

__init__(*type_*, *sim_act*, *reg*, *arch_name=""*)

Parameters

- **type_** (*int*) –
- **sim_act** ([*SimActionData*](#)) –
- **reg** (*int*) –
- **arch_name** (*str*) –

property **display_name**: *str*

class `angr.analyses.data_dep.dep_nodes.TmpDepNode`(*sim_act*, *reg*, *arch_name=""*)

Bases: [*VarDepNode*](#)

Used to represent SimActions of type TMP

Parameters

- **sim_act** ([*SimActionData*](#)) –
- **reg** (*int*) –

```

    • arch_name (str) –
__init__(sim_act, reg, arch_name="")

Parameters
    • sim_act (SimActionData) –
    • reg (int) –
    • arch_name (str) –
class angr.analyses.data_dep.dep_nodes.RegDepNode(sim_act, reg, arch_name="")
Bases: VarDepNode
Base class for representing SimActions of TYPE reg

Parameters
    • sim_act (SimActionData) –
    • reg (int) –
    • arch_name (str) –
__init__(sim_act, reg, arch_name="")

Parameters
    • sim_act (SimActionData) –
    • reg (int) –
    • arch_name (str) –
property reg_size: int

exception angr.blade.BadJumpkindNotification
Bases: Exception
Notifies the caller that the jumpkind is bad (e.g., Ijk_NoDecode)

class angr.blade.Blade(graph, dst_run, dst_stmt_idx, direction='backward', project=None, cfg=None,
                      ignore_sp=False, ignore_bp=False, ignored_regs=None, max_level=3,
                      base_state=None, stop_at_calls=False, cross_insn_opt=False, max_predecessors=10,
                      include_emarks=True)
Bases: object
Blade is a light-weight program slicer that works with networkx DiGraph containing CFGNodes. It is meant to
be used in angr for small or on-the-fly analyses.

Parameters
    • graph (DiGraph) –
    • dst_run (int) –
    • dst_stmt_idx (int) –
    • direction (str) –
    • ignore_sp (bool) –
    • ignore_bp (bool) –
    • max_level (int) –

```

- **stop_at_calls** (*bool*) –
- **max_predecessors** (*int*) –
- **include_emarks** (*bool*) –

__init__(*graph*, *dst_run*, *dst_stmt_idx*, *direction*='backward', *project*=None, *cfg*=None, *ignore_sp*=False, *ignore_bp*=False, *ignored_regs*=None, *max_level*=3, *base_state*=None, *stop_at_calls*=False, *cross_insn_opt*=False, *max_predecessors*=10, *include_emarks*=True)

Parameters

- **graph** (*DiGraph*) – A graph representing the control flow graph. Note that it does not take `angr.analyses.CFGEEmulated` or `angr.analyses.CFGFast`.
- **dst_run** (*int*) – An address specifying the target `SimRun`.
- **dst_stmt_idx** (*int*) – The target statement index. -1 means executing until the last statement.
- **direction** (*str*) – ‘backward’ or ‘forward’ slicing. Forward slicing is not yet supported.
- **project** (*angr.Project*) – The project instance.
- **cfg** (*angr.analyses.CFGBase*) – the CFG instance. It will be made mandatory later.
- **ignore_sp** (*bool*) – Whether the stack pointer should be ignored in dependency tracking. Any dependency from/to stack pointers will be ignored if this options is True.
- **ignore_bp** (*bool*) – Whether the base pointer should be ignored or not.
- **max_level** (*int*) – The maximum number of blocks that we trace back for.
- **stop_at_calls** (*bool*) – Limit slicing within a single function. Do not proceed when encounters a call edge.
- **include_emarks** (*bool*) – Should IMarks (instruction boundaries) be included in the slice.
- **max_predecessors** (*int*) –

Returns

None

property slice

dbg_repr(*arch*=None)

class `angr.slicer.SimLightState`(*temps*=None, *regs*=None, *stack_offsets*=None, *options*=None)

Bases: `object`

Represents a program state. Only used in `SimSlicer`.

__init__(*temps*=None, *regs*=None, *stack_offsets*=None, *options*=None)

temps

regs

stack_offsets

options

```
class angr.slicer.SimSlicer(arch, statements, target_tmps=None, target_regs=None,
                          target_stack_offsets=None, inslice_callback=None,
                          inslice_callback_infodict=None, include_emarks=True)
```

Bases: `object`

A super lightweight intra-IRSB slicing class.

Parameters

include_emarks (*bool*) –

```
__init__(arch, statements, target_tmps=None, target_regs=None, target_stack_offsets=None,
         inslice_callback=None, inslice_callback_infodict=None, include_emarks=True)
```

Parameters

include_emarks (*bool*) –

```
class angr.annocfg.AnnotatedCFG(project, cfg=None, detect_loops=False)
```

Bases: `object`

AnnotatedCFG is a control flow graph with statement whitelists and exit whitelists to describe a slice of the program.

```
__init__(project, cfg=None, detect_loops=False)
```

Constructor.

Parameters

- **project** – The angr Project instance
- **cfg** – Control flow graph.
- **detect_loops** –

```
from_digraph(digraph)
```

Initialize this AnnotatedCFG object with a `networkx.DiGraph` consisting of the following form of nodes:

Tuples like (block address, statement ID)

Those nodes are connected by edges indicating the execution flow.

Parameters

digraph (*networkx.DiGraph*) – A `networkx.DiGraph` object

```
get_addr(run)
```

```
add_block_to_whitelist(block)
```

```
add_statements_to_whitelist(block, stmt_ids)
```

```
add_exit_to_whitelist(run_from, run_to)
```

```
set_last_statement(block_addr, stmt_id)
```

```
add_loop(loop_tuple)
```

A loop tuple contains a series of IRSB addresses that form a loop. Ideally it always starts with the first IRSB that we meet during the execution.

```
should_take_exit(addr_from, addr_to)
```

```
should_execute_statement(addr, stmt_id)
```

```
get_run(addr)
```

get_whitelisted_statements(*addr*)

Returns

True if all statements are whitelisted

get_last_statement_index(*addr*)

Get the statement index of the last statement to execute in the basic block specified by *addr*.

Parameters

addr (*int*) – Address of the basic block.

Returns

The statement index of the last statement to be executed in the block. Usually if the default exit is taken, it will be the last statement to execute. If the block is not in the slice or we should never take any exit going to this block, None is returned.

Return type

int or None

get_loops()

get_targets(*source_addr*)

dbg_repr()

dbg_print_irsb(*irsb_addr*, *project=None*)

Pretty-print an IRSB with whitelist information

keep_path(*path*)

Given a path, returns True if the path should be kept, False if it should be cut.

merge_points(*path*)

successor_func(*path*)

Callback routine that takes in a path, and returns all feasible successors to path group. This callback routine should be passed to the keyword argument “successor_func” of PathGroup.step().

Parameters

path – A Path instance.

Returns

A list of all feasible Path successors.

`angr.codenode.repr_addr`(*addr*)

class `angr.codenode.CodeNode`(*addr*, *size*, *graph=None*, *thumb=False*)

Bases: `object`

Parameters

- **addr** (*int*) –
- **size** (*int*) –

__init__(*addr*, *size*, *graph=None*, *thumb=False*)

Parameters

- **addr** (*int*) –
- **size** (*int*) –


```

    addr: int
    size: int
    thumb
    successors()

    Return type
    List[CodeNode]
    predecessors()
    is_hook = None
class angr.codenode.BlockNode(addr, size, bytestr=None, **kwargs)
    Bases: CodeNode
    Parameters
        • addr (int) –
        • size (int) –
    is_hook = False
    __init__(addr, size, bytestr=None, **kwargs)
    Parameters
        addr (int) –
    bytestr
class angr.codenode.SootBlockNode(addr, size, stmts, **kwargs)
    Bases: BlockNode
    Parameters
        • addr (int) –
        • size (int) –
    __init__(addr, size, stmts, **kwargs)
    stmts
class angr.codenode.HookNode(addr, size, sim_procedure, **kwargs)
    Bases: CodeNode
    Parameters
        • addr (int) –
        • size (int) –
    is_hook = True
    __init__(addr, size, sim_procedure, **kwargs)
    Parameters
        sim_procedure (type) – the the sim_procedure class
    sim_procedure

```

class `angr.codenode.SyscallNode(addr, size, sim_procedure, **kwargs)`

Bases: `HookNode`

Parameters

- **addr** (`int`) –
- **size** (`int`) –

is_hook = `False`

sim_procedure

10.16 SimOS

Manage OS-level configuration.

`angr.simos.register_simos(name, cls)`

class `angr.simos.simos.SimOS(project, name=None)`

Bases: `object`

A class describing OS/arch-level configuration.

Parameters

project (`angr.Project`) –

__init__ (`project, name=None`)

Parameters

project (`Project`) –

configure_project ()

Configure the project to set up global settings (like SimProcedures).

state_blank (`addr=None, initial_prefix=None, brk=None, stack_end=None, stack_size=8388608, stdin=None, thread_idx=None, permissions_backer=None, **kwargs`)

Initialize a blank state.

All parameters are optional.

Parameters

- **addr** – The execution start address.
- **initial_prefix** –
- **stack_end** – The end of the stack (i.e., the byte after the last valid stack address).
- **stack_size** – The number of bytes to allocate for stack space
- **brk** – The address of the process' break.

Returns

The initialized SimState.

Any additional arguments will be passed to the SimState constructor

state_entry (`**kwargs`)

state_full_init (`**kwargs`)

state_call(*addr*, **args*, ***kwargs*)

prepare_call_state(*calling_state*, *initial_state=None*, *preserve_registers=()*, *preserve_memory=()*)

This function prepares a state that is executing a call instruction. If given an *initial_state*, it copies over all of the critical registers to it from the *calling_state*. Otherwise, it prepares the *calling_state* for action.

This is mostly used to create minimalistic for CFG generation. Some ABIs, such as MIPS PIE and x86 PIE, require certain information to be maintained in certain registers. For example, for PIE MIPS, this function transfer *t9*, *gp*, and *ra* to the new state.

prepare_function_symbol(*symbol_name*, *basic_addr=None*)

Prepare the address space with the data necessary to perform relocations pointing to the given symbol

Returns a 2-tuple. The first item is the address of the function code, the second is the address of the relocation target.

handle_exception(*successors*, *engine*, *exception*)

Perform exception handling. This method will be called when, during execution, a *SimException* is thrown. Currently, this can only indicate a segfault, but in the future it could indicate any unexpected exceptional behavior that can't be handled by ordinary control flow.

The method may mutate the provided *SimSuccessors* object in any way it likes, or re-raise the exception.

Parameters

- **successors** – The *SimSuccessors* object currently being executed on
- **engine** – The engine that was processing this step
- **exception** – The actual exception object

syscall(*state*, *allow_unsupported=True*)

syscall_abi(*state*)

Return type

str

syscall_cc(*state*)

Return type

Optional[SimCCSyscall]

is_syscall_addr(*addr*)

syscall_from_addr(*addr*, *allow_unsupported=True*)

syscall_from_number(*number*, *allow_unsupported=True*, *abi=None*)

setup_gdt(*state*, *gdt*)

Write the *GlobalDescriptorTable* object in the current state memory

Parameters

- **state** – state in which to write the GDT
- **gdt** – *GlobalDescriptorTable* object

Returns

generate_gdt(*fs*, *gs*, *fs_size=4294967295*, *gs_size=4294967295*)

Generate a GlobalDescriptorTable object and populate it using the value of the gs and fs register

Parameters

- **fs** – value of the fs segment register
- **gs** – value of the gs segment register
- **fs_size** – size of the fs segment register
- **gs_size** – size of the gs segment register

Returns

gdt a GlobalDescriptorTable object

class `angr.simos.simos.GlobalDescriptorTable`(*addr*, *limit*, *table*, *gdt_sel*, *cs_sel*, *ds_sel*, *es_sel*, *ss_sel*, *fs_sel*, *gs_sel*)

Bases: `object`

__init__(*addr*, *limit*, *table*, *gdt_sel*, *cs_sel*, *ds_sel*, *es_sel*, *ss_sel*, *fs_sel*, *gs_sel*)

class `angr.simos.linux.SimLinux`(*project*, ***kwargs*)

Bases: `SimUserland`

OS-specific configuration for *nix-y OSes.

__init__(*project*, ***kwargs*)

configure_project()

Configure the project to set up global settings (like SimProcedures).

syscall_abi(*state*)

Optionally, override this function to determine which abi is being used for the state's current syscall.

state_blank(*fs=None*, *concrete_fs=False*, *chroot=None*, *cwd=None*, *pathsep=b'/'*, *thread_idx=None*, *init_libc=False*, ***kwargs*)

Initialize a blank state.

All parameters are optional.

Parameters

- **addr** – The execution start address.
- **initial_prefix** –
- **stack_end** – The end of the stack (i.e., the byte after the last valid stack address).
- **stack_size** – The number of bytes to allocate for stack space
- **brk** – The address of the process' break.

Returns

The initialized SimState.

Any additional arguments will be passed to the SimState constructor

state_entry(*args=None*, *env=None*, *argc=None*, ***kwargs*)

set_entry_register_values(*state*)

state_full_init(***kwargs*)

prepare_function_symbol(*symbol_name*, *basic_addr=None*)

Prepare the address space with the data necessary to perform relocations pointing to the given symbol.

Returns a 2-tuple. The first item is the address of the function code, the second is the address of the relocation target.

initialize_segment_register_x64(*state*, *concrete_target*)

Set the fs register in the angr to the value of the fs register in the concrete process

Parameters

- **state** – state which will be modified
- **concrete_target** – concrete target that will be used to read the fs register

Returns

None

initialize_gdt_x86(*state*, *concrete_target*)

Create a GDT in the state memory and populate the segment registers. Rehook the vsyscall address using the real value in the concrete process memory

Parameters

- **state** – state which will be modified
- **concrete_target** – concrete target that will be used to read the fs register

Returns

get_segment_register_name()

class `angr.simos.cgc.SimCGC`(*project*, ***kwargs*)

Bases: [`SimUserland`](#)

Environment configuration for the CGC DECREE platform

__init__(*project*, ***kwargs*)

state_blank(*flag_page=None*, *allocate_stack_page_count=256*, ***kwargs*)

Parameters

- **flag_page** – Flag page content, either a string or a list of BV8s
- **allocate_stack_page_count** – Number of pages to pre-allocate for stack

state_entry(*add_options=None*, ***kwargs*)

class `angr.simos.userland.SimUserland`(*project*, *syscall_library=None*, *syscall_addr_alignment=4*, ***kwargs*)

Bases: [`SimOS`](#)

This is a base class for any SimOS that wants to support syscalls.

It uses the CLE kernel object to provide addresses for syscalls. Syscalls will be emulated as a jump to one of these addresses, where a SimProcedure from the syscall library provided at construction time will be executed.

__init__(*project*, *syscall_library=None*, *syscall_addr_alignment=4*, ***kwargs*)

configure_project(*abi_list=None*)

Configure the project to set up global settings (like SimProcedures).

syscall_cc(*state*)

Return type

SimCCSyscall

syscall(*state*, *allow_unsupported=True*)

Given a state, return the procedure corresponding to the current syscall. This procedure will have .syscall_number, .display_name, and .addr set.

Parameters

- **state** – The state to get the syscall number from
- **allow_unsupported** – Whether to return a “dummy” syscall instead of raising an unsupported exception

syscall_abi(*state*)

Optionally, override this function to determine which abi is being used for the state’s current syscall.

is_syscall_addr(*addr*)

Return whether or not the given address corresponds to a syscall implementation.

syscall_from_addr(*addr*, *allow_unsupported=True*)

Get a syscall SimProcedure from an address.

Parameters

- **addr** – The address to convert to a syscall SimProcedure
- **allow_unsupported** – Whether to return a dummy procedure for an unsupported syscall instead of raising an exception.

Returns

The SimProcedure for the syscall, or None if the address is not a syscall address.

syscall_from_number(*number*, *allow_unsupported=True*, *abi=None*)

Get a syscall SimProcedure from its number.

Parameters

- **number** – The syscall number
- **allow_unsupported** – Whether to return a “stub” syscall for unsupported numbers instead of throwing an error
- **abi** – The name of the abi to use. If None, will assume that the abis have disjoint numbering schemes and pick the right one.

Returns

The SimProcedure for the syscall

class `angr.simos.windows.SecurityCookieInit`(*value*)

Bases: `Enum`

An enumeration.

NONE = 0

RANDOM = 1

STATIC = 2

SYMBOLIC = 3

class `angr.simos.windows.SimWindows`(*project*)

Bases: `SimOS`

Environment for the Windows Win32 subsystem. Does not support syscalls currently.

__init__(*project*)

configure_project()

Configure the project to set up global settings (like SimProcedures).

state_entry(*args=None, env=None, argc=None, **kwargs*)

state_blank(*thread_idx=None, **kwargs*)

Initialize a blank state.

All parameters are optional.

Parameters

- **addr** – The execution start address.
- **initial_prefix** –
- **stack_end** – The end of the stack (i.e., the byte after the last valid stack address).
- **stack_size** – The number of bytes to allocate for stack space
- **brk** – The address of the process' break.

Returns

The initialized SimState.

Any additional arguments will be passed to the SimState constructor

handle_exception(*successors, engine, exception*)

Perform exception handling. This method will be called when, during execution, a SimException is thrown. Currently, this can only indicate a segfault, but in the future it could indicate any unexpected exceptional behavior that can't be handled by ordinary control flow.

The method may mutate the provided SimSuccessors object in any way it likes, or re-raise the exception.

Parameters

- **successors** – The SimSuccessors object currently being executed on
- **engine** – The engine that was processing this step
- **exception** – The actual exception object

initialize_segment_register_x64(*state, concrete_target*)

Set the gs register in the angr to the value of the fs register in the concrete process

Parameters

- **state** – state which will be modified
- **concrete_target** – concrete target that will be used to read the fs register

Returns

None

initialize_gdt_x86(*state, concrete_target*)

Create a GDT in the state memory and populate the segment registers.

Parameters

- **state** – state which will be modified
- **concrete_target** – concrete target that will be used to read the fs register

Returns

the created GlobalDescriptorTable object

get_segment_register_name()

class `angr.simos.javavm.SimJavaVM(*args, **kwargs)`

Bases: `SimOS`

__init__(*args, **kwargs)

state_blank(*addr=None*, **kwargs)

Initialize a blank state.

All parameters are optional.

Parameters

- **addr** – The execution start address.
- **initial_prefix** –
- **stack_end** – The end of the stack (i.e., the byte after the last valid stack address).
- **stack_size** – The number of bytes to allocate for stack space
- **brk** – The address of the process' break.

Returns

The initialized SimState.

Any additional arguments will be passed to the SimState constructor

state_entry(*args=None*, **kwargs)

Create an entry state.

Parameters

args – List of SootArgument values (optional).

static generate_symbolic_cmd_line_arg(*state*, *max_length=1000*)

Generates a new symbolic cmd line argument string. :return: The string reference.

state_call(*addr*, *args, **kwargs)

Create a native or a Java call state.

Parameters

- **addr** – Soot or native addr of the invoke target.
- **args** – List of SootArgument values.

static get_default_value_by_type(*type_*, *state*)

Java specify defaults values for primitive and reference types. This method returns the default value for a given type.

Parameters

- **type** (*str*) – Name of type.
- **state** (`SimState`) – Current SimState.

Returns

Default value for this type.

static cast_primitive(*state, value, to_type*)

Cast the value of primitive types.

Parameters

- **value** – Bitvector storing the primitive value.
- **to_type** – Name of the targeted type.

Returns

Resized value.

static init_static_field(*state, field_class_name, field_name, field_type*)

Initialize the static field with an allocated, but not initialized, object of the given type.

Parameters

- **state** – State associated to the field.
- **field_class_name** – Class containing the field.
- **field_name** – Name of the field.
- **field_type** – Type of the field and the new object.

static get_cmd_line_args(*state*)

get_addr_of_native_method(*soot_method*)

Get address of the implementation from a native declared Java function.

Parameters

soot_method – Method descriptor of a native declared function.

Returns

CLE address of the given method.

get_native_type(*java_type*)

Maps the Java type to a SimTypeReg representation of its native counterpart. This type can be used to indicate the (well-defined) size of native JNI types.

Returns

A SymTypeReg with the JNI size of the given type.

get_method_native_type(*method*)

property native_arch

Arch of the native simos.

Type

return

get_native_cc()

Returns

SimCC object for the native simos.

`angr.simos.javavm.prepare_native_return_state`(*native_state*)

Hook target for native function call returns.

Recovers and stores the return value from native memory and toggles the state, s.t. execution continues in the Soot engine.

Note: Redirection needed for pickling.

10.17 Function Signature Matching

```
class angr.flirt.FlirtSignature(arch, platform, sig_name, sig_path, unique_strings=None, compiler=None,
                             compiler_version=None, os_name=None, os_version=None)
```

Bases: `object`

This class describes a FLIRT signature.

Parameters

- **arch** (*str*) –
- **platform** (*str*) –
- **sig_name** (*str*) –
- **sig_path** (*str*) –
- **unique_strings** (*Set[str] | None*) –
- **compiler** (*str | None*) –
- **compiler_version** (*str | None*) –
- **os_name** (*str | None*) –
- **os_version** (*str | None*) –

```
__init__(arch, platform, sig_name, sig_path, unique_strings=None, compiler=None,
         compiler_version=None, os_name=None, os_version=None)
```

Parameters

- **arch** (*str*) –
- **platform** (*str*) –
- **sig_name** (*str*) –
- **sig_path** (*str*) –
- **unique_strings** (*Set[str] | None*) –
- **compiler** (*str | None*) –
- **compiler_version** (*str | None*) –
- **os_name** (*str | None*) –
- **os_version** (*str | None*) –

`angr.flirt.FS`

alias of *FlirtSignature*

`angr.flirt.load_signatures(path)`

Recursively load all FLIRT signatures under a specific path.

Parameters

path (*str*) – Location of FLIRT signatures.

Return type

`None`

```
angr.flirt.build_sig.get_basic_info(ar_path)
```

Get basic information of the archive file.

Return type

`Dict[str, str]`

Parameters

`ar_path` (*str*) –

```
angr.flirt.build_sig.get_unique_strings(ar_path)
```

For Linux libraries, this method requires `ar` (from `binutils`), `nm` (from `binutils`), and `strings`.

Return type

`List[str]`

Parameters

`ar_path` (*str*) –

```
angr.flirt.build_sig.run_pelf(pelf_path, ar_path, output_path)
```

Parameters

- `pelf_path` (*str*) –
- `ar_path` (*str*) –
- `output_path` (*str*) –

```
angr.flirt.build_sig.run_sigmake(sigmake_path, sig_name, pat_path, sig_path)
```

Parameters

- `sigmake_path` (*str*) –
- `sig_name` (*str*) –
- `pat_path` (*str*) –
- `sig_path` (*str*) –

```
angr.flirt.build_sig.process_exc_file(exc_path)
```

We are doing the stupidest thing possible: For each batch of conflicts, we pick the most likely result based on a set of predefined rules.

TODO: Add caller-callee-based de-duplication.

Parameters

`exc_path` (*str*) –

```
angr.flirt.build_sig.main()
```

10.18 Utils

```
angr.utils.looks_like_sql(s)
```

Determine if string `s` looks like an SQL query.

Parameters

`s` (*str*) – The string to detect.

Return type

`bool`

Returns

True if the string looks like an SQL, False otherwise.

`angr.utils.algo.binary_insert(lst, elem, key, lo=0, hi=None)`

Insert an element into a sorted list, and keep the list sorted.

The major difference from `bisect.bisect_left` is that this function supports a `key` method, so user doesn't have to create the key array for each insertion.

Parameters

- **lst** (*list*) – The list. Must be pre-ordered.
- **element** (*object*) – An element to insert into the list.
- **key** (*func*) – A method to get the key for each element in the list.
- **lo** (*int*) – Lower bound of the search.
- **hi** (*int*) – Upper bound of the search.
- **elem** (*Any*) –

Return type

`None`

Returns

`None`

`angr.utils.constants.is_alignment_mask(n)`

`class angr.utils.cowdict.ChainMapCOW(*args, collapse_threshold=None)`

Bases: `ChainMap`

Implements a copy-on-write version of `ChainMap` that supports auto-collapsing.

`__init__(*args, collapse_threshold=None)`

Initialize a `ChainMap` by setting *maps* to the given mappings. If no mappings are provided, a single empty dictionary is used.

`copy()`

New `ChainMap` or subclass with a new copy of `maps[0]` and refs to `maps[1:]`

`clean()`

`class angr.utils.cowdict.DefaultChainMapCOW(*args, default_factory=None, collapse_threshold=None)`

Bases: `ChainMapCOW`

Implements a copy-on-write version of `ChainMap` with default values that supports auto-collapsing.

`__init__(*args, default_factory=None, collapse_threshold=None)`

Initialize a `ChainMap` by setting *maps* to the given mappings. If no mappings are provided, a single empty dictionary is used.

`clean()`

`class angr.utils.dynamic_dictlist.DynamicDictList(max_size=None, content=None)`

Bases: `Generic[VT]`

A list-like container class that internally uses dicts to store values when the number of values is less than the threshold `LIST2DICT_THRESHOLD`. Keys must be ints.

The default thresholds are determined according to experiments described at <https://github.com/angr/angr/pull/3471#issuecomment-1236515950>.

```
__init__(max_size=None, content=None)
```

Parameters

- **max_size** (*int* | *None*) –
- **content** (*DynamicDictList* | *Dict[int, VT]* | *List[VT]* | *None*) –

```
list_content: Optional[List[TypeVar(VT)]]
```

```
max_size
```

```
dict_content: Optional[Dict[int, TypeVar(VT)]]
```

```
real_length()
```

Return type

```
int
```

```
angr.utils.enums_conv.cfg_jumpkind_to_pb(jk)
```

```
angr.utils.enums_conv.func_edge_type_to_pb(jk)
```

```
angr.utils.enums_conv.cfg_jumpkind_from_pb(pb)
```

```
angr.utils.enums_conv.func_edge_type_from_pb(pb)
```

```
angr.utils.env.is_pyinstaller()
```

Detect if we are currently running as a PyInstaller-packaged program.

Return type

```
bool
```

Returns

True if we are running as a PyInstaller-packaged program. False if we are running in Python directly (e.g., development mode).

```
angr.utils.graph.shallow_reverse(g)
```

Make a shallow copy of a directional graph and reverse the edges. This is a workaround to solve the issue that one cannot easily make a shallow reversed copy of a graph in NetworkX 2, since `networkx.reverse(copy=False)` now returns a `GraphView`, and `GraphViews` are always read-only.

Parameters

g (*networkx.DiGraph*) – The graph to reverse.

Return type

```
DiGraph
```

Returns

A new `networkx.DiGraph` that has all nodes and all edges of the original graph, with edges reversed.

```
angr.utils.graph.inverted_idoms(graph)
```

Invert the given graph and generate the immediate dominator tree on the inverted graph. This is useful for computing post-dominators.

Parameters

graph (*DiGraph*) – The graph to invert and generate immediate dominator tree for.

Return type

```
Tuple[DiGraph, Optional[Dict]]
```

Returns

A tuple of the inverted graph and the immediate dominator tree.

`angr.utils.graph.to_acyclic_graph(graph, ordered_nodes=None, loop_heads=None)`

Convert a given DiGraph into an acyclic graph.

Parameters

- **graph** (`DiGraph`) – The graph to convert.
- **ordered_nodes** (`Optional[List]`) – A list of nodes sorted in a topological order.
- **loop_heads** (`Optional[List]`) – A list of known loop head nodes.

Return type

`DiGraph`

Returns

The converted acyclic graph.

`angr.utils.graph.dfs_back_edges(graph, start_node)`

Perform an iterative DFS traversal of the graph, returning back edges.

Parameters

- **graph** – The graph to traverse.
- **start_node** – The node where to start the traversal.

Returns

An iterator of ‘backward’ edges.

`angr.utils.graph.subgraph_between_nodes(graph, source, frontier, include_frontier=False)`

For a directed graph, return a subgraph that includes all nodes going from a source node to a target node.

Parameters

- **graph** (`networkx.DiGraph`) – The directed graph.
- **source** – The source node.
- **frontier** (`list`) – A collection of target nodes.
- **include_frontier** (`bool`) – Should nodes in frontier be included in the subgraph.

Returns

A subgraph.

Return type

`networkx.DiGraph`

`angr.utils.graph.dominates(idom, dominator_node, node)`

`angr.utils.graph.compute_dominance_frontier(graph, domtree)`

Compute a dominance frontier based on the given post-dominator tree.

This implementation is based on figure 2 of paper An Efficient Method of Computing Static Single Assignment Form by Ron Cytron, etc.

Parameters

- **graph** – The graph where we want to compute the dominance frontier.
- **domtree** – The dominator tree

Returns

A dict of dominance frontier

class `angr.utils.graph.TemporaryNode(label)`

Bases: `object`

A temporary node.

Used as the start node and end node in post-dominator tree generation. Also used in some test cases.

`__init__`(*label*)

class `angr.utils.graph.ContainerNode(obj)`

Bases: `object`

A container node.

Only used in dominator tree generation. We did this so we can set the index property without modifying the original object.

`__init__`(*obj*)

index

property `obj`

class `angr.utils.graph.Dominators(graph, entry_node, successors_func=None, reverse=False)`

Bases: `object`

Describes dominators in a graph.

`__init__`(*graph*, *entry_node*, *successors_func*=None, *reverse*=False)

dom: `DiGraph`

class `angr.utils.graph.PostDominators(graph, entry_node, successors_func=None)`

Bases: `Dominators`

Describe post-dominators in a graph.

`__init__`(*graph*, *entry_node*, *successors_func*=None)

property `post_dom`: `DiGraph`

dom: `DiGraph`

class `angr.utils.graph.SCCPlaceholder(scc_id)`

Bases: `object`

Describes a placeholder for strongly-connected-components in a graph.

`__init__`(*scc_id*)

scc_id

class `angr.utils.graph.GraphUtils`

Bases: `object`

A helper class with some static methods and algorithms implemented, that in fact, might take more than just normal CFGs.

static find_merge_points(*function_addr*, *function_endpoints*, *graph*)

Given a local transition graph of a function, find all merge points inside, and then perform a quasi-topological sort of those merge points.

A merge point might be one of the following cases: - two or more paths come together, and ends at the same address. - end of the current function

Parameters

- **function_addr** (*int*) – Address of the function.
- **function_endpoints** (*list*) – Endpoints of the function. They typically come from `Function.endpoints`.
- **graph** (*networkx.DiGraph*) – A local transition graph of a function. Normally it comes from `Function.graph`.

Returns

A list of ordered addresses of merge points.

Return type

list

static find_widening_points(*function_addr*, *function_endpoints*, *graph*)

Given a local transition graph of a function, find all widening points inside.

Correctly choosing widening points is very important in order to not lose too much information during static analysis. We mainly consider merge points that has at least one loop back edges coming in as widening points.

Parameters

- **function_addr** (*int*) – Address of the function.
- **function_endpoints** (*list*) – Endpoints of the function, typically coming from `Function.endpoints`.
- **graph** (*networkx.DiGraph*) – A local transition graph of a function, normally `Function.graph`.

Returns

A list of addresses of widening points.

Return type

list

static reverse_post_order_sort_nodes(*graph*, *nodes=None*)

Sort a given set of nodes in reverse post ordering.

Parameters

- **graph** (*networkx.DiGraph*) – A local transition graph of a function.
- **nodes** (*iterable*) – A collection of nodes to sort.

Returns

A list of sorted nodes.

Return type

list

static `quasi_topological_sort_nodes`(*graph*, *nodes=None*, *loop_heads=None*)

Sort a given set of nodes from a graph based on the following rules:

- if $A \rightarrow B$ and not $B \rightarrow A$, then we have $A < B$ # - if $A \rightarrow B$ and $B \rightarrow A$, then the ordering is undefined

Following the above rules gives us a quasi-topological sorting of nodes in the graph. It also works for cyclic graphs.

Parameters

- **graph** (*DiGraph*) – A local transition graph of the function.
- **nodes** (*Optional[List]*) – A list of nodes to sort. None if you want to sort all nodes inside the graph.
- **loop_heads** (*Optional[List]*) – A list of nodes that should be treated loop heads.

Return type

List

Returns

A list of ordered nodes.

`angr.utils.lazy_import.lazy_import`(*name*)

`angr.utils.loader.is_pc`(*project*, *ins_addr*, *addr*)

Check if the given address is program counter (PC) or not. This function is for handling the case on some bizarre architectures where PC is always the currently executed instruction address plus a constant value.

Parameters

- **project** (*Project*) – An angr Project instance.
- **ins_addr** (*int*) – The address of an instruction. We calculate PC using this instruction address.
- **addr** (*int*) – The address to check against.

Return type

bool

Returns

True if the given instruction address is the PC, False otherwise.

`angr.utils.loader.is_in_readonly_section`(*project*, *addr*)

Check if the specified address is inside a read-only section.

Parameters

- **project** (*Project*) – An angr Project instance.
- **addr** (*int*) – The address to check.

Return type

bool

Returns

True if the given address belongs to a read-only section, False otherwise.

`angr.utils.loader.is_in_readonly_segment`(*project*, *addr*)

Check if the specified address is inside a read-only segment.

Parameters

- **project** (*Project*) – An angr Project instance.

- **addr** (*int*) – The address to check.

Return type

bool

Returns

True if the given address belongs to a read-only segment, False otherwise.

`angr.utils.library.get_function_name(s)`

Get the function name from a C-style function declaration string.

Parameters

s (*str*) – A C-style function declaration string.

Returns

The function name.

Return type

str

`angr.utils.library.register_kernel_types()`

`angr.utils.library.convert_cproto_to_py(c_decl)`

Convert a C-style function declaration string to its corresponding SimTypes-based Python representation.

Parameters

c_decl (*str*) – The C-style function declaration string.

Return type

Tuple[str, SimTypeFunction, str]

Returns

A tuple of the function name, the prototype, and a string representing the SimType-based Python representation.

`angr.utils.library.convert_cppproto_to_py(cpp_decl, with_param_names=False)`

Pre-process a C++-style function declaration string to its corresponding SimTypes-based Python representation.

Parameters

- **cpp_decl** (*str*) – The C++-style function declaration string.
- **with_param_names** (*bool*) –

Return type

Tuple[Optional[str], Optional[SimTypeCppFunction], Optional[str]]

Returns

A tuple of the function name, the prototype, and a string representing the SimType-based Python representation.

`angr.utils.library.parsedcprotos2py(parsed_cprotos, fd_spots=frozenset({}), remove_sys_prefix=False)`

Parse a list of C function declarations and output to Python code that can be embedded into `angr.procedures.definitions`.

```
>>> # parse the list of glibc C prototypes and output to a file
>>> from angr.procedures.definitions import glibc
>>> with open("glibc_protos", "w") as f: f.write(cprotos2py(glibc._libc_c_decls))
```

Parameters

parsed_cprotos (*List[Tuple[str, SimTypeFunction, str]]*) – A list of tuples where each tuple is (function name, parsed C function prototype, the original function declaration).

Return type

`str`

Returns

A Python string.

`angr.utils.library.cprotos2py(cprotos, fd_spots=frozenset({}), remove_sys_prefix=False)`

Parse a list of C function declarations and output to Python code that can be embedded into `angr.procedures.definitions`.

```
>>> # parse the list of glibc C prototypes and output to a file
>>> from angr.procedures.definitions import glibc
>>> with open("glibc_protos", "w") as f: f.write(cprotos2py(glibc._libc_c_decls))
```

Parameters

cprotos (`List[str]`) – A list of C prototype strings.

Return type

`str`

Returns

A Python string.

`angr.utils.library.get_cpp_function_name(demangled_name, specialized=True, qualified=True)`

`angr.utils.timing.timethis(func)`

`angr.utils.formatting.setup_terminal()`

Check if we are running in a TTY. If so, make sure the terminal supports ANSI escape sequences. If not, disable colored output. Sets global `ansi_color_enabled` to True if colored output should be enabled by default.

`angr.utils.formatting.ansi_color(s, color)`

Colorize string *s* by wrapping in ANSI escape sequence for given *color*.

This function does not consider whether escape sequences are functional or not; it is up to the caller to determine if its appropriate. Check global `ansi_color_enabled` value in this module.

Return type

`str`

Parameters

- **s** (`str`) –
- **color** (`str` | `None`) –

`angr.utils.formatting.add_edge_to_buffer(buf, ref, start, end, formatter=None, dashed=False, ascii_only=None)`

Draw an edge by adding Unicode box and arrow glyphs to beginning of each line in a list of lines.

Parameters

- **buf** (`Sequence[str]`) – Output buffer, used to render formatted edges.
- **ref** (`Sequence[str]`) – Reference buffer, used to calculate edge depth.
- **start** (`int`) – Start line.
- **end** (`int`) – End line, where arrow points.

- **formatter** (*Optional*[*Callable*[[*str*], *str*]]) – Optional callback function used to format the edge before writing it to output buffer.
- **dashed** (*bool*) – Render edge line dashed instead of solid.
- **ascii_only** (*Optional*[*bool*]) – Render edge using ASCII characters only. If unspecified, guess by stdout encoding.

Returns

class `angr.utils.mp.Closure`(*f*: *Callable*[[...], *None*], *args*: *List*[*Any*], *kwargs*: *Dict*[*str*, *Any*])

Bases: `tuple`

A pickle-able lambda; note that *f*, *args*, and *kwargs* must be pickleable

Parameters

- **f** (*Callable*[[...], *None*]) –
- **args** (*List*[*Any*]) –
- **kwargs** (*Dict*[*str*, *Any*]) –

f: *Callable*[..., *None*]

Alias for field number 0

args: *List*[*Any*]

Alias for field number 1

kwargs: *Dict*[*str*, *Any*]

Alias for field number 2

class `angr.utils.mp.Initializer`(*, *_manual*=*True*)

Bases: `object`

A singleton class with global state used to initialize a multiprocessing.Process

Parameters

- **_manual** (*bool*) –

classmethod `get`()

A wrapper around `init` since this class is a singleton

Return type

Initializer

__init__ (*, *_manual*=*True*)

Parameters

- **_manual** (*bool*) –

register (*f*, **args*, ***kwargs*)

A shortcut for adding Closures as initializers

Return type

None

Parameters

- **f** (*Callable*[[...], *None*]) –
- **args** (*Any*) –
- **kwargs** (*Any*) –

initialize()

Initialize a multiprocessing.Process Set the current global initializer to the same state as this initializer, then calls each initializer

Return type

`None`

`angr.utils.mp.mp_context()`

10.19 Errors

exception `angr.errors.AngrError`

Bases: `Exception`

exception `angr.errors.AngrValueError`

Bases: `AngrError`, `ValueError`

exception `angr.errors.AngrLifterError`

Bases: `AngrError`

exception `angr.errors.AngrExitError`

Bases: `AngrError`

exception `angr.errors.AngrPathError`

Bases: `AngrError`

exception `angr.errors.AngrVaultError`

Bases: `AngrError`

exception `angr.errors.PathUnreachableError`

Bases: `AngrPathError`

exception `angr.errors.SimulationManagerError`

Bases: `AngrError`

exception `angr.errors.AngrInvalidArgumentError`

Bases: `AngrError`

exception `angr.errors.AngrSurveyorError`

Bases: `AngrError`

exception `angr.errors.AngrAnalysisError`

Bases: `AngrError`

exception `angr.errors.AngrBladeError`

Bases: `AngrError`

exception `angr.errors.AngrBladeSimProcError`

Bases: `AngrBladeError`

exception `angr.errors.AngrAnnotatedCFGError`

Bases: `AngrError`

exception `angr.errors.AngrBackwardSlicingError`

Bases: `AngrError`

exception `angr.errors.AngrGirlScoutError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrCallableError`
 Bases: [*AngrSurveyorError*](#)

exception `angr.errors.AngrCallableMultistateError`
 Bases: [*AngrCallableError*](#)

exception `angr.errors.AngrSyscallError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrSimOSError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrAssemblyError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrTypeError`
 Bases: [*AngrError*](#), [*TypeError*](#)

exception `angr.errors.AngrMissingTypeError`
 Bases: [*AngrTypeError*](#)

exception `angr.errors.AngrIncongruencyError`
 Bases: [*AngrAnalysisError*](#)

exception `angr.errors.AngrForwardAnalysisError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrSkipJobNotice`
 Bases: [*AngrForwardAnalysisError*](#)

exception `angr.errors.AngrDelayJobNotice`
 Bases: [*AngrForwardAnalysisError*](#)

exception `angr.errors.AngrJobMergingFailureNotice`
 Bases: [*AngrForwardAnalysisError*](#)

exception `angr.errors.AngrJobWideningFailureNotice`
 Bases: [*AngrForwardAnalysisError*](#)

exception `angr.errors.AngrCFGEError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrVFGError`
 Bases: [*AngrError*](#)

exception `angr.errors.AngrVFGRestartAnalysisNotice`
 Bases: [*AngrVFGError*](#)

exception `angr.errors.AngrDataGraphError`
 Bases: [*AngrAnalysisError*](#)

exception `angr.errors.AngrDDGError`
 Bases: [*AngrAnalysisError*](#)

```

exception angr.errors.AngrLoopAnalysisError
    Bases: AngrAnalysisError

exception angr.errors.AngrExplorationTechniqueError
    Bases: AngrError

exception angr.errors.AngrExplorerError
    Bases: AngrExplorationTechniqueError

exception angr.errors.AngrDirectorError
    Bases: AngrExplorationTechniqueError

exception angr.errors.AngrTracerError
    Bases: AngrExplorationTechniqueError

exception angr.errors.AngrVariableRecoveryError
    Bases: AngrAnalysisError

exception angr.errors.AngrDBError
    Bases: AngrError

exception angr.errors.AngrCorruptDBError
    Bases: AngrDBError

exception angr.errors.AngrIncompatibleDBError
    Bases: AngrDBError

exception angr.errors.TracerEnvironmentError
    Bases: AngrError

exception angr.errors.SimError
    Bases: Exception

    bbl_addr = None

    stmt_idx = None

    ins_addr = None

    executed_instruction_count = None

    guard = None

    record_state(state)

exception angr.errors.SimStateError
    Bases: SimError

exception angr.errors.SimMergeError
    Bases: SimStateError

exception angr.errors.SimMemoryError
    Bases: SimStateError

exception angr.errors.SimMemoryMissingError(missing_addr, missing_size, *args)
    Bases: SimMemoryError

    __init__(missing_addr, missing_size, *args)
  
```

exception `angr.errors.SimAbstractMemoryError`
 Bases: *SimMemoryError*

exception `angr.errors.SimRegionMapError`
 Bases: *SimMemoryError*

exception `angr.errors.SimMemoryLimitError`
 Bases: *SimMemoryError*

exception `angr.errors.SimMemoryAddressError`
 Bases: *SimMemoryError*

exception `angr.errors.SimFastMemoryError`
 Bases: *SimMemoryError*

exception `angr.errors.SimEventError`
 Bases: *SimStateError*

exception `angr.errors.SimPosixError`
 Bases: *SimStateError*

exception `angr.errors.SimFilesystemError`
 Bases: *SimError*

exception `angr.errors.SimSymbolicFilesystemError`
 Bases: *SimFilesystemError*

exception `angr.errors.SimFileError`
 Bases: *SimMemoryError*, *SimFilesystemError*

exception `angr.errors.SimHeapError`
 Bases: *SimStateError*

exception `angr.errors.SimUnsupportedError`
 Bases: *SimError*

exception `angr.errors.SimSolverError`
 Bases: *SimError*

exception `angr.errors.SimSolverModeError`
 Bases: *SimSolverError*

exception `angr.errors.SimSolverOptionError`
 Bases: *SimSolverError*

exception `angr.errors.SimValueError`
 Bases: *SimSolverError*

exception `angr.errors.SimUnsatError`
 Bases: *SimValueError*

exception `angr.errors.SimOperationError`
 Bases: *SimError*

exception `angr.errors.UnsupportedIROpError`
 Bases: *SimOperationError*, *SimUnsupportedError*

exception `angr.errors.SimExpressionError`
 Bases: *SimError*


```

exception angr.errors.UnsupportedIRExprError
    Bases: SimExpressionError, SimUnsupportedError

exception angr.errors.SimCCallError
    Bases: SimExpressionError

exception angr.errors.UnsupportedCCallError
    Bases: SimCCallError, SimUnsupportedError

exception angr.errors.SimUninitializedAccessError(expr_type, expr)
    Bases: SimExpressionError
    __init__(expr_type, expr)

exception angr.errors.SimStatementError
    Bases: SimError

exception angr.errors.UnsupportedIRStmtError
    Bases: SimStatementError, SimUnsupportedError

exception angr.errors.UnsupportedDirtyError
    Bases: UnsupportedIRStmtError, SimUnsupportedError

exception angr.errors.SimMissingTempError
    Bases: SimValueError, IndexError

exception angr.errors.SimEngineError
    Bases: SimError

exception angr.errors.SimIRSBBError
    Bases: SimEngineError

exception angr.errors.SimTranslationError
    Bases: SimEngineError

exception angr.errors.SimProcedureError
    Bases: SimEngineError

exception angr.errors.SimProcedureArgumentError
    Bases: SimProcedureError

exception angr.errors.SimShadowStackError
    Bases: SimProcedureError

exception angr.errors.SimFastPathError
    Bases: SimEngineError

exception angr.errors.SimIRSBNNoDecodeError
    Bases: SimIRSBBError

exception angr.errors.AngrUnsupportedSyscallError
    Bases: AngrSyscallError, SimProcedureError, SimUnsupportedError

exception angr.errors.UnsupportedSyscallError
    alias of AngrUnsupportedSyscallError

exception angr.errors.SimReliftException(state)
    Bases: SimEngineError

```

```

    __init__(state)

exception angr.errors.SimSlicerError
    Bases: SimError

exception angr.errors.SimActionError
    Bases: SimError

exception angr.errors.SimCCError
    Bases: SimError

exception angr.errors.SimUCManagerError
    Bases: SimError

exception angr.errors.SimUCManagerAllocationError
    Bases: SimUCManagerError

exception angr.errors.SimUnicornUnsupport
    Bases: SimError

exception angr.errors.SimUnicornError
    Bases: SimError

exception angr.errors.SimUnicornSymbolic
    Bases: SimError

exception angr.errors.SimEmptyCallStackError
    Bases: SimError

exception angr.errors.SimStateOptionsError
    Bases: SimError

exception angr.errors.SimException
    Bases: SimError

exception angr.errors.SimSegfaultException(addr, reason, original_addr=None)
    Bases: SimException, SimMemoryError
    __init__(addr, reason, original_addr=None)

angr.errors.SimSegfaultError
    alias of SimSegfaultException

exception angr.errors.SimZeroDivisionException
    Bases: SimException, SimOperationError

exception angr.errors.AngrNoPluginError
    Bases: AngrError

exception angr.errors.SimConcreteMemoryError
    Bases: AngrError

exception angr.errors.SimConcreteRegisterError
    Bases: AngrError

exception angr.errors.SimConcreteBreakpointError
    Bases: AngrError

exception angr.errors.UnsupportedNodeTypeError
    Bases: AngrError, NotImplementedError

```

10.20 Distributed analysis

```
class angr.distributed.server.Server(project, spill_yard=None, db=None, max_workers=None,
                                     max_states=10, staging_max=10, bucketizer=True,
                                     recursion_limit=1000, worker_exit_callback=None,
                                     techniques=None, add_options=None, remove_options=None)
```

Bases: `object`

Server implements the analysis server with a series of control interfaces exposed.

Variables

- **project** – An instance of `angr.Project`.
- **spill_yard** (*str*) – A directory to store spilled states.
- **db** (*str*) – Path of the database that stores information about spilled states.
- **max_workers** (*int*) – Maximum number of workers. Each worker starts a new process.
- **max_states** (*int*) – Maximum number of active states for each worker.
- **staging_max** (*int*) – Maximum number of inactive states that are kept into memory before spilled onto the disk and potentially be picked up by another worker.
- **bucketizer** (*bool*) – Use the Bucketizer exploration strategy.
- **_worker_exit_callback** – A method that will be called upon the exit of each worker.

```
__init__(project, spill_yard=None, db=None, max_workers=None, max_states=10, staging_max=10,
          bucketizer=True, recursion_limit=1000, worker_exit_callback=None, techniques=None,
          add_options=None, remove_options=None)
```

```
inc_active_workers()
```

```
dec_active_workers()
```

```
stop()
```

```
property active_workers
```

```
property stopped
```

```
on_worker_exit(worker_id, stashes)
```

```
run()
```

```
class angr.distributed.worker.BadStatesDropper(vault, db)
```

Bases: `ExplorationTechnique`

Dumps and drops states that are not “active”.

```
__init__(vault, db)
```

```
step(simgr, stash='active', **kwargs)
```

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

class `angr.distributed.worker.ExplorationStatusNotifier`(*server_state*)

Bases: `ExplorationTechnique`

Force the exploration to stop if the server.stop is True.

Parameters

server_state (*Dict*) –

__init__(*server_state*)

Parameters

server_state (*Dict*) –

step(*simgr*, *stash*='active', ***kwargs*)

Hook the process of stepping a stash forward. Should call `simgr.step(stash, **kwargs)` in order to do the actual processing.

Parameters

- **simgr** (`angr.SimulationManager`) –
- **stash** (*str*) –

class `angr.distributed.worker.Worker`(*worker_id*, *server*, *server_state*, *recursion_limit*=None, *techniques*=None, *add_options*=None, *remove_options*=None)

Bases: `object`

Worker implements a worker thread/process for conducting a task.

__init__(*worker_id*, *server*, *server_state*, *recursion_limit*=None, *techniques*=None, *add_options*=None, *remove_options*=None)

start()

run(*initializer*)

Parameters

initializer (`Initializer`) –

INDICES AND TABLES

- `genindex`
- `modindex`
- `search`

PYTHON MODULE INDEX

a

an`gr`, 157
an`gr`.an`alys`es, 623
an`gr`.an`alys`es.an`alys`is, 623
an`gr`.an`alys`es.back`ward`_s`lice`, 631
an`gr`.an`alys`es.bi`nary`_o`ptim`izer, 869
an`gr`.an`alys`es.bi`ndiff`, 633
an`gr`.an`alys`es.bo`y`sco`ut`, 636
an`gr`.an`alys`es.ca`llee`_c`lean`u`p`_f`inder`, 870
an`gr`.an`alys`es.ca`lling`_c`on`ve`n`tion, 636
an`gr`.an`alys`es.c`dg`, 675
an`gr`.an`alys`es.c`fg`, 641
an`gr`.an`alys`es.c`fg`.c`fb`, 641
an`gr`.an`alys`es.c`fg`.c`fg`, 642
an`gr`.an`alys`es.c`fg`.c`fg`_a`rch`_o`ptions`, 660
an`gr`.an`alys`es.c`fg`.c`fg`_b`ase`, 649
an`gr`.an`alys`es.c`fg`.c`fg`_e`m`u`lated`, 644
an`gr`.an`alys`es.c`fg`.c`fg`_f`ast`, 651
an`gr`.an`alys`es.c`fg`.c`fg`_f`ast`_s`oot`, 673
an`gr`.an`alys`es.c`fg`.c`fg`_j`ob`_b`ase`, 660
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers, 673
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.a`md64`_e`lf`_g`ot`, 661
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.a`rm`_e`lf`_f`ast`, 662
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.c`on`s`t`_r`es`o`l`ver, 671
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.d`e`f`au`l`t`_r`es`o`l`vers, 666
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.j`ump`t`able`, 666
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.m`ips`_e`lf`_f`ast`, 664
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.r`es`o`l`ver, 672
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.x`86`_e`lf`_p`ic`_p`lt`, 665
an`gr`.an`alys`es.c`fg`.i`ndirect`_j`ump`_r`es`o`l`vers.x`86`_p`e`_i`at`, 663
an`gr`.an`alys`es.c`fg`_s`lice`_to_`sink`, 818
an`gr`.an`alys`es.c`fg`_s`lice`_to_`sink`.c`fg`_s`lice`_to_`sink`, 818
an`gr`.an`alys`es.c`fg`_s`lice`_to_`sink`.g`raph`, 819
an`gr`.an`alys`es.c`fg`_s`lice`_to_`sink`.t`rans`i`ti`o`ns`, 820
an`gr`.an`alys`es.c`lass`_i`dent`i`f`i`e`r, 855
an`gr`.an`alys`es.c`ode`_t`ag`g`i`ng, 675
an`gr`.an`alys`es.c`om`p`lete`_c`alling`_c`on`ve`n`ti`o`ns, 638
an`gr`.an`alys`es.c`ong`ru`ency`_c`heck`, 868
an`gr`.an`alys`es.d`ata`_d`ep`, 879
an`gr`.an`alys`es.d`ata`_d`ep`.d`ata`_d`ep`en`d`e`n`c`y`_a`n`a`l`y`s`i`s`, 875
an`gr`.an`alys`es.d`ata`_d`ep`.d`ep`_n`odes`, 877
an`gr`.an`alys`es.d`ata`_d`ep`.s`i`m_`act`_l`oc`a`ti`o`n`, 876
an`gr`.an`alys`es.d`at`a`g`r`a`p`h`_m`e`t`a`, 675
an`gr`.an`alys`es.d`dg`, 748
an`gr`.an`alys`es.d`ecom`p`i`l`e`r, 693
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.a`il`_s`i`m`p`l`i`f`i`e`r`, 693
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.a`il`g`r`a`p`h_`w`a`l`k`e`r, 694
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.b`l`o`c`k_`s`i`m`p`l`i`f`i`e`r, 694
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`all`s`i`t`e`_m`a`k`e`r, 695
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`call`_r`e`w`r`i`t`e`r`s, 695
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`call`_r`e`w`r`i`t`e`r`s.a`md64`_c`calls`, 695
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`call`_r`e`w`r`i`t`e`r`s.r`e`w`r`i`t`e`r`_b`a`s`e`, 695
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`lin`i`c`, 696
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.c`on`d`i`t`i`o`n`_p`r`o`cess`o`r`, 698
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.d`ecom`p`i`l`a`t`i`o`n`_c`a`c`h`e, 700
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.d`ecom`p`i`l`a`t`i`o`n`_o`p`t`i`o`n`s, 699
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.d`ecom`p`i`l`e`r, 700
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.e`m`p`t`y_`n`o`d`e_`r`e`m`o`v`e`r`, 701
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.e`x`p`r`e`s`s`i`o`n`_n`a`r`r`o`w`e`r`, 702
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.g`r`a`p`h_`r`e`g`i`o`n, 702
an`gr`.an`alys`es.d`ecom`p`i`l`e`r.j`ump`_t`a`r`g`e`t`_c`ol`l`e`c`t`o`r`, 703

angr.analyses.identifier.identify, 845
 angr.analyses.init_finder, 870
 angr.analyses.loop_analysis, 846
 angr.analyses.loopfinder, 846
 angr.analyses.propagator, 756
 angr.analyses.propagator.engine_ail, 758
 angr.analyses.propagator.engine_base, 757
 angr.analyses.propagator.engine_vex, 757
 angr.analyses.propagator.outdated_definition_walker, 759
 angr.analyses.propagator.propagator, 760
 angr.analyses.propagator.tmpvar_finder, 760
 angr.analyses.propagator.top_checker_mixin, 761
 angr.analyses.propagator.values, 756
 angr.analyses.propagator.vex_vars, 756
 angr.analyses.proximity_graph, 872
 angr.analyses.reaching_definitions, 761
 angr.analyses.reaching_definitions.call_trace, 793
 angr.analyses.reaching_definitions.dep_graph, 798
 angr.analyses.reaching_definitions.engine_ail, 818
 angr.analyses.reaching_definitions.engine_vex, 794
 angr.analyses.reaching_definitions.function_handler, 802
 angr.analyses.reaching_definitions.heap_allocator, 801
 angr.analyses.reaching_definitions.rd_state, 809
 angr.analyses.reaching_definitions.reaching_definitions, 795
 angr.analyses.reaching_definitions.subject, 817
 angr.analyses.reassembler, 860
 angr.analyses.soot_class_hierarchy, 640
 angr.analyses.stack_pointer_tracker, 821
 angr.analyses.static_hooker, 868
 angr.analyses.typehoon, 845
 angr.analyses.typehoon.lifter, 832
 angr.analyses.typehoon.simple_solver, 832
 angr.analyses.typehoon.translator, 836
 angr.analyses.typehoon.typeconsts, 843
 angr.analyses.typehoon.typehoon, 842
 angr.analyses.typehoon.typevars, 837
 angr.analyses.variable_recovery, 832
 angr.analyses.variable_recovery.annotations, 823
 angr.analyses.variable_recovery.engine_ail, 831
 angr.analyses.variable_recovery.engine_base, 831
 angr.analyses.variable_recovery.engine_vex, 831
 angr.analyses.variable_recovery.irsb_scanner, 832
 angr.analyses.variable_recovery.variable_recovery, 829
 angr.analyses.variable_recovery.variable_recovery_base, 823
 angr.analyses.variable_recovery.variable_recovery_fast, 827
 angr.analyses.veritesting, 847
 angr.analyses.vfg, 849
 angr.analyses.vsa_ddg, 853
 angr.analyses.vtable, 854
 angr.analyses.xrefs, 871
 angr.angrdb, 676
 angr.angrdb.db, 676
 angr.angrdb.models, 677
 angr.angrdb.serializers, 681
 angr.angrdb.serializers.cfg_model, 681
 angr.angrdb.serializers.comments, 682
 angr.angrdb.serializers.funcs, 682
 angr.angrdb.serializers.kb, 683
 angr.angrdb.serializers.labels, 683
 angr.angrdb.serializers.loader, 683
 angr.angrdb.serializers.structured_code, 685
 angr.angrdb.serializers.variables, 684
 angr.angrdb.serializers.xrefs, 684
 angr.annocfg, 881
 angr.blade, 879
 angr.block, 220
 angr.callable, 521
 angr.config, 881
 angr.concretization_conventions, 484
 angr.code_location, 616
 angr.codenode, 882
 angr.concretization_strategies, 335
 angr.concretization_strategies.any, 381
 angr.concretization_strategies.controlled_data, 381
 angr.concretization_strategies.eval, 379
 angr.concretization_strategies.max, 380
 angr.concretization_strategies.nonzero, 381
 angr.concretization_strategies.nonzero_range, 380
 angr.concretization_strategies.norepeats, 379
 angr.concretization_strategies.norepeats_range, 381
 angr.concretization_strategies.range, 380
 angr.concretization_strategies.single, 379
 angr.concretization_strategies.solutions, 379
 angr.concretization_strategies.unlimited_range, 382
 angr.distributed, 909
 angr.distributed.server, 909

angr.distributed.worker, 909
 angr.engines, 427
 angr.engines.concrete, 433
 angr.engines.engine, 428
 angr.engines.failure, 431
 angr.engines.hook, 431
 angr.engines.light, 755
 angr.engines.light.data, 754
 angr.engines.light.engine, 755
 angr.engines.pcode, 434
 angr.engines.pcode.behavior, 445
 angr.engines.pcode.cc, 464
 angr.engines.pcode.emulate, 445
 angr.engines.pcode.engine, 434
 angr.engines.pcode.lifter, 435
 angr.engines.procedure, 430
 angr.engines.soot, 432
 angr.engines.soot.engine, 432
 angr.engines.successors, 429
 angr.engines.syscall, 431
 angr.engines.unicorn, 432
 angr.engines.vex, 432
 angr.errors, 903
 angr.exploration_techniques, 390
 angr.exploration_techniques.bucketizer, 427
 angr.exploration_techniques.common, 425
 angr.exploration_techniques.dfs, 408
 angr.exploration_techniques.director, 418
 angr.exploration_techniques.driller_core, 416
 angr.exploration_techniques.explorer, 408
 angr.exploration_techniques.lengthlimiter, 410
 angr.exploration_techniques.local_loop_seer, 422
 angr.exploration_techniques.loop_seer, 421
 angr.exploration_techniques.manual_mergepoint, 410
 angr.exploration_techniques.memory_watcher, 426
 angr.exploration_techniques.oppologist, 421
 angr.exploration_techniques.slicecutor, 417
 angr.exploration_techniques.spiller, 410
 angr.exploration_techniques.spiller_db, 413
 angr.exploration_techniques.stochastic, 423
 angr.exploration_techniques.suggestions, 427
 angr.exploration_techniques.symbion, 425
 angr.exploration_techniques.tech_builder, 424
 angr.exploration_techniques.threading, 413
 angr.exploration_techniques.timeout, 408
 angr.exploration_techniques.tracer, 414
 angr.exploration_techniques.unique, 423
 angr.exploration_techniques.veritesting, 413
 angr.factory, 216
 angr.flirt, 892
 angr.flirt.build_sig, 892
 angr.keyed_region, 617
 angr.knowledge_base, 523
 angr.knowledge_base.knowledge_base, 523
 angr.knowledge_plugins, 524
 angr.knowledge_plugins.callsite_prototypes, 525
 angr.knowledge_plugins.cfg, 526
 angr.knowledge_plugins.cfg.cfg_manager, 547
 angr.knowledge_plugins.cfg.cfg_model, 539
 angr.knowledge_plugins.cfg.cfg_node, 547
 angr.knowledge_plugins.cfg.indirect_jump, 550
 angr.knowledge_plugins.cfg.memory_data, 545
 angr.knowledge_plugins.comments, 552
 angr.knowledge_plugins.data, 552
 angr.knowledge_plugins.debug_variables, 572
 angr.knowledge_plugins.functions, 553
 angr.knowledge_plugins.functions.function, 555
 angr.knowledge_plugins.functions.function_manager, 553
 angr.knowledge_plugins.functions.function_parser, 563
 angr.knowledge_plugins.functions.soot_function, 563
 angr.knowledge_plugins.indirect_jumps, 552
 angr.knowledge_plugins.key_definitions, 574
 angr.knowledge_plugins.key_definitions.atoms, 588
 angr.knowledge_plugins.key_definitions.constants, 592
 angr.knowledge_plugins.key_definitions.definition, 592
 angr.knowledge_plugins.key_definitions.environment, 594
 angr.knowledge_plugins.key_definitions.heap_address, 595
 angr.knowledge_plugins.key_definitions.key_definition_manager, 596
 angr.knowledge_plugins.key_definitions.live_definitions, 596
 angr.knowledge_plugins.key_definitions.rd_model, 606
 angr.knowledge_plugins.key_definitions.tag, 608
 angr.knowledge_plugins.key_definitions.undefined, 609
 angr.knowledge_plugins.key_definitions.unknown_size, 610
 angr.knowledge_plugins.key_definitions.uses, 610
 angr.knowledge_plugins.labels, 552
 angr.knowledge_plugins.patches, 524
 angr.knowledge_plugins.plugin, 525

angr.knowledge_plugins.propagations, 552
 angr.knowledge_plugins.structured_code, 574
 angr.knowledge_plugins.structured_code.manager, 574
 angr.knowledge_plugins.sync, 612
 angr.knowledge_plugins.sync.sync_controller, 612
 angr.knowledge_plugins.types, 551
 angr.knowledge_plugins.variables, 564
 angr.knowledge_plugins.variables.variable_access, 564
 angr.knowledge_plugins.variables.variable_manager, 565
 angr.knowledge_plugins.xrefs, 614
 angr.knowledge_plugins.xrefs.xref, 614
 angr.knowledge_plugins.xrefs.xref_manager, 615
 angr.knowledge_plugins.xrefs.xref_types, 615
 angr.misc.plugins, 222
 angr.procedures, 474
 angr.procedures.definitions, 476
 angr.procedures.stubs.format_parser, 474
 angr.project, 212
 angr.protos, 621
 angr.serializable, 620
 angr.sim_manager, 382
 angr.sim_options, 228
 angr.sim_procedure, 469
 angr.sim_state, 224
 angr.sim_state_options, 228
 angr.sim_type, 509
 angr.sim_variable, 504
 angr.simos, 884
 angr.simos.cgc, 887
 angr.simos.javavm, 890
 angr.simos.linux, 886
 angr.simos.simos, 884
 angr.simos.userland, 887
 angr.simos.windows, 888
 angr.slicer, 880
 angr.state_hierarchy, 389
 angr.state_plugins, 231
 angr.state_plugins.callstack, 263
 angr.state_plugins.cgc, 271
 angr.state_plugins.concrete, 292
 angr.state_plugins.debug_variables, 307
 angr.state_plugins.filesystem, 248
 angr.state_plugins.gdb, 270
 angr.state_plugins.globals, 278
 angr.state_plugins.heap, 297
 angr.state_plugins.heap.heap_base, 297
 angr.state_plugins.heap.heap_brk, 298
 angr.state_plugins.heap.heap_freelist, 300
 angr.state_plugins.heap.heap_libc, 301
 angr.state_plugins.heap.heap_ptmalloc, 302
 angr.state_plugins.heap.utils, 306
 angr.state_plugins.history, 267
 angr.state_plugins.inspect, 233
 angr.state_plugins.javavm_classloader, 294
 angr.state_plugins.jni_references, 296
 angr.state_plugins.libc, 236
 angr.state_plugins.light_registers, 266
 angr.state_plugins.log, 262
 angr.state_plugins.loop_data, 291
 angr.state_plugins.plugin, 231
 angr.state_plugins.posix, 240
 angr.state_plugins.preconstrainer, 282
 angr.state_plugins.scratch, 280
 angr.state_plugins.sim_action, 467
 angr.state_plugins.sim_action_object, 468
 angr.state_plugins.sim_event, 469
 angr.state_plugins.solver, 254
 angr.state_plugins.symbolizer, 307
 angr.state_plugins.trace_additions, 273
 angr.state_plugins.uc_manager, 279
 angr.state_plugins.unicorn_engine, 284
 angr.state_plugins.view, 309
 angr.storage, 309
 angr.storage.file, 314
 angr.storage.memory_mixins, 336
 angr.storage.memory_mixins.actions_mixin, 342
 angr.storage.memory_mixins.address_concretization_mixin, 344
 angr.storage.memory_mixins.bvv_conversion_mixin, 341
 angr.storage.memory_mixins.clouseau_mixin, 346
 angr.storage.memory_mixins.conditional_store_mixin, 346
 angr.storage.memory_mixins.convenient_mappings_mixin, 348
 angr.storage.memory_mixins.default_filler_mixin, 340
 angr.storage.memory_mixins.dirty_addrs_mixin, 344
 angr.storage.memory_mixins.hex_dumper_mixin, 341
 angr.storage.memory_mixins.javavm_memory, 376
 angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin, 376
 angr.storage.memory_mixins.keyvalue_memory, 375
 angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixin, 375
 angr.storage.memory_mixins.label_merger_mixin, 347
 angr.storage.memory_mixins.multi_value_merger_mixin, 352

angr.storage.memory_mixins.name_resolution_mixin, 343
 angr.storage.memory_mixins.slotted_memory, 339
 angr.storage.memory_mixins.paged_memory, 353
 angr.storage.memory_mixins.paged_memory.page_backends, 374
 angr.storage.memory_mixins.paged_memory.paged_memory_mixin, 340
 angr.storage.memory_mixins.paged_memory.paged_memory_mixin.memory_mixins.symbolic_merger_mixin, 343
 angr.storage.memory_mixins.paged_memory.pages, 359
 angr.storage.memory_mixins.paged_memory.pages.composition, 352
 angr.storage.memory_mixins.paged_memory.pages.composition.memory_mixins.underconstrained_mixin, 342
 angr.storage.memory_mixins.paged_memory.pages.history_storage_mixin, 347
 angr.storage.memory_mixins.paged_memory.pages.isomorphic_memory_object, 334
 angr.storage.pcap, 335
 angr.storage.pcap.list_files, 893
 angr.storage.pcap.list_files, 362
 angr.storage.pcap.list_files.constants, 894
 angr.storage.pcap.list_files.constants, 350
 angr.storage.pcap.list_files.constants, 894
 angr.storage.pcap.list_files.constants, 348
 angr.storage.pcap.list_files.constants, 895
 angr.storage.pcap.list_files.constants, 360
 angr.storage.pcap.list_files.constants, 895
 angr.storage.pcap.list_files.constants, 899
 angr.storage.pcap.list_files.constants, 900
 angr.storage.pcap.list_files.constants, 899
 angr.storage.pcap.list_files.constants, 902
 angr.storage.pcap.list_files.constants, 901
 angr.storage.pcap.list_files.constants, 358
 angr.storage.pcap.list_files.constants, 365
 angr.storage.pcap.list_files.constants, 371
 angr.storage.pcap.list_files.constants, 373
 angr.storage.pcap.list_files.constants, 370
 angr.storage.pcap.list_files.constants, 368
 angr.storage.pcap.list_files.constants, 371
 angr.storage.pcap.list_files.constants, 373
 angr.storage.pcap.list_files.constants, 365
 angr.storage.pcap.list_files.constants, 371
 angr.storage.pcap.list_files.constants, 342
 angr.storage.pcap.list_files.constants, 347
 angr.storage.pcap.list_files.constants, 347

Symbols

`__init__()` (*anqr.BP* method), 161
`__init__()` (*anqr.Blade* method), 167
`__init__()` (*anqr.Block* method), 170
`__init__()` (*anqr.ExplorationTechnique* method), 178
`__init__()` (*anqr.KnowledgeBase* method), 211
`__init__()` (*anqr.PTChunk* method), 209
`__init__()` (*anqr.PointerWrapper* method), 184
`__init__()` (*anqr.Project* method), 164
`__init__()` (*anqr.Server* method), 210
`__init__()` (*anqr.SimCC* method), 185
`__init__()` (*anqr.SimCC.ArgSession* method), 186
`__init__()` (*anqr.SimFile* method), 190
`__init__()` (*anqr.SimFileBase* method), 189
`__init__()` (*anqr.SimFileDescriptor* method), 198
`__init__()` (*anqr.SimFileDescriptorDuplex* method), 200
`__init__()` (*anqr.SimFileStream* method), 194
`__init__()` (*anqr.SimHeapBrk* method), 204
`__init__()` (*anqr.SimHeapPTMalloc* method), 206
`__init__()` (*anqr.SimHostFilesystem* method), 204
`__init__()` (*anqr.SimOS* method), 168
`__init__()` (*anqr.SimPackets* method), 192
`__init__()` (*anqr.SimPacketsStream* method), 196
`__init__()` (*anqr.SimProcedure* method), 159
`__init__()` (*anqr.SimState* method), 182
`__init__()` (*anqr.SimStatePlugin* method), 161
`__init__()` (*anqr.SimulationManager* method), 172
`__init__()` (*anqr.StateHierarchy* method), 180
`__init__()` (*anqr.analyses.analysis.AnalysesHub* method), 623
`__init__()` (*anqr.analyses.analysis.AnalysisFactory* method), 624
`__init__()` (*anqr.analyses.analysis.AnalysisLogEntry* method), 623
`__init__()` (*anqr.analyses.analysis.KnownAnalysesPlugin* method), 624
`__init__()` (*anqr.analyses.backward_slice.BackwardSlice* method), 632
`__init__()` (*anqr.analyses.binary_optimizer.BinaryOptimizer* method), 870
`__init__()` (*anqr.analyses.binary_optimizer.ConstantPropagation* method), 869
`__init__()` (*anqr.analyses.binary_optimizer.DeadAssignment* method), 869
`__init__()` (*anqr.analyses.binary_optimizer.RedundantStackVariable* method), 869
`__init__()` (*anqr.analyses.binary_optimizer.RegisterReallocation* method), 869
`__init__()` (*anqr.analyses.bindiff.BinDiff* method), 635
`__init__()` (*anqr.analyses.bindiff.ConstantChange* method), 633
`__init__()` (*anqr.analyses.bindiff.Difference* method), 633
`__init__()` (*anqr.analyses.bindiff.FunctionDiff* method), 634
`__init__()` (*anqr.analyses.bindiff.NormalizedBlock* method), 634
`__init__()` (*anqr.analyses.bindiff.NormalizedFunction* method), 634
`__init__()` (*anqr.analyses.boyscout.BoyScout* method), 636
`__init__()` (*anqr.analyses.callee_cleanup_finder.CalleeCleanupFinder* method), 870
`__init__()` (*anqr.analyses.calling_convention.CallSiteFact* method), 637
`__init__()` (*anqr.analyses.calling_convention.CallingConventionAnalysis* method), 637
`__init__()` (*anqr.analyses.cdg.CDG* method), 675
`__init__()` (*anqr.analyses.cfg.cfb.CFBlanket* method), 641
`__init__()` (*anqr.analyses.cfg.cfb.CFBlanketView* method), 641
`__init__()` (*anqr.analyses.cfg.cfb.MemoryRegion* method), 641
`__init__()` (*anqr.analyses.cfg.cfb.Unknown* method), 641
`__init__()` (*anqr.analyses.cfg.cfb.CFG* method), 642
`__init__()` (*anqr.analyses.cfg.cfb_arch_options.CFGArchOptions* method), 660
`__init__()` (*anqr.analyses.cfg.cfb_base.CFGBase* method), 649
`__init__()` (*anqr.analyses.cfg.cfb_emulated.CFGEmlated* method), 645

<code>__init__()</code> (<code>angr.analyses.cfg.cfg_emulated.CFGJob</code> method), 644	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.RegOffs</code> method), 668
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_emulated.PendingJob</code> method), 644	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.Register</code> method), 669
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.CFGFast</code> method), 657	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.Tmp</code> method), 667
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.CFGJob</code> method), 656	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.Mips</code> method), 664
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.DecodingAssumption</code> method), 652	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.Over</code> method), 664
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.FunctionCallEdge</code> method), 654	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.resolver.IndirectJu</code> method), 672
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.FunctionFakeRetEdge</code> method), 654	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic_plt.X86</code> method), 665
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.FunctionReturn</code> method), 652	<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat.X86Pe</code> method), 663
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.FunctionReturnEdge</code> method), 655	<code>__init__()</code> (<code>angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceT</code> method), 818
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.FunctionTransitionEdge</code> method), 654	<code>__init__()</code> (<code>angr.analyses.class_identifier.ClassIdentifier</code> method), 855
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast.PendingJobs</code> method), 653	<code>__init__()</code> (<code>angr.analyses.code_tagging.CodeTagging</code> method), 676
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_fast_soot.CFGFastSoot</code> method), 673	<code>__init__()</code> (<code>angr.analyses.complete_calling_conventions.CompleteCallin</code> method), 639
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_job_base.BlockID</code> method), 660	<code>__init__()</code> (<code>angr.analyses.congruency_check.CongruencyCheck</code> method), 868
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_job_base.CFGJobBase</code> method), 661	<code>__init__()</code> (<code>angr.analyses.data_dep.data_dependency_analysis.DataDep</code> method), 875
<code>__init__()</code> (<code>angr.analyses.cfg.cfg_job_base.FunctionKey</code> method), 661	<code>__init__()</code> (<code>angr.analyses.data_dep.data_dependency_analysis.NodalAnr</code> method), 875
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got.AMD64ElfGotResolv</code> method), 661	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.BaseDepNode</code> method), 877
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast.ArmElfFastResolver</code> method), 662	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.ConstantDepNode</code> method), 877
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.constant_resolver.ConstantResolver</code> method), 671	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.MemDepNode</code> method), 878
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddDescriptorToFastBase</code> method), 666	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.RegDepNode</code> method), 879
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.BSSHook</code> method), 669	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.TmpDepNode</code> method), 879
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToAnyValueMessage</code> method), 667	<code>__init__()</code> (<code>angr.analyses.data_dep.dep_nodes.VarDepNode</code> method), 878
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToProcessWord</code> method), 669	<code>__init__()</code> (<code>angr.data_dep.sim_act_location.ParsedInstruction</code> method), 876
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToProcessWordState</code> method), 668	<code>__init__()</code> (<code>angr.data_dep.sim_act_location.SimActLocation</code> method), 876
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToResolver</code> method), 670	<code>__init__()</code> (<code>angr.datagraph_meta.DataGraphMeta</code> method), 675
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToTargetBaseAdd</code> method), 667	<code>__init__()</code> (<code>angr.ddg.AST</code> method), 749
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.CallToHook</code> method), 669	<code>__init__()</code> (<code>angr.analyses.ddg.DDG</code> method), 751
<code>__init__()</code> (<code>angr.analyses.cfg.indirect_jump_resolvers.jumptable.MIPSBlock</code> method), 670	<code>__init__()</code> (<code>angr.analyses.ddg.DDGJob</code> method), 749
	<code>__init__()</code> (<code>angr.analyses.ddg.DDGView</code> method), 751
	<code>__init__()</code> (<code>angr.analyses.ddg.DDGViewInstruction</code> method), 751

`__init__` () (angr.analyses.ddg.DDGViewItem method), 751
`__init__` () (angr.analyses.ddg.LiveDefinitions method), 749
`__init__` () (angr.analyses.ddg.ProgramVariable method), 749
`__init__` () (angr.analyses.decompiler.ail_simplifier.AILBlockFinder method), 693
`__init__` () (angr.analyses.decompiler.ail_simplifier.AILSimplifier method), 694
`__init__` () (angr.analyses.decompiler.ailgraph_walker.AILGraphWalker method), 694
`__init__` () (angr.analyses.decompiler.block_simplifier.BlockSimplifier method), 695
`__init__` () (angr.analyses.decompiler.block_simplifier.HasCallExprWalker method), 694
`__init__` () (angr.analyses.decompiler.callsite_maker.CallSiteMaker method), 695
`__init__` () (angr.analyses.decompiler.ccall_rewriters.rewriter_base.CCallRewriterBase method), 695
`__init__` () (angr.analyses.decompiler.clinic.Clinic method), 697
`__init__` () (angr.analyses.decompiler.clinic.DataRefDesc method), 696
`__init__` () (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 698
`__init__` () (angr.analyses.decompiler.decompilation_cache.DecompilationCache method), 700
`__init__` () (angr.analyses.decompiler.decompilation_options.DecompilationOptions method), 699
`__init__` () (angr.analyses.decompiler.decompiler.Decompiler method), 701
`__init__` () (angr.analyses.decompiler.empty_node_remover.EmptyNodeRemover method), 702
`__init__` () (angr.analyses.decompiler.expression_narrower.ExpressionNarrower method), 702
`__init__` () (angr.analyses.decompiler.graph_region.GraphRegion method), 703
`__init__` () (angr.analyses.decompiler.jump_target_collector.JumpTargetCollector method), 703
`__init__` () (angr.analyses.decompiler.jumptable_entry_condition_rewriter.JumpTableEntryConditionRewriter method), 704
`__init__` () (angr.analyses.decompiler.optimization_passes.base_ptr_swap_optimizer.BasePtrSwapOptimizer method), 708
`__init__` () (angr.analyses.decompiler.optimization_passes.constant_defs_block_walker.ConstantDefsBlockWalker method), 704
`__init__` () (angr.analyses.decompiler.optimization_passes.constant_defs_block_walker.ConstantDefsBlockWalker method), 705
`__init__` () (angr.analyses.decompiler.optimization_passes.dominance_optimizer.DominanceOptimizer method), 708
`__init__` () (angr.analyses.decompiler.optimization_passes.engine_base.EngineBase method), 712
`__init__` () (angr.analyses.decompiler.optimization_passes.engine_base.EngineBase method), 712
`__init__` () (angr.analyses.decompiler.optimization_passes.expr_op_swap_optimizer.ExprOpSwapOptimizer method), 713
`__init__` () (angr.analyses.decompiler.optimization_passes.expr_op_swap_optimizer.ExprOpSwapOptimizer method), 712
`__init__` () (angr.analyses.decompiler.optimization_passes.expr_op_swap_optimizer.ExprOpSwapOptimizer method), 713
`__init__` () (angr.analyses.decompiler.optimization_passes.expr_op_swap_optimizer.ExprOpSwapOptimizer method), 712
`__init__` () (angr.analyses.decompiler.optimization_passes.ite_expr_converter.IteExprConverter method), 708
`__init__` () (angr.analyses.decompiler.optimization_passes.ite_expr_converter.IteExprConverter method), 708
`__init__` () (angr.analyses.decompiler.optimization_passes.ite_expr_converter.IteExprConverter method), 709
`__init__` () (angr.analyses.decompiler.optimization_passes.lowered_switch_optimizer.LoweredSwitchOptimizer method), 709
`__init__` () (angr.analyses.decompiler.optimization_passes.lowered_switch_optimizer.LoweredSwitchOptimizer method), 710
`__init__` () (angr.analyses.decompiler.optimization_passes.lowered_switch_optimizer.LoweredSwitchOptimizer method), 710
`__init__` () (angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifier method), 711
`__init__` () (angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifier method), 711
`__init__` () (angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass method), 705
`__init__` () (angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass method), 706
`__init__` () (angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass method), 706
`__init__` () (angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass method), 707
`__init__` () (angr.analyses.decompiler.optimization_passes.register_save_optimizer.RegisterSaveOptimizer method), 714
`__init__` () (angr.analyses.decompiler.optimization_passes.ret_addr_save_optimizer.RetAddrSaveOptimizer method), 714
`__init__` () (angr.analyses.decompiler.optimization_passes.stack_canary_optimizer.StackCanaryOptimizer method), 707
`__init__` () (angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_optimizer.X86GccGetpcOptimizer method), 714
`__init__` () (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase method), 715
`__init__` () (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase method), 715
`__init__` () (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase method), 725
`__init__` () (angr.analyses.decompiler.region_identifier.RegionIdentifier method), 717
`__init__` () (angr.analyses.decompiler.region_simplifiers.cascading_conditions.CascadingConditions method), 717
`__init__` () (angr.analyses.decompiler.region_simplifiers.cascading_ifs.CascadingIfs method), 718

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.base.PositionManager method), 718

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.base.PositionManager method), 719

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CAILBlock method), 719

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CArrayTypeL method), 720

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CAssignment method), 718

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CBinaryOp method), 719

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CBreak method), 719

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CClosingObj method), 719

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CConstant method), 718

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CConstruct method), 720

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CContinue method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CDirtyExpr method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CDoWhileLo method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CExpression method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CFakeVariab method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CForLoop method), 721

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CFunction method), 722

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CFunctionCa method), 724

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CGoto method), 722

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CITE method), 723

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CIfBreak method), 723

`__init__` () (angr.analyses.decompiler.region_simplifiers.expanding_conditional_region_simplifier.decompiler.structured_codegen.c.CIfElse method), 725

`__init__` () (angr.analyses.decompiler.region_walker.RegionWalker) (angr.analyses.decompiler.structured_codegen.c.CIndexedVar method), 725

`__init__` () (angr.analyses.decompiler.sequence_walker.SequenceWalker) (angr.analyses.decompiler.structured_codegen.c.CLabel method), 725

`__init__` () (angr.analyses.decompiler.structured_codegen.base.BaseStructuredCodeGenerator) (angr.analyses.decompiler.structured_codegen.c.CMultiStaten method), 727

`__init__` () (angr.analyses.decompiler.structured_codegen.base.BaseStructuredCodeGenerator) (angr.analyses.decompiler.structured_codegen.c.CRegister method), 726

`__init__` () (angr.analyses.decompiler.structured_codegen.base.BaseStructuredCodeGenerator) (angr.analyses.decompiler.structured_codegen.c.CReturn method), 726

`__init__` () (angr.analyses.forward_analysis.forward_analysis.ForwardAnalysis method), 625
`__init__` () (angr.analyses.forward_analysis.job_info.JobInfo method), 626
`__init__` () (angr.analyses.forward_analysis.visitors.call_graph_visitor.CallGraphVisitor method), 626
`__init__` () (angr.analyses.forward_analysis.visitors.function_info_visitor.FunctionInfoVisitor method), 627
`__init__` () (angr.analyses.forward_analysis.visitors.graph_graph_visitor.GraphGraphVisitor method), 628
`__init__` () (angr.analyses.forward_analysis.visitors.loop_visitor.LoopVisitor method), 630
`__init__` () (angr.analyses.forward_analysis.visitors.single_node_visitor.SingleNodeVisitor method), 631
`__init__` () (angr.analyses.identifier.identify.FuncInfo method), 845
`__init__` () (angr.analyses.identifier.identify.Identifier method), 845
`__init__` () (angr.analyses.init_finder.InitializationFinder method), 871
`__init__` () (angr.analyses.init_finder.SimEngineInitFinderVEX method), 870
`__init__` () (angr.analyses.loop_analysis.AnnotatedVariable method), 846
`__init__` () (angr.analyses.loop_analysis.Condition method), 847
`__init__` () (angr.analyses.loop_analysis.LoopAnalysis method), 847
`__init__` () (angr.analyses.loop_analysis.LoopAnalysisState method), 847
`__init__` () (angr.analyses.loop_analysis.SootBlockProcessor method), 847
`__init__` () (angr.analyses.loopfinder.Loop method), 846
`__init__` () (angr.analyses.loopfinder.LoopFinder method), 846
`__init__` () (angr.analyses.propagator.engine_base.SimEnginePropagator method), 757
`__init__` () (angr.analyses.propagator.outdated_definition_walker.OutdatedDefinitionWalker method), 759
`__init__` () (angr.analyses.propagator.propagator.Propagator method), 760
`__init__` () (angr.analyses.propagator.tmpvar_finder.TmpvarFinder method), 760
`__init__` () (angr.analyses.propagator.values.Top method), 756
`__init__` () (angr.analyses.propagator.vex_vars.VEXMemVar method), 756
`__init__` () (angr.analyses.propagator.vex_vars.VEXReg method), 756
`__init__` () (angr.analyses.propagator.vex_vars.VEXTmp method), 757
`__init__` () (angr.analyses.proximity_graph.BaseProxiNode method), 873
`__init__` () (angr.analyses.proximity_graph.CallProxiNode method), 873
`__init__` () (angr.analyses.proximity_graph.FunctionProxiNode method), 873
`__init__` () (angr.analyses.proximity_graph.IntegerProxiNode method), 874
`__init__` () (angr.analyses.proximity_graph.ProximityGraphAnalysis method), 874
`__init__` () (angr.analyses.proximity_graph.StringProxiNode method), 873
`__init__` () (angr.analyses.proximity_graph.UnknownProxiNode method), 874
`__init__` () (angr.analyses.proximity_graph.VariableProxiNode method), 873
`__init__` () (angr.analyses.reaching_definitions.Atom method), 770
`__init__` () (angr.analyses.reaching_definitions.ConstantSrc method), 774
`__init__` () (angr.analyses.reaching_definitions.Definition method), 774
`__init__` () (angr.analyses.reaching_definitions.FunctionCallData method), 792
`__init__` () (angr.analyses.reaching_definitions.FunctionHandler method), 787
`__init__` () (angr.analyses.reaching_definitions.GuardUse method), 773
`__init__` () (angr.analyses.reaching_definitions.LiveDefinitions method), 762
`__init__` () (angr.analyses.reaching_definitions.MemoryLocation method), 773
`__init__` () (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis method), 775
`__init__` () (angr.analyses.reaching_definitions.ReachingDefinitionsMode method), 778
`__init__` () (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 781
`__init__` () (angr.analyses.reaching_definitions.Register method), 772
`__init__` () (angr.analyses.reaching_definitions.Tmp method), 773
`__init__` () (angr.analyses.reaching_definitions.call_trace.CallSite method), 793
`__init__` () (angr.analyses.reaching_definitions.call_trace.CallTrace method), 794
`__init__` () (angr.analyses.reaching_definitions.dep_graph.DepGraph method), 799
`__init__` () (angr.analyses.reaching_definitions.dep_graph.FunctionCallIR method), 799
`__init__` () (angr.analyses.reaching_definitions.engine_ail.SimEngineRDA method), 818
`__init__` () (angr.analyses.reaching_definitions.engine_vex.SimEngineRD method), 794
`__init__` () (angr.analyses.reaching_definitions.function_handler.Function method), 806

`__init__` () (angr.analyses.reaching_definitions.function_handler.FunctionHandlerWrapper.`__init__` method), 807
`__init__` () (angr.analyses.reaching_definitions.function_handler.FunctionHandlerWrapper.`__init__` method), 807
`__init__` () (angr.analyses.reaching_definitions.function_handler.FunctionHandlerWrapper.`__init__` method), 807
`__init__` () (angr.analyses.reaching_definitions.heap_allocator.HeapAllocator.`__init__` method), 801
`__init__` () (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState.`__init__` method), 810
`__init__` () (angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis.`__init__` method), 796
`__init__` () (angr.analyses.reaching_definitions.subject.Subject.`__init__` method), 817
`__init__` () (angr.analyses.reassembler.BasicBlock.`__init__` method), 862
`__init__` () (angr.analyses.reassembler.Data.`__init__` method), 864
`__init__` () (angr.analyses.reassembler.DataLabel.`__init__` method), 860
`__init__` () (angr.analyses.reassembler.FunctionLabel.`__init__` method), 860
`__init__` () (angr.analyses.reassembler.Instruction.`__init__` method), 862
`__init__` () (angr.analyses.reassembler.Label.`__init__` method), 860
`__init__` () (angr.analyses.reassembler.NotypeLabel.`__init__` method), 861
`__init__` () (angr.analyses.reassembler.ObjectLabel.`__init__` method), 861
`__init__` () (angr.analyses.reassembler.Operand.`__init__` method), 861
`__init__` () (angr.analyses.reassembler.Procedure.`__init__` method), 863
`__init__` () (angr.analyses.reassembler.ProcedureChunk.`__init__` method), 864
`__init__` () (angr.analyses.reassembler.Reassembler.`__init__` method), 865
`__init__` () (angr.analyses.reassembler.Relocation.`__init__` method), 865
`__init__` () (angr.analyses.reassembler.SymbolManager.`__init__` method), 861
`__init__` () (angr.analyses.soot_class_hierarchy.NoConcreteDispatch.`__init__` method), 640
`__init__` () (angr.analyses.soot_class_hierarchy.SootClassHierarchy.`__init__` method), 640
`__init__` () (angr.analyses.soot_class_hierarchy.SootClassHierarchy.`__init__` method), 640
`__init__` () (angr.analyses.stack_pointer_tracker.Constant.`__init__` method), 821
`__init__` () (angr.analyses.stack_pointer_tracker.Eq.`__init__` method), 821
`__init__` () (angr.analyses.stack_pointer_tracker.FrozenStackPointerTracker.`__init__` method), 821
`__init__` () (angr.analyses.typehoon.simple_solver.ConstraintGraphNode.`__init__` method), 834
`__init__` () (angr.analyses.typehoon.simple_solver.RecursiveRefNode.`__init__` method), 833
`__init__` () (angr.analyses.typehoon.simple_solver.SimpleSolver.`__init__` method), 835
`__init__` () (angr.analyses.typehoon.simple_solver.Sketch.`__init__` method), 833
`__init__` () (angr.analyses.typehoon.simple_solver.SketchNode.`__init__` method), 832
`__init__` () (angr.analyses.typehoon.translator.SimTypeTempRef.`__init__` method), 836
`__init__` () (angr.analyses.typehoon.translator.TypeTranslator.`__init__` method), 837
`__init__` () (angr.analyses.typehoon.typeconsts.Array.`__init__` method), 844
`__init__` () (angr.analyses.typehoon.typeconsts.Function.`__init__` method), 845
`__init__` () (angr.analyses.typehoon.typeconsts.Pointer.`__init__` method), 844
`__init__` () (angr.analyses.typehoon.typeconsts.Pointer32.`__init__` method), 844
`__init__` () (angr.analyses.typehoon.typeconsts.Pointer64.`__init__` method), 844
`__init__` () (angr.analyses.typehoon.typeconsts.Struct.`__init__` method), 844
`__init__` () (angr.analyses.typehoon.typeconsts.TypeVariableReference.`__init__` method), 845
`__init__` () (angr.analyses.typehoon.typehoon.Typehoon.`__init__` method), 842
`__init__` () (angr.analyses.typehoon.typevars.Add.`__init__` method), 838
`__init__` () (angr.analyses.typehoon.typevars.AddN.`__init__` method), 841
`__init__` () (angr.analyses.typehoon.typevars.ConvertTo.`__init__` method), 841
`__init__` () (angr.analyses.typehoon.typevars.DerivedTypeVariable.`__init__` method), 840
`__init__` () (angr.analyses.typehoon.typevars.Equivalence.`__init__` method), 837
`__init__` () (angr.analyses.typehoon.typevars.Existence.`__init__` method), 838

- `method`), 485
- `__init__()` (`angr.calling_conventions.SerializableListIterator` `method`), 485
- `__init__()` (`angr.calling_conventions.SimArrayArg` `method`), 488
- `__init__()` (`angr.calling_conventions.SimCC` `method`), 489
- `__init__()` (`angr.calling_conventions.SimCC.ArgSession` `method`), 490
- `__init__()` (`angr.calling_conventions.SimCC.Usercall` `method`), 492
- `__init__()` (`angr.calling_conventions.SimComboArg` `method`), 487
- `__init__()` (`angr.calling_conventions.SimFunctionArgument` `method`), 486
- `__init__()` (`angr.calling_conventions.SimLyingRegArg` `method`), 492
- `__init__()` (`angr.calling_conventions.SimReferenceArgument` `method`), 488
- `__init__()` (`angr.calling_conventions.SimRegArg` `method`), 486
- `__init__()` (`angr.calling_conventions.SimStackArg` `method`), 487
- `__init__()` (`angr.calling_conventions.SimStructArg` `method`), 487
- `__init__()` (`angr.calling_conventions.UsercallArgSession` `method`), 489
- `__init__()` (`angr.code_location.CodeLocation` `method`), 616
- `__init__()` (`angr.code_location.ExternalCodeLocation` `method`), 617
- `__init__()` (`angr.codenode.BlockNode` `method`), 883
- `__init__()` (`angr.codenode.CodeNode` `method`), 882
- `__init__()` (`angr.codenode.HookNode` `method`), 883
- `__init__()` (`angr.codenode.SootBlockNode` `method`), 883
- `__init__()` (`angr.concretization_strategies.SimConcretizationStrategy` `method`), 335
- `__init__()` (`angr.concretization_strategies.controlled_data.SimConcretizationStrategyControlledData` `method`), 381
- `__init__()` (`angr.concretization_strategies.eval.SimConcretizationStrategyEval` `method`), 379
- `__init__()` (`angr.concretization_strategies.max.SimConcretizationStrategyMax` `method`), 380
- `__init__()` (`angr.concretization_strategies.nonzero_range.SimConcretizationStrategyNonzeroRange` `method`), 380
- `__init__()` (`angr.concretization_strategies.norepeats.SimConcretizationStrategyNoRepeats` `method`), 379
- `__init__()` (`angr.concretization_strategies.norepeats_range.SimConcretizationStrategyNoRepeatsRange` `method`), 381
- `__init__()` (`angr.concretization_strategies.range.SimConcretizationStrategyRange` `method`), 380
- `__init__()` (`angr.concretization_strategies.solutions.SimConcretizationStrategySolutions` `method`), 380
- `__init__()` (`angr.concretization_strategies.unlimited_range.SimConcretizationStrategyUnlimitedRange` `method`), 382
- `__init__()` (`angr.distributed.server.Server` `method`), 909
- `__init__()` (`angr.distributed.worker.BadStatesDropper` `method`), 909
- `__init__()` (`angr.distributed.worker.ExplorationStatusNotifier` `method`), 910
- `__init__()` (`angr.distributed.worker.Worker` `method`), 910
- `__init__()` (`angr.engines.concrete.SimEngineConcrete` `method`), 433
- `__init__()` (`angr.engines.engine.SimEngineBase` `method`), 428
- `__init__()` (`angr.engines.engine.SuccessorsMixin` `method`), 428
- `__init__()` (`angr.engines.engine.TLSProperty` `method`), 428
- `__init__()` (`angr.engines.light.data.ArithmeticExpression` `method`), 755
- `__init__()` (`angr.engines.light.data.RegisterOffset` `method`), 755
- `__init__()` (`angr.engines.light.data.SpOffset` `method`), 755
- `__init__()` (`angr.engines.light.engine.SimEngineLight` `method`), 755
- `__init__()` (`angr.engines.light.engine.SimEngineLightMixin` `method`), 755
- `__init__()` (`angr.engines.pcode.behavior.BehaviorFactory` `method`), 464
- `__init__()` (`angr.engines.pcode.behavior.OpBehavior` `method`), 445
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorBoolAnd` `method`), 459
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorBoolNegate` `method`), 458
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorBoolOr` `method`), 459
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorBoolXor` `method`), 458
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorCopy` `method`), 446
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorEqual` `method`), 447
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorFloatAbs` `method`), 462
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorFloatAdd` `method`), 461
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorFloatCeil` `method`), 463
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorFloatDiv` `method`), 461
- `__init__()` (`angr.engines.pcode.behavior.OpBehaviorFloatEqual` `method`), 460

`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 460
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 460
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 461
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 460
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 461
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 460
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 463
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 461
`__init__` () (angr.engines.pcode.behavior.OpBehaviorFloatFloat method), 462
`__init__` () (angr.engines.pcode.behavior.OpBehaviorInt2Compi method), 452
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntAdd method), 450
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntAnd method), 454
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntCar method), 451
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntDiv method), 456
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntLeft method), 454
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntLess method), 448
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntLessEqual method), 449
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntMul method), 456
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntNeg method), 453
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntOr method), 454
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntRem method), 457
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntRight method), 455
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntShor method), 452

`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntScarry method), 451
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSdiv method), 457
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSext method), 450
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSless method), 448
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSlessEqual method), 448
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSrem method), 457
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSright method), 455
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntSub method), 451
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntXor method), 453
`__init__` () (angr.engines.pcode.behavior.OpBehaviorIntZext method), 449
`__init__` () (angr.engines.pcode.behavior.OpBehaviorNotEqual method), 447
`__init__` () (angr.engines.pcode.behavior.OpBehaviorPiece method), 463
`__init__` () (angr.engines.pcode.behavior.OpBehaviorPopcount method), 464
`__init__` () (angr.engines.pcode.behavior.OpBehaviorSubpiece method), 463
`__init__` () (angr.engines.pcode.emulate.PcodeEmulatorMixin method), 445
`__init__` () (angr.engines.pcode.engine.HeavyPcodeMixin method), 434
`__init__` () (angr.engines.pcode.lifter.ExitStatement method), 435
`__init__` () (angr.engines.pcode.lifter.IRSB method), 437
`__init__` () (angr.engines.pcode.lifter.Lifter method), 440
`__init__` () (angr.engines.pcode.lifter.PcodeBasicBlockLifter method), 441
`__init__` () (angr.engines.pcode.lifter.PcodeDisassemblerInsn method), 436
`__init__` () (angr.engines.pcode.lifter.PcodeLifterEngineMixin method), 443
`__init__` () (angr.engines.successors.SimSuccessors method), 430
`__init__` () (angr.engines.unicorn.SimEngineUnicorn method), 433
`__init__` () (angr.errors.SimMemoryMissingError method), 905
`__init__` () (angr.errors.SimReliftException method), 907
`__init__` () (angr.errors.SimSegfaultException method), 908

`__init__()` (`angr.errors.SimUninitializedAccessError` method), 907
`__init__()` (`angr.exploration_techniques.Bucketizer` method), 406
`__init__()` (`angr.exploration_techniques.CallFunctionGoal` method), 401
`__init__()` (`angr.exploration_techniques.DFS` method), 398
`__init__()` (`angr.exploration_techniques.Director` method), 400
`__init__()` (`angr.exploration_techniques.DrillerCore` method), 393
`__init__()` (`angr.exploration_techniques.ExecuteAddressGoal` method), 400
`__init__()` (`angr.exploration_techniques.ExplorationTechnique` method), 390
`__init__()` (`angr.exploration_techniques.Explorer` method), 397
`__init__()` (`angr.exploration_techniques.LengthLimiter` method), 398
`__init__()` (`angr.exploration_techniques.LocalLoopSeer` method), 406
`__init__()` (`angr.exploration_techniques.LoopSeer` method), 393
`__init__()` (`angr.exploration_techniques.ManualMergepoint` method), 402
`__init__()` (`angr.exploration_techniques.MemoryWatcher` method), 405
`__init__()` (`angr.exploration_techniques.Oppologist` method), 399
`__init__()` (`angr.exploration_techniques.Slicecutor` method), 392
`__init__()` (`angr.exploration_techniques.Spiller` method), 401
`__init__()` (`angr.exploration_techniques.StochasticSearch` method), 403
`__init__()` (`angr.exploration_techniques.Suggestions` method), 407
`__init__()` (`angr.exploration_techniques.Symbion` method), 404
`__init__()` (`angr.exploration_techniques.TechniqueBuilder` method), 403
`__init__()` (`angr.exploration_techniques.Threading` method), 397
`__init__()` (`angr.exploration_techniques.Timeout` method), 407
`__init__()` (`angr.exploration_techniques.Tracer` method), 395
`__init__()` (`angr.exploration_techniques.UniqueSearch` method), 403
`__init__()` (`angr.exploration_techniques.Veritestig` method), 399
`__init__()` (`angr.exploration_techniques.bucketizer.Bucketizer` method), 427
`__init__()` (`angr.exploration_techniques.dfs.DFS` method), 408
`__init__()` (`angr.exploration_techniques.director.BaseGoal` method), 418
`__init__()` (`angr.exploration_techniques.director.CallFunctionGoal` method), 419
`__init__()` (`angr.exploration_techniques.director.Director` method), 420
`__init__()` (`angr.exploration_techniques.director.ExecuteAddressGoal` method), 419
`__init__()` (`angr.exploration_techniques.driller_core.DrillerCore` method), 417
`__init__()` (`angr.exploration_techniques.explorer.Explorer` method), 409
`__init__()` (`angr.exploration_techniques.lengthlimiter.LengthLimiter` method), 410
`__init__()` (`angr.exploration_techniques.local_loop_seer.LocalLoopSeer` method), 422
`__init__()` (`angr.exploration_techniques.loop_seer.LoopSeer` method), 421
`__init__()` (`angr.exploration_techniques.manual_mergepoint.ManualMergepoint` method), 410
`__init__()` (`angr.exploration_techniques.memory_watcher.MemoryWatcher` method), 426
`__init__()` (`angr.exploration_techniques.oppologist.Oppologist` method), 421
`__init__()` (`angr.exploration_techniques.slicecutor.Slicecutor` method), 417
`__init__()` (`angr.exploration_techniques.spiller.PickledStatesDb` method), 411
`__init__()` (`angr.exploration_techniques.spiller.PickledStatesList` method), 411
`__init__()` (`angr.exploration_techniques.spiller.Spiller` method), 412
`__init__()` (`angr.exploration_techniques.spiller_db.PickledState` method), 413
`__init__()` (`angr.exploration_techniques.stochastic.StochasticSearch` method), 423
`__init__()` (`angr.exploration_techniques.suggestions.Suggestions` method), 427
`__init__()` (`angr.exploration_techniques.symbion.Symbion` method), 425
`__init__()` (`angr.exploration_techniques.tech_builder.TechniqueBuilder` method), 425
`__init__()` (`angr.exploration_techniques.threading.Threading` method), 413
`__init__()` (`angr.exploration_techniques.timeout.Timeout` method), 408
`__init__()` (`angr.exploration_techniques.tracer.RepHook` method), 415
`__init__()` (`angr.exploration_techniques.tracer.Tracer` method), 415
`__init__()` (`angr.exploration_techniques.tracer.TracerDesyncError` method), 414

`__init__()` (`angr.exploration_techniques.unique.UniqueSearch` method), 554
`__init__()` (`angr.exploration_techniques.veritestesting.Veritestesting` method), 424
`__init__()` (`angr.exploration_techniques.veritestesting.Veritestesting` method), 414
`__init__()` (`angr.factory.AngrObjectFactory` method), 216
`__init__()` (`angr.flirt.FlirtSignature` method), 892
`__init__()` (`angr.keyed_region.KeyedRegion` method), 618
`__init__()` (`angr.keyed_region.RegionObject` method), 618
`__init__()` (`angr.keyed_region.StoredObject` method), 617
`__init__()` (`angr.knowledge_base.knowledge_base.KnowledgeBase` method), 523
`__init__()` (`angr.knowledge_plugins.callsite_prototypes.CallsitePrototype` method), 525
`__init__()` (`angr.knowledge_plugins.cfg.CFGNode` method), 530
`__init__()` (`angr.knowledge_plugins.cfg.CFGManager` method), 538
`__init__()` (`angr.knowledge_plugins.cfg.CFGModel` method), 532
`__init__()` (`angr.knowledge_plugins.cfg.CFGNode` method), 528
`__init__()` (`angr.knowledge_plugins.cfg.IndirectJump` method), 531
`__init__()` (`angr.knowledge_plugins.cfg.MemoryData` method), 527
`__init__()` (`angr.knowledge_plugins.cfg.cfg_manager.CFGManager` method), 547
`__init__()` (`angr.knowledge_plugins.cfg.cfg_model.CFGModel` method), 539
`__init__()` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` method), 549
`__init__()` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` method), 547
`__init__()` (`angr.knowledge_plugins.cfg.cfg_node.CFGNodeCreationFactory` method), 547
`__init__()` (`angr.knowledge_plugins.cfg.indirect_jump.IndirectJump` method), 551
`__init__()` (`angr.knowledge_plugins.cfg.memory_data.MemoryData` method), 546
`__init__()` (`angr.knowledge_plugins.debug_variables.DebugVariable` method), 572
`__init__()` (`angr.knowledge_plugins.debug_variables.DebugVariable` method), 572
`__init__()` (`angr.knowledge_plugins.debug_variables.DebugVariable` method), 573
`__init__()` (`angr.knowledge_plugins.functions.function.Function` method), 555
`__init__()` (`angr.knowledge_plugins.functions.function_manager.FunctionManager` method), 553
`__init__()` (`angr.knowledge_plugins.functions.function_manager.FunctionManager` method), 553
`__init__()` (`angr.knowledge_plugins.functions.soot_function.SootFunction` method), 563
`__init__()` (`angr.knowledge_plugins.indirect_jumps.IndirectJumps` method), 552
`__init__()` (`angr.knowledge_plugins.key_definitions.Definition` method), 587
`__init__()` (`angr.knowledge_plugins.key_definitions.KeyDefinitionManager` method), 576
`__init__()` (`angr.knowledge_plugins.key_definitions.LiveDefinitions` method), 577
`__init__()` (`angr.knowledge_plugins.key_definitions.ReachingDefinitions` method), 574
`__init__()` (`angr.knowledge_plugins.key_definitions.Uses` method), 585
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.Atom` method), 588
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.ConstantSrc` method), 590
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.GuardUse` method), 590
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.MemoryLocation` method), 591
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.Register` method), 591
`__init__()` (`angr.knowledge_plugins.key_definitions.atoms.Tmp` method), 590
`__init__()` (`angr.knowledge_plugins.key_definitions.definition.Definition` method), 594
`__init__()` (`angr.knowledge_plugins.key_definitions.definition.Definition` method), 593
`__init__()` (`angr.knowledge_plugins.key_definitions.environment.Environment` method), 595
`__init__()` (`angr.knowledge_plugins.key_definitions.heap_address.HeapAddress` method), 595
`__init__()` (`angr.knowledge_plugins.key_definitions.key_definition_manager.KeyDefinitionManager` method), 596
`__init__()` (`angr.knowledge_plugins.key_definitions.key_definition_manager.KeyDefinitionManager` method), 596
`__init__()` (`angr.knowledge_plugins.key_definitions.live_definitions.Definition` method), 597
`__init__()` (`angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions` method), 598
`__init__()` (`angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitions` method), 606
`__init__()` (`angr.knowledge_plugins.key_definitions.tag.FunctionTag` method), 608
`__init__()` (`angr.knowledge_plugins.key_definitions.tag.TagManager` method), 608
`__init__()` (`angr.knowledge_plugins.key_definitions.uses.Uses` method), 610
`__init__()` (`angr.knowledge_plugins.labels.Labels` method), 552
`__init__()` (`angr.knowledge_plugins.patches.Patch` method), 552

method), 524

__init__() (angr.knowledge_plugins.patches.PatchManager method), 524

__init__() (angr.knowledge_plugins.plugin.KnowledgeBasePlugin method), 525

__init__() (angr.knowledge_plugins.structured_code.manager.StructuredCodeManager method), 574

__init__() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 612

__init__() (angr.knowledge_plugins.types.TypesStore method), 551

__init__() (angr.knowledge_plugins.variables.variable_access_tracker.AccessTracker method), 565

__init__() (angr.knowledge_plugins.variables.variable_manager.LiveVariableManager method), 565

__init__() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 571

__init__() (angr.knowledge_plugins.variables.variable_manager.VariableManagerInternal method), 566

__init__() (angr.knowledge_plugins.xrefs.xref.XRef method), 614

__init__() (angr.knowledge_plugins.xrefs.xref_manager.XRefManager method), 615

__init__() (angr.misc.plugins.PluginHub method), 222

__init__() (angr.misc.plugins.PluginPreset method), 223

__init__() (angr.procedures.definitions.SimLibrary method), 477

__init__() (angr.procedures.definitions.SimSyscallLibrary method), 481

__init__() (angr.procedures.definitions.SimTypeCollection method), 476

__init__() (angr.procedures.stubs.format_parser.FormatSpecifier method), 474

__init__() (angr.procedures.stubs.format_parser.FormatString method), 474

__init__() (angr.project.Project method), 213

__init__() (angr.sim_manager.ErrorRecord method), 389

__init__() (angr.sim_manager.SimulationManager method), 383

__init__() (angr.sim_procedure.SimProcedure method), 472

__init__() (angr.sim_state.SimState method), 225

__init__() (angr.sim_state_options.SimStateOptions method), 230

__init__() (angr.sim_state_options.StateOption method), 228

__init__() (angr.sim_type.NamedTypeMixin method), 510

__init__() (angr.sim_type.SimCppClass method), 519

__init__() (angr.sim_type.SimCppClassValue method), 519

__init__() (angr.sim_type.SimStruct method), 517

__init__() (angr.sim_type.SimStructValue method), 518

__init__() (angr.sim_type.SimType method), 509

__init__() (angr.sim_type.SimTypeArray method), 513

__init__() (angr.sim_type.SimTypeBottom method), 516

__init__() (angr.sim_type.SimTypeChar method), 512

__init__() (angr.sim_type.SimTypeCppFunction method), 516

__init__() (angr.sim_type.SimTypeDouble method), 517

__init__() (angr.sim_type.SimTypeFd method), 513

__init__() (angr.sim_type.SimTypeFloat method), 517

__init__() (angr.sim_type.SimTypeFunction method), 515

__init__() (angr.sim_type.SimTypeInt method), 511

__init__() (angr.sim_type.SimTypeLength method), 516

__init__() (angr.sim_type.SimTypeNum method), 511

__init__() (angr.sim_type.SimTypeNumOffset method), 519

__init__() (angr.sim_type.SimTypePointer method), 513

__init__() (angr.sim_type.SimTypeRef method), 520

__init__() (angr.sim_type.SimTypeReference method), 513

__init__() (angr.sim_type.SimTypeReg method), 511

__init__() (angr.sim_type.SimTypeString method), 514

__init__() (angr.sim_type.SimTypeTop method), 511

__init__() (angr.sim_type.SimTypeWString method), 515

__init__() (angr.sim_type.SimTypeWideChar method), 512

__init__() (angr.sim_type.SimUnion method), 518

__init__() (angr.sim_type.SimUnionValue method), 518

__init__() (angr.sim_type.TypeRef method), 510

__init__() (angr.sim_variable.SimConstantVariable method), 505

__init__() (angr.sim_variable.SimMemoryVariable method), 507

__init__() (angr.sim_variable.SimRegisterVariable method), 506

__init__() (angr.sim_variable.SimStackVariable method), 508

__init__() (angr.sim_variable.SimTemporaryVariable method), 505

__init__() (angr.sim_variable.SimVariable method), 504

__init__() (angr.sim_variable.SimVariableSet method), 508

__init__() (angr.simos.cgc.SimCGC method), 887

__init__() (angr.simos.javavm.SimJavaVM method), 890

`__init__()` (*angr.simos.linux.SimLinux* method), 886
`__init__()` (*angr.simos.simos.GlobalDescriptorTable* method), 886
`__init__()` (*angr.simos.simos.SimOS* method), 884
`__init__()` (*angr.simos.userland.SimUserland* method), 887
`__init__()` (*angr.simos.windows.SimWindows* method), 889
`__init__()` (*angr.slicer.SimLightState* method), 880
`__init__()` (*angr.slicer.SimSlicer* method), 881
`__init__()` (*angr.state_hierarchy.StateHierarchy* method), 389
`__init__()` (*angr.state_plugins.callstack.CallStack* method), 263
`__init__()` (*angr.state_plugins.callstack.CallStackAction* method), 266
`__init__()` (*angr.state_plugins.cgc.SimStateCGC* method), 272
`__init__()` (*angr.state_plugins.concrete.Concrete* method), 292
`__init__()` (*angr.state_plugins.debug_variables.SimDebugVariable* method), 280
`__init__()` (*angr.state_plugins.filesystem.SimConcreteFilesystem* method), 252
`__init__()` (*angr.state_plugins.filesystem.SimFilesystem* method), 249
`__init__()` (*angr.state_plugins.filesystem.SimHostFilesystem* method), 254
`__init__()` (*angr.state_plugins.gdb.GDB* method), 270
`__init__()` (*angr.state_plugins.globals.SimStateGlobals* method), 278
`__init__()` (*angr.state_plugins.heap.heap_base.SimHeapBase* method), 298
`__init__()` (*angr.state_plugins.heap.heap_brk.SimHeapBrk* method), 298
`__init__()` (*angr.state_plugins.heap.heap_freelist.Chunk* method), 300
`__init__()` (*angr.state_plugins.heap.heap_ptmalloc.PTChunk* method), 302
`__init__()` (*angr.state_plugins.heap.heap_ptmalloc.PTChunkIterator* method), 304
`__init__()` (*angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc* method), 304
`__init__()` (*angr.state_plugins.history.LambdaAttrIter* method), 270
`__init__()` (*angr.state_plugins.history.LambdaIter* method), 270
`__init__()` (*angr.state_plugins.history.SimStateHistory* method), 267
`__init__()` (*angr.state_plugins.history.TreeIter* method), 270
`__init__()` (*angr.state_plugins.inspect.BP* method), 233
`__init__()` (*angr.state_plugins.inspect.SimInspector* method), 234
`__init__()` (*angr.state_plugins.javavm_classloader.SimJavaVmClassloader* method), 294
`__init__()` (*angr.state_plugins.jni_references.SimStateJNIReferences* method), 296
`__init__()` (*angr.state_plugins.libc.SimStateLibc* method), 238
`__init__()` (*angr.state_plugins.light_registers.SimLightRegisters* method), 266
`__init__()` (*angr.state_plugins.log.SimStateLog* method), 262
`__init__()` (*angr.state_plugins.loop_data.SimStateLoopData* method), 291
`__init__()` (*angr.state_plugins.plugin.SimStatePlugin* method), 231
`__init__()` (*angr.state_plugins.posix.SimSystemPosix* method), 245
`__init__()` (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 282
`__init__()` (*angr.state_plugins.scratch.SimStateScratch* method), 467
`__init__()` (*angr.state_plugins.sim_action.SimAction* method), 467
`__init__()` (*angr.state_plugins.sim_action.SimActionConstraint* method), 467
`__init__()` (*angr.state_plugins.sim_action.SimActionData* method), 468
`__init__()` (*angr.state_plugins.sim_action.SimActionExit* method), 467
`__init__()` (*angr.state_plugins.sim_action.SimActionOperation* method), 468
`__init__()` (*angr.state_plugins.sim_action_object.SimActionObject* method), 469
`__init__()` (*angr.state_plugins.sim_event.SimEvent* method), 469
`__init__()` (*angr.state_plugins.solver.SimSolver* method), 254
`__init__()` (*angr.state_plugins.symbolizer.SimSymbolizer* method), 307
`__init__()` (*angr.state_plugins.trace_additions.ChallRespInfo* method), 274
`__init__()` (*angr.state_plugins.trace_additions.FormatInfoDontConstrain* method), 274
`__init__()` (*angr.state_plugins.trace_additions.FormatInfoIntToStr* method), 274
`__init__()` (*angr.state_plugins.trace_additions.FormatInfoStrToInt* method), 274
`__init__()` (*angr.state_plugins.trace_additions.ZenPlugin* method), 276
`__init__()` (*angr.state_plugins.uc_manager.SimUCManager* method), 279
`__init__()` (*angr.state_plugins.unicorn_engine.AggressiveConcretization* method), 288
`__init__()` (*angr.state_plugins.unicorn_engine.Unicorn*

[illegible]

`__init__()` (*angr.utils.mp.Initializer* method), 902
`__init__()` (*angr.vaults.Vault* method), 621
`__init__()` (*angr.vaults.VaultDict* method), 622
`__init__()` (*angr.vaults.VaultDir* method), 622
`__init__()` (*angr.vaults.VaultDirShelf* method), 622
`__init__()` (*angr.vaults.VaultPickler* method), 621
`__init__()` (*angr.vaults.VaultShelf* method), 622
`__init__()` (*angr.vaults.VaultUnpickler* method), 621

A

`abort()` (*angr.analyses.forward_analysis.forward_analysis* method), 626
`absolutize()` (*angr.storage.memory_mixins.regioned_memory.regioned_memory* method), 370
`absorb()` (*angr.sim_manager.SimulationManager* method), 386
`absorb()` (*angr.SimulationManager* method), 175
`abstract()` (*angr.analyses.typehoon.simple_solver.SimpleSolver* static method), 836
AbstractAddressDescriptor (class in *angr.storage.memory_mixins.regioned_memory.abstract_address_descriptor*), 371
AbstractMemory (class in *angr.storage.memory_mixins*), 339
AbstractMergerMixin (class in *angr.storage.memory_mixins.regioned_memory.abstract_merger_mixin*), 373
`access_type` (*angr.knowledge_plugins.variables.variable_access* attribute), 565
`accessed_data_references` (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* property), 548
`accessed_data_references` (*angr.knowledge_plugins.cfg.CFGNode* property), 529
AccessingZeroPageError, 288
`acquire_shared()` (*angr.storage.memory_mixins.paged_memory.pages.refcount_mixin.RefcountMixin* method), 360
`acquire_unique()` (*angr.storage.memory_mixins.paged_memory.pages.history_tracking_mixin.HistoryTrackingMixin* method), 361
`acquire_unique()` (*angr.storage.memory_mixins.paged_memory.pages.refcount_mixin.RefcountMixin* method), 360
`action()` (*angr.state_plugins.inspect.SimInspector* method), 234
`actions` (*angr.state_plugins.history.SimStateHistory* property), 269
`actions` (*angr.state_plugins.log.SimStateLog* property), 262
`actions_of_type()` (*angr.state_plugins.log.SimStateLog* method), 262
ActionsMixinHigh (class in *angr.storage.memory_mixins.actions_mixin*), 342

ActionsMixinLow (class in *angr.storage.memory_mixins.actions_mixin*), 342
`activate()` (*angr.misc.plugins.PluginPreset* method), 223
`active` (*angr.sim_manager.SimulationManager* attribute), 383
`active` (*angr.SimulationManager* attribute), 172
`active_workers` (*angr.distributed.server.Server* property), 909
`active_workers` (*angr.Server* property), 210
`Add` (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTransform* attribute), 666
`Add` (*angr.engines.light.data.ArithmeticExpression* attribute), 754
`Add` (class in *angr.analyses.typehoon.typevars*), 838
`add()` (*angr.exploration_techniques.spiller.PickledStatesBase* method), 410
`add()` (*angr.exploration_techniques.spiller.PickledStatesDb* method), 411
`add()` (*angr.exploration_techniques.spiller.PickledStatesList* method), 411
`add()` (*angr.procedures.definitions.SimLibrary* method), 478
`add()` (*angr.procedures.definitions.SimTypeCollection* method), 476
`add()` (*angr.sim_state_options.SimStateOptions* method), 230
`add()` (*angr.sim_variable.SimVariableSet* method), 508
`add()` (*angr.state_plugins.solver.SimSolver* method), 259
`add_action()` (*angr.state_plugins.history.SimStateHistory* method), 269
`add_action()` (*angr.state_plugins.log.SimStateLog* method), 262
`add_alias()` (*angr.procedures.definitions.SimLibrary* method), 478
`add_all_from_dict()` (*angr.procedures.definitions.SimLibrary* method), 478
`add_block_to_whitelist()` (*angr.analysis_plugins.annotated_cfg_mixin.AnnotatedCFGMixin* method), 881
`add_breakpoint()` (*angr.state_plugins.inspect.SimInspector* method), 234
`add_constraint()` (*angr.analyses.typehoon.simple_solver.Sketch* method), 834
`add_constraints()` (*angr.sim_state.SimState* method), 226
`add_constraints()` (*angr.SimState* method), 182
`add_data_seg()` (*angr.analyses.cfg.cfg_fast.DecodingAssumption* method), 652
`add_def()` (*angr.analyses.ddg.LiveDefinitions* method), 749
`add_def()` (*angr.analyses.reaching_definitions.ReachingDefinitionsModel* method), 778

Index 935

<code>method</code>), 816	<code>(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions</code>
<code>add_memory_use_by_defs()</code>	<code>method</code>), 604
<code>(angr.analyses.reaching_definitions.ReachingDefinitions</code>	<code>add_register_use_by_def()</code>
<code>method</code>), 786	<code>(angr.knowledge_plugins.key_definitions.LiveDefinitions</code>
<code>add_memory_variable()</code>	<code>method</code>), 583
<code>(angr.sim_variable.SimVariableSet</code>	<code>add_register_use_by_defs()</code>
<code>method</code>), 509	<code>(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions</code>
<code>add_memory_variables()</code>	<code>method</code>), 815
<code>(angr.sim_variable.SimVariableSet</code>	<code>add_register_use_by_defs()</code>
<code>method</code>), 509	<code>(angr.analyses.reaching_definitions.ReachingDefinitionsState</code>
<code>add_node()</code> (<code>angr.analyses.decompiler.structuring.structurer_nodes.StructurerNode</code>	<code>method</code>), 187
<code>method</code>), 687	<code>add_register_variable()</code>
<code>add_node()</code> (<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code>	<code>(angr.sim_variable.SimVariableSet</code>
<code>method</code>), 799	<code>method</code>), 508
<code>add_node()</code> (<code>angr.knowledge_plugins.cfg.cfg_model.CFGModel</code>	<code>add_retout_site()</code> (<code>angr.knowledge_plugins.functions.function.Function</code>
<code>method</code>), 539	<code>method</code>), 559
<code>add_node()</code> (<code>angr.knowledge_plugins.cfg.CFGModel</code>	<code>add_returning_function()</code>
<code>method</code>), 533	<code>(angr.analyses.cfg.cfg_fast.PendingJobs</code>
<code>add_nonreturning_function()</code>	<code>method</code>), 653
<code>(angr.analyses.cfg.cfg_fast.PendingJobs</code>	<code>add_sinkhole()</code> (<code>angr.state_plugins.cgc.SimStateCGC</code>
<code>method</code>), 653	<code>method</code>), 273
<code>add_number_mapping()</code>	<code>add_stack_use()</code> (<code>angr.analyses.reaching_definitions.LiveDefinitions</code>
<code>(angr.procedures.definitions.SimSyscallLibrary</code>	<code>method</code>), 768
<code>method</code>), 482	<code>add_stack_use()</code> (<code>angr.analyses.reaching_definitions.rd_state.ReachingD</code>
<code>add_number_mapping_from_dict()</code>	<code>method</code>), 815
<code>(angr.procedures.definitions.SimSyscallLibrary</code>	<code>add_stack_use()</code> (<code>angr.analyses.reaching_definitions.ReachingDefinition</code>
<code>method</code>), 482	<code>method</code>), 785
<code>add_obj()</code> (<code>angr.analyses.cfg.cfb.CFBlanket</code>	<code>add_stack_use()</code> (<code>angr.knowledge_plugins.key_definitions.live_definition</code>
<code>method</code>), 642	<code>method</code>), 604
<code>add_object()</code> (<code>angr.keyed_region.KeyedRegion</code>	<code>add_stack_use()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinition</code>
<code>method</code>), 619	<code>method</code>), 583
<code>add_object()</code> (<code>angr.keyed_region.RegionObject</code>	<code>add_stack_use_by_def()</code>
<code>method</code>), 618	<code>(angr.analyses.reaching_definitions.LiveDefinitions</code>
<code>add_patch()</code> (<code>angr.knowledge_plugins.patches.PatchManager</code>	<code>method</code>), 768
<code>method</code>), 524	<code>add_stack_use_by_def()</code>
<code>add_patch_obj()</code> (<code>angr.knowledge_plugins.patches.PatchManager</code>	<code>(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefi</code>
<code>method</code>), 524	<code>method</code>), 604
<code>add_regioned_address()</code>	<code>add_stack_use_by_def()</code>
<code>(angr.storage.memory_mixins.regioned_memory.abstract_address</code>	<code>(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions</code>
<code>method</code>), 371	<code>method</code>), 583
<code>add_register_use()</code> (<code>angr.analyses.reaching_definitions.LiveDefinitions</code>	<code>add_stack_use_by_defs()</code>
<code>method</code>), 767	<code>(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions</code>
<code>add_register_use()</code> (<code>angr.analyses.reaching_definitions.rd_state.ReachingDefinitions</code>	<code>method</code>), 815
<code>method</code>), 815	<code>add_stack_use_by_defs()</code>
<code>add_register_use()</code> (<code>angr.analyses.reaching_definitions.ReachingDefinitionsState</code>	<code>add_stack_use_by_defs()</code>
<code>method</code>), 785	<code>(angr.analyses.reaching_definitions.ReachingDefinitionsState</code>
<code>method</code>), 786	<code>add_state()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitions</code>
<code>add_register_use()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitions</code>	<code>method</code>), 389
<code>method</code>), 603	<code>add_state()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitions</code>
<code>method</code>), 583	<code>add_state()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitions</code>
<code>add_register_use_by_def()</code>	<code>add_state()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitions</code>
<code>(angr.analyses.reaching_definitions.LiveDefinitions</code>	<code>method</code>), 180
<code>method</code>), 768	<code>add_statements_to_whitelist()</code>
<code>add_register_use_by_def()</code>	<code>(angr.annocfg.AnnotatedCFG</code>
<code>method</code>), 768	<code>method</code>), 881
<code>add_register_use_by_def()</code>	<code>add_successor()</code> (<code>angr.engines.successors.SimSuccessors</code>
<code>method</code>), 768	<code>method</code>), 430
<code>add_register_use_by_def()</code>	<code>add_tmp_use()</code> (<code>angr.analyses.reaching_definitions.LiveDefinitions</code>

Index 937

`addr` (`angr.analyses.disassembly.DisassemblyPiece` attribute), 856
`addr` (`angr.analyses.disassembly.IROp` attribute), 857
`addr` (`angr.analyses.disassembly.OperandPiece` attribute), 858
`addr` (`angr.analyses.propagator.vex_vars.VEXMemVar` attribute), 756
`addr` (`angr.analyses.reaching_definitions.MemoryLocation` attribute), 773
`addr` (`angr.angrdb.models.DbComment` attribute), 681
`addr` (`angr.angrdb.models.DbFunction` attribute), 679
`addr` (`angr.angrdb.models.DbLabel` attribute), 681
`addr` (`angr.Block` attribute), 170
`addr` (`angr.block.Block` attribute), 221
`addr` (`angr.block.DisassemblerBlock` attribute), 220
`addr` (`angr.codenode.CodeNode` attribute), 882
`addr` (`angr.engines.pcode.lifter.IRSB` attribute), 437
`addr` (`angr.engines.pcode.lifter.Lifter` attribute), 440
`addr` (`angr.engines.pcode.lifter.PcodeDisassemblerBlock` attribute), 435
`addr` (`angr.engines.pcode.lifter.PcodeLifter` attribute), 442
`addr` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` attribute), 548
`addr` (`angr.knowledge_plugins.cfg.CFGNode` attribute), 528
`addr` (`angr.knowledge_plugins.cfg.indirect_jump.IndirectJump` attribute), 551
`addr` (`angr.knowledge_plugins.cfg.IndirectJump` attribute), 531
`addr` (`angr.knowledge_plugins.cfg.memory_data.MemoryData` attribute), 546
`addr` (`angr.knowledge_plugins.cfg.MemoryData` attribute), 527
`addr` (`angr.knowledge_plugins.functions.function.Function` attribute), 556
`addr` (`angr.knowledge_plugins.functions.soot_function.SootFunction` attribute), 563
`addr` (`angr.knowledge_plugins.key_definitions.atoms.MemoryAtom` attribute), 592
`addr` (`angr.sim_state.SimState` property), 225
`addr` (`angr.sim_variable.SimMemoryVariable` attribute), 507
`addr` (`angr.SimState` property), 182
`addr` (`angr.state_plugins.history.SimStateHistory` property), 267
`addr_and_variables` (`angr.analyses.variable_recovery.variable_recovery_analysis.VariableRecoveryAnalysis` attribute), 824
`addr_invalid()` (`angr.state_plugins.cgc.SimStateCGC` method), 272
`addr_to_instruction_addr()` (`angr.knowledge_plugins.functions.function.Function` method), 561
`address` (`angr.analyses.reaching_definitions.function_handler.FunctionHandler` attribute), 804
`address` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 791
`address` (`angr.block.CapstoneInsn` property), 221
`address` (`angr.block.DisassemblerInsn` property), 220
`address` (`angr.engines.pcode.lifter.PcodeDisassemblerInsn` property), 436
`address` (`angr.knowledge_plugins.cfg.memory_data.MemoryData` property), 546
`address` (`angr.knowledge_plugins.cfg.MemoryData` property), 527
`address` (`angr.state_plugins.unicorn_engine.MEM_PATCH` attribute), 284
`address` (`angr.state_plugins.unicorn_engine.MemoryValue` attribute), 284
`address` (`angr.storage.memory_mixins.regioned_memory.region_data.Address` attribute), 369
`address_multi` (`angr.analyses.reaching_definitions.function_handler.FunctionHandler` attribute), 804
`address_multi` (`angr.analyses.reaching_definitions.function_handler.FunctionHandler` attribute), 807
`address_multi` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 791
`AddressConcretizationMixin` (class in `angr.storage.memory_mixins.address_concretization_mixin`), 344
`AddressOperand` (class in `angr.analyses.cfg.indirect_jump_resolvers.jumptable`), 667
`AddressTransformation` (class in `angr.analyses.cfg.indirect_jump_resolvers.jumptable`), 666
`AddressTransformationTypes` (class in `angr.analyses.cfg.indirect_jump_resolvers.jumptable`), 666
`AddressWrapper` (class in `angr.storage.memory_mixins.regioned_memory.region_data`), 368
`addresses_for_hash()` (`angr.storage.memory_mixins.convenient_mappings_r` method), 348
`addresses_for_name()` (`angr.storage.memory_mixins.convenient_mappings_r` method), 348
`ADDS_EXITS` (`angr.sim_procedure.SimProcedure` attribute), 472
`ADDS_EXITS` (`angr.SimProcedure` attribute), 159
`AFTER_AIL_GRAPH_CREATION` (`angr.analyses.decompiler.optimization_passes.optimization_passes` attribute), 705
`AFTER_GLOBAL_SIMPLIFICATION` (`angr.analyses.decompiler.optimization_passes.optimization_passes` attribute), 705
`AFTER_MAKING_CALLSITES` (`angr.analyses.decompiler.optimization_passes.optimization_passes` attribute), 705
`and_build` (`angr.analyses.decompiler.optimization_passes.optimization_passes` attribute), 705

AFTER_SINGLE_BLOCK_SIMPLIFICATION (angr.analyses.decompiler.optimization_passes.optimization_passes.OptimizationPassStage attribute), 705

AFTER_STRUCTURING (angr.analyses.decompiler.optimization_passes.optimization_passes.OptimizationPassStage attribute), 705

AFTER_VARIABLE_RECOVERY (angr.analyses.decompiler.optimization_passes.optimization_passes.OptimizationPassStage attribute), 705

AggressiveConcretizationAnnotation (class in angr.state_plugins.unicorn_engine), 288

AILBlockTempCollector (class in angr.analyses.decompiler.ail_simplifier), 693

AILGraphWalker (class in angr.analyses.decompiler.ailgraph_walker), 694

AILSimplifier (class in angr.analyses.decompiler.ail_simplifier), 693

alignment (angr.knowledge_plugins.functions.function.Function property), 556

alignment (angr.sim_type.SimStruct property), 518

alignment (angr.sim_type.SimType property), 509

alignment (angr.sim_type.SimTypeArray property), 514

alignment (angr.sim_type.SimTypeDouble property), 517

alignment (angr.sim_type.SimTypeString property), 514

alignment (angr.sim_type.SimTypeWString property), 515

alignment (angr.sim_type.SimUnion property), 518

alignment (angr.sim_type.TypeRef property), 510

ALL (angr.sim_manager.SimulationManager attribute), 383

ALL (angr.SimulationManager attribute), 172

all_bytes_changed_in_history() (angr.storage.memory_mixins.paged_memory.paged_memory.PagedMemoryTrackingMixin method), 361

all_constants (angr.engines.pcode.lifter.IRSB property), 439

all_definitions (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState attribute), 811

all_definitions (angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis property), 797

all_definitions (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis property), 776

all_definitions (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis property), 781

all_objects (angr.state_plugins.sim_action.SimAction property), 467

all_objects (angr.state_plugins.sim_action.SimActionConstraint property), 467

all_objects (angr.state_plugins.sim_action.SimActionData property), 468

all_objects (angr.state_plugins.sim_action.SimActionExit property), 467

all_objects (angr.state_plugins.sim_action.SimActionOperation property), 468

all_successors() (angr.analyses.forward_analysis.visitors.graph.Graph property), 468

all_successors() (angr.state_hierarchy.StateHierarchy method), 390

all_successors() (angr.StateHierarchy method), 180

ALL_TABLES (angr.angrdb.db.AngrDB attribute), 676

all_uses (angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis property), 797

all_uses (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis property), 776

alloc() (angr.calling_conventions.AllocHelper method), 485

allocate() (angr.analyses.reaching_definitions.heap_allocator.HeapAllocator method), 801

allocate() (angr.SimHeapBrk method), 205

allocate() (angr.state_plugins.heap.heap_brk.SimHeapBrk method), 298

allocate_stack_pages() (angr.storage.memory_mixins.paged_memory.stack_allocation_mixin.StackAllocationMixin method), 358

allocated_addresses (angr.analyses.reaching_definitions.heap_allocator.HeapAllocator property), 802

allocated_chunks() (angr.SimHeapPTMalloc method), 206

allocated_chunks() (angr.state_plugins.heap.heap_freelist.SimHeapFreelist method), 301

allocated_chunks() (angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc method), 304

AllocHelper (class in angr.calling_conventions), 484

allow_arch_optimizations (angr.engines.pcode.lifter.Lifter attribute), 440

allow_arch_optimizations (angr.engines.pcode.lifter.PcodeLifter attribute), 442

allow_arch_optimizations (angr.engines.pcode.lifter.Lifter attribute), 472

allow_arch_optimizations (angr.engines.pcode.lifter.Lifter attribute), 159

ALWAYS (angr.analyses.decompiler.structuring.phoenix.MultiStmtExprMode attribute), 692

AlwaysUpdate (angr.analyses.calling_convention.UpdateArgumentsOption attribute), 637

AMD64CCallRewriter (class in angr.analyses.decompiler.ccall_rewriters.amd64_ccalls), 695

AMD64ElfGotResolver (class in angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got), 661

analyses (*angr.Project* property), 164
 analyses (*angr.project.Project* property), 214
 AnalysesHub (class in *angr.analyses.analysis*), 623
 AnalysesHubWithDefault (class in *angr.analyses.analysis*), 624
 analysis (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState* attribute), 811
 analysis (*angr.analyses.reaching_definitions.ReachingDefinitionsState* attribute), 781
 Analysis (class in *angr*), 178
 Analysis (class in *angr.analyses.analysis*), 624
 AnalysisFactory (class in *angr.analyses.analysis*), 624
 AnalysisLogEntry (class in *angr.analyses.analysis*), 623
 AnalysisTask (class in *angr.analyses.vfg*), 850
 analyze() (*angr.analyses.callee_cleanup_finder.CalleeCleanupFinder* method), 870
 analyze() (*angr.analyses.code_tagging.CodeTagging* method), 676
 analyze() (*angr.analyses.decompiler.optimization_passes.OptimizationPasses* method), 706
 analyze() (*angr.analyses.decompiler.optimization_passes.OptimizationPasses* method), 707
 analyze() (*angr.analyses.vtable.VtableFinder* method), 854
 analyze_transmit() (*angr.state_plugins.trace_additions.TraceAdditions* method), 277
 And (class in *angr.engines.light.data.ArithmeticExpression* attribute), 754
 angr
 module, 157
 angr.analyses
 module, 623
 angr.analyses.analysis
 module, 623
 angr.analyses.backward_slice
 module, 631
 angr.analyses.binary_optimizer
 module, 869
 angr.analyses.bindiff
 module, 633
 angr.analyses.boyscout
 module, 636
 angr.analyses.callee_cleanup_finder
 module, 870
 angr.analyses.calling_convention
 module, 636
 angr.analyses.cdg
 module, 675
 angr.analyses.cfg
 module, 641
 angr.analyses.cfg.cfb
 module, 641
 angr.analyses.cfg.cfg
 module, 642
 angr.analyses.cfg.cfg_arch_options
 module, 660
 angr.analyses.cfg.cfg_base
 module, 649
 angr.analyses.cfg.cfg_emulated
 module, 644
 angr.analyses.cfg.cfg_fast
 module, 651
 angr.analyses.cfg.cfg_fast_soot
 module, 673
 angr.analyses.cfg.cfg_job_base
 module, 660
 angr.analyses.cfg.indirect_jump_resolvers
 module, 673
 angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got
 module, 661
 angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast
 module, 662
 angr.analyses.cfg.indirect_jump_resolvers.const_resolver
 module, 671
 angr.analyses.cfg.indirect_jump_resolvers.default_resolver
 module, 666
 angr.analyses.cfg.indirect_jump_resolvers.jumptable
 module, 666
 angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast
 module, 664
 angr.analyses.cfg.indirect_jump_resolvers.resolver
 module, 672
 angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic_plt
 module, 665
 angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat
 module, 663
 angr.analyses.cfg.slice_to_sink
 module, 818
 angr.analyses.cfg.slice_to_sink.cfg_slice_to_sink
 module, 818
 angr.analyses.cfg.slice_to_sink.graph
 module, 819
 angr.analyses.cfg.slice_to_sink.transitions
 module, 820
 angr.analyses.class_identifier
 module, 855
 angr.analyses.code_tagging
 module, 675
 angr.analyses.complete_calling_conventions
 module, 638
 angr.analyses.congruency_check
 module, 868
 angr.analyses.data_dep
 module, 879
 angr.analyses.data_dep.data_dependency_analysis
 module, 875
 angr.analyses.data_dep.dep_nodes

module, 877
 angr.analyses.data_dep.sim_act_location
 module, 876
 angr.analyses.datagraph_meta
 module, 675
 angr.analyses.ddg
 module, 748
 angr.analyses.decompiler
 module, 693
 angr.analyses.decompiler.ail_simplifier
 module, 693
 angr.analyses.decompiler.ailgraph_walker
 module, 694
 angr.analyses.decompiler.block_simplifier
 module, 694
 angr.analyses.decompiler.callsite_maker
 module, 695
 angr.analyses.decompiler.ccall_rewriters
 module, 695
 angr.analyses.decompiler.ccall_rewriters.amd64_rewrite_base
 module, 695
 angr.analyses.decompiler.ccall_rewriters.rewriter_base
 module, 695
 angr.analyses.decompiler.clinic
 module, 696
 angr.analyses.decompiler.condition_processor
 module, 698
 angr.analyses.decompiler.decompilation_cache
 module, 700
 angr.analyses.decompiler.decompilation_options
 module, 699
 angr.analyses.decompiler.decompiler
 module, 700
 angr.analyses.decompiler.empty_node_remover
 module, 701
 angr.analyses.decompiler.expression_narrower
 module, 702
 angr.analyses.decompiler.graph_region
 module, 702
 angr.analyses.decompiler.jump_target_collector
 module, 703
 angr.analyses.decompiler.jumptable_entry_condition_analyses
 module, 703
 angr.analyses.decompiler.optimization_passes
 module, 704
 angr.analyses.decompiler.optimization_passes.base_parallel_simplifier
 module, 707
 angr.analyses.decompiler.optimization_passes.const_analysis
 module, 704
 angr.analyses.decompiler.optimization_passes.div_simplifier
 module, 708
 angr.analyses.decompiler.optimization_passes.engine_analysis
 module, 711
 angr.analyses.decompiler.optimization_passes.expr_on_stack
 module, 712
 angr.analyses.decompiler.optimization_passes.ite_expr_conv
 module, 708
 angr.analyses.decompiler.optimization_passes.lowered_switch
 module, 709
 angr.analyses.decompiler.optimization_passes.mod_simplifier
 module, 711
 angr.analyses.decompiler.optimization_passes.multi_simplif
 module, 711
 angr.analyses.decompiler.optimization_passes.optimization
 module, 705
 angr.analyses.decompiler.optimization_passes.register_save
 module, 713
 angr.analyses.decompiler.optimization_passes.ret_addr_save
 module, 714
 angr.analyses.decompiler.optimization_passes.stack_canary
 module, 707
 angr.analyses.decompiler.optimization_passes.x86_gcc_getpo
 module, 714
 angr.analyses.decompiler.peephole_optimizations
 module, 714
 angr.analyses.decompiler.peephole_optimizations.base
 module, 714
 angr.analyses.decompiler.redundant_label_remover
 module, 725
 angr.analyses.decompiler.region_identifier
 module, 716
 angr.analyses.decompiler.region_simplifiers
 module, 717
 angr.analyses.decompiler.region_simplifiers.cascading_conc
 module, 717
 angr.analyses.decompiler.region_simplifiers.cascading_ifs
 module, 717
 angr.analyses.decompiler.region_simplifiers.expr_folding
 module, 718
 angr.analyses.decompiler.region_simplifiers.goto
 module, 720
 angr.analyses.decompiler.region_simplifiers.if_
 module, 721
 angr.analyses.decompiler.region_simplifiers.ifelse
 module, 721
 angr.analyses.decompiler.region_simplifiers.loop
 module, 721
 angr.analyses.decompiler.region_simplifiers.node_address_f
 module, 721
 angr.analyses.decompiler.region_simplifiers.region_simplif
 module, 721
 angr.analyses.decompiler.region_simplifiers.switch_cluster
 module, 722
 angr.analyses.decompiler.region_simplifiers.switch_expr_si
 module, 725
 angr.analyses.decompiler.region_walker
 module, 725
 angr.analyses.decompiler.sequence_walker

module, 725	module, 845
angr.analyses.decompiler.structured_codegen	angr.analyses.init_finder
module, 726	module, 870
angr.analyses.decompiler.structured_codegen.basic	angr.analyses.loop_analysis
module, 726	module, 846
angr.analyses.decompiler.structured_codegen.c	angr.analyses.loopfinder
module, 727	module, 846
angr.analyses.decompiler.structured_codegen.dummy	angr.analyses.propagator
module, 745	module, 756
angr.analyses.decompiler.structured_codegen.dwarf	angr.analyses.propagator.engine_ail
module, 744	module, 758
angr.analyses.decompiler.structuring	angr.analyses.propagator.engine_base
module, 686	module, 757
angr.analyses.decompiler.structuring.dream	angr.analyses.propagator.engine_vex
module, 686	module, 757
angr.analyses.decompiler.structuring.phoenix	angr.analyses.propagator.outdated_definition_walker
module, 692	module, 759
angr.analyses.decompiler.structuring.recursive_ast_unparser	angr.analyses.propagator.propagator
module, 686	module, 760
angr.analyses.decompiler.structuring.structured_base	angr.analyses.propagator.tmpvar_finder
module, 691	module, 760
angr.analyses.decompiler.structuring.structured_base	angr.analyses.propagator.top_checker_mixin
module, 687	module, 761
angr.analyses.decompiler.utils	angr.analyses.propagator.values
module, 745	module, 756
angr.analyses.disassembly	angr.analyses.propagator.vex_vars
module, 856	module, 756
angr.analyses.disassembly_utils	angr.analyses.proximity_graph
module, 860	module, 872
angr.analyses.dominance_frontier	angr.analyses.reaching_definitions
module, 870	module, 761
angr.analyses.find_objects_static	angr.analyses.reaching_definitions.call_trace
module, 855	module, 793
angr.analyses.flirt	angr.analyses.reaching_definitions.dep_graph
module, 754	module, 798
angr.analyses.forward_analysis	angr.analyses.reaching_definitions.engine_ail
module, 625	module, 818
angr.analyses.forward_analysis.forward_analysis	angr.analyses.reaching_definitions.engine_vex
module, 625	module, 794
angr.analyses.forward_analysis.job_info	angr.analyses.reaching_definitions.function_handler
module, 626	module, 802
angr.analyses.forward_analysis.visitors	angr.analyses.reaching_definitions.heap_allocator
module, 626	module, 801
angr.analyses.forward_analysis.visitors.call_graph	angr.analyses.reaching_definitions.rd_state
module, 626	module, 809
angr.analyses.forward_analysis.visitors.function_graph	angr.analyses.reaching_definitions.reaching_definitions
module, 627	module, 795
angr.analyses.forward_analysis.visitors.graph	angr.analyses.reaching_definitions.subject
module, 628	module, 817
angr.analyses.forward_analysis.visitors.loop	angr.analyses.reassembler
module, 630	module, 860
angr.analyses.forward_analysis.visitors.single_node_graph	angr.analyses.soot_class_hierarchy
module, 631	module, 640
angr.analyses.identifier.identify	angr.analyses.stack_pointer_tracker

module, 821
 angr.analyses.static_hooker
 module, 868
 angr.analyses.typehoon
 module, 845
 angr.analyses.typehoon.lifter
 module, 832
 angr.analyses.typehoon.simple_solver
 module, 832
 angr.analyses.typehoon.translator
 module, 836
 angr.analyses.typehoon.typeconsts
 module, 843
 angr.analyses.typehoon.typehoon
 module, 842
 angr.analyses.typehoon.typevars
 module, 837
 angr.analyses.variable_recovery
 module, 832
 angr.analyses.variable_recovery.annotations
 module, 823
 angr.analyses.variable_recovery.engine_ail
 module, 831
 angr.analyses.variable_recovery.engine_base
 module, 831
 angr.analyses.variable_recovery.engine_vex
 module, 831
 angr.analyses.variable_recovery.irsb_scanner
 module, 832
 angr.analyses.variable_recovery.variable_recovery_base
 module, 829
 angr.analyses.variable_recovery.variable_recovery_fast
 module, 823
 angr.analyses.variable_recovery.variable_recovery_slow
 module, 827
 angr.analyses.veritesting
 module, 847
 angr.analyses.vfg
 module, 849
 angr.analyses.vsa_ddg
 module, 853
 angr.analyses.vtable
 module, 854
 angr.analyses.xrefs
 module, 871
 angr.angrdb
 module, 676
 angr.angrdb.db
 module, 676
 angr.angrdb.models
 module, 677
 angr.angrdb.serializers
 module, 681
 angr.angrdb.serializers.cfg_model
 module, 681
 angr.angrdb.serializers.comments
 module, 682
 angr.angrdb.serializers.funcs
 module, 682
 angr.angrdb.serializers.kb
 module, 683
 angr.angrdb.serializers.labels
 module, 683
 angr.angrdb.serializers.loader
 module, 683
 angr.angrdb.serializers.structured_code
 module, 685
 angr.angrdb.serializers.variables
 module, 684
 angr.angrdb.serializers.xrefs
 module, 684
 angr.annocfg
 module, 881
 angr.blade
 module, 879
 angr.block
 module, 220
 angr.callable
 module, 521
 angr.calling_conventions
 module, 484
 angr.code_location
 module, 616
 angr.codenode
 module, 882
 angr.concretization_strategies
 module, 335
 angr.concretization_strategies.any
 module, 381
 angr.concretization_strategies.controlled_data
 module, 381
 angr.concretization_strategies.eval
 module, 379
 angr.concretization_strategies.max
 module, 380
 angr.concretization_strategies.nonzero
 module, 381
 angr.concretization_strategies.nonzero_range
 module, 380
 angr.concretization_strategies.norepeats
 module, 379
 angr.concretization_strategies.norepeats_range
 module, 381
 angr.concretization_strategies.range
 module, 380
 angr.concretization_strategies.single
 module, 379
 angr.concretization_strategies.solutions

- module, 379
- angr.concretization_strategies.unlimited_range
 - module, 382
- angr.distributed
 - module, 909
- angr.distributed.server
 - module, 909
- angr.distributed.worker
 - module, 909
- angr.engines
 - module, 427
- angr.engines.concrete
 - module, 433
- angr.engines.engine
 - module, 428
- angr.engines.failure
 - module, 431
- angr.engines.hook
 - module, 431
- angr.engines.light
 - module, 755
- angr.engines.light.data
 - module, 754
- angr.engines.light.engine
 - module, 755
- angr.engines.pcode
 - module, 434
- angr.engines.pcode.behavior
 - module, 445
- angr.engines.pcode.cc
 - module, 464
- angr.engines.pcode.emulate
 - module, 445
- angr.engines.pcode.engine
 - module, 434
- angr.engines.pcode.lifter
 - module, 435
- angr.engines.procedure
 - module, 430
- angr.engines.soot
 - module, 432
- angr.engines.soot.engine
 - module, 432
- angr.engines.successors
 - module, 429
- angr.engines.syscall
 - module, 431
- angr.engines.unicorn
 - module, 432
- angr.engines.vex
 - module, 432
- angr.errors
 - module, 903
- angr.exploration_techniques
 - module, 390
- angr.exploration_techniques.bucketizer
 - module, 427
- angr.exploration_techniques.common
 - module, 425
- angr.exploration_techniques.dfs
 - module, 408
- angr.exploration_techniques.director
 - module, 418
- angr.exploration_techniques.driller_core
 - module, 416
- angr.exploration_techniques.explorer
 - module, 408
- angr.exploration_techniques.lengthlimiter
 - module, 410
- angr.exploration_techniques.local_loop_seer
 - module, 422
- angr.exploration_techniques.loop_seer
 - module, 421
- angr.exploration_techniques.manual_mergepoint
 - module, 410
- angr.exploration_techniques.memory_watcher
 - module, 426
- angr.exploration_techniques.oppologist
 - module, 421
- angr.exploration_techniques.slicecutor
 - module, 417
- angr.exploration_techniques.spiller
 - module, 410
- angr.exploration_techniques.spiller_db
 - module, 413
- angr.exploration_techniques.stochastic
 - module, 423
- angr.exploration_techniques.suggestions
 - module, 427
- angr.exploration_techniques.symbion
 - module, 425
- angr.exploration_techniques.tech_builder
 - module, 424
- angr.exploration_techniques.threading
 - module, 413
- angr.exploration_techniques.timeout
 - module, 408
- angr.exploration_techniques.tracer
 - module, 414
- angr.exploration_techniques.unique
 - module, 423
- angr.exploration_techniques.veritesting
 - module, 413
- angr.factory
 - module, 216
- angr.flirt
 - module, 892
- angr.flirt.build_sig
 - module, 390

module, 892
 angr.keyed_region
 module, 617
 angr.knowledge_base
 module, 523
 angr.knowledge_base.knowledge_base
 module, 523
 angr.knowledge_plugins
 module, 524
 angr.knowledge_plugins.callsite_prototypes
 module, 525
 angr.knowledge_plugins.cfg
 module, 526
 angr.knowledge_plugins.cfg.cfg_manager
 module, 547
 angr.knowledge_plugins.cfg.cfg_model
 module, 539
 angr.knowledge_plugins.cfg.cfg_node
 module, 547
 angr.knowledge_plugins.cfg.indirect_jump
 module, 550
 angr.knowledge_plugins.cfg.memory_data
 module, 545
 angr.knowledge_plugins.comments
 module, 552
 angr.knowledge_plugins.data
 module, 552
 angr.knowledge_plugins.debug_variables
 module, 572
 angr.knowledge_plugins.functions
 module, 553
 angr.knowledge_plugins.functions.function
 module, 555
 angr.knowledge_plugins.functions.function_manager
 module, 553
 angr.knowledge_plugins.functions.function_parser
 module, 563
 angr.knowledge_plugins.functions.soot_function
 module, 563
 angr.knowledge_plugins.indirect_jumps
 module, 552
 angr.knowledge_plugins.key_definitions
 module, 574
 angr.knowledge_plugins.key_definitions.atoms
 module, 588
 angr.knowledge_plugins.key_definitions.constants
 module, 592
 angr.knowledge_plugins.key_definitions.definitions
 module, 592
 angr.knowledge_plugins.key_definitions.environment
 module, 594
 angr.knowledge_plugins.key_definitions.heap_addresses
 module, 595
 angr.knowledge_plugins.key_definitions.key_definitions
 module, 596
 angr.knowledge_plugins.key_definitions.live_definitions
 module, 596
 angr.knowledge_plugins.key_definitions.rd_model
 module, 606
 angr.knowledge_plugins.key_definitions.tag
 module, 608
 angr.knowledge_plugins.key_definitions.undefined
 module, 609
 angr.knowledge_plugins.key_definitions.unknown_size
 module, 610
 angr.knowledge_plugins.key_definitions.uses
 module, 610
 angr.knowledge_plugins.labels
 module, 552
 angr.knowledge_plugins.patches
 module, 524
 angr.knowledge_plugins.plugin
 module, 525
 angr.knowledge_plugins.propagations
 module, 552
 angr.knowledge_plugins.structured_code
 module, 574
 angr.knowledge_plugins.structured_code.manager
 module, 574
 angr.knowledge_plugins.sync
 module, 612
 angr.knowledge_plugins.sync.sync_controller
 module, 612
 angr.knowledge_plugins.types
 module, 551
 angr.knowledge_plugins.variables
 module, 564
 angr.knowledge_plugins.variables.variable_access
 module, 564
 angr.knowledge_plugins.variables.variable_manager
 module, 565
 angr.knowledge_plugins.xrefs
 module, 614
 angr.knowledge_plugins.xrefs.xref
 module, 614
 angr.knowledge_plugins.xrefs.xref_manager
 module, 615
 angr.knowledge_plugins.xrefs.xref_types
 module, 615
 angr.misc.plugins
 module, 222
 angr.procedures
 module, 474
 angr.procedures.definitions
 module, 476
 angr.procedures.stubs.format_parser
 module, 474
 angr.project

- module, 212
- angr.protos
 - module, 621
- angr.serializable
 - module, 620
- angr.sim_manager
 - module, 382
- angr.sim_options
 - module, 228
- angr.sim_procedure
 - module, 469
- angr.sim_state
 - module, 224
- angr.sim_state_options
 - module, 228
- angr.sim_type
 - module, 509
- angr.sim_variable
 - module, 504
- angr.simos
 - module, 884
- angr.simos.cgc
 - module, 887
- angr.simos.javavm
 - module, 890
- angr.simos.linux
 - module, 886
- angr.simos.simos
 - module, 884
- angr.simos.userland
 - module, 887
- angr.simos.windows
 - module, 888
- angr.slicer
 - module, 880
- angr.state_hierarchy
 - module, 389
- angr.state_plugins
 - module, 231
- angr.state_plugins.callstack
 - module, 263
- angr.state_plugins.cgc
 - module, 271
- angr.state_plugins.concrete
 - module, 292
- angr.state_plugins.debug_variables
 - module, 307
- angr.state_plugins.filesystem
 - module, 248
- angr.state_plugins.gdb
 - module, 270
- angr.state_plugins.globals
 - module, 278
- angr.state_plugins.heap
 - module, 297
- angr.state_plugins.heap.heap_base
 - module, 297
- angr.state_plugins.heap.heap_brk
 - module, 298
- angr.state_plugins.heap.heap_freelist
 - module, 300
- angr.state_plugins.heap.heap_libc
 - module, 301
- angr.state_plugins.heap.heap_ptmalloc
 - module, 302
- angr.state_plugins.heap.utils
 - module, 306
- angr.state_plugins.history
 - module, 267
- angr.state_plugins.inspect
 - module, 233
- angr.state_plugins.javavm_classloader
 - module, 294
- angr.state_plugins.jni_references
 - module, 296
- angr.state_plugins.libc
 - module, 236
- angr.state_plugins.light_registers
 - module, 266
- angr.state_plugins.log
 - module, 262
- angr.state_plugins.loop_data
 - module, 291
- angr.state_plugins.plugin
 - module, 231
- angr.state_plugins.posix
 - module, 240
- angr.state_plugins.preconstrainer
 - module, 282
- angr.state_plugins.scratch
 - module, 280
- angr.state_plugins.sim_action
 - module, 467
- angr.state_plugins.sim_action_object
 - module, 468
- angr.state_plugins.sim_event
 - module, 469
- angr.state_plugins.solver
 - module, 254
- angr.state_plugins.symbolizer
 - module, 307
- angr.state_plugins.trace_additions
 - module, 273
- angr.state_plugins.uc_manager
 - module, 279
- angr.state_plugins.unicorn_engine
 - module, 284
- angr.state_plugins.view
 - module, 297

module, 309
 angr.storage
 module, 309
 angr.storage.file
 module, 314
 angr.storage.memory_mixins
 module, 336
 angr.storage.memory_mixins.actions_mixin
 module, 342
 angr.storage.memory_mixins.address_concretization_mixin
 module, 344
 angr.storage.memory_mixins.bvv_conversion_mixin
 module, 341
 angr.storage.memory_mixins.clouseau_mixin
 module, 346
 angr.storage.memory_mixins.conditional_store_mixin
 module, 346
 angr.storage.memory_mixins.convenient_mappings_mixin
 module, 348
 angr.storage.memory_mixins.default_filler_mixin
 module, 340
 angr.storage.memory_mixins.dirty_addrs_mixin
 module, 344
 angr.storage.memory_mixins.hex_dumper_mixin
 module, 341
 angr.storage.memory_mixins.javavm_memory
 module, 376
 angr.storage.memory_mixins.javavm_memory.javavm_memory
 module, 376
 angr.storage.memory_mixins.keyvalue_memory
 module, 375
 angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory
 module, 375
 angr.storage.memory_mixins.label_merger_mixin
 module, 347
 angr.storage.memory_mixins.multi_value_merger_mixin
 module, 352
 angr.storage.memory_mixins.name_resolution_mixin
 module, 339
 angr.storage.memory_mixins.paged_memory
 module, 353
 angr.storage.memory_mixins.paged_memory.page_handlers_mixin
 module, 357
 angr.storage.memory_mixins.paged_memory.paged_memory
 module, 353
 angr.storage.memory_mixins.paged_memory.pages
 module, 359
 angr.storage.memory_mixins.paged_memory.pages.addressing
 module, 361
 angr.storage.memory_mixins.paged_memory.pages.history_tracking_mixin
 module, 361
 angr.storage.memory_mixins.paged_memory.pages.isolation
 module, 361
 angr.storage.memory_mixins.paged_memory.pages.list_page
 module, 362
 angr.storage.memory_mixins.paged_memory.pages.multi_values
 module, 350
 angr.storage.memory_mixins.paged_memory.pages.mv_list_page
 module, 348
 angr.storage.memory_mixins.paged_memory.pages.permissions
 module, 360
 angr.storage.memory_mixins.paged_memory.pages.refcount_mixin
 module, 359
 angr.storage.memory_mixins.paged_memory.pages.ultra_page
 module, 364
 angr.storage.memory_mixins.paged_memory.privileged_mixin
 module, 359
 angr.storage.memory_mixins.paged_memory.stack_allocation_mixin
 module, 358
 angr.storage.memory_mixins.regioned_memory
 module, 365
 angr.storage.memory_mixins.regioned_memory.abstract_addressing
 module, 371
 angr.storage.memory_mixins.regioned_memory.abstract_merger
 module, 373
 angr.storage.memory_mixins.regioned_memory.region_category
 module, 370
 angr.storage.memory_mixins.regioned_memory.region_data
 module, 368
 angr.storage.memory_mixins.regioned_memory.region_meta_mixin
 module, 371
 angr.storage.memory_mixins.regioned_memory.regioned_addressing
 module, 373
 angr.storage.memory_mixins.regioned_memory.regioned_memory
 module, 365
 angr.storage.memory_mixins.regioned_memory.static_find_mixin
 module, 371
 angr.storage.memory_mixins.simple_interface_mixin
 module, 342
 angr.storage.memory_mixins.simplification_mixin
 module, 347
 angr.storage.memory_mixins.size_resolution_mixin
 module, 343
 angr.storage.memory_mixins.slotted_memory
 module, 374
 angr.storage.memory_mixins.smart_find_mixin
 module, 340
 angr.storage.memory_mixins.symbolic_merger_mixin
 module, 343
 angr.storage.memory_mixins.top_merger_mixin
 module, 352
 angr.storage.memory_mixins.underconstrained_mixin
 module, 342
 angr.storage.memory_mixins.unwrapper_mixin
 module, 347
 angr.storage.memory_object
 module, 334
 angr.storage.pcap

- module, 335
- angr.utils
 - module, 893
- angr.utils.algo
 - module, 894
- angr.utils.constants
 - module, 894
- angr.utils.cowdict
 - module, 894
- angr.utils.dynamic_dictlist
 - module, 894
- angr.utils.enums_conv
 - module, 895
- angr.utils.env
 - module, 895
- angr.utils.formatting
 - module, 901
- angr.utils.graph
 - module, 895
- angr.utils.lazy_import
 - module, 899
- angr.utils.library
 - module, 900
- angr.utils.loader
 - module, 899
- angr.utils.mp
 - module, 902
- angr.utils.timing
 - module, 901
- angr.vaults
 - module, 621
- AngrAnalysisError, 903
- AngrAnnotatedCFGError, 903
- AngrAssemblyError, 904
- AngrBackwardSlicingError, 903
- AngrBladeError, 903
- AngrBladeSimProcError, 903
- AngrCallableError, 904
- AngrCallableMultistateError, 904
- AngrCFGError, 904
- AngrCorruptDBError, 905
- AngrDataGraphError, 904
- AngrDB (*class in angr.angrdb.db*), 676
- AngrDBError, 905
- AngrDDGError, 904
- AngrDelayJobNotice, 904
- AngrDirectorError, 905
- AngrError, 903
- AngrExitError, 903
- AngrExplorationTechniqueError, 905
- AngrExplorerError, 905
- AngrForwardAnalysisError, 904
- AngrGirlScoutError, 903
- AngrIncompatibleDBError, 905

- AngrIncongruencyError, 904
- AngrInvalidArgumentError, 903
- AngrJobMergingFailureNotice, 904
- AngrJobWideningFailureNotice, 904
- AngrLifterError, 903
- AngrLoopAnalysisError, 904
- AngrMissingTypeError, 904
- AngrNoPluginError, 908
- AngrObjectFactory (*class in angr.factory*), 216
- AngrPathError, 903
- AngrSimOSError, 904
- AngrSkipJobNotice, 904
- AngrSurveyorError, 903
- AngrSyscallError, 904
- AngrTracerError, 905
- AngrTypeError, 904
- AngrUnsupportedSyscallError, 907
- AngrValueError, 903
- AngrVariableRecoveryError, 905
- AngrVaultError, 903
- AngrVFGError, 904
- AngrVFGRestartAnalysisNotice, 904
- annotate_mv_with_def()
 - (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState* method), 812
- annotate_mv_with_def()
 - (*angr.analyses.reaching_definitions.ReachingDefinitionsState* method), 782
- annotate_with_def()
 - (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 763
- annotate_with_def()
 - (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState* method), 812
- annotate_with_def()
 - (*angr.analyses.reaching_definitions.ReachingDefinitionsState* method), 782
- annotate_with_def()
 - (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* static method), 599
- annotate_with_def()
 - (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 579
- annotate_with_variables()
 - (*angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase* static method), 825
- annotated_cfg() (*angr.analyses.backward_slice.BackwardSlice* method), 632
- AnnotatedCFG (*class in angr.annocfg*), 881
- AnnotatedVariable (*class in angr.analyses.loop_analysis*), 846
- ansi_color() (*in module angr.utils.formatting*), 901
- append_data() (*angr.analyses.reassembler.Reassembler* method), 867

append_procedure() (angr.analyses.reassembler.Reassembler method), 866
 append_state() (angr.analyses.vfg.VFGNode method), 852
 append_statement() (in module angr.analyses.decompiler.utils), 745
 apply() (angr.analyses.cfg.cfg_fast.FunctionCallEdge method), 654
 apply() (angr.analyses.cfg.cfg_fast.FunctionEdge method), 653
 apply() (angr.analyses.cfg.cfg_fast.FunctionFakeRetEdge method), 655
 apply() (angr.analyses.cfg.cfg_fast.FunctionReturnEdge method), 655
 apply() (angr.analyses.cfg.cfg_fast.FunctionTransitionEdge method), 654
 apply() (angr.calling_conventions.AllocHelper method), 485
 apply() (angr.sim_manager.SimulationManager method), 388
 apply() (angr.SimulationManager method), 176
 apply_at_callsite() (angr.analyses.reaching_definitions.function_handler.FunctionEffect attribute), 803
 apply_definition() (angr.knowledge_plugins.functions.function_handler.FunctionEffect attribute), 500
 apply_function_edges() (angr.analyses.cfg.cfg_fast.CFGJob method), 656
 apply_patches_to_binary() (angr.knowledge_plugins.patches.PatchManager method), 525
 apply_patches_to_state() (angr.knowledge_plugins.patches.PatchManager method), 525
 arch (angr.analyses.cfg.cfg_arch_options.CFGArchOptions attribute), 660
 arch (angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableResolver attribute), 668
 arch (angr.analyses.decompiler.ccall_rewriters.rewriter_base.CallingConventionRewriter attribute), 695
 arch (angr.analyses.reaching_definitions.engine_ail.SimEngine attribute), 818
 arch (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762
 arch (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState attribute), 811
 arch (angr.analyses.reaching_definitions.ReachingDefinitionSite attribute), 781
 arch (angr.analyses.reaching_definitions.Register attribute), 772
 arch (angr.Block attribute), 170
 arch (angr.block.Block attribute), 221
 arch (angr.block.DisassemblerBlock attribute), 220
 ARCH (angr.calling_conventions.SimCCArch64 attribute), 498
 ARCH (angr.calling_conventions.SimCCArch64LinuxSyscall attribute), 498
 ARCH (angr.calling_conventions.SimCCAMD64LinuxSyscall attribute), 496
 ARCH (angr.calling_conventions.SimCCAMD64WindowsSyscall attribute), 497
 ARCH (angr.calling_conventions.SimCCARM attribute), 497
 ARCH (angr.calling_conventions.SimCCARMHF attribute), 497
 ARCH (angr.calling_conventions.SimCCARMLinuxSyscall attribute), 498
 ARCH (angr.calling_conventions.SimCCCdecl attribute), 493
 ARCH (angr.calling_conventions.SimCCMicrosoftAMD64 attribute), 494
 ARCH (angr.calling_conventions.SimCCMicrosoftFastcall attribute), 494
 ARCH (angr.calling_conventions.SimCCN64 attribute), 500
 ARCH (angr.calling_conventions.SimCCN64LinuxSyscall attribute), 500
 ARCH (angr.calling_conventions.SimCCO32 attribute), 499
 ARCH (angr.calling_conventions.SimCCO32LinuxSyscall attribute), 499
 ARCH (angr.calling_conventions.SimCCPowerPC attribute), 501
 ARCH (angr.calling_conventions.SimCCPowerPC64 attribute), 501
 ARCH (angr.calling_conventions.SimCCPowerPC64LinuxSyscall attribute), 502
 ARCH (angr.calling_conventions.SimCCPowerPCLinuxSyscall attribute), 501
 ARCH (angr.calling_conventions.SimCCRISCV64LinuxSyscall attribute), 499
 ARCH (angr.calling_conventions.SimCCS390X attribute), 503
 ARCH (angr.calling_conventions.SimCCS390XLinuxSyscall attribute), 503
 ARCH (angr.calling_conventions.SimCCSoot attribute), 502
 ARCH (angr.calling_conventions.SimCCSystemVAMD64 attribute), 496
 ARCH (angr.calling_conventions.SimCCX86LinuxSyscall attribute), 495
 ARCH (angr.calling_conventions.SimCCX86WindowsSyscall attribute), 495
 arch (angr.engines.pcode.lifter.IRSB attribute), 437
 arch (angr.engines.pcode.lifter.Lifter attribute), 440
 arch (angr.engines.pcode.lifter.PcodeDisassemblerBlock attribute), 435

arch (angr.engines.pcode.lifter.PcodeLifter attribute), 442
 arch (angr.knowledge_plugins.key_definitions.atoms.Register attribute), 591
 arch (angr.knowledge_plugins.key_definitions.live_definition.LiveDefinition attribute), 598
 arch (angr.knowledge_plugins.key_definitions.LiveDefinition attribute), 577
 arch (angr.procedures.stubs.format_parser.FormatParser attribute), 475
 arch (angr.procedures.stubs.format_parser.ScanfFormatParser attribute), 476
 arch (angr.Project attribute), 164
 arch (angr.project.Project attribute), 214
 arch (angr.sim_procedure.SimProcedure attribute), 472
 arch (angr.sim_state.SimState property), 226
 ARCH (angr.SimCC attribute), 185
 arch (angr.SimState property), 182
 arch_overrideable() (in module angr.sim_state), 224
 ARCHES (angr.analyses.decompiler.optimization_passes.base_ptr_save_simplifier.BasePointerSaveSimplifier attribute), 707
 ARCHES (angr.analyses.decompiler.optimization_passes.const_derefs.ConstantDereferencesSimplifier attribute), 704
 ARCHES (angr.analyses.decompiler.optimization_passes.div_simplifier.DivSimplifier attribute), 708
 ARCHES (angr.analyses.decompiler.optimization_passes.expr_op_swapper.ExprOpSwapper attribute), 713
 ARCHES (angr.analyses.decompiler.optimization_passes.ite_expr_converter.IteExprConverter attribute), 709
 ARCHES (angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier.LoweredSwitchSimplifier attribute), 710
 ARCHES (angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifier attribute), 711
 ARCHES (angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifier attribute), 711
 ARCHES (angr.analyses.decompiler.optimization_passes.optimization_pass_base.OptimizationPass attribute), 705
 ARCHES (angr.analyses.decompiler.optimization_passes.optimization_pass_base.OptimizationPass attribute), 706
 ARCHES (angr.analyses.decompiler.optimization_passes.optimization_pass_base.OptimizationPass attribute), 707
 ARCHES (angr.analyses.decompiler.optimization_passes.register_save_area_simplifier.RegisterSaveAreaSimplifier attribute), 713
 ARCHES (angr.analyses.decompiler.optimization_passes.ret_addr_save_simplifier.RetAddrSaveSimplifier attribute), 714
 ARCHES (angr.analyses.decompiler.optimization_passes.stack_canary_simplifier.StackCanarySimplifier attribute), 707
 ARCHES (angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_simplifier.X86GccGetPcSimplifier attribute), 714
 arg_list (angr.analyses.decompiler.structured_codegen.c.CFunction attribute), 495
 arg_list (angr.analyses.decompiler.structured_codegen.c.CFunction attribute), 729
 arg_locs() (angr.calling_conventions.SimCC method), 491
 arg_locs() (angr.SimCC method), 186
 ARG_REGS (angr.calling_conventions.SimCC attribute), 489
 ARG_REGS (angr.calling_conventions.SimCCArch64 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCArch64LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCAMD64LinuxSyscall attribute), 496
 ARG_REGS (angr.calling_conventions.SimCCAMD64WindowsSyscall attribute), 497
 ARG_REGS (angr.calling_conventions.SimCCARM attribute), 497
 ARG_REGS (angr.calling_conventions.SimCCARMHF attribute), 497
 ARG_REGS (angr.calling_conventions.SimCCARMLinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCCdecl attribute), 493
 ARG_REGS (angr.calling_conventions.SimCCMicrosoftAMD64 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCMicrosoftFastcall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCN64 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCN64LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCO32 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCO32LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCPowerPC attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCPowerPC64 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCPowerPC64LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCPowerPCLinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCRISCV64LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCS390X attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCS390XLinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCSoot attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCSystemVAMD64 attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCX86LinuxSyscall attribute), 498
 ARG_REGS (angr.calling_conventions.SimCCX86WindowsSyscall attribute), 498
 ARG_REGS (angr.engines.pcode.cc.SimCCM68k attribute), 465

ARG_REGS (*angr.engines.pcode.cc.SimCCPARISC* attribute), 466
 ARG_REGS (*angr.engines.pcode.cc.SimCCPowerPC* attribute), 466
 ARG_REGS (*angr.engines.pcode.cc.SimCCRISCV* attribute), 465
 ARG_REGS (*angr.engines.pcode.cc.SimCCSH4* attribute), 465
 ARG_REGS (*angr.engines.pcode.cc.SimCCSPARC* attribute), 465
 ARG_REGS (*angr.engines.pcode.cc.SimCCXtensa* attribute), 466
 ARG_REGS (*angr.SimCC* attribute), 185
 arg_session (*angr.procedures.stubs.format_parser.FormatParser* attribute), 475
 arg_session (*angr.procedures.stubs.format_parser.ScanfParser* attribute), 476
 arg_session (*angr.sim_procedure.SimProcedure* attribute), 472
 arg_session() (*angr.calling_conventions.SimCC* method), 490
 arg_session() (*angr.SimCC* method), 186
 args (*angr.analyses.decompiler.structured_codegen.c.CFunctionCall* attribute), 733
 args (*angr.sim_type.SimTypeCppFunction* attribute), 516
 args (*angr.utils.mp.Closure* attribute), 902
 args_atoms (*angr.analyses.reaching_definitions.function_handler.FunctionCallData* attribute), 805
 args_atoms (*angr.analyses.reaching_definitions.FunctionCallData* attribute), 791
 args_defns (*angr.analyses.reaching_definitions.dep_graph.FunctionCallRelationships* attribute), 798
 ARGS_MISMATCH (*angr.procedures.stubs.format_parser.FormatParser* attribute), 475
 ARGS_MISMATCH (*angr.sim_procedure.SimProcedure* attribute), 472
 ARGS_MISMATCH (*angr.SimProcedure* attribute), 159
 args_values (*angr.analyses.reaching_definitions.function_handler.FunctionCallData* attribute), 805
 args_values (*angr.analyses.reaching_definitions.FunctionCallData* attribute), 791
 ArgSession (*angr.calling_conventions.SimCCMicrosoftAM386* attribute), 494
 ArgSession (*angr.calling_conventions.SimCCUsercall* attribute), 493
 ArgSession (class in *angr.calling_conventions*), 488
 argument_types (*angr.sim_procedure.SimProcedure* property), 474
 argument_types (*angr.SimProcedure* property), 161
 arguments (*angr.knowledge_plugins.functions.function.Function* property), 562
 ArithmeticExpression (class in *angr.engines.light.data*), 754
 ARM (*angr.analyses.cfg.cfg_fast.ARMDecodingMode* attribute), 652
 ARMDecodingMode (class in *angr.analyses.cfg.cfg_fast*), 652
 ArmElfFastResolver (class in *angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast*), 662
 Array (class in *angr.analyses.typehoon.typeconsts*), 844
 array() (*angr.state_plugins.debug_variables.SimDebugVariable* method), 308
 array() (*angr.state_plugins.view.SimMemView* method), 314
 assembly() (*angr.analyses.reassembler.BasicBlock* method), 863
 assembly() (*angr.analyses.reassembler.Data* method), 864
 assembly() (*angr.analyses.reassembler.Instruction* method), 862
 assembly() (*angr.analyses.reassembler.Operand* method), 862
 assembly() (*angr.analyses.reassembler.Procedure* method), 863
 assembly() (*angr.analyses.reassembler.Reassembler* method), 867
 assign() (*angr.state_plugins.uc_manager.SimUCManager* method), 279
 assign_labels() (*angr.analyses.reassembler.BasicBlock* method), 864
 assign_labels() (*angr.analyses.reassembler.Data* method), 864
 assign_labels() (*angr.analyses.reassembler.Instruction* method), 862
 assign_labels() (*angr.analyses.reassembler.Procedure* method), 863
 assign_unified_variable_names() (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 570
 assign_variable_names() (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 569
 ast_argument (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.Address* attribute), 666
 ast_argument (*angr.analyses.data_dep.dep_nodes.BaseDepNode* property), 877
 AST (class in *angr.analyses.ddg*), 748
 ast_graph (*angr.analyses.ddg.DDG* property), 752
 ast_preserving_op() (in module *angr.state_plugins.sim_action_object*), 468
 ast_stripping_decorator() (in module *angr.state_plugins.sim_action_object*), 468
 ast_stripping_op() (in module *angr.state_plugins.sim_action_object*), 468
 ast_weight() (in module *angr.exploration_techniques.suggestions*), 427

[at_new_block\(\)](#) ([angr.analyses.reaching_definitions.ReachingDefinitionsModel](#) [SimType](#) attribute), 509
[method](#)), 778
[at_new_block\(\)](#) ([angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel](#) [SimStackVariable](#) attribute), 508
[method](#)), 606
[at_new_block\(\)](#) ([angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel](#) [SimMemoryObject](#) attribute), 508
[method](#)), 575
[at_new_stmt\(\)](#) ([angr.analyses.reaching_definitions.ReachingDefinitionsModel](#) [SimStackVariable](#) attribute), 508
[method](#)), 778
[at_new_stmt\(\)](#) ([angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel](#) [SimStackVariable](#) attribute), 508
[method](#)), 606
[at_new_stmt\(\)](#) ([angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel](#) [SimStackVariable](#) attribute), 508
[method](#)), 575
[atoi_dumps\(\)](#) ([angr.state_plugins.trace_additions.ChallengeNode](#) [BaseDepNode](#) (class in [angr.analyses.data_dep.dep_nodes](#)), 877
[static method](#)), 276
[atom](#) ([angr.analyses.reaching_definitions.Definition](#) [BaseGoal](#) (class in [angr.exploration_techniques.director](#)), 418
[attribute](#)), 774
[atom](#) ([angr.knowledge_plugins.key_definitions.Definition](#) [BaseLabel](#) (class in [angr.analyses.typehoon.typevars](#)), 841
[attribute](#)), 587
[atom](#) ([angr.knowledge_plugins.key_definitions.definition.DefinitionModel](#) [BaseNode](#) (class in [angr.analyses.decompiler.structuring.structurer_nodes](#)), 687
[attribute](#)), 594
[Atom](#) (class in [angr.analyses.reaching_definitions](#)), 770
[Atom](#) (class in [angr.knowledge_plugins.key_definitions.atoms](#)), [BaseOptimizationPass](#) (class in [angr.analyses.decompiler.optimization_passes.optimization_passes](#)), 705
588
[atom_hash](#) ([angr.knowledge_plugins.variables.variable_access.Access](#) [BasePointerSaveSimplifier](#) (class in [angr.analyses.decompiler.optimization_passes.base_ptr_save_simplifier](#)), 707
[attribute](#)), 565
[AtomKind](#) (class in [angr.analyses.reaching_definitions](#)), 770
[AtomKind](#) (class in [angr.knowledge_plugins.key_definitions.atoms](#)), [BaseProxiNode](#) (class in [angr.analyses.proximity_graph](#)), 872
588
[available_flavors\(\)](#) ([angr.knowledge_plugins.structured_code.manager.StructuredCodeManager](#) [BaseStructuredCodeGenerator](#) (class in [angr.analyses.decompiler.structured_codegen.base](#)), 720
[method](#)), 574
B
[b\(\)](#) ([angr.state_plugins.inspect.SimInspector](#) [BasicBlock](#) (class in [angr.analyses.reassembler](#)), 862
[method](#)), 234
[back_edges\(\)](#) ([angr.analyses.forward_analysis.visitors.function_graph.FunctionGraphVisitor](#) [BasicClarityCooperation](#) (class in [angr.storage.memory_mixins.paged_memory.pages.cooperation](#)), 362
[method](#)), 628
[back_edges\(\)](#) ([angr.analyses.forward_analysis.visitors.graph.GraphVisitor](#) [bbl_addr](#) ([angr.errors.SimError](#) attribute), 905
[method](#)), 629
[backend](#) ([angr.angrdb.models.DbObject](#) attribute), 678
[backend2name](#) ([angr.angrdb.serializers.loader.LoaderSerializer](#) [bbl_addr](#) ([angr.knowledge_plugins.key_definitions.definition.DefinitionModel](#) attribute), 593
[attribute](#)), 684
[backend_args](#) ([angr.angrdb.models.DbObject](#) [bbl_addrs](#) ([angr.state_plugins.history.SimStateHistory](#) property), 269
[attribute](#)), 678
[backpatch\(\)](#) ([angr.analyses.typehoon.translator.TypeTranslator](#) [bck_chunk\(\)](#) ([angr.PTChunk](#) method), 210
[method](#)), 837
[BackwardSlice](#) ([angr.analyses.analysis.KnownAnalysesPlugin](#) [bck_chunk\(\)](#) ([angr.state_plugins.heap.heap_ptmalloc.PTChunk](#) method), 303
[attribute](#)), 623
[BackwardSlice](#) (class in [angr.analyses.backward_slice](#)), [BEFORE_REGION_IDENTIFICATION](#) ([angr.analyses.decompiler.optimization_passes.optimization_passes](#) attribute), 705
631
[BadJumpkindNotification](#), 879
[BadStatesDropper](#) (class in [angr.distributed.worker](#)), [BehaviorFactory](#) (class in [angr.engines.pcode.behavior](#)), 464
909

behaviors (angr.engines.pcode.lifter.IRSB attribute), 438
 behaviors (angr.engines.pcode.lifter.PcodeBasicBlockLifter attribute), 442
 binary (angr.knowledge_plugins.functions.function.Function property), 559
 binary_insert() (in module angr.utils.algo), 894
 binary_name (angr.knowledge_plugins.functions.function.Function attribute), 556
 binary_name (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564
 BinaryError, 860
 BinaryOptimizer (angr.analyses.analysis.KnownAnalysesPlugin attribute), 623
 BinaryOptimizer (class in angr.analyses.binary_optimizer), 870
 BinDiff (angr.analyses.analysis.KnownAnalysesPlugin attribute), 623
 BinDiff (class in angr.analyses.bindiff), 635
 binop_operators (angr.analyses.decompiler.decompilation_block_addr (angr.knowledge_plugins.functions.function.Function attribute), 700
 bitlen (angr.analyses.stack_pointer_tracker.Register attribute), 821
 bits (angr.analyses.propagator.values.Top property), 756
 bits (angr.analyses.reaching_definitions.Atom property), 770
 bits (angr.analyses.typehoon.lifter.TypeLifter attribute), 832
 bits (angr.analyses.typehoon.typevars.HasField attribute), 842
 bits (angr.analyses.variable_recovery.engine_base.RichR property), 831
 bits (angr.engines.light.data.RegisterOffset property), 755
 bits (angr.knowledge_plugins.key_definitions.atoms.Atom property), 588
 bits (angr.sim_variable.SimMemoryVariable property), 507
 bits (angr.sim_variable.SimRegisterVariable property), 506
 Blade (class in angr), 167
 Blade (class in angr.blade), 879
 blank_state() (angr.factory.AngrObjectFactory method), 217
 blob (angr.angrdb.models.DbCFGModel attribute), 679
 blob (angr.angrdb.models.DbFunction attribute), 679
 blob (angr.angrdb.models.DbVariableCollection attribute), 680
 blob (angr.angrdb.models.DbXRefs attribute), 681
 block (angr.analyses.decompiler.structured_codegen.c.CAILBlock attribute), 730
 Block (angr.analyses.reaching_definitions.subject.SubjectType attribute), 817
 block (angr.analyses.variable_recovery.engine_ail.SimEngineVRAIL attribute), 831
 block (angr.knowledge_plugins.cfg.cfg_node.CFGNode property), 549
 block (angr.knowledge_plugins.cfg.CFGNode property), 530
 Block (class in angr), 170
 Block (class in angr.block), 221
 block() (angr.analyses.decompiler.clinic.Clinic method), 697
 block() (angr.factory.AngrObjectFactory method), 220
 block() (angr.sim_state.SimState method), 226
 block() (angr.SimState method), 183
 block_addr (angr.analyses.decompiler.clinic.DataRefDesc attribute), 696
 block_addr (angr.analyses.decompiler.region_simplifiers.expr_folding.Expr attribute), 718
 block_addr (angr.analyses.decompiler.region_simplifiers.expr_folding.State attribute), 718
 block_addr (angr.knowledge_plugins.functions.function.Function attribute), 794
 block_addr (angr.code_location.CodeLocation attribute), 617
 block_addr (angr.knowledge_plugins.xrefs.xref.XRef attribute), 614
 block_addr (angr.state_plugins.unicorn_engine.BlockDetails attribute), 285
 block_addr (angr.state_plugins.unicorn_engine.StopDetails attribute), 287
 block_addrs (angr.knowledge_plugins.functions.function.Function property), 557
 block_addrs_set (angr.knowledge_plugins.functions.function.Function property), 557
 block_count (angr.state_plugins.history.SimStateHistory property), 269
 block_id (angr.analyses.cfg.cfg_emulated.CFGJob property), 644
 block_id (angr.analyses.vfg.PendingJob attribute), 850
 block_id (angr.analyses.vfg.VFGJob property), 849
 block_id (angr.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 548
 block_id (angr.knowledge_plugins.cfg.CFGNode attribute), 529
 block_idx (angr.analyses.decompiler.region_simplifiers.expr_folding.Expr attribute), 718
 block_idx (angr.analyses.decompiler.region_simplifiers.expr_folding.State attribute), 718
 block_idx (angr.analyses.decompiler.structured_codegen.c.CLabel attribute), 734
 block_idx (angr.code_location.CodeLocation attribute), 617
 block_matches (angr.analyses.bindiff.FunctionDiff property), 634
 BLOCK_MAX_SIZE (angr.Block attribute), 170

BLOCK_MAX_SIZE (*angr.block.Block* attribute), 221
 block_similarity() (*angr.analyses.bindiff.FunctionDiff* method), 635
 block_size (*angr.state_plugins.unicorn_engine.BlockDetails* attribute), 285
 block_size (*angr.state_plugins.unicorn_engine.StopDetails* attribute), 287
 block_trace_ind (*angr.state_plugins.unicorn_engine.BlockDetails* attribute), 285
 BlockCache (class in *angr.analyses.decompiler.clinic*), 696
 BlockDetails (class in *angr.state_plugins.unicorn_engine*), 285
 BlockID (class in *angr.analyses.cfg.cfg_job_base*), 660
 BlockLocator (class in *angr.analyses.decompiler.optimization_passes.iter_expr_converter*), 708
 BlockNode (class in *angr.codenode*), 883
 blocks (*angr.knowledge_plugins.functions.function.Function* property), 557
 blocks_by_addr (*angr.analyses.decompiler.optimization_passes.optimizer* property), 706
 blocks_by_addr_and_idx (*angr.analyses.decompiler.optimization_passes.optimizer* property), 706
 blocks_probably_identical() (*angr.analyses.bindiff.FunctionDiff* method), 635
 BLOCKS_THRESHOLD (*angr.analyses.binary_optimizer.BinaryOptimizer* attribute), 870
 blocks_with_differing_constants (*angr.analyses.bindiff.BinDiff* property), 636
 blocks_with_differing_constants (*angr.analyses.bindiff.FunctionDiff* property), 634
 BlockSimplifier (class in *angr.analyses.decompiler.block_simplifier*), 694
 BlockStart (class in *angr.analyses.disassembly*), 857
 BlockWalker (class in *angr.analyses.decompiler.optimization_passes.codegen*), 704
 body (*angr.analyses.decompiler.structured_codegen.c.CDoWhileLoop* attribute), 730
 body (*angr.analyses.decompiler.structured_codegen.c.CForLoop* attribute), 731
 body (*angr.analyses.decompiler.structured_codegen.c.CWhileLoop* attribute), 730
 booleanize() (*angr.engines.pcode.behavior.OpBehavior* class method), 446
 both_iter (*angr.calling_conventions.ArgSession* attribute), 488
 both_iter (*angr.calling_conventions.SimCC.ArgSession* attribute), 490
 both_iter (*angr.SimCC.ArgSession* attribute), 186
 Bottom (class in *angr.analyses.propagator.values*), 756
 BottomType (class in *angr.analyses.stack_pointer_tracker*), 821
 BottomType (class in *angr.analyses.typehoon.typeconstrs*), 843
 BoyScout (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 624
 BoyScout (class in *angr.analyses.boyscout*), 636
 BP (class in *angr*), 161
 BP (class in *angr.state_plugins.inspect*), 233
 BP_AFTER (*angr.state_plugins.inspect.SimInspector* attribute), 233
 BP_BEFORE (*angr.state_plugins.inspect.SimInspector* attribute), 233
 BP_BOTH (*angr.state_plugins.inspect.SimInspector* attribute), 233
 bp_on_stack (*angr.knowledge_plugins.functions.function.Function* attribute), 556
 bp_on_stack (*angr.knowledge_plugins.functions.soot_function.SootFunction* attribute), 564
 branch() (*angr.analyses.ddg.LiveDefinitions* method), 740
 BreakNode (class in *angr.analyses.decompiler.structuring.structurer_nodes*), 689
 bss_memory_read_hook() (*angr.analyses.cfg.indirect_jump_resolvers.jumtable.BSSHHook* method), 669
 bss_memory_write_hook() (*angr.analyses.cfg.indirect_jump_resolvers.jumtable.BSSHHook* method), 669
 BSSHHook (class in *angr.analyses.cfg.indirect_jump_resolvers.jumtable*), 669
 Bucketizer (class in *angr.exploration_techniques*), 406
 Bucketizer (class in *angr.exploration_techniques.bucketizer*), 427
 build() (*angr.analyses.disassembly.Operand* static method), 858
 bv_slice() (in module *angr.storage.memory_object*), 335
 bvslice (*angr.state_plugins.solver.SimSolver* method), 256
 byte_string (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* attribute), 548
 byte_string (*angr.knowledge_plugins.cfg.CFGNode* attribute), 528
 bytes (*angr.Block* property), 170
 bytes (*angr.block.Block* property), 221
 bytes_at() (*angr.storage.memory_object.SimMemoryObject* method), 334
 bytes_offset (*angr.engines.pcode.lifter.Lifter* attribute), 440
 bytes_offset (*angr.engines.pcode.lifter.PcodeLifter* attribute), 442

bytestr (*angr.codenode.BlockNode* attribute), 883

C

- `c_args_as_atoms()` (*angr.analyses.reaching_definitions.function_handler.FunctionHandler* static method), 809
- `c_args_as_atoms()` (*angr.analyses.reaching_definitions.FunctionHandler* static method), 789
- `c_repr()` (*angr.analyses.decompiler.structured_codegen.c.CConstruct* method), 728
- `c_repr()` (*angr.analyses.typehoon.translator.SimTypeTempRef* method), 837
- `c_repr()` (*angr.sim_type.SimStruct* method), 517
- `c_repr()` (*angr.sim_type.SimType* method), 509
- `c_repr()` (*angr.sim_type.SimTypeArray* method), 514
- `c_repr()` (*angr.sim_type.SimTypeBottom* method), 510
- `c_repr()` (*angr.sim_type.SimTypeFunction* method), 515
- `c_repr()` (*angr.sim_type.SimTypeInt* method), 512
- `c_repr()` (*angr.sim_type.SimTypePointer* method), 513
- `c_repr()` (*angr.sim_type.SimTypeRef* method), 520
- `c_repr()` (*angr.sim_type.SimTypeReference* method), 513
- `c_repr()` (*angr.sim_type.SimUnion* method), 518
- `c_repr()` (*angr.sim_type.TypeRef* method), 510
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CAILBlock* method), 730
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CAssignment* method), 732
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CBinaryOp* method), 738
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CBreak* method), 732
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CConstant* method), 739
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CConstruct* method), 728
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CContinue* method), 732
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CExprExpression* method), 740
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CForLoop* method), 730
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CFakeVariable* method), 735
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CForLoop* method), 731
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CFunction* method), 729
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CFunctionCall* method), 733
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CGoto* method), 734
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CIfElse* method), 731
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CIfElse* method), 731
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CInclude* method), 736
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CITE* method), 740
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CLabel* method), 734
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CMulti* method), 740
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CRegister* method), 739
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CReturn* method), 734
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CState* method), 730
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CStruct* method), 735
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CSwitch* method), 732
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CType* method), 738
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CUnary* method), 737
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CUnsu* method), 734
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CVariable* method), 736
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CVariable* method), 737
- `c_repr_chunks()` (*angr.analyses.decompiler.structured_codegen.c.CWhile* method), 730
- `c_return_as_atoms()` (*angr.analyses.reaching_definitions.function_handler.FunctionHandler* static method), 809
- `c_return_as_atoms()` (*angr.analyses.reaching_definitions.FunctionHandler* static method), 789
- `cache_key` (*angr.storage.memory_object.SimMemoryObject* property), 334
- `CAILBlock` (class in *angr.analyses.decompiler.structured_codegen.c*), 729
- `calc_size()` (*angr.calling_conventions.AllocHelper* class method), 485
- `call()` (*angr.sim_procedure.SimProcedure* method), 473
- `call()` (*angr.sim_procedure.SimProcedure* method), 160
- `call()` (*angr.state_plugins.callstack.CallStack* method), 266
- `call_c()` (*angr.callable.Callable* method), 522
- `call_site_addr` (*angr.analyses.cfg.cfg_fast.FunctionReturn* attribute), 652
- `call_stack` (*angr.analyses.cfg.cfg_job_base.CFGJobBase* property), 661
- `call_stack` (*angr.analyses.vfg.PendingJob* attribute),

850

`call_stack_copy()` (*angr.analyses.cfg.cfg_job_base.CFGJobBase* static method), 661

`call_state()` (*angr.factory.AngrObjectFactory* static method), 218

`call_string` (*angr.code_location.ExternalCodeLocation* attribute), 617

`callable` (*angr.knowledge_plugins.functions.function.Function* property), 562

`Callable` (class in *angr.callable*), 521

`callable()` (*angr.factory.AngrObjectFactory* method), 219

`CallAnalysis` (class in *angr.analyses.vfg*), 850

`CALLEE_CLEANUP` (*angr.calling_conventions.SimCC* attribute), 489

`CALLEE_CLEANUP` (*angr.calling_conventions.SimCCStdcall* attribute), 493

`CALLEE_CLEANUP` (*angr.SimCC* attribute), 185

`callee_func` (*angr.analyses.decompiler.structured_codegen.c.CFunction* attribute), 733

`callee_func_addr` (*angr.analyses.cfg.cfg_fast.FunctionReachingDefinitions* attribute), 652

`callee_func_addr` (*angr.analyses.reaching_definitions.call_trace* attribute), 793

`callee_target` (*angr.analyses.decompiler.structured_codegen.c.CFunction* attribute), 733

`CalleeCleanupFinder` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623

`CalleeCleanupFinder` (class in *angr.analyses.callee_cleanup_finder*), 870

`caller_func_addr` (*angr.analyses.cfg.cfg_fast.FunctionReachingDefinitions* attribute), 652

`caller_func_addr` (*angr.analyses.reaching_definitions.call_trace* attribute), 793

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCC* attribute), 489

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCARMv7* attribute), 496

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCARMv8* attribute), 497

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCARMv8_32* attribute), 497

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCAArch64* attribute), 493

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCNeon* attribute), 500

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCO32* attribute), 499

`CALLER_SAVED_REGS` (*angr.calling_conventions.SimCCSystemZ* attribute), 496

`CALLER_SAVED_REGS` (*angr.SimCC* attribute), 185

`caller_saved_regs_as_atoms()` (*angr.analyses.reaching_definitions.function_handler.FunctionHandler* static method), 809

`CallerSavedRegsAsAtoms` (*angr.analyses.reaching_definitions.FunctionHandler* static method), 789

`caller_will_handle_single_ret` (*angr.analyses.reaching_definitions.function_handler.FunctionHandler* attribute), 805

`caller_will_handle_single_ret` (*angr.analyses.reaching_definitions.FunctionCallData* attribute), 791

`CallFunctionGoal` (class in *angr.exploration_techniques*), 401

`CallFunctionGoal` (class in *angr.exploration_techniques.director*), 419

`callgraph` (*angr.knowledge_base.knowledge_base.KnowledgeBase* property), 523

`callgraph` (*angr.KnowledgeBase* property), 211

`CallGraphVisitor` (class in *angr.analyses.forward_analysis.visitors.call_graph*), 626

`calling_convention` (*angr.knowledge_plugins.functions.function.Function* attribute), 556

`calling_convention` (*angr.knowledge_plugins.functions.soot_function.SootFunction* attribute), 564

`CallingConvention` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 624

`CallingConventionAnalysis` (class in *angr.analyses.calling_convention*), 637

`calloc()` (*angr.SimHeapPTMalloc* method), 207

`calloc()` (*angr.state_plugins.heap.heap_libc.SimHeapLibc* method), 302

`calloc()` (*angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc* method), 305

`callout_calls` (*angr.knowledge_plugins.functions.function.Function* property), 559

`CallProxiNode` (class in *angr.analyses.proximity_graph*), 873

`CallProxiNode` (in module *angr.analyses.decompiler.utils*), 748

`callsite` (*angr.analyses.reaching_definitions.dep_graph.FunctionCallRelationship* attribute), 798

`callsite` (class in *angr.analyses.reaching_definitions.call_trace*), 793

`callsite_codeloc` (*angr.analyses.reaching_definitions.function_handler.FunctionHandler* attribute), 804

`callsite_codeloc` (*angr.analyses.reaching_definitions.FunctionCallData* attribute), 791

`callsite_repr()` (*angr.analyses.cfg.cfg_job_base.BlockID* method), 660

`callsite_repr()` (*angr.analyses.cfg.cfg_job_base.FunctionKey* method), 661

`CallSiteFact` (class in *angr.analyses.calling_convention*), 636

`CallSiteHandler` (class in *angr.analyses.calling_convention*), 636

`angr.analyses.decompiler.callsite_maker`), 695
CallSitePrototypes (class in `angr.knowledge_plugins.callsite_prototypes`), 525
`callsites` (`angr.analyses.reaching_definitions.call_trace.CallTrace` attribute), 794
`callsites_to()` (`angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis` method), 798
`callsites_to()` (`angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis` method), 778
`callstack` (`angr.sim_state.SimState` attribute), 225
`callstack` (`angr.SimState` attribute), 181
CallStack (class in `angr.state_plugins.callstack`), 263
`callstack_key` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` static method), 710
`callstack_key` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` property), 550
`callstack_key` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` property), 549
`callstack_key` (`angr.knowledge_plugins.cfg.CFGNode` property), 530
`callstack_key` (`angr.knowledge_plugins.cfg.CFGNode` property), 529
`callstack_repr()` (`angr.analyses.vfg.VFGJob` method), 849
CallStackAction (class in `angr.state_plugins.callstack`), 266
CallTrace (`angr.analyses.reaching_definitions.subject.SubjectCategory` attribute), 817
CallTrace (class in `angr.analyses.reaching_definitions.call_trace`), 794
CallTracingFilter (class in `angr.analyses.veritestng`), 847
`can_call_same_name()` (`angr.analyses.identifier.identify.Identifier` method), 845
`candidate_names` (`angr.sim_variable.SimVariable` attribute), 505
`capstone` (`angr.Block` property), 170
`capstone` (`angr.block.Block` property), 221
CapstoneBlock (class in `angr.block`), 220
CapstoneInsn (class in `angr.block`), 220
`cardinality` (`angr.storage.memory_mixins.regioned_memory.abstract_memory.AbstractMemoryDescriptor` property), 371
CArrayTypeLength (class in `angr.analyses.decompiler.structured_codegen.c`), 741
CascadingConditionNode (class in `angr.analyses.decompiler.structuring.structurer_nodes`), 688
CascadingConditionTransformer (class in `angr.analyses.decompiler.region_simplifiers.cascading_condition_transformer`), 717
CascadingIfsRemover (class in `angr.analyses.decompiler.region_simplifiers.cascading_ifs_remover`), 717
Case (class in `angr.analyses.decompiler.optimization_passes.lowered_switch_cases`), 709
`case_addrs` (`angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCase` attribute), 691
`case_index` (`angr.analyses.decompiler.region_simplifiers.expr_folding.ConditionalExpression` attribute), 718
`cases` (`angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCase` attribute), 732
`cases` (`angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCase` attribute), 691
`cases` (`angr.analyses.decompiler.structuring.structurer_nodes.SwitchCase` attribute), 690
`cases_issubset()` (`angr.analyses.decompiler.optimization_passes.lowered_switch_cases` static method), 710
CAssignment (class in `angr.analyses.decompiler.structured_codegen.c`), 732
`cast_primitive()` (`angr.simos.javavm.SimJavaVM` static method), 891
`cast_to_mem()` (`angr.analyses.data_dep.dep_nodes.MemDepNode` class method), 878
CastType (`angr.state_plugins.solver.SimSolver` attribute), 259
CatchDesync (`angr.exploration_techniques.tracer.TracingMode` attribute), 414
Category (`angr.sim_variable.SimVariable` attribute), 504
category (`angr.SimFile` property), 190
category (`angr.storage.file.SimFile` property), 317
category (`angr.storage.memory_mixins.MemoryMixin` property), 336
category (`angr.storage.memory_mixins.regioned_memory.region_category` property), 370
CBinaryOp (class in `angr.analyses.decompiler.structured_codegen.c`), 737
CBreak (class in `angr.analyses.decompiler.structured_codegen.c`), 731
`cc` (`angr.analyses.reaching_definitions.function_handler.FunctionCallData` attribute), 805
`cc` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 794
`cc` (`angr.analyses.reaching_definitions.subject.SubjectCategory` property), 817
`cc` (`angr.calling_conventions.ArgSession` attribute), 488
`cc` (`angr.calling_conventions.SimCC.ArgSession` attribute), 490
`cc` (`angr.calling_conventions.UsercallArgSession` attribute), 489
`cc` (`angr.procedures.stubs.format_parser.FormatParser` attribute), 476
`cc` (`angr.procedures.stubs.format_parser.ScanfFormatParser` attribute), 476
`cc` (`angr.sim_procedure.SimProcedure` attribute), 472

`cc` (*angr.SimCC.ArgSession* attribute), 185
`cc()` (*angr.factory.AngrObjectFactory* method), 219
`CCallRewriterBase` (class in *angr.analyses.decompiler.ccall_rewriters.rewriter_base*), 695
`CClosingObject` (class in *angr.analyses.decompiler.structured_codegen.c*), 740
`CConstant` (class in *angr.analyses.decompiler.structured_codegen.c*), 738
`CConstruct` (class in *angr.analyses.decompiler.structured_codegen.c*), 728
`CContinue` (class in *angr.analyses.decompiler.structured_codegen.c*), 732
`CDG` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CDG` (class in *angr.analyses.cdg*), 675
`CDirtyExpression` (class in *angr.analyses.decompiler.structured_codegen.c*), 740
`CDoWhileLoop` (class in *angr.analyses.decompiler.structured_codegen.c*), 730
`ceiling_addr()` (*angr.analyses.cfg.cfb.CFBlanket* method), 642
`ceiling_addr()` (*angr.knowledge_plugins.functions.function_manager.FunctionManager* method), 553
`ceiling_func()` (*angr.knowledge_plugins.functions.function_manager.FunctionManager* method), 554
`ceiling_item()` (*angr.analyses.cfg.cfb.CFBlanket* method), 642
`ceiling_items()` (*angr.analyses.cfg.cfb.CFBlanket* method), 642
`CExpression` (class in *angr.analyses.decompiler.structured_codegen.c*), 729
`CFakeVariable` (class in *angr.analyses.decompiler.structured_codegen.c*), 735
`CFB` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CFBlanket` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CFBlanket` (class in *angr.analyses.cfg.cfb*), 641
`CFBlanketView` (class in *angr.analyses.cfg.cfb*), 641
`CFG` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CFG` (class in *angr.analyses.cfg.cfg*), 642
`cfg_cache` (*angr.analyses.veritesting.CallTracingFilter* attribute), 848
`cfg_cache` (*angr.analyses.veritesting.Veritesting* attribute), 848
`cfg_jumpkind_from_pb()` (in *angr.utils.enums_conv*), 895
`cfg_jumpkind_to_pb()` (in *angr.utils.enums_conv*), 895
`CFGArchOptions` (class in *angr.analyses.cfg.cfg_arch_options*), 660
`CFGBase` (class in *angr.analyses.cfg.cfg_base*), 649
`CFGEmulated` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CFGEmulated` (class in *angr.analyses.cfg.cfg_emulated*), 623
`CFGNode` (class in *angr.knowledge_plugins.cfg*), 530
`CFGNode` (class in *angr.knowledge_plugins.cfg.cfg_node*), 549
`CFGFast` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`CFGFast` (class in *angr.analyses.cfg.cfg_fast*), 656
`CFGFastSoot` (class in *angr.analyses.cfg.cfg_fast_soot*), 673
`CFGJob` (class in *angr.analyses.cfg.cfg_emulated*), 644
`CFGJob` (class in *angr.analyses.cfg.cfg_fast*), 655
`CFGJobBase` (class in *angr.analyses.cfg.cfg_job_base*), 661
`CFGJobType` (class in *angr.analyses.cfg.cfg_fast*), 655
`CFGManager` (class in *angr.knowledge_plugins.cfg*), 538
`CFGManager` (class in *angr.knowledge_plugins.cfg.cfg_manager*), 547
`CFGModel` (*angr.knowledge_plugins.cfg*), 532
`CFGModel` (class in *angr.knowledge_plugins.cfg.cfg_model*), 681
`CFGModelSerializer` (class in *angr.angrdb.serializers.cfg_model*), 681
`CFGNode` (class in *angr.knowledge_plugins.cfg*), 528
`CFGNode` (class in *angr.knowledge_plugins.cfg.cfg_node*), 547
`CFGNodeCreationFailure` (class in *angr.knowledge_plugins.cfg.cfg_node*), 547
`cfgs` (*angr.angrdb.models.DbKnowledgeBase* attribute), 678
`cfgs` (*angr.knowledge_base.knowledge_base.KnowledgeBase* attribute), 523
`cfgs` (*angr.KnowledgeBase* attribute), 211
`CFGSliceToSink` (class in *angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink*), 818
`CForLoop` (class in *angr.analyses.decompiler.structured_codegen.c*), 730
`CFunction` (class in *angr.analyses.decompiler.structured_codegen.c*), 728
`CFunctionCall` (class in *angr.analyses.decompiler.structured_codegen.c*), 732
`CGoto` (class in *angr.analyses.decompiler.structured_codegen.c*), 734
`ChainMapCOW` (class in *angr.utils.cowdict*), 894
`ChallRespInfo` (class in *angr.knowledge_plugins.chall_resp_info*), 894

angr.state_plugins.trace_additions), 274
 changed_bytes() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.PagedMemoryMixin method), 355
 changed_bytes() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.HistoryTrackingMixin method), 361
 changed_bytes() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.HistoryTrackingMixin method), 363
 changed_bytes() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.HistoryTrackingMixin method), 350
 changed_bytes() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.HistoryTrackingMixin method), 365
 changed_bytes() (angr.storage.memory_mixins.slotted_memory.slotted_memory.history_tracking_mixin.HistoryTrackingMixin method), 375
 changed_pages() (angr.storage.memory_mixins.paged_memory.paged_memory.history_tracking_mixin.HistoryTrackingMixin method), 355
 chdir() (angr.state_plugins.filesystem.SimFilesystem method), 250
 check() (angr.BP method), 161
 check() (angr.exploration_techniques.CallFunctionGoal method), 401
 check() (angr.exploration_techniques.director.BaseGoal method), 418
 check() (angr.exploration_techniques.director.CallFunctionGoal method), 419
 check() (angr.exploration_techniques.director.ExecuteAddressGoal method), 419
 check() (angr.exploration_techniques.ExecuteAddressGoal method), 400
 check() (angr.state_plugins.inspect.BP method), 233
 check_concrete_target_methods() (angr.engines.concrete.SimEngineConcrete static method), 434
 check_offset() (angr.calling_conventions.SimRegArg method), 486
 check_state() (angr.exploration_techniques.CallFunctionGoal method), 401
 check_state() (angr.exploration_techniques.director.BaseGoal method), 419
 check_state() (angr.exploration_techniques.director.CallFunctionGoal method), 420
 check_state() (angr.exploration_techniques.director.ExecuteAddressGoal method), 419
 check_state() (angr.exploration_techniques.ExecuteAddressGoal method), 401
 check_tests() (angr.analyses.identifier.identify.Identifier method), 845
 check_value_get() (angr.calling_conventions.SimFunctionCall method), 486
 check_value_set() (angr.calling_conventions.SimFunctionCall method), 486
 Chunk (class in angr.state_plugins.heap.heap_freelist), 300
 chunk_from_mem() (angr.SimHeapPTMalloc method), 207
 chunk_from_mem() (angr.state_plugins.heap.heap_freelist.SimHeapFreelist method), 301
 chunk_from_mem() (angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc method), 305
 chunks() (angr.SimHeapPTMalloc method), 206
 chunks() (angr.state_plugins.heap.heap_freelist.SimHeapFreelist method), 301
 chunks() (angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc method), 304
 CILBreak (class in angr.analyses.decompiler.structured_codegen.c), 731
 CILFileSelector (class in angr.analyses.decompiler.structured_codegen.c), 731
 CILIndexedVariableMixin (class in angr.analyses.decompiler.structured_codegen.c), 736
 CITE (class in angr.analyses.decompiler.structured_codegen.c), 739
 CLabel (class in angr.analyses.decompiler.structured_codegen.c), 734
 claripy_ast_from_ail_condition() (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 699
 claripy_ast_to_sympy_expr() (angr.analyses.decompiler.condition_processor.ConditionProcessor static method), 699
 ClassIdentifier (class in angr.analyses.class_identifier), 855
 clean() (angr.utils.cowdict.ChainMapCOW method), 894
 clean() (angr.utils.cowdict.DefaultChainMapCOW method), 894
 cleanup() (angr.analyses.cfg.cfg_fast.PendingJobs method), 653
 cleanup() (angr.analyses.decompiler.structured_codegen.c.CStructuredCodegen method), 742
 clear() (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 698
 clear() (angr.knowledge_plugins.functions.function_manager.FunctionManager method), 554
 clear() (angr.state_plugins.log.SimStateLog method), 263
 clear() (angr.state_plugins.scratch.SimStateScratch method), 282
 clear() (angr.storage.memory_mixins.regioned_memory.abstract_address_mixin.AbstractAddressMixin method), 371
 clear_cache() (angr.engines.pcode.lifter.PcodeLifterEngineMixin method), 443
 clear_local_references() (angr.state_plugins.jni_references.SimStateJNIReferences method), 296
 clear_page_cache() (angr.state_plugins.unicorn_engine.Unicorn method), 290
 clear_region_for_reflow()

method), 601

compare() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 580

compare() (angr.storage.memory_mixins.MemoryMixin method), 337

compare() (angr.storage.memory_mixins.paged_memory.paged_memory method), 354

compare() (angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MVListPage method), 350

compare_path_group() (angr.analyses.congruency_check.CongruencyCheck method), 868

compare_paths() (angr.analyses.congruency_check.CongruencyCheck method), 868

compare_statement_dict() (in module angr.analyses.bindiff), 633

compare_states() (angr.analyses.congruency_check.CongruencyCheck method), 868

complement() (angr.sim_variable.SimVariableSet method), 509

complete() (angr.exploration_techniques.ExplorationTechnique method), 391

complete() (angr.exploration_techniques.Explorer method), 397

complete() (angr.exploration_techniques.explorer.Explorer method), 409

complete() (angr.exploration_techniques.Symbion method), 405

complete() (angr.exploration_techniques.symbion.Symbion method), 426

complete() (angr.exploration_techniques.Tracer method), 395

complete() (angr.exploration_techniques.tracer.Tracer method), 416

complete() (angr.ExplorationTechnique method), 179

complete() (angr.sim_manager.SimulationManager method), 385

complete() (angr.SimulationManager method), 174

COMPLETE_SCANNING (angr.analyses.cfg.cfg_fast.CFGJobType attribute), 655

CompleteCallingConventions (angr.analyses.analysis.KnownAnalysesPlugin attribute), 624

CompleteCallingConventionsAnalysis (class in angr.analyses.complete_calling_conventions), 638

compute() (angr.state_plugins.trace_additions.FormatInfo method), 273

compute() (angr.state_plugins.trace_additions.FormatInfo method), 274

compute() (angr.state_plugins.trace_additions.FormatInfo method), 274

compute() (angr.state_plugins.trace_additions.FormatInfo method), 274

compute_common_type() (angr.analyses.decompiler.structured_codegen.c.CBinaryOp static method), 737

compute_dominance_frontier() (in module angr.utils.graph), 896

compute_quotient() (angr.analyses.typehoon.simple_solver.SimpleSolver method), 340

concat() (angr.storage.memory_mixins.paged_memory.pages.multi_value method), 352

concrete() (angr.state_plugins.debug_variables.SimDebugVariable property), 308

concrete() (angr.state_plugins.view.SimMemView property), 314

Concrete (class in angr.state_plugins.concrete), 292

concrete_bytes() (angr.storage.memory_object.SimMemoryObject method), 334

concrete_load() (angr.storage.memory_mixins.address_concretization method), 346

concrete_load() (angr.storage.memory_mixins.MemoryMixin method), 337

concrete_load() (angr.storage.memory_mixins.paged_memory.paged_memory method), 354

concrete_load() (angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MVListPage method), 365

concrete_path_bool() (in module angr.state_plugins.solver), 254

concrete_path_list() (in module angr.state_plugins.solver), 254

concrete_path_not_bool() (in module angr.state_plugins.solver), 254

concrete_path_scalar() (in module angr.state_plugins.solver), 254

concrete_path_tuple() (in module angr.state_plugins.solver), 254

concrete_states (angr.analyses.variable_recovery.variable_recovery.VariableRecovery property), 830

ConcreteBackerMixin (class in angr.storage.memory_mixins.paged_memory.page_backer_mixins), 357

concretize() (angr.concretization_strategies.SimConcretizationStrategy method), 335

concretize() (angr.SimFile method), 190

concretize() (angr.SimFileBase method), 189

concretize() (angr.SimFileDescriptor method), 198

concretize() (angr.SimFileDescriptorDuplex method), 201

concretize() (angr.SimPackets method), 192

concretize() (angr.storage.file.SimFile method), 317

concretize() (angr.storage.file.SimFileBase method), 316

concretize() (angr.storage.file.SimFileDescriptor method), 327

concretize() (angr.storage.file.SimFileDescriptorBase method), 327

method), 326

concretize() (angr.storage.file.SimFileDescriptorDuplex method), 330

concretize() (angr.storage.file.SimPackets method), 321

concretize() (angr.storage.file.SimPacketsSlots method), 332

concretize() (in module angr.state_plugins.heap.utils), 306

concretize_load_idx() (angr.storage.memory_mixins.javavm_memory.javavm_memory_concretization_mixin method), 377

concretize_read_addr() (angr.storage.memory_mixins.address_concretization_mixin method), 346

concretize_store_idx() (angr.storage.memory_mixins.javavm_memory.javavm_memory_concretization_mixin method), 377

concretize_write_addr() (angr.storage.memory_mixins.address_concretization_mixin method), 345

cond (angr.analyses.decompiler.structured_codegen.c.CITE attribute), 740

condition (angr.analyses.decompiler.structured_codegen.c.CDoWhileLoop attribute), 730

condition (angr.analyses.decompiler.structured_codegen.c.CIfBreak attribute), 731

condition (angr.analyses.decompiler.structured_codegen.c.CIfElse attribute), 730

condition (angr.analyses.decompiler.structured_codegen.c.CWhileLoop attribute), 730

condition (angr.analyses.decompiler.structuring.structurer_nodes.CongruencyCheck attribute), 690

condition (angr.analyses.decompiler.structuring.structurer_nodes.CongruencyCheck attribute), 688

condition (angr.analyses.decompiler.structuring.structurer_nodes.CongruencyCheck attribute), 689

Condition (class in angr.analyses.loop_analysis), 846

condition_and_nodes (angr.analyses.decompiler.structured_codegen.c.CIfElse attribute), 731

condition_and_nodes (angr.analyses.decompiler.structuring.structurer_nodes.CongruencyCheck attribute), 689

condition_to_lambda() (in module angr.exploration_techniques.common), 425

CONDITIONAL (angr.state_plugins.sim_action.SimActionExit attribute), 467

ConditionalBreakLocation (class in angr.analyses.decompiler.region_simplifiers.expr_folding), 719

ConditionalBreakNode (class in angr.analyses.decompiler.structuring.structurer_nodes), 690

ConditionalMixin (class in angr.storage.memory_mixins.conditional_store_mixin), 346

ConditionalRegion (class in angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifiers), 722

ConditionLocation (class in angr.analyses.decompiler.region_simplifiers.expr_folding), 718

ConditionNode (class in angr.analyses.decompiler.structuring.structurer_nodes), 688

ConditionProcessor (class in angr.analyses.decompiler.structuring.structurer_nodes), 698

configuration (angr.angrdb.models.DbStructuredCode attribute), 680

configure_project() (angr.SimOS method), 168

configure_project() (angr.simos.linux.SimLinux method), 886

configure_project() (angr.simos.simos.SimOS method), 884

configure_project() (angr.simos.userland.SimUserland method), 887

configure_project() (angr.simos.windows.SimWindows method), 889

confirmed (angr.analyses.cfg.cfg_fast.FunctionFakeRetEdge attribute), 654

CongruencyCheck (angr.analyses.analysis.KnownAnalysesPlugin attribute), 622

CongruencyCheck (class in angr.analyses.analysis.known_analyses_plugin), 622

connect() (angr.knowledge_plugins.sync.sync_controller.SyncController property), 612

connected (angr.knowledge_plugins.sync.sync_controller.SyncController property), 612

const_formats (angr.angrdb.models.DbStructuredCode attribute), 680

CONST_TYPES (angr.engines.light.data.ArithmeticExpression attribute), 754

CONST_CANDIDATE (angr.knowledge_plugins.key_definitions.definition.Definition attribute), 593

Constant (angr.analyses.data_dep.dep_nodes.DepNodeTypes attribute), 877

CONSTANT (angr.analyses.reaching_definitions.AtomKind attribute), 770

CONSTANT (angr.knowledge_plugins.key_definitions.atoms.AtomKind attribute), 588

Constant (class in angr.analyses.stack_pointer_tracker), 821

constant_after() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 823

constant_after_block() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 572
 constant_before() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 823
 constant_before_block() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 823
 constant_jump_targets (angr.engines.pcode.lifter.IRSB property), 439
 constant_jump_targets_and_jumpkinds (angr.engines.pcode.lifter.IRSB property), 439
 ConstantChange (class in angr.analyses.bindiff), 633
 ConstantDepNode (class in angr.analyses.data_dep.dep_nodes), 877
 ConstantDereferencesSimplifier (class in angr.analyses.decompiler.optimization_passes.constant_folding), 704
 ConstantOperand (class in angr.analyses.disassembly), 858
 ConstantPropagation (class in angr.analyses.binary_optimizer), 869
 ConstantResolver (class in angr.analyses.cfg.indirect_jump_resolvers.constant_resolver), 671
 constants (angr.engines.pcode.lifter.IRSB property), 439
 ConstantSrc (class in angr.analyses.reaching_definitions), 774
 ConstantSrc (class in angr.knowledge_plugins.key_definitions.atoms), 590
 ConstantValueManager (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 667
 constrain_all_zero() (angr.analyses.identifier.identify.Identifier static method), 845
 constraint_hook() (in module angr.state_plugins.trace_additions), 274
 ConstraintGraphNode (class in angr.analyses.typehoon.simple_solver), 834
 ConstraintGraphTag (class in angr.analyses.typehoon.simple_solver), 834
 constraints (angr.state_plugins.solver.SimSolver property), 257
 constraints_since() (angr.state_plugins.history.SimStateHistory method), 270
 construct() (angr.knowledge_plugins.key_definitions.definition_variable_manager.DefinitionVariableManager static method), 593
 ContainerNode (class in angr.utils.graph), 897
 contains() (angr.knowledge_plugins.debug_variables.DebugVariable method), 572
 contains_addr() (angr.knowledge_plugins.functions.function_manager.FunctionManager method), 654
 contains_atom() (angr.analyses.reaching_definitions.dep_graph.DepGraph method), 800
 contains_memory_variable() (angr.sim_variable.SimVariableSet method), 509
 contains_register_variable() (angr.sim_variable.SimVariableSet method), 509
 content (angr.analyses.reaching_definitions.subject.Subject property), 818
 content (angr.analyses.reassembler.Data property), 864
 content (angr.angrdb.models.DbObject attribute), 678
 content (angr.knowledge_plugins.cfg.memory_data.MemoryData attribute), 546
 content (angr.knowledge_plugins.cfg.MemoryData attribute), 527
 content_gen() (angr.storage.memory_mixins.paged_memory.pages.memory_page.MemoryPage method), 350
 context (angr.code_location.CodeLocation attribute), 617
 context (angr.engines.pcode.lifter.PcodeBasicBlockLifter attribute), 441
 context_sensitivity_level (angr.analyses.cfg.cfg_base.CFGBase property), 650
 context_sensitivity_level (angr.analyses.cfg.cfg_emulated.CFGEmulated property), 648
 continue_addr (angr.analyses.decompiler.structuring.structurer_nodes.LabeledNode property), 689
 ContinueNode (class in angr.analyses.decompiler.structuring.structurer_nodes), 689
 ContinueScanningNotification, 651
 ConvenientMappingsMixin (class in angr.storage.memory_mixins.convenient_mappings_mixin), 348
 convert_claripy_bool_ast() (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 699
 convert_claripy_bool_ast_core() (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 699
 convert_cppproto_to_py() (in module angr.utils.library), 900
 convert_cproto_to_py() (in module angr.utils.library), 900
 convert_defvar_to_py() (in module angr.knowledge_plugins.variables.variable_manager.VariableManager static method), 571

- `ConvertTo` (class in `angr.analyses.typehoon.typevars`), 841
- `CooperationBase` (class in `angr.storage.memory_mixins.paged_memory.pages.cooperation`), 361
- `copy()` (`angr.analyses.cfg.cfg_base.CFGBase` method), 650
- `copy()` (`angr.analyses.cfg.cfg_emulated.CFGEmulated` method), 646
- `copy()` (`angr.analyses.cfg.cfg_fast.CFGFast` method), 660
- `copy()` (`angr.analyses.ddg.LiveDefinitions` method), 749
- `copy()` (`angr.analyses.decompiler.graph_region.GraphRegion` method), 703
- `copy()` (`angr.analyses.decompiler.optimization_passes.engine` method), 712
- `copy()` (`angr.analyses.decompiler.region_simplifiers.expr_folding` method), 718
- `copy()` (`angr.analyses.decompiler.structuring.structurer_node` method), 688
- `copy()` (`angr.analyses.decompiler.structuring.structurer_node` method), 689
- `copy()` (`angr.analyses.decompiler.structuring.structurer_node` method), 687
- `copy()` (`angr.analyses.decompiler.structuring.structurer_node` method), 688
- `copy()` (`angr.analyses.loop_analysis.LoopAnalysisState` method), 847
- `copy()` (`angr.analyses.reaching_definitions.call_trace.CallTrace` method), 794
- `copy()` (`angr.analyses.reaching_definitions.LiveDefinitions` method), 763
- `copy()` (`angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState` method), 813
- `copy()` (`angr.analyses.reaching_definitions.ReachingDefinitionsState` method), 779
- `copy()` (`angr.analyses.reaching_definitions.ReachingDefinitionsState` method), 783
- `copy()` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` method), 822
- `copy()` (`angr.analyses.typehoon.typevars.TypeVariables` method), 840
- `copy()` (`angr.analyses.variable_recovery.variable_recovery` method), 830
- `copy()` (`angr.analyses.variable_recovery.variable_recovery` method), 828
- `copy()` (`angr.analyses.vfg.VFG` method), 853
- `copy()` (`angr.concretization_strategies.norepeats.SimConcretizationStrategy` method), 379
- `copy()` (`angr.concretization_strategies.norepeats_range.SimConcretizationStrategy` method), 381
- `copy()` (`angr.concretization_strategies.SimConcretizationStrategy` method), 335
- `copy()` (`angr.engines.pcode.lifter.IRSB` method), 438
- `copy()` (`angr.keyed_region.KeyedRegion` method), 618
- `copy()` (`angr.keyed_region.RegionObject` method), 618
- `copy()` (`angr.knowledge_plugins.callsite_prototypes.CallsitePrototypes` method), 526
- `copy()` (`angr.knowledge_plugins.cfg.cfg_manager.CFGManager` method), 547
- `copy()` (`angr.knowledge_plugins.cfg.cfg_model.CFGModel` method), 539
- `copy()` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` method), 550
- `copy()` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` method), 549
- `copy()` (`angr.knowledge_plugins.cfg.CFGNode` method), 531
- `copy()` (`angr.knowledge_plugins.cfg.CFGManager` method), 538
- `copy()` (`angr.knowledge_plugins.cfg.CFGModel` method), 533
- `copy()` (`angr.knowledge_plugins.cfg.CFGNode` method), 530
- `copy()` (`angr.knowledge_plugins.cfg.memory_data.MemoryData` method), 546
- `copy()` (`angr.knowledge_plugins.memory_data.MemoryData` method), 527
- `copy()` (`angr.knowledge_plugins.comments.Comments` method), 552
- `copy()` (`angr.knowledge_plugins.data.Data` method), 552
- `copy()` (`angr.knowledge_plugins.functions.function.Function` method), 563
- `copy()` (`angr.knowledge_plugins.functions.function_manager.FunctionManager` method), 554
- `copy()` (`angr.knowledge_plugins.indirect_jumps.IndirectJumps` method), 552
- `copy()` (`angr.knowledge_plugins.key_definitions.key_definition_manager.KeyDefinitionManager` method), 596
- `copy()` (`angr.knowledge_plugins.key_definitions.KeyDefinitionManager` method), 576
- `copy()` (`angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions` method), 599
- `copy()` (`angr.knowledge_plugins.key_definitions.LiveDefinitions` method), 578
- `copy()` (`angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel` method), 607
- `copy()` (`angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel` method), 575
- `copy()` (`angr.knowledge_plugins.key_definitions.Uses` method), 587
- `copy()` (`angr.knowledge_plugins.key_definitions.uses.Uses` method), 587
- `copy()` (`angr.knowledge_plugins.labels.Labels` method), 553
- `copy()` (`angr.knowledge_plugins.patches.PatchManager` method), 525

- `copy()` (`angr.knowledge_plugins.plugin.KnowledgeBasePlugin` method), 525
- `copy()` (`angr.knowledge_plugins.structured_code.manager.StructuredCodeManager` method), 574
- `copy()` (`angr.knowledge_plugins.sync.sync_controller.SyncController` method), 612
- `copy()` (`angr.knowledge_plugins.types.TypesStore` method), 552
- `copy()` (`angr.knowledge_plugins.variables.variable_manager.VariableManager` method), 571
- `copy()` (`angr.knowledge_plugins.xrefs.xref.XRefManager` method), 615
- `copy()` (`angr.knowledge_plugins.xrefs.xref_manager.XRefManager` method), 615
- `copy()` (`angr.misc.plugins.PluginPreset` method), 224
- `copy()` (`angr.procedures.definitions.SimLibrary` method), 477
- `copy()` (`angr.procedures.definitions.SimSyscallLibrary` method), 481
- `copy()` (`angr.sim_manager.SimulationManager` method), 384
- `copy()` (`angr.sim_state.SimState` method), 227
- `copy()` (`angr.sim_state_options.SimStateOptions` method), 231
- `copy()` (`angr.sim_type.SimCppClass` method), 519
- `copy()` (`angr.sim_type.SimCppClassValue` method), 519
- `copy()` (`angr.sim_type.SimStruct` method), 518
- `copy()` (`angr.sim_type.SimStructValue` method), 518
- `copy()` (`angr.sim_type.SimType` method), 509
- `copy()` (`angr.sim_type.SimTypeArray` method), 514
- `copy()` (`angr.sim_type.SimTypeBottom` method), 511
- `copy()` (`angr.sim_type.SimTypeChar` method), 512
- `copy()` (`angr.sim_type.SimTypeCppFunction` method), 516
- `copy()` (`angr.sim_type.SimTypeDouble` method), 517
- `copy()` (`angr.sim_type.SimTypeFd` method), 513
- `copy()` (`angr.sim_type.SimTypeFloat` method), 517
- `copy()` (`angr.sim_type.SimTypeFunction` method), 515
- `copy()` (`angr.sim_type.SimTypeInt` method), 512
- `copy()` (`angr.sim_type.SimTypeLength` method), 516
- `copy()` (`angr.sim_type.SimTypeNum` method), 511
- `copy()` (`angr.sim_type.SimTypeNumOffset` method), 520
- `copy()` (`angr.sim_type.SimTypePointer` method), 513
- `copy()` (`angr.sim_type.SimTypeReference` method), 513
- `copy()` (`angr.sim_type.SimTypeReg` method), 511
- `copy()` (`angr.sim_type.SimTypeString` method), 514
- `copy()` (`angr.sim_type.SimTypeTop` method), 511
- `copy()` (`angr.sim_type.SimTypeWideChar` method), 512
- `copy()` (`angr.sim_type.SimTypeWString` method), 515
- `copy()` (`angr.sim_type.SimUnion` method), 518
- `copy()` (`angr.sim_type.SimUnionValue` method), 519
- `copy()` (`angr.sim_type.TypeRef` method), 510
- `copy()` (`angr.sim_variable.SimConstantVariable` method), 505
- `copy()` (`angr.sim_variable.SimMemoryVariable` method), 507
- `copy()` (`angr.sim_variable.SimRegisterVariable` method), 506
- `copy()` (`angr.sim_variable.SimStackVariable` method), 508
- `copy()` (`angr.sim_variable.SimTemporaryVariable` method), 505
- `copy()` (`angr.sim_variable.SimVariable` method), 505
- `copy()` (`angr.sim_variable.SimVariableSet` method), 509
- `copy()` (`angr.SimFile` method), 191
- `copy()` (`angr.SimFileBase` method), 189
- `copy()` (`angr.SimFileDescriptor` method), 199
- `copy()` (`angr.SimFileDescriptorDuplex` method), 201
- `copy()` (`angr.SimFileStream` method), 195
- `copy()` (`angr.SimHeapBrk` method), 204
- `copy()` (`angr.SimHeapPTMalloc` method), 206
- `copy()` (`angr.SimHostFilesystem` method), 204
- `copy()` (`angr.SimPackets` method), 193
- `copy()` (`angr.SimPacketsStream` method), 197
- `copy()` (`angr.SimState` method), 183
- `copy()` (`angr.SimStatePlugin` method), 161
- `copy()` (`angr.SimulationManager` method), 173
- `copy()` (`angr.state_plugins.callstack.CallStack` method), 264
- `copy()` (`angr.state_plugins.cgc.SimStateCGC` method), 272
- `copy()` (`angr.state_plugins.concrete.Concrete` method), 292
- `copy()` (`angr.state_plugins.filesystem.SimConcreteFilesystem` method), 252
- `copy()` (`angr.state_plugins.filesystem.SimFilesystem` method), 249
- `copy()` (`angr.state_plugins.filesystem.SimHostFilesystem` method), 254
- `copy()` (`angr.state_plugins.gdb.GDB` method), 271
- `copy()` (`angr.state_plugins.globals.SimStateGlobals` method), 279
- `copy()` (`angr.state_plugins.heap.heap_base.SimHeapBase` method), 298
- `copy()` (`angr.state_plugins.heap.heap_brk.SimHeapBrk` method), 298
- `copy()` (`angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc` method), 304
- `copy()` (`angr.state_plugins.history.SimStateHistory` method), 268
- `copy()` (`angr.state_plugins.inspect.SimInspector` method), 234
- `copy()` (`angr.state_plugins.javavm_classloader.SimJavaVmClassloader` method), 294
- `copy()` (`angr.state_plugins.jni_references.SimStateJNIReferences` method), 296
- `copy()` (`angr.state_plugins.libc.SimStateLibc` method), 238

- `copy()` (*angr.state_plugins.light_registers.SimLightRegisters* method), 267
- `copy()` (*angr.state_plugins.log.SimStateLog* method), 262
- `copy()` (*angr.state_plugins.loop_data.SimStateLoopData* method), 292
- `copy()` (*angr.state_plugins.plugin.SimStatePlugin* method), 232
- `copy()` (*angr.state_plugins.posix.PosixDevFS* method), 241
- `copy()` (*angr.state_plugins.posix.PosixProcFS* method), 243
- `copy()` (*angr.state_plugins.posix.SimSystemPosix* method), 245
- `copy()` (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 283
- `copy()` (*angr.state_plugins.scratch.SimStateScratch* method), 280
- `copy()` (*angr.state_plugins.sim_action.SimAction* method), 467
- `copy()` (*angr.state_plugins.sim_action_object.SimActionObject* method), 469
- `copy()` (*angr.state_plugins.solver.SimSolver* method), 256
- `copy()` (*angr.state_plugins.symbolizer.SimSymbolizer* method), 307
- `copy()` (*angr.state_plugins.trace_additions.ChallRespInfo* method), 274
- `copy()` (*angr.state_plugins.trace_additions.FormatInfo* method), 273
- `copy()` (*angr.state_plugins.trace_additions.FormatInfoDontConstrain* method), 274
- `copy()` (*angr.state_plugins.trace_additions.FormatInfoIntToStr* method), 274
- `copy()` (*angr.state_plugins.trace_additions.FormatInfoStrToInt* method), 274
- `copy()` (*angr.state_plugins.trace_additions.ZenPlugin* method), 276
- `copy()` (*angr.state_plugins.uc_manager.SimUCManager* method), 279
- `copy()` (*angr.state_plugins.unicorn_engine.Unicorn* method), 289
- `copy()` (*angr.state_plugins.view.SimMemView* method), 313
- `copy()` (*angr.state_plugins.view.SimRegNameView* method), 309
- `copy()` (*angr.storage.file.SimFile* method), 318
- `copy()` (*angr.storage.file.SimFileBase* method), 316
- `copy()` (*angr.storage.file.SimFileDescriptor* method), 328
- `copy()` (*angr.storage.file.SimFileDescriptorDuplex* method), 330
- `copy()` (*angr.storage.file.SimFileStream* method), 320
- `copy()` (*angr.storage.file.SimPackets* method), 322
- `copy()` (*angr.storage.file.SimPacketsSlots* method), 332
- `copy()` (*angr.storage.file.SimPacketsStream* method), 324
- `copy()` (*angr.storage.memory_mixins.address_concretization_mixin.AddressConcretization* method), 345
- `copy()` (*angr.storage.memory_mixins.convenient_mappings_mixin.ConvenientMappings* method), 348
- `copy()` (*angr.storage.memory_mixins.default_filler_mixin.ExplicitFillerMixin* method), 340
- `copy()` (*angr.storage.memory_mixins.default_filler_mixin.SpecialFillerMixin* method), 340
- `copy()` (*angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.JavavmMemory* method), 377
- `copy()` (*angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixin.KeyvalueMemory* method), 376
- `copy()` (*angr.storage.memory_mixins.label_merger_mixin.LabelMergerMixin* method), 347
- `copy()` (*angr.storage.memory_mixins.MemoryMixin* method), 336
- `copy()` (*angr.storage.memory_mixins.multi_value_merger_mixin.MultiValueMerger* method), 352
- `copy()` (*angr.storage.memory_mixins.paged_memory.page_backer_mixins.PagedMemoryPageBacker* method), 357
- `copy()` (*angr.storage.memory_mixins.paged_memory.page_backer_mixins.PagedMemoryPageBacker2* method), 358
- `copy()` (*angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemory* method), 356
- `copy()` (*angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemory2* method), 353
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.history_tracking_mixin.HistoryTracking* method), 361
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.list_page.ListPage* method), 362
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MvListPage* method), 349
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.permissions_mixin.Permissions* method), 360
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.refcount_mixin.Refcount* method), 359
- `copy()` (*angr.storage.memory_mixins.paged_memory.pages.ultra_page.UltraPage* method), 364
- `copy()` (*angr.storage.memory_mixins.paged_memory.stack_allocation_mixin.StackAllocation* method), 358
- `copy()` (*angr.storage.memory_mixins.regioned_memory.region_data.RegionData* method), 370
- `copy()` (*angr.storage.memory_mixins.regioned_memory.region_meta_mixin.RegionMeta* method), 371
- `copy()` (*angr.storage.memory_mixins.regioned_memory.regioned_address_mixin.RegionedAddress* method), 373
- `copy()` (*angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemory* method), 366
- `copy()` (*angr.storage.memory_mixins.size_resolution_mixin.SizeConcretization* method), 344
- `copy()` (*angr.storage.memory_mixins.slotted_memory.SlottedMemoryMixin* method), 374

method), 374

copy() (angr.storage.memory_mixins.top_merger_mixin.TopMergerMixin method), 352

copy() (angr.storage.memory_mixins.underconstrained_mixin.UnderconstrainedMixin method), 342

copy() (angr.storage.pcap.PCAP method), 335

copy() (angr.utils.cowdict.ChainMapCOW method), 894

copy_contents() (angr.storage.memory_mixins.MemoryMixin method), 338

copy_contents() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin method), 355

copy_contents() (angr.storage.memory_mixins.unwrapper_mixin.UnwrapperMixin method), 347

copy_graph() (angr.analyses.decompiler.clinic.Clinic method), 697

copy_graph() (in module angr.analyses.decompiler.utils), 747

CouldNotResolveException, 822

count (angr.state_plugins.unicorn_engine.TRANSMIT_RECORD attribute), 284

count() (angr.exploration_techniques.spiller.PickledStatesDb method), 412

count() (angr.state_plugins.history.TreeIter method), 270

count() (angr.storage.memory_mixins.paged_memory.pages.multi_values.Values method), 351

cprotos2py() (in module angr.utils.library), 901

crash_windup() (angr.exploration_techniques.Tracer class method), 396

crash_windup() (angr.exploration_techniques.tracer.Tracer class method), 416

create_extract_vtable() (angr.analyses.vtable.VtableFinder method), 854

create_jump_target_var() (angr.analyses.decompiler.condition_processor.ConditionProcessor method), 699

create_new_reference() (angr.state_plugins.jni_references.SimStateJNIReferences method), 794

creation_failed (angr.knowledge_plugins.cfg.cfg_node.CFGNode property), 550

creation_failed (angr.knowledge_plugins.cfg.CFGNode property), 530

creation_failure_info (angr.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 550

creation_failure_info (angr.knowledge_plugins.cfg.CFGNode attribute), 530

CRegister (class in angr.analyses.decompiler.structured_codegen.c), 739

CReturn (class in angr.analyses.decompiler.structured_codegen.c), 733

cs_operand (angr.analyses.disassembly.Operand property), 858

CStatement (class in angr.analyses.decompiler.structured_codegen.c), 729

CStatements (class in angr.analyses.decompiler.structured_codegen.c), 729

CStructField (class in angr.analyses.decompiler.structured_codegen.c), 724

CStructFieldNameDef (class in angr.analyses.decompiler.structured_codegen.c), 741

CStructuredCodeGenerator (class in angr.analyses.decompiler.structured_codegen.c), 741

CStructuredCodeWalker (class in angr.analyses.decompiler.structured_codegen.c), 742

cstyle_ifs (angr.analyses.decompiler.structured_codegen.c.CIfBreak attribute), 731

cstyle_ifs (angr.analyses.decompiler.structured_codegen.c.CIfElse attribute), 731

CSwitchCase (class in angr.analyses.decompiler.structured_codegen.c), 732

CTypeCast (class in angr.analyses.decompiler.structured_codegen.c), 738

CUnaryOp (class in angr.analyses.decompiler.structured_codegen.c), 737

CUnsupportedStatement (class in angr.analyses.decompiler.structured_codegen.c), 734

current_function_address (angr.state_plugins.callstack.CallStack property), 265

current_function_address() (angr.analyses.reaching_definitions.call_trace.CallTrace method), 794

current_return_target (angr.state_plugins.callstack.CallStack property), 265

current_stack_pointer (angr.analyses.cfg.cfg_job_base.CFGJobBase property), 661

current_stack_pointer (angr.state_plugins.callstack.CallStack property), 265

CVariable (class in angr.analyses.decompiler.structured_codegen.c), 735

CVariableField (class in angr.analyses.decompiler.structured_codegen.c), 736

CWhileLoop (class in angr.analyses.decompiler.structured_codegen.c), 736

- 730
- cyclic (*angr.analyses.decompiler.graph_region.GraphRegion* attribute), 703
- cyclic_ancestor (*angr.analyses.decompiler.graph_region.GraphRegion* attribute), 703
- cyclomatic_complexity (*angr.knowledge_plugins.functions.function.Function* property), 557
- ## D
- data (*angr.analyses.variable_recovery.engine_base.RichR* attribute), 831
- data (*angr.engines.pcode.lifter.Lifter* attribute), 440
- data (*angr.engines.pcode.lifter.PcodeLifter* attribute), 442
- data (*angr.state_plugins.unicorn_engine.TRANSMIT_RECORD* attribute), 284
- Data (class in *angr.analyses.reassembler*), 864
- Data (class in *angr.knowledge_plugins.data*), 552
- data_addr (*angr.analyses.decompiler.clinic.DataRefDesc* attribute), 696
- data_graph (*angr.analyses.ddg.DDG* property), 752
- data_ptr() (*angr.PTChunk* method), 209
- data_ptr() (*angr.state_plugins.heap.heap_freelist.Chunk* method), 300
- data_ptr() (*angr.state_plugins.heap.heap_ptmalloc.PTChunk* method), 303
- data_refs (*angr.engines.pcode.lifter.IRSB* attribute), 438
- data_size (*angr.analyses.decompiler.clinic.DataRefDesc* attribute), 696
- data_sub_graph() (*angr.analyses.ddg.DDG* method), 752
- data_type_str (*angr.analyses.decompiler.clinic.DataRefDesc* attribute), 696
- DataDependencyGraphAnalysis (class in *angr.analyses.data_dep.data_dependency_analysis*), 875
- DataGraphError, 675
- DataGraphMeta (class in *angr.analyses.datagraph_meta*), 675
- DataLabel (class in *angr.analyses.reassembler*), 860
- DataNormalizationMixin (class in *angr.storage.memory_mixins.bvv_conversion_mixin*), 341
- DATAREF_HINTS (*angr.analyses.cfg.cfg_fast.CFGJobType* attribute), 655
- DataRefDesc (class in *angr.analyses.decompiler.clinic*), 696
- db_compatible() (*angr.angrdb.db.AngrDB* method), 677
- DbCFGModel (class in *angr.angrdb.models*), 679
- DbComment (class in *angr.angrdb.models*), 681
- DbFunction (class in *angr.angrdb.models*), 679
- dbg_comments() (*angr.analyses.reassembler.Instruction* method), 862
- dbg_draw() (*angr.knowledge_plugins.functions.function.Function* method), 561
- dbg_draw() (*angr.knowledge_plugins.functions.function_manager.FunctionManager* method), 555
- dbg_get_repr() (*angr.analyses.decompiler.graph_region.GraphRegion* static method), 703
- dbg_print() (*angr.analyses.decompiler.graph_region.GraphRegion* method), 703
- dbg_print() (*angr.knowledge_plugins.functions.function.Function* method), 561
- dbg_print() (*angr.storage.memory_mixins.regioned_memory.region_memory* method), 373
- dbg_print_irsb() (*angr.annocfg.AnnotatedCFG* method), 882
- dbg_print_stack() (*angr.sim_state.SimState* method), 228
- dbg_print_stack() (*angr.SimState* method), 184
- dbg_repr() (*angr.analyses.backward_slice.BackwardSlice* method), 632
- dbg_repr() (*angr.analyses.cfg.cfb.CFBlanket* method), 642
- dbg_repr() (*angr.analyses.ddg.DDG* method), 752
- dbg_repr() (*angr.analyses.decompiler.clinic.Clinic* method), 697
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.BaseNode* method), 687
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.BreakpointNode* method), 689
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.CodeBlockNode* method), 688
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.ConditionNode* method), 690
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.ConditionNode* method), 688
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.ContinueNode* method), 690
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.LoopNode* method), 689
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.MultiNode* method), 687
- dbg_repr() (*angr.analyses.decompiler.structuring.structurer_nodes.SequenceNode* method), 688
- dbg_repr() (*angr.annocfg.AnnotatedCFG* method), 882
- dbg_repr() (*angr.Blade* method), 168
- dbg_repr() (*angr.blade.Blade* method), 880
- dbg_repr() (*angr.keyed_region.KeyedRegion* method), 619
- dbg_repr() (*angr.state_plugins.callstack.CallStack* method), 266
- dbg_repr_run() (*angr.analyses.backward_slice.BackwardSlice* method), 632
- DbInformation (class in *angr.angrdb.models*), 677

DbKnowledgeBase (class in *angr.angrdb.models*), 678
 DbLabel (class in *angr.angrdb.models*), 681
 DbObject (class in *angr.angrdb.models*), 678
 DbStructuredCode (class in *angr.angrdb.models*), 680
 DbVariableCollection (class in *angr.angrdb.models*), 679
 DbXRefs (class in *angr.angrdb.models*), 680
 DDG (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
 DDG (class in *angr.analyses.ddg*), 751
 DDGJob (class in *angr.analyses.ddg*), 749
 DDGView (class in *angr.analyses.ddg*), 751
 DDGViewInstruction (class in *angr.analyses.ddg*), 751
 DDGViewItem (class in *angr.analyses.ddg*), 751
 deactivate() (*angr.misc.plugins.PluginPreset* method), 223
 dead_ref() (*angr.state_hierarchy.StateHierarchy* method), 389
 dead_ref() (*angr.StateHierarchy* method), 180
 DeadAssignment (class in *angr.analyses.binary_optimizer*), 869
 deadended (*angr.sim_manager.SimulationManager* attribute), 383
 deadended (*angr.SimulationManager* attribute), 172
 deadends (*angr.analyses.cfg.cfg_emulated.CFGEmulated* property), 648
 debug() (*angr.sim_manager.ErrorRecord* method), 389
 DebugVariable (class in *angr.knowledge_plugins.debug_variables*), 572
 DebugVariableContainer (class in *angr.knowledge_plugins.debug_variables*), 572
 DebugVariableManager (class in *angr.knowledge_plugins.debug_variables*), 573
 dec_active_workers() (*angr.distributed.server.Server* method), 909
 dec_active_workers() (*angr.Server* method), 210
 decode_instruction() (in module *angr.analyses.disassembly_utils*), 860
 DecodingAssumption (class in *angr.analyses.cfg.cfg_fast*), 652
 DecompilationCache (class in *angr.analyses.decompiler.decompilation_cache*), 700
 DecompilationOption (class in *angr.analyses.decompiler.decompilation_options*), 699
 DECOMPILE (*angr.analyses.decompiler.clinic.ClinicMode* attribute), 696
 decompile_functions() (in module *angr.analyses.decompiler.utils*), 748
 Decompiler (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 624
 Decompiler (class in *angr.analyses.decompiler.decompiler*), 700
 decorate() (*angr.analyses.reaching_definitions.function_handler.Function* static method), 807
 default (*angr.analyses.decompiler.structured_codegen.c.CSwitchCase* attribute), 732
 default (*angr.sim_state_options.StateOption* attribute), 228
 DEFAULT (*angr.state_plugins.sim_action.SimActionExit* attribute), 467
 default_cc() (in module *angr*), 184
 default_cc() (in module *angr.calling_conventions*), 503
 default_exit_target (*angr.engines.pcode.lifter.IRSB* attribute), 438
 default_indirect_jump_resolvers() (in module *angr.analyses.cfg.indirect_jump_resolvers.default_resolvers*), 666
 default_node (*angr.analyses.decompiler.structuring.structurer_nodes.Sw* attribute), 690
 default_simtype_from_size() (*angr.analyses.decompiler.structured_codegen.c.CStructuredCode* method), 742
 DefaultChainMapCOW (class in *angr.utils.cowdict*), 894
 DefaultFillerMixin (class in *angr.storage.memory_mixins.default_filler_mixin*), 340
 DefaultListPagesMemory (class in *angr.storage.memory_mixins*), 338
 DefaultMemory (class in *angr.storage.memory_mixins*), 338
 defer_cleanup() (*angr.state_hierarchy.StateHierarchy* method), 389
 defer_cleanup() (*angr.StateHierarchy* method), 180
 definition (*angr.knowledge_plugins.key_definitions.live_definitions.Definition* attribute), 597
 Definition (class in *angr.analyses.reaching_definitions*), 774
 Definition (class in *angr.knowledge_plugins.key_definitions*), 587
 Definition (class in *angr.knowledge_plugins.key_definitions.definition*), 594
 DefinitionAnnotation (class in *angr.knowledge_plugins.key_definitions.live_definitions*), 597
 DefinitionMatchPredicate (class in *angr.knowledge_plugins.key_definitions.definition*), 592
 definitions (*angr.analyses.ddg.DDGViewInstruction* property), 751
 defs (*angr.knowledge_base.knowledge_base.KnowledgeBase* attribute), 523
 Defs (*angr.KnowledgeBase* attribute), 211

DefUseChain (class in `angr.analyses.vsa_ddg`), 853
delete() (`angr.SimMount` method), 203
delete() (`angr.state_plugins.filesystem.SimConcreteFilesystem` method), 252
delete() (`angr.state_plugins.filesystem.SimFilesystem` method), 250
delete() (`angr.state_plugins.filesystem.SimMount` method), 251
delete() (`angr.state_plugins.posix.PosixDevFS` method), 240
delete() (`angr.state_plugins.posix.PosixProcFS` method), 242
delete_reference() (`angr.state_plugins.jni_references.SimJniReference` method), 296
delete_uc() (`angr.state_plugins.unicorn_engine.UnicornEngine` static method), 290
demangled_name (`angr.analyses.decompiler.structured_codegen.c.CFunction` attribute), 729
demangled_name (`angr.knowledge_plugins.functions.function.Function` property), 562
demote() (`angr.state_plugins.history.SimStateHistory` method), 269
dep_graph (`angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState` property), 813
dep_graph (`angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis` property), 797
dep_graph (`angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis` property), 776
dep_graph (`angr.analyses.reaching_definitions.ReachingDefinitionsState` property), 783
dependents (`angr.analyses.ddg.DDGViewItem` property), 751
depends() (`angr.analyses.reaching_definitions.function_handler.FunctionCallData` method), 805
depends() (`angr.analyses.reaching_definitions.FunctionCallData` method), 792
depends_on (`angr.analyses.ddg.DDGViewItem` property), 751
DepGraph (class in `angr.analyses.reaching_definitions.dep_graph`), 799
DepNodeTypes (class in `angr.analyses.data_dep.dep_nodes`), 877
depth (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` attribute), 550
depth (`angr.knowledge_plugins.cfg.CFGNode` attribute), 530
deref (`angr.state_plugins.debug_variables.SimDebugVariable` property), 308
deref (`angr.state_plugins.view.SimMemView` property), 314
deref() (`angr.analyses.reaching_definitions.LiveDefinitions` method), 769
deref() (`angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState` method), 817
deref() (`angr.analyses.reaching_definitions.ReachingDefinitionsState` method), 787
deref() (`angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions` method), 605
deref() (`angr.knowledge_plugins.key_definitions.LiveDefinitions` method), 584
dereference_simtype() (in module `angr.sim_type`), 521
DerefSize (class in `angr.knowledge_plugins.key_definitions`), 585
DerefSize (class in `angr.knowledge_plugins.key_definitions.live_definitions`), 596
DefinedTypeVariable (class in `angr.analyses.typehoon.typevars`), 839
describe_variables() (`angr.state_plugins.solver.SimSolver` method), 255
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.base_ptr_save_restore` attribute), 708
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.const_derefs` attribute), 704
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.div_simplify` attribute), 708
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.expr_op_swap` attribute), 708
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.ite_expr_con` attribute), 709
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.lowered_swit` attribute), 710
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.mod_simplifi` attribute), 711
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.multi_simplifi` attribute), 714
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.optimization` attribute), 705
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.register_save` attribute), 713
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.ret_addr_save` attribute), 714
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.stack_canary` attribute), 707
DESCRIPTION (`angr.analyses.decompiler.optimization_passes.x86_gcc_getp` attribute), 714
DESCRIPTION (`angr.analyses.decompiler.peephole_optimizations.base.Peep` attribute), 716
DESCRIPTION (`angr.analyses.decompiler.peephole_optimizations.base.Peep` attribute), 715
DESCRIPTION (`angr.analyses.decompiler.peephole_optimizations.base.Peep` attribute), 714
description (`angr.sim_state_options.StateOption` attribute), 228
descriptions (`angr.state_plugins.history.SimStateHistory` property), 269
dest (`angr.analyses.reaching_definitions.function_handler.FunctionEffect`

- attribute*), 802
- `destroy()` (*angr.state_plugins.unicorn_engine.Unicorn method*), 290
- `desymbolize()` (*angr.analyses.reassembler.Data method*), 864
- `determine()` (*angr.analyses.typehoon.simple_solver.Simple method*), 836
- `DFS` (*class in Angr exploration techniques*), 398
- `DFS` (*class in Angr exploration techniques.dfs*), 408
- `dfs_back_edges()` (*in module Angr utils.graph*), 896
- `dict_content` (*angr.utils.dynamic_dictlist.DynamicDictList attribute*), 895
- `dict_strkey_to_intkey()` (*angr.angrdb.serializers.structured_code.StructuredCodeManager static method*), 685
- `DictBackerMixin` (*class in Angr storage.memory_mixins.paged_memory.paged_memory_mixin*), 358
- `Difference` (*class in Angr analyses.bindiff*), 633
- `difference()` (*angr.sim_state_options.SimStateOptions method*), 230
- `differing_blocks` (*angr.analyses.bindiff.BinDiff property*), 636
- `differing_blocks` (*angr.analyses.bindiff.FunctionDiff property*), 634
- `differing_constants()` (*in module Angr analyses.bindiff*), 633
- `differing_functions` (*angr.analyses.bindiff.BinDiff property*), 636
- `differing_functions_with_consts()` (*angr.analyses.bindiff.BinDiff method*), 636
- `direct_next` (*angr.engines.pcode.lifter.IRSB property*), 439
- `Director` (*class in Angr exploration techniques*), 399
- `Director` (*class in Angr exploration techniques.director*), 420
- `dirty` (*angr.analyses.decompiler.structured_codegen.c.CDirtyExpression attribute*), 740
- `DirtyAddrsMixin` (*class in Angr storage.memory_mixins.dirty_addrs_mixin*), 344
- `disable_profiling()` (*in module Angr analyses.cfg.indirect_jump_resolvers.mips_elf_fast*), 664
- `disable_timing()` (*in module Angr state_plugins.solver*), 254
- `DisassemblerBlock` (*class in Angr block*), 220
- `DisassemblerInsn` (*class in Angr block*), 220
- `Disassembly` (*angr.analyses.analysis.KnownAnalysesPlugin attribute*), 623
- `disassembly` (*angr.Block property*), 170
- `disassembly` (*angr.block.Block property*), 221
- `disassembly` (*angr.engines.pcode.lifter.IRSB property*), 439
- `Disassembly` (*class in Angr analyses.disassembly*), 859
- `DisassemblyPiece` (*class in Angr analyses.disassembly*), 856
- `discard()` (*angr.knowledge_plugins.structured_code.manager.StructuredCodeManager method*), 574
- `discard()` (*angr.sim_state_options.SimStateOptions method*), 230
- `discard()` (*angr.sim_variable.SimVariableSet method*), 509
- `discard_input()` (*angr.state_plugins.cgc.SimStateCGC method*), 272
- `discard_memory_variable()` (*angr.sim_variable.SimVariableSet method*), 509
- `discard_output()` (*angr.state_plugins.cgc.SimStateCGC method*), 272
- `discard_plugin_preset()` (*angr.misc.plugins.PluginHub method*), 223
- `discard_register_variable()` (*angr.sim_variable.SimVariableSet method*), 509
- `display_name` (*angr.analyses.data_dep.dep_nodes.VarDepNode property*), 878
- `dissect_instruction()` (*angr.analyses.disassembly.Instruction method*), 857
- `dissect_instruction_by_default()` (*angr.analyses.disassembly.Instruction method*), 857
- `dissect_instruction_for_arm()` (*angr.analyses.disassembly.Instruction method*), 857
- `DivSimplifier` (*class in Angr analyses.decompiler.optimization_passes.div_simplifier*), 708
- `DivSimplifierAILEngine` (*class in Angr analyses.decompiler.optimization_passes.div_simplifier*), 708
- `do_full_xrefs()` (*angr.analyses.cfg.cfg_fast.CFGFast method*), 659
- `do_preprocess()` (*in module Angr sim_type*), 520
- `do_trace()` (*angr.analyses.identifier.identify.Identifier method*), 845
- `dom` (*angr.utils.graph.Dominators attribute*), 897
- `dom` (*angr.utils.graph.PostDominators attribute*), 897
- `dominance_frontiers` (*angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase property*), 826
- `DominanceFrontier` (*class in Angr analyses.dominance_frontier*), 870
- `dominates()` (*in module Angr utils.graph*), 896
- `Dominators` (*class in Angr utils.graph*), 897
- `done` (*angr.analyses.vfg.AnalysisTask property*), 850
- `done` (*angr.analyses.vfg.CallAnalysis property*), 851

done (angr.analyses.vfg.FunctionAnalysis property), 850
DoNotUpdate (angr.analyses.calling_convention.UpdateArgumentsOperation attribute), 654
dst_addr (angr.analyses.cfg.cfg_fast.FunctionTransitionEdge attribute), 654
dst_func_addr (angr.analyses.cfg.cfg_fast.FunctionReturnEdge attribute), 655
dst_func_addr (angr.analyses.cfg.cfg_fast.FunctionTransitionEdge attribute), 654
dst_type (angr.analyses.decompiler.structured_codegen.c.CTypeCast attribute), 738
dummy (angr.analyses.reaching_definitions.ReachingDefinitionState attribute), 774
dummy (angr.knowledge_plugins.key_definitions.Definition attribute), 587
dummy_base (angr.knowledge_plugins.key_definitions.definition.Definition attribute), 594
DummyStructuralRedoGenerator (class in angr.analyses.decompiler.structured_codegen.dummy), 745
dump() (angr.angrdb.db.AngrDB method), 677
dump() (angr.angrdb.serializers.cfg_model.CFGModelSerializer static method), 682
dump() (angr.angrdb.serializers.comments.CommentsSerializer static method), 682
dump() (angr.angrdb.serializers.funcs.FunctionManagerSerializer static method), 682
dump() (angr.angrdb.serializers.kb.KnowledgeBaseSerializer static method), 683
dump() (angr.angrdb.serializers.labels.LabelsSerializer static method), 683
dump() (angr.angrdb.serializers.loader.LoaderSerializer static method), 684
dump() (angr.angrdb.serializers.loader.LoaderSerializer static method), 685
dump() (angr.angrdb.serializers.variables.VariableManagerSerializer static method), 684
dump() (angr.angrdb.serializers.xrefs.XRefsSerializer static method), 684
dump() (angr.calling_conventions.AllocHelper method), 485
dump_file_by_path() (angr.state_plugins.posix.SimSystemPosix method), 247
dump_graph() (angr.analyses.decompiler.structuring.phoenix.PhoenixStructurer static method), 693
dump_internal() (angr.angrdb.serializers.variables.VariableManagerSerializer static method), 685
dumps() (angr.state_plugins.posix.SimSystemPosix method), 247
dumps() (angr.vaults.Vault method), 621
DUPLICATION_CHECK (angr.analyses.decompiler.structured_codegen.base.Base attribute), 726
DURING_REGION_IDENTIFICATION (angr.analyses.decompiler.optimization_passes.optimization_passes attribute), 705
dwarf_cfa (angr.state_plugins.debug_variables.SimDebugVariablePlugin attribute), 705

property), 309
dwarf_cfa_approx (angr.state_plugins.debug_variables.SimDebugVariable attribute), 309
DYNAMIC_RET (angr.sim_procedure.SimProcedure attribute), 472
DYNAMIC_RET (angr.SimProcedure attribute), 159
dynamic_returns() (angr.sim_procedure.SimProcedure method), 473
dynamic_returns() (angr.SimProcedure method), 159
DynamicDictList (class in angr.utils.dynamic_dictlist), 894

E

E2BIG (angr.state_plugins.posix.SimSystemPosix attribute), 244
EACCES (angr.state_plugins.posix.SimSystemPosix attribute), 244
EAGAIN (angr.state_plugins.posix.SimSystemPosix attribute), 244
EBADF (angr.state_plugins.cgc.SimStateCGC attribute), 271
EBADF (angr.state_plugins.posix.SimSystemPosix attribute), 244
EBUSY (angr.state_plugins.posix.SimSystemPosix attribute), 244
ECHILD (angr.state_plugins.posix.SimSystemPosix attribute), 244
edges_to_repair (angr.knowledge_plugins.cfg.cfg_model.CFGModel attribute), 539
edges_to_repair (angr.knowledge_plugins.cfg.CFGModel attribute), 532
EDOM (angr.state_plugins.posix.SimSystemPosix attribute), 245
EEXIST (angr.state_plugins.posix.SimSystemPosix attribute), 244
EFAULT (angr.state_plugins.cgc.SimStateCGC attribute), 271
EFAULT (angr.state_plugins.posix.SimSystemPosix attribute), 244
EFBIG (angr.state_plugins.posix.SimSystemPosix attribute), 245
effects (angr.analyses.reaching_definitions.function_handler.FunctionHandler attribute), 805
effects (angr.analyses.reaching_definitions.FunctionCallData attribute), 791
EINTR (angr.state_plugins.posix.SimSystemPosix attribute), 244
EINVAL (angr.state_plugins.cgc.SimStateCGC attribute), 272
EINVAL (angr.state_plugins.posix.SimSystemPosix attribute), 244
EIO (angr.state_plugins.posix.SimSystemPosix attribute), 244
EISDIR (angr.state_plugins.posix.SimSystemPosix attribute), 244
ELFHeader (angr.knowledge_plugins.cfg.memory_data.MemoryDataSort attribute), 545
ELFHeader (angr.knowledge_plugins.cfg.MemoryDataSort attribute), 526
eliminatable (angr.analyses.cfg.indirect_jump_resolvers.jumptable.RegC attribute), 668
eliminatable (angr.analyses.data_dep.data_dependency_analysis.Nodal attribute), 875
eliminatable (angr.analyses.variable_recovery.annotations.StackLocation attribute), 823
eliminatable (angr.analyses.variable_recovery.annotations.VariableSource attribute), 823
eliminatable (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase attribute), 824
eliminatable (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 597
eliminatable (angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin attribute), 344
else_node (angr.analyses.decompiler.structured_codegen.c.CIfElse attribute), 731
else_node (angr.analyses.decompiler.structuring.structurer_nodes.CascadingNodes attribute), 689
EMFILE (angr.state_plugins.posix.SimSystemPosix attribute), 245
EMLINK (angr.state_plugins.posix.SimSystemPosix attribute), 245
Empty (angr.analyses.proximity_graph.ProxiNodeTypes attribute), 872
empty_block() (angr.engines.pcode.lifter.IRSB static method), 438
EmptyBlockNotice, 687
EmptyNodeRemover (class in angr.analyses.decompiler.empty_node_remover), 701
enable_profiling() (in module angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast), 664
enable_timing() (in module angr.state_plugins.solver), 254
end (angr.knowledge_plugins.RegionObject property), 618
end_info_hook() (in module angr.state_plugins.trace_additions), 274
endness (angr.analyses.reaching_definitions.MemoryLocation attribute), 773
endness (angr.knowledge_plugins.key_definitions.atoms.MemoryLocation attribute), 592
endness (angr.storage.memory_object.SimMemoryObject attribute), 334
endpoints (angr.knowledge_plugins.functions.function.Function property), 559
endpoints_with_type (angr.knowledge_plugins.functions.function.Function

- property), 559
- ENFILE (angr.state_plugins.posix.SimSystemPosix attribute), 245
- ENODEV (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOENT (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOEXEC (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOMEM (angr.state_plugins.cgc.SimStateCGC attribute), 272
- ENOMEM (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOSPC (angr.state_plugins.posix.SimSystemPosix attribute), 245
- ENOSYS (angr.state_plugins.cgc.SimStateCGC attribute), 272
- ENOTBLK (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOTDIR (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ENOTTY (angr.state_plugins.posix.SimSystemPosix attribute), 245
- entry_state() (angr.factory.AngrObjectFactory method), 217
- entrypoints (angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink property), 819
- environment (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813
- environment (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783
- Environment (class in angr.knowledge_plugins.key_definitions.environment), 594
- ENXIO (angr.state_plugins.posix.SimSystemPosix attribute), 244
- eof() (angr.SimFileDescriptor method), 198
- eof() (angr.SimFileDescriptorDuplex method), 201
- eof() (angr.storage.file.SimFileDescriptor method), 327
- eof() (angr.storage.file.SimFileDescriptorBase method), 326
- eof() (angr.storage.file.SimFileDescriptorDuplex method), 330
- EPERM (angr.state_plugins.posix.SimSystemPosix attribute), 244
- EPIPE (angr.state_plugins.cgc.SimStateCGC attribute), 272
- EPIPE (angr.state_plugins.posix.SimSystemPosix attribute), 245
- EQ (angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifiers.CmpOp attribute), 722
- Eq (class in angr.analyses.stack_pointer_tracker), 821
- Equal (angr.analyses.loop_analysis.Condition attribute), 846
- Equivalence (class in angr.analyses.typehoon.typevars), 837
- ERANGE (angr.state_plugins.posix.SimSystemPosix attribute), 245
- erase() (angr.storage.memory_mixins.MemoryMixin method), 338
- erase() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin method), 353
- erase() (angr.storage.memory_mixins.paged_memory.pages.list_page.ListPage method), 362
- erase() (angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MvListPage method), 349
- EROFS (angr.state_plugins.posix.SimSystemPosix attribute), 245
- errno (angr.state_plugins.libc.SimStateLibc property), 240
- error_converter() (in module angr.state_plugins.solver), 254
- ERROR_REG (angr.calling_conventions.SimCCN64LinuxSyscall attribute), 500
- ERROR_REG (angr.calling_conventions.SimCCO32LinuxSyscall attribute), 499
- ERROR_REG (angr.calling_conventions.SimCCPowerPC64LinuxSyscall attribute), 502
- ERROR_REG (angr.calling_conventions.SimCCPowerPCLinuxSyscall attribute), 501
- ERROR_REG (angr.calling_conventions.SimCCSyscall attribute), 499
- errored (angr.sim_manager.SimulationManager property), 384
- errored (angr.SimulationManager property), 172
- ErrorRecord (class in angr.sim_manager), 389
- errors (angr.analyses.analysis.Analysis attribute), 625
- errors (angr.Analysis attribute), 178
- ESPIPE (angr.state_plugins.posix.SimSystemPosix attribute), 245
- ESRCH (angr.state_plugins.posix.SimSystemPosix attribute), 244
- ETXTBSY (angr.state_plugins.posix.SimSystemPosix attribute), 245
- eval() (angr.state_plugins.solver.SimSolver method), 260
- eval_atleast() (angr.state_plugins.solver.SimSolver method), 261
- eval_atmost() (angr.state_plugins.solver.SimSolver method), 260
- eval_exact() (angr.state_plugins.solver.SimSolver method), 261
- eval_one() (angr.state_plugins.solver.SimSolver method), 260
- eval_to_ast() (angr.state_plugins.solver.SimSolver method), 258
- eval_upto() (angr.state_plugins.solver.SimSolver method), 259

[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehavior](#) method), 446
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorBoolNegate](#) method), 459
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorCopy](#) method), 459
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorInt2Comp](#) method), 458
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntNegate](#) method), 447
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntSext](#) method), 450
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntZext](#) method), 454
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorPopcount](#) method), 451
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorDiv](#) method), 456
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorLeft_type\(\)](#) method), 454
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 448
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 449
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 456
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 454
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 457
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 455
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 452
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 451
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 457
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 448
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 448
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 457
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 455
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 451
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 453
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 447
[evaluate_binary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorEXX_COUNTER](#) method), 464
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehavior](#) method), 446
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorBoolNegate](#) method), 458
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorCopy](#) method), 446
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorInt2Comp](#) method), 452
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntNegate](#) method), 453
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntSext](#) method), 450
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorIntZext](#) method), 449
[evaluate_unary\(\)](#) ([angr.engines.pcode.behavior.OpBehaviorPopcount](#) method), 464
[events](#) ([angr.state_plugins.history.SimStateHistory](#) property), 269
[events_left_type\(\)](#) ([angr.state_plugins.log.SimStateLog](#) method), 262
[EXX_COUNTER](#) ([angr.analyses.decompiler.condition_processor.ConditionProcessor](#) attribute), 699
[EXX_COUNTER](#) ([angr.state_plugins.posix.SimSystemPosix](#) attribute), 244
[execute\(\)](#) ([angr.Project](#) method), 166
[execute\(\)](#) ([angr.project.Project](#) method), 216
[execute\(\)](#) ([angr.sim_procedure.SimProcedure](#) method), 472
[execute\(\)](#) ([angr.SimProcedure](#) method), 159
[ExecuteAddressGoal](#) (class in [angr.exploration_techniques](#)), 400
[ExecuteAddressGoal](#) (class in [angr.exploration_techniques.director](#)), 419
[executed_instruction_count](#) ([angr.errors.SimError](#) attribute), 905
[Existence](#) (class in [angr.analyses.typehoon.typevars](#)), 837
[exists_in_replacements\(\)](#) (in module [angr.analyses.cfg.indirect_jump_resolvers.const_resolver](#)), 671
[exit\(\)](#) ([angr.SimProcedure.SimProcedure](#) method), 473
[exit\(\)](#) ([angr.SimProcedure](#) method), 160
[exit_in_hook\(\)](#) (in module [angr.state_plugins.trace_additions](#)), 274
[exit_observed\(\)](#) ([angr.analyses.reaching_definitions.reaching_definitions](#) method), 798
[exit_observed\(\)](#) ([angr.analyses.reaching_definitions.ReachingDefinitions](#) method), 777
[exit_observed\(\)](#) ([angr.analyses.reaching_definitions.rd_state.ReachingDefinitions](#) attribute), 811
[exit_observed\(\)](#) ([angr.analyses.reaching_definitions.ReachingDefinitions](#) attribute), 781
[exit_replacements](#) ([angr.engines.pcode.lifter.IRSB](#) property), 438

ExitStatement (class in *angr.engines.pcode.lifter*), 435

ExplicitFillerMixin (class in *angr.storage.memory_mixins.default_filler_mixin*), 340

ExplorationStatusNotifier (class in *angr.distributed.worker*), 909

ExplorationTechnique (class in *angr*), 178

ExplorationTechnique (class in *angr.exploration_techniques*), 390

explore() (*angr.sim_manager.SimulationManager* method), 384

explore() (*angr.SimulationManager* method), 173

Explorer (class in *angr.exploration_techniques*), 396

Explorer (class in *angr.exploration_techniques.explorer*), 408

expr (*angr.analyses.decompiler.optimization_passes.lowered_expression_type* attribute), 710

expr (*angr.analyses.decompiler.structured_codegen.c.CMulexpression* attribute), 740

expr (*angr.analyses.decompiler.structured_codegen.c.CTypesExpr* attribute), 738

expr_classes (*angr.analyses.decompiler.peephole_optimizer* attribute), 716

expr_comments (*angr.angrdb.models.DbStructuredCode* attribute), 680

expr_idx (*angr.analyses.decompiler.region_simplifiers.expr_folding* attribute), 718

ExpressionCounter (class in *angr.analyses.decompiler.region_simplifiers.expr_counter*), 719

ExpressionFolder (class in *angr.analyses.decompiler.region_simplifiers.expr_folding*), 720

ExpressionLocation (class in *angr.analyses.decompiler.region_simplifiers.expr_folding*), 718

ExpressionNarrowingWalker (class in *angr.analyses.decompiler.expression_narrower*), 702

ExpressionReplacer (class in *angr.analyses.decompiler.optimization_passes.expr_op_swapper*), 712

ExpressionReplacer (class in *angr.analyses.decompiler.optimization_passes.iterative_expr_replacer*), 708

ExpressionReplacer (class in *angr.analyses.decompiler.region_simplifiers.expr_folding*), 719

expressions (*angr.engines.pcode.lifter.IRSB* property), 439

ExpressionUseFinder (class in *angr.analyses.decompiler.region_simplifiers.expr_folding*), 719

ExprOpSwapper (class in *angr.analyses.decompiler.optimization_passes.expr_op_swapper*), 713

extend() (*angr.engines.pcode.lifter.IRSB* method), 438

extend_actions() (*angr.state_plugins.history.SimStateHistory* method), 269

extend_actions() (*angr.state_plugins.log.SimStateLog* method), 262

extern (*angr.knowledge_plugins.key_definitions.definition.DefinitionMatch* attribute), 593

ExternalCodeLocation (class in *angr.code_location*), 617

extract() (*angr.sim_type.SimCppClass* method), 519

extract() (*angr.sim_type.SimStruct* method), 517

extract() (*angr.sim_type.SimTypeArray* method), 514

extract() (*angr.sim_type.SimTypeBool* method), 513

extract() (*angr.sim_type.SimTypeChar* method), 512

extract() (*angr.sim_type.SimTypeFloat* method), 517

extract() (*angr.sim_type.SimTypeInt* method), 512

extract() (*angr.sim_type.SimTypeNum* method), 511

extract() (*angr.sim_type.SimTypeNumOffset* method), 520

extract() (*angr.sim_type.SimTypeRegBase* method), 511

extract() (*angr.sim_type.SimTypeString* method), 514

extract() (*angr.sim_type.SimTypeWideChar* method), 512

extract() (*angr.sim_type.SimTypeWString* method), 515

extract() (*angr.sim_type.SimUnion* method), 518

extract() (*angr.storage.memory_mixins.paged_memory.pages.multi_value* method), 351

extract_claripy() (*angr.sim_type.SimType* method), 509

extract_components() (*angr.procedures.stubs.format_parser.FormatParser* method), 475

extract_defs() (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 764

extract_defs() (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitions* method), 812

extract_defs() (*angr.analyses.reaching_definitions.ReachingDefinitions* method), 783

extract_defs() (*angr.knowledge_plugins.key_definitions.live_definitions* static method), 600

extract_defs() (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 579

extract_defs_from_annotations() (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 764

extract_defs_from_annotations() (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* static method), 600

extract_defs_from_annotations() (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 579

extract_defs_from_mv(
 (angr.analyses.reaching_definitions.LiveDefinitions
 static method), 764
 extract_defs_from_mv(
 (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions
 static method), 600
 extract_defs_from_mv(
 (angr.knowledge_plugins.key_definitions.LiveDefinitions
 static method), 579
 extract_jump_targets() (in module
 angr.analyses.decompiler.utils), 745
 extract_offset_to_sp(
 (angr.analyses.propagator.engine_ail.SimEnginePropagatorAil
 method), 758
 extract_offset_to_sp(
 (angr.engines.light.engine.SimEngineLightMixin
 static method), 755
 extract_stack_offset_from_addr(
 (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase
 static method), 826
 extract_terms() (in module
 angr.analyses.decompiler.structured_codegen.c),
 727
 extract_value_if_concrete(
 (angr.analyses.xrefs.SimEngineXRefsVEX
 static method), 871
 extract_variables(
 (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase
 static method), 825
F
 f (angr.utils.mp.Closure attribute), 902
 failure() (angr.engines.successors.SimSuccessors
 class method), 430
 false_node (angr.analyses.decompiler.structuring.structured_nodes.ConditionNode
 attribute), 688
 fast_memory_load() (angr.analyses.reassembler.Reassembler
 method), 868
 FastMemory (class in angr.storage.memory_mixins), 339
 fd (angr.state_plugins.unicorn_engine.TRANSMIT_RECORD
 attribute), 284
 FD_SETSIZE (angr.state_plugins.cgc.SimStateCGC at-
 tribute), 272
 FetchingZeroPageError, 288
 field (angr.analyses.decompiler.structured_codegen.c.CStructField
 attribute), 735
 FieldReferenceCleanup (class in
 angr.analyses.decompiler.structured_codegen.c),
 744
 fields (angr.sim_type.SimUnion attribute), 518
 file_exists (angr.SimFileDescriptor property), 199
 file_exists (angr.storage.file.SimFileDescriptor prop-
 erty), 328
 file_exists (angr.storage.file.SimFileDescriptorBase
 property), 327
 fill_content() (angr.knowledge_plugins.cfg.memory_data.MemoryData
 method), 546
 fill_content_def() (angr.knowledge_plugins.cfg.MemoryData
 method), 528
 fill_reg_map() (in module
 angr.analyses.reassembler), 860
 filter() (angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got.AMD64ElfGotResolver
 method), 661
 filter() (angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast.ArmElfFastResolver
 method), 662
 filter() (angr.analyses.cfg.indirect_jump_resolvers.const_resolver.ConstantResolver
 method), 671
 filter() (angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableResolver
 method), 670
 filter() (angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.MipsElfFastResolver
 method), 664
 filter() (angr.analyses.cfg.indirect_jump_resolvers.sig_in_base.SigInBaseResolver
 method), 672
 filter() (angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic_plt.X86ElfPicPltResolver
 method), 665
 filter() (angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat.X86PeIatResolver
 method), 663
 filter() (angr.analyses.veriteesting.CallTracingFilter
 method), 848
 filter() (angr.exploration_techniques.ExplorationTechnique
 method), 397
 filter() (angr.exploration_techniques.Explorer
 method), 397
 filter() (angr.exploration_techniques.explorer.Explorer
 method), 409
 filter() (angr.exploration_techniques.local_loop_seer.LocalLoopSeer
 method), 423
 filter() (angr.exploration_techniques.LocalLoopSeer
 method), 406
 filter() (angr.exploration_techniques.loop_seer.LoopSeer
 method), 422
 filter() (angr.exploration_techniques.LoopSeer
 method), 394
 filter() (angr.exploration_techniques.Slicecutor
 method), 392
 filter() (angr.exploration_techniques.slicecutor.Slicecutor
 method), 417
 filter() (angr.exploration_techniques.Tracer method),
 396
 filter() (angr.exploration_techniques.tracer.Tracer
 method), 416
 filter() (angr.ExplorationTechnique method), 179
 filter() (angr.sim_manager.SimulationManager
 method), 386
 filter() (angr.SimulationManager method), 175
 filter_actions() (angr.state_plugins.history.SimStateHistory
 method), 268

<code>filter_cond_regions()</code>	(in module <code>angr.knowledge_plugins.cfg.CFGModel</code>), 544
<code>find_function_for_reflow_into_addr()</code>	(<code>angr.knowledge_plugins.cfg.CFGModel</code> method), 538
<code>filter_constraints()</code>	(<code>angr.state_plugins.trace_additions.ZenPlugin</code> method), 277
<code>filter_variables()</code>	(<code>angr.analyses.decompiler.optimization_passes.stagnate_optimizer.AILState</code> method), 712
<code>final_states</code>	(<code>angr.knowledge_plugins.cfg.cfg_node.CFGNode</code> attribute), 550
<code>final_states</code>	(<code>angr.knowledge_plugins.cfg.CFGNode</code> attribute), 530
<code>find()</code>	(<code>angr.storage.memory_mixins.MemoryMixin</code> method), 336
<code>find()</code>	(<code>angr.storage.memory_mixins.regioned_memory.regioned_memory.RegionedMemoryMixin</code> method), 367
<code>find()</code>	(<code>angr.storage.memory_mixins.regioned_memory.static_find_mixin.StaticFindMixin</code> method), 371
<code>find()</code>	(<code>angr.storage.memory_mixins.smart_find_mixin.SmartFindMixin</code> method), 340
<code>find()</code>	(<code>angr.storage.memory_mixins.unwrapper_mixin.UnwrapperMixin</code> method), 347
<code>find_all_predecessors()</code>	(<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 800
<code>find_all_successors()</code>	(<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 800
<code>find_block_by_addr()</code>	(in module <code>angr.analyses.decompiler.utils</code>), 748
<code>find_cc()</code>	(<code>angr.calling_conventions.SimCC</code> static method), 492
<code>find_cc()</code>	(<code>angr.SimCC</code> static method), 187
<code>find_consumers()</code>	(<code>angr.analyses.ddg.DDG</code> method), 753
<code>find_data_references_and_update_memory_data()</code>	(<code>angr.analyses.decompiler.decompiler.Decompiler</code> method), 701
<code>find_declaration()</code>	(<code>angr.knowledge_plugins.functions.function.Function</code> method), 562
<code>find_definition()</code>	(<code>angr.analyses.decompiler.peephole_optimization_passes.angr_base_optimizer.RegionExcluder</code> static method), 716
<code>find_definitions()</code>	(<code>angr.analyses.ddg.DDG</code> method), 753
<code>find_definitions()</code>	(<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 800
<code>find_defs_at()</code>	(<code>angr.analyses.reaching_definitions.ReachingDefinitionsModel</code> method), 779
<code>find_defs_at()</code>	(<code>angr.knowledge_plugins.key_definitions.find_defs_at.ReachingDefinitionsModel</code> method), 607
<code>find_defs_at()</code>	(<code>angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel</code> method), 575
<code>find_function_for_reflow_into_addr()</code>	(<code>angr.knowledge_plugins.cfg.cfg_model.CFGModel</code> method), 473
<code>find_killers()</code>	(<code>angr.analyses.ddg.DDG</code> method), 753
<code>find_merge_points()</code>	(<code>angr.utils.graph.GraphUtils</code> method), 846
<code>find_path()</code>	(<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 801
<code>find_paths()</code>	(<code>angr.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 801
<code>find_sources()</code>	(<code>angr.analyses.ddg.DDG</code> method), 753
<code>find_stack_vars_x86()</code>	(<code>angr.analyses.identifier.identifier.Identifier</code> method), 846
<code>find_variable_by_atom()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 567
<code>find_variable_by_stmt()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 567
<code>find_variables_by_atom()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 567
<code>find_variables_by_insn()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 567
<code>find_variables_by_register()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 568
<code>find_variables_by_stack_offset()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 568
<code>find_variables_by_stmt()</code>	(<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 567
<code>find_widening_points()</code>	(<code>angr.utils.graph.GraphUtils</code> static method), 846
<code>find_first_node_in_set()</code>	(class <code>FindFirstNodeInSet</code> in module <code>angr.knowledge_plugins.functions.function.Function</code>), 562
<code>finish()</code>	(<code>angr.state_plugins.unicorn_engine.Unicorn</code> method), 290
<code>fire()</code>	(<code>angr.state_plugins.inspect.BP</code> method), 233
<code>find_node_by_addr()</code>	(in module <code>angr.analyses.decompiler.utils</code>), 746
<code>find_node_by_addr()</code>	(in module <code>angr.analyses.decompiler.utils</code>), 746
<code>fix_prototype_return_type()</code>	(<code>angr.SimProcedure</code> method), 473

- method), 160
- flags (angr.procedures.stubs.format_parser.FormatParser attribute), 475
- Flags (class in angr.storage.file), 314
- flatten_typevar() (angr.analyses.typehoon.simple_solver.Sketch static method), 834
- flavor (angr.angrdb.models.DbStructuredCode attribute), 680
- FlirtAnalysis (class in angr.analyses.flirt), 754
- FlirtSignature (class in angr.flirt), 892
- Float (class in angr.analyses.typehoon.typeconsts), 844
- float_len_mod (angr.procedures.stubs.format_parser.ScanfFormatInfo attribute), 476
- float_spec (angr.procedures.stubs.format_parser.ScanfFormatInfo attribute), 476
- float_type() (in module angr.analyses.typehoon.typeconsts), 845
- FloatBase (class in angr.analyses.typehoon.typeconsts), 844
- FloatingPoint (angr.knowledge_plugins.cfg.memory_data.MemoryDataSort attribute), 545
- FloatingPoint (angr.knowledge_plugins.cfg.MemoryDataSort attribute), 527
- floor_addr() (angr.analyses.cfg.cfb.CFBlanket method), 641
- floor_addr() (angr.knowledge_plugins.functions.function_calls.function_calls.attribute), 553
- floor_func() (angr.knowledge_plugins.functions.function_calls.function_calls.attribute), 554
- floor_item() (angr.analyses.cfg.cfb.CFBlanket method), 641
- floor_items() (angr.analyses.cfg.cfb.CFBlanket method), 642
- flush_pages() (angr.storage.memory_mixins.paged_memory.attribute), 355
- fmt (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- fmt_char (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- fmt_double (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- fmt_float (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- fmt_hex (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- fmt_int() (angr.analyses.decompiler.structured_codegen.c.CConst method), 739
- fmt_neg (angr.analyses.decompiler.structured_codegen.c.CConst property), 739
- force_unroll_loops() (angr.analyses.cfg.cfg_emulated.CFGEEmulated method), 647
- forget_last_label() (angr.analyses.typehoon.simple_solver.ConstraintGraphNode attribute), 835
- FORGOTTEN (class in angr.analyses.typehoon.simple_solver), 834
- FormatInfo (class in angr.state_plugins.trace_additions), 273
- FormatInfoDontConstrain (class in angr.state_plugins.trace_additions), 274
- FormatInfoIntToStr (class in angr.state_plugins.trace_additions), 274
- FormatInfoStrToInt (class in angr.state_plugins.trace_additions), 274
- FormatParser (class in angr.procedures.stubs.format_parser), 475
- FormatSpecifier (class in angr.procedures.stubs.format_parser), 474
- FormatString (class in angr.procedures.stubs.format_parser), 474
- ForwardAnalysis (class in angr.analyses.forward_analysis.forward_analysis), 625
- found (angr.sim_manager.SimulationManager attribute), 383
- found (angr.SimulationManager attribute), 172
- FP_ARG_REGS (angr.calling_conventions.SimCC attribute), 489
- FP_ARG_REGS (angr.calling_conventions.SimCCArch64 attribute), 498
- FP_ARG_REGS (angr.calling_conventions.SimCCArch64LinuxSyscall attribute), 498
- FP_ARG_REGS (angr.calling_conventions.SimCCAMD64WindowsSyscall attribute), 497
- FP_ARG_REGS (angr.calling_conventions.SimCCARM attribute), 497
- FP_ARG_REGS (angr.calling_conventions.SimCCARMHF attribute), 497
- FP_ARG_REGS (angr.calling_conventions.SimCCARMLinuxSyscall attribute), 498
- FP_ARG_REGS (angr.calling_conventions.SimCCdecl attribute), 493
- FP_ARG_REGS (angr.calling_conventions.SimCCMicrosoftAMD64 attribute), 494
- FP_ARG_REGS (angr.calling_conventions.SimCCN64 attribute), 500
- FP_ARG_REGS (angr.calling_conventions.SimCCN64LinuxSyscall attribute), 500
- FP_ARG_REGS (angr.calling_conventions.SimCCO32 attribute), 499
- FP_ARG_REGS (angr.calling_conventions.SimCCO32LinuxSyscall attribute), 499
- FP_ARG_REGS (angr.calling_conventions.SimCCPowerPC attribute), 500
- FP_ARG_REGS (angr.calling_conventions.SimCCPowerPC64 attribute), 500

<code>attribute</code>), 501	<code>FreezeState</code> (<code>angr.analyses.stack_pointer_tracker.StackPointerTrackerState</code> method), 304
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCPowerPC64LinuxSyscall</code> attribute), 501	<code>from_ail_expr()</code> (<code>angr.analyses.reaching_definitions.Atom</code> static method), 770
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCPowerPCLinuxSyscall</code> attribute), 501	<code>from_ail_expr()</code> (<code>angr.knowledge_plugins.key_definitions.atoms.Atom</code> static method), 588
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCRISCV64LinuxSyscall</code> attribute), 499	<code>from_argument()</code> (<code>angr.analyses.reaching_definitions.Atom</code> static method), 770
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCS390XLinuxSyscall</code> attribute), 503	<code>from_argument()</code> (<code>angr.knowledge_plugins.key_definitions.atoms.Atom</code> static method), 588
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCS390XLinuxSyscall</code> attribute), 503	<code>from_argument()</code> (<code>angr.knowledge_plugins.key_definitions.atoms.Atom</code> static method), 588
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCSystemVAMD64LinuxSyscall</code> attribute), 496	<code>from_c_repr_chunks()</code> (<code>angr.analyses.decompiler.structured_codegen.c.CFunction</code> method), 729
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCX86LinuxSyscall</code> attribute), 495	<code>full_graph</code> (<code>angr.analyses.decompiler.graph_region.GraphRegion</code> attribute), 703
<code>FP_ARG_REGS</code> (<code>angr.calling_conventions.SimCCX86WindowsSyscall</code> attribute), 495	<code>full_init_state()</code> (<code>angr.factory.AngrObjectFactory</code> method), 217
<code>FP_ARG_REGS</code> (<code>angr.engines.pcode.cc.SimCCM68k</code> attribute), 465	<code>full_simplify()</code> (<code>angr.state_hierarchy.StateHierarchy</code> method), 390
<code>FP_ARG_REGS</code> (<code>angr.engines.pcode.cc.SimCCPowerPC</code> attribute), 466	<code>full_state()</code> (<code>angr.StateHierarchy</code> method), 180
<code>FP_ARG_REGS</code> (<code>angr.engines.pcode.cc.SimCCXtensa</code> attribute), 466	
<code>FP_ARG_REGS</code> (<code>angr.SimCC</code> attribute), 185	
<code>fp_args</code> (<code>angr.calling_conventions.SimCC</code> property), 490	
<code>fp_args</code> (<code>angr.SimCC</code> property), 185	
<code>fp_iter</code> (<code>angr.calling_conventions.ArgSession</code> attribute), 488	
<code>fp_iter</code> (<code>angr.calling_conventions.SimCC.ArgSession</code> attribute), 490	
<code>fp_iter</code> (<code>angr.SimCC.ArgSession</code> attribute), 186	
<code>FP_RETURN_VAL</code> (<code>angr.calling_conventions.SimCC</code> attribute), 489	
<code>FP_RETURN_VAL</code> (<code>angr.calling_conventions.SimCCARMHF</code> attribute), 497	
<code>FP_RETURN_VAL</code> (<code>angr.calling_conventions.SimCCdecl</code> attribute), 493	
<code>FP_RETURN_VAL</code> (<code>angr.calling_conventions.SimCCMicrosoftAMD64</code> attribute), 494	
<code>FP_RETURN_VAL</code> (<code>angr.calling_conventions.SimCCSystemVAMD64</code> attribute), 496	
<code>FP_RETURN_VAL</code> (<code>angr.SimCC</code> attribute), 185	
<code>free()</code> (<code>angr.analyses.reaching_definitions.heap_allocator.HeapAllocator</code> method), 802	
<code>free()</code> (<code>angr.SimHeapPTMalloc</code> method), 207	
<code>free()</code> (<code>angr.state_plugins.heap.heap_libc.SimHeapLibc</code> method), 301	
<code>free()</code> (<code>angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc</code> method), 305	
<code>free_chunks()</code> (<code>angr.SimHeapPTMalloc</code> method), 206	
<code>free_chunks()</code> (<code>angr.state_plugins.heap.heap_freelist.SimHeapFreelist</code> method), 301	
<code>free_chunks()</code> (<code>angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc</code> method), 305	

`func` (`angr.analyses.cfg.indirect_jump_resolvers.jumptable.FunctionNode` attribute), 667
`func_addr` (`angr.analyses.cfg.cfg_fast.CFGJob` attribute), 656
`func_addr` (`angr.analyses.cfg.cfg_job_base.BlockID` property), 661
`func_addr` (`angr.analyses.cfg.cfg_job_base.CFGJobBase` property), 661
`func_addr` (`angr.analyses.decompiler.peephole_optimization_reachable_definitions.reaching_definitions` attribute), 716
`func_addr` (`angr.analyses.decompiler.peephole_optimization_reachable_definitions.reaching_definitions` attribute), 715
`func_addr` (`angr.analyses.decompiler.peephole_optimization_reachable_definitions.reaching_definitions` attribute), 715
`func_addr` (`angr.analyses.variable_recovery.engine_base.Function/Dependency_graph` property), 832
`func_addr` (`angr.analyses.variable_recovery.variable_recovery_engine_base.Function/Dependency_graph` property), 826
`func_addr` (`angr.angrdb.models.DbStructuredCode` attribute), 680
`func_addr` (`angr.angrdb.models.DbVariableCollection` attribute), 680
`func_addr` (`angr.knowledge_plugins.cfg.indirect_jump.IndirectJump` attribute), 551
`func_addr` (`angr.knowledge_plugins.cfg.IndirectJump` attribute), 532
`func_edge_type_from_pb()` (in `module` `angr.utils.enums_conv`), 895
`func_edge_type_to_pb()` (in `module` `angr.utils.enums_conv`), 895
`func_graph` (`angr.analyses.reaching_definitions.subject.SubjectType` property), 818
`func_lookup()` (`angr.analyses.disassembly.Disassembly` method), 859
`func_typevar` (`angr.analyses.decompiler.decompilation_cache.DecompilationCache` attribute), 700
`FuncComment` (class in `angr.analyses.disassembly`), 859
`FuncIn` (class in `angr.analyses.typehoon.typevars`), 841
`FuncInfo` (class in `angr.analyses.identifier.identify`), 845
`FuncOut` (class in `angr.analyses.typehoon.typevars`), 841
`funcs` (`angr.angrdb.models.DbKnowledgeBase` attribute), 678
`Function` (`angr.analyses.proximity_graph.ProxiNodeTypes` attribute), 872
`function` (`angr.analyses.reaching_definitions.function_handler.FunctionCallData` attribute), 805
`function` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 791
`Function` (`angr.analyses.reaching_definitions.subject.SubjectType` attribute), 817
`Function` (class in `angr.analyses.typehoon.typeconsts`), 844
`Function` (class in `angr.knowledge_plugins.functions.function`), 555
`FunctionNode` (`angr.knowledge_plugins.functions.function_manager.FunctionNode` method), 555
`function_address` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` attribute), 548
`function_address` (`angr.knowledge_plugins.cfg.CFGNode` attribute), 528
`function_address` (`angr.storage.memory_mixins.regioned_memory.regioned_memory` attribute), 369
`function_reachable_definitions.reaching_definitions` attribute), 797
`function_reachable_definitions.reaching_definitions` attribute), 804
`function_reachable_definitions.reaching_definitions` attribute), 791
`Function/Dependency_graph` (`angr.analyses.ddg.DDG` method), 752
`function_initial_states` (`angr.analyses.vfg.VFG` property), 853
`function_name` (`angr.analyses.reassembler.FunctionLabel` property), 861
`function_needs_variable_recovery()` (`angr.analyses.complete_calling_conventions.CompleteCallingConventions` static method), 640
`FUNCTION_PROLOGUE` (`angr.analyses.cfg.cfg_fast.CFGJobType` attribute), 655
`function_prototype()` (`angr.factory.AngrObjectFactory` method), 220
`FunctionAnalysis` (class in `angr.analyses.vfg`), 850
`FunctionCall` (`angr.analyses.proximity_graph.ProxiNodeTypes` attribute), 872
`FunctionCallData` (class in `angr.analyses.reaching_definitions`), 790
`FunctionCallData` (class in `angr.analyses.reaching_definitions.function_handler`), 803
`FunctionCallDataUnwrapped` (class in `angr.analyses.reaching_definitions.function_handler`), 806
`FunctionCallEdge` (class in `angr.analyses.cfg.cfg_fast`), 654
`FunctionCallRelationships` (class in `angr.analyses.reaching_definitions.dep_graph`), 798
`FunctionDict` (class in `angr.knowledge_plugins.functions.function_manager`), 553
`FunctionDiff` (class in `angr.analyses.bindiff`), 634
`FunctionEdge` (class in `angr.analyses.cfg.cfg_fast`), 653
`FunctionEffect` (class in `angr.analyses.reaching_definitions.function_handler`), 802

FunctionFakeRetEdge (class in *angr.analyses.cfg.cfg_fast*), 654
 FunctionGraphVisitor (class in *angr.analyses.forward_analysis.visitors.function_graph*), 627
 FunctionHandler (class in *angr.analyses.reaching_definitions*), 787
 FunctionHandler (class in *angr.analyses.reaching_definitions.function_handler*), 807
 FunctionKey (class in *angr.analyses.cfg.cfg_job_base*), 661
 FunctionLabel (class in *angr.analyses.reassembler*), 860
 FunctionManager (class in *angr.knowledge_plugins.functions.function_manager*), 553
 FunctionManagerSerializer (class in *angr.angrdb.serializers.funcs*), 682
 FunctionParser (class in *angr.knowledge_plugins.functions.function_parser*), 563
 FunctionProxiNode (class in *angr.analyses.proximity_graph*), 873
 FunctionReturn (class in *angr.analyses.cfg.cfg_fast*), 652
 FunctionReturnEdge (class in *angr.analyses.cfg.cfg_fast*), 655
 functions (*angr.analyses.cfg.cfg_base.CFGBase* property), 650
 functions (*angr.knowledge_base.knowledge_base.KnowledgeBase* attribute), 523
 functions (*angr.KnowledgeBase* attribute), 211
 functions_called() (*angr.knowledge_plugins.functions.function_manager.FunctionDict* method), 563
 functions_probably_identical() (*angr.analyses.bindiff.BinDiff* method), 635
 FunctionStart (class in *angr.analyses.disassembly*), 856
 FunctionTag (class in *angr.knowledge_plugins.key_definitions.tag*), 608
 FunctionTransitionEdge (class in *angr.analyses.cfg.cfg_fast*), 654
 functy (*angr.analyses.decompiler.structured_codegen.c.CFG* attribute), 729
 fwd_chunk() (*angr.PTChunk* method), 209
 fwd_chunk() (*angr.state_plugins.heap.heap_freelist.Chunk* method), 300
 fwd_chunk() (*angr.state_plugins.heap.heap_ptmalloc.PTChunk* method), 303
 G
 g_label_ctr (*angr.analyses.reassembler.Label* attribute), 860
 GDB (class in *angr.state_plugins.gdb*), 270
 generate_code_cover() (*angr.analyses.cfg.cfg_fast.CFGFast* method), 660
 generate_gdt() (*angr.SimOS* method), 169
 generate_gdt() (*angr.simos.simos.SimOS* method), 885
 generate_index() (*angr.analyses.cfg.cfg_base.CFGBase* method), 650
 generate_symbolic_cmd_line_arg() (*angr.simos.javavm.SimJavaVM* static method), 890
 generic_compare() (*angr.engines.pcode.behavior.OpBehavior* static method), 446
 generic_info_hook() (in module *angr.state_plugins.trace_additions*), 274
 get() (*angr.analyses.stack_pointer_tracker.StackPointerTrackerState* method), 822
 get() (*angr.knowledge_plugins.functions.function_manager.FunctionDict* method), 553
 get() (*angr.knowledge_plugins.key_definitions.environment.Environment* method), 595
 get() (*angr.knowledge_plugins.labels.Labels* method), 553
 get() (*angr.procedures.definitions.SimCppLibrary* method), 480
 get() (*angr.procedures.definitions.SimLibrary* method), 479
 get() (*angr.procedures.definitions.SimSyscallLibrary* method), 482
 get() (*angr.procedures.definitions.SimTypeCollection* method), 476
 get() (*angr.procedures.definitions.SimMount* method), 203
 get() (*angr.state_plugins.filesystem.SimConcreteFilesystem* method), 252
 get() (*angr.state_plugins.filesystem.SimFilesystem* method), 250
 get() (*angr.state_plugins.filesystem.SimMount* method), 251
 get() (*angr.state_plugins.globals.SimStateGlobals* method), 279
 get() (*angr.state_plugins.posix.PosixDevFS* method), 240
 get() (*angr.state_plugins.posix.PosixProcFS* method), 242
 get() (*angr.state_plugins.view.SimRegNameView* method), 310
 get() (*angr.utils.mp.Initializer* class method), 902
 get_abstract_locations() (*angr.storage.memory_mixins.regioned_memory.region_meta_mixin* method), 372
 get_addr() (*angr.annocfg.AnnotatedCFG* method), 881
 get_addr_of_native_method()

(*angr.simos.javavm.SimJavaVM* method), 891

get_all_definitions() (in module *angr.analyses.reaching_definitions*), 793

get_all_nodes() (*angr.analyses.cfg.cfg_base.CFGBase* method), 650

get_all_nodes() (*angr.analyses.vfg.VFG* method), 853

get_all_nodes() (*angr.analyses.vsa_ddg.VSA_DDG* method), 854

get_all_nodes() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 540

get_all_nodes() (*angr.knowledge_plugins.cfg.CFGModel* method), 534

get_all_nodes_intersecting_region() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 541

get_all_nodes_intersecting_region() (*angr.knowledge_plugins.cfg.CFGModel* method), 534

get_all_patches() (*angr.knowledge_plugins.patches.PatchManager* method), 524

get_all_predecessors() (*angr.analyses.cfg.cfg_base.CFGBase* method), 650

get_all_predecessors() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 543

get_all_predecessors() (*angr.knowledge_plugins.cfg.CFGModel* method), 536

get_all_successors() (*angr.analyses.cfg.cfg_base.CFGBase* method), 650

get_all_successors() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 543

get_all_successors() (*angr.knowledge_plugins.cfg.CFGModel* method), 536

get_all_variables() (*angr.keyed_region.KeyedRegion* method), 620

get_alloc_depth() (*angr.state_plugins.uc_manager.SimUCManager* method), 280

get_any_node() (*angr.analyses.cfg.cfg_base.CFGBase* method), 650

get_any_node() (*angr.analyses.vfg.VFG* method), 853

get_any_node() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 540

get_any_node() (*angr.knowledge_plugins.cfg.CFGModel* method), 533

get_arg_info() (*angr.calling_conventions.SimCC* method), 492

get_arg_info() (*angr.SimCC* method), 188

get_args() (*angr.calling_conventions.SimCC* method), 491

get_args() (*angr.SimCC* method), 187

get_ast_subexprs() (in module *angr.analyses.decompiler.utils*), 745

get_base_addr() (*angr.keyed_region.KeyedRegion* method), 620

get_basic_info() (in module *angr.flirt.build_sig*), 892

get_behavior_for_opcode() (*angr.engines.pcode.behavior.BehaviorFactory* method), 464

get_block() (*angr.knowledge_plugins.functions.function.Function* method), 557

get_block_size() (*angr.knowledge_plugins.functions.function.Function* method), 558

get_branching_nodes() (*angr.analyses.cfg.cfg_base.CFGBase* method), 651

get_branching_nodes() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 543

get_branching_nodes() (*angr.knowledge_plugins.cfg.CFGModel* method), 537

get_by_addr() (*angr.knowledge_plugins.functions.function_manager.FunctionManager* method), 554

get_by_name() (*angr.knowledge_plugins.functions.function_manager.FunctionManager* method), 554

get_byte() (*angr.state_plugins.trace_additions.ChallRespInfo* static method), 276

get_call_args() (*angr.analyses.identifier.identify.Identifier* method), 845

get_call_return() (*angr.knowledge_plugins.functions.function.Function* method), 560

get_call_sites() (*angr.knowledge_plugins.functions.function.Function* method), 560

get_call_stack_suffix() (*angr.analyses.cfg.cfg_job_base.CFGJobBase* method), 661

get_call_target() (*angr.knowledge_plugins.functions.function.Function* method), 560

get_cc() (*angr.knowledge_plugins.callsite_prototypes.CallsitePrototypes* method), 526

get_class() (*angr.state_plugins.javavm_classloader.SimJavaVmClassloader* method), 294

get_class_hierarchy() (*angr.state_plugins.javavm_classloader.SimJavaVmClassloader* method), 294

get_cmd_line_args() (*angr.simos.javavm.SimJavaVM* static method), 891

get_concrete_fd() (*angr.state_plugins.posix.SimSystemPosix* method), 246

get_concrete_state() (*angr.analyses.variable_recovery.variable_recovery.VariableRecovery* method), 526

method), 830
get_concrete_value() (angr.analyses.reaching_definitions.LiveDefinitions method), 767
get_concrete_value() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 816
get_concrete_value() (angr.analyses.reaching_definitions.ReachingDefinitions method), 787
get_concrete_value() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603
get_concrete_value() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582
get_concrete_value_from_atom() (angr.analyses.reaching_definitions.LiveDefinitions method), 767
get_concrete_value_from_atom() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603
get_concrete_value_from_atom() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582
get_concrete_value_from_definition() (angr.analyses.reaching_definitions.LiveDefinitions method), 767
get_concrete_value_from_definition() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603
get_concrete_value_from_definition() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582
get_cpp_function_name() (in module angr.utils.library), 901
get_data_dep() (angr.analyses.data_dep.data_dependency_analysis.DataDependencyGraphAnalysis method), 876
get_data_references() (angr.knowledge_plugins.cfg.cfg_node.CFGNode method), 548
get_data_references() (angr.knowledge_plugins.cfg.CFGNode method), 529
get_data_size() (angr.PTChunk method), 209
get_data_size() (angr.state_plugins.heap.heap_freelist.Cat method), 300
get_data_size() (angr.state_plugins.heap.heap_ptmalloc.Cat method), 302
get_dbinfo() (angr.angrdb.db.AngrDB method), 677
get_default_optimization_passes() (in module angr.analyses.decompiler.optimization_passes), 704
get_default_value_by_type() (angr.simos.javavm.SimJavaVM static method), 890
get_definitions() (angr.analyses.reaching_definitions.LiveDefinitions method), 765
get_definitions() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 816
get_definitions() (angr.analyses.reaching_definitions.ReachingDefinitions method), 786
get_definitions() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 602
get_definitions() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 581
get_definitions_from_atoms() (angr.analyses.reaching_definitions.LiveDefinitions method), 767
get_definitions_from_atoms() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603
get_definitions_from_atoms() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582
get_defs() (angr.analyses.reaching_definitions.ReachingDefinitionsMode method), 779
get_defs() (angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel method), 607
get_defs() (angr.knowledge_plugins.key_definitions.ReachingDefinitionsMode method), 575
get_dependants() (angr.analyses.cdg.CDG method), 675
get_live_definitions() (angr.analyses.decompiler.structured_codegen.base.PositionalStructuredCodegen method), 726
get_exit_livedefinitions() (in module angr.analyses.reaching_definitions.function_handler), 802
get_exit_stmt_idx() (angr.analyses.cfg.cfg_base.CFGBase method), 661
get_exit_stmt_idx() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 543
get_exit_stmt_idx() (angr.knowledge_plugins.cfg.CFGModel method), 537
get_expr_depth() (angr.state_plugins.trace_additions.ZenPlugin method), 276
get_flag() (angr.state_plugins.posix.SimSystemPosix method), 246
get_flag_bytes() (angr.state_plugins.trace_additions.ZenPlugin method), 277
get_flag_rand_args() (angr.state_plugins.trace_additions.ZenPlugin static method), 276
get_footprint() (angr.calling_conventions.SimArrayArg method), 488

`get_footprint()` (*angr.calling_conventions.SimComboArg* method), 487
`get_footprint()` (*angr.calling_conventions.SimFunctionArgument* method), 486
`get_footprint()` (*angr.calling_conventions.SimReferenceArgument* method), 488
`get_footprint()` (*angr.calling_conventions.SimRegArg* method), 486
`get_footprint()` (*angr.calling_conventions.SimStackArg* method), 487
`get_footprint()` (*angr.calling_conventions.SimStructArg* method), 487
`get_func_addr_from_addr()` (*angr.knowledge_plugins.sync.sync_controller.SyncController* method), 614
`get_func_info()` (*angr.analyses.identifier.identify.Identifier* method), 845
`get_function_diff()` (*angr.analyses.bindiff.BinDiff* method), 636
`get_function_manager()` (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 571
`get_function_name()` (in module *angr.utils.library*), 900
`get_function_subgraph()` (*angr.analyses.cfg.cfg_emulated.CFGEmulated* method), 648
`get_global_variables()` (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 568
`get_guardians()` (*angr.analyses.cdg.CDG* method), 675
`get_heap_definitions()` (*angr.analyses.reaching_definitions.LiveDefinitions* method), 766
`get_heap_definitions()` (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* method), 602
`get_heap_definitions()` (*angr.knowledge_plugins.key_definitions.LiveDefinitions* method), 581
`get_heap_offset()` (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 769
`get_heap_offset()` (*angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions* static method), 812
`get_heap_offset()` (*angr.analyses.reaching_definitions.ReachingDefinitions* static method), 782
`get_heap_offset()` (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* static method), 605
`get_heap_offset()` (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 585
`get_implementers()` (*angr.analyses.soot_class_hierarchy.SootClassHierarchy* method), 640
`get_info()` (*angr.angrdb.db.AngrDB* static method),
`get_intersecting_functions()` (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 544
`get_intersecting_functions()` (*angr.knowledge_plugins.cfg.CFGModel* method), 538
`get_irsb_at()` (*angr.analyses.datagraph_meta.DataGraphMeta* method), 675
`get_knowledge()` (*angr.knowledge_base.knowledge_base.KnowledgeBase* method), 523
`get_knowledge()` (*angr.KnowledgeBase* method), 211
`get_last_statement()` (*angr.analyses.decompiler.condition_processor.ConditionProcessor* class method), 698
`get_last_statement_index()` (*angr.annocfg.AnnotatedCFG* method), 882
`get_last_statements()` (*angr.analyses.decompiler.condition_processor.ConditionProcessor* class method), 698
`get_loop_block_knowledges()` (*angr.analyses.cfg.cfg_base.CFGBase* method), 651
`get_loops()` (*angr.annocfg.AnnotatedCFG* method), 882
`get_max_sinkhole()` (*angr.state_plugins.cgc.SimStateCGC* method), 273
`get_memory_definitions()` (*angr.knowledge_plugins.reaching_definitions.LiveDefinitions* method), 766
`get_memory_definitions()` (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* method), 603
`get_memory_definitions()` (*angr.knowledge_plugins.key_definitions.LiveDefinitions* method), 582
`get_method_definition_type()` (*angr.simos.javavm.SimJavaVM* method), 891
`get_model()` (*angr.knowledge_plugins.key_definitions.key_definition_manager.KeyDefinitionManager* method), 596
`get_model()` (*angr.knowledge_plugins.key_definitions.KeyDefinitionManager* method), 576
`get_model_state()` (*angr.knowledge_plugins.cfg.cfg_manager.CFGManager* method), 538
`get_model_state()` (*angr.knowledge_plugins.cfg.CFGManager* method), 538
`get_native_type()` (*angr.state_plugins.filesystem.SimFilesystem* method), 250
`get_native_type()` (*angr.simos.javavm.SimJavaVM* method), 891
`get_native_type()` (*angr.simos.javavm.SimJavaVM* method), 891

<code>method</code>), 891	<code>get_observation_by_stmt()</code>
<code>get_nearest_pos()</code> (<code>angr.analyses.decompiler.structured_codegen.haskell.knowledge_mappings.key_definitions.ReachingDefinitionsModel</code>), 726	<code>get_one_value()</code> (<code>angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsModel</code>), 576
<code>get_new_uuid()</code> (<code>angr.storage.memory_mixins.javavm_memory_mixins.java_byte_array_memory_mixins.LiveDefinitionsModel</code>), 376	<code>get_one_value()</code> (<code>angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsModel</code>), 767
<code>get_node()</code> (<code>angr.analyses.cfg.cfg_base.CFGBase</code>), 650	<code>get_one_value()</code> (<code>angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsModel</code>), 816
<code>get_node()</code> (<code>angr.analyses.decompiler.structured_codegen.haskell.knowledge_mappings.key_definitions.ReachingDefinitionsModel</code>), 726	<code>get_one_value()</code> (<code>angr.analyses.reaching_definitions.ReachingDefinitionsModel</code>), 786
<code>get_node()</code> (<code>angr.knowledge_plugins.cfg.cfg_model.CFGModel</code>), 540	<code>get_one_value()</code> (<code>angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitionsModel</code>), 603
<code>get_node()</code> (<code>angr.knowledge_plugins.cfg.CFGModel</code>), 533	<code>get_one_value()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitionsModel</code>), 582
<code>get_node()</code> (<code>angr.knowledge_plugins.functions.function.FunctionModel</code>), 558	<code>get_one_value_from_atom()</code>
<code>get_normalized_block()</code>	<code>get_one_value_from_atom()</code> (<code>angr.analyses.reaching_definitions.LiveDefinitionsModel</code>), 767
<code>(angr.analyses.bindiff.FunctionDiff</code> static <code>method</code>), 635	<code>get_one_value_from_atom()</code>
<code>get_objects_by_offset()</code>	<code>get_one_value_from_atom()</code> (<code>angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitionsModel</code>), 603
<code>(angr.keyed_region.KeyedRegion</code> static <code>method</code>), 620	<code>get_one_value_from_atom()</code>
<code>get_observation_by_exit()</code>	<code>get_one_value_from_atom()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitionsModel</code>), 582
<code>(angr.analyses.reaching_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 780	<code>get_one_value_from_definition()</code>
<code>get_observation_by_exit()</code>	<code>get_one_value_from_definition()</code> (<code>angr.analyses.reaching_definitions.LiveDefinitionsModel</code>), 767
<code>(angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel</code> static <code>method</code>), 608	<code>get_one_value_from_definition()</code>
<code>get_observation_by_exit()</code>	<code>get_one_value_from_definition()</code> (<code>angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitionsModel</code>), 603
<code>(angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 576	<code>get_one_value_from_definition()</code>
<code>get_observation_by_insn()</code>	<code>get_one_value_from_definition()</code> (<code>angr.knowledge_plugins.key_definitions.LiveDefinitionsModel</code>), 582
<code>(angr.analyses.reaching_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 779	<code>get_optimization_passes()</code> (in module <code>angr.analyses.decompiler.optimization_passes</code>), 704
<code>get_observation_by_insn()</code>	<code>get_optimization_passes()</code> (<code>angr.knowledge_plugins.patches.PatchManager</code>), 524
<code>(angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel</code> static <code>method</code>), 607	<code>get_phi_subvariables()</code>
<code>get_observation_by_insn()</code>	<code>get_phi_subvariables()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>(angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 575	<code>get_phi_variables()</code>
<code>get_observation_by_node()</code>	<code>get_phi_variables()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>(angr.analyses.reaching_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 779	<code>get_plugin()</code> (<code>angr.knowledge_base.knowledge_base.KnowledgeBase</code>), 211
<code>get_observation_by_node()</code>	<code>get_plugin()</code> (<code>angr.knowledge_base.knowledge_base.KnowledgeBase</code>), 211
<code>(angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel</code> static <code>method</code>), 607	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>get_observation_by_node()</code>	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>(angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 576	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>get_observation_by_stmt()</code>	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>(angr.analyses.reaching_definitions.ReachingDefinitionsModel</code> static <code>method</code>), 779	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>get_observation_by_stmt()</code>	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569
<code>(angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel</code> static <code>method</code>), 608	<code>get_plugin()</code> (<code>angr.knowledge_plugins.variables.variable_manager.VariableManager</code>), 569

method), 650
get_predecessors() (angr.analyses.ddg.DDG method), 752
get_predecessors() (angr.analyses.vsa_ddg.VSA_DDG method), 854
get_predecessors() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 541
get_predecessors() (angr.knowledge_plugins.cfg.CFGModel method), 534
get_predecessors_and_jumpkind() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 542
get_predecessors_and_jumpkind() (angr.knowledge_plugins.cfg.CFGModel method), 536
get_predecessors_and_jumpkinds() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 542
get_predecessors_and_jumpkinds() (angr.knowledge_plugins.cfg.CFGModel method), 536
get_prototype() (angr.knowledge_plugins.callsite_prototypes.CallSitePrototypes method), 526
get_prototype() (angr.procedures.definitions.SimCppLibrary method), 480
get_prototype() (angr.procedures.definitions.SimLibrary method), 479
get_prototype() (angr.procedures.definitions.SimSyscallLibrary method), 483
get_prototype_type() (angr.knowledge_plugins.callsite_prototypes.CallSitePrototypes method), 526
get_reaching_definitions() (angr.analyses.reaching_definitions.reaching_definitions.LiveDefinitions method), 797
get_reaching_definitions() (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis method), 776
get_reaching_definitions_by_insn() (angr.analyses.reaching_definitions.reaching_definitions.LiveDefinitions method), 797
get_reaching_definitions_by_insn() (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis method), 776
get_reaching_definitions_by_node() (angr.analyses.reaching_definitions.reaching_definitions.LiveDefinitions method), 797
get_reaching_definitions_by_node() (angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis method), 776
get_real_len() (angr.state_plugins.trace_additions.ChallRespInfo method), 276
get_recent_bbl_addrs() (angr.state_plugins.unicorn_engine.Unicorn method), 290
get_recent_n() (angr.exploration_techniques.spiller.PickledStatesDb method), 412
get_ref() (angr.state_hierarchy.StateHierarchy method), 389
get_ref() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 180
get_reg_name() (angr.analyses.identifier.identify.Identifier static method), 845
get_register_definitions() (angr.analyses.reaching_definitions.LiveDefinitions method), 766
get_register_definitions() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 602
get_register_definitions() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 581
get_regs() (angr.state_plugins.unicorn_engine.Unicorn method), 290
get_run() (angr.annocfg.AnnotatedCFG method), 881
get_same_length_constraints() (angr.knowledge_plugins.trace_additions.ChallRespInfo method), 276
get_segment_register_name() (angr.simos.linux.SimLinux method), 887
get_segment_register_name() (angr.simos.windows.SimWindows method), 890
get_size() (angr.PTChunk method), 209
get_size() (angr.state_plugins.heap.heap_freelist.Chunk method), 300
get_size() (angr.state_plugins.heap.heap_ptmalloc.PTChunk method), 302
get_sp() (angr.analyses.reaching_definitions.reaching_definitions.LiveDefinitions method), 764
get_sp() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions method), 813
get_sp() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 783
get_sp() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 600
get_sp() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 579
get_sp_offset() (angr.analyses.reaching_definitions.LiveDefinitions method), 764
get_sp_offset() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 600
get_sp_offset() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 579
get_stack_address() (angr.analyses.reaching_definitions.LiveDefinitions method), 764
get_stack_address() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions method), 764

method), 813

get_stack_address() (angr.analyses.reaching_definitions.ReachingDefinitions method), 783

get_stack_address() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 600

get_stack_address() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 579

get_stack_definitions() (angr.analyses.reaching_definitions.LiveDefinitions method), 766

get_stack_definitions() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 602

get_stack_definitions() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 581

get_stack_offset() (angr.analyses.reaching_definitions.LiveDefinitions static method), 763

get_stack_offset() (angr.analyses.reaching_definitions.ReachingDefinitions static method), 782

get_stack_offset() (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase method), 826

get_stack_offset() (angr.knowledge_plugins.key_definitions.LiveDefinitions static method), 599

get_stack_offset() (angr.knowledge_plugins.key_definitions.LiveDefinitions static method), 578

get_stack_values() (angr.analyses.reaching_definitions.LiveDefinitions method), 766

get_stack_values() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 602

get_stack_values() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 581

get_stdin_indices() (angr.state_plugins.trace_additions.ChallRespInfo method), 276

get_stdout_indices() (angr.state_plugins.trace_additions.ChallRespInfo method), 276

get_stop_details() (angr.state_plugins.unicorn_engine.Unicorn method), 290

get_stop_msg() (angr.state_plugins.unicorn_engine.STOP static method), 287

get_structurer_option() (in module angr.analyses.decompiler.decompilation_options), 700

get_stub() (angr.procedures.definitions.SimCppLibrary method), 480

get_stub() (angr.procedures.definitions.SimLibrary method), 479

get_stub() (angr.procedures.definitions.SimSyscallLibrary method), 483

get_sub_classes() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641

get_sub_classes_including() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641

get_sub_interfaces() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640

get_sub_interfaces_including() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640

get_subgraph() (angr.analyses.cfg.cfg_emulated.CFGEmulated method), 648

get_successors() (angr.analyses.cfg.cfg_base.CFGBase method), 650

get_successors() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 541

get_successors() (angr.knowledge_plugins.cfg.CFGModel method), 535

get_successors_and_jumpkind() (angr.analyses.cfg.cfg_base.CFGBase method), 648

get_successors_and_jumpkind() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 542

get_successors_and_jumpkind() (angr.knowledge_plugins.cfg.CFGModel method), 535

get_successors_and_jumpkinds() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 542

get_successors_and_jumpkinds() (angr.knowledge_plugins.cfg.CFGModel method), 535

get_super_classes() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640

get_super_classes_including() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640

get_superclass() (angr.state_plugins.javavm_classloader.SimJavaVmClassLoader method), 294

get_symbolic_addrs() (angr.storage.memory_mixins.convenient_mappings_mixin.ConvenientMappingsMixin method), 348

get_targets() (angr.annocfg.AnnotatedCFG method), 882

get_tmp_definitions() (angr.analyses.reaching_definitions.LiveDefinitions method), 766

get_tmp_definitions() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 766

method), 602

get_tmp_definitions() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 581

get_topological_order() (angr.analyses.cfg.cfg_emulated.CFGEEmulated method), 648

get_type() (angr.state_plugins.trace_additions.FormatInfo method), 274

get_type() (angr.state_plugins.trace_additions.FormatInfo method), 274

get_type() (angr.state_plugins.trace_additions.FormatInfo method), 274

get_type() (angr.state_plugins.trace_additions.FormatInfo method), 274

get_type_variable() (angr.analyses.typehoon.typevars.TypeVariables method), 840

get_unambiguous_name() (angr.knowledge_plugins.functions.function.Function method), 562

get_unconstrained_simprocedure() (angr.engines.soot.engine.SootMixin method), 432

get_unified_local_vars() (angr.analyses.decompiler.structured_codegen.c.CFunction method), 729

get_unified_variables() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 568

get_unique_label() (angr.knowledge_plugins.labels.Label method), 553

get_unique_strings() (in module angr.flirt.build_sig), 893

get_unique_symbol_name() (angr.analyses.reassembler.SymbolManager method), 861

get_uses() (angr.knowledge_plugins.key_definitions.Uses method), 585

get_uses() (angr.knowledge_plugins.key_definitions.uses.Uses method), 610

get_uses_by_insaddr() (angr.knowledge_plugins.key_definitions.Uses method), 586

get_uses_by_insaddr() (angr.knowledge_plugins.key_definitions.uses.Uses method), 611

get_uses_by_location() (angr.knowledge_plugins.key_definitions.Uses method), 586

get_uses_by_location() (angr.knowledge_plugins.key_definitions.uses.Uses method), 611

get_uses_with_expr() (angr.knowledge_plugins.key_definitions.Uses method), 586

get_uses_with_expr() (angr.knowledge_plugins.key_definitions.uses.Uses method), 610

get_value() (angr.calling_conventions.SimArrayArg method), 488

get_value() (angr.calling_conventions.SimComboArg method), 487

get_value() (angr.calling_conventions.SimFunctionArgument method), 486

get_value() (angr.calling_conventions.SimLyingRegArg method), 492

get_value() (angr.calling_conventions.SimReferenceArgument method), 488

get_value() (angr.calling_conventions.SimRegArg method), 486

get_value() (angr.calling_conventions.SimStackArg method), 487

get_value() (angr.calling_conventions.SimStructArg method), 488

get_value_from_atom() (angr.analyses.reaching_definitions.LiveDefinitions method), 767

get_value_from_atom() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603

get_value_from_atom() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 582

get_value_from_definition() (angr.analyses.reaching_definitions.LiveDefinitions method), 767

get_value_from_definition() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603

get_value_from_definition() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582

get_values() (angr.analyses.reaching_definitions.LiveDefinitions method), 767

get_values() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions method), 816

get_values() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 786

get_values() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 603

get_values() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 582

get_variable() (angr.analyses.decompiler.optimization_passes.engine_b method), 712

get_variable() (angr.state_plugins.debug_variables.SimDebugVariable method), 309

get_variable_accesses()

(`angr.knowledge_plugins.variables.variable_manager.VariableManager` method), 571

`get_variable_accesses()` (`angr.knowledge_plugins.variables.variable_manager.GlobalDescriptorTable` method), 568

`get_variable_definitions()` (`angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase` method), 824

`get_variable_definitions()` (`angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase` method), 826

`get_variable_type()` (`angr.knowledge_plugins.variables.variable_manager.GlobalDescriptorTable` method), 570

`get_variables()` (`angr.knowledge_plugins.variables.variable_manager.GlobalDescriptorTable` method), 568

`get_variables()` (`angr.state_plugins.solver.SimSolver` method), 255

`get_variables_by_offset()` (`angr.keyed_region.KeyedRegion` method), 620

`get_variables_without_writes()` (`angr.knowledge_plugins.variables.variable_manager.GlobalDescriptorTable` method), 569

`get_whitelisted_statements()` (`angr.annocfg.AnnotatedCFG` method), 881

`get_xrefs_by_dst()` (`angr.knowledge_plugins.xrefs.xref_manager.XRefManager` method), 615

`get_xrefs_by_dst_region()` (`angr.knowledge_plugins.xrefs.xref_manager.XRefManager` method), 615

`get_xrefs_by_ins_addr()` (`angr.knowledge_plugins.xrefs.xref_manager.XRefManager` method), 615

`get_xrefs_by_ins_addr_region()` (`angr.knowledge_plugins.xrefs.xref_manager.XRefManager` method), 616

`getpiece()` (`angr.analyses.disassembly.DisassemblyPiece` method), 856

`getstate()` (`angr.calling_conventions.ArgSession` method), 488

`getstate()` (`angr.calling_conventions.SerializableCounter` method), 485

`getstate()` (`angr.calling_conventions.SerializableIterator` method), 485

`getstate()` (`angr.calling_conventions.SerializableListIterator` method), 485

`getstate()` (`angr.calling_conventions.SimCC.ArgSession` method), 490

`getstate()` (`angr.calling_conventions.UsercallArgSession` method), 489

`getstate()` (`angr.SimCC.ArgSession` method), 186

`give_up_on_memory_tracking()` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` method), 822

`global_addr()` (`angr.knowledge_plugins.key_definitions.definition.Definition` attribute), 593

`GlobalDescriptorTable` (class in `angr.simos.simos`), 886

`GotoSimplifier` (class in `angr.analyses.variable_recovery.decompiler.region_simplifiers.goto`), 720

`GOTPLTEEntry` (`angr.knowledge_plugins.cfg.memory_data.MemoryDataSort` attribute), 545

`GOTPLTEEntry` (`angr.knowledge_plugins.cfg.MemoryDataSort` attribute), 526

`graph` (`angr.knowledge_plugins.cfg.cfg_fast.CFGJob` attribute), 656

`gp_register_read_hook()` (`angr.knowledge_plugins.functions.function.Function` method), 670

`gp_register_write_hook()` (`angr.analyses.cfg.indirect_jump_resolvers.jumtable.MIPSGPH` method), 670

`graph` (`angr.analyses.cdg.CDG` property), 675

`graph` (`angr.analyses.cfg.cfg_base.CFGBase` property), 651

`graph` (`angr.analyses.cfg.cfg_emulated.CFGEEmulated` property), 648

`graph` (`angr.analyses.cfg.cfg_fast.CFGFast` property), 659

`graph` (`angr.analyses.data_dep.data_dependency_analysis.DataDependency` property), 875

`graph` (`angr.analyses.ddg.DDG` property), 752

`graph` (`angr.analyses.decompiler.graph_region.GraphRegion` attribute), 703

`graph` (`angr.analyses.forward_analysis.forward_analysis.ForwardAnalysis` property), 625

`graph` (`angr.analyses.reaching_definitions.dep_graph.DepGraph` property), 799

`graph` (`angr.analyses.typehoon.simple_solver.Sketch` attribute), 833

`graph` (`angr.knowledge_plugins.cfg.cfg_model.CFGModel` attribute), 539

`graph` (`angr.knowledge_plugins.cfg.CFGModel` attribute), 532

`graph` (`angr.knowledge_plugins.functions.function.Function` property), 560

`graph_ex()` (`angr.knowledge_plugins.functions.function.Function` method), 560

`graph_with_successors` (`angr.analyses.decompiler.graph_region.GraphRegion` attribute), 703

`GraphChangedNotification`, 692

`GraphRegion` (class in `angr.analyses.decompiler.graph_region`), 702

`GraphUtils` (class in `angr.utils.graph`), 897

`GraphVisitor` (class in `angr.knowledge_plugins.functions.function`), 897

`angr.analyses.forward_analysis.visitors.graph`),
 628
`GT` (`angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.CmpOps` attribute), 722
`GUARD` (`angr.analyses.reaching_definitions.AtomKind` attribute), 770
`guard` (`angr.errors.SimError` attribute), 905
`GUARD` (`angr.knowledge_plugins.key_definitions.atoms.AtomKind` attribute), 588
`GuardUse` (class in `angr.analyses.reaching_definitions`), 773
`GuardUse` (class in `angr.knowledge_plugins.key_definitions.atoms`), 590
`guess_prototype()` (`angr.calling_conventions.SimCC` static method), 491
`guess_prototype()` (`angr.calling_conventions.SimCCSoon` static method), 502
`guess_prototype()` (`angr.SimCC` static method), 186
`guess_value_type()` (in module `angr.analyses.decompiler.structured_codegen.c`), 727
`guessed_cc` (`angr.analyses.reaching_definitions.function_handler.FunctionCallData` attribute), 805
`guessed_cc` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 791
`guessed_prototype` (`angr.analyses.reaching_definitions.function_handler.FunctionCallData` attribute), 805
`guessed_prototype` (`angr.analyses.reaching_definitions.FunctionCallData` attribute), 791
H
`handle()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CAssignment()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CAssignment()` (`angr.analyses.decompiler.structured_codegen.c.MakeTypecastsSimplifier` class method), 743
`handle_CBinaryOp()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CBinaryOp()` (`angr.analyses.decompiler.structured_codegen.c.MakeTypecastsSimplifier` class method), 744
`handle_CBinaryOp()` (`angr.analyses.decompiler.structured_codegen.c.PolynomialArithmeticFixer` class method), 744
`handle_CDoWhileLoop()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CForLoop()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CFunction()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CFunctionCall()` (`angr.analyses.decompiler.structured_codegen.c.StructuredCodeWalker` class method), 743
`handle_CFunctionCall()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CGoto()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CIfBreak()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CIfElse()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CIndexedVariable()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CITE()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CReturn()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CReturn()` (`angr.analyses.decompiler.structured_codegen.c.MakeTypecastsSimplifier` class method), 744
`handle_CStatements()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CSwitchCase()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CTypeCast()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CTypeCast()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 744
`handle_CTypeCast()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 744
`handle_CUnaryOp()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CVariableField()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_CWhileLoop()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_default()` (`angr.analyses.decompiler.structured_codegen.c.CStructuralCodeWalker` class method), 743
`handle_exception()` (`angr.simos.simos.SimOS` method), 169
`handle_exception()` (`angr.simos.simos.SimOS` method), 885
`handle_exception()` (`angr.simos.windows.SimWindows` method), 889
`handle_external_function()` (`angr.analyses.reaching_definitions.function_handler.FunctionHandler` method), 808
`handle_external_function()` (`angr.analyses.reaching_definitions.FunctionHandler` method), 789
`handle_function()` (`angr.analyses.reaching_definitions.function_handler.FunctionHandler` method), 807

<code>handle_function()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 788	<code>has_metadata()</code> (angr.state_plugins.unicorn_engine.VEXStmtDetails attribute), 285
<code>handle_generic_function()</code> (angr.analyses.reaching_definitions.function_handler. FunctionHandler method), 808	<code>has_metadata()</code> (angr.procedures.definitions.SimCppLibrary method), 480
<code>handle_generic_function()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 788	<code>has_metadata()</code> (angr.procedures.definitions.SimLibrary method), 479
<code>handle_indirect_function()</code> (angr.analyses.reaching_definitions.function_handler. FunctionHandler method), 808	<code>has_metadata()</code> (angr.procedures.definitions.SimSyscallLibrary method), 483
<code>handle_indirect_function()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 788	<code>has_model()</code> (angr.knowledge_plugins.key_definitions.key_definition_manager. KeyDefinitionManager method), 596
<code>handle_indirect_function()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 788	<code>has_model()</code> (angr.knowledge_plugins.key_definitions.KeyDefinitionManager method), 576
<code>handle_local_function()</code> (angr.analyses.find_objects_static.NewFunctionHandler method), 855	<code>has_nonlabel_statements()</code> (in module angr.analyses.decompiler.utils), 746
<code>handle_local_function()</code> (angr.analyses.reaching_definitions.function_handler. FunctionHandler method), 808	<code>has_plugin()</code> (angr.knowledge_base.knowledge_base.KnowledgeBase method), 523
<code>handle_local_function()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 788	<code>has_plugin()</code> (angr.KnowledgeBase method), 211
<code>handle_pcode_block()</code> (angr.engines.pcode.emulate.PcodeEmulatorMixin method), 445	<code>has_plugin()</code> (angr.misc.plugins.PluginHub method), 201
<code>hardcopy</code> (angr.state_plugins.history.TreeIter property), 270	<code>has_plugin()</code> (angr.sim_state.SimState method), 226
<code>HAS_BITSHIFTS</code> (angr.analyses.code_tagging.CodeTags attribute), 675	<code>has_plugin()</code> (angr.SimState method), 182
<code>has_bitshifts()</code> (angr.analyses.code_tagging.CodeTagging method), 676	<code>has_plugin_preset</code> (angr.misc.plugins.PluginHub property), 223
<code>has_clobbered()</code> (angr.analyses.reaching_definitions.function_handler. FunctionHandler method), 805	<code>has_prototype()</code> (angr.knowledge_plugins.callsite_prototypes.CallsitePrototype method), 526
<code>has_clobbered()</code> (angr.analyses.reaching_definitions. FunctionHandler method), 792	<code>has_prototype()</code> (angr.procedures.definitions.SimCppLibrary method), 481
<code>has_default_value</code> (angr.sim_state_options.StateOption property), 228	<code>has_prototype()</code> (angr.procedures.definitions.SimLibrary method), 479
<code>has_function_manager()</code> (angr.knowledge_plugins.variables.variable_manager. VariableManager method), 571	<code>has_prototype()</code> (angr.procedures.definitions.SimSyscallLibrary method), 484
<code>has_implementation()</code> (angr.procedures.definitions.SimCppLibrary method), 481	<code>has_remote</code> (angr.knowledge_plugins.sync.sync_controller.SyncController attribute), 548
<code>has_implementation()</code> (angr.procedures.definitions.SimLibrary method), 479	<code>has_return</code> (angr.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 548
<code>has_implementation()</code> (angr.procedures.definitions.SimSyscallLibrary method), 484	<code>has_return</code> (angr.knowledge_plugins.cfg.CFGNode attribute), 529
<code>has_job()</code> (angr.analyses.forward_analysis.forward_analysis.ForwardAnalysis method), 626	<code>has_return</code> (angr.knowledge_plugins.functions.function.Function property), 562
<code>has_load</code> (angr.analyses.decompiler.region_simplifiers.expr_folding.ExprSimplifier attribute), 719	<code>has_sql</code> (angr.analyses.code_tagging.CodeTagging attribute), 676
	<code>has_sql()</code> (angr.analyses.code_tagging.CodeTagging method), 676
	<code>has_statements</code> (angr.engines.pcode.lifter.IRSB property), 438
	<code>has_store()</code> (angr.analyses.decompiler.region_simplifiers.expr_folding.ExprSimplifier method), 720
	<code>has_super_class()</code> (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640
	<code>has_symbolic_exit</code> (angr.state_plugins.unicorn_engine.BlockDetails attribute), 285
	<code>has_tmpexpr()</code> (angr.analyses.propagator.engine_ail.SimEnginePropagator attribute), 719
	<code>has_type_variable_for()</code>

[\(angr.analyses.typehoon.typevars.TypeVariables method\), 841](#)
[has_unresolved_calls \(angr.knowledge_plugins.functions.function.Function property\), 558](#)
[has_unresolved_jumps \(angr.knowledge_plugins.functions.function.Function property\), 558](#)
[HAS_XOR \(angr.analyses.code_tagging.CodeTags attribute\), 675](#)
[has_xor\(\) \(angr.analyses.code_tagging.CodeTagging method\), 676](#)
[HasCallExprWalker \(class in angr.analyses.decompiler.block_simplifier\), 694](#)
[HasCallNotification, 693](#)
[HasField \(class in angr.analyses.typehoon.typevars\), 842](#)
[HasNext \(angr.analyses.loop_analysis.VariableTypes attribute\), 846](#)
[head \(angr.analyses.decompiler.graph_region.GraphRegion attribute\), 703](#)
[head \(angr.analyses.decompiler.structuring.structurer_nodes.IncompleteSwitchCaseNode attribute\), 691](#)
[headerless_c_repr_chunks\(\) \(angr.analyses.decompiler.structured_codegen.c.CFunction method\), 729](#)
[heap \(angr.analyses.reaching_definitions.LiveDefinitions attribute\), 762](#)
[heap \(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions property\), 813](#)
[heap \(angr.analyses.reaching_definitions.ReachingDefinitions property\), 783](#)
[heap \(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute\), 598](#)
[heap \(angr.knowledge_plugins.key_definitions.LiveDefinitions attribute\), 577](#)
[heap_address\(\) \(angr.analyses.reaching_definitions.LiveDefinitions method\), 770](#)
[heap_address\(\) \(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions method\), 811](#)
[heap_address\(\) \(angr.analyses.reaching_definitions.ReachingDefinitions method\), 782](#)
[heap_address\(\) \(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method\), 606](#)
[heap_address\(\) \(angr.knowledge_plugins.key_definitions.LiveDefinitions method\), 585](#)
[heap_allocator \(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions attribute\), 811](#)
[heap_allocator \(angr.analyses.reaching_definitions.ReachingDefinitions attribute\), 781](#)
[heap_definitions \(angr.analyses.reaching_definitions.LiveDefinitions property\), 763](#)
[heap_definitions \(angr.knowledge_plugins.key_definitions.LiveDefinitions property\), 599](#)
[heap_definitions \(angr.knowledge_plugins.key_definitions.definition.Definition attribute\), 593](#)
[heap_uses \(angr.analyses.reaching_definitions.LiveDefinitions attribute\), 762](#)
[heap_uses \(angr.analyses.reaching_definitions.rd_state.ReachingDefinitions property\), 813](#)
[heap_uses \(angr.analyses.reaching_definitions.ReachingDefinitionsState property\), 783](#)
[heap_uses \(angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute\), 598](#)
[heap_uses \(angr.knowledge_plugins.key_definitions.LiveDefinitions attribute\), 577](#)
[HeapAddress \(class in angr.knowledge_plugins.key_definitions.heap_address\), 595](#)
[HeapAllocator \(class in angr.analyses.reaching_definitions.heap_allocator\), 801](#)
[HeavyPcodeMixin \(class in angr.engines.pcode.engine\), 425](#)
[height\(\) \(angr.analyses.disassembly.Comment method\), 859](#)
[height\(\) \(angr.analyses.disassembly.DisassemblyPiece method\), 856](#)
[height\(\) \(angr.analyses.disassembly.FunctionStart method\), 856](#)
[hexdump\(\) \(angr.storage.memory_mixins.hex_dumper_mixin.HexDumper method\), 341](#)
[HexDumperMixin \(class in angr.storage.memory_mixins.hex_dumper_mixin\), 341](#)
[highlight\(\) \(angr.analyses.disassembly.DisassemblyPiece method\), 856](#)
[history \(angr.sim_state.SimState attribute\), 225](#)
[history \(angr.SimState attribute\), 181](#)
[history_contains\(\) \(angr.state_hierarchy.StateHierarchy method\), 180](#)
[history_contains\(\) \(angr.StateHierarchy method\), 180](#)
[history_predecessors\(\) \(angr.StateHierarchy method\), 390](#)
[history_predecessors\(\) \(angr.StateHierarchy method\), 180](#)
[history_successors\(\) \(angr.StateHierarchy method\), 180](#)
[HistoryIter \(class in angr.state_plugins.history\), 270](#)
[HistoryTrackingMixin \(class in angr.knowledge_plugins.history_plugins.history_tracking_mixin\), 270](#)

angr.storage.memory_mixins.paged_memory.paged_memory_mixin , 361	Identify (class in angr.knowledge_plugins.disassembly.OperandPiece attribute) , 858
Hook (class in angr.analyses.disassembly) , 857	ident (angr.angrdb.models.DbCFGModel attribute) , 679
hook() (angr.analyses.cfg.indirect_jump_resolvers.jumptable static method), 669	ident_hook (angr.angrdb.models.DbVariableCollection attribute) , 680
hook() (angr.analyses.cfg.indirect_jump_resolvers.jumptable method), 669	IdentHook (angr.knowledge_plugins.cfg.cfg_model.CFGModel attribute) , 539
hook() (angr.analyses.cfg.indirect_jump_resolvers.jumptable static method), 669	IdentHook (angr.knowledge_plugins.cfg.CFGModel attribute) , 532
hook() (angr.analyses.find_objects_static.NewFunctionHandler method), 855	ident (angr.sim_variable.SimVariable attribute) , 504
hook() (angr.analyses.reaching_definitions.function_handler.FunctionHandler method), 807	identical_blocks (angr.analyses.bindiff.BinDiff property) , 636
hook() (angr.analyses.reaching_definitions.FunctionHandler method), 787	identical_blocks (angr.analyses.bindiff.FunctionDiff property) , 634
hook() (angr.Project method), 164	identical_functions (angr.analyses.bindiff.BinDiff property) , 635
hook() (angr.project.Project method), 214	Identifier (angr.analyses.analysis.KnownAnalysesPlugin attribute) , 623
hook() (angr.state_plugins.unicorn_engine.Unicorn method), 290	Identifier (class in angr.analyses.identifier.identify) , 845
hook_add() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288	identify_func() (angr.analyses.identifier.identify.Identifier method), 845
hook_after() (angr.analyses.cfg.indirect_jump_resolvers.jumptable method), 669	idx (angr.analyses.decompiler.structuring.structurer_nodes.CodeNode attribute) , 688
hook_before() (angr.analyses.cfg.indirect_jump_resolvers.jumptable method), 669	idx (angr.analyses.decompiler.structuring.structurer_nodes.MultiNode attribute) , 687
hook_del() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288	idx (angr.analyses.typehoon.typevars.TypeVariable attribute) , 839
hook_reset() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288	IfElseFlattener (class in angr.analyses.decompiler.region_simplifiers.ifelse) , 721
hook_symbol() (angr.Project method), 165	iffalse (angr.analyses.decompiler.structured_codegen.c.CITE attribute) , 740
hook_symbol() (angr.project.Project method), 215	IfSimplifier (class in angr.analyses.decompiler.region_simplifiers.if_) , 721
hooked_by() (angr.Project method), 165	iftrue (angr.analyses.decompiler.structured_codegen.c.CITE attribute) , 740
hooked_by() (angr.project.Project method), 214	IFUNC_HINTS (angr.analyses.cfg.cfg_fast.CFGJobType attribute) , 655
HookNode (class in angr.codenode) , 883	immediate_dominators() (angr.analyses.cfg.cfg_emulated.CFGEmulated method), 647
HooksMixin (class in angr.engines.hook) , 431	immediate_postdominators() (angr.analyses.cfg.cfg_emulated.CFGEmulated method), 647
I	import_binsync() (in module angr.knowledge_plugins.sync.sync_controller), 612
id (angr.angrdb.models.DbCFGModel attribute) , 679	ImportedLine (class in angr.analyses.decompiler.structured_codegen.dwarf_import) , 744
id (angr.angrdb.models.DbComment attribute) , 681	ImportSourceCode (class in angr.analyses.decompiler.structured_codegen.dwarf_import) , 744
id (angr.angrdb.models.DbFunction attribute) , 679	
id (angr.angrdb.models.DbInformation attribute) , 678	
id (angr.angrdb.models.DbKnowledgeBase attribute) , 678	
id (angr.angrdb.models.DbLabel attribute) , 681	
id (angr.angrdb.models.DbObject attribute) , 678	
id (angr.angrdb.models.DbStructuredCode attribute) , 680	
id (angr.angrdb.models.DbVariableCollection attribute) , 679	
id (angr.angrdb.models.DbXRefs attribute) , 680	
id (angr.exploration_techniques.spiller_db.PickledState attribute) , 413	
ident (angr.analyses.disassembly.DisassemblyPiece attribute) , 856	

744

`inc_active_workers()` (`angr.distributed.server.Server` method), 909

`inc_active_workers()` (`angr.Server` method), 210

`includes()` (`angr.keyed_region.RegionObject` method), 618

`includes()` (`angr.storage.memory_object.SimMemoryObject` method), 334

`includes_function()` (`angr.analyses.reaching_definitions.call_trace.CallTrace` method), 794

`IncompleteSwitchCaseHeadStatement` (class in `angr.analyses.decompiler.structuring.structurer_nodes`), 691

`IncompleteSwitchCaseNode` (class in `angr.analyses.decompiler.structuring.structurer_nodes`), 690

`inconsistent` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` property), 823

`inconsistent_for()` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` method), 823

`indent_str()` (`angr.analyses.decompiler.structured_codegen.c.CComment` static method), 728

`index` (`angr.utils.graph.ContainerNode` attribute), 897

`indirect_jumps` (`angr.analyses.cfg.cfg_fast.CFGFast` attribute), 660

`indirect_jumps` (`angr.analyses.cfg.cfg_fast_soot.CFGFastSoot` attribute), 675

`IndirectJump` (class in `angr.knowledge_plugins.cfg`), 531

`IndirectJump` (class in `angr.knowledge_plugins.cfg.indirect_jump`), 550

`IndirectJumpResolver` (class in `angr.analyses.cfg.indirect_jump_resolvers.resolver`), 672

`IndirectJumps` (class in `angr.knowledge_plugins.indirect_jumps`), 552

`IndirectJumpType` (class in `angr.knowledge_plugins.cfg`), 532

`IndirectJumpType` (class in `angr.knowledge_plugins.cfg.indirect_jump`), 550

`infer_shapes()` (`angr.analyses.typehoon.simple_solver.SimpleSolver` method), 835

`info` (`angr.code_location.CodeLocation` attribute), 617

`info` (`angr.knowledge_plugins.functions.function.Function` attribute), 556

`info` (`angr.knowledge_plugins.functions.soot_function.SootFunction` attribute), 564

`init_checker()` (in `angr.knowledge_plugins.sync.sync_controller`), 612

`init_class()` (`angr.state_plugins.javavm_classloader.SimJavaVmClassLoader` method), 294

`init_hierarchy()` (`angr.analyses.soot_class_hierarchy.SootClassHierarchy` method), 640

`init_state()` (`angr.SimHeapPTMalloc` method), 208

`init_state()` (`angr.SimStatePlugin` method), 163

`init_state()` (`angr.state_plugins.heap.heap_base.SimHeapBase` method), 298

`init_state()` (`angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc` method), 306

`init_state()` (`angr.state_plugins.history.SimStateHistory` method), 267

`init_state()` (`angr.state_plugins.plugin.SimStatePlugin` method), 233

`init_state()` (`angr.state_plugins.posix.SimSystemPosix` method), 245

`init_state()` (`angr.state_plugins.symbolizer.SimSymbolizer` method), 307

`init_static_field()` (`angr.simos.javavm.SimJavaVM` method), 891

`init_str()` (`angr.procedures.definitions.SimTypeCollection` method), 477

`INITIAL_SP_32BIT` (`angr.analyses.reaching_definitions.LiveDefinitions` attribute), 762

`INITIAL_SP_32BIT` (`angr.knowledge_plugins.key_definitions.live_definition` attribute), 598

`INITIAL_SP_32BIT` (`angr.knowledge_plugins.key_definitions.LiveDefinition` attribute), 577

`INITIAL_SP_64BIT` (`angr.analyses.reaching_definitions.LiveDefinitions` attribute), 762

`INITIAL_SP_64BIT` (`angr.knowledge_plugins.key_definitions.live_definition` attribute), 598

`INITIAL_SP_64BIT` (`angr.knowledge_plugins.key_definitions.LiveDefinition` attribute), 577

`InitializationFinder` (class in `angr.analyses.init_finder`), 870

`initialize()` (`angr.storage.pcap.PCAP` method), 335

`initialize()` (`angr.utils.mp.Initializer` method), 902

`initialize_dominance_frontiers()` (`angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase` method), 824

`initialize_gdt_x86()` (`angr.simos.linux.SimLinux` method), 887

`initialize_gdt_x86()` (`angr.simos.windows.SimWindows` method), 889

`initialize_segment_register_x64()` (`angr.simos.linux.SimLinux` method), 887

`initialize_segment_register_x64()` (`angr.simos.windows.SimWindows` method), 889

`initialize_variable_names()` (`angr.knowledge_plugins.variables.variable_manager.VariableManager` method), 571

[initialized_classes](#) ([angr.state_plugins.javavm_classloader.SimJavaVmClassLoader](#) attribute), 294
[initializer](#) ([angr.analyses.decompiler.structured_codegen.c.CForLoopNode](#) attribute), 731
[initializer](#) ([angr.analyses.decompiler.structuring.structurer_nodes.LoopNode](#) attribute), 689
[Initializer](#) (class in [angr.utils.mp](#)), 902
[InitialValueTag](#) (class in [angr.knowledge_plugins.key_definitions.tag](#)), 609
[inline_call\(\)](#) ([angr.sim_procedure.SimProcedure](#) method), 473
[inline_call\(\)](#) ([angr.SimProcedure](#) method), 160
[inner_step\(\)](#) ([angr.exploration_techniques.Threading](#) method), 398
[inner_step\(\)](#) ([angr.exploration_techniques.threading.Threading](#) method), 413
[input_state](#) ([angr.knowledge_plugins.cfg.cfg_node.CFGNode](#) attribute), 550
[input_state](#) ([angr.knowledge_plugins.cfg.CFGNode](#) attribute), 530
[input_variables\(\)](#) ([angr.knowledge_plugins.variables.variable_mappings.MappingFlowModel](#) method), 569
[insn_addr](#) ([angr.analyses.cfg.cfg_fast.FunctionEdge](#) attribute), 654
[insn_addr](#) ([angr.analyses.decompiler.clinic.DataRefDesc](#) attribute), 696
[insn_addr](#) ([angr.analyses.decompiler.structured_codegen.basic.MappingFlowModel](#) attribute), 726
[insn_addr](#) ([angr.analyses.decompiler.structured_codegen.c.CForLoopNode](#) attribute), 734
[insn_addr](#) ([angr.code_location.CodeLocation](#) attribute), 617
[insn_addr](#) ([angr.errors.SimError](#) attribute), 905
[insn_addr](#) ([angr.knowledge_plugins.cfg.indirect_jump.IndirectJump](#) attribute), 551
[insn_addr](#) ([angr.knowledge_plugins.cfg.IndirectJump](#) attribute), 532
[insn_addr](#) ([angr.knowledge_plugins.key_definitions.definition.Definition](#) attribute), 593
[insn_addr](#) ([angr.knowledge_plugins.xrefs.xref.XRef](#) attribute), 614
[insn_addrs](#) ([angr.state_plugins.history.SimStateHistory](#) property), 270
[insert\(\)](#) ([angr.SimMount](#) method), 203
[insert\(\)](#) ([angr.state_plugins.filesystem.SimConcreteFilesystem](#) method), 252
[insert\(\)](#) ([angr.state_plugins.filesystem.SimFilesystem](#) method), 250
[insert\(\)](#) ([angr.state_plugins.filesystem.SimMount](#) method), 251
[insert\(\)](#) ([angr.state_plugins.posix.PosixDevFS](#) method), 240
[insert\(\)](#) ([angr.state_plugins.posix.PosixProcFS](#) method), 242
[insert_asm\(\)](#) ([angr.analyses.reassembler.Reassembler](#) method), 866
[insert_node\(\)](#) ([angr.analyses.decompiler.structuring.structurer_nodes.SemanticNode](#) method), 487
[insert_node\(\)](#) (in [angr.analyses.decompiler.utils](#) module), 745
[inserted_asm_after_label](#) ([angr.analyses.reassembler.Reassembler](#) property), 865
[inserted_asm_before_label](#) ([angr.analyses.reassembler.Reassembler](#) property), 865
[insn](#) ([angr.block.CapstoneInsn](#) attribute), 220
[insn_addr_to_memory_data](#) ([angr.analyses.cfg.cfg_fast.CFGFast](#) property), 659
[insn_addr_to_memory_data](#) ([angr.knowledge_plugins.cfg.cfg_model.CFGModel](#) attribute), 539
[insn_addr_to_memory_data](#) ([angr.knowledge_plugins.cfg.cfg_model.CFGModel](#) attribute), 532
[insn_observe\(\)](#) ([angr.analyses.reaching_definitions.reaching_definitions](#) method), 797
[insn_observe\(\)](#) ([angr.analyses.reaching_definitions.ReachingDefinitions](#) method), 777
[insn_stop_ida_mapping_flow](#) ([angr.knowledge_plugins.xrefs.xref.XRef](#) attribute), 614
[InsnType](#) ([angr.knowledge_plugins.xrefs.xref.XRef](#) attribute), 615
[insns](#) ([angr.block.DisassemblerBlock](#) attribute), 220
[insns](#) ([angr.engines.pcode.lifter.PcodeDisassemblerBlock](#) attribute), 435
[inspect](#) ([angr.sim_state.SimState](#) attribute), 225
[inspect](#) ([angr.SimState](#) attribute), 181
[InspectMixinHigh](#) (class in [angr.storage.memory_mixins.clouseau_mixin](#)), 444
[InstructionMatchPredicate](#) (class in [angr.analyses.disassembly](#)), 857
[Instruction](#) (class in [angr.analyses.reassembler](#)), 862
[instruction_addresses](#) ([angr.engines.pcode.lifter.IRSB](#) property), 439
[instruction_addresses\(\)](#) ([angr.analyses.reassembler.BasicBlock](#) method), 863
[instruction_addresses\(\)](#) ([angr.analyses.reassembler.Procedure](#) method), 864
[instruction_addrs](#) ([angr.Block](#) property), 170
[instruction_addrs](#) ([angr.block.Block](#) property), 221
[instruction_addrs](#) ([angr.knowledge_plugins.cfg.cfg_node.CFGNode](#)

attribute), 548
 instruction_addrs (angr.knowledge_plugins.cfg.CFGNode attribute), 529
 instruction_size() (angr.knowledge_plugins.functions.function.Function method), 561
 InstructionError, 860
 InstructionMapping (class in ang_r.analyses.decompiler.structured_codegen.base), 726
 InstructionMappingElement (class in ang_r.analyses.decompiler.structured_codegen.base), 726
 instructions (ang_r.analyses.reassembler.Reassembler property), 865
 instructions (ang_r.Block property), 170
 instructions (ang_r.block.Block property), 221
 instructions (ang_r.engines.pcode.lifter.IRSB property), 439
 Int (class in ang_r.analyses.typehoon.typeconsts), 843
 Int1 (class in ang_r.analyses.typehoon.typeconsts), 843
 Int128 (class in ang_r.analyses.typehoon.typeconsts), 843
 Int16 (class in ang_r.analyses.typehoon.typeconsts), 843
 int2base() (in module ang_r.state_plugins.trace_additions), 274
 Int32 (class in ang_r.analyses.typehoon.typeconsts), 843
 Int64 (class in ang_r.analyses.typehoon.typeconsts), 843
 Int8 (class in ang_r.analyses.typehoon.typeconsts), 843
 int_args (ang_r.calling_conventions.SimCC property), 489
 int_args (ang_r.SimCC property), 185
 int_iter (ang_r.calling_conventions.ArgSession attribute), 488
 int_iter (ang_r.calling_conventions.SimCC.ArgSession attribute), 490
 int_iter (ang_r.SimCC.ArgSession attribute), 186
 int_len_mod (ang_r.procedures.stubs.format_parser.FormatParser attribute), 475
 int_sign (ang_r.procedures.stubs.format_parser.FormatParser attribute), 475
 int_type() (in module ang_r.analyses.typehoon.typeconsts), 845
 Integer (ang_r.analyses.proximity_graph.ProxiNodeTypes attribute), 872
 Integer (ang_r.knowledge_plugins.cfg.memory_data.MemoryDataSort attribute), 545
 Integer (ang_r.knowledge_plugins.cfg.MemoryDataSort attribute), 526
 IntegerProxiNode (class in ang_r.analyses.proximity_graph), 874
 internal_objects (ang_r.keyed_region.RegionObject property), 618
 interpret() (ang_r.procedures.stubs.format_parser.FormatParser method), 474
 intersection() (ang_r.state_plugins.sim_action_object.SimActionObject method), 469
 invalidate_direct_next() (ang_r.engines.pcode.lifter.IRSB method), 438
 inverse() (ang_r.analyses.typehoon.simple_solver.ConstraintGraphNode method), 835
 inverse_wo_tag() (ang_r.analyses.typehoon.simple_solver.ConstraintGraphNode method), 835
 inverted_idoms() (in module ang_r.utils.graph), 895
 ip (ang_r.sim_state.SimState property), 225
 ip (ang_r.SimState property), 182
 IROp (class in ang_r.analyses.disassembly), 856
 irsb (ang_r.analyses.disassembly.IROp attribute), 857
 irsb (ang_r.engines.pcode.lifter.Lifter attribute), 440
 irsb (ang_r.engines.pcode.lifter.PcodeLifter attribute), 442
 irsb (ang_r.engines.UberEngine attribute), 427
 irsb (ang_r.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 548
 irsb (ang_r.knowledge_plugins.cfg.CFGNode attribute), 529
 IRSB (class in ang_r.engines.pcode.lifter), 436
 irsb_from_node() (ang_r.analyses.vfg.VFG method), 853
 is_a_jump_target() (ang_r.analyses.decompiler.structuring.structurer_base.Static method), 692
 is_alignment (ang_r.knowledge_plugins.functions.function.Function attribute), 556
 is_alignment (ang_r.knowledge_plugins.functions.soot_function.SootFunction attribute), 564
 is_alignment_mask() (in module ang_r.utils.constants), 894
 is_arm (ang_r.knowledge_plugins.cfg.cfg_model.CFGModel attribute), 539
 is_arm (ang_r.knowledge_plugins.cfg.CFGModel attribute), 532
 is_base (ang_r.engines.light.data.SpOffset attribute), 755
 is_bool_expr() (ang_r.analyses.decompiler.peephole_optimizations.base.Static method), 716
 is_bounded() (ang_r.state_plugins.uc_manager.SimUCManager method), 280
 is_bytes (ang_r.storage.memory_object.SimMemoryObject attribute), 334
 is_class_initialized() (ang_r.state_plugins.javavm_classloader.SimJavaVmClassloader method), 294
 is_concrete() (ang_r.analyses.init_finder.SimEngineInitFinderVEX static method), 870
 is_cross_referenced() (ang_r.analyses.vtable.VtableFinder method), 854
 is_default_name (ang_r.knowledge_plugins.functions.function.Function attribute), 556
 is_default_name (ang_r.knowledge_plugins.functions.soot_function.SootFunction attribute), 556

- `attribute`), 564
- `is_empty` (*angr.engines.successors.SimSuccessors* property), 430
- `is_empty` (*angr.keyed_region.RegionObject* property), 618
- `is_empty` (*angr.storage.memory_mixins.regioned_memory.region_data_region.MemoryRegion* property), 370
- `is_empty()` (*angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSinkLoader*), 899
- `is_empty_node()` (in module *angr.analyses.decompiler.utils*), 746
- `is_empty_or_label_only_node()` (in module *angr.analyses.decompiler.utils*), 746
- `is_exception` (*angr.analyses.cfg.cfg_fast.FunctionTransitionsEdgeJumptable* attribute), 654
- `is_expr` (*angr.analyses.decompiler.structured_codegen.c.FromMachineWordSizeType* attribute), 733
- `is_false()` (*angr.state_plugins.solver.SimSolver* method), 259
- `is_fp_arg()` (*angr.calling_conventions.SimCC* method), 490
- `is_fp_arg()` (*angr.SimCC* method), 185
- `is_fp_value()` (*angr.calling_conventions.SimCC* static method), 491
- `is_fp_value()` (*angr.SimCC* static method), 186
- `is_free()` (*angr.PTChunk* method), 209
- `is_free()` (*angr.state_plugins.heap.heap_freelist.Chunk* method), 300
- `is_free()` (*angr.state_plugins.heap.heap_ptmalloc.PTChunk* method), 303
- `IS_FUNCTION` (*angr.sim_procedure.SimProcedure* attribute), 472
- `IS_FUNCTION` (*angr.SimProcedure* attribute), 159
- `is_function()` (*angr.analyses.vtable.VtableFinder* method), 854
- `is_function_argument` (*angr.sim_variable.SimVariable* property), 505
- `is_global_variable_address()` (*angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryStateBase* method), 826
- `is_heap_address()` (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 769
- `is_heap_address()` (*angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions* static method), 811
- `is_heap_address()` (*angr.analyses.reaching_definitions.ReachingDefinitions* static method), 782
- `is_heap_address()` (*angr.knowledge_plugins.key_definitions.key_definitions.StaticKeyDefinitions* static method), 605
- `is_heap_address()` (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 584
- `is_hex()` (in module *angr.analyses.reassembler*), 860
- `is_hook` (*angr.codenode.BlockNode* attribute), 883
- `is_hook` (*angr.codenode.CodeNode* attribute), 883
- `is_hook` (*angr.codenode.HookNode* attribute), 883
- `is_hook` (*angr.codenode.SyscallNode* attribute), 884
- `is_hooked()` (*angr.Project* method), 165
- `is_hooked()` (*angr.project.Project* method), 214
- `is_immediate` (*angr.analyses.reassembler.Operand* property), 166
- `is_in_readonly_section()` (in module *angr.utils.loader*), 899
- `is_in_readonly_segment()` (in module *angr.utils.loader*), 899
- `is_java` (*angr.sim_procedure.SimProcedure* property), 474
- `is_java` (*angr.SimProcedure* property), 160
- `is_jumptable` (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.Jumptable* attribute), 668
- `is_machine_word_size_type()` (in module *angr.analyses.decompiler.structured_codegen.c*), 727
- `is_not_in_cfg()` (*angr.analyses.veriteesting.Veriteesting* method), 848
- `is_on_stack` (*angr.analyses.reaching_definitions.MemoryLocation* property), 773
- `is_on_stack` (*angr.knowledge_plugins.key_definitions.atoms.MemoryLocation* property), 592
- `is_on_stack` (*angr.storage.memory_mixins.regioned_memory.region_data_region.MemoryRegion* attribute), 369
- `is_overbound()` (*angr.analyses.veriteesting.Veriteesting* method), 849
- `is_pc()` (in module *angr.utils.loader*), 899
- `is_phi_variable()` (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 569
- `is_plt` (*angr.analyses.reassembler.Procedure* property), 863
- `is_plt` (*angr.knowledge_plugins.functions.function.Function* attribute), 556
- `is_plt` (*angr.knowledge_plugins.functions.soot_function.SootFunction* attribute), 563
- `is_prev_free()` (*angr.PTChunk* method), 209
- `is_prev_free()` (*angr.state_plugins.heap.heap_ptmalloc.PTChunk* method), 303
- `is_prototype_guessed` (*angr.knowledge_plugins.functions.function.Function* attribute), 556
- `is_prototype_guessed` (*angr.knowledge_plugins.functions.soot_function.SootFunction* attribute), 564
- `is_pyinstaller()` (in module *angr.utils.env*), 895
- `is_simple_jump_node_definition` (in module *angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifiers*), 895
- `is_simprocedure` (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* property), 548
- `is_simprocedure` (*angr.knowledge_plugins.cfg.CFGNode* property), 529

`is_simprocedure(angr.knowledge_plugins.functions.function_type, attribute), 556`
`is_simprocedure(angr.knowledge_plugins.functions.soot_function_type, attribute), 564`
`is_special(angr.engines.pcode.behavior.OpBehaviorInt2Comp, attribute), 453`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntAdd, attribute), 450`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntAnd, attribute), 454`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntCarry, attribute), 451`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntDiv, attribute), 456`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntLeft, attribute), 455`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntLess, attribute), 449`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntLessEqual, attribute), 449`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntMult, attribute), 456`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntNegate, attribute), 453`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntOr, attribute), 454`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntRem, attribute), 457`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntRight, attribute), 455`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSborrow, attribute), 452`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntScarry, attribute), 452`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSdiv, attribute), 457`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSext, attribute), 450`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSless, attribute), 448`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSlessEqual, attribute), 448`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSrem, attribute), 458`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSright, attribute), 456`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntSub, attribute), 451`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntXor, attribute), 453`
`is_special(angr.engines.pcode.behavior.OpBehaviorIntZext, attribute), 450`
`is_special(angr.engines.pcode.behavior.OpBehaviorNotEqual, attribute), 447`
`is_special(angr.engines.pcode.behavior.OpBehaviorPiece, attribute), 463`
`is_special(angr.engines.pcode.behavior.OpBehaviorPopcount, attribute), 464`

`is_special` (`angr.engines.pcode.behavior.OpBehaviorSubpiece` attribute), 464
`is_stack` (`angr.storage.memory_mixins.regioned_memory.RegionMetaMixin` property), 371
`is_stack_address()` (`angr.analyses.reaching_definitions.LiveDefinitions` method), 632
`is_stack_address()` (`angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState` method), 812
`is_stack_address()` (`angr.analyses.reaching_definitions.ReachingDefinitionsState` method), 782
`is_stack_address()` (`angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryStateBase` static method), 826
`is_stack_address()` (`angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions` static method), 599
`is_stack_address()` (`angr.knowledge_plugins.key_definitions.LiveDefinitions` static method), 578
`is_statement_terminating()` (in module `angr.analyses.decompiler.utils`), 747
`is_stored()` (`angr.vaults.Vault` method), 621
`is_stored()` (`angr.vaults.VaultDict` method), 622
`is_subclass()` (`angr.analyses.soot_class_hierarchy.SootClassHierarchy` method), 640
`is_subclass_including()` (`angr.analyses.soot_class_hierarchy.SootClassHierarchy` method), 640
`is_symbol_hooked()` (`angr.Project` method), 166
`is_symbol_hooked()` (`angr.project.Project` method), 215
`is_symbolic` (`angr.state_plugins.sim_action.SimAction` property), 467
`is_symbolic` (`angr.state_plugins.sim_action.SimActionConstraint` attribute), 468
`is_symbolic` (`angr.state_plugins.sim_action.SimActionData` property), 468
`is_symbolic` (`angr.state_plugins.sim_action.SimActionExit` property), 467
`is_symbolic` (`angr.state_plugins.sim_action.SimActionOperation` attribute), 468
`is_syscall` (`angr.analyses.cfg.cfg_emulated.CFGJob` property), 644
`is_syscall` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` attribute), 548
`is_syscall` (`angr.knowledge_plugins.cfg.CFGNode` attribute), 528
`is_syscall` (`angr.knowledge_plugins.functions.function.Function` attribute), 556
`is_syscall` (`angr.knowledge_plugins.functions.soot_function.SootFunction` attribute), 563
`is_syscall_addr()` (`angr.SimOS` method), 169
`is_syscall_addr()` (`angr.simos.simos.SimOS` method), 885
`is_syscall_addr()` (`angr.simos.userland.SimUserland` method), 888
`is_taint_impacting_stack_pointers()`
`is_thumb_addr()` (`angr.analyses.cfg.cfg_base.CFGBase` method), 633
`is_top()` (`angr.analyses.reaching_definitions.LiveDefinitions` method), 763
`is_top()` (`angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState` method), 763
`is_top()` (`angr.analyses.reaching_definitions.ReachingDefinitionsState` method), 763
`is_top()` (`angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryStateBase` static method), 825
`is_top()` (`angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions` static method), 599
`is_top()` (`angr.knowledge_plugins.key_definitions.LiveDefinitions` static method), 578
`is_tracking_memory` (`angr.analyses.stack_pointer_tracker.FrozenStackPointerTracker` attribute), 822
`is_tracking_memory` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` attribute), 822
`is_true()` (`angr.state_plugins.solver.SimSolver` method), 258
`is_unary` (`angr.engines.pcode.behavior.OpBehavior` attribute), 445
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorBoolAnd` attribute), 459
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorBoolNegate` attribute), 458
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorBoolOr` attribute), 459
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorBoolXor` attribute), 459
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorCopy` attribute), 447
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorEqual` attribute), 447
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatAbs` attribute), 462
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatAdd` attribute), 461
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatCeil` attribute), 463
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatDiv` attribute), 460
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatFloat2Float` attribute), 462
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatFloor` attribute), 463
`is_unary` (`angr.engines.pcode.behavior.OpBehaviorFloatInt2Float` attribute), 463

attribute), 462
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatLessEqual attribute), 460
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatLessEqual attribute), 460
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatMore attribute), 461
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatNot attribute), 460
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatNotEqual attribute), 461
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatNotEqual attribute), 460
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatRising attribute), 463
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatSign attribute), 462
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatSign attribute), 461
 is_unary (angr.engines.pcode.behavior.OpBehaviorFloatTailing attribute), 463
 is_unary (angr.engines.pcode.behavior.OpBehaviorInt2Comps attribute), 453
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntAddis_using_outdated_def() attribute), 450
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntAnd attribute), 454
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntCarry attribute), 451
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntDivis_value_set (angr.state_plugins.unicorn_engine.MemoryValue attribute), 456
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntLeftis_value_symbolic (angr.state_plugins.unicorn_engine.MemoryValue attribute), 455
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntLessis_variable_used_at() attribute), 449
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntLessEqual attribute), 449
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntMult attribute), 456
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntNegate attribute), 453
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntOr attribute), 454
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntRem attribute), 457
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntRight attribute), 455
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSborrow attribute), 452
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntScarry attribute), 452
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSdivitems() attribute), 457
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSextitems() attribute), 450
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSless attribute), 448
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSlessEqual attribute), 448
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSrem attribute), 458
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSright attribute), 456
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntSub attribute), 451
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntXor attribute), 453
 is_unary (angr.engines.pcode.behavior.OpBehaviorIntZext attribute), 450
 is_unary (angr.engines.pcode.behavior.OpBehaviorNotEqual attribute), 447
 is_unary (angr.engines.pcode.behavior.OpBehaviorPiece attribute), 463
 is_unary (angr.engines.pcode.behavior.OpBehaviorPopcount attribute), 464
 is_unary (angr.engines.pcode.behavior.OpBehaviorSubpiece attribute), 464
 is_using_outdated_def() (angr.analyses.propagator.engine_ail.SimEnginePropagatorAIL method), 758
 is_va_start_amd64() (angr.analyses.calling_convention.CallingConventionAnalysis method), 638
 is_value_set (angr.state_plugins.unicorn_engine.MemoryValue attribute), 284
 is_value_symbolic (angr.state_plugins.unicorn_engine.MemoryValue attribute), 284
 is_variable_used_at() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 567
 is_visible_class() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640
 is_visible_method() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 640
 IsArray (class in angr.analyses.typehoon.typevars), 842
 ISPOMixin (class in angr.storage.memory_mixins.paged_memory.pages.isp 361
 ite_exprs (angr.analyses.decompiler.decompilation_cache.DecompilationCache attribute), 700
 ite_exprs (angr.angrdb.models.DbStructuredCode attribute), 680
 ITEExprConverter (class in angr.analyses.decompiler.optimization_passes.ite_expr_converter 709
 items() (angr.analyses.ddg.LiveDefinitions method), 750
 items() (angr.analyses.decompiler.structured_codegen.base.InstructionModel

- method*), 726
- items()* (*angr.analyses.decompiler.structured_codegen.base.PositionMapping* *method*), 726
- items()* (*angr.knowledge_plugins.labels.Labels* *method*), 552
- items()* (*angr.knowledge_plugins.patches.PatchManager* *method*), 525
- items()* (*angr.state_plugins.globals.SimStateGlobals* *method*), 279
- items()* (*angr.storage.memory_mixins.paged_memory.pages.multi_values_values* *method*), 351
- iter_own()* (*angr.knowledge_plugins.types.TypesStore* *method*), 552
- iterator* (*angr.analyses.decompiler.structured_codegen.c.CFGModel* *attribute*), 731
- iterator* (*angr.analyses.decompiler.structuring.structurer_jumpkind* *attribute*), 689
- Iterator* (*angr.analyses.loop_analysis.VariableTypes* *attribute*), 846
- itervariables()* (*angr.analyses.ddg.LiveDefinitions* *method*), 750
- J**
- javvm_memory* (*angr.sim_state.SimState* *property*), 226
- javvm_memory* (*angr.SimState* *property*), 182
- javvm_registers* (*angr.sim_state.SimState* *property*), 226
- javvm_registers* (*angr.SimState* *property*), 182
- JavaVmMemory* (*class in angr.storage.memory_mixins*), 339
- JavaVmMemoryMixin* (*class in angr.storage.memory_mixins.javvm_memory.javvm_memory_mixin*), 376
- jni_references* (*angr.sim_state.SimState* *attribute*), 225
- jni_references* (*angr.SimState* *attribute*), 181
- job* (*angr.analyses.forward_analysis.job_info.JobInfo* *property*), 626
- job_type* (*angr.analyses.cfg.cfg_fast.CFGJob* *attribute*), 656
- JobInfo* (*class in angr.analyses.forward_analysis.job_info*), 626
- jobs* (*angr.analyses.forward_analysis.forward_analysis.ForwardAnalysis* *property*), 626
- join()* (*angr.analyses.typehoon.simple_solver.SimpleSolver* *method*), 836
- jump()* (*angr.sim_procedure.SimProcedure* *method*), 473
- jump()* (*angr.SimProcedure* *method*), 160
- jump_guards* (*angr.state_plugins.history.SimStateHistory* *property*), 269
- jump_sources* (*angr.state_plugins.history.SimStateHistory* *property*), 269
- jump_tables* (*angr.analyses.cfg.cfg_fast.CFGFast* *property*), 659
- jump_tables* (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* *attribute*), 539
- jump_tables* (*angr.knowledge_plugins.cfg.CFGModel* *attribute*), 532
- jump_targets* (*angr.state_plugins.history.SimStateHistory* *property*), 269
- jumpkind* (*angr.analyses.cfg.cfg_fast.CFGJob* *attribute*), 656
- jumpkind* (*angr.engines.pcode.lifter.ExitStatement* *attribute*), 438
- jumpkind* (*angr.engines.pcode.lifter.IRSB* *attribute*), 438
- jumpkind* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumpkind* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- jumpkind* (*angr.state_plugins.history.SimStateHistory* *property*), 269
- jumpout_sites* (*angr.knowledge_plugins.functions.function.Function* *property*), 559
- jumptable* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumptable* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- jumptable_addr* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumptable_addr* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- Jumtable_AddressComputed* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJumpType* *attribute*), 550
- Jumtable_AddressComputed* (*angr.knowledge_plugins.cfg.IndirectJumpType* *attribute*), 532
- Jumtable_AddressLoadedFromMemory* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJumpType* *attribute*), 550
- Jumtable_AddressLoadedFromMemory* (*angr.knowledge_plugins.cfg.IndirectJumpType* *attribute*), 532
- jumptable_entries* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumptable_entries* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- jumptable_entry_size* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumptable_entry_size* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- jumptable_size* (*angr.knowledge_plugins.cfg.indirect_jump.IndirectJump* *attribute*), 551
- jumptable_size* (*angr.knowledge_plugins.cfg.IndirectJump* *attribute*), 532
- JumpTableEntryConditionRewriter* (*class in*

[angr.analyses.decompiler.jumptable_entry_conditional](#) (class in [angr.analyses.decompiler.block_simplifier.BlockSimplifier](#) attribute), 695
[703](#)
[JumpTableProcessor](#) (class in [angr.analyses.decompiler.callsite_maker.CallSiteMaker](#) attribute), 695
[angr.analyses.cfg.indirect_jump_resolvers.jumptable](#)), [668](#)
[JumpTableProcessorState](#) (class in [angr.analyses.decompiler.decompiler.Decompiler](#) attribute), 701
[angr.analyses.cfg.indirect_jump_resolvers.jumptable](#)), [667](#)
[JumpTableResolver](#) (class in [angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization](#) property), 706
[angr.analyses.cfg.indirect_jump_resolvers.jumptable](#)), [670](#)
[JumpTargetBaseAddr](#) (class in [angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization](#) attribute), 715
[angr.analyses.cfg.indirect_jump_resolvers.jumptable](#)), [667](#)
[JumpTargetCollector](#) (class in [angr.analyses.decompiler.region_identifier.RegionIdentifier](#) attribute), 715
[angr.analyses.decompiler.jump_target_collector](#)), [703](#)
K
[K](#) ([angr.knowledge_base.knowledge_base.KnowledgeBase](#) attribute), 523
[K](#) ([angr.KnowledgeBase](#) attribute), 211
[kb](#) ([angr.analyses.analysis.Analysis](#) attribute), 625
[kb](#) ([angr.analyses.backward_slice.BackwardSlice](#) attribute), 633
[kb](#) ([angr.analyses.binary_optimizer.BinaryOptimizer](#) attribute), 870
[kb](#) ([angr.analyses.bindiff.Bindiff](#) attribute), 636
[kb](#) ([angr.analyses.boyscout.BoyScout](#) attribute), 636
[kb](#) ([angr.analyses.callee_cleanup_finder.CalleeCleanupFinder](#) attribute), 870
[kb](#) ([angr.analyses.calling_convention.CallingConventionAnalysis](#) attribute), 638
[kb](#) ([angr.analyses.cdg.CDG](#) attribute), 675
[kb](#) ([angr.analyses.cfg.cfb.CFBlanket](#) attribute), 642
[kb](#) ([angr.analyses.cfg.cfg_fast.CFGFast](#) attribute), 660
[kb](#) ([angr.analyses.cfg.cfg_fast_soot.CFGFastSoot](#) attribute), 675
[kb](#) ([angr.analyses.cfg.indirect_jump_resolvers.jumptable.CompleteBlockAnalysis](#) attribute), 667
[kb](#) ([angr.analyses.class_identifier.ClassIdentifier](#) attribute), 856
[kb](#) ([angr.analyses.code_tagging.CodeTagging](#) attribute), 676
[kb](#) ([angr.analyses.complete_calling_conventions.CompleteCallingConventionAnalysis](#) attribute), 639
[kb](#) ([angr.analyses.congruency_check.CongruencyCheck](#) attribute), 868
[kb](#) ([angr.analyses.data_dep.data_dependency_analysis.DataDependencyAnalysis](#) attribute), 876
[kb](#) ([angr.analyses.ddg.DDG](#) attribute), 754
[kb](#) ([angr.analyses.decompiler.ail_simplifier.AILSimplifier](#) attribute), 694
[kb](#) ([angr.analyses.decompiler.block_simplifier.BlockSimplifier](#) attribute), 695
[kb](#) ([angr.analyses.decompiler.callsite_maker.CallSiteMaker](#) attribute), 695
[kb](#) ([angr.analyses.decompiler.clinic.Clinic](#) attribute), 698
[kb](#) ([angr.analyses.decompiler.decompiler.Decompiler](#) attribute), 701
[kb](#) ([angr.analyses.decompiler.optimization_passes.optimization_pass.BaseOptimizationPass](#) attribute), 716
[kb](#) ([angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization](#) attribute), 715
[kb](#) ([angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization](#) attribute), 715
[kb](#) ([angr.analyses.decompiler.region_identifier.RegionIdentifier](#) attribute), 717
[kb](#) ([angr.analyses.decompiler.region_simplifiers.region_simplifier.RegionSimplifier](#) attribute), 721
[kb](#) ([angr.analyses.decompiler.structured_codegen.c.CStructuredCodeGenerator](#) attribute), 742
[kb](#) ([angr.analyses.decompiler.structured_codegen.dwarf_import.ImportSource](#) attribute), 744
[kb](#) ([angr.analyses.decompiler.structuring.phoenix.PhoenixStructurer](#) attribute), 693
[kb](#) ([angr.analyses.decompiler.structuring.recursive_structurer.RecursiveStructurer](#) attribute), 686
[kb](#) ([angr.analyses.disassembly.Disassembly](#) attribute), 859
[kb](#) ([angr.analyses.dominance_frontier.DominanceFrontier](#) attribute), 870
[kb](#) ([angr.analyses.find_objects_static.StaticObjectFinder](#) attribute), 855
[kb](#) ([angr.analyses.flirt.FlirtAnalysis](#) attribute), 754
[kb](#) ([angr.analyses.identifier.identify.Identifier](#) attribute), 846
[kb](#) ([angr.analyses.init_finder.InitializationFinder](#) attribute), 871
[kb](#) ([angr.analyses.loop_analysis.LoopAnalysis](#) attribute), 847
[kb](#) ([angr.analyses.loopfinder.LoopFinder](#) attribute), 846
[kb](#) ([angr.analyses.propagator.propagator.PropagatorAnalysis](#) attribute), 761
[kb](#) ([angr.analyses.proximity_graph.ProximityGraphAnalysis](#) attribute), 875
[kb](#) ([angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions](#) attribute), 798
[kb](#) ([angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis](#) attribute), 778
[kb](#) ([angr.analyses.reassembly.Reassembler](#) attribute), 867
[kb](#) ([angr.analyses.soot_class_hierarchy.SootClassHierarchy](#) attribute), 641
[kb](#) ([angr.analyses.stack_pointer_tracker.StackPointerTracker](#) attribute), 703

attribute), 823
 kb (angr.analyses.static_hooker.StaticHooker attribute), 869
 kb (angr.analyses.typehoon.typehoon.Typehoon attribute), 843
 kb (angr.analyses.variable_recovery.variable_recovery.VariableRecovery attribute), 831
 kb (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase attribute), 825
 kb (angr.analyses.variable_recovery.variable_recovery_fast.VariableRecoveryFast attribute), 829
 kb (angr.analyses.veritesting.Veritesting attribute), 849
 kb (angr.analyses.vfg.VFG attribute), 853
 kb (angr.analyses.vsa_ddg.VSA_DDG attribute), 854
 kb (angr.analyses.vtable.VtableFinder attribute), 855
 kb (angr.analyses.xrefs.XRefsAnalysis attribute), 872
 kb (angr.Analysis attribute), 178
 kb (angr.angrdb.models.DbCFGModel attribute), 679
 kb (angr.angrdb.models.DbComment attribute), 681
 kb (angr.angrdb.models.DbFunction attribute), 679
 kb (angr.angrdb.models.DbLabel attribute), 681
 kb (angr.angrdb.models.DbStructuredCode attribute), 680
 kb (angr.angrdb.models.DbVariableCollection attribute), 680
 kb (angr.angrdb.models.DbXRefs attribute), 680
 kb_id (angr.angrdb.models.DbCFGModel attribute), 679
 kb_id (angr.angrdb.models.DbComment attribute), 681
 kb_id (angr.angrdb.models.DbFunction attribute), 679
 kb_id (angr.angrdb.models.DbLabel attribute), 681
 kb_id (angr.angrdb.models.DbStructuredCode attribute), 680
 kb_id (angr.angrdb.models.DbVariableCollection attribute), 680
 kb_id (angr.angrdb.models.DbXRefs attribute), 680
 keep_path() (angr.annocfg.AnnotatedCFG method), 882
 key (angr.angrdb.models.DbInformation attribute), 678
 KeyDefinitionManager (class in angr.knowledge_plugins.key_definitions), 576
 KeyDefinitionManager (class in angr.knowledge_plugins.key_definitions.key_definitions), 596
 KeyedRegion (class in angr.keyed_region), 618
 keys() (angr.knowledge_plugins.patches.PatchManager method), 525
 keys() (angr.state_plugins.globals.SimStateGlobals method), 279
 keys() (angr.storage.memory_mixins.paged_memory.pages.multi_values_analysis), 623
 keys() (angr.storage.memory_mixins.paged_memory.pages.multi_values_analysis method), 351
 keys() (angr.vaults.Vault method), 621
 keys() (angr.vaults.VaultDict method), 622
 keys() (angr.vaults.VaultDir method), 622
 keys() (angr.vaults.VaultDirShelf method), 622
 KeyValueMemory (class in angr.storage.memory_mixins), 339
 KeyValueMemoryMixin (class in angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory), 339
 kill_and_add_definition() (angr.analyses.reaching_definitions.LiveDefinitions method), 765
 kill_and_add_definition() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 814
 kill_and_add_definition() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 784
 kill_and_add_definition() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 601
 kill_and_add_definition() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 580
 kill_def() (angr.analyses.ddg.LiveDefinitions method), 750
 kill_def() (angr.analyses.reaching_definitions.ReachingDefinitionsMode method), 778
 kill_def() (angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsMode method), 606
 kill_def() (angr.knowledge_plugins.key_definitions.ReachingDefinitionsMode method), 574
 kill_definitions() (angr.analyses.reaching_definitions.LiveDefinitions method), 765
 kill_definitions() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 814
 kill_definitions() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 784
 kill_definitions() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 601
 kill_definitions() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 580
 kind (angr.knowledge_plugins.key_definitions.definition.DefinitionMatchPr attribute), 593
 KnowledgeBase (class in angr), 211
 KnowledgeBase (class in angr.knowledge_base.knowledge_base), 523
 KnowledgeBasePlugin (class in angr.knowledge_plugins.plugin), 525
 KnowledgeBaseSerializer (class in angr.angrdb.serializers.kb), 683
 KnownAnalysesPlugin (class in angr.knowledge_plugins.known_analyses.known_analyses), 623
 kwargs (angr.utils.mp.Closure attribute), 902
L
 label (angr.storage.memory_object.SimLabeledMemoryObject

attribute), 335
 Label (class in *angr.analyses.disassembly*), 856
 Label (class in *angr.analyses.reassembler*), 860
 label_got() (*angr.analyses.reassembler.SymbolManager* method), 861
 LabeledMemory (class in *angr.storage.memory_mixins*), 339
 LabeledPagesMixin (class in *angr.storage.memory_mixins.paged_memory.paged_memory_mixins*), 355
 LabelMergerMixin (class in *angr.storage.memory_mixins.label_merger_mixin*), 347
 labels (*angr.analyses.typehoon.typevars.DerivedTypeVariable* attribute), 840
 labels (*angr.angrdb.models.DbKnowledgeBase* attribute), 678
 Labels (class in *angr.knowledge_plugins.labels*), 552
 LabelsSerializer (class in *angr.angrdb.serializers.labels*), 683
 LambdaAttrIter (class in *angr.state_plugins.history*), 270
 LambdaIterIter (class in *angr.state_plugins.history*), 270
 LARGE_SWITCH (*angr.analyses.code_tagging.CodeTags* attribute), 676
 last_addr (*angr.analyses.cfg.cfg_fast.CFGJob* attribute), 656
 last_addr (*angr.storage.memory_object.SimMemoryObject* property), 334
 last_nonlabel_statement() (in module *angr.analyses.decompiler.utils*), 746
 lazy_import() (in module *angr.utils.lazy_import*), 899
 LEFT (*angr.analyses.typehoon.simple_solver.ConstraintGraphTag* attribute), 834
 length (*angr.analyses.decompiler.structured_codegen.base.PositionMappingElement* attribute), 726
 length (*angr.state_plugins.unicorn_engine.MEM_PATCH* attribute), 284
 length (*angr.storage.memory_object.SimMemoryObject* attribute), 334
 length_spec (*angr.procedures.stubs.format_parser.FormatSpec* attribute), 474
 LengthLimiter (class in *angr.exploration_techniques*), 398
 LengthLimiter (class in *angr.exploration_techniques.lengthlimiter*), 410
 lhs (*angr.analyses.decompiler.structured_codegen.c.CAssignment* attribute), 732
 lhs (*angr.analyses.decompiler.structured_codegen.c.CBinaryOp* attribute), 737
 lift() (*angr.analyses.typehoon.lifter.TypeLifter* method), 832
 lift() (*angr.engines.pcode.lifter.Lifter* method), 440
 lift() (*angr.engines.pcode.lifter.PcodeBasicBlockLifter* method), 442
 lift() (*angr.engines.pcode.lifter.PcodeLifter* method), 442
 lift() (in module *angr.engines.pcode.lifter*), 440
 lift_pcode() (*angr.engines.pcode.lifter.PcodeLifterEngineMixin* method), 444
 lift_root() (class in *angr.engines.soot.engine.SootMixin* method), 432
 lift_vex() (*angr.engines.pcode.lifter.PcodeLifterEngineMixin* method), 443
 Lifter (class in *angr.engines.pcode.lifter*), 439
 lineage (*angr.state_plugins.history.SimStateHistory* property), 269
 lineage() (*angr.state_hierarchy.StateHierarchy* method), 390
 lineage() (*angr.StateHierarchy* method), 180
 linux_syscall_update_error_reg() (*angr.calling_conventions.SimCCSyscall* method), 495
 list_content (*angr.utils.dynamic_dictlist.DynamicDictList* attribute), 895
 list_default_plugins() (*angr.misc.plugins.PluginPreset* method), 223
 ListPage (class in *angr.storage.memory_mixins.paged_memory.pages.list_page*), 362
 ListPagesMixin (class in *angr.storage.memory_mixins.paged_memory.paged_memory_mixins*), 356
 ListPagesWithLabelsMixin (class in *angr.storage.memory_mixins.paged_memory.paged_memory_mixins*), 356
 live_definitions (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitions* attribute), 781
 LiveDefinitions (class in *angr.analyses.ddg*), 749
 LiveDefinitions (class in *angr.analyses.reaching_definitions*), 761
 LiveDefinitions (class in *angr.knowledge_plugins.key_definitions*), 577
 LiveDefinitions (class in *angr.knowledge_plugins.key_definitions.live_definitions*), 597
 LiveVariables (class in *angr.knowledge_plugins.variables.variable_manager*), 565
 load (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTransformer* attribute), 666
 Load (class in *angr.analyses.typehoon.typevars*), 841
 load() (*angr.analyses.stack_pointer_tracker.StackPointerTrackerState* method), 832

- method), 822
- load() (angr.angrdb.db.AngrDB method), 677
- load() (angr.angrdb.serializers.cfg_model.CFGModelSerializer static method), 682
- load() (angr.angrdb.serializers.comments.CommentsSerializer static method), 682
- load() (angr.angrdb.serializers.funcs.FunctionManagerSerializer static method), 683
- load() (angr.angrdb.serializers.kb.KnowledgeBaseSerializer static method), 683
- load() (angr.angrdb.serializers.labels.LabelsSerializer static method), 683
- load() (angr.angrdb.serializers.loader.LoaderSerializer static method), 684
- load() (angr.angrdb.serializers.structured_code.StructuredCodeSerializer static method), 685
- load() (angr.angrdb.serializers.variables.VariableManagerSerializer static method), 685
- load() (angr.angrdb.serializers.xrefs.XRefsSerializer static method), 684
- load() (angr.state_plugins.light_registers.SimLightRegisters method), 267
- load() (angr.storage.memory_mixins.actions_mixin.ActionMixin method), 342
- load() (angr.storage.memory_mixins.actions_mixin.ActionMixin method), 342
- load() (angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin method), 346
- load() (angr.storage.memory_mixins.bvv_conversion_mixin.BVVConversionMixin method), 341
- load() (angr.storage.memory_mixins.clouseau_mixin.InspectClouseauMixin method), 346
- load() (angr.storage.memory_mixins.conditional_store_mixin.ConditionalStoreMixin method), 347
- load() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.JavavmMemoryMixin method), 376
- load() (angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixin.KeyValueMemoryMixin method), 376
- load() (angr.storage.memory_mixins.MemoryMixin method), 336
- load() (angr.storage.memory_mixins.name_resolution_mixin.NameResolutionMixin method), 340
- load() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin method), 353
- load() (angr.storage.memory_mixins.paged_memory.pages.list_page_list_page_mixin.ListPageMixin method), 362
- load() (angr.storage.memory_mixins.paged_memory.pages.list_page_list_page_mixin method), 349
- load() (angr.storage.memory_mixins.paged_memory.pages.list_page_list_page_mixin method), 364
- load() (angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemoryMixin method), 372
- load() (angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin method), 366
- load() (angr.storage.memory_mixins.simple_interface_mixin.SimpleInterfaceMixin method), 342
- load() (angr.storage.memory_mixins.size_resolution_mixin.SizeConcretizationMixin method), 344
- load() (angr.storage.memory_mixins.size_resolution_mixin.SizeNormalizationMixin method), 343
- load() (angr.storage.memory_mixins.slotted_memory.SlottedMemoryMixin method), 375
- load() (angr.storage.memory_mixins.underconstrained_mixin.UnderconstrainedMixin method), 342
- load() (angr.storage.memory_mixins.unwrapper_mixin.UnwrapperMixin method), 347
- load() (angr.vaults.Vault method), 621
- load() (angr.vaults.VaultDirShelf method), 622
- load_module_definitions() (in module angr.procedures.definitions), 484
- load_array_element() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin method), 377
- load_array_elements() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin method), 377
- load_external_definitions() (in module angr.procedures.definitions), 484
- load_from_dwarf() (angr.knowledge_plugins.debug_variables.DebugVariables method), 574
- load_from_dwarf() (angr.knowledge_plugins.variables.variable_manager method), 571
- load_intermediate() (in module angr.angrdb.serializers.variables.VariableManagerSerializer static method), 685
- load_shellcode() (in module angr), 167
- load_shellcode() (in module angr.project), 212
- load_signatures() (in module angr.flirt), 892
- load_type_collections() (in module angr.procedures.definitions), 484
- load_win32_type_collections() (in module angr.procedures.definitions), 484
- load_win32api_definitions() (in module angr.procedures.definitions), 484
- load_with_labels() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin method), 683
- LoadHook (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 651
- loads() (angr.vaults.Vault method), 622
- Loc (in module angr.typevars.FuncIn attribute), 841
- Loc (in module angr.typevars.FuncOut attribute), 841
- LocExpr (in module angr.RegionedMemoryMixin method), 505
- LocExpr (in module angr.RegionedMemoryMixin method), 507

`loc_repr()` (*angr.sim_variable.SimRegisterVariable* method), 276
`loc_repr()` (*angr.sim_variable.SimStackVariable* method), 506
`loc_repr()` (*angr.sim_variable.SimTemporaryVariable* method), 505
`loc_repr()` (*angr.sim_variable.SimVariable* method), 505
`local_runtime_values` (*angr.knowledge_plugins.functions.function.Function* property), 558
`local_types` (*angr.analyses.decompiler.decompilation_cache.DecompilationCache* property), 700
`local_vars` (*angr.sim_procedure.SimProcedure* attribute), 472
`local_vars` (*angr.SimProcedure* attribute), 159
`LOCALE_ARRAY` (*angr.state_plugins.libc.SimStateLibc* attribute), 236
`LocalLoopSeer` (class in *angr.exploration_techniques*), 406
`LocalLoopSeer` (class in *angr.exploration_techniques.local_loop_seer*), 422
`LocalVariableTag` (class in *angr.knowledge_plugins.key_definitions.tag*), 609
`location` (*angr.knowledge_plugins.variables.variable_accessors.VariableAccessors* attribute), 565
`LocationBase` (class in *angr.analyses.decompiler.region_simplifiers.expression_simplifiers*), 718
`long_reason` (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* attribute), 547
`longest_prefix()` (*angr.analyses.typehoon.typevars.DerivedTypeVariable* method), 840
`looks_like_sql()` (in module *angr.utils*), 893
`lookup()` (*angr.analyses.typehoon.simple_solver.Sketch* method), 833
`lookup()` (*angr.knowledge_plugins.labels.Labels* method), 553
`lookup()` (*angr.SimMount* method), 203
`lookup()` (*angr.state_plugins.filesystem.SimConcreteFilesystem* method), 252
`lookup()` (*angr.state_plugins.filesystem.SimMount* method), 251
`lookup()` (*angr.state_plugins.jni_references.SimStateJNIReferences* method), 296
`lookup()` (*angr.state_plugins.posix.PosixDevFS* method), 240
`lookup()` (*angr.state_plugins.posix.PosixProcFS* method), 242
`lookup_defs()` (*angr.analyses.ddg.LiveDefinitions* method), 750
`lookup_original()` (*angr.state_plugins.trace_additions.ChallResponse* method), 866
`Loop` (class in *angr.analyses.loopfinder*), 846
`LoopAnalysis` (class in *angr.analyses.loop_analysis*), 847
`LoopAnalysisState` (class in *angr.analyses.loop_analysis*), 847
`LoopFinder` (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 623
`LoopFinder` (class in *angr.analyses.loopfinder*), 846
`looping_times` (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* attribute), 550
`LoopingTimesCoupler` (*angr.knowledge_plugins.cfg.CFGNode* attribute), 530
`LoopNode` (class in *angr.analyses.decompiler.structuring.structurer_nodes*), 689
`LoopSeer` (class in *angr.exploration_techniques*), 393
`LoopSeer` (class in *angr.exploration_techniques.loop_seer*), 421
`LoopSimplifier` (class in *angr.analyses.decompiler.region_simplifiers.loop*), 721
`LoopVisitor` (class in *angr.analyses.forward_analysis.visitors.loop*), 630
`lower_bound` (*angr.analyses.typehoon.simple_solver.SketchNode* attribute), 833
`LoweredSwitchSimplifier` (class in *angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier*), 710
`LoweredSwitchSimplifier` (*angr.engines.light.data.ArithmeticExpression* attribute), 754
`LoweredSwitchSimplifier` (*angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier* attribute), 722

M

`main()` (in module *angr.flirt.build_sig*), 893
`main_executable_region_limbo_contains()` (*angr.analyses.reassembler.Reassembler* method), 865
`main_executable_regions` (*angr.analyses.reassembler.Reassembler* property), 865
`main_executable_regions_contain()` (*angr.analyses.reassembler.Reassembler* method), 865
`main_nonexecutable_region_limbo_contains()` (*angr.analyses.reassembler.Reassembler* method), 866
`main_nonexecutable_regions` (*angr.analyses.reassembler.Reassembler* property), 865
`main_nonexecutable_regions_contain()` (*angr.analyses.reassembler.Reassembler* method), 866

main_object (angr.angrdb.models.DbObject attribute), 612
 678
 make() (angr.sim_type.SimTypePointer method), 513
 make() (angr.sim_type.SimTypeReference method), 513
 make_breakpoint() (angr.state_plugins.inspect.SimInspector method), 234
 make_bv_sizes_equal() (in module
 angr.engines.pcode.behavior), 445
 make_child() (angr.state_plugins.history.SimStateHistory method), 270
 make_concrete_int() (angr.sim_state.SimState method), 227
 make_concrete_int() (angr.SimState method), 184
 make_continuation() (angr.sim_procedure.SimProcedure method), 472
 make_continuation() (angr.SimProcedure method), 159
 make_copy() (angr.analyses.cfg.cfg_base.CFGBase method), 650
 make_function_codeloc() (angr.analyses.reaching_definitions.function_handler.FunctionHandler method), 807
 make_function_codeloc() (angr.analyses.reaching_definitions.FunctionHandler method), 788
 make_functions() (angr.analyses.cfg.cfg_base.CFGBase method), 651
 make_functions() (angr.analyses.cfg.cfg_fast_soot.CFGFastSoot method), 674
 make_ident() (angr.SimFileBase static method), 189
 make_ident() (angr.storage.file.SimFileBase static method), 316
 make_initial_state() (angr.analyses.identifier.identify.Identifier static method), 846
 make_liveness_snapshot() (angr.analyses.reaching_definitions.ReachingDefinitionsModel method), 779
 make_liveness_snapshot() (angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel method), 607
 make_liveness_snapshot() (angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel method), 575
 make_methods() (in module
 angr.state_plugins.sim_action_object), 469
 make_phi_node() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 567
 make_ro_state() (in module
 angr.knowledge_plugins.sync.sync_controller), 612
 make_state() (in module
 angr.knowledge_plugins.sync.sync_controller), 612
 make_symbolic_state() (angr.analyses.identifier.identify.Identifier static method), 846
 MakeTypecastsImplicit (class in
 angr.analyses.decompiler.structured_codegen.c), 743
 malloc() (angr.SimHeapPTMalloc method), 207
 malloc() (angr.state_plugins.heap.heap_libc.SimHeapLibc method), 301
 malloc() (angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc method), 305
 ManualMergepoint (class in
 angr.exploration_techniques), 402
 ManualMergepoint (class in
 angr.exploration_techniques.manual_mergepoint), 410
 map() (angr.storage.memory_mixins.regioned_memory.region_data.RegionData method), 370
 map_callsites() (angr.analyses.identifier.identify.Identifier method), 845
 MapRegion() (angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin method), 346
 map_region() (angr.storage.memory_mixins.MemoryMixin method), 337
 map_region() (angr.storage.memory_mixins.paged_memory.paged_memory.PagedMemory method), 354
 mapping (angr.analyses.cfg.indirect_jump_resolvers.jumptable.ConstantValue attribute), 667
 mark_const() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 817
 mark_const() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 787
 mark_function_alignments() (angr.analyses.cfg.cfg_base.CFGBase method), 651
 mark_guard() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 817
 mark_guard() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 787
 mark_no_defer() (angr.exploration_techniques.manual_mergepoint.ManualMergepoint method), 410
 mark_nofilter() (angr.exploration_techniques.ManualMergepoint method), 402
 mark_nonreturning_calls_endpoints() (angr.knowledge_plugins.functions.function.Function method), 560
 mark_nofilter() (angr.exploration_techniques.manual_mergepoint.ManualMergepoint method), 410
 mark_okfilter() (angr.exploration_techniques.ManualMergepoint method), 402
 match_stmt_classes() (in module
 angr.analyses.decompiler.utils), 747
 matches() (angr.analyses.reaching_definitions.Definition

method), 775

matches() (angr.knowledge_plugins.key_definitions.Definition method), 588

matches() (angr.knowledge_plugins.key_definitions.definition.Definition method), 594

matches() (angr.knowledge_plugins.key_definitions.definition.DefinitionMatchPredicate method), 593

max() (angr.state_plugins.solver.SimSolver method), 258

max_allocation (angr.state_plugins.cgc.SimStateCGC attribute), 272

max_bytes (angr.engines.pcode.lifter.Lifter attribute), 440

max_bytes (angr.engines.pcode.lifter.PcodeLifter attribute), 442

MAX_DATA_REFS (angr.engines.pcode.lifter.IRSB attribute), 437

MAX_EXITS (angr.engines.pcode.lifter.IRSB attribute), 437

max_inst (angr.engines.pcode.lifter.Lifter attribute), 440

max_inst (angr.engines.pcode.lifter.PcodeLifter attribute), 442

max_int() (angr.state_plugins.solver.SimSolver method), 261

MAX_ONE_CALL (angr.analyses.decompiler.structuring.phoenix.MultiStateExprModel attribute), 692

max_size (angr.knowledge_plugins.cfg.memory_data.MemoryData attribute), 762

max_size (angr.knowledge_plugins.cfg.MemoryData attribute), 527

max_size (angr.utils.dynamic_dictlist.DynamicDictList attribute), 895

maximum_syscall_number() (angr.procedures.definitions.SimSyscallLibrary method), 482

meet() (angr.analyses.typehoon.simple_solver.SimpleSolver method), 836

mem (angr.sim_state.SimState attribute), 225

mem (angr.SimState attribute), 181

mem (angr.state_plugins.debug_variables.SimDebugVariable property), 308

MEM (angr.state_plugins.sim_action.SimAction attribute), 467

mem() (angr.analyses.reaching_definitions.Atom static method), 771

mem() (angr.knowledge_plugins.key_definitions.atoms.Atom static method), 589

mem_concrete() (angr.sim_state.SimState method), 227

mem_concrete() (angr.SimState method), 183

mem_map() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288

mem_map_ptr() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288

MEM_PATCH (class in angr.state_plugins.unicorn_engine), 284

mem_reset() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288

mem_unmap() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288

mem_untyped (angr.state_plugins.debug_variables.SimDebugVariable property), 308

member() (angr.state_plugins.debug_variables.SimDebugVariable method), 308

member() (angr.state_plugins.view.SimMemView method), 314

members (angr.sim_type.SimCppClass property), 519

MemDepNode (class in angr.analyses.data_dep.dep_nodes), 878

memo (angr.analyses.typehoon.lifter.TypeLifter attribute), 832

memo() (angr.SimStatePlugin static method), 161

memo() (angr.state_plugins.plugin.SimStatePlugin static method), 232

memoize() (in module angr.analyses.typehoon.typeconsts), 843

Memory (angr.analyses.data_dep.dep_nodes.DepNodeTypes attribute), 877

MEMORY (angr.analyses.reaching_definitions.AtomKind attribute), 588

memory (angr.analyses.reaching_definitions.LiveDefinitions attribute), 598

memory (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813

memory (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783

memory (angr.analyses.stack_pointer_tracker.FrozenStackPointerTrackerState attribute), 821

memory (angr.analyses.stack_pointer_tracker.StackPointerTrackerState attribute), 822

MEMORY (angr.knowledge_plugins.key_definitions.atoms.AtomKind attribute), 588

memory (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

memory (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

MEMORY (angr.knowledge_plugins.variables.variable_manager.VariableType attribute), 565

memory (angr.sim_state.SimState attribute), 225

memory (angr.SimState attribute), 181

memory() (angr.analyses.reaching_definitions.Atom static method), 772

memory() (angr.knowledge_plugins.key_definitions.atoms.Atom static method), 590

memory_args (angr.calling_conventions.SimCC property), 489

memory_args (angr.SimCC property), 185

memory_data (angr.analyses.cfg.cfg_fast.CFGFast property), 659

memory_data (angr.knowledge_plugins.cfg.cfg_model.CFGModel

attribute), 539
 memory_data (angr.knowledge_plugins.cfg.CFGModel attribute), 532
 memory_data (angr.knowledge_plugins.xrefs.xref.XRef attribute), 614
 memory_definitions (angr.analyses.reaching_definitions.LiveDefinitions property), 763
 memory_definitions (angr.knowledge_plugins.key_definitions.LiveDefinitions property), 599
 memory_definitions (angr.knowledge_plugins.key_definitions.LiveDefinitions property), 578
 memory_uses (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762
 memory_uses (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813
 memory_uses (angr.analyses.reaching_definitions.ReachingDefinitionsModel property), 783
 memory_uses (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598
 memory_uses (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 578
 memory_values (angr.state_plugins.unicorn_engine.VEXStmtDetails attribute), 285
 memory_values_count (angr.state_plugins.unicorn_engine.VEXStmtDetails attribute), 285
 MemoryData (class in Angr.knowledge_plugins.cfg), 527
 MemoryData (class in Angr.knowledge_plugins.cfg.memory_data), 545
 MemoryDataSort (class in Angr.knowledge_plugins.cfg), 526
 MemoryDataSort (class in Angr.knowledge_plugins.cfg.memory_data), 545
 MemoryLocation (class in Angr.analyses.reaching_definitions), 773
 MemoryLocation (class in Angr.knowledge_plugins.key_definitions.atoms), 591
 MemoryMappingError, 288
 MemoryMixin (class in Angr.storage.memory_mixins), 336
 MemoryObjectMixin (class in Angr.storage.memory_mixins.paged_memory.pages.cooperativemixin), 362
 MemoryObjectSetMixin (class in Angr.storage.memory_mixins.paged_memory.paged_memory_setmixin), 362
 MemoryOperand (class in Angr.analyses.disassembly), 858
 MemoryRegion (class in Angr.analyses.cfg.cfb), 641
 MemoryRegionMetaMixin (class in Angr.storage.memory_mixins.regioned_memory.regioned_memory_meta_mixin), 371
 MemoryValue (class in Angr.state_plugins.unicorn_engine), 284
 MemoryWatcher (class in Angr.exploration_techniques), 405
 MemoryWatcher (class in Angr.exploration_techniques.memory_watcher), 426
 merge() (Angr.knowledge_plugins.key_definitions.LiveDefinitions method), 712
 merge() (Angr.knowledge_plugins.key_definitions.LiveDefinitions method), 847
 merge() (Angr.analyses.reaching_definitions.LiveDefinitions method), 764
 merge() (Angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 813
 merge() (Angr.analyses.reaching_definitions.ReachingDefinitionsModel method), 779
 merge() (Angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 783
 merge() (Angr.knowledge_plugins.key_definitions.LiveDefinitions method), 822
 merge() (Angr.knowledge_plugins.key_definitions.LiveDefinitions method), 822
 merge() (Angr.analyses.variable_recovery.variable_recovery.VariableRecovery method), 830
 merge() (Angr.analyses.variable_recovery.variable_recovery_fast.VariableRecoveryFast method), 828
 merge() (Angr.concretization_strategies.norepeats.SimConcretizationStrategy method), 379
 merge() (Angr.concretization_strategies.norepeats_range.SimConcretizationStrategyRange method), 381
 merge() (Angr.concretization_strategies.SimConcretizationStrategy method), 336
 merge() (Angr.keyed_region.KeyedRegion method), 618
 merge() (Angr.knowledge_plugins.cfg.cfg_node.CFGNode method), 549
 merge() (Angr.knowledge_plugins.cfg.CFGNode method), 530
 merge() (Angr.knowledge_plugins.key_definitions.environment.Environment method), 595
 merge() (Angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 600
 merge() (Angr.knowledge_plugins.key_definitions.LiveDefinitions method), 580
 merge() (Angr.knowledge_plugins.key_definitions.rd_model.ReachingDefinitionsModel method), 607
 merge() (Angr.knowledge_plugins.key_definitions.ReachingDefinitionsModel method), 575
 merge() (Angr.knowledge_plugins.key_definitions.Uses method), 587
 merge() (Angr.knowledge_plugins.key_definitions.uses.Uses method), 611
 merge() (Angr.sim_manager.SimulationManager method), 388

- `merge()` (*angr.sim_state.SimState* method), 227
- `merge()` (*angr.SimFile* method), 191
- `merge()` (*angr.SimFileDescriptor* method), 199
- `merge()` (*angr.SimFileDescriptorDuplex* method), 202
- `merge()` (*angr.SimFileStream* method), 195
- `merge()` (*angr.SimHeapBrk* method), 205
- `merge()` (*angr.SimHeapPTMalloc* method), 207
- `merge()` (*angr.SimPackets* method), 193
- `merge()` (*angr.SimPacketsStream* method), 197
- `merge()` (*angr.SimState* method), 183
- `merge()` (*angr.SimStatePlugin* method), 162
- `merge()` (*angr.SimulationManager* method), 177
- `merge()` (*angr.state_plugins.callstack.CallStack* method), 264
- `merge()` (*angr.state_plugins.cgc.SimStateCGC* method), 272
- `merge()` (*angr.state_plugins.concrete.Concrete* method), 293
- `merge()` (*angr.state_plugins.filesystem.SimConcreteFilesystem* method), 252
- `merge()` (*angr.state_plugins.filesystem.SimFilesystem* method), 249
- `merge()` (*angr.state_plugins.globals.SimStateGlobals* method), 278
- `merge()` (*angr.state_plugins.heap.heap_brk.SimHeapBrk* method), 299
- `merge()` (*angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc* method), 305
- `merge()` (*angr.state_plugins.history.SimStateHistory* method), 267
- `merge()` (*angr.state_plugins.inspect.SimInspector* method), 235
- `merge()` (*angr.state_plugins.javavm_classloader.SimJavaVmClassLoader* method), 295
- `merge()` (*angr.state_plugins.jni_references.SimStateJNIReferences* method), 296
- `merge()` (*angr.state_plugins.libc.SimStateLibc* method), 239
- `merge()` (*angr.state_plugins.log.SimStateLog* method), 262
- `merge()` (*angr.state_plugins.loop_data.SimStateLoopData* method), 291
- `merge()` (*angr.state_plugins.plugin.SimStatePlugin* method), 232
- `merge()` (*angr.state_plugins.posix.PosixDevFS* method), 240
- `merge()` (*angr.state_plugins.posix.PosixProcFS* method), 242
- `merge()` (*angr.state_plugins.posix.SimSystemPosix* method), 246
- `merge()` (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 282
- `merge()` (*angr.state_plugins.scratch.SimStateScratch* method), 281
- `merge()` (*angr.state_plugins.solver.SimSolver* method), 256
- `merge()` (*angr.state_plugins.trace_additions.ChallRespInfo* method), 275
- `merge()` (*angr.state_plugins.trace_additions.ZenPlugin* method), 276
- `merge()` (*angr.state_plugins.unicorn_engine.Unicorn* method), 289
- `merge()` (*angr.state_plugins.view.SimMemView* method), 313
- `merge()` (*angr.state_plugins.view.SimRegNameView* method), 309
- `merge()` (*angr.storage.file.SimFile* method), 318
- `merge()` (*angr.storage.file.SimFileDescriptor* method), 328
- `merge()` (*angr.storage.file.SimFileDescriptorDuplex* method), 331
- `merge()` (*angr.storage.file.SimFileStream* method), 320
- `merge()` (*angr.storage.file.SimPackets* method), 322
- `merge()` (*angr.storage.file.SimPacketsSlots* method), 333
- `merge()` (*angr.storage.file.SimPacketsStream* method), 324
- `merge()` (*angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin* method), 345
- `merge()` (*angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.JavavmMemoryMixin* method), 378
- `merge()` (*angr.storage.memory_mixins.MemoryMixin* method), 336
- `merge()` (*angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin* method), 354
- `merge()` (*angr.storage.memory_mixins.paged_memory.pages.list_page.ListPage* method), 363
- `merge()` (*angr.storage.memory_mixins.paged_memory.pages.multi_values.MultiValuesPage* method), 351
- `merge()` (*angr.storage.memory_mixins.paged_memory.pages.mv_list_page.MvListPage* method), 349
- `merge()` (*angr.storage.memory_mixins.paged_memory.pages.ultra_page.UltraPage* method), 364
- `merge()` (*angr.storage.memory_mixins.regioned_memory.region_meta_mixin.RegionMetaMixin* method), 372
- `merge()` (*angr.storage.memory_mixins.regioned_memory.regioned_address_mixin.RegionedAddressMixin* method), 373
- `merge()` (*angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemoryMixin* method), 367
- `merge()` (*angr.storage.memory_mixins.slotted_memory.SlottedMemoryMixin* method), 374
- `merge_jobs()` (*angr.analyses.vfg.CallAnalysis* method), 851
- `merge_points()` (*angr.annocfg.AnnotatedCFG* method), 882
- `merge_to_top()` (*angr.keyed_region.KeyedRegion* method), 618
- `merge_transitions()` (in module *angr.analyses.cfg_slice_to_sink.transitions*),

820
merged_jobs (*angr.analyses.forward_analysis.job_info.JobInfo* property), 626
MicrosoftAMD64ArgSession (class in *angr.calling_conventions*), 494
min() (*angr.state_plugins.solver.SimSolver* method), 258
min_int() (*angr.state_plugins.solver.SimSolver* method), 261
minimum_syscall_number() (*angr.procedures.definitions.SimSyscallLibrary* method), 481
MipsElfFastResolver (class in *angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast*), 664
MIPSGPHook (class in *angr.analyses.cfg.indirect_jump_resolvers.jumpable*), 669
MixedPermissionsError, 288
mnemonic (*angr.analyses.disassembly.Instruction* property), 857
mnemonic (*angr.block.CapstoneInsn* property), 221
mnemonic (*angr.block.DisassemblerInsn* property), 220
mnemonic (*angr.engines.pcode.lifter.PcodeDisassemblerInsn* property), 436
model (*angr.analyses.cfg.cfg_base.CFGBase* property), 650
model (*angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis* attribute), 796
ModSimplifier (class in *angr.analyses.decompiler.optimization_passes.mod_simplifier*), 711
ModSimplifierAILEngine (class in *angr.analyses.decompiler.optimization_passes.mod_simplifier*), 711
module
 angr, 157
 angr.analyses, 623
 angr.analyses.analysis, 623
 angr.analyses.backward_slice, 631
 angr.analyses.binary_optimizer, 869
 angr.analyses.bindiff, 633
 angr.analyses.boyscout, 636
 angr.analyses.callee_cleanup_finder, 870
 angr.analyses.calling_convention, 636
 angr.analyses.cdg, 675
 angr.analyses.cfg, 641
 angr.analyses.cfg.cfb, 641
 angr.analyses.cfg.cfg, 642
 angr.analyses.cfg.cfg_arch_options, 660
 angr.analyses.cfg.cfg_base, 649
 angr.analyses.cfg.cfg_emulated, 644
 angr.analyses.cfg.cfg_fast, 651
 angr.analyses.cfg.cfg_fast_soot, 673
 angr.analyses.cfg.cfg_job_base, 660
 angr.analyses.cfg.indirect_jump_resolvers, 673
 angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got, 661
 angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast, 662
 angr.analyses.cfg.indirect_jump_resolvers.const_resolver, 671
 angr.analyses.cfg.indirect_jump_resolvers.default_resolver, 666
 angr.analyses.cfg.indirect_jump_resolvers.jumptable, 666
 angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast, 664
 angr.analyses.cfg.indirect_jump_resolvers.resolver, 671
 angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic, 665
 angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat, 663
 angr.analyses.cfg_slice_to_sink, 818
 angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink, 818
 angr.analyses.cfg_slice_to_sink.graph, 819
 angr.analyses.cfg_slice_to_sink.transitions, 820
 angr.analyses.class_identifier, 855
 angr.analyses.code_tagging, 675
 angr.analyses.complete_calling_conventions, 638
 angr.analyses.congruency_check, 868
 angr.analyses.data_dep, 879
 angr.analyses.data_dep.data_dependency_analysis, 875
 angr.analyses.data_dep.dep_nodes, 877
 angr.analyses.data_dep.sim_act_location, 876
 angr.analyses.datagraph_meta, 675
 angr.analyses.ddg, 748
 angr.analyses.decompiler, 693
 angr.analyses.decompiler.ail_simplifier, 693
 angr.analyses.decompiler.ailgraph_walker, 694
 angr.analyses.decompiler.block_simplifier, 694
 angr.analyses.decompiler.callsite_maker, 695
 angr.analyses.decompiler.ccall_rewriters, 695
 angr.analyses.decompiler.ccall_rewriters.amd64_ccalls, 695
 angr.analyses.decompiler.ccall_rewriters.rewriter_base, 695

angr.analyses.decompiler.clinic, 696
 angr.analyses.decompiler.condition_processor, 698
 angr.analyses.decompiler.decompilation_cache, 700
 angr.analyses.decompiler.decompilation_options, 699
 angr.analyses.decompiler.decompiler, 700
 angr.analyses.decompiler.empty_node_remover, 701
 angr.analyses.decompiler.expression_narrower, 702
 angr.analyses.decompiler.graph_region, 702
 angr.analyses.decompiler.jump_target_collector, 703
 angr.analyses.decompiler.jumptable_entry_condition_analysier, 703
 angr.analyses.decompiler.optimization_passes, 704
 angr.analyses.decompiler.optimization_passes.base_ptr_base_simplifier, 707
 angr.analyses.decompiler.optimization_passes.canonicalizer, 704
 angr.analyses.decompiler.optimization_passes.dangling_simplifier, 708
 angr.analyses.decompiler.optimization_passes.engine_base, 711
 angr.analyses.decompiler.optimization_passes.expr_optimizer, 712
 angr.analyses.decompiler.optimization_passes.int_expr_converter, 708
 angr.analyses.decompiler.optimization_passes.liveness_analysier, 709
 angr.analyses.decompiler.optimization_passes.mnemonics_simplifier, 711
 angr.analyses.decompiler.optimization_passes.mnemonics_simplifier, 711
 angr.analyses.decompiler.optimization_passes.optimize_analysier, 705
 angr.analyses.decompiler.optimization_passes.register_base_simplifier, 713
 angr.analyses.decompiler.optimization_passes.ret_addr_save_simplifier, 714
 angr.analyses.decompiler.optimization_passes.stack_canary_simplifier, 707
 angr.analyses.decompiler.optimization_passes.x86_getpc_simplifier, 714
 angr.analyses.decompiler.peephole_optimizations, 714
 angr.analyses.decompiler.peephole_optimizations.base, 714
 angr.analyses.decompiler.redundant_label_remover, 725
 angr.analyses.decompiler.region_identifier, 716
 angr.analyses.decompiler.region_simplifiers, 717
 angr.analyses.decompiler.region_simplifiers.cascading, 717
 angr.analyses.decompiler.region_simplifiers.cascading, 717
 angr.analyses.decompiler.region_simplifiers.expr_fold, 718
 angr.analyses.decompiler.region_simplifiers.goto, 720
 angr.analyses.decompiler.region_simplifiers.if_, 721
 angr.analyses.decompiler.region_simplifiers.iffalse, 721
 angr.analyses.decompiler.region_simplifiers.loop, 721
 angr.analyses.decompiler.region_simplifiers.node_address, 721
 angr.analyses.decompiler.region_simplifiers.region_simplifier, 721
 angr.analyses.decompiler.region_simplifiers.switch_case, 722
 angr.analyses.decompiler.region_simplifiers.switch_expr, 725
 angr.analyses.decompiler.region_walker, 725
 angr.analyses.decompiler.sequence_walker, 725
 angr.analyses.decompiler.structured_codegen, 726
 angr.analyses.decompiler.structured_codegen.base, 726
 angr.analyses.decompiler.structured_codegen.c, 727
 angr.analyses.decompiler.structured_codegen.dummy, 745
 angr.analyses.decompiler.structured_codegen.dwarf_import, 744
 angr.analyses.decompiler.structuring, 686
 angr.analyses.decompiler.structuring.dream, 692
 angr.analyses.decompiler.structuring.phoenix, 692
 angr.analyses.decompiler.structuring.recursive_structurer, 692
 angr.analyses.decompiler.structuring.structurer_base, 692
 angr.analyses.decompiler.structuring.structurer_nodes, 692
 angr.analyses.decompiler.utils, 745
 angr.analyses.disassembly, 856
 angr.analyses.disassembly_utils, 860

angr.analyses.dominance_frontier, 870
 angr.analyses.find_objects_static, 855
 angr.analyses.flirt, 754
 angr.analyses.forward_analysis, 625
 angr.analyses.forward_analysis.forward_analysis_graph, 625
 angr.analyses.forward_analysis.job_info, 626
 angr.analyses.forward_analysis.visitors, 626
 angr.analyses.forward_analysis.visitors.call_graph, 626
 angr.analyses.forward_analysis.visitors.function_graph, 627
 angr.analyses.forward_analysis.visitors.graph, 628
 angr.analyses.forward_analysis.visitors.loop, 630
 angr.analyses.forward_analysis.visitors.single_node_graph, 631
 angr.analyses.identifier.identify, 845
 angr.analyses.init_finder, 870
 angr.analyses.loop_analysis, 846
 angr.analyses.loopfinder, 846
 angr.analyses.propagator, 756
 angr.analyses.propagator.engine_ail, 758
 angr.analyses.propagator.engine_base, 757
 angr.analyses.propagator.engine_vex, 757
 angr.analyses.propagator.outdated_definition_walker, 759
 angr.analyses.propagator.propagator, 760
 angr.analyses.propagator.tmpvar_finder, 760
 angr.analyses.propagator.top_checker_mixin, 761
 angr.analyses.propagator.values, 756
 angr.analyses.propagator.vex_vars, 756
 angr.analyses.proximity_graph, 872
 angr.analyses.reaching_definitions, 761
 angr.analyses.reaching_definitions.call_trace, 793
 angr.analyses.reaching_definitions.dep_graph, 798
 angr.analyses.reaching_definitions.engine_ail, 818
 angr.analyses.reaching_definitions.engine_vex, 794
 angr.analyses.reaching_definitions.function_handler, 802
 angr.analyses.reaching_definitions.heap_allocator, 801
 angr.analyses.reaching_definitions.rd_state, 809
 angr.analyses.reaching_definitions.reaching_definitions_table, 521
 angr.analyses.reaching_definitions.subject, 817
 angr.analyses.reassembler, 860
 angr.analyses.soot_class_hierarchy, 640
 angr.analyses.stack_pointer_tracker, 821
 angr.analyses.static_hooker, 868
 angr.analyses.typehoon, 845
 angr.analyses.typehoon.lifter, 832
 angr.analyses.typehoon.simple_solver, 832
 angr.analyses.typehoon.translator, 836
 angr.analyses.typehoon.typeconsts, 843
 angr.analyses.typehoon.typehoon, 842
 angr.analyses.typehoon.typevars, 837
 angr.analyses.variable_recovery, 832
 angr.analyses.variable_recovery.annotations, 823
 angr.analyses.variable_recovery.engine_ail, 831
 angr.analyses.variable_recovery.engine_base, 831
 angr.analyses.variable_recovery.engine_vex, 831
 angr.analyses.variable_recovery.irsb_scanner, 832
 angr.analyses.variable_recovery.variable_recovery, 829
 angr.analyses.variable_recovery.variable_recovery_base, 823
 angr.analyses.variable_recovery.variable_recovery_fast, 827
 angr.analyses.veritesting, 847
 angr.analyses.vfg, 849
 angr.analyses.vsa_ddg, 853
 angr.analyses.vtable, 854
 angr.analyses.xrefs, 871
 angr.angrdb, 676
 angr.angrdb.db, 676
 angr.angrdb.models, 677
 angr.angrdb.serializers, 681
 angr.angrdb.serializers.cfg_model, 681
 angr.angrdb.serializers.comments, 682
 angr.angrdb.serializers.funcs, 682
 angr.angrdb.serializers.kb, 683
 angr.angrdb.serializers.labels, 683
 angr.angrdb.serializers.loader, 683
 angr.angrdb.serializers.structured_code, 685
 angr.angrdb.serializers.variables, 684
 angr.angrdb.serializers.xrefs, 684
 angr.annocfg, 881
 angr.blade, 879
 angr.block, 220
 angr.fragmentable, 521

angr.calling_conventions, 484
 angr.code_location, 616
 angr.codenode, 882
 angr.concretization_strategies, 335
 angr.concretization_strategies.any, 381
 angr.concretization_strategies.controlled_data, 381
 angr.concretization_strategies.eval, 379
 angr.concretization_strategies.max, 380
 angr.concretization_strategies.nonzero, 381
 angr.concretization_strategies.nonzero_range, 380
 angr.concretization_strategies.norepeats, 379
 angr.concretization_strategies.norepeats_range, 381
 angr.concretization_strategies.range, 380
 angr.concretization_strategies.single, 379
 angr.concretization_strategies.solutions, 379
 angr.concretization_strategies.unlimited_range, 382
 angr.distributed, 909
 angr.distributed.server, 909
 angr.distributed.worker, 909
 angr.engines, 427
 angr.engines.concrete, 433
 angr.engines.engine, 428
 angr.engines.failure, 431
 angr.engines.hook, 431
 angr.engines.light, 755
 angr.engines.light.data, 754
 angr.engines.light.engine, 755
 angr.engines.pcode, 434
 angr.engines.pcode.behavior, 445
 angr.engines.pcode.cc, 464
 angr.engines.pcode.emulate, 445
 angr.engines.pcode.engine, 434
 angr.engines.pcode.lifter, 435
 angr.engines.procedure, 430
 angr.engines.soot, 432
 angr.engines.soot.engine, 432
 angr.engines.successors, 429
 angr.engines.syscall, 431
 angr.engines.unicorn, 432
 angr.engines.vex, 432
 angr.errors, 903
 angr.exploration_techniques, 390
 angr.exploration_techniques.bucketizer, 427
 angr.exploration_techniques.common, 425
 angr.exploration_techniques.dfs, 408
 angr.exploration_techniques.director, 418
 angr.exploration_techniques.driller_core, 416
 angr.exploration_techniques.explorer, 408
 angr.exploration_techniques.lengthlimiter, 410
 angr.exploration_techniques.local_loop_seer, 422
 angr.exploration_techniques.loop_seer, 421
 angr.exploration_techniques.manual_mergepoint, 410
 angr.exploration_techniques.memory_watcher, 426
 angr.exploration_techniques.oppologist, 421
 angr.exploration_techniques.slicecutor, 417
 angr.exploration_techniques.spiller, 410
 angr.exploration_techniques.spiller_db, 413
 angr.exploration_techniques.stochastic, 423
 angr.exploration_techniques.suggestions, 427
 angr.exploration_techniques.symbion, 425
 angr.exploration_techniques.tech_builder, 424
 angr.exploration_techniques.threading, 413
 angr.exploration_techniques.timeout, 408
 angr.exploration_techniques.tracer, 414
 angr.exploration_techniques.unique, 423
 angr.exploration_techniques.veritesting, 413
 angr.factory, 216
 angr.flirt, 892
 angr.flirt.build_sig, 892
 angr.keyed_region, 617
 angr.knowledge_base, 523
 angr.knowledge_base.knowledge_base, 523
 angr.knowledge_plugins, 524
 angr.knowledge_plugins.callsite_prototypes, 525
 angr.knowledge_plugins.cfg, 526
 angr.knowledge_plugins.cfg.cfg_manager, 547
 angr.knowledge_plugins.cfg.cfg_model, 539
 angr.knowledge_plugins.cfg.cfg_node, 547
 angr.knowledge_plugins.cfg.indirect_jump, 550
 angr.knowledge_plugins.cfg.memory_data, 545
 angr.knowledge_plugins.comments, 552

angr.knowledge_plugins.data, 552
 angr.knowledge_plugins.debug_variables, 572
 angr.knowledge_plugins.functions, 553
 angr.knowledge_plugins.functions.function, 555
 angr.knowledge_plugins.functions.function_manager, 615
 angr.knowledge_plugins.functions.function_parser, 615
 angr.knowledge_plugins.functions.soot_function, 563
 angr.knowledge_plugins.indirect_jumps, 552
 angr.knowledge_plugins.key_definitions, 574
 angr.knowledge_plugins.key_definitions.atoms, 588
 angr.knowledge_plugins.key_definitions.constants, 592
 angr.knowledge_plugins.key_definitions.definition, 592
 angr.knowledge_plugins.key_definitions.environment, 594
 angr.knowledge_plugins.key_definitions.heap_address, 595
 angr.knowledge_plugins.key_definitions.key_definition, 596
 angr.knowledge_plugins.key_definitions.live_definitions, 596
 angr.knowledge_plugins.key_definitions.rd_mode, 606
 angr.knowledge_plugins.key_definitions.tag, 608
 angr.knowledge_plugins.key_definitions.undefined, 609
 angr.knowledge_plugins.key_definitions.unknown_sizes, 610
 angr.knowledge_plugins.key_definitions.uses, 610
 angr.knowledge_plugins.labels, 552
 angr.knowledge_plugins.patches, 524
 angr.knowledge_plugins.plugin, 525
 angr.knowledge_plugins.propagations, 552
 angr.knowledge_plugins.structured_code, 574
 angr.knowledge_plugins.structured_code.manager, 574
 angr.knowledge_plugins.sync, 612
 angr.knowledge_plugins.sync.sync_controller, 612
 angr.knowledge_plugins.types, 551
 angr.knowledge_plugins.variables, 564
 angr.knowledge_plugins.variables.variable_access, 564
 angr.knowledge_plugins.variables.variable_manager, 565
 angr.knowledge_plugins.xrefs, 614
 angr.knowledge_plugins.xrefs.xref, 614
 angr.knowledge_plugins.xrefs.xref_manager, 615
 angr.knowledge_plugins.xrefs.xref_types, 615
 angr.misc.plugins, 222
 angr.procedures, 474
 angr.procedures.definitions, 476
 angr.procedures.stubs.format_parser, 474
 angr.project, 212
 angr.protos, 621
 angr.serializable, 620
 angr.sim_manager, 382
 angr.sim_options, 228
 angr.sim_procedure, 469
 angr.sim_state, 224
 angr.sim_state_options, 228
 angr.sim_type, 509
 angr.sim_variable, 504
 angr.simos, 884
 angr.simos.cgc, 887
 angr.simos.javavm, 890
 angr.simos.jvarkit, 886
 angr.simos.simos, 884
 angr.simos.userland, 887
 angr.simos.windows, 888
 angr.slicer, 880
 angr.state_hierarchy, 389
 angr.state_plugins, 231
 angr.state_plugins.callstack, 263
 angr.state_plugins.cgc, 271
 angr.state_plugins.concrete, 292
 angr.state_plugins.debug_variables, 307
 angr.state_plugins.filesystem, 248
 angr.state_plugins.gdb, 270
 angr.state_plugins.globals, 278
 angr.state_plugins.heap, 297
 angr.state_plugins.heap.heap_base, 297
 angr.state_plugins.heap.heap_brk, 298
 angr.state_plugins.heap.heap_freelist, 300
 angr.state_plugins.heap.heap_libc, 301
 angr.state_plugins.heap.heap_ptmalloc, 302
 angr.state_plugins.heap.utils, 306
 angr.state_plugins.history, 267
 angr.state_plugins.inspect, 233
 angr.state_plugins.javavm_classloader, 294
 angr.state_plugins.jni_references, 296

Index	1017
--------------	-------------

angr.storage.memory_mixins.smart_find_mixin, 340
 angr.storage.memory_mixins.symbolic_merger_mixin, 343
 angr.storage.memory_mixins.top_merger_mixin, 352
 angr.storage.memory_mixins.underconstrained_mixin, 342
 angr.storage.memory_mixins.unwrapper_mixin, 347
 angr.storage.memory_object, 334
 angr.storage.pcap, 335
 angr.utils, 893
 angr.utils.algo, 894
 angr.utils.constants, 894
 angr.utils.cowdict, 894
 angr.utils.dynamic_dictlist, 894
 angr.utils.enums_conv, 895
 angr.utils.env, 895
 angr.utils.formatting, 901
 angr.utils.graph, 895
 angr.utils.lazy_import, 899
 angr.utils.library, 900
 angr.utils.loader, 899
 angr.utils.mp, 902
 angr.utils.timing, 901
 angr.vaults, 621
 most_mergeable() (angr.state_hierarchy.StateHierarchy method), 390
 most_mergeable() (angr.StateHierarchy method), 180
 mount() (angr.state_plugins.filesystem.SimFilesystem method), 250
 move() (angr.sim_manager.SimulationManager method), 386
 move() (angr.SimulationManager method), 175
 move_codelocs() (angr.analyses.reaching_definitions.ReachingDefinitions method), 814
 move_codelocs() (angr.analyses.reaching_definitions.ReachingDefinitions method), 784
 mp_context() (in module angr.utils.mp), 903
 Mul (angr.engines.light.data.ArithmeticExpression attribute), 754
 mulpyplex() (angr.sim_manager.SimulationManager method), 384
 mulpyplex() (angr.SimulationManager method), 172
 MultiNode (class in angr.analyses.decompiler.structuring.structuring), 687
 MultipleBlocksException, 705
 MultiSimplifier (class in angr.analyses.decompiler.optimization_passes.multi_simplifier), 711
 MultiSimplifierAILEngine (class in angr.analyses.decompiler.optimization_passes.multi_simplifier), 711
 MultiStatementExpressionAssignmentFinder (class in angr.analyses.decompiler.region_simplifiers.expr_folding), 719
 MultiStmtExprMode (class in angr.analyses.decompiler.structuring.phoenix), 692
 MultiValueMemory (class in angr.storage.memory_mixins), 339
 MultiValueMergerMixin (class in angr.storage.memory_mixins.multi_value_merger_mixin), 352
 MultiValues (class in angr.storage.memory_mixins.paged_memory.pages.multi_values), 350
 MultiwriteAnnotation (class in angr.storage.memory_mixins.address_concretization_mixin), 344
 MVListPage (class in angr.storage.memory_mixins.paged_memory.pages.mv_list_page), 348
 MVListPagesMixin (class in angr.storage.memory_mixins.paged_memory.paged_memory_mixin), 356
 MVListPagesWithLabelsMixin (class in angr.storage.memory_mixins.paged_memory.paged_memory_mixin), 357
 N
 n (angr.analyses.typehoon.typevars.AddN attribute), 841
 n (angr.analyses.typehoon.typevars.SubN attribute), 841
 NAME (angr.analyses.decompiler.optimization_passes.base_ptr_save_simplifier), 708
 NAME (angr.analyses.decompiler.optimization_passes.const_derefs.ConstantDerefs), 704
 NAME (angr.analyses.decompiler.optimization_passes.div_simplifier.DivSimplifier), 708
 NAME (angr.analyses.decompiler.optimization_passes.expr_op_swapper.ExprOpSwapper), 713
 NAME (angr.analyses.decompiler.optimization_passes.ite_expr_converter.ITEExprConverter), 709
 NAME (angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier), 710
 NAME (angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifier), 711
 NAME (angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifier), 711
 NAME (angr.analyses.decompiler.optimization_passes.optimization_pass.BaseOptimizationPass), 705
 NAME (angr.analyses.decompiler.optimization_passes.register_save_area_simplifier), 713
 NAME (angr.analyses.decompiler.optimization_passes.ret_addr_save_simplifier), 714
 NAME (angr.analyses.decompiler.optimization_passes.stack_canary_simplifier), 714

NAME (angr.analyses.decompiler.optimization_passes.x86_gadget_extractor.X86GadgetExtractorAnalysis attribute), 714

NAME (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationStmtBase attribute), 716

NAME (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationStmtBase attribute), 715

NAME (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationStmtBase attribute), 714

name (angr.analyses.decompiler.structured_codegen.c.CFakeVariable attribute), 735

name (angr.analyses.decompiler.structured_codegen.c.CFunction attribute), 729

name (angr.analyses.decompiler.structured_codegen.c.CLabel attribute), 734

name (angr.analyses.decompiler.structured_codegen.c.CStructFieldNameDef attribute), 741

name (angr.analyses.decompiler.structured_codegen.c.CVariable attribute), 736

NAME (angr.analyses.decompiler.structuring.dream.DreamStructurer attribute), 686

NAME (angr.analyses.decompiler.structuring.phoenix.PhoenixStructurer attribute), 693

NAME (angr.analyses.decompiler.structuring.structurer_base.StructurerBase attribute), 691

name (angr.analyses.reaching_definitions.function_handler.FunctionCallData attribute), 805

name (angr.analyses.reaching_definitions.FunctionCallData attribute), 791

name (angr.analyses.reaching_definitions.Register property), 773

name (angr.analyses.reassembler.Procedure property), 863

name (angr.analyses.typehoon.typevars.TypeVariable attribute), 839

name (angr.angrdb.models.DbKnowledgeBase attribute), 678

name (angr.angrdb.models.DbLabel attribute), 681

name (angr.knowledge_plugins.cfg.cfg_node.CFGNode property), 548

name (angr.knowledge_plugins.cfg.CFGNode property), 529

name (angr.knowledge_plugins.functions.function.Function property), 557

name (angr.knowledge_plugins.key_definitions.atoms.Register property), 591

name (angr.procedures.definitions.SimLibrary property), 477

name (angr.sim_state_options.StateOption attribute), 228

name (angr.sim_type.NamedTypeMixin property), 510

name (angr.sim_type.SimTypeRef property), 520

name (angr.sim_type.TypeRef property), 510

name (angr.sim_variable.SimVariable attribute), 504

name_stop() (angr.state_plugins.unicorn_engine.STOP static method), 287

named_block_extractor(NamedBlockExtractorAnalysis attribute), 625

named_block_extractor(NamedBlockExtractorAnalysis attribute), 178

NamedTypeMixin (class in angr.sim_type), 510

NamedTypeMixin (class in angr.storage.memory_mixins.name_resolution_mixin), 510

native_arch (angr.simos.javavm.SimJavaVM property), 891

NE (angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier.C switch_cluster_simplifier), 722

NEVER (angr.analyses.decompiler.structuring.phoenix.MultiStmtExprMode attribute), 692

new() (angr.analyses.cfg.cfg_job_base.BlockID static method), 661

new() (angr.analyses.cfg.cfg_job_base.FunctionKey static method), 661

new() (angr.analyses.typehoon.typeconsts.Pointer static method), 844

new_block_addr() (angr.analyses.decompiler.clinic.Clinic static method), 698

new_block_addr() (angr.analyses.decompiler.optimization_passes.optimization_passes.lowered_switch attribute), 710

new_from_shared() (angr.storage.memory_mixins.paged_memory.pages.PagedMemory static method), 364

new_label() (angr.analyses.reassembler.Label static method), 860

new_label() (angr.analyses.reassembler.SymbolManager static method), 861

new_model() (angr.knowledge_plugins.cfg.cfg_manager.CFGManager static method), 547

new_model() (angr.knowledge_plugins.cfg.CFGManager static method), 538

NewFunctionHandler (class in angr.analyses.find_objects_static), 855

Next (angr.analyses.loop_analysis.VariableTypes attribute), 846

next (angr.engines.pcode.lifter.IRSB attribute), 438

next (angr.state_plugins.unicorn_engine.MEM_PATCH attribute), 284

next_addr (angr.analyses.decompiler.optimization_passes.lowered_switch attribute), 710

next_arg() (angr.calling_conventions.SimCC method), 491

next_arg() (angr.calling_conventions.SimCCARM static method), 497

next_arg() (angr.calling_conventions.SimCCCdecl static method), 493

next_arg() (angr.calling_conventions.SimCCMicrosoftAMD64 static method), 494

next_arg() (angr.calling_conventions.SimCCO32 static method), 499

next_arg() (angr.calling_conventions.SimCCSystemVAMD64 static method), 496

<code>next_arg()</code> (<code>anгр.calling_conventions.SimCCUsercall</code> method), 493	<code>NodeFoundNotification</code> , 708
<code>next_arg()</code> (<code>anгр.SimCC</code> method), 186	<code>nodes</code> (<code>anгр.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink</code> property), 819
<code>next_chunk()</code> (<code>anгр.PTChunk</code> method), 209	<code>nodes</code> (<code>anгр.analyses.decompiler.structuring.structurer_nodes.MultiNode</code> attribute), 687
<code>next_chunk()</code> (<code>anгр.state_plugins.heap.heap_freelist.Chunk</code> method), 300	<code>nodes</code> (<code>anгр.analyses.decompiler.structuring.structurer_nodes.SequenceNode</code> attribute), 687
<code>next_chunk()</code> (<code>anгр.state_plugins.heap.heap_ptmalloc.PTChunk</code> method), 303	<code>nodes</code> (<code>anгр.knowledge_plugins.functions.function.Function</code> property), 558
<code>next_node()</code> (<code>anгр.analyses.forward_analysis.visitors.graph.GraphVisitor</code> method), 629	<code>nodes</code> (<code>anгр.analyses.cfg_base.CFGBase</code> method), 651
<code>next_node()</code> (<code>anгр.analyses.forward_analysis.visitors.single_node.SingleNode</code> method), 631	<code>nodes()</code> (<code>anгр.analyses.forward_analysis.visitors.graph.GraphVisitor</code> method), 629
<code>next_variable_ident()</code> (<code>anгр.knowledge_plugins.variables.variable_manager.VariableManager</code> method), 566	<code>nodes()</code> (<code>anгр.analyses.reaching_definitions.dep_graph.DepGraph</code> method), 799
<code>no_ret</code> (<code>anгр.knowledge_plugins.cfg.cfg_node.CFGNode</code> attribute), 548	<code>nodes()</code> (<code>anгр.knowledge_plugins.cfg.cfg_model.CFGModel</code> method), 541
<code>no_ret</code> (<code>anгр.knowledge_plugins.cfg.CFGNode</code> at- tribute), 528	<code>nodes()</code> (<code>anгр.knowledge_plugins.cfg.CFGModel</code> method), 534
<code>NO_RET</code> (<code>anгр.sim_procedure.SimProcedure</code> attribute), 472	<code>nodes_iter()</code> (<code>anгр.analyses.cfg.cfg_base.CFGBase</code> method), 651
<code>NO_RET</code> (<code>anгр.SimProcedure</code> attribute), 159	<code>nodes_iter()</code> (<code>anгр.analyses.forward_analysis.visitors.graph.GraphVisitor</code> method), 629
<code>NoConcreteDispatch</code> , 640	<code>NONE</code> (<code>anгр.simos.windows.SecurityCookieInit</code> attribute), 888
<code>NodalAnnotation</code> (class in <code>anгр.analyses.data_dep.data_dependency_analysis.data_dependency_analysis</code>), 875	<code>NORMAL</code> (<code>anгр.analyses.cfg_fast.CFGJobType</code> at- tribute), 655
<code>node</code> (<code>anгр.analyses.decompiler.region_simplifiers.switch_case.SwitchCaseRegion</code> attribute), 722	<code>normalize()</code> (<code>anгр.analyses.cfg_base.CFGBase</code> method), 651
<code>node</code> (<code>anгр.analyses.decompiler.region_simplifiers.switch_case.SwitchCaseRegion</code> attribute), 723	<code>normalize()</code> (<code>anгр.analyses.cfg_fast_soot.CFGFastSoot</code> method), 674
<code>node</code> (<code>anгр.analyses.decompiler.structuring.structurer_nodes.MultiNode</code> attribute), 688	<code>normalize()</code> (<code>anгр.knowledge_plugins.functions.function.Function</code> method), 562
<code>node</code> (<code>anгр.analyses.decompiler.structuring.structurer_nodes.SequenceNode</code> attribute), 688	<code>normalize()</code> (<code>anгр.knowledge_plugins.functions.soot_function.SootFunction</code> method), 564
<code>node</code> (<code>anгр.analyses.forward_analysis.visitors.single_node.SingleNode</code> attribute), 631	<code>normalize()</code> (<code>anгр.knowledge_plugins.key_definitions.definition.Definition</code> method), 593
<code>node_addr</code> (<code>anгр.analyses.decompiler.region_simplifiers.expression.ExpressionRegion</code> attribute), 719	<code>normalize_optimization_name()</code> (in module <code>anгр.sim_type</code>), 521
<code>node_addr</code> (<code>anгр.analyses.decompiler.region_simplifiers.expression.ExpressionRegion</code> attribute), 718	<code>normalized</code> (<code>anгр.analyses.cfg_base.CFGBase</code> property), 650
<code>node_mapping</code> (<code>anгр.analyses.typehoon.simple_solver.Sketch</code> attribute), 833	<code>normalized</code> (<code>anгр.analyses.cfg_model.CFGModel</code> attribute), 539
<code>node_observe()</code> (<code>anгр.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis</code> method), 797	<code>normalized</code> (<code>anгр.knowledge_plugins.cfg.CFGModel</code> at- tribute), 532
<code>node_observe()</code> (<code>anгр.analyses.reaching_definitions.ReachingDefinitionsAnalysis</code> method), 776	<code>normalized</code> (<code>anгр.knowledge_plugins.functions.function.Function</code> attribute), 556
<code>node_position()</code> (<code>anгр.analyses.decompiler.structuring.structurer_nodes.MultiNode</code> method), 687	<code>normalized</code> (<code>anгр.knowledge_plugins.functions.soot_function.SootFunction</code> attribute), 563
<code>node_returned</code> (<code>anгр.analyses.forward_analysis.visitors.single_node.SingleNode</code> attribute), 631	<code>NormalizedBlock</code> (<code>anгр.analyses.bindiff</code>), 634
<code>node_type</code> (<code>anгр.analyses.decompiler.optimization_passes.NormalizedBlock</code> attribute), 709	<code>NormalizedFunction</code> (class in <code>anгр.analyses.bindiff</code>), 634
<code>NodeAddressFinder</code> (class in <code>anгр.analyses.decompiler.region_simplifiers.node_address_finder</code>), 666	<code>NodeFoundNotification</code> , 666

NotEqual (angr.analyses.loop_analysis.Condition attribute), 847
 NotMemoryview (class in angr.storage.memory_mixins.paged_memory.page_backer_mixins), 357
 NotypeLabel (class in angr.analyses.reassembler), 861
 NULL_TERMINATE (angr.knowledge_plugins.key_definitions.Definition attribute), 585
 NULL_TERMINATE (angr.knowledge_plugins.key_definitions.Definition attribute), 597
 num_arguments (angr.knowledge_plugins.functions.function.Function property), 558
O
 0 (in module angr.analyses.decompiler.decompilation_options), 700
 O_ACCMODE (angr.storage.file.Flags attribute), 315
 O_APPEND (angr.storage.file.Flags attribute), 315
 O_ASYNC (angr.storage.file.Flags attribute), 315
 O_CLOEXEC (angr.storage.file.Flags attribute), 315
 O_CREAT (angr.storage.file.Flags attribute), 315
 O_DIRECT (angr.storage.file.Flags attribute), 315
 O_DIRECTORY (angr.storage.file.Flags attribute), 315
 O_DSYNC (angr.storage.file.Flags attribute), 315
 O_EXCL (angr.storage.file.Flags attribute), 315
 O_LARGEFILE (angr.storage.file.Flags attribute), 315
 O_NDELAY (angr.storage.file.Flags attribute), 315
 O_NOATIME (angr.storage.file.Flags attribute), 315
 O_NOCTTY (angr.storage.file.Flags attribute), 315
 O_NOFOLLOW (angr.storage.file.Flags attribute), 315
 O_NONBLOCK (angr.storage.file.Flags attribute), 315
 O_PATH (angr.storage.file.Flags attribute), 315
 O_RDONLY (angr.storage.file.Flags attribute), 314
 O_RDWR (angr.storage.file.Flags attribute), 314
 O_SYNC (angr.storage.file.Flags attribute), 315
 O_TMPFILE (angr.storage.file.Flags attribute), 315
 O_TRUNC (angr.storage.file.Flags attribute), 315
 O_WRONLY (angr.storage.file.Flags attribute), 314
 obj (angr.analyses.decompiler.structured_codegen.base.PositionMappingElement attribute), 726
 obj (angr.analyses.disassembly.IROp attribute), 857
 obj (angr.keyed_region.StoredObject attribute), 617
 obj (angr.utils.graph.ContainerNode property), 897
 obj_bit_size() (in module angr.storage.memory_object), 334
 obj_id (angr.keyed_region.StoredObject property), 618
 object (angr.storage.memory_object.SimMemoryObject attribute), 334
 ObjectLabel (class in angr.analyses.reassembler), 861
 ObservationPointType (class in angr.analyses.reaching_definitions), 770
 ObservationPointType (class in angr.knowledge_plugins.key_definitions.constants), 592
 observed_results (angr.analyses.reaching_definitions.reaching_definition property), 797
 observed_results (angr.analyses.reaching_definitions.ReachingDefinition property), 776
 offset (angr.analyses.decompiler.structured_codegen.c.CStructField attribute), 735
 offset (angr.analyses.propagator.vex_vars.VEXReg attribute), 756
 offset (angr.analyses.reaching_definitions.Definition property), 774
 offset (angr.analyses.reassembler.Label property), 860
 offset (angr.analyses.stack_pointer_tracker.OffsetVal property), 821
 offset (angr.analyses.stack_pointer_tracker.Register attribute), 821
 offset (angr.analyses.typehoon.typevars.HasField attribute), 842
 offset (angr.engines.light.data.RegisterOffset attribute), 755
 offset (angr.knowledge_plugins.functions.function.Function property), 559
 offset (angr.knowledge_plugins.key_definitions.Definition property), 588
 offset (angr.knowledge_plugins.key_definitions.definition.Definition property), 594
 offset (angr.knowledge_plugins.variables.variable_access.VariableAccess attribute), 565
 Offset (angr.knowledge_plugins.xrefs.xref_types.XRefType attribute), 615
 offset (angr.sim_variable.SimStackVariable attribute), 508
 offset (angr.state_plugins.unicorn_engine.RegisterValue attribute), 285
 offset_after() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 822
 offset_after_block() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 823
 offset_before() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 822
 offset_before_block() (angr.analyses.stack_pointer_tracker.StackPointerTracker method), 823
 offsets (angr.sim_type.SimStruct property), 517
 OffsetVal (class in angr.analyses.stack_pointer_tracker), 821
 offsIP (angr.engines.pcode.lifter.IRSB property), 439
 omit_header (angr.analyses.decompiler.structured_codegen.c.CFunction attribute), 729
 on_worker_exit() (angr.distributed.server.Server method), 909
 on_worker_exit() (angr.Server method), 211
 one_active (angr.sim_manager.SimulationManager attribute), 383

<code>one_active</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorBoolAnd</code> (class <code>angr.engines.pcode.behavior</code>), 459	in
<code>one_deadended</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorBoolNegate</code> (class <code>angr.engines.pcode.behavior</code>), 458	in
<code>one_deadended</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorBoolOr</code> (class <code>angr.engines.pcode.behavior</code>), 459	in
<code>one_found</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorBoolXor</code> (class <code>angr.engines.pcode.behavior</code>), 458	in
<code>one_found</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorCopy</code> (class <code>angr.engines.pcode.behavior</code>), 446	in
<code>one_label()</code> (<code>angr.analyses.typehoon.typevars.DerivedType</code> method), 840	<code>OpBehaviorEqual</code> (class <code>angr.engines.pcode.behavior</code>), 447	in
<code>one_pruned</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorFloatAbs</code> (class <code>angr.engines.pcode.behavior</code>), 462	in
<code>one_pruned</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorFloatAdd</code> (class <code>angr.engines.pcode.behavior</code>), 461	in
<code>one_result</code> (<code>angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitionsAnalysis</code> property), 797	<code>OpBehaviorFloatCeil</code> (class <code>angr.engines.pcode.behavior</code>), 463	in
<code>one_result</code> (<code>angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis</code> property), 776	<code>OpBehaviorFloatDiv</code> (class <code>angr.engines.pcode.behavior</code>), 461	in
<code>one_stashed</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorFloatEqual</code> (class <code>angr.engines.pcode.behavior</code>), 459	in
<code>one_stashed</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorFloatFloat2Float</code> (class <code>angr.engines.pcode.behavior</code>), 462	in
<code>one_type()</code> (<code>angr.sim_state_options.StateOption</code> method), 228	<code>OpBehaviorFloatFloor</code> (class <code>angr.engines.pcode.behavior</code>), 463	in
<code>one_unconstrained</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorFloatInt2Float</code> (class <code>angr.engines.pcode.behavior</code>), 462	in
<code>one_unconstrained</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorFloatLess</code> (class <code>angr.engines.pcode.behavior</code>), 460	in
<code>one_unsat</code> (<code>angr.sim_manager.SimulationManager</code> attribute), 383	<code>OpBehaviorFloatLessEqual</code> (class <code>angr.engines.pcode.behavior</code>), 460	in
<code>one_unsat</code> (<code>angr.SimulationManager</code> attribute), 172	<code>OpBehaviorFloatMult</code> (class <code>angr.engines.pcode.behavior</code>), 461	in
<code>one_value()</code> (<code>angr.storage.memory_mixins.paged_memory.pages.multiple_paged_memory</code> method), 351	<code>OpBehaviorFloatNan</code> (class <code>angr.engines.pcode.behavior</code>), 460	in
<code>op</code> (<code>angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifiers.RegionSimplificationRegion</code> attribute), 722	<code>OpBehaviorFloatNeg</code> (class <code>angr.engines.pcode.behavior</code>), 461	in
<code>op</code> (<code>angr.analyses.decompiler.structured_codegen.c.CBinaryOp</code> attribute), 737	<code>OpBehaviorFloatNotEqual</code> (class <code>angr.engines.pcode.behavior</code>), 460	in
<code>op</code> (<code>angr.analyses.decompiler.structured_codegen.c.CUnaryOp</code> attribute), 737	<code>OpBehaviorFloatRound</code> (class <code>angr.engines.pcode.behavior</code>), 463	in
<code>op</code> (<code>angr.engines.light.data.ArithmeticExpression</code> attribute), 755	<code>OpBehaviorFloatSqrt</code> (class <code>angr.engines.pcode.behavior</code>), 462	in
<code>OP_AFTER</code> (<code>angr.analyses.reaching_definitions.ObservationPointType</code> attribute), 770	<code>OpBehaviorFloatSub</code> (class <code>angr.engines.pcode.behavior</code>), 461	in
<code>OP_AFTER</code> (<code>angr.knowledge_plugins.key_definitions.constants.ObservationPointType</code> attribute), 592	<code>OpBehaviorFloatTrunc</code> (class <code>angr.engines.pcode.behavior</code>), 462	in
<code>OP_BEFORE</code> (<code>angr.analyses.reaching_definitions.ObservationPointType</code> attribute), 770	<code>OpBehaviorInt2Comp</code> (class <code>angr.engines.pcode.behavior</code>), 452	in
<code>OP_BEFORE</code> (<code>angr.knowledge_plugins.key_definitions.constants.ObservationPointType</code> attribute), 592	<code>OpBehaviorIntAdd</code> (class <code>angr.engines.pcode.behavior</code>), 450	in
<code>op_precedence</code> (<code>angr.analyses.decompiler.structured_codegen.c.CBinaryOp</code> property), 738	<code>OpBehaviorIntAnd</code> (class <code>angr.engines.pcode.behavior</code>), 453	in
<code>op_str</code> (<code>angr.block.CapstoneInsn</code> property), 221		
<code>op_str</code> (<code>angr.block.DisassemblerInsn</code> property), 220		
<code>op_str</code> (<code>angr.engines.pcode.lifter.PcodeDisassemblerInsn</code> property), 436		
<code>OpBehavior</code> (class in <code>angr.engines.pcode.behavior</code>), 445		

OpBehaviorIntCarry	(class angr.engines.pcode.behavior), 451	in opcode (angr.engines.pcode.behavior.OpBehaviorBoolNegate attribute), 458
OpBehaviorIntDiv	(class angr.engines.pcode.behavior), 456	in opcode (angr.engines.pcode.behavior.OpBehaviorBoolOr attribute), 459
OpBehaviorIntLeft	(class angr.engines.pcode.behavior), 454	in opcode (angr.engines.pcode.behavior.OpBehaviorBoolXor attribute), 459
OpBehaviorIntLess	(class angr.engines.pcode.behavior), 448	in opcode (angr.engines.pcode.behavior.OpBehaviorCopy attribute), 447
OpBehaviorIntLessEqual	(class angr.engines.pcode.behavior), 449	in opcode (angr.engines.pcode.behavior.OpBehaviorEqual attribute), 447
OpBehaviorIntMult	(class angr.engines.pcode.behavior), 456	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatAbs attribute), 462
OpBehaviorIntNegate	(class angr.engines.pcode.behavior), 453	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatAdd attribute), 461
OpBehaviorIntOr	(class angr.engines.pcode.behavior), 454	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatCeil attribute), 463
OpBehaviorIntRem	(class angr.engines.pcode.behavior), 457	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatDiv attribute), 461
OpBehaviorIntRight	(class angr.engines.pcode.behavior), 455	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatEqual attribute), 460
OpBehaviorIntSborrow	(class angr.engines.pcode.behavior), 452	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatFloat2Float attribute), 462
OpBehaviorIntScarry	(class angr.engines.pcode.behavior), 451	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatFloor attribute), 463
OpBehaviorIntSdiv	(class angr.engines.pcode.behavior), 456	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatInt2Float attribute), 462
OpBehaviorIntSext	(class angr.engines.pcode.behavior), 450	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatLess attribute), 460
OpBehaviorIntSless	(class angr.engines.pcode.behavior), 447	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatLessEqual attribute), 460
OpBehaviorIntSlessEqual	(class angr.engines.pcode.behavior), 448	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatMult attribute), 461
OpBehaviorIntSrem	(class angr.engines.pcode.behavior), 457	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatNan attribute), 460
OpBehaviorIntSright	(class angr.engines.pcode.behavior), 455	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatNeg attribute), 461
OpBehaviorIntSub	(class angr.engines.pcode.behavior), 450	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatNotEqual attribute), 460
OpBehaviorIntXor	(class angr.engines.pcode.behavior), 453	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatRound attribute), 463
OpBehaviorIntZext	(class angr.engines.pcode.behavior), 449	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatSqrt attribute), 462
OpBehaviorNotEqual	(class angr.engines.pcode.behavior), 447	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatSub attribute), 461
OpBehaviorPiece	(class angr.engines.pcode.behavior), 463	in opcode (angr.engines.pcode.behavior.OpBehaviorFloatTrunc attribute), 462
OpBehaviorPopcount	(class angr.engines.pcode.behavior), 464	in opcode (angr.engines.pcode.behavior.OpBehaviorInt2Comp attribute), 453
OpBehaviorSubpiece	(class angr.engines.pcode.behavior), 463	in opcode (angr.engines.pcode.behavior.OpBehaviorIntAdd attribute), 450
opcode	(angr.engines.pcode.behavior.OpBehavior attribute), 445	opcode (angr.engines.pcode.behavior.OpBehaviorIntAnd attribute), 454
opcode (angr.engines.pcode.behavior.OpBehaviorBoolAnd	opcode (angr.engines.pcode.behavior.OpBehaviorBoolAnd attribute), 459	opcode (angr.engines.pcode.behavior.OpBehaviorIntCarry attribute), 451

- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntDiv* attribute), 456
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntLeft* attribute), 455
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntLess* attribute), 449
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntLessEqual* attribute), 449
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntMult* attribute), 456
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntNegate* attribute), 453
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntOr* attribute), 454
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntRem* attribute), 457
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntRight* attribute), 455
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSborrow* attribute), 452
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntScarry* attribute), 452
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSdiv* attribute), 457
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSext* attribute), 450
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSless* attribute), 448
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSlessEqual* attribute), 448
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSrem* attribute), 458
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSright* attribute), 456
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntSub* attribute), 451
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntXor* attribute), 453
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorIntZext* attribute), 450
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorNotEqual* attribute), 447
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorPiece* attribute), 463
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorPopcount* attribute), 464
- `opcode` (*angr.engines.pcode.behavior.OpBehaviorSubpiece* attribute), 464
- `Opcode` (class in *angr.analyses.disassembly*), 858
- `OpDescriptor` (class in *angr.analyses.decompiler.optimization_passes.expr_op_swap* attribute), 712
- `open()` (*angr.state_plugins.posix.SimSystemPosix* method), 245
- `open_db()` (*angr.angrdb.db.AngrDB* static method), 676
- `open_socket()` (*angr.state_plugins.posix.SimSystemPosix* method), 246
- `opening_symbol` (*angr.analyses.decompiler.structured_codegen.c.CClosin* attribute), 741
- `operand` (*angr.analyses.decompiler.structured_codegen.c.CUnaryOp* attribute), 737
- `Operand` (class in *angr.analyses.disassembly*), 858
- `Operand` (class in *angr.analyses.reassembler*), 861
- `operand_str` (*angr.analyses.reassembler.DataLabel* property), 860
- `operand_str` (*angr.analyses.reassembler.FunctionLabel* property), 861
- `operand_str` (*angr.analyses.reassembler.Label* property), 860
- `operand_str` (*angr.analyses.reassembler.NotypeLabel* property), 861
- `operand_str` (*angr.analyses.reassembler.ObjectLabel* property), 861
- `OperandPiece` (class in *angr.analyses.disassembly*), 858
- `operands` (*angr.engines.light.data.ArithmeticExpression* attribute), 755
- `OPERATE` (*angr.state_plugins.sim_action.SimActionData* attribute), 468
- `operations` (*angr.engines.pcode.lifter.IRSB* property), 439
- `operations` (*angr.knowledge_plugins.functions.function.Function* property), 558
- `Oppologist` (class in *angr.exploration_techniques*), 399
- `Oppologist` (class in *angr.exploration_techniques.oppologist*), 421
- `opt_level` (*angr.engines.pcode.lifter.Lifter* attribute), 440
- `opt_level` (*angr.engines.pcode.lifter.PcodeLifter* attribute), 442
- `OptimizationPass` (class in *angr.analyses.decompiler.optimization_passes.optimization_pass*), 706
- `OptimizationPassStage` (class in *angr.analyses.decompiler.optimization_passes.optimization_pass*), 705
- `optimize()` (*angr.analyses.binary_optimizer.BinaryOptimizer* method), 870
- `optimize()` (*angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization* method), 716
- `optimize()` (*angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization* method), 715
- `optimize()` (*angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization* method), 715
- `OPTIONS` (*angr.analyses.cfg.cfg_arch_options.CFGArchOptions* attribute), 660
- `OPTIONS` (*angr.sim_state_options.SimStateOptions* attribute), 228
- `options` (*angr.slicer.SimLightState* attribute), 880

options_to_params() (angr.calling_conventions.SimCCO32 attribute), 499
 (angr.analyses.decompiler.decompiler.Decompiler static method), 701
 Or (angr.engines.light.data.ArithmeticExpression attribute), 754
 Or1 (angr.analyses.cfg.indirect_jump_resolvers.jumptable.Armv7MOverflowReturnVal (angr.SimCC attribute), 185
 attribute), 666
 original_node (angr.analyses.decompiler.optimization_passes.lowered_switch_duplication.Case attribute), 709
 other_input_defns (angr.analyses.reaching_definitions.dep_graph.FunctionCycleRelationships_jump_resolvers.mips_elf_fast.OverwriteTmpValueCallback method), 664
 other_output_defns (angr.analyses.reaching_definitions.OverwriteTmpValueCallback class in ang_r_analyses_cfg_indirect_jump_resolvers_mips_elf_fast), attribute), 799
 other_types (angr.procedures.stubs.format_parser.FormatParser attribute), 475
 other_uses (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762
 other_uses (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions.stubs.format_parser.FormatSpecifier attribute), 598
 other_uses (angr.knowledge_plugins.key_definitions.LiveDefinitions.PAGE_TYPE (angr.storage.memory_mixins.paged_memory.paged_memory attribute), 578
 attribute), 356
 others (angr.analyses.reaching_definitions.LiveDefinitions.PAGE_TYPE (angr.storage.memory_mixins.paged_memory.paged_memory attribute), 762
 attribute), 356
 others (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions.PAGE_TYPE (angr.storage.memory_mixins.paged_memory.paged_memory attribute), 598
 attribute), 353
 others (angr.knowledge_plugins.key_definitions.LiveDefinitions.PAGE_TYPE (angr.storage.memory_mixins.paged_memory.paged_memory attribute), 577
 attribute), 357
 OutdatedDefinitionWalker (class in PageBase (class in ang_r_storage_memory_mixins_paged_memory_pages), ang_r_analyses_propagator_outdated_definition_walker), 359
 759
 OutdatedError, 642
 OuterWalker (class in PagedMemoryMixin (class in ang_r_storage_memory_mixins_paged_memory_paged_memory_mixin), ang_r_analyses_decompiler_optimization_passes_expanded_parameter_tag), (class in 353
 712
 attribute), 609
 output() (angr.analyses.cfg.cfg_base.CFGBase method), 650
 output() (angr.analyses.cfg.cfg_fast.CFGFast method), 660
 OVERFLOW_FP_RETURN_VAL (angr.calling_conventions.SimCCSystemVAMD64 attribute), 496
 OVERFLOW_RETURN_VAL (angr.calling_conventions.SimCC attribute), 489
 OVERFLOW_RETURN_VAL (angr.calling_conventions.SimCCARM attribute), 497
 OVERFLOW_RETURN_VAL (angr.calling_conventions.SimCCCdecl attribute), 493
 OVERFLOW_RETURN_VAL (angr.calling_conventions.SimCCMicrosoftAMD64 attribute), 494
 OVERFLOW_RETURN_VAL (angr.calling_conventions.SimCC attribute), 494

<code>parse_from_cmessage()</code> (<i>angr.block.Block</i> class method), 222	<i>angr.analyses.variable_recovery.variable_recovery_base</i> , 823
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.cfg_model.CFGModel</i> class method), 539	<code>parse_type()</code> (in module <i>angr.sim_type</i>), 521
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.cfg_node.CFGNode</i> class method), 549	<code>parse_type_with_name()</code> (in module <i>angr.sim_type</i>), 521
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.CFGModel</i> class method), 533	<code>parse_types()</code> (in module <i>angr.sim_type</i>), 521
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.CFGNode</i> class method), 529	<code>parse_variable_addr()</code> (<i>angr.analyses.decompiler.clinic.Clinic</i> method), 697
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.memory_data.MemoryData</i> class method), 546	<code>parsedcprotos2py()</code> (in module <i>angr.utils.library</i>), 900
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.cfg.MemoryData</i> class method), 528	<code>ParsedInstruction</code> (class in <i>angr.analyses.data_dep.sim_act_location</i>), 876
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.functions.function.Function</i> class method), 558	<code>Patch</code> (class in <i>angr.knowledge_plugins.patches</i>), 524
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.variables.variable_access.VariableAccess</i> class method), 565	<code>patch_addr()</code> (<i>angr.knowledge_plugins.patches.PatchManager</i> method), 524
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.variables.variable_manager.VariableManager</i> class method), 566	<code>patched_entry_state</code> (<i>angr.knowledge_plugins.patches.PatchManager</i> property), 525
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.xrefs.xref.XRef</i> class method), 615	<code>PatchManager</code> (class in <i>angr.knowledge_plugins.patches</i>), 524
<code>parse_from_cmessage()</code> (<i>angr.knowledge_plugins.xrefs.xref_manager.XRefManager</i> class method), 616	<code>path</code> (<i>angr.angrdb.models.DbObject</i> attribute), 678
<code>parse_from_cmessage()</code> (<i>angr.serializable.Serializable</i> class method), 621	<code>path()</code> (<i>angr.analyses.typehoon.typevars.DerivedTypeVariable</i> method), 840
<code>parse_from_cmessage()</code> (<i>angr.sim_variable.SimMemoryVariable</i> class method), 507	<code>path_between()</code> (<i>angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink</i> method), 819
<code>parse_from_cmessage()</code> (<i>angr.sim_variable.SimRegisterVariable</i> class method), 506	<code>PathUnreachableError</code> , 913
<code>parse_from_cmessage()</code> (<i>angr.sim_variable.SimStackVariable</i> class method), 508	<code>PCAP</code> (class in <i>angr.storage.pcap</i>), 335
<code>parse_from_cmessage()</code> (<i>angr.sim_variable.SimTemporaryVariable</i> class method), 506	<code>PcodeBasicBlockLifter</code> (class in <i>angr.engines.pcode.lifter</i>), 441
<code>parse_from_cmsg()</code> (<i>angr.knowledge_plugins.functions.function.Function</i> static method), 563	<code>PcodeDisassemblerBlock</code> (class in <i>angr.engines.pcode.lifter</i>), 435
<code>parse_signature()</code> (in module <i>angr.sim_type</i>), 520	<code>PcodeDisassemblerInsn</code> (class in <i>angr.engines.pcode.lifter</i>), 435
<code>parse_stack_pointer()</code> (in module <i>angr.analyses.decompiler.clinic.clinic</i>), 697	<code>PcodeEmulatorMixin</code> (class in <i>angr.engines.pcode.emulate</i>), 445
	<code>PcodeLifter</code> (class in <i>angr.engines.pcode.lifter</i>), 442
	<code>PcodeLifterEngineMixin</code> (class in <i>angr.engines.pcode.lifter</i>), 443
	<code>peek_input()</code> (<i>angr.state_plugins.cgc.SimStateCGC</i> method), 272
	<code>peek_output()</code> (<i>angr.state_plugins.cgc.SimStateCGC</i> method), 272
	<code>peephole_optimize_expr()</code> (in module <i>angr.analyses.decompiler.utils</i>), 747
	<code>peephole_optimize_exprs()</code> (in module <i>angr.analyses.decompiler.utils</i>), 747
	<code>peephole_optimize_multistmts()</code> (in module <i>angr.analyses.decompiler.utils</i>), 748
	<code>peephole_optimize_stmts()</code> (in module <i>angr.analyses.decompiler.utils</i>), 747
	<code>PeepholeOptimizationExprBase</code> (class in <i>angr.analyses.decompiler.peephole_optimizations.base</i>), 747

716 attribute), 709
 PeepholeOptimizationMultiStmtBase (class in PLATFORMS (angr.analyses.decompiler.optimization_passes.lowered_switch),
 angr.analyses.decompiler.peephole_optimizations.base), attribute), 710
 715 PLATFORMS (angr.analyses.decompiler.optimization_passes.mod_simplifier.
 PeepholeOptimizationStmtBase (class in attribute), 711
 angr.analyses.decompiler.peephole_optimizations.PLATFORMS (angr.analyses.decompiler.optimization_passes.multi_simplifier.
 714 attribute), 711
 PendingJob (class in angr.analyses.cfg.cfg_emulated), PLATFORMS (angr.analyses.decompiler.optimization_passes.optimization_pa
 644 attribute), 705
 PendingJob (class in angr.analyses.vfg), 849 PLATFORMS (angr.analyses.decompiler.optimization_passes.optimization_pa
 PendingJobs (class in angr.analyses.cfg.cfg_fast), 652 attribute), 706
 perform_call() (angr.callable.Callable method), 522 PLATFORMS (angr.analyses.decompiler.optimization_passes.optimization_pa
 perm_exec (angr.storage.memory_mixins.paged_memory.pages.permissions), 707 PermissionsMixin
 property), 360 PLATFORMS (angr.analyses.decompiler.optimization_passes.register_save_a
 perm_read (angr.storage.memory_mixins.paged_memory.pages.permissions), 713 PermissionsMixin
 property), 360 PLATFORMS (angr.analyses.decompiler.optimization_passes.ret_addr_save_
 perm_write (angr.storage.memory_mixins.paged_memory.pages.permissions), 714 PermissionsMixin
 property), 360 PLATFORMS (angr.analyses.decompiler.optimization_passes.stack_canary_s
 permissions() (angr.storage.memory_mixins.address_concretization), 407 AddressConcretizationMixin
 method), 346 PLATFORMS (angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_
 permissions() (angr.storage.memory_mixins.MemoryMixin attribute), 714
 method), 337 plugin_preset (angr.misc.plugins.PluginHub prop-
 permissions() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin
 method), 354 PluginHub (class in angr.misc.plugins), 222
 PermissionsMixin (class in PluginPreset (class in angr.misc.plugins), 223
 angr.storage.memory_mixins.paged_memory.pages.plugins (angr.misc.plugins), 223
 360 plugins (angr.SimState property), 225
 Permissive (angr.exploration_techniques.tracer.TracingMixin), 414 PluginVendor (class in angr.misc.plugins), 224
 attribute), 414 Pointer (class in angr.analyses.typehoon.typeconsts),
 persistent_id() (angr.vaults.VaultPickler method), 844
 621 Pointer32 (class in angr.analyses.typehoon.typeconsts),
 persistent_load() (angr.vaults.VaultUnpickler 844
 method), 621 Pointer64 (class in angr.analyses.typehoon.typeconsts),
 844
 PhoenixStructurer (class in 844
 angr.analyses.decompiler.structuring.phoenix), pointer_addr (angr.knowledge_plugins.cfg.memory_data.MemoryData
 692 attribute), 546
 PickledState (class in pointer_addr (angr.knowledge_plugins.cfg.MemoryData
 angr.exploration_techniques.spiller_db), attribute), 527
 413 method), 817
 PickledStatesBase (class in pointer_to_atom() (angr.analyses.reaching_definitions.rd_state.Reachin
 angr.exploration_techniques.spiller), 410 method), 787
 PickledStatesDb (class in method), 817
 angr.exploration_techniques.spiller), 411 pointer_to_atoms() (angr.analyses.reaching_definitions.rd_state.Reachi
 PickledStatesList (class in method), 817
 angr.exploration_techniques.spiller), 411 pointer_to_atoms() (angr.analyses.reaching_definitions.ReachingDefini
 PLATFORMS (angr.analyses.decompiler.optimization_passes.base_ptr_save_simplifier.BasePointerSaveSimplifier
 attribute), 707 PointerArithmeticFixer (class in
 PLATFORMS (angr.analyses.decompiler.optimization_passes.const_derived_codegen_plugins.SimplifiedCodegen), 744
 attribute), 704 744
 PLATFORMS (angr.analyses.decompiler.optimization_passes.PointerArithmeticFixer), 744
 attribute), 708 PointerArray (angr.knowledge_plugins.cfg.memory_data.MemoryDataSo
 PLATFORMS (angr.analyses.decompiler.optimization_passes.PointerArray), 744
 attribute), 713 PointerArraySort (angr.knowledge_plugins.cfg.MemoryDataSort
 attribute), 526
 PLATFORMS (angr.analyses.decompiler.optimization_passes.PointerWrapper (angr.knowledge_plugins.cfg.MemoryDataSort), 526
 attribute), 526
 PLATFORMS (angr.analyses.decompiler.optimization_passes.PointerWrapper (angr.knowledge_plugins.cfg.MemoryDataSort), 526
 attribute), 526

PointerWrapper (class in *angr.calling_conventions*), 484
 pop() (*angr.state_plugins.callstack.CallStack* method), 265
 pop() (*angr.state_plugins.globals.SimStateGlobals* method), 279
 pop_from_backup() (*angr.state_plugins.trace_additions.ChallRespInfo* method), 276
 pop_job() (*angr.analyses.cfg.cfg_fast.PendingJobs* method), 653
 pop_n() (*angr.exploration_techniques.spiller.PickledStatesBase* method), 411
 pop_n() (*angr.exploration_techniques.spiller.PickledStatesDb* method), 412
 pop_n() (*angr.exploration_techniques.spiller.PickledStatesList* method), 411
 pop_priv() (*angr.state_plugins.scratch.SimStateScratch* method), 280
 pop_stack_frame() (*angr.storage.memory_mixins.javavm_memory_mixins.JavaVmMemoryMixin* method), 376
 populate() (*angr.sim_manager.SimulationManager* method), 386
 populate() (*angr.SimulationManager* method), 175
 pos (*angr.SimFileBase* attribute), 188
 pos (*angr.storage.file.SimFileBase* attribute), 316
 PositionMapping (class in *angr.analyses.decompiler.structured_codegen.base*), 726
 PositionMappingElement (class in *angr.analyses.decompiler.structured_codegen.base*), 726
 posix (*angr.sim_state.SimState* attribute), 225
 posix (*angr.SimState* attribute), 181
 PosixDevFS (class in *angr.state_plugins.posix*), 240
 PosixProcFS (class in *angr.state_plugins.posix*), 242
 posmap_pos (*angr.analyses.decompiler.structured_codegen.posmap_pos* attribute), 726
 PossibleObject (class in *angr.analyses.find_objects_static*), 855
 post_dom (*angr.utils.graph.PostDominators* property), 897
 POST_FORGOTTEN (*angr.analyses.typehoon.simple_solver.FORGOTTEN* attribute), 834
 PostDominators (class in *angr.utils.graph*), 897
 pp() (*angr.analyses.datagraph_meta.DataGraphMeta* method), 675
 pp() (*angr.analyses.ddg.DDG* method), 752
 pp() (*angr.Block* method), 170
 pp() (*angr.block.Block* method), 221
 pp() (*angr.block.DisassemblerBlock* method), 220
 pp() (*angr.engines.pcode.lifter.IRSB* method), 438
 pp() (*angr.knowledge_plugins.functions.function.Function* method), 563
 pp_constraints() (*angr.analyses.typehoon.typehoon.Typehoon* method), 842
 pp_solution() (*angr.analyses.typehoon.typehoon.Typehoon* method), 842
 pp_str() (*angr.analyses.typehoon.typeconsts.TypeConstant* method), 843
 pp_str() (*angr.analyses.typehoon.typevars.Add* method), 838
 pp_str() (*angr.analyses.typehoon.typevars.DerivedTypeVariable* method), 840
 pp_str() (*angr.analyses.typehoon.typevars.Equivalence* method), 837
 pp_str() (*angr.analyses.typehoon.typevars.Existence* method), 838
 pp_str() (*angr.analyses.typehoon.typevars.Sub* method), 839
 pp_str() (*angr.analyses.typehoon.typevars.Subtype* method), 838
 pp_str() (*angr.analyses.typehoon.typevars.TypeConstraint* method), 839
 pp_str() (*angr.analyses.typehoon.typevars.TypeVariable* method), 839
 PRE_FORGOTTEN (*angr.analyses.typehoon.simple_solver.FORGOTTEN* attribute), 834
 preconstrain() (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 283
 preconstrain_file() (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 283
 preconstrain_flag_page() (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 283
 predecessors (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* property), 548
 predecessors (*angr.knowledge_plugins.cfg.CFGNode* property), 529
 predecessors() (*angr.analyses.forward_analysis.visitors.call_graph.CallGraph* method), 627
 predecessors() (*angr.analyses.forward_analysis.visitors.function_graph.FunctionGraph* method), 627
 predecessors() (*angr.analyses.forward_analysis.visitors.graph.GraphVisitor* method), 628
 predecessors() (*angr.analyses.forward_analysis.visitors.loop.LoopVisitor* method), 630
 predecessors() (*angr.analyses.forward_analysis.visitors.single_node_graph.SingleNodeGraph* method), 631
 predecessors() (*angr.analyses.reaching_definitions.dep_graph.DepGraph* method), 800
 predecessors() (*angr.codenode.CodeNode* method), 883
 predecessors_and_jumpkinds() (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* method), 548
 predecessors_and_jumpkinds() (*angr.knowledge_plugins.cfg.CFGNode* method), 548

`(angr.engines.procedure.ProcedureEngine method)`, 430
`process_successors()`
`(angr.engines.soot.engine.SootMixin method)`, 432
`process_successors()``(angr.engines.syscall.SimEngineSyscall method)`, 431
`process_successors()``(angr.engines.unicorn.SimEngineUnicorn method)`, 433
`ProgramVariable` (class in `angr.analyses.ddg`), 749
`project` (`angr.analyses.analysis.Analysis` attribute), 625
`project` (`angr.analyses.backward_slice.BackwardSlice` attribute), 633
`project` (`angr.analyses.binary_optimizer.BinaryOptimizer` attribute), 870
`project` (`angr.analyses.bindiff.BinDiff` attribute), 636
`project` (`angr.analyses.boyscout.BoyScout` attribute), 636
`project` (`angr.analyses.callee_cleanup_finder.CalleeCleanupFinder` attribute), 870
`project` (`angr.analyses.calling_convention.CallingConvention` attribute), 638
`project` (`angr.analyses.cdg.CDG` attribute), 675
`project` (`angr.analyses.cfg.cfb.CFBlanket` attribute), 642
`project` (`angr.analyses.cfg.cfg_fast.CFGFast` attribute), 660
`project` (`angr.analyses.cfg.cfg_fast_soot.CFGFastSoot` attribute), 675
`project` (`angr.analyses.cfg.indirect_jump_resolvers.jump_target_resolver.IndirectJumpTargetResolver` attribute), 667
`project` (`angr.analyses.class_identifier.ClassIdentifier` attribute), 856
`project` (`angr.analyses.code_tagging.CodeTagging` attribute), 676
`project` (`angr.analyses.complete_calling_conventions.CompleteCallingConventionsAnalysis` attribute), 639
`project` (`angr.analyses.congruency_check.CongruencyCheck` attribute), 868
`project` (`angr.analyses.data_dep.data_dependency_analysis.DataDependencyAnalysis` attribute), 876
`project` (`angr.analyses.ddg.DDG` attribute), 754
`project` (`angr.analyses.decompiler.ail_simplifier.AILSimplifier` attribute), 694
`project` (`angr.analyses.decompiler.block_simplifier.BlockSimplifier` attribute), 695
`project` (`angr.analyses.decompiler.callsite_maker.CallSiteMaker` attribute), 695
`project` (`angr.analyses.decompiler.clinic.Clinic` attribute), 698
`project` (`angr.analyses.decompiler.decompiler.Decompiler` attribute), 701
`project` (`angr.analyses.decompiler.optimization_passes.optimization_pass.OptimizationPass` attribute), 705
`project` (`angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase` attribute), 716
`project` (`angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase` attribute), 715
`project` (`angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimizationBase` attribute), 715
`project` (`angr.analyses.decompiler.region_identifier.RegionIdentifier` attribute), 717
`project` (`angr.analyses.decompiler.region_simplifiers.region_simplifier.RegionSimplifier` attribute), 721
`project` (`angr.analyses.decompiler.structured_codegen.c.CStructuredCodegenC` attribute), 742
`project` (`angr.analyses.decompiler.structured_codegen.dwarf_import.ImportDwarfImport` attribute), 744
`project` (`angr.analyses.decompiler.structuring.phoenix.PhoenixStructurer` attribute), 693
`project` (`angr.analyses.decompiler.structuring.recursive_structurer.RecursiveStructurer` attribute), 686
`project` (`angr.analyses.disassembly.Disassembly` attribute), 859
`project` (`angr.analyses.disassembly.Value` property), 858
`project` (`angr.analyses.dominance_frontier.DominanceFrontier` attribute), 870
`project` (`angr.analyses.find_objects_static.StaticObjectFinder` attribute), 855
`project` (`angr.analyses.flirt.FlirtAnalysis` attribute), 754
`project` (`angr.analyses.identifier.identify.Identifier` attribute), 846
`project` (`angr.analyses.initialization_finder.InitializationFinder` attribute), 871
`project` (`angr.analyses.loop_analysis.LoopAnalysis` attribute), 847
`project` (`angr.analyses.loopfinder.LoopFinder` attribute), 846
`project` (`angr.analyses.propagator.propagator.PropagatorAnalysis` attribute), 761
`project` (`angr.analyses.proximity_graph.ProximityGraphAnalysis` attribute), 874
`project` (`angr.analyses.reaching_definitions.LiveDefinitions` attribute), 762
`project` (`angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions` attribute), 798
`project` (`angr.analyses.reaching_definitions.ReachingDefinitionsAnalysis` attribute), 778
`project` (`angr.analyses.reassembler.Reassembler` attribute), 867
`project` (`angr.analyses.soot_class_hierarchy.SootClassHierarchy` attribute), 641
`project` (`angr.analyses.stack_pointer_tracker.StackPointerTracker` attribute), 823
`project` (`angr.analyses.static_hooker.StaticHooker` attribute), 823

- tribute), 869
- project (angr.analyses.typehoon.typehoon.Typehoon attribute), 843
- project (angr.analyses.variable_recovery.variable_recovery.VariableRecovery attribute), 831
- project (angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase attribute), 825
- project (angr.analyses.variable_recovery.variable_recovery_fast.VariableRecoveryFast attribute), 829
- project (angr.analyses.veritestesting.Veritestesting attribute), 849
- project (angr.analyses.vfg.VFG attribute), 853
- project (angr.analyses.vsa_ddg.VSA_DDG attribute), 854
- project (angr.analyses.vtable.VtableFinder attribute), 855
- project (angr.analyses.xrefs.XRefsAnalysis attribute), 872
- project (angr.Analysis attribute), 178
- project (angr.knowledge_plugins.cfg.cfg_model.CFGModel property), 539
- project (angr.knowledge_plugins.cfg.CFGModel property), 532
- project (angr.knowledge_plugins.functions.function.Function property), 557
- project (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598
- project (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577
- project (angr.procedures.stubs.format_parser.FormatParser attribute), 475
- project (angr.procedures.stubs.format_parser.ScanfFormatParser attribute), 476
- project (angr.sim_procedure.SimProcedure attribute), 472
- Project (class in angr), 163
- Project (class in angr.project), 212
- prop (angr.analyses.decompiler.clinic.BlockCache attribute), 696
- prop_key (angr.analyses.propagator.propagator.PropagatorAnalysis method), 613
- property), 761
- propagations (angr.knowledge_base.knowledge_base.KnowledgeBase attribute), 523
- propagations (angr.KnowledgeBase attribute), 211
- Propagator (angr.analyses.analysis.KnownAnalysesPlugin attribute), 624
- PropagatorAnalysis (class in angr.analyses.propagator.propagator), 760
- prototype (angr.analyses.decompiler.structured_codegen.c.CFunctionCall attribute), 733
- prototype (angr.analyses.reaching_definitions.function_handler.FunctionCallData attribute), 805
- prototype (angr.analyses.reaching_definitions.FunctionCallData attribute), 791
- prototype (angr.knowledge_plugins.functions.function.Function attribute), 556
- prototype (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564
- prototype (angr.procedures.stubs.format_parser.FormatParser attribute), 475
- prototype (angr.procedures.stubs.format_parser.ScanfFormatParser attribute), 476
- prototype (angr.sim_procedure.SimProcedure attribute), 472
- prototype_libname (angr.knowledge_plugins.functions.function.Function attribute), 556
- prototype_libname (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564
- ProximityGraphAnalysis (class in angr.analyses.proximity_graph), 874
- ProxiNodeTypes (class in angr.analyses.proximity_graph), 872
- prune() (angr.sim_manager.SimulationManager method), 386
- prune() (angr.SimulationManager method), 175
- pruned (angr.sim_manager.SimulationManager attribute), 383
- pruned (angr.SimulationManager attribute), 172
- pseudocode (angr.knowledge_plugins.functions.function.Function attribute), 559
- PTChunk (class in angr), 208
- PTChunk (class in angr.state_plugins.heap.heap_ptmalloc), 302
- PTChunkIterator (class in angr.state_plugins.heap.heap_ptmalloc), 304
- pull() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 612
- pull_comment() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 613
- pull_comments() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 613
- pull_function() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 613
- pull_patches() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 614
- pull_stack_variables() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 614
- push() (angr.state_plugins.callstack.CallStack method), 265
- push_comment() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 612
- push_comments() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 613
- push_function() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 612
- push_priv() (angr.state_plugins.scratch.SimStateScratch

method), 280

push_stack_frame() (angr.storage.memory_mixins.jvavm_memory_mixin.method), 376

push_stack_variable() (angr.knowledge_plugins.sync.sync_controller.SyncController.method), 613

push_stack_variables() (angr.knowledge_plugins.sync.sync_controller.SyncController.method), 613

put() (angr.analyses.stack_pointer_tracker.StackPointerTrackerState.method), 822

PutHook (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 669

ReachingDefinitions (class in angr.analyses.reaching_definitions), 775

ReachingDefinitionsAnalysis (class in angr.analyses.reaching_definitions), 775

ReachingDefinitionsModel (class in angr.analyses.reaching_definitions), 778

ReachingDefinitionsModel (class in angr.knowledge_plugins.key_definitions), 574

ReachingDefinitionsModel (class in angr.knowledge_plugins.key_definitions.rd_model), 606

ReachingDefinitionsState (class in angr.analyses.reaching_definitions), 780

ReachingDefinitionsState (class in angr.analyses.reaching_definitions.rd_state), 809

READ (angr.knowledge_plugins.variables.variable_access.VariableAccess.attribute), 564

Read (angr.knowledge_plugins.xrefs.xref_types.XRefType.attribute), 615

read() (angr.SimFile method), 190

read() (angr.SimFileBase method), 189

read() (angr.SimFileStream method), 194

read() (angr.SimPackets method), 192

read() (angr.SimPacketsStream method), 196

read() (angr.storage.file.SimFile method), 317

read() (angr.storage.file.SimFileBase method), 316

read() (angr.storage.file.SimFileDescriptorBase method), 325

read() (angr.storage.file.SimFileStream method), 319

read() (angr.storage.file.SimPackets method), 321

read() (angr.storage.file.SimPacketsSlots method), 332

read() (angr.storage.file.SimPacketsStream method), 323

read_data() (angr.SimFileDescriptor method), 198

read_data() (angr.SimFileDescriptorDuplex method), 200

read_data() (angr.storage.file.SimFileDescriptor method), 327

read_data() (angr.storage.file.SimFileDescriptorBase method), 325

read_data() (angr.storage.file.SimFileDescriptorDuplex method), 329

read_from() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 566

read_msr() (angr.state_plugins.unicorn_engine.UnicornEngine method), 290

qualifies_for_implicit_cast() (in module angr.analyses.decompiler.structured_codegen.c), 727

qualifies_for_simple_cast() (in module angr.analyses.decompiler.structured_codegen.c), 727

quasi_topological_sort_nodes() (angr.utils.graph.GraphUtils static method), 898

query() (angr.knowledge_plugins.functions.function_manager.FunctionManager.method), 554

R

ran_cca (angr.knowledge_plugins.functions.function.Function attribute), 556

ran_cca (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564

RANDOM (angr.simos.windows.SecurityCookieInit attribute), 888

randomize_procedures() (angr.analyses.reassembler.Reassembler method), 867

rd (angr.analyses.decompiler.clinic.BlockCache attribute), 696

rda_observe_callback() (angr.knowledge_plugins.key_definitions.key_definition_manager.RDAObserverControl method), 596

RDAObserverControl (class in angr.knowledge_plugins.key_definitions.key_definition_manager), 596

reachable() (angr.state_plugins.history.SimStateHistory method), 269

reached_fixedpoint() (angr.analyses.forward_analysis.visitors.graph.GraphVisitor method), 630

reaching_condition (angr.analyses.decompiler.structuring.structurer_nodes.CodeNode attribute), 688

reaching_condition (angr.analyses.decompiler.structuring.structurer_nodes.ConditionNode attribute), 688

[read_pos \(angr.SimFileDescriptor property\)](#), 199
[read_pos \(angr.SimFileDescriptorDuplex property\)](#), 201
[read_pos \(angr.storage.file.SimFileDescriptor property\)](#), 328
[read_pos \(angr.storage.file.SimFileDescriptorBase property\)](#), 326
[read_pos \(angr.storage.file.SimFileDescriptorDuplex property\)](#), 330
[read_storage \(angr.SimFileDescriptor property\)](#), 199
[read_storage \(angr.SimFileDescriptorDuplex property\)](#), 201
[read_storage \(angr.storage.file.SimFileDescriptor property\)](#), 328
[read_storage \(angr.storage.file.SimFileDescriptorBase property\)](#), 326
[read_storage \(angr.storage.file.SimFileDescriptorDuplex property\)](#), 330
[real_args \(angr.calling_conventions.UsercallArgSession attribute\)](#), 489
[real_length\(\) \(angr.utils.dynamic_dictlist.DynamicDictList method\)](#), 895
[realloc\(\) \(angr.SimHeapPTMalloc method\)](#), 207
[realloc\(\) \(angr.state_plugins.heap.heap_libc.SimHeapLibc method\)](#), 302
[realloc\(\) \(angr.state_plugins.heap.heap_ptmalloc.SimHeapPtmalloc method\)](#), 305
[reapply_options\(\) \(angr.analyses.decompiler.structured_codegen.BaseBaseStructuredCodeGenerator method\)](#), 727
[reapply_options\(\) \(angr.analyses.decompiler.structured_codegen.CStructuralCodeGenerator method\)](#), 742
[Reassembler \(angr.analyses.analysis.KnownAnalysesPlugin attribute\)](#), 623
[Reassembler \(class in angr.analyses.reassembler\)](#), 865
[ReassemblerFailureNotice](#), 860
[rebuild_callgraph\(\) \(angr.knowledge_plugins.functions.function_manager.FunctionManager method\)](#), 555
[recall\(\) \(angr.analyses.typehoon.simple_solver.ConstraintRefinement method\)](#), 835
[recent_actions \(angr.state_plugins.history.SimStateHistory property\)](#), 269
[recent_constraints \(angr.state_plugins.history.SimStateHistory property\)](#), 269
[reconstrain\(\) \(angr.state_plugins.preconstrainer.SimStatePreconstrainer method\)](#), 284
[record_state\(\) \(angr.errors.SimError method\)](#), 905
[record_variable\(\) \(angr.knowledge_plugins.variables.variable_manager.VariableManager method\)](#), 566
[recover_edge_condition\(\) \(angr.analyses.decompiler.condition_processor.ConditionProcessor method\)](#), 698
[recover_edge_conditions\(\) \(angr.analyses.decompiler.condition_processor.ConditionProcessor method\)](#), 698
[recover_reaching_conditions\(\) \(angr.analyses.decompiler.condition_processor.ConditionProcessor method\)](#), 698
[recurse_analysis\(\) \(angr.analyses.reaching_definitions.function_handler.FunctionHandler method\)](#), 808
[recurse_analysis\(\) \(angr.analyses.reaching_definitions.FunctionHandler method\)](#), 789
[recursive_copy\(\) \(angr.analyses.decompiler.graph_region.GraphRegion method\)](#), 703
[RecursiveRefNode \(class in angr.analyses.typehoon.simple_solver\)](#), 833
[RecursiveStructurer \(class in angr.analyses.decompiler.structuring.recursive_structurer\)](#), 686
[recv\(\) \(angr.storage.pcap.PCAP method\)](#), 335
[redefine_locals \(angr.analyses.reaching_definitions.function_handler.FunctionHandler attribute\)](#), 805
[redefine_locals \(angr.analyses.reaching_definitions.FunctionCallData attribute\)](#), 791
[RedundantLabelRemover \(class in angr.analyses.decompiler.redundant_label_remover\)](#), 725
[RedundantStackVariable \(class in angr.analyses.binary_optimizer\)](#), 869
[RefCountMixin \(class in angr.storage.memory_mixins.paged_memory.pages.refcount_mixin\)](#), 859
[BaseBaseStructuredCodeGenerator
REFERENCE \(angr.knowledge_plugins.variables.variable_access.VariableAccess attribute\)
reference_at\(\) \(angr.knowledge_plugins.variables.variable_manager.VariableManager method\), 566
reference_size \(angr.knowledge_plugins.cfg.memory_data.MemoryData attribute\), 546
reference_size \(angr.knowledge_plugins.cfg.MemoryData attribute\), 527
reference_values \(angr.analyses.decompiler.structured_codegen.c.CConstant attribute\), 739
register_argument \(angr.calling_conventions.SimFunctionArgument method\), 486
refine\(\) \(angr.calling_conventions.SimLyingRegArg method\), 492
refine\(\) \(angr.calling_conventions.SimRegArg method\), 486
refine\(\) \(angr.calling_conventions.SimStackArg method\), 487
refine_locs_with_struct_type\(\) \(in module angr.analyses.decompiler.structuring.recursive_structurer\), 701
reflow_variable_types\(\) \(angr.analyses.decompiler.decompiler.Decompiler method\), 701
reg \(angr.analyses.decompiler.structured_codegen.c.CRegister attribute\), 739
reg \(angr.analyses.decompiler.stack_pointer_tracker.OffsetVal property\), 821](#)

reg (an ^{gr} .engines.light.data.RegisterOffset attribute), 755	RegionedMemory (class in an ^{gr} .storage.memory_mixins), 339
reg (an ^{gr} .sim_variable.SimRegisterVariable attribute), 506	RegionedMemoryMixin (class in an ^{gr} .storage.memory_mixins.regioned_memory.regioned_memory), 365
REG (an ^{gr} .state_plugins.sim_action.SimAction attribute), 467	RegionIdentifier (class in an ^{gr} .analyses.decompiler.region_identifier), 716
reg() (an ^{gr} .analyses.reaching_definitions.Atom static method), 771	RegionMap (class in an ^{gr} .storage.memory_mixins.regioned_memory.regioned_memory), 369
reg() (an ^{gr} .knowledge_plugins.key_definitions.atoms.Atom static method), 589	RegionObject (class in an ^{gr} .keyed_region), 618
reg_concrete() (an ^{gr} .sim_state.SimState method), 227	regions (an ^{gr} .analyses.cfg.cfb.CFBlanket property), 641
reg_concrete() (an ^{gr} .SimState method), 183	RegionSimplifier (class in an ^{gr} .analyses.decompiler.region_simplifiers.region_simplifier), 725
reg_deps (an ^{gr} .state_plugins.sim_action.SimAction property), 467	RegionWalker (class in an ^{gr} .analyses.decompiler.region_walker), 725
reg_deps (an ^{gr} .state_plugins.sim_action.SimActionData property), 468	Register (an ^{gr} .analyses.data_dep.dep_nodes.DepNodeTypes attribute), 877
reg_name (an ^{gr} .knowledge_plugins.key_definitions.definition.Definition attribute), 593	Register (an ^{gr} .analyses.disassembly.RegisterOperand property), 858
reg_offset (an ^{gr} .analyses.cfg.indirect_jump_resolvers.jumptable.RegOffset attribute), 668	REGISTER (an ^{gr} .analyses.reaching_definitions.AtomKind attribute), 770
reg_offset (an ^{gr} .analyses.reaching_definitions.Register attribute), 772	REGISTER (an ^{gr} .knowledge_plugins.key_definitions.atoms.AtomKind attribute), 588
reg_offset (an ^{gr} .knowledge_plugins.key_definitions.atoms.RegOffset attribute), 591	REGISTER (an ^{gr} .knowledge_plugins.variables.variable_manager.VariableType attribute), 565
reg_read_callback() (an ^{gr} .analyses.cfg.indirect_jump_resolvers.jumptable.ConstantValueManager method), 667	Register (class in an ^{gr} .analyses.disassembly), 858
reg_size (an ^{gr} .analyses.data_dep.dep_nodes.RegDepNode property), 879	Register (class in an ^{gr} .analyses.reaching_definitions), 772
RegDepNode (class in an ^{gr} .analyses.data_dep.dep_nodes), 879	Register (class in an ^{gr} .analyses.reaching_definitions), 772
regenerate_text() (an ^{gr} .analyses.decompiler.structured_codegen.StructuredCodeGenerator method), 727	Register (class in an ^{gr} .analyses.reaching_definitions), 772
regenerate_text() (an ^{gr} .analyses.decompiler.structured_codegen.StructuredCodeGenerator method), 742	Register (class in an ^{gr} .analyses.reaching_definitions), 772
regenerate_text() (an ^{gr} .analyses.decompiler.structured_codegen.StructuredCodeGenerator method), 744	Register (class in an ^{gr} .analyses.reaching_definitions), 772
region (an ^{gr} .sim_variable.SimVariable attribute), 504	Register (class in an ^{gr} .analyses.reaching_definitions), 772
region (an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper attribute), 369	Register (class in an ^{gr} .analyses.reaching_definitions), 772
region_base_addr (an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper attribute), 369	Register (class in an ^{gr} .analyses.reaching_definitions), 772
region_id (an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper attribute), 369	Register (class in an ^{gr} .analyses.reaching_definitions), 772
region_ids (an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper property), 370	Register (class in an ^{gr} .analyses.reaching_definitions), 772
RegionCategoryMixin (class in an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper), 370	Register (class in an ^{gr} .analyses.reaching_definitions), 772
RegionDescriptor (class in an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper), 369	Register (class in an ^{gr} .analyses.reaching_definitions), 772
RegionedAddressConcretizationMixin (class in an ^{gr} .storage.memory_mixins.regioned_memory.region_data.AddressWrapper), 369	Register (class in an ^{gr} .analyses.reaching_definitions), 772

static method), 525

register_default() (angr.misc.plugins.PluginHub class method), 222

register_default() (angr.SimStatePlugin class method), 162

register_default() (angr.state_plugins.plugin.SimStatePlugin attribute), 598

register_default() (class method), 233

register_default_cc() (in module angr.calling_conventions), 503

register_definitions (angr.analyses.reaching_definitions.LiveDefinitions property), 762

register_definitions (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions property), 599

register_definitions (angr.knowledge_plugins.key_definitions.LiveDefinitions property), 578

register_function_analysis() (angr.analyses.vfg.CallAnalysis method), 851

register_instruction_reference() (angr.analyses.reassembler.Reassembler method), 866

register_kernel_types() (in module angr.utils.library), 900

register_optimization_pass() (in module angr.analyses.decompiler.optimization_passes), 704

register_option() (angr.sim_state_options.SimStateOptions class method), 231

register_pcode_arch_default_cc() (in module angr.engines.pcode.cc), 466

register_plugin() (angr.knowledge_base.knowledge_base.KnowledgeBase method), 523

register_plugin() (angr.KnowledgeBase method), 211

register_plugin() (angr.misc.plugins.PluginHub method), 223

register_plugin() (angr.misc.plugins.PluginVendor method), 224

register_plugin() (angr.sim_state.SimState method), 226

register_plugin() (angr.SimState method), 182

register_preset() (angr.misc.plugins.PluginHub class method), 222

register_region (angr.knowledge_plugins.variables.variable_manager.VariableManager attribute), 565

register_simos() (in module angr.simos), 884

register_syscall_cc() (in module angr.calling_conventions), 504

register_types() (in module angr.sim_type), 520

register_uses (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

register_uses (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions attribute), 813

register_uses (angr.analyses.reaching_definitions.ReachingDefinitionsState attribute), 783

register_uses (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

register_uses (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

register_values (angr.state_plugins.unicorn_engine.BlockDetails attribute), 285

register_values_count (angr.state_plugins.unicorn_engine.BlockDetails attribute), 285

register_variables() (angr.state_plugins.solver.SimSolver method), 255

RegisterInitializerHook (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 669

RegisterOffset (class in angr.engines.light.data), 755

RegisterOperand (class in angr.analyses.disassembly), 858

RegisterReallocation (class in angr.analyses.binary_optimizer), 869

registers (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

registers (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions attribute), 813

registers (angr.analyses.reaching_definitions.ReachingDefinitionsState attribute), 783

registers (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

registers (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

registers (angr.sim_state.SimState attribute), 225

registers (angr.SimState attribute), 181

registers_read_afterwards (angr.knowledge_plugins.functions.function.Function attribute), 556

registers_read_afterwards (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564

RegisterSaveAreaSimplifier (class in angr.analyses.decompiler.optimization_passes.register_save_area), 713

RegisterValue (class in angr.knowledge_plugins.unicorn_engine), 285

RegOffsetAnnotation (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 668

regs (angr.analyses.stack_pointer_tracker.FrozenStackPointerTrackerState attribute), 821

regs (angr.analyses.stack_pointer_tracker.StackPointerTrackerState attribute), 822

regs (*angr.sim_state.SimState* attribute), 225
 regs (*angr.SimState* attribute), 181
 regs (*angr.slicer.SimLightState* attribute), 880
 regs_to_initialize (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableProcessorState* attribute), 668
 rehook_symbol() (*angr.Project* method), 166
 rehook_symbol() (*angr.project.Project* method), 216
 ReinterpretAs (class in *angr.analyses.typehoon.typevars*), 841
 related_function_addr (*angr.storage.memory_mixins.regioned_memory.region_metadata.RegionMetadata* property), 372
 related_function_address (*angr.storage.memory_mixins.regioned_memory.region_data.RegionData* attribute), 369
 relativize() (*angr.storage.memory_mixins.regioned_memory.RegionMemory* method), 370
 release() (*angr.SimHeapBrk* method), 205
 release() (*angr.state_plugins.heap.heap_brk.SimHeapBrk* method), 299
 release_plugin() (*angr.knowledge_base.knowledge_base.KnowledgeBase* method), 523
 release_plugin() (*angr.KnowledgeBase* method), 211
 release_plugin() (*angr.misc.plugins.PluginHub* method), 223
 release_plugin() (*angr.misc.plugins.PluginVendor* method), 224
 release_shared() (*angr.storage.memory_mixins.paged_memory.PageBasedMemory* method), 360
 reload_analyses() (*angr.analyses.analysis.AnalysesHub* method), 623
 reload_format() (*angr.analyses.disassembly.Instruction* method), 857
 reload_solver() (*angr.state_plugins.solver.SimSolver* method), 254
 reload_variable_types() (*angr.analyses.decompiler.structured_codegen.base.BaseStructuredCodeGenerator* method), 727
 reload_variable_types() (*angr.analyses.decompiler.structured_codegen.c.CStructuredCodeGenerator* method), 742
 relocatable (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.RegionMetadata* property), 668
 relocatable (*angr.analyses.data_dep.data_dependency_analysis.DataDependencyAnalysis* property), 875
 relocatable (*angr.analyses.variable_recovery.annotations.SimPreconstrainer* property), 823
 relocatable (*angr.analyses.variable_recovery.annotations.VariableRecoveryAnnotation* property), 823
 relocatable (*angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBaseAnnotation* property), 824
 relocatable (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* property), 597
 relocateable (*angr.storage.memory_mixins.address_concretization.AddressConcretization* method), 668
 property), 344
 Relocation (class in *angr.analyses.reassembler*), 865
 relocations (*angr.analyses.reassembler.Reassembler* property), 865
 remove() (*angr.sim_state_options.SimStateOptions* method), 230
 remove_breakpoint() (*angr.state_plugins.inspect.SimInspector* method), 234
 remove_cgc_attachments() (*angr.solvers.Solver* method), 867
 remove_claripy_bool_ast() (*angr.analyses.cfg.compiler.condition_processor.ConditionProcessor* method), 698
 remove_cyless_region_map() (*angr.analyses.cfg.cfg_emulated.CFGEmulated* method), 647
 remove_edge() (*angr.analyses.cfg.cfg_base.CFGBase* method), 651
 remove_empty_nodes() (*angr.analyses.decompiler.clinic.Clinic* static method), 698
 remove_fakerets() (*angr.analyses.cfg.cfg_emulated.CFGEmulated* method), 648
 remove_instruction() (*angr.analyses.reassembler.Reassembler* method), 867
 remove_labels() (*angr.analyses.decompiler.utils* module), 746
 remove_last_statement() (in *angr.analyses.decompiler.utils* module), 745
 remove_node() (*angr.analyses.decompiler.structuring.structurer_nodes.StructurerNodes* method), 687
 remove_node() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 540
 remove_node() (*angr.knowledge_plugins.cfg.CFGModel* method), 540
 remove_node_and_graph_node() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 537
 remove_node_and_graph_node() (*angr.knowledge_plugins.cfg.CFGModel* method), 537
 remove_node_and_graph_node() (*angr.knowledge_plugins.patches.PatchManager* method), 524
 remove_preconstraints() (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 824
 remove_technique() (*angr.sim_manager.SimulationManager* method), 184
 remove_technique() (*angr.SimulationManager* method), 184
 remove_types() (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 668
 remove_write_annotation() (*angr.knowledge_plugins.variables.variable_manager.VariableManager* method), 668

remove_unnecessary_stuff() (angr.analyses.reassembler.Reassembler method), 867
 remove_unnecessary_stuff_glibc() (angr.analyses.reassembler.Reassembler method), 867
 remove_use() (angr.knowledge_plugins.key_definitions.Uses method), 586
 remove_use() (angr.knowledge_plugins.key_definitions.uses.Uses method), 610
 remove_uses() (angr.knowledge_plugins.key_definitions.Uses method), 586
 remove_uses() (angr.knowledge_plugins.key_definitions.uses.Uses method), 611
 remove_variable() (angr.analyses.decompiler.optimization_replacements.angr.SimplifierPluginState.propagator.PropagatorAnalysis method), 712
 remove_variable_by_atom() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 566
 RemoveNodeNotice, 694
 rename() (angr.knowledge_plugins.types.TypesStore method), 552
 renamed (angr.sim_variable.SimVariable attribute), 504
 render() (angr.analyses.disassembly.Disassembly method), 859
 render() (angr.analyses.disassembly.DisassemblyPiece method), 856
 render_text() (angr.analyses.decompiler.structured_codegen.c.CStructuralCodeGenerator method), 742
 RENDER_TYPE (angr.analyses.decompiler.structured_codegen.c.CStructuralCodeGenerator attribute), 742
 RepHook (class in angr.exploration_techniques.tracer), 414
 replace() (angr.analyses.typehoon.typevars.Add method), 839
 replace() (angr.analyses.typehoon.typevars.DerivedTypeVariable method), 840
 replace() (angr.analyses.typehoon.typevars.Existence method), 838
 replace() (angr.analyses.typehoon.typevars.Sub method), 839
 replace() (angr.analyses.typehoon.typevars.Subtype method), 838
 replace() (angr.keyed_region.KeyedRegion method), 619
 replace() (angr.procedures.stubs.format_parser.FormatString method), 474
 replace_all() (angr.storage.memory_mixins.convenient_mappings.mixin.ConvenientMappingsMixin method), 348
 replace_all() (angr.storage.memory_mixins.MemoryMixin method), 338
 replace_all() (angr.storage.memory_mixins.regioned_memory.regioned_memory.mixin.RegionedMemoryMixin method), 367
 replace_all_with_offsets() (angr.storage.memory_mixins.paged_memory.pages.ultra_page.UltraPage method), 365
 replace_last_statement() (in module angr.analyses.decompiler.utils), 745
 replace_node_in_node() (angr.analyses.decompiler.structuring.structurer_base.StructurerBase static method), 692
 replace_nodes() (angr.analyses.decompiler.structuring.structurer_base.StructurerBase static method), 692
 replace_region() (angr.analyses.decompiler.graph_region.GraphRegion method), 703
 replace_region_with_region() (angr.analyses.decompiler.graph_region.GraphRegion method), 703
 replacements (angr.SimplifierPluginState property), 761
 report() (angr.exploration_techniques.Suggestions static method), 498
 report() (angr.exploration_techniques.suggestions.Suggestions static method), 427
 repr_addr() (in module angr.codenode), 882
 request_knowledge() (angr.knowledge_base.knowledge_base.KnowledgeBase method), 524
 request_knowledge() (angr.KnowledgeBase method), 212
 request_plugin() (angr.misc.plugins.PluginPreset method), 331
 REQUIRE_CFG_STATES (angr.exploration_techniques.CallFunctionGoal attribute), 418
 REQUIRE_CFG_STATES (angr.exploration_techniques.director.BaseGoal attribute), 418
 REQUIRE_CFG_STATES (angr.exploration_techniques.director.CallFunctionGoal attribute), 419
 REQUIRE_DATA_C (angr.engines.pcode.lifter.Lifter attribute), 440
 REQUIRE_DATA_PY (angr.engines.pcode.lifter.Lifter attribute), 440
 reraise() (angr.sim_manager.ErrorRecord method), 389
 reset() (angr.analyses.forward_analysis.visitors.graph.GraphVisitor method), 629
 reset() (angr.analyses.forward_analysis.visitors.single_node_graph.SingleNodeGraph method), 631
 reset() (angr.state_plugins.unicorn_engine.Uniwrapper method), 288
 reset_initial_regs() (angr.Block static method), 170
 reset_initial_regs() (angr.block.Block static method), 221
 reset_prototype() (angr.analyses.reaching_definitions.function_handler.FunctionHandler method), 806
 reset_prototype() (angr.analyses.reaching_definitions.FunctionCallData static method), 792

reset_uses() (angr.analyses.reaching_definitions.LiveDefinitions method), 763
 reset_uses() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 599
 reset_uses() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 578
 resolvable (angr.state_plugins.debug_variables.SimDebugVariable property), 308
 resolvable (angr.state_plugins.view.SimMemView property), 314
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.amd64_elf_got.AMD64ElfGotResolver method), 662
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.arm_elf_fast.ArmElfFastResolver method), 663
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.const_resolver.ConstantResolver method), 671
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTableResolver method), 671
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.mips_elf_fast.MipsElfFastResolver method), 664
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.resolver.IndirectJumpResolver method), 672
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic.X86ElfPicResolver method), 665
 resolve() (angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat.X86PeIatResolver method), 663
 resolve_abstract_dispatch() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641
 resolve_concrete_dispatch() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641
 resolve_invoke() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641
 resolve_register() (angr.state_plugins.light_registers.SimLightRegisters method), 267
 resolve_special_dispatch() (angr.analyses.soot_class_hierarchy.SootClassHierarchy method), 641
 resolved (angr.state_plugins.debug_variables.SimDebugVariable property), 308
 resolved (angr.state_plugins.view.SimMemView property), 314
 resolved_indirect_jumps (angr.knowledge_base.knowledge_base.KnowledgeBase property), 523
 resolved_indirect_jumps (angr.KnowledgeBase property), 211
 resolved_targets (angr.knowledge_plugins.cfg.indirect_jump.IndirectJump attribute), 551
 resolved_targets (angr.knowledge_plugins.cfg.IndirectJump attribute), 532
 resource_event() (in module angr.state_plugins.sim_event), 469
 restore_graph() (angr.analyses.decompiler.optimization_passes.lowered static method), 710
 ret_addr (angr.analyses.decompiler.ccall_rewriters.rewriter_base.CCallRewriter attribute), 695
 ret_addr (angr.analyses.cfg.cfg_emulated.CFGEmulated method), 646
 ret_addr_with_new_graph() (angr.analyses.forward_analysis.visitors.function_graph.FunctionGraph method), 627
 resymbolize() (angr.state_plugins.symbolizer.SimSymbolizer method), 627
 ret() (angr.sim_procedure.SimProcedure method), 473
 ret() (angr.state_plugins.callstack.CallStack method), 160
 ret_addr (angr.analyses.cfg.cfg_fast.FunctionCallEdge attribute), 666
 ret_atoms (angr.analyses.reaching_definitions.function_handler.FunctionHandler method), 666
 ret_atoms (angr.analyses.reaching_definitions.FunctionCallData attribute), 666
 ret_defns (angr.analyses.reaching_definitions.dep_graph.FunctionCallData attribute), 666
 ret_errno() (angr.state_plugins.libc.SimStateLibc method), 666
 ret_expr (angr.analyses.decompiler.structured_codegen.c.CFunctionCall attribute), 733
 ret_from_addr (angr.analyses.cfg.cfg_fast.FunctionReturnEdge attribute), 655
 ret_sites (angr.knowledge_plugins.functions.function.Function property), 559
 ret_target (angr.analyses.cfg.cfg_fast.CFGJob attribute), 656
 ret_to_addr (angr.analyses.cfg.cfg_fast.FunctionReturnEdge attribute), 655
 ret_values (angr.analyses.reaching_definitions.function_handler.FunctionHandler attribute), 805
 ret_values (angr.analyses.reaching_definitions.FunctionCallData attribute), 791
 ret_values_deps (angr.analyses.reaching_definitions.function_handler.FunctionHandler attribute), 805
 ret_values_deps (angr.analyses.reaching_definitions.FunctionCallData attribute), 791
 retaddr_on_stack (angr.knowledge_plugins.functions.function.Function attribute), 556
 retaddr_on_stack (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564
 retaddr_popped (angr.analyses.reaching_definitions.function_handler.FunctionHandler attribute), 805
 retaddr_popped (angr.analyses.reaching_definitions.FunctionCallData attribute), 791
 RetAddrSaveSimplifier (class in angr.analyses.decompiler.optimization_passes.ret_addr_save_simplifier module), 714

`retout_sites` (`angr.knowledge_plugins.functions.function` attribute), 559
`RETURN_ADDR` (`angr.calling_conventions.SimCC` attribute), 489
`return_addr` (`angr.calling_conventions.SimCC` property), 490
`RETURN_ADDR` (`angr.calling_conventions.SimCCArch64LinuxSyscall` attribute), 498
`RETURN_ADDR` (`angr.calling_conventions.SimCCArch64LinuxSyscall` attribute), 498
`RETURN_ADDR` (`angr.calling_conventions.SimCCAMD64LinuxSyscall` attribute), 496
`RETURN_ADDR` (`angr.calling_conventions.SimCCAMD64WindowsSyscall` attribute), 497
`RETURN_ADDR` (`angr.calling_conventions.SimCCARM` attribute), 497
`RETURN_ADDR` (`angr.calling_conventions.SimCCARMHF` attribute), 497
`RETURN_ADDR` (`angr.calling_conventions.SimCCARMLinuxSyscall` attribute), 498
`RETURN_ADDR` (`angr.calling_conventions.SimCCCdecl` attribute), 493
`RETURN_ADDR` (`angr.calling_conventions.SimCCMicrosoftAMD64LinuxSyscall` attribute), 494
`RETURN_ADDR` (`angr.calling_conventions.SimCCMicrosoftFastcall` attribute), 494
`RETURN_ADDR` (`angr.calling_conventions.SimCCN64LinuxSyscall` attribute), 500
`RETURN_ADDR` (`angr.calling_conventions.SimCCN64LinuxSyscall` attribute), 500
`RETURN_ADDR` (`angr.calling_conventions.SimCCO32LinuxSyscall` attribute), 499
`RETURN_ADDR` (`angr.calling_conventions.SimCCO32LinuxSyscall` attribute), 499
`RETURN_ADDR` (`angr.calling_conventions.SimCCPowerPC` attribute), 501
`RETURN_ADDR` (`angr.calling_conventions.SimCCPowerPC64LinuxSyscall` attribute), 501
`RETURN_ADDR` (`angr.calling_conventions.SimCCPowerPC64LinuxSyscall` attribute), 502
`RETURN_ADDR` (`angr.calling_conventions.SimCCPowerPCLinuxSyscall` attribute), 501
`RETURN_ADDR` (`angr.calling_conventions.SimCCRISCV64LinuxSyscall` attribute), 499
`RETURN_ADDR` (`angr.calling_conventions.SimCCS390X` attribute), 503
`RETURN_ADDR` (`angr.calling_conventions.SimCCS390XLinuxSyscall` attribute), 503
`RETURN_ADDR` (`angr.calling_conventions.SimCCS390XLinuxSyscall` attribute), 503
`RETURN_ADDR` (`angr.calling_conventions.SimCCSystemVAMD64LinuxSyscall` attribute), 496
`RETURN_ADDR` (`angr.calling_conventions.SimCCX86LinuxSyscall` attribute), 495
`RETURN_ADDR` (`angr.calling_conventions.SimCCX86WindowsSyscall` attribute), 495
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCM68k` attribute), 465
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCPARISC` attribute), 466
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCPowerPC` attribute), 466
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCRISCV` attribute), 465
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCSH4` attribute), 465
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCSPARC` attribute), 465
`RETURN_ADDR` (`angr.engines.pcode.cc.SimCCXtensa` attribute), 466
`RETURN_ADDR` (`angr.SimCC` attribute), 185
`return_addr` (`angr.SimCC` property), 186
`return_in_implicit_outparam()` (`angr.calling_conventions.SimCC` method), 490
`return_in_implicit_outparam()` (`angr.calling_conventions.SimCCCdecl` method), 493
`return_in_implicit_outparam()` (`angr.calling_conventions.SimCCMicrosoftAMD64LinuxSyscall` method), 494
`return_in_implicit_outparam()` (`angr.calling_conventions.SimCCMicrosoftFastcall` method), 494
`return_in_implicit_outparam()` (`angr.calling_conventions.SimCCSystemVAMD64LinuxSyscall` method), 496
`return_in_implicit_outparam()` (`angr.SimCC` method), 186
`return_target` (`angr.knowledge_plugins.cfg.cfg_node.CFGNode` attribute), 550
`return_target` (`angr.knowledge_plugins.cfg.CFGNode` attribute), 530
`return_to` (`angr.analyses.cfg.cfg_fast.FunctionReturn` attribute), 652
`return_type` (`angr.sim_procedure.SimProcedure` property), 474
`return_type` (`angr.SimProcedure` property), 161
`RETURN_VAL` (`angr.calling_conventions.SimCC` attribute), 489
`RETURN_VAL` (`angr.calling_conventions.SimCCArch64LinuxSyscall` attribute), 498
`RETURN_VAL` (`angr.calling_conventions.SimCCArch64LinuxSyscall` attribute), 498
`RETURN_VAL` (`angr.calling_conventions.SimCCAMD64LinuxSyscall` attribute), 496
`RETURN_VAL` (`angr.calling_conventions.SimCCAMD64WindowsSyscall` attribute), 497
`RETURN_VAL` (`angr.calling_conventions.SimCCARM` attribute), 497
`RETURN_VAL` (`angr.calling_conventions.SimCCARMHF` attribute), 497
`RETURN_VAL` (`angr.calling_conventions.SimCCARMLinuxSyscall` attribute), 497

attribute), 498
 RETURN_VAL (angr.calling_conventions.SimCCCdecl attribute), 493
 RETURN_VAL (angr.calling_conventions.SimCCMicrosoftAMD64 attribute), 494
 RETURN_VAL (angr.calling_conventions.SimCCMicrosoftFastcall attribute), 494
 RETURN_VAL (angr.calling_conventions.SimCCN64 attribute), 500
 RETURN_VAL (angr.calling_conventions.SimCCN64LinuxSyscall attribute), 500
 RETURN_VAL (angr.calling_conventions.SimCCO32 attribute), 499
 RETURN_VAL (angr.calling_conventions.SimCCO32LinuxSyscall attribute), 499
 RETURN_VAL (angr.calling_conventions.SimCCPowerPC attribute), 501
 RETURN_VAL (angr.calling_conventions.SimCCPowerPC64 attribute), 501
 RETURN_VAL (angr.calling_conventions.SimCCPowerPC64LinuxSyscall attribute), 502
 RETURN_VAL (angr.calling_conventions.SimCCPowerPCLinuxSyscall attribute), 501
 RETURN_VAL (angr.calling_conventions.SimCCRISCV64LinuxSyscall attribute), 499
 RETURN_VAL (angr.calling_conventions.SimCCS390X attribute), 503
 RETURN_VAL (angr.calling_conventions.SimCCS390XLinuxSyscall attribute), 503
 RETURN_VAL (angr.calling_conventions.SimCCSystemVAMD64 attribute), 496
 RETURN_VAL (angr.calling_conventions.SimCCX86LinuxSyscall attribute), 495
 RETURN_VAL (angr.calling_conventions.SimCCX86WindowsSyscall attribute), 495
 RETURN_VAL (angr.engines.pcode.cc.SimCCM68k attribute), 465
 RETURN_VAL (angr.engines.pcode.cc.SimCCPARISC attribute), 466
 RETURN_VAL (angr.engines.pcode.cc.SimCCPowerPC attribute), 466
 RETURN_VAL (angr.engines.pcode.cc.SimCCRISCV attribute), 465
 RETURN_VAL (angr.engines.pcode.cc.SimCCSH4 attribute), 465
 RETURN_VAL (angr.engines.pcode.cc.SimCCSPARC attribute), 465
 RETURN_VAL (angr.engines.pcode.cc.SimCCXtensa attribute), 466
 RETURN_VAL (angr.SimCC attribute), 185
 return_val() (angr.calling_conventions.SimCC method), 490
 return_val() (angr.calling_conventions.SimCCCdecl method), 493
 return_val() (angr.calling_conventions.SimCCSystemVAMD64 method), 496
 return_val() (angr.calling_conventions.SimCCUsercall method), 493
 return_val() (angr.SimCC method), 186
 returning (angr.analyses.decompiler.structured_codegen.c.CFunctionCall attribute), 733
 returning (angr.knowledge_plugins.functions.function.Function property), 557
 returning_source (angr.analyses.cfg.cfg_fast.CFGJob attribute), 656
 returnty (angr.sim_type.SimTypeCppFunction attribute), 516
 ReturnValueTag (class in angr.knowledge_plugins.key_definitions.tag), 609
 retval (angr.analyses.decompiler.structured_codegen.c.CReturn attribute), 733
 reverse_post_order_sort_nodes() (angr.utils.graph.GraphUtils static method), 898
 reverse_post_order_sort_nodes() (angr.analyses.forward_analysis.visitors.graph.GraphVisitor method), 630
 reverse_post_order_sort_nodes() (angr.analyses.forward_analysis.visitors.graph.GraphVisitor method), 629
 rhs (angr.analyses.decompiler.structured_codegen.c.CAssignment attribute), 732
 rhs (angr.analyses.decompiler.structured_codegen.c.CBinaryOp attribute), 737
 RichR (class in angr.analyses.variable_recovery.engine_base), 831
 RIGHT (angr.analyses.typehoon.simple_solver.ConstraintGraphTag attribute), 834
 root (angr.analyses.typehoon.simple_solver.Sketch attribute), 833
 RShift (angr.engines.light.data.ArithmeticExpression attribute), 754
 run() (angr.analyses.congruency_check.CongruencyCheck method), 868
 run() (angr.analyses.identifier.identify.Identifier method), 845
 run() (angr.distributed.server.Server method), 909
 run() (angr.distributed.worker.Worker method), 910
 run() (angr.exploration_techniques.tracer.RepHook method), 415
 run() (angr.Server method), 211
 run() (angr.sim_manager.SimulationManager method), 384
 run() (angr.sim_procedure.SimProcedure method), 472
 run() (angr.SimProcedure method), 159
 run() (angr.SimulationManager method), 173
 run_pelf() (in module angr.flirt.build_sig), 893
 run_sigmake() (in module angr.flirt.build_sig), 893

S

- s2u() (in module *angr.analyses.decompiler.optimization_passes.register_save_area_simplifier*), 713
- s2u() (in module *angr.analyses.decompiler.optimization_passes.stack_caching_simplifier*), 707
- satisfiable() (*angr.sim_state.SimState* method), 226
- satisfiable() (*angr.SimState* method), 183
- satisfiable() (*angr.state_plugins.solver.SimSolver* method), 259
- save_info() (*angr.angrdb.db.AngrDB* static method), 676
- SCANF_DELIMITERS (*angr.procedures.stubs.format_parser.FormatString* attribute), 474
- ScanfFormatParser (class in *angr.procedures.stubs.format_parser*), 475
- scc_id (*angr.utils.graph.SCCPlaceholder* attribute), 897
- SCCPlaceholder (class in *angr.utils.graph*), 897
- scratch (*angr.sim_state.SimState* attribute), 225
- scratch (*angr.SimState* attribute), 181
- SDiv() (*angr.state_plugins.sim_action_object.SimActionObject* method), 469
- se (*angr.sim_state.SimState* property), 225
- se (*angr.SimState* property), 182
- section_alignment() (*angr.analyses.reassembler.Reassembler* method), 865
- SecurityCookieInit (class in *angr.simos.windows*), 888
- seek() (*angr.SimFileDescriptor* method), 198
- seek() (*angr.SimFileDescriptorDuplex* method), 201
- seek() (*angr.storage.file.SimFileDescriptor* method), 327
- seek() (*angr.storage.file.SimFileDescriptorBase* method), 326
- seek() (*angr.storage.file.SimFileDescriptorDuplex* method), 330
- seekable (*angr.SimFileBase* attribute), 188
- seekable (*angr.storage.file.SimFileBase* attribute), 316
- seekable (*angr.storage.file.SimPacketsSlots* attribute), 332
- SegfaultError, 288
- SegmentBoundary (*angr.knowledge_plugins.cfg.memory_data.MemoryDataSort* attribute), 545
- SegmentBoundary (*angr.knowledge_plugins.cfg.MemoryDataSort* attribute), 526
- selector() (*angr.exploration_techniques.ExplorationTechnique* method), 391
- selector() (*angr.ExplorationTechnique* method), 179
- selector() (*angr.sim_manager.SimulationManager* method), 386
- selector() (*angr.SimulationManager* method), 175
- seq (*angr.analyses.disassembly.IROp* attribute), 857
- sequence_matcher_similarity() (*angr.exploration_techniques.unique.UniqueSearch* static method), 424
- sequence_matcher_similarity() (*angr.exploration_techniques.UniqueSearch* static method), 404
- sequence_node (*angr.analyses.decompiler.structuring.structurer_nodes.L* attribute), 689
- sequence_to_blocks() (in module *angr.analyses.decompiler.utils*), 748
- sequence_to_statements() (in module *angr.analyses.decompiler.utils*), 748
- SequenceNode (class in *angr.analyses.decompiler.structuring.structurer_nodes*), 687
- SequenceOptimizationPass (class in *angr.analyses.decompiler.optimization_passes.optimization_passes*), 706
- SequenceWalker (class in *angr.analyses.decompiler.sequence_walker*), 725
- Serializable (class in *angr.serializable*), 620
- SerializableCounter (class in *angr.calling_conventions*), 485
- SerializableIterator (class in *angr.calling_conventions*), 485
- SerializableListIterator (class in *angr.calling_conventions*), 485
- serialize() (*angr.knowledge_plugins.functions.function_parser.Function* static method), 563
- serialize() (*angr.serializable.Serializable* method), 620
- serialize_to_cmessage() (*angr.Block* method), 170
- serialize_to_cmessage() (*angr.block.Block* method), 221
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.cfg_model.CFGModel* method), 539
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* method), 549
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.CFGModel* method), 532
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.CFGNode* method), 529
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.memory_data.MemoryData* method), 546
- serialize_to_cmessage() (*angr.knowledge_plugins.cfg.MemoryData* method), 528
- serialize_to_cmessage() (*angr.knowledge_plugins.functions.function.Function* method), 558

serialize_to_cmessage() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 565
 serialize_to_cmessage() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 566
 serialize_to_cmessage() (angr.knowledge_plugins.xrefs.xref.XRef method), 615
 serialize_to_cmessage() (angr.knowledge_plugins.xrefs.xref_manager.XRefManager method), 616
 serialize_to_cmessage() (angr.serializable.Serializable method), 620
 serialize_to_cmessage() (angr.sim_variable.SimMemoryVariable method), 507
 serialize_to_cmessage() (angr.sim_variable.SimRegisterVariable method), 506
 serialize_to_cmessage() (angr.sim_variable.SimStackVariable method), 508
 serialize_to_cmessage() (angr.sim_variable.SimTemporaryVariable method), 505
 Server (class in angr), 210
 Server (class in angr.distributed.server), 909
 session_scope() (angr.angrdb.db.AngrDB static method), 676
 set() (angr.knowledge_plugins.key_definitions.environment.Environment method), 595
 set_abi_cc() (angr.procedures.definitions.SimSyscallLibrary method), 482
 set_args() (angr.sim_procedure.SimProcedure method), 473
 set_args() (angr.SimProcedure method), 160
 set_base_state() (angr.callable.Callable method), 522
 set_bck_chunk() (angr.PTChunk method), 210
 set_bck_chunk() (angr.state_plugins.heap.heap_freelist.Chunk method), 301
 set_bck_chunk() (angr.state_plugins.heap.heap_ptmalloc.PTChunk method), 304
 set_brk() (angr.state_plugins.posix.SimSystemPosix method), 245
 set_c_prototype() (angr.procedures.definitions.SimLibrary method), 478
 set_data() (angr.state_plugins.gdb.GDB method), 271
 set_default_cc() (angr.procedures.definitions.SimLibrary method), 477
 set_entry_register_values() (angr.simos.linux.SimLinux method), 886
 set_fd_data() (angr.exploration_techniques.Tracer method), 395
 set_fd_data() (angr.exploration_techniques.tracer.Tracer method), 415
 set_fwd_chunk() (angr.PTChunk method), 210
 set_fwd_chunk() (angr.state_plugins.heap.heap_freelist.Chunk method), 300
 set_fwd_chunk() (angr.state_plugins.heap.heap_ptmalloc.PTChunk method), 303
 set_heap() (angr.state_plugins.gdb.GDB method), 271
 set_initial_regs() (angr.Block method), 170
 set_initial_regs() (angr.block.Block method), 221
 set_last_block_details() (angr.state_plugins.unicorn_engine.Unicorn method), 290
 set_last_statement() (angr.annocfg.AnnotatedCFG method), 881
 set_library_names() (angr.procedures.definitions.SimLibrary method), 477
 set_live_variables() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 567
 set_manager() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 566
 set_mode() (angr.sim_state.SimState method), 228
 set_mode() (angr.SimState method), 184
 set_names() (angr.procedures.definitions.SimTypeCollection method), 476
 set_non_returning() (angr.procedures.definitions.SimLibrary method), 477
 set_object() (angr.keyed_region.KeyedRegion method), 619
 set_object() (angr.keyed_region.RegionObject method), 618
 set_prev_freeness() (angr.PTChunk method), 209
 set_prev_freeness() (angr.state_plugins.heap.heap_ptmalloc.PTChunk method), 303
 set_prototype() (angr.knowledge_plugins.callsite_prototypes.CallsitePrototype method), 525
 set_prototype() (angr.procedures.definitions.SimLibrary method), 478
 set_prototype() (angr.procedures.definitions.SimSyscallLibrary method), 482
 set_prototypes() (angr.procedures.definitions.SimLibrary method), 478
 set_prototypes() (angr.procedures.definitions.SimSyscallLibrary method), 482
 set_regs() (angr.state_plugins.gdb.GDB method), 271
 set_regs() (angr.state_plugins.unicorn_engine.Unicorn method), 290
 set_return_val() (angr.calling_conventions.SimCC method), 491

[set_return_val\(\)](#) ([angr.calling_conventions.SimCCSyscall method](#)), 495
[set_return_val\(\)](#) ([angr.SimCC method](#)), 187
[set_simgr\(\)](#) ([angr.analyses.congruency_check.CongruencyCheck method](#)), 868
[set_size\(\)](#) ([angr.PTChunk method](#)), 209
[set_size\(\)](#) ([angr.sim_type.SimTypeRef method](#)), 520
[set_size\(\)](#) ([angr.state_plugins.heap.heap_freelist.Chunk method](#)), 300
[set_size\(\)](#) ([angr.state_plugins.heap.heap_ptmalloc.PTChunk method](#)), 302
[set_stack\(\)](#) ([angr.state_plugins.gdb.GDB method](#)), 271
[set_stack_address_mapping\(\)](#) ([angr.storage.memory_mixins.regioned_memory.regioned_memory method](#)), 368
[set_stack_size\(\)](#) ([angr.storage.memory_mixins.regioned_memory.regioned_memory method](#)), 368
[set_state\(\)](#) ([angr.SimFile method](#)), 190
[set_state\(\)](#) ([angr.SimFileDescriptor method](#)), 199
[set_state\(\)](#) ([angr.SimFileDescriptorDuplex method](#)), 201
[set_state\(\)](#) ([angr.SimFileStream method](#)), 194
[set_state\(\)](#) ([angr.SimPackets method](#)), 192
[set_state\(\)](#) ([angr.SimStatePlugin method](#)), 161
[set_state\(\)](#) ([angr.state_plugins.callstack.CallStack method](#)), 264
[set_state\(\)](#) ([angr.state_plugins.concrete.Concrete method](#)), 293
[set_state\(\)](#) ([angr.state_plugins.filesystem.SimConcreteFilesystem method](#)), 252
[set_state\(\)](#) ([angr.state_plugins.filesystem.SimFilesystem method](#)), 249
[set_state\(\)](#) ([angr.state_plugins.globals.SimStateGlobals method](#)), 278
[set_state\(\)](#) ([angr.state_plugins.inspect.SimInspector method](#)), 236
[set_state\(\)](#) ([angr.state_plugins.light_registers.SimLightRegisters method](#)), 267
[set_state\(\)](#) ([angr.state_plugins.plugin.SimStatePlugin method](#)), 232
[set_state\(\)](#) ([angr.state_plugins.posix.SimSystemPosix method](#)), 245
[set_state\(\)](#) ([angr.state_plugins.uc_manager.SimUCManager method](#)), 280
[set_state\(\)](#) ([angr.state_plugins.unicorn_engine.Unicorn method](#)), 290
[set_state\(\)](#) ([angr.state_plugins.view.SimMemView method](#)), 311
[set_state\(\)](#) ([angr.storage.file.SimFile method](#)), 317
[set_state\(\)](#) ([angr.storage.file.SimFileDescriptor method](#)), 328
[set_state\(\)](#) ([angr.storage.file.SimFileDescriptorDuplex method](#)), 330
[set_state\(\)](#) ([angr.storage.file.SimFileStream method](#)), 319
[set_state\(\)](#) ([angr.storage.file.SimPackets method](#)), 321
[set_state\(\)](#) ([angr.storage.memory_mixins.address_concretization_mixin method](#)), 345
[set_state\(\)](#) ([angr.storage.memory_mixins.javavm_memory.javavm_memory method](#)), 377
[set_state\(\)](#) ([angr.storage.memory_mixins.paged_memory.pages.isp method](#)), 361
[set_state\(\)](#) ([angr.storage.memory_mixins.regioned_memory.regioned_memory method](#)), 373
[set_state\(\)](#) ([angr.storage.memory_mixins.regioned_memory.regioned_memory method](#)), 367
[set_state\(\)](#) ([angr.storage.memory_mixins.slotted_memory.SlottedMemory method](#)), 374
[set_state_options\(\)](#) ([angr.storage.memory_mixins.regioned_memory.regioned_memory method](#)), 868
[set_states\(\)](#) ([angr.analyses.congruency_check.CongruencyCheck method](#)), 868
[set_stops\(\)](#) ([angr.state_plugins.unicorn_engine.Unicorn method](#)), 290
[set_strongref_state\(\)](#) ([angr.SimStatePlugin method](#)), 161
[set_strongref_state\(\)](#) ([angr.state_plugins.history.SimStateHistory method](#)), 267
[set_strongref_state\(\)](#) ([angr.state_plugins.plugin.SimStatePlugin method](#)), 232
[set_symbolization_for_all_pages\(\)](#) ([angr.state_plugins.symbolizer.SimSymbolizer method](#)), 307
[set_symbolized_target_range\(\)](#) ([angr.state_plugins.symbolizer.SimSymbolizer method](#)), 307
[set_tracking\(\)](#) ([angr.state_plugins.unicorn_engine.Unicorn method](#)), 290
[set_tyenv\(\)](#) ([angr.state_plugins.scratch.SimStateScratch method](#)), 280
[set_type\(\)](#) ([angr.analyses.decompiler.structured_codegen.c.CExpression method](#)), 729
[set_unified_variable\(\)](#) ([angr.knowledge_plugins.variables.variable_manager.VariableManager method](#)), 570
[set_value\(\)](#) ([angr.calling_conventions.SimArrayArg method](#)), 488
[set_value\(\)](#) ([angr.calling_conventions.SimComboArg method](#)), 487
[set_value\(\)](#) ([angr.calling_conventions.SimFunctionArgument method](#)), 486
[set_value\(\)](#) ([angr.calling_conventions.SimLyingRegArg method](#)), 492
[set_value\(\)](#) ([angr.calling_conventions.SimReferenceArgument method](#)), 492

method), 488

set_value() (angr.calling_conventions.SimRegArg method), 486

set_value() (angr.calling_conventions.SimStackArg method), 487

set_value() (angr.calling_conventions.SimStructArg method), 488

set_variable() (angr.keyed_region.KeyedRegion method), 619

set_variable() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 566

set_variable_type() (angr.knowledge_plugins.variables.variable_manager.VariableManager method), 570

setstate() (angr.calling_conventions.ArgSession method), 488

setstate() (angr.calling_conventions.SerializableCounter method), 485

setstate() (angr.calling_conventions.SerializableIterator method), 485

setstate() (angr.calling_conventions.SerializableListIterator method), 485

setstate() (angr.calling_conventions.SimCC.ArgSession method), 490

setstate() (angr.calling_conventions.UsercallArgSession method), 489

setstate() (angr.SimCC.ArgSession method), 186

setup() (angr.exploration_techniques.DFS method), 398

setup() (angr.exploration_techniques.dfs.DFS method), 408

setup() (angr.exploration_techniques.driller_core.DrillerCore method), 417

setup() (angr.exploration_techniques.DrillerCore method), 393

setup() (angr.exploration_techniques.ExplorationTechnique method), 390

setup() (angr.exploration_techniques.Explorer method), 397

setup() (angr.exploration_techniques.explorer.Explorer method), 409

setup() (angr.exploration_techniques.local_loop_seer.LocalLoopSeer method), 422

setup() (angr.exploration_techniques.LocalLoopSeer method), 406

setup() (angr.exploration_techniques.loop_seer.LoopSeer method), 422

setup() (angr.exploration_techniques.LoopSeer method), 394

setup() (angr.exploration_techniques.manual_mergepoint.ManualMergepoint method), 410

setup() (angr.exploration_techniques.ManualMergepoint method), 402

setup() (angr.exploration_techniques.memory_watcher.MemoryWatcher method), 426

setup() (angr.exploration_techniques.MemoryWatcher method), 405

setup() (angr.exploration_techniques.Slicecutor method), 392

setup() (angr.exploration_techniques.slicecutor.Slicecutor method), 417

setup() (angr.exploration_techniques.Symbion method), 404

setup() (angr.exploration_techniques.symbion.Symbion method), 425

setup() (angr.exploration_techniques.Timeout method), 407

setup() (angr.exploration_techniques.timeout.Timeout method), 408

setup() (angr.exploration_techniques.Tracer method), 395

setup() (angr.exploration_techniques.tracer.Tracer method), 415

setup() (angr.exploration_techniques.unique.UniqueSearch method), 424

setup() (angr.exploration_techniques.UniqueSearch method), 404

setup() (angr.ExplorationTechnique method), 178

setup() (angr.state_plugins.unicorn_engine.Unicorn method), 290

setup_arguments() (angr.engines.soot.engine.SootMixin static method), 432

setup_callsite() (angr.calling_conventions.SimCC method), 491

setup_callsite() (angr.calling_conventions.SimCCSoot method), 502

setup_callsite() (angr.engines.soot.engine.SootMixin class method), 432

setup_callsite() (angr.SimCC method), 187

setup_flags() (angr.state_plugins.unicorn_engine.Unicorn method), 290

setup_gdt() (angr.SimOS method), 169

setup_gdt() (angr.simos.simos.SimOS method), 885

setup_gdt() (angr.state_plugins.unicorn_engine.Unicorn method), 290

setup_terminal() (in module angr.utils.formatting), 901

shallow_reverse() (in module angr.utils.graph), 895

ShiftLeft (angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTable attribute), 666

ShiftRight (angr.analyses.cfg.indirect_jump_resolvers.jumptable.AddressTable attribute), 666

short_reason (angr.knowledge_plugins.cfg.cfg_node.CFGNodeCreationFunction attribute), 547

short_repr (angr.analyses.ddg.ProgramVariable property), 749

short_repr (angr.code_location.CodeLocation property), 617

should_abort (angr.analyses.forward_analysis.forward_analysis.FormatAnalysis plugins.sim_action), 467
 (property), 625 SimActionData (class in
 should_add_successors (angr.state_plugins.sim_action), 468
 (angr.sim_procedure.SimProcedure prop- SimActionError, 908
 erty), 473 SimActionExit (class in
 should_add_successors (angr.SimProcedure prop- ang_r.state_plugins.sim_action), 467
 erty), 160 SimActionObject (class in
 should_execute_statement() ang_r.state_plugins.sim_action_object), 468
 (angr.annocfg.AnnotatedCFG method), 881 SimActionOperation (class in
 should_force_replace() ang_r.state_plugins.sim_action), 468
 (angr.analyses.propagator.engine_ail.SimEnginePSimActionLocation (class in
 method), 758 ang_r.analyses.data_dep.sim_act_location),
 should_take_exit() (angr.annocfg.AnnotatedCFG 876
 method), 881 SimArrayArg (class in ang_r.calling_conventions), 488
 show_demangled_name SimCC (class in ang_r), 184
 (angr.analyses.decompiler.structured_codegen.c.SimCC (class in ang_r.calling_conventions), 489
 attribute), 729 SimCC.ArgSession (class in ang_r), 185
 show_demangled_name SimCC.ArgSession (class in ang_r.calling_conventions),
 (angr.analyses.decompiler.structured_codegen.c.CFunctionCall 489
 attribute), 733 SimCCAArch64 (class in ang_r.calling_conventions), 498
 show_disambiguated_name SimCCAArch64LinuxSyscall (class in
 (angr.analyses.decompiler.structured_codegen.c.CFunctionCall ang_r.calling_conventions), 498
 attribute), 733 SimCCallError, 907
 shrink() (angr.analyses.reassembler.Data method), 864 SimCCAMD64LinuxSyscall (class in
 SideEffectTag (class in ang_r.calling_conventions), 496
 ang_r.knowledge_plugins.key_definitions.tag), 608 SimCCAMD64WindowsSyscall (class in
 ang_r.calling_conventions), 496
 SIG_BLOCK (angr.state_plugins.posix.SimSystemPosix at- SimCCARM (class in ang_r.calling_conventions), 497
 tribute), 244 SimCCARMHF (class in ang_r.calling_conventions), 497
 SIG_SETMASK (angr.state_plugins.posix.SimSystemPosix SimCCARMLinuxSyscall (class in
 attribute), 244 ang_r.calling_conventions), 498
 SIG_UNBLOCK (angr.state_plugins.posix.SimSystemPosix SimCCCdecl (class in ang_r.calling_conventions), 493
 attribute), 244 SimCCError, 908
 sigmask() (angr.state_plugins.posix.SimSystemPosix SimCCM68k (class in ang_r.engines.pcode.cc), 464
 method), 246 SimCCMicrosoftAMD64 (class in
 signed (angr.procedures.stubs.format_parser.FormatSpecifier ang_r.calling_conventions), 494
 attribute), 474 SimCCMicrosoftCdecl (class in
 ang_r.calling_conventions), 493
 signed (angr.sim_type.SimTypeFloat attribute), 517 SimCCP386AddFastTraps (class in
 SignedExtension (angr.analyses.cfg.indirect_jump_resolver.SimCCP386AddFastTraps, 494
 attribute), 666 ang_r.calling_conventions), 494
 sigprocmask() (angr.state_plugins.posix.SimSystemPosix SimCCN64 (class in ang_r.calling_conventions), 500
 method), 246 SimCCN64LinuxSyscall (class in
 silence_logger() (in module ang_r.calling_conventions), 500
 ang_r.state_plugins.heap.heap_ptmalloc), 302 SimCCO32 (class in ang_r.calling_conventions), 499
 SimCCO32LinuxSyscall (class in
 ang_r.calling_conventions), 499
 sim_procedure (angr.code_location.CodeLocation at- SimCCO64 (in module ang_r.calling_conventions), 500
 tribute), 617 SimCCPARISC (class in ang_r.engines.pcode.cc), 465
 sim_procedure (angr.codenode.HookNode attribute), SimCCPowerPC (class in ang_r.calling_conventions), 500
 883 SimCCPowerPC (class in ang_r.engines.pcode.cc), 466
 sim_procedure (angr.codenode.SyscallNode attribute), SimCCPowerPC64 (class in ang_r.calling_conventions),
 884 501
 SimAbstractMemoryError, 905
 SimAction (class in ang_r.state_plugins.sim_action), 467
 SimActionConstraint (class in ang_r.calling_conventions), 501

SimCCPowerPCLinuxSyscall (class in <i>angr.calling_conventions</i>), 501	in	SimConcretizationStrategySolutions (class in <i>angr.concretization_strategies.solutions</i>), 379
SimCCRISCV (class in <i>angr.engines.pcode.cc</i>), 465		SimConcretizationStrategyUnlimitedRange (class in <i>angr.concretization_strategies.unlimited_range</i>), 382
SimCCRISCV64LinuxSyscall (class in <i>angr.calling_conventions</i>), 498	in	
SimCCS390X (class in <i>angr.calling_conventions</i>), 503		SimConstantVariable (class in <i>angr.sim_variable</i>), 505
SimCCS390XLinuxSyscall (class in <i>angr.calling_conventions</i>), 503	in	
SimCCSH4 (class in <i>angr.engines.pcode.cc</i>), 465		SimCppClass (class in <i>angr.sim_type</i>), 519
SimCCSoot (class in <i>angr.calling_conventions</i>), 502		SimCppClassValue (class in <i>angr.sim_type</i>), 519
SimCCSPARC (class in <i>angr.engines.pcode.cc</i>), 465		SimCppClassLibrary (class in <i>angr.procedures.definitions</i>), 480
SimCCStdcall (class in <i>angr.calling_conventions</i>), 493		SimDebugVariable (class in <i>angr.state_plugins.debug_variables</i>), 307
SimCCSyscall (class in <i>angr.calling_conventions</i>), 494		SimDebugVariablePlugin (class in <i>angr.state_plugins.debug_variables</i>), 308
SimCCSystemVAMD64 (class in <i>angr.calling_conventions</i>), 495	in	
SimCCUnknown (class in <i>angr.calling_conventions</i>), 503		SimEmptyCallStackError, 908
SimCCUsercall (class in <i>angr.calling_conventions</i>), 492		SimEngine (class in <i>angr.engines.engine</i>), 428
SimCCX86LinuxSyscall (class in <i>angr.calling_conventions</i>), 495	in	SimEngineBase (class in <i>angr.engines.engine</i>), 428
SimCCX86WindowsSyscall (class in <i>angr.calling_conventions</i>), 495	in	SimEngineConcrete (class in <i>angr.engines.concrete</i>), 433
SimCCXtensa (class in <i>angr.engines.pcode.cc</i>), 466		SimEngineError, 907
SimCGC (class in <i>angr.simos.cgc</i>), 887		SimEngineFailure (class in <i>angr.engines.failure</i>), 431
SimComboArg (class in <i>angr.calling_conventions</i>), 487		SimEngineInitFinderVEX (class in <i>angr.analyses.init_finder</i>), 870
SimConcreteBreakpointError, 908		SimEngineLight (class in <i>angr.engines.light.engine</i>), 755
SimConcreteFilesystem (class in <i>angr.state_plugins.filesystem</i>), 251	in	SimEngineLightAIL (in module <i>angr.engines.light.engine</i>), 756
SimConcreteMemoryError, 908		SimEngineLightAILMixin (class in <i>angr.engines.light.engine</i>), 756
SimConcreteRegisterError, 908		SimEngineLightMixin (class in <i>angr.engines.light.engine</i>), 755
SimConcretizationStrategy (class in <i>angr.concretization_strategies</i>), 335	in	SimEngineLightVEX (in module <i>angr.engines.light.engine</i>), 756
SimConcretizationStrategyAny (class in <i>angr.concretization_strategies.any</i>), 381	in	SimEngineLightVEXMixin (class in <i>angr.engines.light.engine</i>), 756
SimConcretizationStrategyControlledData (class in <i>angr.concretization_strategies.controlled_data</i>), 381		SimEnginePropagatorAIL (class in <i>angr.analyses.propagator.engine_ail</i>), 758
SimConcretizationStrategyEval (class in <i>angr.concretization_strategies.eval</i>), 379	in	SimEnginePropagatorBase (class in <i>angr.analyses.propagator.engine_base</i>), 757
SimConcretizationStrategyMax (class in <i>angr.concretization_strategies.max</i>), 380	in	SimEnginePropagatorVEX (class in <i>angr.analyses.propagator.engine_vex</i>), 757
SimConcretizationStrategyNonzero (class in <i>angr.concretization_strategies.nonzero</i>), 381	in	SimEngineRDAIL (class in <i>angr.analyses.reaching_definitions.engine_ail</i>), 818
SimConcretizationStrategyNonzeroRange (class in <i>angr.concretization_strategies.nonzero_range</i>), 380		SimEngineRDVEX (class in <i>angr.analyses.reaching_definitions.engine_vex</i>), 794
SimConcretizationStrategyNorepeats (class in <i>angr.concretization_strategies.norepeats</i>), 379	in	SimEngineSyscall (class in <i>angr.engines.syscall</i>), 431
SimConcretizationStrategyNorepeatsRange (class in <i>angr.concretization_strategies.norepeats_range</i>), 381		SimEngineUnicorn (class in <i>angr.engines.unicorn</i>), 432
SimConcretizationStrategyRange (class in <i>angr.concretization_strategies.range</i>), 380	in	SimEngineVRAIL (class in <i>angr.analyses.variable_recovery.engine_ail</i>), 831
SimConcretizationStrategySingle (class in <i>angr.concretization_strategies.single</i>), 379	in	SimEngineVRBase (class in <i>angr.analyses.variable_recovery.engine_ail</i>), 831

angr.analyses.variable_recovery.engine_base), 831

SimEngineVRVEX (class in *angr.analyses.variable_recovery.engine_vex*), 831

SimEngineXRefsVEX (class in *angr.analyses.xrefs*), 871

SimError, 905

SimEvent (class in *angr.state_plugins.sim_event*), 469

SimEventError, 906

SimException, 908

SimExpressionError, 906

SimFastMemoryError, 906

SimFastPathError, 907

SimFile (class in *angr*), 189

SimFile (class in *angr.storage.file*), 317

SimFileBase (class in *angr*), 188

SimFileBase (class in *angr.storage.file*), 315

SimFileDescriptor (class in *angr*), 198

SimFileDescriptor (class in *angr.storage.file*), 327

SimFileDescriptorBase (class in *angr.storage.file*), 325

SimFileDescriptorDuplex (class in *angr*), 200

SimFileDescriptorDuplex (class in *angr.storage.file*), 329

SimFileError, 906

SimFileStream (class in *angr*), 194

SimFileStream (class in *angr.storage.file*), 319

SimFilesystem (class in *angr.state_plugins.filesystem*), 249

SimFilesystemError, 906

SimFunctionArgument (class in *angr.calling_conventions*), 485

simgr() (*angr.factory.AngrObjectFactory* method), 219

SimHeapBase (class in *angr.state_plugins.heap.heap_base*), 297

SimHeapBrk (class in *angr*), 204

SimHeapBrk (class in *angr.state_plugins.heap.heap_brk*), 298

SimHeapError, 906

SimHeapFreelist (class in *angr.state_plugins.heap.heap_freelist*), 301

SimHeapLibc (class in *angr.state_plugins.heap.heap_libc*), 301

SimHeapPTMalloc (class in *angr*), 206

SimHeapPTMalloc (class in *angr.state_plugins.heap.heap_ptmalloc*), 304

SimHostFilesystem (class in *angr*), 203

SimHostFilesystem (class in *angr.state_plugins.filesystem*), 253

similarity() (*angr.exploration_techniques.unique.UniqueSearch* static method), 424

similarity() (*angr.exploration_techniques.UniqueSearchsimplified_data_graph* static method), 404

SimInspector (class in *angr.state_plugins.inspect*), 233

SimIRSBError, 907

SimIRSBNoDecodeError, 907

SimJavaVM (class in *angr.simos.javavm*), 890

SimJavaVmClassLoader (class in *angr.state_plugins.javavm_classloader*), 294

SimLabeledMemoryObject (class in *angr.storage.memory_object*), 334

SimLibrary (class in *angr.procedures.definitions*), 477

SimLightRegisters (class in *angr.state_plugins.light_registers*), 266

SimLightState (class in *angr.slicer*), 880

SimLinux (class in *angr.simos.linux*), 886

SimLyingRegArg (class in *angr.calling_conventions*), 492

SimMemoryAddressError, 906

SimMemoryError, 905

SimMemoryLimitError, 906

SimMemoryMissingError, 905

SimMemoryObject (class in *angr.storage.memory_object*), 334

SimMemoryVariable (class in *angr.sim_variable*), 507

SimMemView (class in *angr.state_plugins.view*), 310

SimMergeError, 905

SimMissingTempError, 907

SimMount (class in *angr*), 203

SimMount (class in *angr.state_plugins.filesystem*), 251

SimOperationError, 906

SimOS (class in *angr*), 168

SimOS (class in *angr.simos.simos*), 884

SIMOS_CGC (*angr.state_plugins.unicorn_engine.SimOSEnum* attribute), 287

SIMOS_LINUX (*angr.state_plugins.unicorn_engine.SimOSEnum* attribute), 287

SIMOS_OTHER (*angr.state_plugins.unicorn_engine.SimOSEnum* attribute), 288

SimOSEnum (class in *angr.state_plugins.unicorn_engine*), 287

SimPackets (class in *angr*), 192

SimPackets (class in *angr.storage.file*), 321

SimPacketsSlots (class in *angr.storage.file*), 332

SimPacketsStream (class in *angr*), 196

SimPacketsStream (class in *angr.storage.file*), 323

SimpleInterfaceMixin (class in *angr.storage.memory_mixins.simple_interface_mixin*), 342

SimpleSolver (class in *angr.analyses.typehoon.simple_solver*), 835

SimplificationMixin (class in *angr.storage.memory_mixins.simplification_mixin*), 347

SimpleInterfaceMixin (class in *angr.storage.memory_mixins.simple_interface_mixin*), 342

[simplified_graph\(angr.analyses.data_dep.data_dependency_graph.DependencyGraphAnalysis property\)](#), 876
[SimplifierAILEngine](#) (class in [SimplifierAILEngine](#)), 712
[SimplifierAILState](#) (class in [SimplifierAILState](#)), 711
[simplify\(\)](#) ([angr.sim_state.SimState](#) method), 226
[simplify\(\)](#) ([angr.SimState](#) method), 182
[simplify\(\)](#) ([angr.state_hierarchy.StateHierarchy](#) method), 389
[simplify\(\)](#) ([angr.state_plugins.solver.SimSolver](#) method), 262
[simplify\(\)](#) ([angr.StateHierarchy](#) method), 180
[simplify_condition\(\)](#) ([angr.analyses.decompiler.condition_processor.ConditionProcessor](#) static method), 699
[simplify_condition_deprecated\(\)](#) ([angr.analyses.decompiler.condition_processor.ConditionProcessor](#) static method), 699
[simplify_else_scope](#) ([angr.analyses.decompiler.structured_codegen.C](#) attribute), 731
[simplify_lowered_switches\(\)](#) (in module [angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier](#)), 724
[simplify_lowered_switches_core\(\)](#) (in module [angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier](#)), 724
[simplify_switch_clusters\(\)](#) (in module [angr.analyses.decompiler.region_simplifiers.switch_cluster_simplifier](#)), 724
[SimPosixError](#), 906
[SimProcedure](#) (class in [angr](#)), 157
[SimProcedure](#) (class in [angr.sim_procedure](#)), 469
[simprocedure_name](#) ([angr.knowledge_plugins.cfg.cfg_node.CFGNode](#) attribute), 548
[simprocedure_name](#) ([angr.knowledge_plugins.cfg.CFGNode](#) attribute), 528
[SimProcedureArgumentError](#), 907
[SimProcedureError](#), 907
[SimReferenceArgument](#) (class in [angr.calling_conventions](#)), 488
[SimRegArg](#) (class in [angr.calling_conventions](#)), 486
[SimRegionMapError](#), 906
[SimRegisterVariable](#) (class in [angr.sim_variable](#)), 506
[SimRegNameView](#) (class in [angr.state_plugins.view](#)), 309
[SimReliftException](#), 907
[SimSegfaultError](#) (in module [angr.errors](#)), 908
[SimSegfaultException](#), 908
[SimShadowStackError](#), 907
[SimSlicer](#) (class in [angr.slicer](#)), 880
[SimSlicerError](#), 908
[SimSolver](#) (class in [angr.state_plugins.solver](#)), 254
[SimSolverError](#), 906
[SimSolverModeError](#), 906
[SimSolverOptionError](#), 906
[SimStackArg](#) (class in [angr.calling_conventions](#)), 487
[SimStackVariable](#) (class in [angr.sim_variable](#)), 507
[SimState](#) (class in [angr](#)), 180
[SimState](#) (class in [angr.sim_state](#)), 224
[SimStateCGC](#) (class in [angr.state_plugins.cgc](#)), 271
[SimStateError](#), 905
[SimStateGlobals](#) (class in [angr.state_plugins.globals](#)), 278
[SimStateHistory](#) (class in [angr.state_plugins.history](#)), 267
[SimStateJNIReferences](#) (class in [angr.state_plugins.jni_references](#)), 296
[SimStateLibc](#) (class in [angr.state_plugins.libc](#)), 236
[SimStateLog](#) (class in [angr.state_plugins.log](#)), 262
[SimStateLoopData](#) (class in [angr.state_plugins.loop_data](#)), 291
[SimStatementError](#), 907
[SimStateOptions](#) (class in [angr.sim_state_options](#)), 228
[SimStateOptionsError](#), 908
[SimStatePluginError](#) (class in [angr](#)), 161
[SimStatePlugin](#) (class in [angr.state_plugins.plugin](#)), 231
[SimStatePredefiner](#) (class in [angr.state_plugins.preconstrainer](#)), 282
[SimStateScratch](#) (class in [angr.state_plugins.scratch](#)), 380
[SimStruct](#) (class in [angr.sim_type](#)), 517
[SimStructArg](#) (class in [angr.calling_conventions](#)), 487
[SimStructValue](#) (class in [angr.sim_type](#)), 518
[SimSuccessors](#) (class in [angr.engines.successors](#)), 429
[SimSymbolicFilesystemError](#), 906
[SimSymbolizer](#) (class in [angr.state_plugins.symbolizer](#)), 307
[SimSyscallLibrary](#) (class in [angr.procedures.definitions](#)), 481
[SimSystemPosix](#) (class in [angr.state_plugins.posix](#)), 244
[SimTemporaryVariable](#) (class in [angr.sim_variable](#)), 505
[SimTranslationError](#), 907
[SimType](#) (class in [angr.sim_type](#)), 509
[simtype2tc\(\)](#) ([angr.analyses.typehoon.translator.TypeTranslator](#) method), 837
[SimTypeArray](#) (class in [angr.sim_type](#)), 513
[SimTypeBool](#) (class in [angr.sim_type](#)), 512
[SimTypeBottom](#) (class in [angr.sim_type](#)), 510
[SimTypeChar](#) (class in [angr.sim_type](#)), 512
[SimTypeCollection](#) (class in [angr.procedures.definitions](#)), 476

SimTypeCppFunction (class in *angr.sim_type*), 515
 SimTypeDouble (class in *angr.sim_type*), 517
 SimTypeFd (class in *angr.sim_type*), 513
 SimTypeFixedSizeArray (in module *angr.sim_type*), 514
 SimTypeFloat (class in *angr.sim_type*), 516
 SimTypeFunction (class in *angr.sim_type*), 515
 SimTypeInt (class in *angr.sim_type*), 511
 SimTypeLength (class in *angr.sim_type*), 516
 SimTypeLong (class in *angr.sim_type*), 512
 SimTypeLongLong (class in *angr.sim_type*), 512
 SimTypeNum (class in *angr.sim_type*), 511
 SimTypeNumOffset (class in *angr.sim_type*), 519
 SimTypePointer (class in *angr.sim_type*), 513
 SimTypeRef (class in *angr.sim_type*), 520
 SimTypeReference (class in *angr.sim_type*), 513
 SimTypeReg (class in *angr.sim_type*), 511
 SimTypeShort (class in *angr.sim_type*), 512
 SimTypeString (class in *angr.sim_type*), 514
 SimTypeTempRef (class in *angr.analyses.typehoon.translator*), 836
 SimTypeTop (class in *angr.sim_type*), 511
 SimTypeWideChar (class in *angr.sim_type*), 512
 SimTypeWString (class in *angr.sim_type*), 514
 SimUCManager (class in *angr.state_plugins.uc_manager*), 279
 SimUCManagerAllocationError, 908
 SimUCManagerError, 908
 simulation_manager() (in *angr.factory.AngrObjectFactory* method), 219
 SimulationManager (class in *angr*), 171
 SimulationManager (class in *angr.sim_manager*), 382
 SimulationManagerError, 903
 SimUnicornError, 908
 SimUnicornSymbolic, 908
 SimUnicornUnsupport, 908
 SimUninitializedAccessError, 907
 SimUnion (class in *angr.sim_type*), 518
 SimUnionValue (class in *angr.sim_type*), 518
 SimUnsatError, 906
 SimUnsupportedError, 906
 SimUserland (class in *angr.simos.userland*), 887
 SimValueError, 906
 SimVariable (class in *angr.sim_variable*), 504
 SimVariableSet (class in *angr.sim_variable*), 508
 SimWindows (class in *angr.simos.windows*), 888
 SimZeroDivisionException, 908
 single_valued() (in *angr.state_plugins.solver.SimSolver* method), 262
 SingleNodeGraphVisitor (class in *angr.analyses.forward_analysis.visitors.single_node_graph_visitor*), 631
 size (in *angr.analyses.propagator.values.Top* attribute), 756
 size (in *angr.analyses.propagator.vex_vars.VEXMemVar* attribute), 756
 size (in *angr.analyses.propagator.vex_vars.VEXReg* attribute), 756
 size (in *angr.analyses.reaching_definitions.Atom* attribute), 770
 size (in *angr.analyses.reaching_definitions.Definition* property), 774
 SIZE (in *angr.analyses.typehoon.typeconsts.Double* attribute), 844
 SIZE (in *angr.analyses.typehoon.typeconsts.Float* attribute), 844
 SIZE (in *angr.analyses.typehoon.typeconsts.Int1* attribute), 843
 SIZE (in *angr.analyses.typehoon.typeconsts.Int128* attribute), 844
 SIZE (in *angr.analyses.typehoon.typeconsts.Int16* attribute), 843
 SIZE (in *angr.analyses.typehoon.typeconsts.Int32* attribute), 843
 SIZE (in *angr.analyses.typehoon.typeconsts.Int64* attribute), 843
 SIZE (in *angr.analyses.typehoon.typeconsts.Int8* attribute), 843
 SIZE (in *angr.analyses.typehoon.typeconsts.TypeConstant* attribute), 843
 size (in *angr.analyses.typehoon.typeconsts.TypeConstant* property), 843
 size (in *angr.Block* attribute), 170
 size (in *angr.block.Block* attribute), 221
 size (in *angr.block.CapstoneInsn* property), 221
 size (in *angr.block.DisassemblerInsn* property), 220
 size (in *angr.block.SootBlock* property), 222
 size (in *angr.codenode.CodeNode* attribute), 883
 size (in *angr.engines.pcode.lifter.IRSB* property), 439
 size (in *angr.engines.pcode.lifter.PcodeDisassemblerInsn* property), 436
 size (in *angr.keyed_region.RegionObject* attribute), 618
 size (in *angr.keyed_region.StoredObject* attribute), 618
 size (in *angr.knowledge_plugins.cfg.cfg_node.CFGNode* attribute), 548
 size (in *angr.knowledge_plugins.cfg.CFGNode* attribute), 528
 size (in *angr.knowledge_plugins.cfg.memory_data.MemoryData* attribute), 546
 size (in *angr.knowledge_plugins.cfg.MemoryData* attribute), 527
 size (in *angr.knowledge_plugins.functions.function.Function* property), 559
 size (in *angr.knowledge_plugins.key_definitions.atoms.Atom* attribute), 588
 size (in *angr.knowledge_plugins.key_definitions.Definition*

- property*), 588
- size* (*angr.knowledge_plugins.key_definitions.definition.Definition* *tribute*), 442
- property*), 594
- size* (*angr.procedures.stubs.format_parser.FormatSpecifiers* *attribute*), 474
- size* (*angr.sim_type.SimStruct* *property*), 518
- size* (*angr.sim_type.SimType* *property*), 509
- size* (*angr.sim_type.SimTypeArray* *property*), 514
- size* (*angr.sim_type.SimTypeFunction* *property*), 515
- size* (*angr.sim_type.SimTypeInt* *property*), 512
- size* (*angr.sim_type.SimTypeLength* *property*), 516
- size* (*angr.sim_type.SimTypePointer* *property*), 513
- size* (*angr.sim_type.SimTypeReference* *property*), 513
- size* (*angr.sim_type.SimTypeString* *property*), 514
- size* (*angr.sim_type.SimTypeWString* *property*), 515
- size* (*angr.sim_type.SimUnion* *property*), 518
- size* (*angr.sim_type.TypeRef* *property*), 510
- size* (*angr.sim_variable.SimVariable* *attribute*), 505
- size* (*angr.SimFile* *property*), 190
- size* (*angr.SimFileBase* *property*), 189
- size* (*angr.SimPackets* *property*), 192
- size* (*angr.state_plugins.unicorn_engine.RegisterValue* *attribute*), 285
- size* (*angr.storage.file.SimFile* *property*), 317
- size* (*angr.storage.file.SimFileBase* *property*), 316
- size* (*angr.storage.file.SimPackets* *property*), 321
- size* (*angr.storage.file.SimPacketsSlots* *property*), 332
- size*() (*angr.calling_conventions.AllocHelper* *method*), 485
- size*() (*angr.SimFileDescriptor* *method*), 198
- size*() (*angr.SimFileDescriptorDuplex* *method*), 201
- size*() (*angr.storage.file.SimFileDescriptor* *method*), 327
- size*() (*angr.storage.file.SimFileDescriptorBase* *method*), 326
- size*() (*angr.storage.file.SimFileDescriptorDuplex* *method*), 330
- size*() (*angr.storage.memory_object.SimMemoryObject* *method*), 334
- SizeConcretizationMixin* (*class* in *angr.storage.memory_mixins.size_resolution_mixin*), 343
- SizeNormalizationMixin* (*class* in *angr.storage.memory_mixins.size_resolution_mixin*), 343
- Sketch* (*class* in *angr.analyses.typehoon.simple_solver*), 833
- SketchNode* (*class* in *angr.analyses.typehoon.simple_solver*), 832
- SketchNodeBase* (*class* in *angr.analyses.typehoon.simple_solver*), 832
- skip_stmts* (*angr.engines.pcode.lifter.Lifter* *attribute*), 440
- skip_stmts* (*angr.engines.pcode.lifter.PcodeLifter* *attribute*), 442
- slice* (*angr.Blade* *property*), 168
- slice* (*angr.blade.Blade* *property*), 880
- slice_callgraph*() (*in* *module* *angr.analyses.cfg_slice_to_sink.graph*), 819
- slice_cfg_graph*() (*in* *module* *angr.analyses.cfg_slice_to_sink.graph*), 820
- slice_function_graph*() (*in* *module* *angr.analyses.cfg_slice_to_sink.graph*), 820
- slice_graph*() (*angr.analyses.decompiler.region_identifier.RegionIdentifier* *static method*), 717
- SliceCutor* (*class* in *angr.exploration_techniques*), 392
- SliceCutor* (*class* in *angr.exploration_techniques.slicecutor*), 417
- SlottedMemoryMixin* (*class* in *angr.storage.memory_mixins.slotted_memory*), 374
- SmartFindMixin* (*class* in *angr.storage.memory_mixins.smart_find_mixin*), 340
- SMod*() (*angr.state_plugins.sim_action_object.SimActionObject* *method*), 469
- snippet*() (*angr.factory.AngrObjectFactory* *method*), 216
- solution*() (*angr.state_plugins.solver.SimSolver* *method*), 258
- solve*() (*angr.analyses.typehoon.simple_solver.SimpleSolver* *method*), 835
- solver* (*angr.analyses.typehoon.simple_solver.Sketch* *attribute*), 833
- solver* (*angr.sim_state.SimState* *attribute*), 225
- solver* (*angr.SimState* *attribute*), 181
- soot* (*angr.block.SootBlock* *property*), 222
- soot_block* (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* *attribute*), 548
- soot_block* (*angr.knowledge_plugins.cfg.CFGNode* *attribute*), 529
- SootBlock* (*class* in *angr.block*), 222
- SootBlockNode* (*class* in *angr.codenode*), 883
- SootBlockProcessor* (*class* in *angr.analyses.loop_analysis*), 847
- SootClassHierarchy* (*class* in *angr.analyses.soot_class_hierarchy*), 640
- SootClassHierarchyError*, 640
- SootExpression* (*class* in *angr.analyses.disassembly*), 857
- SootExpressionInvoke* (*class* in *angr.analyses.disassembly*), 857
- SootExpressionStaticFieldRef* (*class* in *angr.analyses.disassembly*), 857
- SootExpressionTarget* (*class* in *angr.analyses.disassembly*), 857
- SootFunction* (*class* in *angr.analyses.disassembly*), 857

`angr.knowledge_plugins.functions.soot_function`), `split()` (`angr.SimulationManager` method), 177
`split_arm_op_string()` (`angr.analyses.disassembly.Instruction` static method), 857
`SootMixin` (class in `angr.engines.soot.engine`), 432
`SootStatement` (class in `angr.analyses.disassembly`), 858
`sort` (`angr.analyses.decompiler.structuring.structurer_nodes.LoopNode` attribute), 689
`sort` (`angr.knowledge_plugins.cfg.memory_data.MemoryData` attribute), 546
`sort` (`angr.knowledge_plugins.cfg.MemoryData` attribute), 527
`sort` (`angr.sim_type.SimTypeDouble` attribute), 517
`sort` (`angr.sim_type.SimTypeFloat` attribute), 517
`sort()` (`angr.exploration_techniques.spiller.PickledStatesBase` method), 410
`sort()` (`angr.exploration_techniques.spiller.PickledStatesDb` method), 411
`sort()` (`angr.exploration_techniques.spiller.PickledStatesList` method), 411
`sort_nodes()` (`angr.analyses.forward_analysis.visitors.call_graph.CallGraphVisitor` method), 627
`sort_nodes()` (`angr.analyses.forward_analysis.visitors.function_graph.FunctionGraphVisitor` method), 628
`sort_nodes()` (`angr.analyses.forward_analysis.visitors.graph.GraphVisitor` method), 628
`sort_nodes()` (`angr.analyses.forward_analysis.visitors.loop.LoopVisitor` method), 630
`sort_nodes()` (`angr.analyses.forward_analysis.visitors.single_node.SingleNodeGraphVisitor` method), 631
`sources` (`angr.analyses.reaching_definitions.function_handler.FunctionEffect` attribute), 802
`sources_defns` (`angr.analyses.reaching_definitions.function_handler.FunctionEffect` attribute), 803
`sp_delta` (`angr.knowledge_plugins.functions.function.Function` attribute), 556
`sp_delta` (`angr.knowledge_plugins.functions.soot_function.SootFunction` attribute), 564
`sp_offset()` (`angr.engines.light.engine.SimEngineLightMixin` static method), 755
`spec_type` (`angr.procedures.stubs.format_parser.FormatSpecifier` attribute), 474
`Special` (`angr.analyses.disassembly.SootExpressionInvoke` attribute), 858
`SPECIAL_THUNKS` (`angr.analyses.cfg.cfg_fast.CFGFast` attribute), 657
`SpecialFillerMixin` (class in `angr.storage.memory_mixins.default_filler_mixin`), 340
`Spiller` (class in `angr.exploration_techniques`), 401
`Spiller` (class in `angr.exploration_techniques.spiller`), 412
`split()` (`angr.keyed_region.RegionObject` method), 618
`split()` (`angr.sim_manager.SimulationManager` method), 388
`split_op_string()` (`angr.analyses.disassembly.Instruction` static method), 857
`split_operands()` (in module `angr.analyses.reassembler`), 860
`SpOffset` (class in `angr.engines.light.data`), 755
`squash_array_reference()` (in module `angr.analyses.decompiler.structured_codegen.c`), 727
`src_block_id` (`angr.analyses.vfg.PendingJob` attribute), 850
`src_func_addr` (`angr.analyses.cfg.cfg_fast.FunctionEdge` attribute), 654
`src_ins_addr` (`angr.analyses.cfg.cfg_fast.CFGJob` attribute), 656
`src_ins_addr` (`angr.analyses.vfg.PendingJob` attribute), 656
`src_node` (`angr.analyses.cfg.cfg_fast.CFGJob` attribute), 654
`src_node` (`angr.analyses.cfg.cfg_fast.FunctionCallEdge` attribute), 654
`src_node` (`angr.analyses.cfg.cfg_fast.FunctionFakeRetEdge` attribute), 654
`src_node` (`angr.analyses.cfg.cfg_fast.FunctionTransitionEdge` attribute), 654
`src_stmt_idx` (`angr.analyses.cfg.cfg_fast.CFGJob` attribute), 656
`src_stmt_idx` (`angr.analyses.vfg.PendingJob` attribute), 850
`src_type` (`angr.analyses.decompiler.structured_codegen.c.CTypeCast` attribute), 738
`sse_extend()` (`angr.calling_conventions.SimRegArg` method), 486
`st_atime` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_atimensec` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_blksize` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_blocks` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_ctime` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_ctimensec` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_dev` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_gid` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_ino` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_mode` (`angr.state_plugins.filesystem.Stat` attribute), 248
`st_mtime` (`angr.state_plugins.filesystem.Stat` attribute), 248

248

st_mtimensec (angr.state_plugins.filesystem.Stat attribute), 248

st_nlink (angr.state_plugins.filesystem.Stat attribute), 248

st_rdev (angr.state_plugins.filesystem.Stat attribute), 248

st_size (angr.state_plugins.filesystem.Stat attribute), 248

st_uid (angr.state_plugins.filesystem.Stat attribute), 248

StableVarExprHasher (class in (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

stack (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813

stack (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783

stack (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

stack (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

stack (angr.storage.memory_mixins.javavm_memory.javavm_memory.MemoryMixin property), 376

stack_actions (angr.state_plugins.history.SimStateHistory property), 270

stack_addr_from_offset() (angr.analyses.variable_recovery.variable_recovery_state.VariableRecoveryState method), 826

stack_address() (angr.analyses.reaching_definitions.LiveDefinitions method), 763

stack_address() (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState method), 812

stack_address() (angr.analyses.reaching_definitions.ReachingDefinitionsState method), 782

stack_address() (angr.analyses.variable_recovery.variable_recovery_state.VariableRecoveryState method), 826

stack_address() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 599

stack_address() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 578

STACK_ALIGNMENT (angr.calling_conventions.SimCC attribute), 489

STACK_ALIGNMENT (angr.calling_conventions.SimCCMicrosystem attribute), 494

STACK_ALIGNMENT (angr.calling_conventions.SimCCSystem attribute), 496

STACK_ALIGNMENT (angr.SimCC attribute), 185

stack_base (angr.storage.memory_mixins.regioned_memory.RegionedMemoryMap property), 370

stack_definitions (angr.analyses.reaching_definitions.LiveDefinitions property), 762

stack_definitions (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions property), 599

stack_definitions (angr.knowledge_plugins.key_definitions.LiveDefinitions property), 578

stack_id() (angr.storage.memory_mixins.regioned_memory.RegionedMemoryMap method), 368

stack_loc() (angr.calling_conventions.AllocHelper class method), 485

stack_offset (angr.knowledge_plugins.key_definitions.definition.Definition attribute), 593

stack_offset_to_stack_addr() (angr.analyses.reaching_definitions.LiveDefinitions method), 600

stack_offset_to_stack_addr() (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions method), 600

stack_offset_to_stack_addr() (angr.knowledge_plugins.key_definitions.LiveDefinitions method), 579

stack_offsets (angr.slicer.SimLightState attribute), 809

stack_pointer_as_atom() (angr.analyses.reaching_definitions.function_handler.FunctionHandler static method), 809

stack_pointer_is_atom() (angr.analyses.reaching_definitions.FunctionHandler static method), 790

stack_pop() (angr.sim_state.SimState method), 227

stack_pop() (angr.SimState method), 184

stack_push() (angr.sim_state.SimState method), 227

stack_push() (angr.SimState method), 183

stack_read() (angr.sim_state.SimState method), 227

stack_read() (angr.SimState method), 184

stack_region_definitions (angr.knowledge_plugins.variables.variable_manager.LiveVariables attribute), 565

stack_space() (angr.calling_conventions.SimCC method), 490

stack_space() (angr.calling_conventions.SimCCMicrosystem method), 494

stack_space() (angr.calling_conventions.SimCCSystem method), 496

stack_space() (angr.SimCC method), 185

stack_suffix() (angr.state_plugins.callstack.CallStack method), 265

stack_suffix_to_string() (angr.state_plugins.callstack.CallStack static method), 265

stack_uses (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

stack_uses (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813

stack_uses (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783

stack_uses (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 599

stack_uses (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

StackAllocationMixin (class in (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 577

StackAllocationMixin (class in (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 577

358

STACKARG_SP_BUFF (angr.calling_conventions.SimCC attribute), 489

STACKARG_SP_BUFF (angr.calling_conventions.SimCCMicro attribute), 494

STACKARG_SP_BUFF (angr.calling_conventions.SimCCN64 attribute), 500

STACKARG_SP_BUFF (angr.calling_conventions.SimCCO32 attribute), 499

STACKARG_SP_BUFF (angr.calling_conventions.SimCCPower attribute), 501

STACKARG_SP_BUFF (angr.calling_conventions.SimCCPower attribute), 501

STACKARG_SP_BUFF (angr.calling_conventions.SimCCS390 attribute), 503

STACKARG_SP_BUFF (angr.engines.pcode.cc.SimCCPower attribute), 466

STACKARG_SP_BUFF (angr.SimCC attribute), 185

STACKARG_SP_DIFF (angr.calling_conventions.SimCC attribute), 489

STACKARG_SP_DIFF (angr.calling_conventions.SimCCDec attribute), 493

STACKARG_SP_DIFF (angr.calling_conventions.SimCCMicro attribute), 494

STACKARG_SP_DIFF (angr.calling_conventions.SimCCMicro attribute), 494

STACKARG_SP_DIFF (angr.calling_conventions.SimCCSystem attribute), 496

STACKARG_SP_DIFF (angr.engines.pcode.cc.SimCCM68k attribute), 465

STACKARG_SP_DIFF (angr.SimCC attribute), 185

StackCanarySimplifier (class in angr.analyses.decompiler.optimization_passes.stack_canary_simplifier), 707

StackLocationAnnotation (class in angr.analyses.variable_recovery.annotations), 823

StackPointerTracker (class in angr.analyses.stack_pointer_tracker), 822

StackPointerTrackerState (class in angr.analyses.stack_pointer_tracker), 822

STAGE (angr.analyses.decompiler.optimization_passes.base_ptr_save attribute), 708

STAGE (angr.analyses.decompiler.optimization_passes.const_derefs.ContributedReferencesSimplifier attribute), 704

STAGE (angr.analyses.decompiler.optimization_passes.div_simplifier.DivSimplifier attribute), 708

STAGE (angr.analyses.decompiler.optimization_passes.expr_op_swapper.ExprOpSwapper attribute), 713

STAGE (angr.analyses.decompiler.optimization_passes.ite_expr_converter.IteExprConverter attribute), 709

STAGE (angr.analyses.decompiler.optimization_passes.lowered_switch_simplifier.LoweredSwitchSimplifier attribute), 710

STAGE (angr.analyses.decompiler.optimization_passes.mod_simplifier.ModSimplifier attribute), 711

STAGE (angr.analyses.decompiler.optimization_passes.multi_simplifier.MultiSimplifier attribute), 711

STAGE (angr.analyses.decompiler.optimization_passes.optimization_pass.BaseOptimizationPass attribute), 705

STAGE (angr.analyses.decompiler.optimization_passes.optimization_pass.Se attribute), 706

STAGE (angr.analyses.decompiler.optimization_passes.optimization_pass.St attribute), 707

STAGE (angr.analyses.decompiler.optimization_passes.register_save_area attribute), 713

STAGE (angr.analyses.decompiler.optimization_passes.ret_addr_save_simpl attribute), 714

STAGE (angr.analyses.decompiler.optimization_passes.stack_canary_simpli attribute), 707

STAGE (angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_simp attribute), 714

start (angr.analyses.decompiler.structured_codegen.base.PositionMapping attribute), 726

start (angr.keyed_region.RegionObject attribute), 618

start (angr.keyed_region.StoredObject attribute), 617

start() (angr.distributed.worker.Worker method), 910

start() (angr.state_plugins.unicorn_engine.Unicorn method), 290

startpoint (angr.knowledge_plugins.functions.function.Function attribute), 556

startpoint (angr.knowledge_plugins.functions.soot_function.SootFunction attribute), 564

stash (angr.exploration_techniques.spiller_db.PickledState attribute), 413

stash() (angr.sim_manager.SimulationManager method), 387

stash() (angr.sim_manager.SimulationManager method), 176

stashed (angr.sim_manager.SimulationManager attribute), 383

stashed (angr.SimulationManager attribute), 172

stashes (angr.sim_manager.SimulationManager property), 384

stashes (angr.SimulationManager property), 172

Stat (class in angr.state_plugins.filesystem), 248

state (angr.analyses.propagator.engine_ail.SimEnginePropagatorAIL attribute), 18

state (angr.analyses.propagator.engine_vex.SimEnginePropagatorVEX attribute), 18

state (angr.analyses.reaching_definitions.engine_ail.SimEngineRDAIL attribute), 18

state (angr.analyses.reaching_definitions.engine_vex.SimEngineRDVEX attribute), 18

state (angr.analyses.variable_recovery.engine_ail.SimEngineVRail attribute), 18

state (angr.analyses.variable_recovery.engine_base.SimEngineVRBase attribute), 18

state (angr.analyses.variable_recovery.engine_vex.SimEngineVRVEX attribute), 18

- state (angr.analyses.vfg.PendingJob attribute), 850
- state (angr.engines.UberEngine attribute), 427
- state (angr.procedures.stubs.format_parser.FormatParser attribute), 475
- state (angr.procedures.stubs.format_parser.FormatString property), 474
- state (angr.procedures.stubs.format_parser.ScanfFormatParser attribute), 476
- state (angr.sim_procedure.SimProcedure attribute), 472
- state (angr.SimFile attribute), 192
- state (angr.SimFileBase attribute), 189
- state (angr.SimFileDescriptor attribute), 200
- state (angr.SimFileDescriptorDuplex attribute), 203
- state (angr.SimFileStream attribute), 196
- state (angr.SimHeapBrk attribute), 206
- state (angr.SimHeapPTMalloc attribute), 208
- state (angr.SimHostFilesystem attribute), 204
- state (angr.SimMount attribute), 203
- state (angr.SimPackets attribute), 194
- state (angr.SimPacketsStream attribute), 198
- state (angr.SimProcedure attribute), 159
- state (angr.state_plugins.callstack.CallStack attribute), 264
- state (angr.state_plugins.cgc.SimStateCGC attribute), 273
- state (angr.state_plugins.concrete.Concrete attribute), 294
- state (angr.state_plugins.debug_variables.SimDebugVariablePlugin attribute), 309
- state (angr.state_plugins.filesystem.SimConcreteFilesystem attribute), 253
- state (angr.state_plugins.filesystem.SimFilesystem attribute), 251
- state (angr.state_plugins.filesystem.SimHostFilesystem attribute), 254
- state (angr.state_plugins.filesystem.SimMount attribute), 251
- state (angr.state_plugins.gdb.GDB attribute), 271
- state (angr.state_plugins.globals.SimStateGlobals attribute), 279
- state (angr.state_plugins.heap.heap_base.SimHeapBase attribute), 298
- state (angr.state_plugins.heap.heap_brk.SimHeapBrk attribute), 300
- state (angr.state_plugins.heap.heap_freelist.SimHeapFreelist attribute), 301
- state (angr.state_plugins.heap.heap_libc.SimHeapLibc attribute), 302
- state (angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc attribute), 306
- state (angr.state_plugins.history.SimStateHistory attribute), 270
- state (angr.state_plugins.inspect.SimInspector attribute), 236
- state (angr.state_plugins.javavm_classloader.SimJavaVmClassLoader attribute), 296
- state (angr.state_plugins.jni_references.SimStateJNIReferences attribute), 297
- state (angr.state_plugins.libc.SimStateLibc attribute), 240
- state (angr.state_plugins.light_registers.SimLightRegisters attribute), 267
- state (angr.state_plugins.log.SimStateLog attribute), 263
- state (angr.state_plugins.loop_data.SimStateLoopData attribute), 292
- state (angr.state_plugins.plugin.SimStatePlugin attribute), 232
- state (angr.state_plugins.posix.PosixDevFS attribute), 242
- state (angr.state_plugins.posix.PosixProcFS attribute), 243
- state (angr.state_plugins.posix.SimSystemPosix attribute), 248
- state (angr.state_plugins.preconstrainer.SimStatePreconstrainer attribute), 284
- state (angr.state_plugins.scratch.SimStateScratch attribute), 280
- state (angr.state_plugins.solver.SimSolver attribute), 260
- state (angr.state_plugins.symbolizer.SimSymbolizer attribute), 307
- state (angr.state_plugins.trace_additions.ChallRespInfo attribute), 276
- state (angr.state_plugins.trace_additions.ZenPlugin attribute), 278
- state (angr.state_plugins.uc_manager.SimUCManager attribute), 280
- state (angr.state_plugins.unicorn_engine.Unicorn attribute), 291
- state (angr.state_plugins.view.SimMemView attribute), 312
- state (angr.state_plugins.view.SimRegNameView attribute), 310
- state (angr.storage.file.SimFile attribute), 319
- state (angr.storage.file.SimFileBase attribute), 317
- state (angr.storage.file.SimFileDescriptor attribute), 329
- state (angr.storage.file.SimFileDescriptorBase attribute), 327
- state (angr.storage.file.SimFileDescriptorDuplex attribute), 332
- state (angr.storage.file.SimFileStream attribute), 321
- state (angr.storage.file.SimPackets attribute), 323
- state (angr.storage.file.SimPacketsSlots attribute), 333
- state (angr.storage.file.SimPacketsStream attribute), 325
- state (angr.storage.memory_mixins.AbstractMemory attribute), 339

Index 1055

`state(angr.storage.memory_mixins.underconstrained_mixin.UnwrappedMemoryMixin attribute), 342`
`state(angr.storage.memory_mixins.unwrapper_mixin.UnwrappedMemoryMixin attribute), 348`
`state_blank() (angr.SimOS method), 168`
`state_blank() (angr.simos.cgc.SimCGC method), 887`
`state_blank() (angr.simos.javavm.SimJavaVM method), 890`
`state_blank() (angr.simos.linux.SimLinux method), 886`
`state_blank() (angr.simos.simos.SimOS method), 884`
`state_blank() (angr.simos.windows.SimWindows method), 889`
`state_call() (angr.SimOS method), 169`
`state_call() (angr.simos.javavm.SimJavaVM method), 890`
`state_call() (angr.simos.simos.SimOS method), 884`
`state_entry() (angr.SimOS method), 168`
`state_entry() (angr.simos.cgc.SimCGC method), 887`
`state_entry() (angr.simos.javavm.SimJavaVM method), 890`
`state_entry() (angr.simos.linux.SimLinux method), 886`
`state_entry() (angr.simos.simos.SimOS method), 884`
`state_entry() (angr.simos.windows.SimWindows method), 889`
`state_full_init() (angr.SimOS method), 168`
`state_full_init() (angr.simos.linux.SimLinux method), 886`
`state_full_init() (angr.simos.simos.SimOS method), 884`
`state_priority() (angr.exploration_techniques.Spiller static method), 402`
`state_priority() (angr.exploration_techniques.spiller.Spiller static method), 412`
`StateHierarchy (class in angr), 180`
`StateHierarchy (class in angr.state_hierarchy), 389`
`statement_location() (angr.analyses.decompiler.region_simplifiers.expr_folding.ExpressionLocation method), 718`
`StatementLocation (class in angr.analyses.decompiler.region_simplifiers.expr_folding.ExpressionLocation), 718`
`statements(angr.analyses.decompiler.structured_codegen.C generator attribute), 729`
`statements(angr.analyses.decompiler.structured_codegen.C generator attribute), 729`
`statements(angr.engines.pcode.lifter.IRSB property), 439`
`StateOption (class in angr.sim_state_options), 228`
`Static(angr.analyses.disassembly.SootExpressionInvoke attribute), 858`
`STATIC(angr.simos.windows.SecurityCookieInit attribute), 888`
`StaticFindMixin (class in angr.storage.memory_mixins.regioned_memory.static_find_mixin), 371`
`StaticHooker(angr.analyses.analysis.KnownAnalysesPlugin attribute), 623`
`StaticHooker (class in angr.analyses.static_hooker), 868`
`StaticObjectFinder (class in angr.analyses.find_objects_static), 855`
`status() (angr.knowledge_plugins.sync.sync_controller.SyncController method), 612`
`step() (angr.distributed.worker.BadStatesDropper method), 909`
`step() (angr.distributed.worker.ExplorationStatusNotifier method), 910`
`step() (angr.exploration_techniques.DFS method), 398`
`step() (angr.exploration_techniques.dfs.DFS method), 408`
`step() (angr.exploration_techniques.Director method), 400`
`step() (angr.exploration_techniques.director.Director method), 420`
`step() (angr.exploration_techniques.driller_core.DrillerCore method), 417`
`step() (angr.exploration_techniques.DrillerCore method), 393`
`step() (angr.exploration_techniques.ExplorationTechnique method), 390`
`step() (angr.exploration_techniques.Explorer method), 397`
`step() (angr.exploration_techniques.explorer.Explorer method), 409`
`step() (angr.exploration_techniques.LengthLimiter method), 398`
`step() (angr.exploration_techniques.lengthlimiter.LengthLimiter method), 410`
`step() (angr.exploration_techniques.manual_mergepoint.ManualMergepoint method), 410`
`step() (angr.exploration_techniques.ManualMergepoint method), 402`
`step() (angr.exploration_techniques.memory_watcher.MemoryWatcher method), 426`
`step() (angr.exploration_techniques.MemoryWatcher method), 406`
`step() (angr.exploration_techniques.Spiller method), 402`
`step() (angr.exploration_techniques.spiller.Spiller method), 412`
`step() (angr.exploration_techniques.stochastic.StochasticSearch method), 423`
`step() (angr.exploration_techniques.StochasticSearch`

method), 403

step() (angr.exploration_techniques.Suggestions method), 407

step() (angr.exploration_techniques.suggestions.Suggestions method), 427

step() (angr.exploration_techniques.Symbion method), 404

step() (angr.exploration_techniques.symbion.Symbion method), 425

step() (angr.exploration_techniques.Threading method), 398

step() (angr.exploration_techniques.threading.Threading method), 413

step() (angr.exploration_techniques.Timeout method), 407

step() (angr.exploration_techniques.timeout.Timeout method), 408

step() (angr.exploration_techniques.Tracer method), 396

step() (angr.exploration_techniques.tracer.Tracer method), 416

step() (angr.exploration_techniques.unique.UniqueSearch method), 424

step() (angr.exploration_techniques.UniqueSearch method), 404

step() (angr.ExplorationTechnique method), 178

step() (angr.sim_manager.SimulationManager method), 385

step() (angr.sim_state.SimState method), 226

step() (angr.SimState method), 183

step() (angr.SimulationManager method), 174

step_back() (angr.analyses.reaching_definitions.call_trace.CallTrace method), 794

step_state() (angr.exploration_techniques.ExplorationTechnique method), 797

step_state() (angr.exploration_techniques.Slicecutor method), 392

step_state() (angr.exploration_techniques.slicecutor.Slicecutor method), 418

step_state() (angr.exploration_techniques.Symbion method), 405

step_state() (angr.exploration_techniques.symbion.Symbion method), 425

step_state() (angr.exploration_techniques.Tracer method), 396

step_state() (angr.exploration_techniques.tracer.Tracer method), 416

step_state() (angr.exploration_techniques.Veritesting method), 399

step_state() (angr.exploration_techniques.veritesting.Veritesting method), 414

step_state() (angr.ExplorationTechnique method), 179

step_state() (angr.sim_manager.SimulationManager method), 386

step_state() (angr.SimulationManager method), 175

stmt (angr.analyses.decompiler.structured_codegen.c.CUnsupportedStatement attribute), 734

stmt_classes (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization attribute), 715

stmt_classes (angr.analyses.decompiler.peephole_optimizations.base.PeepholeOptimization attribute), 715

stmt_comments (angr.angrdb.models.DbStructuredCode attribute), 680

stmt_idx (angr.analyses.cfg.cfg_fast.FunctionEdge attribute), 654

stmt_idx (angr.analyses.decompiler.clinic.DataRefDesc attribute), 696

stmt_idx (angr.analyses.decompiler.region_simplifiers.expr_folding.Expression attribute), 718

stmt_idx (angr.analyses.decompiler.region_simplifiers.expr_folding.Statement attribute), 718

stmt_idx (angr.analyses.disassembly.SootStatement property), 858

stmt_idx (angr.code_location.CodeLocation attribute), 617

stmt_idx (angr.engines.UberEngine attribute), 427

stmt_idx (angr.errors.SimError attribute), 905

stmt_idx (angr.knowledge_plugins.cfg.indirect_jump.IndirectJump attribute), 551

stmt_idx (angr.knowledge_plugins.cfg.IndirectJump attribute), 532

stmt_idx (angr.knowledge_plugins.xrefs.xref.XRef attribute), 614

stmt_idx (angr.state_plugins.unicorn_engine.VEXStmtDetails attribute), 285

stmt_observe() (angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions method), 777

stmt_observe() (angr.analyses.reaching_definitions.ReachingDefinitions method), 777

stmts (angr.analyses.decompiler.structured_codegen.c.CMultiStatementExpression attribute), 740

stmts (angr.codenode.SootBlockNode attribute), 883

stmts_to_instrument (angr.analyses.cfg.indirect_jump_resolvers.jumptable.JumpTable attribute), 668

stmts_used (angr.engines.pcode.lifter.IRSB property), 439

StochasticSearch (class in angr.exploration_techniques), 403

StochasticSearch (class in angr.exploration_techniques.stochastic), 423

STOP (class in angr.state_plugins.unicorn_engine), 286

stop() (angr.distributed.server.Server method), 909

stop() (angr.Server method), 210

STOP_ERROR (angr.state_plugins.unicorn_engine.STOP attribute), 286

STOP_EXECNONE (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_HLT (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 stop_message (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 STOP_NODECODE (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_NORMAL (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_NOSTART (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 stop_reason (*angr.state_plugins.unicorn_engine.StopDetails* attribute), 287
 STOP_SEGFAULT (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_STOPPOINT (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_BLOCK_EXIT_CONDITION (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_BLOCK_EXIT_TARGET (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_PC (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_READ_ADDR (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_READ_SYMBOLIC_TRACKING_DISABLED (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYMBOLIC_WRITE_ADDR (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYSCALL (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_SYSCALL_ARM (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 STOP_UNKNOWN_MEMORY_WRITE_SIZE (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 STOP_UNSUPPORTED_EXPR_GETI (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_EXPR_UNKNOWN (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 STOP_UNSUPPORTED_STMT_CAS (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_DIRTY (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_LLSC (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_LOADG (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_PUTI (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_STOREG (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_UNSUPPORTED_STMT_UNKNOWN (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_VEX_LIFT_FAILED (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_X86_CPUID (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 STOP_ZERO_DIV (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 STOP_ZEROPAGE (*angr.state_plugins.unicorn_engine.STOP* attribute), 286
 StopDetails (class in *angr.state_plugins.unicorn_engine*), 287
 stopped (*angr.distributed.server.Server* property), 909
 stopped (*angr.Server* property), 211
 storage (*angr.state_plugins.sim_action.SimActionData* property), 468
 Store (class in *angr.analyses.typehoon.typevars*), 841
 store() (*angr.analyses.stack_pointer_tracker.StackPointerTrackerState* method), 822
 store() (*angr.sim_type.SimCppClass* method), 519
 store() (*angr.sim_type.SimStruct* method), 518
 store() (*angr.sim_type.SimTypeArray* method), 514
 store() (*angr.sim_type.SimTypeBool* method), 512
 store() (*angr.sim_type.SimTypeChar* method), 512
 store() (*angr.sim_type.SimTypeFloat* method), 517
 store() (*angr.sim_type.SimTypeNum* method), 511
 store() (*angr.sim_type.SimTypeNumOffset* method), 520
 store() (*angr.sim_type.SimTypeReg* method), 511
 store() (*angr.sim_type.SimTypeWideChar* method), 512
 store() (*angr.state_plugins.debug_variables.SimDebugVariable* method), 308
 store() (*angr.state_plugins.light_registers.SimLightRegisters* method), 267
 store() (*angr.state_plugins.view.SimMemView* method), 314
 store() (*angr.storage.memory_mixins.actions_mixin.ActionsMixinHigh* method), 342
 store() (*angr.storage.memory_mixins.actions_mixin.ActionsMixinLow* method), 343

store() (angr.storage.memory_mixins.address_concretization_mixin.AddressConcretizationMixin.javavm_memory.javavm_memory_ method), 346

store() (angr.storage.memory_mixins.bvv_conversion_mixin.BvvConversionMixin.plugins.scratch.SimStateScratch method), 341

store() (angr.storage.memory_mixins.clouseau_mixin.InspectMixin.inspectable() (angr.analyses.decompiler.optimization_passes.engine method), 346

store() (angr.storage.memory_mixins.conditional_store_mixin.ConditionalStoreMixin.conditional_store_mixin.RegionObject attribute), 347

store() (angr.storage.memory_mixins.convenient_mapping_mixin.ConvenientMappingMixin.convenient_mapping_mixin.Region), 348

store() (angr.storage.memory_mixins.dirty_addrs_mixin.DirtyAddrsMixin.dirty_addrs_mixin.StoreHook (class in angr.analyses.cfg.indirect_jump_resolvers.jumptable), 344

store() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.javavm_memory_mixin.simplifiers.expr_folding), method), 376

store() (angr.storage.memory_mixins.keyvalue_memory_mixin.KeyValueMemoryMixin.keyvalue_memory_mixin.Structured_codegen.c.CConst static method), 376

store() (angr.storage.memory_mixins.MemoryMixin.Strict(angr.exploration_techniques.tracer.TracingMode attribute), 336

store() (angr.storage.memory_mixins.name_resolution_mixin.NameResolutionMixin.name_resolution_mixin.Lifter attribute), 340

store() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin.paged_memory_mixin.Lifter attribute), 353

store() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin.paged_memory_mixin.PcodeLifter attribute), 361

store() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin.paged_memory_mixin.PcodeLifter attribute), 362

store() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin.paged_memory_mixin.PcodeLifter attribute), 349

store() (angr.storage.memory_mixins.paged_memory.paged_memory_mixin.PagedMemoryMixin.paged_memory_mixin.PcodeLifter attribute), 364

store() (angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemoryMixin.regioned_memory_mixin.RegionedMemoryMixin attribute), 372

store() (angr.storage.memory_mixins.regioned_memory.regioned_memory_mixin.RegionedMemoryMixin.regioned_memory_mixin.RegionedMemoryMixin attribute), 367

store() (angr.storage.memory_mixins.simple_interface_mixin.SimpleInterfaceMixin.simple_interface_mixin.SimpleInterfaceMixin attribute), 342

store() (angr.storage.memory_mixins.simplification_mixin.SimplificationMixin.simplification_mixin.SimplificationMixin attribute), 347

store() (angr.storage.memory_mixins.size_resolution_mixin.SizeResolutionMixin.size_resolution_mixin.SizeResolutionMixin attribute), 344

store() (angr.storage.memory_mixins.size_resolution_mixin.SizeResolutionMixin.size_resolution_mixin.SizeResolutionMixin attribute), 343

store() (angr.storage.memory_mixins.slotted_memory.slotted_memory_mixin.SlottedMemoryMixin.slotted_memory_mixin.SlottedMemoryMixin attribute), 375

store() (angr.storage.memory_mixins.underconstrained_mixin.UnderconstrainedMixin.underconstrained_mixin.UnderconstrainedMixin attribute), 342

store() (angr.storage.memory_mixins.unwrapper_mixin.UnwrapperMixin.unwrapper_mixin.UnwrapperMixin attribute), 347

store() (angr.vaults.Vault method), 621

store() (angr.vaults.VaultDirShelf method), 622

store_array_element() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.javavm_memory_mixin.javavm_memory_mixin attribute), 376

store_array_elements() (angr.storage.memory_mixins.javavm_memory.javavm_memory_mixin.javavm_memory_mixin.javavm_memory_mixin attribute), 376

(*angr.calling_conventions.SimCCMicrosoftCdecl* attribute), 493

struct_type (*angr.analyses.decompiler.structured_codegen.SubType* attribute), 735

StructMode (class in *angr.state_plugins.view*), 314

structured_code (*angr.angrdb.models.DbKnowledgeBase* attribute), 679

structured_code (*angr.knowledge_base.knowledge_base.KnowledgeBase* attribute), 523

structured_code (*angr.KnowledgeBase* attribute), 211

structured_node_is_simple_return() (in module *angr.analyses.decompiler.utils*), 747

StructuredCodeGenerator (in module *angr.analyses.decompiler.structured_codegen.c*), 744

StructuredCodeManager (class in *angr.knowledge_plugins.structured_code.managers*), 574

StructuredCodeManagerSerializer (class in *angr.angrdb.serializers.structured_code*), 685

structurer_class_from_name() (in module *angr.analyses.decompiler.structuring*), 686

StructurerBase (class in *angr.analyses.decompiler.structuring.structurer_base*), 691

STRUCTURING (*angr.analyses.decompiler.optimization_passes* attribute), 710

STRUCTURING (*angr.analyses.decompiler.optimization_passes* attribute), 705

StructuringOptimizationPass (class in *angr.analyses.decompiler.optimization_passes.optimization_passes*), 706

Sub (*angr.engines.light.data.ArithmeticExpression* attribute), 754

Sub (class in *angr.analyses.typehoon.typevars*), 839

sub_graph (*angr.analyses.data_dep.data_dependency_analysis* property), 876

sub_type (*angr.analyses.typehoon.typevars.Subtype* attribute), 838

subgraph() (*angr.knowledge_plugins.functions.function.Function* method), 561

subgraph_between_nodes() (in module *angr.utils.graph*), 896

subject (*angr.analyses.reaching_definitions.reaching_definitions* property), 798

subject (*angr.analyses.reaching_definitions.ReachingDefinitions* property), 777

Subject (class in *angr.analyses.reaching_definitions.subjects*), 817

SubjectType (class in *angr.analyses.reaching_definitions.subjects*), 817

SubN (class in *angr.analyses.typehoon.typevars*), 841

subscribe_actions()

(*angr.state_plugins.history.SimStateHistory* method), 269

SubType (class in *angr.analyses.typehoon.typevars*), 838

successor_func() (*angr.annocfg.AnnotatedCFG* method), 882

successors (*angr.analyses.decompiler.graph_region.GraphRegion* attribute), 703

successors (*angr.engines.UberEngine* attribute), 428

successors (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* property), 548

successors (*angr.knowledge_plugins.cfg.CFGNode* property), 529

successors() (*angr.analyses.forward_analysis.visitors.call_graph.CallGraph* method), 626

successors() (*angr.analyses.forward_analysis.visitors.function_graph.FunctionGraph* method), 627

successors() (*angr.analyses.forward_analysis.visitors.graph.GraphVisitor* method), 628

successors() (*angr.analyses.forward_analysis.visitors.loop.LoopVisitor* method), 630

successors() (*angr.analyses.forward_analysis.visitors.single_node_graph.SingleNodeGraph* method), 631

successors() (*angr.codenode.CodeNode* method), 883

successors() (*angr.exploration_techniques.Bucketizer* method), 406

successors() (*angr.exploration_techniques.Bucketizer* method), 427

successors() (*angr.exploration_techniques.ExplorationTechnique* method), 391

successors() (*angr.exploration_techniques.local_loop_seer.LocalLoopSeer* method), 423

successors() (*angr.exploration_techniques.LocalLoopSeer* method), 407

successors() (*angr.exploration_techniques.loop_seer.LoopSeer* method), 422

successors() (*angr.exploration_techniques.LoopSeer* method), 394

successors() (*angr.exploration_techniques.Oppologist* method), 399

successors() (*angr.exploration_techniques.oppologist.Oppologist* method), 421

successors() (*angr.exploration_techniques.Slicecutor* method), 393

successors() (*angr.exploration_techniques.slicecutor.Slicecutor* method), 418

successors() (*angr.exploration_techniques.Threading* method), 398

successors() (*angr.exploration_techniques.threading.Threading* method), 413

successors() (*angr.ExplorationTechnique* method), 179

successors() (*angr.factory.AngrObjectFactory* method), 216

successors() (*angr.sim_manager.SimulationManager* method), 216

method), 386

successors() (angr.SimulationManager method), 175

successors_and_jumpkinds() (angr.knowledge_plugins.cfg.cfg_node.CFGNode method), 548

successors_and_jumpkinds() (angr.knowledge_plugins.cfg.CFGNode method), 529

SuccessorsMixin (class in angr.engines.engine), 428

Suggestions (class in angr.exploration_techniques), 407

Suggestions (class in angr.exploration_techniques.suggestions), 427

super_type (angr.analyses.typehoon.typevars.Subtype attribute), 838

SUPPORTS_CONCRETE_LOAD (angr.storage.memory_mixins.MemoryMixin attribute), 336

SUPPORTS_CONCRETE_LOAD (angr.storage.memory_mixins.paged_memory.pages.paged_memory_mixin.PagedMemoryMixin attribute), 353

SUPPORTS_CONCRETE_LOAD (angr.storage.memory_mixins.paged_memory.pages.ultra_paged_memory_mixin.UltraPagedMemoryMixin attribute), 364

switch (angr.analyses.decompiler.structured_codegen.c.CSwitch attribute), 732

switch_expr (angr.analyses.decompiler.structuring.structurer_nodes.SwitchExpr attribute), 690

switch_extract_cmp_bounds() (in module angr.analyses.decompiler.utils), 745

switch_variable (angr.analyses.decompiler.structuring.structurer_nodes.SwitchVariable attribute), 691

SwitchCaseNode (class in angr.analyses.decompiler.structuring.structurer_nodes), 690

SwitchCaseRegion (class in angr.analyses.decompiler.region_simplifiers.switch_case_region.SwitchCaseRegion), 722

SwitchClusterFinder (class in angr.analyses.decompiler.region_simplifiers.switch_cluster_finder.SwitchClusterFinder), 723

SwitchClusterReplacer (class in angr.analyses.decompiler.region_simplifiers.switch_cluster_replacer.SwitchClusterReplacer), 723

SwitchExpressionSimplifier (class in angr.analyses.decompiler.region_simplifiers.switch_expr_simplifier.SwitchExpressionSimplifier), 725

Symbion (class in angr.exploration_techniques), 404

Symbion (class in angr.exploration_techniques.symbion), 425

symbol (angr.analyses.reaching_definitions.function_handlers.symbol.Symbol attribute), 804

symbol (angr.analyses.reaching_definitions.FunctionCallData attribute), 791

symbol (angr.knowledge_plugins.functions.function.Function property), 559

symbol_hooked_by() (angr.Project method), 166

symbol_hooked_by() (angr.project.Project method), 215

symbol_name (angr.analyses.reassembler.NotypeLabel property), 861

symbol_name (angr.analyses.reassembler.ObjectLabel property), 861

symbolic (angr.analyses.reaching_definitions.MemoryLocation property), 773

symbolic (angr.engines.light.data.RegisterOffset property), 755

symbolic (angr.knowledge_plugins.key_definitions.atoms.MemoryLocation property), 592

SYMBOLIC (angr.simos.windows.SecurityCookieInit attribute), 888

symbolic (angr.storage.memory_object.SimMemoryObject property), 334

symbolic() (angr.knowledge_plugins.solvers.SolverMixin method), 262

symbolic_stop_reasons (angr.knowledge_plugins.unicorn_engine.STOP attribute), 287

symbolize_vex_stmts (angr.state_plugins.unicorn_engine.BlockDetails attribute), 285

symbolize_vex_stmts (angr.state_plugins.unicorn_engine.BlockDetails attribute), 286

SymbolicMergeMixin (class in angr.analyses.reassembler.symbolic_merge_mixin.SymbolicMergeMixin), 343

symbolize() (angr.analyses.reassembler.Reassembler method), 867

symbolized (angr.analyses.reassembler.Operand property), 862

SymbolManager (class in angr.analyses.reassembler), 861

sympy_expr_to_claripy_ast() (angr.analyses.decompiler.condition_processor.ConditionProcessor static method), 699

sync() (angr.state_plugins.concrete.Concrete method), 334

SyncController (class in angr.knowledge_plugins.sync.sync_controller), 334

syscall (angr.analyses.cfg.cfg_fast.CFGJob attribute), 656

syscall (angr.analyses.cfg.cfg_fast.FunctionCallEdge attribute), 654

syscall (angr.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 550

syscall (angr.knowledge_plugins.cfg.CFGNode attribute), 550

- `attribute`), 530
 - `syscall()` (*angr.SimOS* method), 169
 - `syscall()` (*angr.simos.simos.SimOS* method), 885
 - `syscall()` (*angr.simos.userland.SimUserland* method), 888
 - `syscall_abi()` (*angr.SimOS* method), 169
 - `syscall_abi()` (*angr.simos.linux.SimLinux* method), 886
 - `syscall_abi()` (*angr.simos.simos.SimOS* method), 885
 - `syscall_abi()` (*angr.simos.userland.SimUserland* method), 888
 - `syscall_cc()` (*angr.SimOS* method), 169
 - `syscall_cc()` (*angr.simos.simos.SimOS* method), 885
 - `syscall_cc()` (*angr.simos.userland.SimUserland* method), 887
 - `SYSCALL_ERRNO_START` (*angr.calling_conventions.SimCCN64LinuxSyscall* attribute), 500
 - `SYSCALL_ERRNO_START` (*angr.calling_conventions.SimCCO32LinuxSyscall* attribute), 500
 - `SYSCALL_ERRNO_START` (*angr.calling_conventions.SimCCPowerPC64LinuxSyscall* attribute), 502
 - `SYSCALL_ERRNO_START` (*angr.calling_conventions.SimCCPowerPCLinuxSyscall* attribute), 501
 - `SYSCALL_ERRNO_START` (*angr.calling_conventions.SimCCSyscall* attribute), 495
 - `syscall_from_addr()` (*angr.SimOS* method), 169
 - `syscall_from_addr()` (*angr.simos.simos.SimOS* method), 885
 - `syscall_from_addr()` (*angr.simos.userland.SimUserland* method), 888
 - `syscall_from_number()` (*angr.SimOS* method), 169
 - `syscall_from_number()` (*angr.simos.simos.SimOS* method), 885
 - `syscall_from_number()` (*angr.simos.userland.SimUserland* method), 888
 - `syscall_hook()` (in module *angr.state_plugins.trace_additions*), 274
 - `syscall_name` (*angr.knowledge_plugins.cfg.cfg_node.CFGNode* attribute), 549
 - `syscall_name` (*angr.knowledge_plugins.cfg.CFGNode* attribute), 530
 - `syscall_num()` (*angr.calling_conventions.SimCCAArch64LinuxSyscall* static method), 498
 - `syscall_num()` (*angr.calling_conventions.SimCCAMD64LinuxSyscall* static method), 496
 - `syscall_num()` (*angr.calling_conventions.SimCCAMD64WindowsSyscall* static method), 497
 - `syscall_num()` (*angr.calling_conventions.SimCCARMLinuxSyscall* static method), 498
 - `syscall_num()` (*angr.calling_conventions.SimCCN64LinuxSyscall* static method), 500
 - `syscall_num()` (*angr.calling_conventions.SimCCO32LinuxSyscall* static method), 500
 - `syscall_num()` (*angr.calling_conventions.SimCCPowerPC64LinuxSyscall* static method), 502
 - `syscall_num()` (*angr.calling_conventions.SimCCPowerPCLinuxSyscall* static method), 501
 - `syscall_num()` (*angr.calling_conventions.SimCCRISCV64LinuxSyscall* static method), 499
 - `syscall_num()` (*angr.calling_conventions.SimCCS390XLinuxSyscall* static method), 503
 - `syscall_num()` (*angr.calling_conventions.SimCCSyscall* static method), 495
 - `syscall_num()` (*angr.calling_conventions.SimCCX86LinuxSyscall* static method), 495
 - `syscall_num()` (*angr.calling_conventions.SimCCX86WindowsSyscall* static method), 495
 - `SyscallNode` (class in *angr.codenode*), 883
- ## T
- `T` (*angr.sim_state.SimState* attribute), 226
 - `T` (*angr.SimState* attribute), 182
 - `tag` (*angr.analyses.cfg.cfg_base.CFGBase* attribute), 649
 - `tag` (*angr.analyses.cfg.cfg_emulated.CFGEmulated* attribute), 645
 - `tag` (*angr.analyses.cfg.cfg_fast.CFGFast* attribute), 657
 - `tag` (*angr.analyses.typehoon.simple_solver.ConstraintGraphNode* attribute), 835
 - `Tag` (class in *angr.knowledge_plugins.key_definitions.tag*), 608
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CAssignment* attribute), 732
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CBinaryOp* attribute), 737
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CBreak* attribute), 732
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CConstant* attribute), 739
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CContinue* attribute), 732
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CDoWhileLoop* attribute), 730
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CFakeVariable* attribute), 735
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CForLoop* attribute), 731
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CFunctionCall* attribute), 733
 - `tags` (*angr.analyses.decompiler.structured_codegen.c.CGoto* attribute), 734

test_unsupported_overlap() (angr.knowledge_plugins.debug_variables.DebugVariables method), 572

text (angr.analyses.decompiler.structured_codegen.c.CArray type property), 741

Threading (class in angr.exploration_techniques), 397

Threading (class in angr.exploration_techniques.threading), 413

THUMB (angr.analyses.cfg.cfg_fast.ARMDecodingMode attribute), 652

thumb (angr.Block attribute), 170

thumb (angr.block.Block attribute), 221

thumb (angr.block.DisassemblerBlock attribute), 220

thumb (angr.codenode.CodeNode attribute), 883

thumb (angr.engines.pcode.lifter.PcodeDisassemblerBlock attribute), 435

thumb (angr.knowledge_plugins.cfg.cfg_node.CFGNode attribute), 548

thumb (angr.knowledge_plugins.cfg.CFGNode attribute), 528

thumb (angr.sim_state.SimState property), 228

thumb (angr.SimState property), 184

tidy_data_references() (angr.knowledge_plugins.cfg.cfg_model.CFGModel method), 544

tidy_data_references() (angr.knowledge_plugins.cfg.CFGModel method), 537

timed_function() (in module angr.state_plugins.solver), 254

Timeout (class in angr.exploration_techniques), 407

Timeout (class in angr.exploration_techniques.timeout), 408

timestamp (angr.exploration_techniques.spiller_db.PickledState attribute), 413

timethis() (in module angr.utils.timing), 901

TLSMixin (class in angr.engines.engine), 428

TLSPROPERTY (class in angr.engines.engine), 428

Tmp (angr.analyses.data_dep.dep_nodes.DepNodeTypes attribute), 877

tmp (angr.analyses.propagator.vex_vars.VEXTmp attribute), 757

TMP (angr.analyses.reaching_definitions.AtomKind attribute), 770

TMP (angr.knowledge_plugins.key_definitions.atoms.AtomKind attribute), 588

TMP (angr.state_plugins.sim_action.SimAction attribute), 467

Tmp (class in angr.analyses.cfg.indirect_jump_resolvers.jump_target_finder), 667

Tmp (class in angr.analyses.reaching_definitions), 773

Tmp (class in angr.knowledge_plugins.key_definitions.atoms), 590

tmp_deps (angr.state_plugins.sim_action.SimAction property), 467

tmp_deps (angr.state_plugins.sim_action.SimActionData property), 468

tmp_expr (angr.state_plugins.scratch.SimStateScratch method), 280

tmp_id (angr.sim_variable.SimTemporaryVariable attribute), 505

tmp_idx (angr.analyses.reaching_definitions.Tmp attribute), 773

tmp_idx (angr.knowledge_plugins.key_definitions.atoms.Tmp attribute), 591

tmp_idx (angr.knowledge_plugins.key_definitions.definition.DefinitionMatch attribute), 593

tmp_uses (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

tmp_uses (angr.analyses.reaching_definitions.rd_state.ReachingDefinitions property), 813

tmp_uses (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783

tmp_uses (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

tmp_uses (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 578

TmpDepNode (class in angr.analyses.data_dep.dep_nodes), 878

tmps (angr.analyses.reaching_definitions.LiveDefinitions attribute), 762

tmps (angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState property), 813

tmps (angr.analyses.reaching_definitions.ReachingDefinitionsState property), 783

tmps (angr.engines.UberEngine attribute), 428

tmps (angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions attribute), 598

tmps (angr.knowledge_plugins.key_definitions.LiveDefinitions attribute), 577

TmpvarFinder (class in angr.analyses.propagator.tmpvar_finder), 760

to_acyclic_graph() (in module angr.utils.graph), 896

to_ail_supergraph() (in module angr.analyses.decompiler.utils), 745

to_bits (angr.analyses.typehoon.typevars.ConvertTo attribute), 841

to_bits (angr.analyses.typehoon.typevars.ReinterpretAs attribute), 842

to_claripy() (angr.state_plugins.sim_action_object.SimActionObject method), 469

to_codenode() (angr.knowledge_plugins.cfg.cfg_node.CFGNode method), 549

to_codenode() (angr.knowledge_plugins.cfg.CFGNode method), 530

to_engine() (angr.engines.concrete.SimEngineConcrete method), 433

to_outside(*angr.analyses.cfg.cfg_fast.FunctionTransitionEdge* attribute), 654
 to_string() (*angr.knowledge_plugins.xrefs.xref_types.XRefType* static method), 615
 to_type(*angr.analyses.typehoon.typevars.ReinterpretAs* attribute), 841
 to_valueset() (*angr.storage.memory_mixins.regioned_memory.regioned_memory.AddressWrapper* method), 369
 TOLOWER_LOC_ARRAY (*angr.state_plugins.libc.SimStateLibc* attribute), 238
 top (*angr.state_plugins.callstack.CallStack* property), 265
 Top (*class in angr.analyses.propagator.values*), 756
 top() (*angr.analyses.reaching_definitions.LiveDefinitions* static method), 763
 top() (*angr.analyses.reaching_definitions.rd_state.ReachingDefinitionsState* method), 811
 top() (*angr.analyses.reaching_definitions.ReachingDefinitionsState* method), 781
 top() (*angr.analyses.variable_recovery.variable_recovery_base.VariableRecoveryBase* static method), 825
 top() (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* static method), 599
 top() (*angr.knowledge_plugins.key_definitions.LiveDefinitions* static method), 578
 TopCheckerMixin (*class in angr.analyses.propagator.top_checker_mixin*), 761
 TopMergerMixin (*class in angr.storage.memory_mixins.top_merger_mixin*), 352
 TopType (*class in angr.analyses.typehoon.typeconsts*), 843
 TOUPPER_LOC_ARRAY (*angr.state_plugins.libc.SimStateLibc* attribute), 238
 traceback (*angr.knowledge_plugins.cfg.cfg_node.CFGNodeCreationFailure* attribute), 547
 traceflags (*angr.engines.pcode.lifter.Lifter* attribute), 440
 traceflags (*angr.engines.pcode.lifter.PcodeLifter* attribute), 442
 Tracer (*class in angr.exploration_techniques*), 394
 Tracer (*class in angr.exploration_techniques.tracer*), 415
 TracerDesyncError, 414
 TracerEnvironmentError, 905
 TracingMode (*class in angr.exploration_techniques.tracer*), 414
 track_tmps (*angr.analyses.reaching_definitions.LiveDefinitions* attribute), 762
 track_tmps (*angr.knowledge_plugins.key_definitions.live_definitions.LiveDefinitions* attribute), 598
 track_tmps (*angr.knowledge_plugins.key_definitions.LiveDefinitions* attribute), 577
 transition_graph (*angr.knowledge_plugins.functions.function.Function* attribute), 556
 transition_graph (*angr.knowledge_plugins.functions.soot_function.SootFunction* attribute), 563
 transition_graph_ex() (*angr.knowledge_plugins.functions.function.Function* method), 818
 transitions (*angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink* property), 819
 transitions_as_tuples (*angr.analyses.cfg_slice_to_sink.cfg_slice_to_sink.CFGSliceToSink* property), 819
 transitive_closure() (*angr.analyses.reaching_definitions.dep_graph.DepGraph* method), 800
 TRANSITABLE (*class in angr.calling_conventions.AllocHelper* method), 485
 TRANSIT_RECORD (*class in angr.state_plugins.unicorn_engine*), 284
 TrueTypeLibRes (*class in angr.state_plugins.history*), 270
 trim() (*angr.state_plugins.history.SimStateHistory* method), 268
 true_node (*angr.analyses.decompiler.structuring.structurer_nodes.ConditionNode* attribute), 688
 Truncation (*angr.analyses.cfg.indirect_jump_resolvers.jumptable.Address* attribute), 666
 try_unpack_const() (*angr.engines.light.data.ArithmeticExpression* static method), 755
 ty_ptr() (*angr.sim_procedure.SimProcedure* method), 473
 ty_ptr() (*angr.SimProcedure* method), 160
 tyenv (*angr.engines.pcode.lifter.IRSB* property), 438
 type (*angr.analyses.data_dep.dep_nodes.BaseDepNode* property), 877
 type (*angr.analyses.decompiler.structured_codegen.c.CBinaryOp* property), 738
 type (*angr.analyses.decompiler.structured_codegen.c.CConstant* property), 739
 type (*angr.analyses.decompiler.structured_codegen.c.CDirtyExpression* property), 740
 type (*angr.analyses.decompiler.structured_codegen.c.CExpression* property), 729
 type (*angr.analyses.decompiler.structured_codegen.c.CFakeVariable* property), 735
 type (*angr.analyses.decompiler.structured_codegen.c.CFunctionCall* property), 733
 type (*angr.analyses.decompiler.structured_codegen.c.CIndexedVariable* property), 736
 type (*angr.analyses.decompiler.structured_codegen.c.CITE* property), 740
 type (*angr.analyses.decompiler.structured_codegen.c.CMultiStatementExpression* property), 740
 type (*angr.analyses.decompiler.structured_codegen.c.CRegister* property), 739

[type \(angr.analyses.decompiler.structured_codegen.c.CStructFieldConstant \(class in angr.analyses.typehoon.typeconsts\), 843](#)
[property\), 735](#)
[type \(angr.analyses.decompiler.structured_codegen.c.CTypeConstraint \(class in angr.analyses.typehoon.typevars\), 837](#)
[property\), 738](#)
[type \(angr.analyses.decompiler.structured_codegen.c.CUndeclaredVariable \(class in angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory](#)
[property\), 737](#)
[type \(angr.analyses.decompiler.structured_codegen.c.CVariable 375](#)
[property\), 736](#)
[type \(angr.analyses.decompiler.structured_codegen.c.CVariableField 842](#)
[property\), 737](#)
[type \(angr.analyses.loop_analysis.AnnotatedVariable attribute\), 846](#)
[type \(angr.analyses.reaching_definitions.subject.Subject](#)
[property\), 818](#)
[type \(angr.angrdb.models.DbComment attribute\), 681](#)
[type \(angr.knowledge_plugins.cfg.indirect_jump.IndirectJump](#)
[attribute\), 551](#)
[type \(angr.knowledge_plugins.cfg.IndirectJump attribute\), 532](#)
[type \(angr.knowledge_plugins.xrefs.xref.XRef attribute\),](#)
[615](#)
[type \(angr.storage.memory_mixins.keyvalue_memory.keyvalue_memory_mixins.TypeValueTranslator\), 837](#)
[attribute\), 375](#)
[type_ \(angr.analyses.typehoon.typevars.Existence](#)
[attribute\), 838](#)
[type_0 \(angr.analyses.typehoon.typevars.Add attribute\),](#)
[838](#)
[type_0 \(angr.analyses.typehoon.typevars.Sub attribute\),](#)
[839](#)
[type_1 \(angr.analyses.typehoon.typevars.Add attribute\),](#)
[838](#)
[type_1 \(angr.analyses.typehoon.typevars.Sub attribute\),](#)
[839](#)
[type_a \(angr.analyses.typehoon.typevars.Equivalence](#)
[attribute\), 837](#)
[type_b \(angr.analyses.typehoon.typevars.Equivalence](#)
[attribute\), 837](#)
[type_constraints \(angr.analyses.decompiler.decompilation_cache.DecompilationCache](#)
[attribute\), 700](#)
[type_constraints \(angr.analyses.variable_recovery.engine_base.RichR](#)
[attribute\), 831](#)
[type_parser_singleton\(\) \(in module angr.sim_type\),](#)
[521](#)
[type_r \(angr.analyses.typehoon.typevars.Add attribute\),](#)
[838](#)
[type_r \(angr.analyses.typehoon.typevars.Sub attribute\),](#)
[839](#)
[type_string \(angr.knowledge_plugins.xrefs.xref.XRef](#)
[property\), 615](#)
[type_to_c_repr_chunks\(\) \(in module](#)
[angr.analyses.decompiler.structured_codegen.c\),](#)
[728](#)
[type_var \(angr.analyses.typehoon.typevars.DerivedTypeVariable](#)
[attribute\), 840](#)

U

[UberEngine \(class in angr.engines\), 427](#)
[UberEngineCode \(class in angr.engines\), 428](#)
[uc \(angr.state_plugins.unicorn_engine.Unicorn prop-](#)
[erty\), 290](#)
[UC_CONFIG \(angr.state_plugins.unicorn_engine.Unicorn](#)
[attribute\), 288](#)
[UltraPage \(class in angr.storage.memory_mixins.paged_memory.pages.ult](#)
[364](#)
[UltraPagesMixin \(class in](#)
[angr.storage.memory_mixins.paged_memory.paged_memory_mix](#)
[357](#)
[uncache_region\(\) \(angr.state_plugins.unicorn_engine.Unicorn](#)
[method\), 290](#)
[unconstrained \(angr.sim_manager.SimulationManager](#)
[attribute\), 383](#)
[unconstrained \(angr.SimulationManager attribute\),](#)
[172](#)

Unconstrained() (angr.state_plugins.solver.SimSolver method), 255

Undefined (class in angr.knowledge_plugins.key_definitions), 609

UnderconstrainedMixin (class in angr.storage.memory_mixins.underconstrained_mixin), 342

unfreeze() (angr.analyses.stack_pointer_tracker.FrozenStackPointerTrackerState method), 822

unhook() (angr.Project method), 165

unhook() (angr.project.Project method), 215

unhook_symbol() (angr.Project method), 166

unhook_symbol() (angr.project.Project method), 216

UnicodeString (angr.knowledge_plugins.cfg.memory_data.MemoryDataSort attribute), 545

UnicodeString (angr.knowledge_plugins.cfg.MemoryDataSort attribute), 526

Unicorn (class in angr.state_plugins.unicorn_engine), 288

unified_local_vars (angr.analyses.decompiler.structured_codegen attribute), 729

unified_variable (angr.analyses.decompiler.structured_codegen attribute), 736

unified_variable() (angr.knowledge_plugins.variables.Variable method), 570

unify_arch_name() (in module angr.calling_conventions), 504

unify_variables() (angr.knowledge_plugins.variables.Variable method), 570

uninit_read_base (angr.analyses.cfg.indirect_jump_resolvers.jump_table_indirect_read_base attribute), 666

UninitReadMeta (class in angr.analyses.cfg.indirect_jump_resolvers.jump_table_indirect_read_base), 666

union() (angr.state_plugins.sim_action_object.SimActionObject method), 469

unique() (angr.state_plugins.solver.SimSolver method), 261

unique_type_name() (angr.knowledge_plugins.types.TypesStore method), 552

UniqueSearch (class in angr.exploration_techniques), 403

UniqueSearch (class in angr.exploration_techniques.unique), 423

Uniwrapper (class in angr.state_plugins.unicorn_engine), 288

Unknown (angr.analyses.proximity_graph.ProxiNodeTypes attribute), 872

UNKNOWN (angr.analyses.typehoon.simple_solver.ConstraintGraphTag attribute), 834

Unknown (angr.knowledge_plugins.cfg.indirect_jump.IndirectJumpType attribute), 550

Unknown (angr.knowledge_plugins.cfg.IndirectJumpType attribute), 532

Unknown (angr.knowledge_plugins.cfg.memory_data.MemoryDataSort attribute), 545

Unknown (angr.knowledge_plugins.cfg.MemoryDataSort attribute), 526

Unknown (class in angr.analyses.cfg.cfb), 641

UnknownProxiNode (class in angr.analyses.proximity_graph), 874

UnknownSize (class in angr.knowledge_plugins.key_definitions.unknown_size), 610

UnknownSizeTag (class in angr.knowledge_plugins.key_definitions.tag), 609

UnicodeString (angr.state_plugins.filesystem.SimFilesystem property), 249

Unmap_by_address() (angr.storage.memory_mixins.regioned_memory.regioned_memory method), 370

unmap_region() (angr.storage.memory_mixins.address_concretization_mixin.address_concretization_mixin method), 346

unmap_region() (angr.storage.memory_mixins.MemoryMixin method), 337

unmap_region() (angr.storage.memory_mixins.paged_memory.paged_memory method), 354

unmatched_functions (angr.analyses.bindiff.Bindiff property), 635

unmatched_functions (angr.analyses.bindiff.Bindiff property), 636

unmatched_functions (angr.analyses.bindiff.Bindiff property), 637

unmount() (angr.state_plugins.filesystem.SimFilesystem method), 672

unmount() (angr.state_plugins.filesystem.SimFilesystem method), 673

unmount() (angr.state_plugins.filesystem.SimFilesystem method), 674

unpack_array() (in module angr.analyses.decompiler.structured_codegen.c), 727

unpack_pointer() (in module angr.analyses.decompiler.structured_codegen.c), 727

unpack_typeof() (in module angr.analyses.decompiler.structured_codegen.c), 727

unqualified_name() (angr.sim_type.NamedTypeMixin method), 510

unreachable_history() (angr.state_hierarchy.StateHierarchy method), 390

unreachable_history() (angr.StateHierarchy method), 180

unreachable_state() (angr.state_hierarchy.StateHierarchy method), 390

unreachable_state() (angr.StateHierarchy method), 180

unresolvables (angr.analyses.cfg.cfg_emulated.CFGEEmulated property), 648

unresolved_indirect_jumps

(*angr.knowledge_base.knowledge_base.KnowledgeBase* method), 552
 property), 523
 unresolved_indirect_jumps (*angr.KnowledgeBase* property), 211
 unroll_loops() (*angr.analyses.cfg.cfg_emulated.CFGEmu* method), 647
 unsat (*angr.sim_manager.SimulationManager* attribute), 383
 unsat (*angr.SimulationManager* attribute), 172
 unsat_core() (*angr.state_plugins.solver.SimSolver* method), 259
 unset_stack_address_mapping() (*angr.storage.memory_mixins.regioned_memory.un* method), 368
 UnsignedExtension (*angr.analyses.cfg.indirect_jump_reso* attribute), 666
 unsilence_logger() (in module *angr.state_plugins.heap.heap_ptmalloc*), 302
 Unspecified (*angr.knowledge_plugins.cfg.memory_data.MemoryData* attribute), 545
 Unspecified (*angr.knowledge_plugins.cfg.MemoryDataSort* attribute), 526
 unstash() (*angr.sim_manager.SimulationManager* method), 387
 unstash() (*angr.SimulationManager* method), 176
 unsupported_reasons (*angr.state_plugins.unicorn_engine.STOP* attribute), 287
 UnsupportedCCallError, 907
 UnsupportedDirtyError, 907
 UnsupportedIRExprError, 906
 UnsupportedIROpError, 906
 UnsupportedIRStmtError, 907
 UnsupportedNodeTypeError, 908
 UnsupportedSyscallError (in module *angr.errors*), 907
 UnwrapperMixin (class in *angr.storage.memory_mixins.unwrapper_mixin*), 347
 update() (*angr.knowledge_plugins.sync.sync_controller.SyncController* method), 612
 update() (*angr.procedures.definitions.SimLibrary* method), 477
 update() (*angr.procedures.definitions.SimSyscallLibrary* method), 481
 update() (*angr.sim_state_options.SimStateOptions* method), 230
 update_dbinfo() (*angr.angrdb.db.AngrDB* method), 677
 update_labels() (in module *angr.analyses.decompiler.utils*), 747
 update_resolved_addrs() (*angr.knowledge_plugins.indirect_jumps.IndirectJumps* method), 552
 update_switch_case_list() (in module *angr.analyses.decompiler.region_simplifiers.switch_cluster_simpl*), 723
 update_variable_types() (*angr.analyses.typehoon.typehoon.Typehoon* method), 842
 UpdateArgumentsOption (class in *angr.analyses.calling_convention*), 637
 UpdateWhenCCHasNoArgs (*angr.analyses.calling_convention.UpdateArgumentsOption* attribute), 637
 upper_bound (*angr.knowledge_plugins.solver.SketchNode* attribute), 833
 use_plugin_by_addr() (*angr.knowledge_plugins.PluginHub* method), 223
 use_technique() (*angr.sim_manager.SimulationManager* method), 384
 use_technique() (*angr.SimulationManager* method), 384
 UserSort (class in *angr.calling_conventions*), 488
 users() (*angr.knowledge_plugins.sync.sync_controller.SyncController* method), 612
 uses (*angr.analyses.decompiler.region_simplifiers.expr_folding.Expression* attribute), 719
 Uses (class in *angr.knowledge_plugins.key_definitions*), 585
 Uses (class in *angr.knowledge_plugins.key_definitions.uses*), 610
 uses_by_codeloc (*angr.analyses.reaching_definitions.LiveDefinitions* attribute), 762
 uses_by_codeloc (*angr.analyses.reaching_definitions.rd_state.ReachingD* property), 813
 uses_by_codeloc (*angr.analyses.reaching_definitions.ReachingDefinition* property), 783
 uses_by_codeloc (*angr.knowledge_plugins.key_definitions.live_definition* attribute), 598
 uses_by_codeloc (*angr.knowledge_plugins.key_definitions.LiveDefinition* attribute), 578

V

va_arg() (*angr.sim_procedure.SimProcedure* method), 473
 va_arg() (*angr.SimProcedure* method), 160
 val (*angr.analyses.stack_pointer_tracker.Constant* attribute), 821
 val0 (*angr.analyses.stack_pointer_tracker.Eq* attribute), 821
 val1 (*angr.analyses.stack_pointer_tracker.Eq* attribute), 821
 value (*angr.analyses.decompiler.optimization_passes.lowered_switch_simp* attribute), 710

VariableRecoveryStateBase (class in [756](#)
[angr.analyses.variable_recovery.variable_recovery_base](#)), 825
variables ([angr.analyses.variable_recovery.variable_recovery_base](#) property), 826
variables ([angr.knowledge_base.knowledge_base.KnowledgeBase](#) attribute), 523
variables ([angr.KnowledgeBase](#) attribute), 211
variables ([angr.storage.memory_object.SimMemoryObject](#) property), 334
variables() ([angr.state_plugins.solver.SimSolver](#) method), 262
variables_in_use ([angr.analyses.decompiler.structured_codegen.CFunction](#) attribute), 729
VariableSourceAnnotation (class in [angr.analyses.variable_recovery.annotations](#)), 823
VariableType (class in [angr.knowledge_plugins.variables.variable_manager](#)), 565
VariableTypes (class in [angr.analyses.loop_analysis](#)), 846
variance ([angr.analyses.typehoon.simple_solver.ConstraintSolver](#) attribute), 835
variance ([angr.analyses.typehoon.typevars.BaseLabel](#) property), 841
variance ([angr.analyses.typehoon.typevars.Store](#) property), 841
Vault (class in [angr.vaults](#)), 621
VaultDict (class in [angr.vaults](#)), 622
VaultDir (class in [angr.vaults](#)), 622
VaultDirShelf (class in [angr.vaults](#)), 622
VaultPickler (class in [angr.vaults](#)), 621
VaultShelf (class in [angr.vaults](#)), 622
VaultUnpickler (class in [angr.vaults](#)), 621
VendorPreset (class in [angr.misc.plugins](#)), 224
Veritesting ([angr.analyses.analysis.KnownAnalysesPlugin](#) attribute), 623
Veritesting (class in [angr.analyses.veritesting](#)), 848
Veritesting (class in [angr.exploration_techniques](#)), 399
Veritesting (class in [angr.exploration_techniques.veritesting](#)), 413
VeritestingError, 847
VERSION ([angr.angrdb.db.AngrDB](#) attribute), 676
vex ([angr.Block](#) property), 170
vex ([angr.block.Block](#) property), 221
vex_nostmt ([angr.Block](#) property), 170
vex_nostmt ([angr.block.Block](#) property), 221
VEXIRSBScanner (class in [angr.analyses.variable_recovery.irsb_scanner](#)), 832
VEXMemVar (class in [angr.analyses.propagator.vex_vars](#)), 756
VEXReg (class in [angr.analyses.propagator.vex_vars](#)), 756
VEXStmtDetails (class in [angr.analyses.propagator.vex_vars](#)), 756
VEXTmp (class in [angr.analyses.propagator.vex_vars](#)), 756
VEXVariable (class in [angr.analyses.propagator.vex_vars](#)), 756
VFG ([angr.analyses.analysis.KnownAnalysesPlugin](#) attribute), 623
VFG (class in [angr.analyses.vfg](#)), 852
VFGJob (class in [angr.analyses.vfg](#)), 849
VFGNode (class in [angr.analyses.vfg](#)), 851
Vidual ([angr.analyses.disassembly.SootExpressionInvoke](#) attribute), 857
visited_blocks ([angr.analyses.reaching_definitions.function_handler.FunctionHandler](#) attribute), 805
visited_blocks ([angr.analyses.reaching_definitions.FunctionCallData](#) attribute), 791
visited_blocks ([angr.analyses.reaching_definitions.reaching_definitions.ReachingDefinitions](#) property), 797
visited_blocks ([angr.analyses.reaching_definitions.ReachingDefinitions](#) property), 776
visited_blocks ([angr.analyses.reaching_definitions.subject.Subject](#) property), 818
VSA_DDG ([angr.analyses.analysis.KnownAnalysesPlugin](#) attribute), 623
VSA_DDG (class in [angr.analyses.vsa_ddg](#)), 853
Vtable ([angr.knowledge_plugins.cfg.indirect_jump.IndirectJumpType](#) attribute), 550
Vtable ([angr.knowledge_plugins.cfg.IndirectJumpType](#) attribute), 532
Vtable (class in [angr.analyses.vtable](#)), 854
VtableFinder (class in [angr.analyses.vtable](#)), 854
W
walk() ([angr.analyses.decompiler.ailgraph_walker.AILGraphWalker](#) method), 694
walk() ([angr.analyses.decompiler.optimization_passes.const_derefs.BlockWalker](#) method), 704
walk() ([angr.analyses.decompiler.region_walker.RegionWalker](#) method), 725
walk() ([angr.analyses.decompiler.sequence_walker.SequenceWalker](#) method), 726
walk_node() ([angr.analyses.decompiler.optimization_passes.ite_expr_concrete.IteExprConcrete](#) method), 708
walk_node() ([angr.analyses.decompiler.region_walker.RegionWalker](#) method), 725
whitelist ([angr.analyses.veritesting.CallTracingFilter](#) attribute), 847
widen() ([angr.sim_state.SimState](#) method), 227
widen() ([angr.SimFile](#) method), 191
widen() ([angr.SimFileDescriptor](#) method), 200
widen() ([angr.SimFileDescriptorDuplex](#) method), 202
widen() ([angr.SimHeapBrk](#) method), 206

`widen()` (*angr.SimHeapPTMalloc* method), 208
`widen()` (*angr.SimPackets* method), 194
`widen()` (*angr.SimState* method), 183
`widen()` (*angr.SimStatePlugin* method), 162
`widen()` (*angr.state_plugins.callstack.CallStack* method), 265
`widen()` (*angr.state_plugins.cgc.SimStateCGC* method), 273
`widen()` (*angr.state_plugins.concrete.Concrete* method), 293
`widen()` (*angr.state_plugins.filesystem.SimConcreteFilesystem* method), 253
`widen()` (*angr.state_plugins.filesystem.SimFilesystem* method), 250
`widen()` (*angr.state_plugins.globals.SimStateGlobals* method), 278
`widen()` (*angr.state_plugins.heap.heap_brk.SimHeapBrk* method), 299
`widen()` (*angr.state_plugins.heap.heap_ptmalloc.SimHeapPTMalloc* method), 306
`widen()` (*angr.state_plugins.history.SimStateHistory* method), 268
`widen()` (*angr.state_plugins.inspect.SimInspector* method), 235
`widen()` (*angr.state_plugins.javavm_classloader.SimJavaVmClassloader* method), 295
`widen()` (*angr.state_plugins.jni_references.SimStateJNIReferences* method), 297
`widen()` (*angr.state_plugins.libc.SimStateLibc* method), 239
`widen()` (*angr.state_plugins.log.SimStateLog* method), 263
`widen()` (*angr.state_plugins.loop_data.SimStateLoopData* method), 292
`widen()` (*angr.state_plugins.plugin.SimStatePlugin* method), 233
`widen()` (*angr.state_plugins.posix.PosixDevFS* method), 241
`widen()` (*angr.state_plugins.posix.PosixProcFS* method), 243
`widen()` (*angr.state_plugins.posix.SimSystemPosix* method), 247
`widen()` (*angr.state_plugins.preconstrainer.SimStatePreconstrainer* method), 283
`widen()` (*angr.state_plugins.scratch.SimStateScratch* method), 281
`widen()` (*angr.state_plugins.sim_action_object.SimActionObject* method), 469
`widen()` (*angr.state_plugins.solver.SimSolver* method), 257
`widen()` (*angr.state_plugins.trace_additions.ChallRespInfo* method), 275
`widen()` (*angr.state_plugins.trace_additions.ZenPlugin* method), 277
`widen()` (*angr.state_plugins.unicorn_engine.Unicorn* method), 290
`widen()` (*angr.state_plugins.view.SimMemView* method), 314
`widen()` (*angr.state_plugins.view.SimRegNameView* method), 310
`widen()` (*angr.storage.file.SimFile* method), 319
`widen()` (*angr.storage.file.SimFileDescriptor* method), 329
`widen()` (*angr.storage.file.SimFileDescriptorDuplex* method), 331
`widen()` (*angr.storage.file.SimPackets* method), 323
`widen()` (*angr.storage.file.SimPacketsSlots* method), 333
`widen()` (*angr.storage.memory_mixins.javavm_memory.javavm_memory* method), 378
`widen()` (*angr.storage.memory_mixins.MemoryMixin* method), 337
`widen()` (*angr.storage.memory_mixins.regioned_memory.region_meta* method), 373
`widened_jobs` (*angr.analyses.forward_analysis.job_info.JobInfo* property), 626
`width` (*angr.analyses.data_dep.dep_nodes.MemDepNode* property), 878
`width()` (*angr.analyses.disassembly.DisassemblyPiece* method), 856
`with_arch()` (*angr.sim_type.SimType* method), 509
`with_arch()` (*angr.sim_type.TypeRef* method), 510
`with_condition` (*angr.sim_state.SimState* property), 228
`with_condition` (*angr.SimState* property), 184
`with_type()` (*angr.state_plugins.debug_variables.SimDebugVariable* method), 308
`with_type()` (*angr.state_plugins.view.SimMemView* method), 313
`work()` (*angr.analyses.complete_calling_conventions.CompleteCallingConventions* method), 639
`Worker` (class in *angr.distributed.worker*), 910
`WRITE` (*angr.knowledge_plugins.variables.variable_access.VariableAccess* attribute), 564
`Write` (*angr.knowledge_plugins.xrefs.xref_types.XRefType* attribute), 615
`WRITE` (*angr.state_plugins.sim_action.SimActionData* attribute), 468
`write()` (*angr.SimFile* method), 190
`write()` (*angr.SimFileBase* method), 189
`write()` (*angr.SimFileStream* method), 195
`write()` (*angr.SimPackets* method), 193
`write()` (*angr.SimPacketsStream* method), 196
`write()` (*angr.storage.file.SimFile* method), 318
`write()` (*angr.storage.file.SimFileBase* method), 316
`write()` (*angr.storage.file.SimFileDescriptorBase* method), 325
`write()` (*angr.storage.file.SimFileStream* method), 320
`write()` (*angr.storage.file.SimPackets* method), 322

[write\(\)](#) (*angr.storage.file.SimPacketsSlots* method), 332
[write\(\)](#) (*angr.storage.file.SimPacketsStream* method), 324
[write_data\(\)](#) (*angr.SimFileDescriptor* method), 198
[write_data\(\)](#) (*angr.SimFileDescriptorDuplex* method), 201
[write_data\(\)](#) (*angr.storage.file.SimFileDescriptor* method), 327
[write_data\(\)](#) (*angr.storage.file.SimFileDescriptorBase* method), 326
[write_data\(\)](#) (*angr.storage.file.SimFileDescriptorDuplex* method), 330
[write_msr\(\)](#) (*angr.state_plugins.unicorn_engine.Unicorn* method), 290
[write_pos](#) (*angr.SimFileDescriptor* property), 199
[write_pos](#) (*angr.SimFileDescriptorDuplex* property), 201
[write_pos](#) (*angr.storage.file.SimFileDescriptor* property), 328
[write_pos](#) (*angr.storage.file.SimFileDescriptorBase* property), 326
[write_pos](#) (*angr.storage.file.SimFileDescriptorDuplex* property), 330
[write_storage](#) (*angr.SimFileDescriptor* property), 199
[write_storage](#) (*angr.SimFileDescriptorDuplex* property), 201
[write_storage](#) (*angr.storage.file.SimFileDescriptor* property), 328
[write_storage](#) (*angr.storage.file.SimFileDescriptorBase* property), 326
[write_storage](#) (*angr.storage.file.SimFileDescriptorDuplex* property), 330
[write_to\(\)](#) (*angr.knowledge_plugins.variables.variable_manager.VariableManagerInternal* method), 566

X

[X86ElfPicPltResolver](#) (class in *angr.analyses.cfg.indirect_jump_resolvers.x86_elf_pic_plt*), 665
[X86GccGetPcSimplifier](#) (class in *angr.analyses.decompiler.optimization_passes.x86_gcc_getpc_simplifier*), 714
[X86PeIatResolver](#) (class in *angr.analyses.cfg.indirect_jump_resolvers.x86_pe_iat*), 663
[Xor](#) (*angr.engines.light.data.ArithmeticExpression* attribute), 754
[XRef](#) (class in *angr.knowledge_plugins.xrefs.xref*), 614
[XRefManager](#) (class in *angr.knowledge_plugins.xrefs.xref_manager*), 615
[XRefs](#) (*angr.analyses.analysis.KnownAnalysesPlugin* attribute), 624

[xrefs](#) (*angr.angrdb.models.DbKnowledgeBase* attribute), 678
[xrefs](#) (*angr.knowledge_base.knowledge_base.KnowledgeBase* attribute), 523
[xrefs](#) (*angr.knowledge_plugins.functions.function.Function* property), 557
[xrefs](#) (*angr.KnowledgeBase* attribute), 211
[XRefsAnalysis](#) (class in *angr.analyses.xrefs*), 871
[XRefsSerializer](#) (class in *angr.angrdb.serializers.xrefs*), 684
[XRefType](#) (class in *angr.knowledge_plugins.xrefs.xref_types*), 615

Z

[zen_hook\(\)](#) (in module *angr.state_plugins.trace_additions*), 276
[zen_memory_write\(\)](#) (in module *angr.state_plugins.trace_additions*), 276
[zen_register_write\(\)](#) (in module *angr.state_plugins.trace_additions*), 276
[ZenPlugin](#) (class in *angr.state_plugins.trace_additions*), 276